



This is a digital copy of a book that was preserved for generations on library shelves before it was carefully scanned by Google as part of a project to make the world's books discoverable online.

It has survived long enough for the copyright to expire and the book to enter the public domain. A public domain book is one that was never subject to copyright or whose legal copyright term has expired. Whether a book is in the public domain may vary country to country. Public domain books are our gateways to the past, representing a wealth of history, culture and knowledge that's often difficult to discover.

Marks, notations and other marginalia present in the original volume will appear in this file - a reminder of this book's long journey from the publisher to a library and finally to you.

Usage guidelines


Google is proud to partner with libraries to digitize public domain materials and make them widely accessible. Public domain books belong to the public and we are merely their custodians. Nevertheless, this work is expensive, so in order to keep providing this resource, we have taken steps to prevent abuse by commercial parties, including placing technical restrictions on automated querying.

We also ask that you:

- + *Make non-commercial use of the files* We designed Google Book Search for use by individuals, and we request that you use these files for personal, non-commercial purposes.
- + *Refrain from automated querying* Do not send automated queries of any sort to Google's system: If you are conducting research on machine translation, optical character recognition or other areas where access to a large amount of text is helpful, please contact us. We encourage the use of public domain materials for these purposes and may be able to help.
- + *Maintain attribution* The Google "watermark" you see on each file is essential for informing people about this project and helping them find additional materials through Google Book Search. Please do not remove it.
- + *Keep it legal* Whatever your use, remember that you are responsible for ensuring that what you are doing is legal. Do not assume that just because we believe a book is in the public domain for users in the United States, that the work is also in the public domain for users in other countries. Whether a book is still in copyright varies from country to country, and we can't offer guidance on whether any specific use of any specific book is allowed. Please do not assume that a book's appearance in Google Book Search means it can be used in any manner anywhere in the world. Copyright infringement liability can be quite severe.

About Google Book Search

Google's mission is to organize the world's information and to make it universally accessible and useful. Google Book Search helps readers discover the world's books while helping authors and publishers reach new audiences. You can search through the full text of this book on the web at <http://books.google.com/>



10 FEET

5

0 6112

Digitized by Google

KD 10557

WEALE'S SCIENTIFIC & TECHNICAL SERIES.

CIVIL ENGINEERING & SURVEYING.

Civil Engineering. H. LAW & D. K. CLARK . . .	6/6
Pioneer Engineering. E. DOBSON . . .	4/6
Iron Bridges of Moderate Span. H. W. PENDRED. 2/-	
Iron Bridges & Girders. F. CAMPIN . . .	2/6
Constructional Steel & Ironwork. F. CAMPIN . .	3/6
Tubular & Girder Bridges. G. D. DEMPSEY . .	2/-
Materials and Construction. F. CAMPIN . . .	3/-
Sanitary Work. C. SLAGG . . .	3/-
Roads and Streets. H. LAW & D. K. CLARK . .	4/6
Construction of Gasworks. S. HUGHES & W. RICHARDS	5/6
Water Works. S. HUGHES . . .	4/-
Well-Sinking. J. G. SWINDELL & G. R. BURNELL . .	2/-
Drainage. G. D. DEMPSEY & D. K. CLARK . . .	4/6
Blasting and Quarrying. J. BURGOYNE . . .	1/6
Foundations and Concrete Work. E. DOBSON . .	1/6
Pneumatics. C. TOMLINSON . . .	1/6
Land & Engineering Surveying. T. BAKER . . .	2/-

MECHANICAL ENGINEERING, &c.

Engineering Drawing. J. MAXTON . . .	3/6
Fuels, Analysis and Valuation. H. J. PHILLIPS . .	2/-
Fuel. C. W. WILLIAMS & D. K. CLARK . . .	3/6
Boilermaker's Assistant. J. COURTNEY . . .	2/-
Boilermaker's Ready Reckoner. J. COURTNEY . .	4/-
Boilermaker's Ready Reckoner and Assistant. . .	7/-
Steam Boilers. R. ARMSTRONG . . .	1/6
Steam and Machinery Management. M. P. BALE. .	2/6
Steam and the Steam Engine. D. K. CLARK . . .	3/6
Steam Engine, Theory of. T. BAKER . . .	1/6
Steam Engine. Dr. LARDNER . . .	1/6
Locomotive Engines. G. D. DEMPSEY & D. K. CLARK .	3/-
Locomotive Engine Driving. M. REYNOLDS . . .	3/6
Stationary Engine Driving. M. REYNOLDS . . .	3/6
Model Locomotive Engineer. M. REYNOLDS . . .	3/6
Modern Workshop Practice. J. G. WINTON . . .	3/6
Mechanical Engineering. F. CAMPIN . . .	2/6
Details of Machinery. F. CAMPIN . . .	3/-
Elementary Marine Engineering. J. S. BREWER . .	1/6

CROSBY & SONS

7, Stationers' Hall Court, E.C.

WEALE'S SCIENTIFIC & TECHNICAL SERIES.

MECHANICAL ENGINEERING, &c.—contd.

Sewing Machinery. J. W. URQUHART	2/-
Power of Water. J. GLYNN	2/-
Power in Motion. J. ARMOUR	2/-
Iron and Heat. J. ARMOUR	2/6
Mechanism and Machines. T. BAKER & J. NASMYTH	2/6
Mechanics. C. TOMLINSON	1/6
Cranes and Machinery. J. GLYNN	1/6
Smithy and Forge. W. J. E. CRANE	2/6
Sheet-Metal Worker's Guide. W. J. E. CRANE	1/6

MINING & METALLURGY.

Mineralogy. A. RAMSAY	3/6
Coal and Coal Mining. Sir W. W. SMYTH	3/6
Metallurgy of Iron. H. BAUERMAN	5/-
Mineral Surveyor's Guide. W. LINTERN	3/6
Slate and Slate Quarrying. D. C. DAVIES	3/-
Mining and Quarrying. J. H. COLLINS	1/6
Subterraneous Surveying. T. FENWICK & T. BAKER	2/6
Mining Tools. W. MORGANS	2/6
Plates to ditto. 4to.	4/6
Physical Geology. PORTLOCK & TATE	2/-
Historical Geology. R. TATE	2/6
The above 2 vols., bound together	4/6
Electro-Metallurgy. A. WATT	3/6

NAVIGATION, SHIPBUILDING, &c.

Navigation. J. GREENWOOD & W. H. ROSSER	2/6
Practical Navigation. GREENWOOD, ROSSER & LAW	7/-
Navigation and Nautical Astronomy. J. R. YOUNG	2/6
Mathematical & Nautical Tables. LAW & YOUNG	4/-
Masting and Rigging. R. KIPPING	2/-
Sails and Sailmaking. R. KIPPING	2/6
Marine Engines. R. MURRAY & G. CARLISLE	4/6
Iron Ship-Building. J. GRANTHAM	4/-
Naval Architecture. J. PEAKE	3/6
Ships, Construction of. H. A. SOMMERFELDT	1/6
Plates to ditto, 4to	7/6
Ships and Boats. W. BLAND	1/6

CROSBY LOCKWOOD & SON, 7, Stationers' Hall Court, E.C.

WEALE'S SCIENTIFIC & TECHNICAL SERIES.

AGRICULTURE & GARDENING.

Fertilisers & Feeding Stuff.	DR. B. DYER . . .	1/-
Draining and Embanking.	PROF. J. SCOTT . . .	1/6
Irrigation and Water Supply.	PROF. J. SCOTT . . .	1/6
Farm Roads, Fences, and Gates.	PROF. J. SCOTT . . .	1/6
Farm Buildings.	PROF. J. SCOTT . . .	2/-
Barn Implements and Machines.	PROF. J. SCOTT . . .	2/-
Field Implements and Machines.	PROF. J. SCOTT . . .	2/-
Agricultural Surveying.	PROF. J. SCOTT . . .	1/6
The above 7 vols., bound together . . .		12/-
Farm Management.	R. S. BURN . . .	2/6
Landed Estates Management.	R. S. BURN . . .	2/6
Farm & Landed Estates Management.	R. S. BURN . . .	6/-
Farming—Soils, Manures, and Crops.	R. S. BURN . . .	2/-
Farming—Outlines—Farming Economy.	R. S. BURN . . .	3/-
Farming—Oattle, Sheep, and Horses.	R. S. BURN . . .	2/6
Farming—Dairy, Pigs, and Poultry.	R. S. BURN . . .	2/-
Farming—Sewage & Irrigation.	R. S. BURN . . .	2/6
The above 5 vols., bound together . . .		12/-
Book-keeping for Farmers.	J. M. WOODMAN . . .	2/6
Ready Reckoner for Land.	A. ARMAN . . .	2/-
Miller's & Farmer's Ready Reckoner . . .		2/-
Hay and Straw Measurer.	J. STEELE . . .	2/-
Meat Production.	J. EWART . . .	2/6
The Sheep.	W. C. SPOONER . . .	3/6
Mulm-in-Parvo Gardening.	S. WOOD . . .	1/-
Forcing Garden.	S. WOOD . . .	3/6
Market and Kitchen Gardening.	C. W. SHAW . . .	3/-
Kitchen Gardening.	G. M. F. GLENNY . . .	1/6
Cottage Gardening.	E. HOBDAV . . .	1/6
Garden Receipts.	C. W. QUIN . . .	1/6
Potatoes: How to Grow.	J. PINK . . .	2/-
Culture of Fruit Trees.	M. DU BREUIL . . .	3/6
Tree Planter & Plant Propagator.	S. WOOD . . .	2/-
Tree Pruner.	S. WOOD . . .	1/6
Tree Planter, Propagator, & Pruner.	S. WOOD . . .	3/6
Grafting and Budding.	C. BALTET . . .	2/6
Bees for Pleasure & Profit.	G. G. SAMSON . . .	1/-

CROSBY LOCKWOOD & SON, 7, Stationers' Hall Court, E.C.

HYDRAULIC
TABLES, COEFFICIENTS, AND FORMULÆ,
FOR
FINDING THE DISCHARGE OF WATER
FROM
ORIFICES, NOTCHES, WEIRS, PIPES, AND RIVERS.

By JOHN NEVILLE,

CIVIL ENGINEER, M.R.I.A.,
COUNTY SURVEYOR OF LOUTH AND OF THE COUNTY OF THE TOWN OF DROGHEDA ;
FELLOW OF THE ROYAL GEOLOGICAL SOCIETY OF IRELAND.

Third Edition :

WITH ADDITIONS, CONSISTING OF NEW FORMULÆ FOR THE DISCHARGE
FROM TIDAL AND FLOOD SLUICES, AND SYPHONS ; GENERAL INFOR-
MATION ON RAINFALL, CATCHMENT-BASINS, DRAINAGE, SEWERAGE,
WATER SUPPLY FOR TOWNS, AND MILL POWER.

"In physics the memory disburthens itself of its cumbrous catalogue of particulars and carries centuries of observation in a single formula.—EMERSON ON NATURE.

"It ought to be more generally known, that theory is nothing more than the conclusions of reason from numerous and accurately observed phenomena, and the deductions of the laws which connect causes with effects ; that practice is the application of those general truths and principles to the common affairs and purposes of life ; and that science is the recorded experience and discoveries of mankind, or, as it has been well defined, 'the knowledge of many, orderly and methodically digested, and arranged, so as to become attainable by one.'"—AMERICAN QUARTERLY REVIEW.



LONDON :
LOCKWOOD & CO., 7, STATIONERS' HALL COURT.
1875.

KD 10557



*Let. y Ray H. S.
N. H. H.*

LONDON :

BRADBURY, AGNEW, & CO., PRINTERS, WHITEFRIARS.

INTRODUCTION

TO THE THIRD EDITION.

IN order to render this edition more valuable to the hydraulic engineer the work has been again considerably extended by the insertion of several new formulæ, experimental coefficients, and general estimates of cost. It is hoped that the extent and practical nature of these additions, will render the book still more useful than before, to meet the ever-varying requirements of the profession in connexion with rivers and water-works. The experiments of Mr. Mallet on syphons made in 1843, and printed in Weale's Quarterly Papers on Engineering, have been reduced. New formulæ are given for finding the discharge from syphons, flood-sluiques, and tidal-sluiques. The practical formulæ for gauging by weirs have been added to. The arrangement of the matter is in some places altered, and some portions of the former introductions transferred, at their proper places, to the text, and others are retained here.

At page 85 the erroneous practice of different engineers in giving only two-thirds of the coefficient of discharge for weirs is noticed. This practice assumes that the theoretical discharge from a notch is the same as if all the particles of water had the same mean theoretical velocity as those undermost, which, being too large by one-third, the experimental coefficient has to be reduced in the same proportion to give a correct result. There is no reason for sanctioning a different coefficient for notches, or orifices at the surface, and for sunk orifices. The coefficients when in thin plates, with large cisterns, have nearly the same general value, $\cdot 615$ to $\cdot 628$, for both, and it tends to confusion to adopt in one place a coefficient for a correct formula, and in another a coefficient for an incorrect one; although the final result, by an equality of contrary errors, may be the same. I may here observe how very general the coefficient of *two-thirds*, and thereabouts, is for all orifices and notches; likewise for the useful effect derived from the application of water power; as well also for the relation of the velocity due to the fall and the velocity of water wheels to give a maximum result. The modifications of coefficients, dependent on the position, thickness, form, and approaches of an orifice, are as yet little understood by the profession. The defects in the ordinary formula when the velocity of approach has to be considered are pointed out in pages 88 to 124, and it is to be regretted

that the authority of some writers on the subject has misled many as to the correct form. Before the effective power of a water-wheel, or water-engine, can be determined, we must know how to gauge the water supplied to it correctly. This can be done only by the application of formulæ and coefficients varied to suit the circumstances of the case under consideration. From causes, which it is not necessary to enter into here, this has seldom been done, and very little dependence can be placed on results obtained by the formula in common use when applied generally. It is pleasing to follow Mr. Francis and Professor J. Thomson through the steps by which they get the effective power of their wheels, and I have accordingly made considerable use of their labours in Section XIV.

In practice, the irregular, sometimes sloping, broken and jagged crests of most weirs, on larger rivers, render any close estimate of the quantity passing over quite uncertain, especially for lesser depths, unless where the observer has a large scientific experience; and the quantities are generally too large to apply the ordinary notch-gauge. In such cases it is better to measure the flow of the river, stream, or mill-race, from the cross section and the observed mean velocity. Frequently, however, this method presents another difficulty, in an irregular channel, where the depths and velocities vary considerably in the same cross section, and where the cross sections themselves vary in short distances apart.

In such cases I have often found it necessary to divide a selected stretch into two or more longitudinal sections, determining the cross section and mean velocity of each, and taking the sum of the results for the flow: which may be checked off by like admeasurements on a different stretch of the channel.

Long solid stone weirs, with an enlarged weir basin in connexion with mills, to regulate the head and to pond water, above a water-wheel, have especial advantages for this duty; but their application for the purpose of keeping down the head, and to effect drainage for long distances up a river, without a sluice, or falling crest, see page 290, was marvellous—unless for the drainage of capital. In November, 1849, in connexion with a paper on the Benburb Mills and Weir case, page 288, I drew the attention of the Institution of Civil Engineers of Ireland* to the misapplication of such long solid weirs on the Shannon, for navigation and drainage purposes. The “Arterial Drainage Commissioner,” on the Board of Works, who was present, “pooh - poohed” the inferences; but the failure of those works—rather the injury they do—has since become patent to all; and after an expenditure of about £600,000, an Act has been passed for the

* This paper, although read at the special request of the President, then Chairman of the Board of Works, and ordered to be printed, did not appear in the *Transactions*, but its substance afterwards became the nucleus of our First Edition. The Commissioner of Drainage was one of the Vice-Presidents, and the author a Member of Council at the time.

outlay of another £300,000, a moiety of which the riparian proprietors are again expected to contribute. This amount is proposed to be now expended in order to remedy the misapplication of a large portion of the first sum, £300,000 of which had to be paid by the proprietors of the adjacent counties, without having had any control over its expenditure.

Since the Report of the "Commissioners of Inquiry into the Arterial Drainage, in eleven districts in Ireland," see pages 396, 397, and 398, and the removal of the Arterial Drainage Commissioner, Treasury Minute, 24th June, 1853, drainage works have been carried on under a better system. The riparian proprietors of the Shannon, however, if again taxed, should have power to nominate an engineer of their own selection, to consult, act with, or control, if necessary, any engineer selected by the Treasury, or by the Commissioners of Public Works, and to see after and protect their special interests. The system of executing works solely by or under the staff of the Government in Ireland, to the cost of which districts or individuals contribute, has not been successful, and has not given satisfaction. When the Treasury is solicited to lend, or to contribute for State purposes, the control exercised by the Board of Public Works and its engineers, with reference to the plans, estimates, and specifications submitted, is of much value ; but the sooner the system adopted for drainage works since 1853 is gene-

rally carried out, and persons to be taxed for the Shannon, or for piers, harbours, and other works, are also permitted to have a voice in the engineering plans, and *fair control over their execution*, the better for the State and for all parties immediately interested.

The TABLES, from I. to XIV., at the end of the volume are all original, with the exception of TABLE I., which contains the well-known coefficients of PONCELET and LESBROS; but these are newly arranged, the heads reduced to English inches, and the coefficients for heads measured over and back from the orifice, placed side by side, for more ready comparison. The coefficients in the small Tables throughout the work were all calculated by the author from the original experiments; the formulæ have been carefully investigated, and the continental ones reduced to English measures—some of them, as will be seen, for the first time.

The correction of some of the experimental formulæ, particularly the continental ones, as printed in some English books, cost the author some labour. Even Du Buât's well-known formula is frequently misprinted; and in a hydraulic work, $\sqrt{d}-1$, one of the factors, is printed $\sqrt{d}-\cdot 1$ in every page where it is given. It is not always that such mistakes can be avoided, but experimental formulæ are so often copied from one work into another without sufficient examination, that an error of this kind frequently becomes fixed; and when applied to practical purposes erroneous formulæ get the

correct ones into disrepute. See note to formula (91), page 218.

The TABLES of velocities and discharges over weirs and notches have been calculated for a great number of coefficients TO MEET DIFFERENT CIRCUMSTANCES OF APPROACH AND OVERFALL, and for various heads from $\frac{1}{4}$ th of an inch up to 6 feet. TABLE II. embodies the velocities acquired by falling bodies under the head of "theoretical velocity," and the velocities, suited to various coefficients, for heads up to 40 feet.

The formulæ (45), (46), (45a), and (46a), for calculating the effects of the velocity of approach to orifices and weirs, and the necessary corrections for the ratio of the channel to the orifice at pages 88 to 114, as well as TABLE V., I believe to be original. They will be found of much value in determining the proper coefficients suited to various ratios. The remarks throughout SECTION IV. are particularly applicable to the proper understanding and use of this TABLE. The hypothesis from which formulæ (44), (45), and (46) are derived, page 96 and 97, and from which TABLE V. is calculated, was framed for the purpose of giving practical results when the orifice A approximates, in size, to the channel c . They are less than those derivable from formulæ (44a), (45a), and (46a), which give, for every value of the coefficient c_a , infinite results, when $A = c$; and results much too large in practice as the values of A and c approximate. As the values of the

coefficients for (45a) and (46a) can be immediately deduced from the last two columns of that TABLE, by using the values therein given, for the ratio of the channel to the orifice, as multipliers, for any primary coefficient c_d , as pointed out in the text, the resulting OR SECONDARY coefficients for both sets of formulæ can be compared with much advantage.

TABLE VII. of surface and mean velocities will be found to vary from those generally in use, and to be much more correct, and better suited for practical purposes, particularly when applied to finding the mean velocities in rivers.

The TABLES at pages 270 and 271 being for a mean width of 100 feet, will be found perhaps more generally applicable to river channels than TABLES XI. and XII., for a mean width of 70 feet. The TABLES at pages 28, 29, 146, and 199 give similar results for long and short cylindrical pipes. The formula (119A), page 230, for finding the velocity in pipes and rivers, is general in its practical application.

The loss of head from friction in a uniform water channel is $h = \left(\frac{v}{m} \right)^2 \times \frac{l}{r}$ in which the value of m for feet measures may be taken from the Table, page 231, with reference to the velocity v . The loss is therefore directly as the length of the channel, directly as $\left(\frac{v}{m} \right)^2$, and inversely as the hydraulic mean depth

—which is one-fourth of the diameter for a cylindrical pipe. I have known an engineer of considerable practice take it as proportionate to the inner surface of a pipe, which was only correct when the diameter remained constant.

The Statistics of rain-fall, and of catchment-basins have not yet received the full attention which the subjects deserve. The distribution of rain gauges with reference to elevation, contour, temperature, and isothermal lines has not been sufficiently attended to. The connexion of the rain-fall with the discharge generally, for the whole catchment, for the tributary catchments, and their sub-catchments, at the sea in the middle districts and at the sources, noting the geology, must be observed for several years before the questions of supply, discharge, absorption, and evaporation in any climate can be answered. The maximum and minimum discharges in each year and series of years must be observed, as well as the average mean discharges, and the maximums and minimums of these also, before the physical connexion of climate and catchment can be correctly ascertained, and the engineer furnished with reliable data. Heretofore observations, even when of the best, have been partial or limited, and a wide field is here yet open to competent physicists in connexion with our drainage works. Mr. Symons is now, however, reducing the rain-fall in Great Britain and Ireland to a scientific form.

The general items of cost given in SECTION XIII. will be found of use ; they are intended, however, more as guides than as standards for estimating other works, the cost of which must depend on their own circumstances. Those who have practical experience of the differences between estimates, cost, and value, and how they are affected by changes of time, locality, quality, and quantity, will estimate for themselves in detail ; but the discrepancies between estimates and cost, even under the same circumstances, are too well known to call for any remarks here.

A few words about my publishers. The Messrs. Lockwood and Co. having purchased the copyright of the work, decided on adopting for this edition a more convenient size for the engineer and student than that of the last edition ; but printed on paper as good, and with type fully as clear. I have reason to be satisfied with the manner in which the work is again brought out and published, and wish them a full return. I am indebted to Mr. R. Field, Westminster, for some observations and corrections, which, coming after the text was printed, I have only here to thank him for, having made use of them in the errata.

JOHN NEVILLE.

RODEN PLACE, DUNDALK,
February, 1875.

CONTENTS.

	PAGES
INTRODUCTION TO THE THIRD EDITION	iii—xi
SECTION I. APPLICATION AND USE OF THE TABLES, FORMULÆ—EXTRA HORSE-POWER REQUIRED IN PUMPING ENGINES FROM FRICTION IN THE PIPES —TABLE OF HEADS DUE TO FRICTION AND OF DISCHARGES	1—31
SECTION II. FORMULÆ FOR THE VELOCITY AND DIS- CHARGE FROM ORIFICES, WEIRS, AND NOTCHES— COEFFICIENTS OF VELOCITY, CONTRACTION, AND DISCHARGE—PRACTICAL REMARKS ON THE USE OF THE FORMULÆ	31—51
SECTION III. EXPERIMENTAL RESULTS AND FORMULÆ —COEFFICIENTS OF DISCHARGE FOR ORIFICES, NOTCHES, AND WEIRS	51—86
SECTION IV. VARIATIONS IN THE COEFFICIENTS FROM THE POSITION OF THE ORIFICE—GENERAL AND PARTIAL CONTRACTION—VELOCITY OF APPROACH— CENTRAL AND MEAN VELOCITIES—VARIOUS PRACTI- CAL FORMULÆ FOR THE DISCHARGE OVER WEIRS AND NOTCHES	86—134
SECTION V. SUBMERGED ORIFICES AND WEIRS—CON- TRACTED RIVER CHANNELS	134—144
SECTION VI. SHORT TUBES, MOUTH-PIECES, AND AP- PROACHES—ALTERATION IN THE COEFFICIENTS FROM FRICTION BY INCREASING THE LENGTH—CO- EFFICIENTS OF DISCHARGE FOR SIMPLE AND COM- POUND TUBES—SHOOTS	144—160

	PAGES
SECTION VII. LATERAL CONTACT OF THE WATER AND TUBE—ATMOSPHERIC PRESSURE—HEAD MEASURED TO THE DISCHARGING ORIFICE—COEFFICIENT OF RESISTANCE—FORMULA FOR THE DISCHARGE FROM A SHORT TUBE—DIAPHRAGMS—OBLIQUE JUNCTIONS —FORMULA FOR THE TIME OF THE SURFACE SINKING A GIVEN DEPTH—LOCK CHAMBERS—FLOOD AND TIDAL SLUICES	160—188
SECTION VIII. FLOW OF WATER IN UNIFORM CHAN- NELS—MEAN VELOCITY—MEAN RADII AND HY- DRAULIC MEAN DEPTHS — BORDER — TRAIN — HYDRAULIC INCLINATION—EFFECTS OF FRICTION— FORMULÆ FOR CALCULATING THE MEAN VELOCITY —APPLICATION OF THE FORMULÆ AND TABLES TO THE SOLUTIONS OF THREE USEFUL PROBLEMS . .	188—251
SECTION IX. BEST FORMS OF THE CHANNEL—REGIMEN —VELOCITY—EQUALLY DISCHARGING CHANNELS .	251—272
SECTION X. EFFECTS OF ENLARGEMENTS AND CON- TRACTIONS—BACKWATER WEIR CASE—LONG AND SHORT WEIRS—THE RIVER SHANNON . . .	272—291
SECTION XI. BENDS AND CURVES—BRANCH PIPES— DIFFERENT LOSSES OF HEAD—GENERAL EQUATION FOR FINDING THE VELOCITY—HYDROSTATIC AND HYDRAULIC PRESSURE—PIEZOMETER—SYPHONS .	291—315
SECTION XII. RAIN-FALL—CATCHMENT BASINS—DIS- CHARGE INTO CHANNELS — DISCHARGE FROM SEWERS — LOSS FROM EVAPORATION, ETC. . .	315—343
SECTION XIII. WATER SUPPLY FOR TOWNS—STRENGTH OF PIPES — SEWERAGE ESTIMATES AND COST— THOROUGH DRAINAGE—ARTERIAL DRAINAGE .	343—399
SECTION XIV. WATER POWER — DYNAMOMETER, OR FRICTION BRAKE — OVERSHOT, BREAST, AND UNDERSHOT VERTICAL WHEELS—TURBINES AND HORIZONTAL WHEELS—HYDRAULIC RAM—WATER- PRESSURE ENGINE—WORK OF FLOUR MILLS. .	399—435

TABLES NOT EMBODIED IN THE TEXT.

	PAGES
TABLE I. <i>Coefficients of Discharge from Square and Differently proportioned Rectangular Lateral Orifices in Thin Vertical Plates.</i> (See pp. 60, 61, and 62.)	436—437
TABLE II. <i>For finding the Velocities from the Altitudes and the Altitudes from the Velocities</i>	438—447
TABLE III. <i>Square Roots for finding the Effects of the Velocity of Approach, when the Orifice is small in proportion to the Head. Also, for finding the Increase in the Discharge from an Increase of Head.</i> (See pp. 91 to 99.)	448—449
TABLE IV. <i>For finding the discharge through Rectangular Orifices; in which $n = \frac{h}{d}$. Also, for finding the Effects of the Velocity of Approach to Weirs, and the Depression on the Crest.</i> (See pp. 91 to 99.)	450—453
TABLE V. <i>Coefficients of Discharge for different Ratios of the Channel to the Orifice.</i> (See pp. 98 to 114.)	454—459
TABLE VI. <i>The Discharge over Weirs or Notches of One Foot in Length, in Cubic Feet per Minute.</i> (See pp. 62 to 86, 90, 96, 109, and 114 to 125.)	460—465
TABLE VII. <i>For finding the Mean Velocity from the Maximum Velocity at the surface, in Mill-races, Streams, and Rivers with Uniform Channels; and the Maximum Velocity from the Mean Velocity.</i> (See pp. 188 to 191.)	466
TABLE VIII. <i>For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.</i> (See p. 209.)	467—479
TABLE IX. <i>For finding the Discharge in Cubic Feet, per Minute, when the Diameter of a Pipe or Orifice, and the Velocity of Discharge, are known, and vice versa</i>	480—481
TABLE X. <i>For finding the Depths on Weirs of different Lengths, the Quantity discharged over each being supposed constant.</i> (See p. 289.)	482

	PAGES
TABLE XI. <i>Relative dimensions of Equally-Discharging Trapezoidal Channels, with Slopes from 0 to 1, up to 2 to 1. (See pp. 267 to 272.)</i>	483
TABLE XII. <i>Discharges from the Primary Channel in the first column of Table XI. (See pp. 270 and 271.)</i>	484—485
TABLE XIII. <i>The Square Roots of the Fifth Powers of Numbers for finding the Diameter of a Pipe, or Dimensions of a Channel from the Discharge, or the reverse; showing the relative Discharging Powers of Pipes of different Diameters, and of any similar Channels whatever, closed or open. (See pp. 28, 29, 245, etc.)</i>	486
TABLE XIV. <i>English and French Measures</i>	487—493
TABLE XV. <i>Weight, Specific Gravity, Ultimate Strength and Elasticity of Various Materials.</i>	494

ERRATA.

Page 99, line 13, for c_d within the brackets read c_d^2 .

Page 179, second line from top, for " $c_d h t$," read " $c_d a h t$;"
and for " f_1 " read " f ."

Page 219, lines 4 to 11. This is Dr. Young's modification of Eytelwein. The original formula in the "Handbuch" is equivalent to $92.3 \sqrt{r s}$. (Mr. Field.)

Page 222, line one at top, for " v_s ," read " v^2 ."

ON THE DISCHARGE OF WATER

FROM
ORIFICES, WEIRS, PIPES, AND RIVERS.

SECTION I.

APPLICATION AND USE OF THE TABLES, AND FORMULÆ.

To find the velocity of a falling body from the height fallen, or the height fallen from the velocity.

RULE.—MULTIPLY THE SQUARE ROOT OF THE HEIGHT IN INCHES BY 27·8, AND THE PRODUCT WILL BE THE VELOCITY IN INCHES.* TO FIND THE HEIGHT FROM THE VELOCITY, SQUARE THE VELOCITY IN INCHES AND DIVIDE THE SQUARE BY 772·84, THE QUOTIENT WILL BE THE HEIGHT IN INCHES. See equation (1). TABLE II., column 1, will give the velocity from the height, found in the column of “altitudes,” or the height from the velocity, directly.

EXAMPLE 1.—*What is the velocity acquired by a heavy body falling $\frac{1}{8}$ th of an inch?*

In the Table opposite to $\frac{1}{8}$ th of an inch, found in the column headed “altitudes h ,” is found 9·829 in

* The square root of the height in feet multiplied by 8·025 gives the velocity per second in feet; and the square of the velocity in feet divided by 64·4 will give the height in feet. The decimals may be omitted in applications for engineering practice, and the multiplier 8 and divisor 64 only used.

column 1, for the required velocity, in inches per second.

EXAMPLE 2.—*What is the velocity acquired by a fall of 11 feet 3 inches?*

Opposite to 11 feet 3 inches, as before, is found 323·007 inches, for the velocity required.

EXAMPLE 3.—*What height must a heavy body fall through to acquire a velocity of $40\frac{1}{2}$ feet per second?*

Here $40\frac{1}{2}$ feet is equal 486 inches, opposite the nearest number to which, found in column 1, is found 25 feet 6 inches for the required fall. In this example, the nearest number to 486 found in the Table is 486·301. The difference ·301 corresponds, very nearly, to $\frac{3}{8}$ ths of an inch in altitude, and, therefore, the true head according to the rule would be 25' 5 $\frac{5}{8}$ "; but for all practical purposes the difference is immaterial.

By means of TABLE II., directly, or by simple interpolation, the velocity due to all heights from $\frac{1}{16}$ part of an inch up to 40 feet, can be found, and the heights from the velocities. For a greater height than 40 feet it may be divided by 4, 9, or some square number, n^2 , and the velocity found for the quotient, from the Table, multiplied by 2, 3, or n , the square root of the divisor, will give the velocity required.

EXAMPLE 4.—*What is the velocity acquired by a fall of 45 feet?*

$\frac{45}{4} = 11' 3''$, the velocity corresponding to which, found from the Table, is 323·007. Hence, $323\cdot007 \times \sqrt{4} = 323\cdot007 \times 2 = 646''\cdot014 = 53' 10''\cdot014$ is the velocity per second required. The reverse of this example is equally simple.

Columns 3, 4, 5, 6, 7, 8, 9, 10, 11, and 12 in the Table, give the values of $\sqrt{2gh}$ multiplied by the coefficients therein stated. These columns will be found of great practical use in finding the mean velocities in the *vena-contracta*, in the orifice, and in short tubes; and consequently, also, in finding the mechanical force, as well as the discharge. An examination of the coefficients in the small Tables in SECTION III., and also of those in TABLES I. and V., at the end of the work, will show how much they vary; but those most generally useful, and their products by the theoretical velocity due to different heads, up to 40 feet, are given in the columns referred to.

EXAMPLE 5.—*What is the discharge from an orifice 4 inches by 8 inches, the centre sunk 20 feet below the surface of a reservoir?*

From TABLE II., is found 430·676 inches equal 35·89 feet for the theoretical velocity of discharge:

hence, $\frac{8 \times 4}{144} \times 35 \cdot 89 = \frac{2}{9} \times 35 \cdot 89 = 7 \cdot 976$ cubic

feet per second is the theoretical discharge. If the discharge takes place through a thin plate, or if the inner arrises next the water in the reservoir be *perfectly square*, and the water in flowing out does not fill the passage so as to convert the orifice into a short tube, the coefficient is found from TABLE I. to be ·608. The true discharge then is $7 \cdot 976 \times \cdot 608 = 4 \cdot 809$ cubic feet per second.

For the determination of the coefficient suited to any particular orifice, and the circumstances of its position, the reader must refer generally to the following pages. If in the example just given, the arrises

next the reservoir were rounded into the form of the contracted vein, see Fig. 4, the coefficient would increase from $\cdot 603$ to $\cdot 974$ or $\cdot 956$, for a passage not exceeding a couple of feet in length. With the former the discharge would be $7\cdot 976 \times \cdot 974 = 7\cdot 769$ cubic feet, and with the latter $7\cdot 976 \times \cdot 956 = 7\cdot 625$ cubic feet. The latter results may be found otherwise from TABLE II. With a head of 20 feet and the coefficient $\cdot 974$, the velocity is $419\cdot 48$ inches = $34\cdot 957$ feet; hence, the discharge is $\frac{2}{9} \times 34\cdot 957 = 7\cdot 768$ cubic feet. With a coefficient of $\cdot 956$, the velocity is $411\cdot 73$ inches = $34\cdot 31$ feet, and $\frac{2}{9} \times 34\cdot 31 = 7\cdot 624$, cubic feet. These results are the same, practically, as those previously found.

If the inner arrises be square, and the passage out be from 18 inches to 2 feet long, the orifice will be converted into a short tube, the coefficient for which is $\cdot 815$. With this coefficient, and a head of 20 feet, find as before, from TABLE II., the mean velocity of discharge 351 inches = $29\cdot 25$ feet; hence, the discharge now is $\frac{2}{9} \times 29\cdot 25 = 6\cdot 5$ cubic feet per second.

The velocities in inches per second, given in TABLES II. and VIII., or elsewhere in the following pages, may be converted into velocities in feet per minute, by multiplying by 5; equal $\frac{60}{12}$.

EXAMPLE 6.—*The discharge from a small orifice having its centre placed 10 feet below the surface of a*

reservoir is 18 feet per minute, what will be the discharge from the same orifice at a depth of 17 feet?

The discharges will be to each other as $\sqrt{10} : \sqrt{17}$, or as $1 : \sqrt{1.7}$; or, from TABLE III., as $1 : 1.3038$, whence the discharge sought is equal $1.3038 \times 18 = 23.4684$ cubic feet.

EXAMPLE 7.—*What is the value of the expression $c_d \left\{ 1 + \frac{c_d^3}{m^2 - c_d^2} \right\}^{\frac{1}{2}}$ in equation (45), when $c_d = .617$, and $m = 2$?*

$$\text{Here } \frac{c_d^3}{m^2 - c_d^2} = \frac{.617^3}{4 - .617^2} = \frac{.3807}{3.6193} = .1052;$$

whence the first expression becomes equal to $.617 (1.1052)^{\frac{1}{2}}$ equal, from TABLE III., $.617 \times 1.0513 = .649$, the value sought. TABLE V. contains the values of this expression for various values of c_d and m , which latter, m , stands for the ratio of the channel to an orifice; and then immediately find from it, opposite 2 in the first column, and under the coefficient $.617$ in the sixth column, $.649$ the value sought. When the head due to the pressure, and to the velocity of approach, are both known, we can determine the new coefficient of discharge by the above expression, and thence the discharge itself. The coefficient suited to the velocity of approach may however be found directly in TABLE V. The usual methods for finding the effects of the velocity of approach, given by d'Aubuisson and others, are incorrect in principle, see SECTION IV.

EXAMPLE 8.—*What is the discharge from an orifice 17 inches long and 9 inches deep, having the upper*

edge placed 4 inches below the surface, and the lower edge 13 inches?

The expression for the discharge is $\frac{2}{3} \times \Delta \sqrt{2gd}$ $\times c_d \left\{ \left(1 + \frac{h_t}{d}\right)^{\frac{3}{2}} - \left(\frac{h_t}{d}\right)^{\frac{3}{2}} \right\}$ equation (49), in which take $d = 9$ inches; $h_t = 4$ inches; $\Delta = 17 \times 9 = 153$ square inches; and $\sqrt{2gd}$, found from TABLE II. = 83.4 inches. Also, $\frac{h_t}{d} = .444$, and hence the value of

$$(1.444)^{\frac{3}{2}} - (.444)^{\frac{3}{2}} = (\text{from TABLE IV.}) 1.44.$$

Assuming the coefficient of discharge to be .617, then the discharge in cubic inches per second is equal to

$$\frac{2}{3} \times 153 \times 83.4 \times .617 \times 1.44 =$$

$$\frac{2}{3} \times 12760.2 \times .88848 = 7558.$$

Consequently, $\frac{7558}{1728} = 4.374$ is the discharge in cubic feet per second. From equation (6.), the discharge is equal to

$$\frac{2}{3} \times .617 \times 27.8 \times 17 \times \{13^{\frac{3}{2}} - 4^{\frac{3}{2}}\}$$

But $13^{\frac{3}{2}} - 4^{\frac{3}{2}} = 46.872 - 8$, from TABLE IV., equal to 38.872, whence the discharge is

$$\frac{2}{3} \times .617 \times 27.8 \times 17 \times 38.872 = 11.4351 \times 17 \times 38.872 = 194.3967 \times 38.872 = 7557 \text{ cubic inches} = 4.374 \text{ cubic feet, the same as before.}$$

It is shown, equation (31), that by using the mean depth for orifices near the surface, the discharge will approximate very closely to the true discharge, and that even for weirs the error will not exceed

6 per cent. The discharge is then expressed by $\cdot 617 \sqrt{2g \times 8\frac{1}{2}} \times 9 \times 17 =$ (from TABLE II.) $50\cdot 01 \times 153 = 7651\cdot 58$ cubic inches $= 4\cdot 427$ cubic feet per second. The head to the centre of the orifice is here $8\frac{1}{2}$ inches, and the depth of the orifice 9 inches, therefore, in equation (31), $h = d$ very nearly; and, therefore, this result must be multiplied by $\cdot 989$, as shown in that equation; then $\cdot 989 \times 4\cdot 427 = 4\cdot 378$ cubic feet, which gives a result differing from those otherwise found, by a very small quantity, which, practically, is of no value. By means of TABLE VI. the discharge from rectangular orifices near the surface can be found with very great facility.

The discharge from an orifice near the surface may always be found with sufficient accuracy, for practical purposes, by measuring the head to the centre, in the same manner as if the orifice were sunk to a considerable depth; then by applying the corrections given in equation (31); or if the orifice be circular, those given in equation (28); sufficient accuracy, according to the correct formula, is obtainable.

EXAMPLE 9.—*What is the discharge from a circular orifice 4 inches in diameter, having its centre placed 4 inches below the surface, when the coefficient of discharge is $\cdot 617$?*

The area of the orifice is $4 \times 4 \times \cdot 7854 = 12\cdot 566$ square inches. The velocity in the orifice at the mean depth of 4 inches, with a coefficient of $\cdot 617$, is $34\cdot 31$ inches, whence the discharge is $12\cdot 566 \times 34\cdot 31 = 431\cdot 139$ cubic inches $= 2\cdot 496$ cubic feet per second, or $14\cdot 97$ cubic feet per minute. By means of TABLE IX. the discharge in cubic feet per minute can be

found very readily when the velocity (34·31 inches per second) is known. Thus,

	Inches.		Cubic feet.
For a velocity of	30·00	the discharge is	13·089
" "	4·00	" "	1·745
" "	·30	" "	0·131
" "	·01	" "	0·004
<hr/>			
" "	34·31	" "	14·969

By applying the coefficient found from equation (28), which is ·992, when the depth at the centre is twice the radius, as it is in this example, $\cdot992 \times 14\cdot97 = 14\cdot85$ is found for the correct discharge in cubic feet per minute. Here the difference in the results is only 1 in 125.

The application of TABLE VI. enables us to find the discharge from rectangular orifices near the surface very quickly. Resuming "EXAMPLE 8," the discharge may be found from this Table for each foot in length of the orifice, as follows. The discharge in cubic feet per minute, when the coefficient is ·617 for a notch 1 foot long and 13 inches deep, is 223·323; and for a notch of 4 inches deep, 38·116; therefore, the discharge from an orifice 9 inches deep, with the upper edge 4 inches below the surface, is $223\cdot323 - 38\cdot116 = 185\cdot207$ cubic feet per minute. But as the length of the orifice is 17 inches, this must be multiplied by $\frac{17}{12}$, and the product 262·377 is the discharge in cubic feet per minute; this is equal to a discharge of 4·373 cubic feet per second, and agrees with that before found. This is the simplest way of finding the discharge from rectangular orifices near the surface.

EXAMPLE 10.—*What is the discharge in cubic feet per minute, from an orifice 2 feet 6 inches long and 7 inches deep, the upper edge being 8 inches below the surface, and the coefficient of discharge .628?*

From TABLE VI. the discharge from a notch 1 foot long and 10 inches deep is found to be 153.853, and for a notch 8 inches deep, 25.199. The difference, or 128.154, multiplied by $2\frac{1}{2}$, will be the discharge required; viz. $2\frac{1}{2} \times 128.154 = 320.385$ cubic feet per minute.

EXAMPLE 11.—*The size of a channel is 2.75 times the size of an orifice, what is the coefficient of discharge when that for a very large channel in proportion to the orifice is .628?*

From TABLE V. the coefficient is found to be .645, when the approaching water suffers full contraction. By attending to the auxiliary Tables in the text, we find for this case, $\frac{\text{orifice}}{\text{channel}} = \frac{1}{2.75} = .36$. Hence, therefore, multiply 2.75 by .857, which gives 2.36 for the ratio of the mean velocities in the orifice and in the channel approaching it. With this new value of the ratio of the channel to the orifice, find, as before, the value of the coefficient from TABLE V. which is .651. The remarks throughout the work, with the auxiliary tables, will be found of much use in determining the coefficients for different ratios of the channel to the orifice, notch, or weir, and the corrections suited to each. If in this example,—other things being the same,—the alteration in the coefficient for a notch, or weir, had to be considered, it would be found from the Table, column 4, to be .672 instead of .645 found in column

3, for an orifice sunk some depth below the surface. For the corrections suited to mean and central velocity, and to the nature of the approaches, they may be found in the body of this work and in the auxiliary tables at the end of SECTION IV.

EXAMPLE 12.—*What is the discharge over a weir 50 feet long; the circumstances of the overfall, crest, and approaches, being such that the coefficient of discharge is .617, when the head measured from the water in the weir basin, 6 feet above the crest, is $17\frac{1}{2}$ inches?*

TABLE VI. gives the discharge in cubic feet per minute, over each foot in length of weir, for various depths up to 6 feet. It is divided into two parts; the first for "greater coefficients," viz. .667 to .617; and the second for "lesser coefficients," viz. .606 to .518. The coefficient assumed being .617, the discharge over 1 foot in length, with a head of $17\frac{1}{2}$ inches, is found to be 348.799 cubic feet per minute; hence the required discharge is $50 \times 348.799 = 17439.95$ cubic feet.

The determination of the coefficient suited to the circumstances of the overfall, crest, approaches, and approaching section, will be found discussed elsewhere through this work. The valuable Table derived from Mr. Blackwell's experiments will also be of use; but the heads being taken at a much greater distance back from the crest than is generally usual, the coefficients taken from it for heads greater than 5 or 6 inches, will be found less than the true ones for heads measured immediately at or about 6 feet, above the crest. For heads measured on the crest, the small Table of coefficients in SECTION III., applicable to the purpose, will be of use.

EXAMPLE 18.—*What is the mean velocity in a large channel, when the maximum velocity along the central line of the surface is 31 inches per second?*

TABLE VII. gives 25·89 inches for the required velocity, and for smaller channels 24·86 inches. In order to find the mean velocity at the surface from the maximum central velocity, the latter must be multiplied by ·914.

The velocity at the surface is best found by means of a floating hollow ball, which just rises out of the water. The velocity at a given depth is best found by means of two hollow balls connected with a link, the lower being made heavier than the upper, and both so weighted by the admission of a certain quantity of water that they shall float along the current, the upper one being in advance but nearly vertical over the other. The velocity of both will then be the velocity at half the depth between them. The velocity at the surface, found by means of a single ball, being also found, the velocity lost at the half depth is had by subtracting the common velocity due to the linked balls from that of the single ball at the surface. The velocity at any given depth is then easily found by a simple proportion; but the result will be most accurate when the given depth is nearly half the distance between the balls, which distance can never exceed the depth of the channel. *Pitot's tube*, *Woltmann's tachometer*, the *hydrometric pendulum*, the *rheometer*, and several other hydrometers, have been used for finding the velocity; but these instruments require certain corrections suited to each separate instrument, as well as each kind of instrument, and are not so correct or simple, for

for measuring the velocity in open channels, as a ball and linked balls. In general the surface maximum velocity can be found by throwing in a rag-weed, or some other plant, and observing the time it is carried over a given distance, say from 30 to 100 feet or more, according to the circumstances of the channel; and multiplying the velocity so found by $\cdot 88$ to find the mean velocity. If the velocity at the surface be taken at several sections, between the centre and the banks, the multiplier should be increased to $\cdot 91$.

EXAMPLE 14.—*What is the discharge from a river having a surface inclination of 18 inches per mile, or 1 in 3520, 40 feet wide, with nearly vertical banks, and 3 feet deep?*

The area is $40 \times 3 = 120$ feet, and the border $40 + 2 \times 3 = 46$ feet; therefore the hydraulic mean depth is $\frac{120}{46} = 2\cdot 61$ feet = 2 feet 7·3 inches.* With this and the inclination we find from TABLE VIII.

$$28\cdot 27 + 2\cdot 75 \times \frac{1\cdot 8}{6} = 28\cdot 87 \text{ inches per second} =$$

$$28\cdot 87 \times 5 = 144\cdot 35 \text{ feet per minute for the mean velocity; hence } 144\cdot 35 \times 120 = 17,322 \text{ cubic feet per minute is the required discharge.}$$

For channels with sloping banks divide the border, which is always known, into the area for the hydraulic mean depth, with which, and the surface inclination, find the velocity by TABLE VIII., and thence the discharge. Unless the banks of

* For greater hydraulic depths than 144 inches, the extent of the TABLE, divide by 9, and find the corresponding velocity. This multiplied by 3 will be the velocity sought. Or divide by 4 and multiply by 2.

rivers be protected by stone pavement or otherwise, the slopes will not continue permanent; it is therefore almost useless to give the discharges for channels of particular widths and slide slopes. When the mean velocity is once known, the remaining calculations are those of mere mensuration, and they should be made separately. This example may also be solved, practically, by means of TABLE XI. and XII. A channel 40×3 has the same conveying power as one 70×2 , TABLE XI., which latter, TABLE XII. discharges with a fall of 18 inches in the mile, 17,157 feet; or about one per cent. less than that previously found.

EXAMPLE 15.—*The diameter of a very long pipe is $1\frac{1}{2}$ inch, and the rate of inclination, or whole length of the pipe divided by the whole fall, is 1 in $71\frac{1}{2}$; what is the discharge in cubic feet per minute?*

The hydraulic mean depth, or mean radius, is $\frac{1.5}{4} = .375$ inch $= \frac{3}{8}$ inch. Consequently from TABLE VIII. the velocity in inches per second is equal to $25.09 - 1.92 \times \frac{1.5}{10} = 25.09 - .29 = 24.80$. The discharge in cubic feet per minute for a $1\frac{1}{2}$ -inch pipe is now found most readily by means of TABLE IX., as follows:—

		Inches.			Cubic feet.
For a velocity of	20.0		the discharge is	1.227	
„	„	4.0	„	„	.245
„	„	.8	„	„	.049
		<hr/>			<hr/>
„	„	24.8	„	„	1.521

Whence the discharge in cubic feet per minute is 1.521.

For short pipes, of 100 or 200 feet in length, and under, the height due to the velocity and orifice of entry must be deducted from the whole height to find the proper hydraulic inclination, and also the height due to bends, curves, cocks, slides, and erogation. The neglect of these corrections has led some writers into mistakes in applying certain formulæ, and in testing them by experimental results obtained with short pipes. The TABLES shall now be applied to the determination of the discharge from short pipes, and the results compared with experiment, referring generally to equation (153A) and the remarks preceding it for a correct and direct solution.

EXAMPLE 16.—*What is the discharge in cubic feet per minute from a pipe 100 feet long, with a fall or head of 35 inches to the lower end, when the diameter is $1\frac{1}{2}$ inch? Find also the discharge from pipes 80 feet, 60 feet, 40 feet, and 20 feet, of the same diameter and having the same head.*

If the water be admitted by a stop-cock at the upper end, the coefficient due to the orifice of entry will probably be about .75 or less, .815 being that for a clear entry to a short cylindrical tube. The approximate inclination is $\frac{100 \times 12}{35} = 1$ in 34.3; but as a portion of the fall must be absorbed by the velocity and orifice of entry, it may be assumed for the present that the inclination is 1 in 35. With this inclination and the mean radius $\frac{1\frac{1}{2}}{4} = \frac{3}{8}$ inch, we find the mean velocity from TABLE VIII. to be 38.06 inches. Now when the coefficient due to the orifice of entry and

velocity is $\cdot 75$, from TABLE II. the head due to this velocity is $3\frac{3}{8}$ inches nearly, whence $35 - 3\frac{3}{8} = 31\frac{5}{8} = 31\cdot625$ inches is the height due to friction, and $\frac{100 \times 12}{31\cdot625}$

equals 1 in $37\cdot9$, the inclination, very nearly. With this new inclination find, as before, from TABLE VIII. the mean velocity of discharge which is now $36\cdot35$ inches; and by repeating the operation the velocity to any degree of accuracy is found in accordance with the table; and the shorter the pipe is, the oftener must it be repeated. The height due to $36\cdot35$ inches taken from TABLE II. as before, with a coefficient of $\cdot 750$, is $3\frac{1}{8} = 3\cdot125$ inches. The corrected fall due to the

friction is now $35 - 3\cdot125 = 31\cdot875$, and $\frac{1200}{31\cdot875}$ equal

1 in $37\cdot6$, the corrected inclination. With this inclination the corrected velocity is now $36\cdot53$ inches per second. It is not necessary to repeat this operation again. The discharge determined from TABLE IX. is as follows :—

	Inches.		Cubic feet.
For a velocity of	30·00	the discharge is	1·841
„	6·00	„	·368
„	·50	„	·031
„	·03	„	·002
	<hr/>		<hr/>
„	36·53	„	2·242

The experimental discharge found by Mr. Provis was $2\cdot264$ cubic feet per minute in one experiment, and $2\cdot285$ in another. The discharge from the shorter pipes may be found in a similar manner, and the results placed alongside the experimental ones given

in the work referred to below * are inserted in the following short table :—

EXPERIMENTAL AND CALCULATED DISCHARGES FROM SHORT PIPES.

Length of pipe, in feet.	Head, in inches.	Observed discharge, in cubic feet.	Velocity per second.	Head due to the orifice and velocity.	Head due to friction.	Hydraulic inclinations.	Calculated velocity.	Calculated discharge.
100	35	2·275	37·082	3½	31½	37·6	36·53	2·242
80	35	2·500	40·750	3¾	31½	30·8	41·18	2·521
60	35	2·874	46·846	5	30	24·0	48·02	2·946
40	35	3·504	57·115	7½	27½	17·5	58·50	3·590
20	35	4·528	73·801	12½	22½	10·7	78·61	4·824

The velocities in the fourth column have been calculated by the author from the observed quantities discharged, from which the height due to the orifice of entry and velocity in column 5 is determined, and thence the quantities in the other columns as above shown. The differences between the experimental and calculated results are not large, and had a lesser coefficient than ·750 been used for calculating the reduction of head due to the velocity, stop-cock, and orifice of entry, say ·715, the calculated results, and

* "Transactions of the Institution of Civil Engineers," vol. ii. p. 203. "Experiments on the Flow of Water through small Pipes." By W. A. Provis. The small Tables in SECTIONS VI. and VIII. of this edition give at once the coefficient to be multiplied by $\sqrt{2 g H}$, or $8\sqrt{H}$, to find the velocity when the ratio of the diameter to the length of the pipe is known. They will be found of great advantage in calculating directly the velocity from short pipes. For long pipes, see the TABLE at the end of this Section.

those in all of Mr. Provis's experiments in the work referred to, would be nearly identical.*

EXAMPLE 17.—*It is proposed to supply a reservoir near the town of Drogheda with water by a long pipe, having an inclination of 1 in 480, the daily supply to be 80,000 cubic feet; what must the diameter of the pipe be?*

The discharge per minute must be $\frac{80,000}{1440} = 56 \frac{1}{3}$ cubic feet, nearly. Assume a pipe whose "mean radius" is 1 inch, or diameter 4 inches, and the velocity per second found from TABLE VIII. will be 14.41 inches. Then from TABLE IX.,

		Inches.			Cubic feet.
For a velocity of	10.00		a discharge of	4.363	
" "	4.00		" "	1.745	
" "	.40		" "	.175	
" "	.01		" "	.004	
		—			—
" "	14.41		" "	6.287	

The discharge from a pipe 4 inches in diameter would be therefore 6.287 cubic feet per minute. Then

$4^{\frac{5}{2}} : d^{\frac{5}{2}} :: 6.287 : 56$, or $1 : d^{\frac{5}{2}} :: .196 : 56 :: 1 : 286$; therefore $d^{\frac{5}{2}} = 286$, and $d = 9.61$ inches, nearly, as may be found from TABLE XIII., &c. This is nearly the required diameter. It is to be observed that the diameters thus found will not always agree exactly

* In a late work, "Researches in Hydraulics," the author is led into a series of mistakes as to the accuracy of Du Buat's and several other formulæ, from neglecting to take into consideration the head due to the velocity and orifice of entry when testing them by the experiments above referred to.—*Second Edition.*

† "Hydraulic Tables," Weale, 1854, give at once this discharge for a pipe between 9 and 10 inches in diameter, also the TABLE, p. 28.

with those found from Du Buât's or other formulæ, nor with each other, because the discharges are not strictly as $d^{\frac{5}{2}}$; but in practice the difference is immaterial, and the approximative value thus found can be easily corrected. If a pipe whose diameter is 1, were assumed, the operation would have been more simple; for the velocity would then be, TABLE VIII., at the given inclination, 6.4 inches; and the discharge .175 cubic feet, TABLE IX. Hence $d^{\frac{5}{2}} = \frac{56}{.175} = 320$, and,

therefore, TABLE XIII., $d = 10$ inches nearly, which differs about half-an-inch from the former value, 9.6 inches, found by assuming a pipe of 4 inches to calculate from. It is necessary to understand that different results must be expected, in working from practical formulæ, for different operations. When once an approximate value is obtained, it can be easily corrected to any required degree of accuracy.

Again, *the velocity in inches per second, from a cylindrical pipe 6 inches in diameter, is nearly equal to the discharge in cubic feet per minute; and as $6^{\frac{5}{2}} = 88.2$, then $88.2 : d :: \text{the velocity in inches per second from a 6-inch pipe} : \text{the discharge per minute from a pipe whose diameter is } d$. Hence this proposition gives, very nearly, the discharge from the diameter and fall; or the diameter from the discharge and fall by finding the velocity only, due to a 6-inch pipe. See TABLES pp. 28 and 29.*

EXAMPLE 18.—*The area of a channel is 50 square feet, and the border 20.6 feet; the surface has an inclination of 4 inches in a mile; what is the mean velocity of discharge?*

$\frac{50}{20.6} = 2.427$ feet = 29.124 inches is the hydraulic mean depth; and from TABLE VIII., $12.03 - \frac{1.30 \times .876}{6} = 12.03 - .19 = 11.84$ inches per second is the required velocity. Though this velocity will be found under the true value for straight clear channels, it will yet be more correct for ordinary river courses, with bends and turns, of the dimensions given, than the velocity found from equation (114.). For a straight clear channel of these dimensions, Watt found the mean velocity to be 13.5 to 14 inches; that is to say, 17 at top, 10 at bottom, and 14 in the middle. The author's formula $v = 140 (r s)^{\frac{1}{2}} - 11 (r s)^{\frac{1}{3}}$ gives $v = 1.148$ feet, or nearly a mean of these two.

EXAMPLE 19.—*A pipe 5 inches in diameter, 14,637 feet in length, has a fall of 44 feet; what is the discharge in cubic feet per minute?*

The inclination is $\frac{14,637}{44} = 332.7$, and mean radius $\frac{5}{4} = 1\frac{1}{4}$. Then find from TABLE VIII. the velocity which is equal to $19.81 + \frac{.41 \times 4.8}{12.5} = 19.81 + .16 = 19.97$, or 20 inches per second very nearly; and by TABLE IX. the discharge in cubic feet per minute is, as before found to be, 13.635. The TABLE, p. 28, gives, by inspection, 13.6 feet.

EXAMPLE 20.—*What is the velocity of discharge from a pipe or culvert 4 feet in diameter, having a fall of 1 foot to a mile?*

Here $s = \frac{1}{5280}$, and $r = 1$ foot. Next we find the velocity of discharge from TABLE VIII. which is 14.09 inches, equal to 1.174 feet per second. By calculating from the different formulæ referred to below, the velocities, when $r s = .0001894$, and $\sqrt{r s} = .01876$, are as follows.

	Velocity in feet.
Reduction of Du Buât's formula equation (81.)	1.174
„ Girard's do. (Canals with aquatic plants and very slow velocities) „ (86.)	.521
„ Prony's do. (Canals) „ (88.)	1.201
„ Prony's formula (Pipes) „ (90.)	1.257
„ Prony's do. (Pipes and Canals) „ (92.)	1.229
„ Eytelwein's do. (Rivers) „ (94.)	1.200
„ Eytelwein's do. (Rivers) „ (96.)	1.285
„ Eytelwein's do. (Pipes) „ (98.)	1.364
„ Eytelwein's do. (Pipes) „ (99.)	1.350
„ Dr. Young's do. „ (104.)	1.120
„ *D'Aubuisson's do. (Pipes) „ (109.)	1.259
„ *D'Aubuisson's (Rivers) „ (111.)	1.199
„ The writer's do. (Clear straight Channels with small velocities) „ (114.)	1.268
„ Weisbach's do. (Pipes) „ (119.)	1.285
„ The author's, for Pipes and Rivers „ (119A.)	1.295

This example is calculated from the several formulæ above referred to, whether for pipes or rivers, in order that the results may be more readily compared. The formula from which the velocities and tables for the discharges of rivers are usually calculated is, for measures in feet, $v = 94.17 \sqrt{r s}$. This gives the mean velocity, for the foregoing example, equal to

* These two formulæ of D'Aubuisson's are, simply, adoptions of Eytelwein's and Prony's.

1.295 feet per second. This is the same as is found from the author's general formula for all velocities; but the particular expression, $v = 99.17 \sqrt{r s}$, is only suited for velocities of about 15 inches per second; the results found from it for lesser velocities are too much, and for higher velocities too little, if bends and curves be allowed for separately. For ordinary practical purposes the result of Du Buât's general formula, equation (81), may be safely adopted; and, accordingly, the results in TABLE VIII. calculated for the first edition from it, have been retained, notwithstanding the greater accuracy and simplicity of the general equation (119 A) for the velocity in pipes and rivers, viz., $v = 140 (r s)^{\frac{1}{2}} - 11 (r s)^{\frac{1}{2}}$.

Dr. Young's formula gives lesser results for rivers and large pipes than Du Buât's, but they are too small unless when the curves and bends are numerous and sudden. Girard's formula (86.) is only suited for small velocities in canals containing aquatic plants, and it is entirely inapplicable to rivers or regular channels for conveyance of water. A knowledge of various formulæ, and their comparative results, applied to any particular case, will be found of great value to the hydraulic engineer, and the differences in the results show only an amount of error that may be expected in all practical operations, and which becomes of less importance when it is considered that by increasing the dimensions of a channel every way, by only one-third, its discharging power is more than doubled. See TABLE XIII.

EXAMPLE 21.—*Water flowing down a river rises to a height of $10\frac{1}{2}$ inches on a weir 62 feet long; to*

what height will the same quantity of water rise, on a weir similarly circumstanced, 120 feet long?

$$\frac{62}{120} = \cdot 517, \text{ nearly.}$$

In TABLE X. is found, by inspection, opposite to $\cdot 517$, the ratio of the lengths, the coefficient $\cdot 644$, rejecting the fourth place of decimals; whence $10\frac{1}{2} \times \cdot 644 = 6\cdot 76$ inches, the height required. When the height is given in inches it is not necessary to take out the coefficient to further than two places of decimals.

EXAMPLE 22.—*The head on a weir 220 feet long is 6 inches; what will the head be on a weir 60 feet long, similarly circumstanced, the same quantity of water flowing over each?*

$$\frac{60}{220} = \cdot 273.$$

As this lies between $\cdot 27$ and $\cdot 28$, from TABLE X. the coefficient $\cdot 4208$ is found; hence $\frac{6}{\cdot 4208} = 14\cdot 26$ inches, the head required.

TABLE X. will be found equally applicable in finding the head above the pass into weir basins, and above contracted water channels. See SECTION X.

EXAMPLE 23.—*A river channel 40 feet wide and 4·5 feet deep is to be altered and widened to 70 feet; what must the depth of the new channel be so that the surface inclination and discharge shall remain unaltered?*

In "TABLE XI., OF EQUALLY DISCHARGING RECTANGULAR CHANNELS," opposite to $4\cdot 54$, in the column of 40 feet widths, 3 is found in the column of 70 feet widths, which is the depth required in feet.

EXAMPLE 24.—*It is necessary to unwater a river channel 70 feet wide and 1 foot deep, by a rectangular side cut 10 feet wide; what must the depth of the side cut be, the surface inclination remaining the same as in the old channel?*

In TABLE XI. is found 4.5 feet for the required depth. When the width of a channel remains constant, the discharge varies as $\sqrt{r} s \times d$, in which d is the depth; and when the width is very large compared with the depth, the hydraulic mean depth r approximates very closely to the depth d , and therefore $d=r$; consequently the discharge then varies as $d^{\frac{3}{2}} \times s^{\frac{1}{2}}$, and when the discharge is given $d^{\frac{3}{2}}$ must vary inversely as $s^{\frac{1}{2}}$; or more generally $dr^{\frac{1}{2}}$ must vary inversely, as $s^{\frac{1}{2}}$, when the width and discharge remain constant.

In narrow cuts for unwatering, it is prudent to make the depth of the water half the width of the cut very nearly, when local circumstances admit of these proportions; for then a maximum effect will be obtained with the least possible quantity of excavation; but for rivers and permanent channels the proper relation of the depth to the width must be regulated by the principles referred to in SECTION IX.

TABLE XI. is equally applicable, whether the measures be taken in feet, yards, or any other standards whatever.

EXAMPLE 25.—*A new river channel is to have a fall of eighteen inches in a mile, and must discharge 18,700 cubic feet per minute; what shall the dimensions be?*

In TABLE XII., in the column of 18 inches per mile, opposite to 18,766, it is seen that a primary channel 70×2.125 will be sufficient; and opposite to 2.125 in TABLE XI. it is also seen the equivalent rectangular channels 60×2.37 ; 50×2.70 ; 40×3.19 ; 35×3.52 ; 30×3.96 ; 25×4.61 ; 20×5.58 ; 15×7.29 ; and 10×11.37 , to select from. If the side have any given slopes, the discharge will not be practically affected as long as the depth and area of the rectangular channel and the one with sloping banks remain the same. See SECTION IX.

EXAMPLE 26.—*A pipe 100 feet long and 1 inch in diameter has a head of 150 feet over the lower end, what will be the discharging velocity?*

Here $r = .020833$ in feet, and $s = 1.5$, therefore $rs = .03125$. Hence by formulæ (119A) $v = 140 \times (.03125)^{\frac{1}{2}} - 11 \times (.03125)^{\frac{1}{2}} = 140 \times .1766 - 11 \times .315 = 24.724 - 3.465 = 21.259$ feet per second. If allowance is required for the orifice of entry, the velocity is corrected as follows. A square orifice of entry has a coefficient of .815. The head due to this coefficient for a velocity of about $20\frac{1}{2}$ feet, or 246 inches, is about 10 feet, TABLE II.—The head due to friction is therefore $150 - 10 = 140$ feet, and $s = \frac{100}{140} = 1.4$; rs now becomes $1.4 \times .020833 = .02917$.

Hence $v = 140 \sqrt{rs} - 11 \sqrt[3]{rs}$ now becomes $140 \times .171 - 11 \times .308$ nearly, equal to $23.940 - 3.388 = 20.552$ feet, the velocity for a square junction.

EXAMPLE 27.—*A sewer 9 feet in diameter has a fall of 2 feet per mile, what will be the velocity and discharge of water flowing through it when full?*

Here $r = 2.25$ and $s = \frac{1}{2640}$, therefore $rs = .0008528$,
 $(rs)^{\frac{1}{2}} = .02919$ and $(rs)^{\frac{1}{3}} = .0948$; and by formula
 (119A), $v = 140 (rs)^{\frac{1}{2}} - 11 (rs)^{\frac{1}{3}} = 140 \times .02919 - 11 \times$
 $.0948 = 4.0866 - 1.0428 = 3.0438$ feet per second.
 Hence the discharge per minute is $9^2 \times .7854 \times$
 $3.0438 \times 60 = 63.62 \times 182.6 = 11,617$ cubic feet
 nearly. The velocity from a circular pipe or sewer
 is however greatest when the circumference is open
 for about $78\frac{1}{2}$ degrees at the top, but the velocity
 of sewage matter would not be equal to that of
 water. It would vary according to the dilution in the
 sewer, and 50 per cent. should be allowed, at least,
 in deduction, unless the dilution be very consi-
 derable.

The TABLE for the values of rs and v , calculated
 from the formula (119 A) SEC. VIII., will give the
 velocity at once when rs is known, and rs when
 the velocity is known, from the latter of which a
 definite value of r or s can be fixed upon, when the
 other may be then found, by an operation of simple
 division.

EXAMPLE 28.—*Water is to be pumped through a
 pipe 3000 feet long and 2 feet in diameter, with
 a velocity not exceeding 4 feet per second, what head
 must be allowed extra for friction in the pipe when
 calculating horse power?*

From the TABLE of the values of the velocity and
 products of the hydraulic mean depth and hydraulic
 inclination, given near the conclusion of SECTION VIII.,
 that for a velocity of 4 feet per second $rs = .00142$.
 The diameter of the pipe is 2 feet, therefore $r = .5$,

whence $s = \frac{.00142}{.5} = .00284$, and as the length of the pipe is 3000 feet we get $3000 \times .00284 = 8.52$ feet, the head required. The TABLE p. 29, would give 9.6 feet nearly, which corresponds with Du Buât's formula. If the velocity in the pipe were 10 feet instead of 4 feet per second, then from the table, $r s = .007576$, and $\frac{r s}{r} = s = \frac{.007576}{.5} = .015152$, and therefore, $h = l s = 3000 \times .015152 = 45.456$ feet, or about six times as much as when the velocity was only 4 feet per second. The great loss of head arising from pumping at high velocities, from friction alone, is therefore apparent. Were the velocity double, or 8 feet per second, the head would be 30 feet nearly, or from the TABLE, p. 29, 31.6 feet.

For velocities of about 2.1 feet per second, v , is equal to $100 \sqrt{r s}$, and for velocities of about $5\frac{1}{2}$ feet per second, $v = 110 \sqrt{r s}$. If l be the length of a pipe, it would be found in the former case that the head, h , in feet due to friction from the formula is $h = \frac{l v^2}{10,000 r} = l s$; and in the latter $h = \frac{l v^2}{12,100 r} = l s$.

In questions of this kind, however, the diameter of a pipe, d should be used in preference to the hydraulic mean depth, and as $d = 4 r$ it will be found in the first case that $h = \frac{l v^2}{2500 d} = l s$; and in the second case, $h = \frac{l v^2}{3025 d} = l s$.

If it be necessary to substitute the fall per mile for

the hydraulic inclination, the first of these will again become $h = \frac{2.11 v^3}{d} = l s$ for the loss per mile; and in the second case, $h = \frac{1.72 v^3}{d} = l s$ for the loss per mile in feet.

If the velocity were so slow as about 1 foot per second, then $v = 90 \sqrt{r s}$, and we should find $h = \frac{l v^3}{2025 d} = l s$.

If for the inclination the fall per mile be substituted, this will become $h = \frac{2.61 v^3}{d} = l s$; for the loss per mile in feet.

The loss of head varies in the same pipe with the velocity, and must be calculated differently, for small and for high velocities, when using the common formulæ. The TABLE near the end of SECTION VIII. will always give the correct value of $r s$, and thence $s = \frac{r s}{r}$.

In addition to the loss of head arising from friction, losses also occur from straight or curved bends, from diaphragms, from junctions, and from the orifices of entry and discharge; these must be determined separately for each case, as is shown hereafter, and added together, including the loss of head arising from friction. The sum must then be added to the height the water is to be raised, before the full or total head for determining the power of an engine can be accurately known.

The TABLE on the two following pages will be found

TABLE for finding, very nearly, the velocity and discharge from Cylindrical Water Pipes or Sewers when the diameter and fall are given. Any two of the four quantities, the velocity, discharge diameter, and fall or inclination, being given, the others can be found in the TABLE from inspection. See TABLE XIII.

Height in ft. due to friction per mile of length.	Mean hydraulic radius in inches.	Fall in inches per mile.	The VELOCITY IN INCHES PER SECOND is given in the first horizontal line for each inclination or fall; and the DISCHARGE IN CUBIC FEET PER MINUTE in the next following one.							
			1 in. diam.	2 in. diam.	3 in. diam.	4 in. diam.	5 in. diam.	6 in. diam.	7 in. diam.	8 in. diam.
1	5280	1.7	2.5	3.2	3.8	4.2	4.7	5.1	5.5	5.9
		.05	.27	.79	1.6	2.9	4.6	6.8	9.6	12.9
2	2640	2.5	3.8	4.7	5.6	6.3	6.9	7.5	8.1	8.6
		.07	.41	1.2	2.4	4.3	6.8	10.1	14.2	19.1
3	1760	3.1	4.7	5.9	7.0	7.8	8.7	9.4	10.2	10.8
		.08	.51	1.4	3.0	5.3	8.5	12.6	17.7	23.9
4	1320	3.6	5.5	6.9	8.2	9.2	10.2	11.1	11.9	12.7
		.10	.60	1.7	3.6	6.3	10.0	14.8	20.8	28.0
5	1056	4.1	6.2	7.9	9.3	10.4	11.6	12.5	13.5	14.4
		.11	.68	1.9	4.0	7.1	11.3	16.8	23.6	31.7
6	880	4.6	6.9	8.7	10.3	11.5	12.8	13.9	15.0	15.9
		.12	.76	2.2	4.5	7.9	12.6	18.6	26.1	35.1
7	754	5.0	7.5	9.5	11.2	12.6	14.0	15.1	16.3	17.4
		.14	.82	2.3	4.9	8.6	13.7	20.2	28.5	38.3
8	660	5.4	8.1	10.2	12.0	13.5	15.0	16.3	17.6	18.7
		.15	.89	2.5	5.3	9.2	14.8	21.8	30.6	41.3
9	587	5.7	8.7	11.0	12.9	14.5	16.1	17.4	18.8	20.0
		.16	.95	2.7	5.6	9.9	15.8	23.3	32.8	44.1
10	528	6.1	9.2	11.6	13.7	15.4	17.1	18.5	19.9	21.2
		.17	1.00	2.9	6.0	9.2	16.7	24.7	34.8	46.8
11	480	6.4	9.7	12.3	14.4	16.2	18.0	19.5	21.0	22.4
		.17	1.1	3.0	6.3	11.1	17.7	26.1	36.7	49.4
12	440	6.7	10.2	12.9	15.2	17.1	18.9	20.5	22.1	23.5
		.18	1.1	3.2	6.6	11.6	18.6	27.4	38.6	51.9
13.2	400	7.1	10.8	13.6	16.0	18.0	20.0	21.7	23.3	24.8
		.19	1.2	3.3	6.9	12.3	19.6	28.9	40.7	54.6
15.1	350	7.7	11.6	14.7	17.2	19.4	21.6	23.4	25.2	26.8
		.21	1.3	3.6	7.5	13.2	21.2	31.2	43.9	59.1
17.6	300	8.4	12.7	16.0	18.8	21.2	23.5	25.5	27.5	29.2
		.23	1.4	3.9	8.2	14.4	23.1	34.1	48.8	64.6
21.1	250	9.4	14.1	17.8	20.9	23.5	26.1	28.3	30.5	32.5
		.26	1.5	4.4	9.2	16.0	25.7	37.8	53.3	71.7
26.4	200	10.6	16.0	20.2	23.8	26.8	29.7	32.3	34.7	36.9
		.29	1.7	5.0	10.4	18.2	29.2	43.1	60.6	81.6
35.2	150	12.5	19.0	23.9	28.1	31.6	35.1	38.1	41.0	43.7
		.34	2.1	5.9	12.3	21.6	34.5	50.9	71.6	96.4
52.8	100	15.9	24.1	30.4	35.7	40.1	44.6	48.3	52.1	55.4
		.43	2.6	7.4	15.6	27.3	43.8	64.6	90.9	122.3
58.7	90	16.9	25.6	32.3	38.0	42.7	47.4	51.4	55.4	58.9
		.46	2.8	7.9	16.6	29.1	46.6	68.7	96.7	130.2
66.8	80	18.1	27.5	34.6	40.7	45.8	50.9	55.2	59.4	63.2
		.49	3.0	8.5	17.8	31.2	49.9	73.7	103.7	139.6
75.4	70	19.6	30.0	37.5	44.1	49.6	55.1	59.7	64.4	68.4
		.53	3.2	9.2	19.2	33.8	54.1	79.8	112.3	151.2
88.8	60	21.5	32.6	41.1	48.3	54.4	60.4	65.5	70.6	75.1
		.59	3.6	10.1	21.1	37.1	59.3	87.5	123.2	165.8
105.6	50	24.0	36.4	45.8	53.9	60.7	67.4	73.1	78.7	83.7
		.65	4.0	11.2	23.5	41.3	66.2	97.6	137.4	184.9
132.8	40	27.4	41.6	52.5	61.7	69.4	77.1	83.6	90.1	95.8
		.75	4.5	12.8	26.9	47.3	75.7	111.7	157.2	211.6
176	30	32.6	49.5	62.5	73.4	82.6	91.7	99.5	107.2	114.0
		.89	5.4	15.3	32.0	56.3	90.0	132.9	187.1	251.8
212.2	25	36.4	55.3	69.8	82.0	92.2	102.4	111.7	119.7	127.3
		.99	6.0	17.1	35.8	62.9	100.6	148.4	208.9	281.2
264.1	20	41.7	63.3	79.9	93.8	105.6	117.3	127.2	137.0	145.7
		1.14	6.9	19.6	40.9	72.0	115.1	169.9	239.2	321.9
352.8	15	49.3	75.3	95.0	111.7	125.6	139.6	151.3	163.1	173.4
		1.35	8.2	23.3	48.3	85.6	137.0	202.2	284.6	383.1
528	10	63.3	96.0	121.2	142.4	160.2	178.0	192.9	207.9	221.1
		1.73	10.5	29.7	62.1	109.2	174.7	257.8	362.9	488.6

of great practical utility in solving all questions connected with water-pipes and sewers discharging fully-diluted sewage. In using it, interpolate, by inspection, for intermediate diameters or inclinations. For greater diameters, divide those given by 4, and multiply the corresponding velocity found in the table by 2, and the corresponding discharge in the table by 32. If the object be to find the size of the channel, divide greater given velocities by 2, and multiply the diameters or inclinations found from the table by 4; also divide greater discharges by 32, and multiply the diameters found from the table by 4. The small auxiliary table, p. 29, embodied in the larger one, is of great use in making allowance for the velocity and orifice of entry in short pipes, before finding the head due to friction. The table also gives the different diameters and inclinations which, taken together, give the same velocity or discharge; and it enables, from inspection, to select that relation of diameter to declivity which is best suited for other engineering aspects of the question. Taken in connexion with TABLES VIII., XI., XII., and XIII., this table completes the means of finding, by inspection, the dimensions, inclinations, velocities, and discharges of every class of water-channel or sewage-conduit required in engineering practice.

TABLE XIV. gives the comparative values of English and French measures; and TABLE XV. gives the weight, specific gravity, and ultimate strength and elasticity of various materials with which the engineer has to operate.

SECTION II.

FORMULÆ FOR THE VELOCITY, AND DISCHARGE, FROM ORIFICES, WEIRS, AND NOTCHES.—COEFFICIENTS OF VELOCITY, CONTRACTION AND DISCHARGE.—PRACTICAL REMARKS ON THE USE OF THE FORMULÆ.

The quantity of water discharged in a given time through an aperture of a given area in the side or bottom of a vessel, is modified by different circumstances, and varies more or less with the form, position, and depth of the orifice; but the discharge may be easily found, when the velocity and the contraction of the fluid vein has been determined.

VELOCITY.

If g be the velocity acquired by a heavy body falling from a state of rest for one second, *in vacuo*, then it has been shown by writers on mechanics, that the velocity v per second acquired by falling from a height h , will be

$$(1.) \quad v = \sqrt{2gh}.$$

The numerical value of g varies with the latitude; then it shall be assumed that $2g = 772.84$ inches $= 64.403$ feet. These will give for measures in inches,

$$v = 27.8 \sqrt{h},^* \text{ and } h = \frac{v^2}{772.84} = .001293v^2,$$

and for measures in feet,

* The velocities for different heights are given in column number 1, TABLE II.


$$v = 8.025 \sqrt{h}, \text{ and } h = \frac{v^2}{64.403} = .01553 v^2.$$

If v be in feet, and h in inches, then

$$v = 2.817 \sqrt{h}, \text{ and } h = \frac{v^2}{5.367} = .1864 v^2.*$$

COEFFICIENT OF VELOCITY.

Let the vessel A B C D, Fig. 1, be filled with water to the level E F: then it has been found, by experi-



ment, that the velocity of discharge through a small orifice O , in a thin plate, at the distance of half the diameter outside it, in the *vena-contracta*, will be very nearly that due to a heavy body falling freely from the height h , of the surface of the water E F, above the

* The force of gravity increases with the latitude, and decreases with the altitude above the level of the sea, but not to any considerable extent. If λ be the latitude, and h the altitude, in feet, above the mean sea level, then it may be generally taken that

$$g = 32.17 (1 - .0029 \cos 2\lambda) \times \left(1 - \frac{2h}{R}\right),$$

in which R , the radius of the earth at the given latitude is equal to 20887600 $(1 + .0016 \cos 2\lambda)$.

centre of the orifice. The velocity of discharge determined by the equation $v = \sqrt{2gh}$, for falling bodies, is, therefore, called the "*theoretical velocity*." If v_a be now put for the actual mean velocity of discharge in the *vena-contracta*, and c_v for its ratio to the theoretical velocity v , we shall get $v_a = c_v v$; and by substituting for v , its value $\sqrt{2gh}$,

$$(2.) \quad v_a = c_v \sqrt{2gh},$$

c_v is termed "*the coefficient of velocity*;" its numerical value, at about half the diameter from the orifice, is about .974; and, consequently,

$$v_a = .974 \sqrt{2gh}.$$

This for measures in inches becomes

$$v_a = 27.077 \sqrt{h},^*$$

and for measures in feet

$$v_a = 7.816 \sqrt{h}.$$

The orifice *o*, is termed an *horizontal orifice* in Fig. 1,

* The velocities for different heights calculated from this formulæ are given in the column numbered 2, TABLE II. It has been latterly asserted in a *Blue Book* that theoretically $v_a = \frac{2}{3} \sqrt{2gh}$. It is not necessary here to combat this error, which confounds the discharge with its velocity, and a single practical fact, applicable only to a thin plate, with a theoretical principle. The experimental discharge approximates to $\frac{2}{3} \sqrt{2gh}$ multiplied by the area of the orifice; but the theoretical velocity $\sqrt{2gh}$ *always* approximates to the experimental velocity, or $.974 \sqrt{2gh}$, obtained immediately outside the orifice in the *vena-contracta*. It would be unnecessary to allude to this theory here if it were not supported and put forward by three engineers whose authority in practical questions may mislead others. *Vide* p. 4 of "Brief observations of Messrs. Bidder, Hawksley, and Bazalgette on the answers of the *Government Referees* on the METROPOLITAN MAIN DRAINAGE, ordered by the House of Commons to be printed 13th July, 1858."

and in Fig. 2 a *vertical* or *lateral orifice*. When small, each is found to have practically the same velocity of discharge, when the centres of the contracted sections are at the same depth, h , below the surface; but when lateral orifices are large, or rather deep, the velocity at the centre is not, even practically, the mean velocity; and in thick plates and modified forms of adjutage, the mean velocities are found to vary.

VENA-CONTRACTA AND CONTRACTION.

It has been found that the diameter of a column issuing from a circular orifice in a thin plate, is contracted to very nearly eight-tenths of the whole diameter at the distance of the radius from it, and that at this distance the contraction is greatest. The ratio of the diameter of the orifice to that of the contracted vein, *vena-contracta*, is not always found constant by the same or different experimentalists.


Newton makes it	1 :	.841,	{ and, therefore, that of the areas as 1 :	.707
Poleni	„	1 : { .846 .788	„ „	1 : { .7156 .622
Borda	„	1 : .802	„ „	1 : .6432
Michellotti	„	1 : .8	„ „	1 : .64
Bossut	„	1 : { .81 .818	„ „	1 : { .656 .669
Du Buât	„	1 : .816	„ „	1 : .667
Venturi	„	1 : .798	„ „	1 : .637
Eytelwein	„	1 : .8	„ „	1 : .64
Bayer	„	1 : .7854	„ „	1 : .617

Bayer's value for the contraction has been determined on the hypothesis, that the velocities of the particles of water as they approach the orifice from

all sides, are inversely as the squares of their distances from its centre; and the calculations made of the discharge from circular, square, and rectangular orifices, on this hypothesis, coincide pretty closely with experiments.

APPROXIMATE FORM OF THE CONTRACTED VEIN.

Let $OR = d$, Fig. 3, be the diameter of an orifice; then at the distance $Rs = \frac{d}{2}$ the contraction is found to be greatest; assuming that the contracted diameter $or = .7854 d$. Suppose the fluid column between OR and or to be so reduced, that the curve lines Rr and oo shall become arcs of circles, then it is easy to show from the properties of the circle, that the radius cr must be equal to $1.22 d$. The mean velocity in the orifice, OR , is to that in the *vena-contracta*, or , as $.617$:




1; and the mouth piece, $Rroo$, Fig. 4, in which $op = \frac{1}{2} OR$, and $or = .7854 \times OR$, will give for the velocity of discharge at or , the *vena-contracta*,

$$v_d = .974 \sqrt{2gh} = 7.816 \sqrt{h},$$

in feet very nearly.* In speaking of the velocity of

* Correctly the curves Oo and Rr should perhaps have the line OR continued, for their common tangent. No practically useful result would, however, follow from a more accurate construction than is here given. Running a file round the arris O, R , will effect the object better than a complex construction.

discharge from orifices in thin plates, we always



assume it to be the velocity in the *vena-contracta*, and not that in the orifice itself, which varies with the coefficient of discharge, un-

less in TABLE II., where the mean velocity in the latter, as representing $c_d \sqrt{2gh}$, is also given.

COEFFICIENTS OF CONTRACTION AND OF DISCHARGE.

Put A for the area of the orifice $o r$, Fig. 3, and $c_o \times A$ for that of the contracted section at $o r$, then c_o is called the "*coefficient of contraction.*" The velocity of discharge v_a is equal to $c_v \sqrt{2gh}$, equation (2). Multiply this by the area of the contracted section $c_o \times A$, and there is found for the discharge

$$D = c_v \times c_o \times A \sqrt{2gh}.$$

It is evident $A \sqrt{2gh}$ would be the discharge if there were no contraction and no change of velocity due to the height, h ; $c_v \times c_o$ is therefore equal to the coefficient of discharge. Call the latter c_d , and there results the equation

$$(3.) \quad c = c_v \times c_o,$$

and hence the "*coefficient of discharge*" is equal to the product of the coefficients of velocity and contraction.

The expression $c_v c_o \sqrt{2gh} = c_d \sqrt{2gh}$ represents the mean velocity in the orifice; the coefficient for this is, therefore, equal to c_d . The values of the

velocity $c_d \sqrt{2 g h}$, for different heights and coefficients, are given in TABLE II.

In the foregoing expression for the discharge D , h must be so taken, that the velocity at that depth shall be the mean velocity in the orifice A . *In full prismatic tubes the coefficients of velocity and discharge are equal to each other.*

MEAN AND CENTRAL VELOCITY.

In order to find the mean velocity of discharge from an orifice, it is, in the first instance, necessary to determine the velocity due to each point in its surface, and the discharge itself; after which, the mean velocity is found by simply dividing the area of the orifice into the discharge. The velocity due to the height of water at the centre of a circular, square, or rectangular orifice, is not strictly the mean velocity, nor is the latter in these, or other figures, that at the centre of gravity. When, however, an orifice is small in proportion to its depth in the water, the velocity of efflux determined for the centre approaches very closely to the mean velocity; and, indeed, at depths exceeding four times the depth of the orifice, the error in assuming the mean velocity to be that at the centre of the orifice is so small as to be of little or no practical consequence, and for lesser depths it never exceeds six per cent. It is, therefore, for greater simplicity, the practice to determine the velocity from the depth h of the centre of the orifice, unless in weirs or notches; and the coefficients of discharge and velocity in the following pages have been calculated

from experiments on this assumption, unless it shall be otherwise stated.


DISCHARGES THROUGH ORIFICES OF DIFFERENT FORMS
IN THIN PLATES.

The orifices which the engineer has to deal with in practice are square, rectangular, or circular; and sometimes, perhaps, triangular or quadrangular in form. It will be necessary to give here only the theoretical expressions for the discharge and velocity for each kind of form, but as the demonstrations are unsuited to the purposes of this work they shall be omitted.

TRAPEZOIDAL ORIFICES WITH TWO HORIZONTAL SIDES.

Put d for the vertical depth of an orifice, h_t for the altitude of pressure at top, above the upper side, and h_b for the altitude at bottom, above the lower side, then

$$h_b - h_t = d.$$



Let also the top or upper side of the orifice A or C,

Fig. 5, be represented by l_t , and the lower or bottom side by l_b , and put $\frac{l_t + l_b}{2} = l$.

Now, when $l_t = l_b$, the trapezoid becomes a parallelogram whose length is l and depth d ; and putting h for the depth to the centre of gravity, there exists the equation

$$h_t + \frac{d}{2} = h_b - \frac{d}{2} = h.$$

The general expression for the discharge, D , through a trapezoidal orifice, A , is then

$$(4.) \quad D = c_d \sqrt{2g} \times \frac{2}{3} \left\{ l_b h_b^{\frac{3}{2}} - l_t h_t^{\frac{3}{2}} + \frac{2}{5} (l_t - l_b) \frac{h_b^{\frac{5}{2}} - h_t^{\frac{5}{2}}}{d} \right\},$$

in which c_d is the coefficient of discharge; and when the smaller side is uppermost as at C ,

$$(5.) \quad D = c_d \sqrt{2g} \times \frac{2}{3} \left\{ l_b h_b^{\frac{3}{2}} - l_t h_t^{\frac{3}{2}} - \frac{2}{5} (l_b - l_t) \frac{h_b^{\frac{5}{2}} - h_t^{\frac{5}{2}}}{d} \right\}.$$

PARALLELOGRAMIC AND RECTANGULAR ORIFICES.

When $l_t = l_b = l$, the orifice becomes a parallelogram, or a rectangle, B , and then the discharge is

$$(6.) \quad D = c_d \sqrt{2g} \times \frac{2}{3} l \{ h_b^{\frac{3}{2}} - h_t^{\frac{3}{2}} \}.$$

NOTCHES.

When the upper sides of the orifices A , B , and C , rise to the surface as at A_o , B_o , and C_o , h_t becomes nothing, and then, as $h_b = d$, for the trapezoidal notch A_o with the larger side up,

$$(7.) \quad D = c_d \sqrt{2g} \times \frac{2}{3} d^{\frac{3}{2}} \left\{ l_b + \frac{1}{5} (l_t - l_b) \right\} \\ = \frac{2}{15} c_d \sqrt{2g} d^{\frac{3}{2}} (2 l_t + 3 l_b).$$

Also for the trapezoidal notch, c_o , with the smaller side up,

$$(8.) \quad D = c_d \sqrt{2g} \times \frac{2}{3} d^{\frac{5}{3}} \left\{ l_d - \frac{2}{5} (l_b - l_t) \right\} \\ = \frac{2}{15} c_d \sqrt{2g} d^{\frac{5}{3}} (2 l_t + 3 l_b),$$

which is the same in form, but not in value, as the preceding equation. And for a parallelogramic or rectangular notch B_o ,

$$(9.) \quad D = c_d \sqrt{2g} \times \frac{2}{3} l d^{\frac{5}{3}} = \frac{2}{3} c_d l d^{\frac{5}{3}} \sqrt{2g}.$$

It is easy to perceive that the forms of equations (4) and (5), and also of equations (7) and (8), are identical. The values for the discharge in equations (6) and (9) are equally applicable, whether the form of the orifice be a parallelogram or a rectangle, the only difference being in the value of the coefficient of discharge, c_d , which becomes only slightly modified for any form of orifice, and may be taken at .617 when it is in a thin plate for each.

TRIANGULAR ORIFICES WITH HORIZONTAL BASES, AND RECTILINEAL ORIFICES IN GENERAL.

When the length of the lower side, $l_b = 0$, the orifice becomes a triangle, D , Fig. 6, with the base upwards.

In this case, equation (4) becomes


$$(10.) \quad D = c_d \sqrt{2g} \times \frac{2}{3} l_t \left\{ \frac{2}{5} \times \frac{h_b^{\frac{5}{3}} - h_t^{\frac{5}{3}}}{d} - h_t^{\frac{5}{3}} \right\};$$

which gives the discharge through the triangular orifice, D .

When $l_1 = 0$, in equation (5), the orifice becomes a triangle, F , with the base downwards; in this case, the value of the discharge is

$$(11.) \quad D = c_d \sqrt{2g} \times \frac{2}{3} l_b \left\{ h_b^{\frac{3}{2}} - \frac{2}{5} \times \frac{h_b^{\frac{5}{2}} - h_t^{\frac{5}{2}}}{d} \right\}.$$

As any triangular orifice whatever can be divided into two others by a line of division through one of the angles parallel to the horizon; and as the discharge from the triangular orifice D or F is the same as for any other on the same base and between the same parallels, by such a division, the discharge from



any triangle not having one side parallel to the horizon can easily be found, and thence the discharge from any rectilineal figure whatever by dividing it into triangles.

If the triangle F be raised so that the base shall be on the same level with the upper side of the triangular orifice D ; if, also, the bases be equal, and also the depths, by adding equations (10) and (11), and making the necessary changes indicated by the diagram, there is found

$$(12.) \quad D = c_d \sqrt{2g} \times \frac{4}{15} l \{h_b^5 + h_t^5 - 2 \times \overline{h_t + d}\}^{\frac{5}{2}}$$

for the discharge from a parallelogram E with one diagonal horizontal. Now this is the same as the discharge from any quadrilateral figure, whatever, having the same horizontal diagonal, and also having the upper and lower angles on the same parallels, or at the same depths, as those of the parallelogram. If the orifices D, F, and E rise to the surface of the water, as at D_o , E_o , F_o , then for the discharge from the notch D_o there results

$$(13.) \quad D = c_d \sqrt{2g} \times \frac{4}{15} l d^{\frac{5}{2}};$$

which for a right angled triangle becomes

$$D = c_d \sqrt{2g} \times \frac{8}{15} d^{\frac{5}{2}}.*$$

For the discharge from the notch F_o ,

$$(14.) \quad D = c_d \sqrt{2g} \times \frac{6}{15} l_b d^{\frac{3}{2}}:$$

* In the Civil Engineer and Architects' Journal, 1858, p. 370, it is stated that Professor Thomson, now of the University of Glasgow, gave at the British Association in Leeds for a right angled triangle, for discharges of from 2 to 10 cubic feet per minute, the expression $Q = .317 H^{\frac{5}{2}}$, in which Q is the quantity in cubic feet per minute, and H the head in inches. Now the above equation for a coefficient of .617 becomes, for inch measures, $D = 17.153 \times \frac{1}{15} d^{\frac{5}{2}} = 9.15 d^{\frac{5}{2}}$; or by multiplying by 60, and dividing by 1728, to reduce the discharge to feet per minute, $D = .317 d^{\frac{5}{2}}$, identically the same as Professor Thomson derived from his experiments. All sections of a triangular notch are similar triangles, and hence the advantage of a triangular-notch-gauge, where it can be used, as, probably, the coefficient remains constant throughout. Professor Thomson first drew attention to this. But the coefficient .617 gives practically correct results for all forms of orifices in thin plates.

and for the discharge through the notch E_0 ,

$$(15.) D = c_d \sqrt{2g} \times \frac{4l}{15d} \{h_b^{\frac{5}{2}} - 2d^{\frac{5}{2}}\} = c_d \sqrt{2g} \times .9752 l d^{\frac{5}{2}}.$$


When the parallelogram E_0 becomes a square $l = 2d$, and hence,

$$(16.) D = c_d \sqrt{2g} \times .9752 l^{\frac{5}{2}} \times \sqrt{\frac{1}{8}} = c_d \sqrt{2gl} \times .34478 l^{\frac{3}{2}}.$$

The foregoing equations enables the engineer to find an expression for the discharge from any rectilinear orifice whatever; as it can be divided into triangles, the discharge from each of which can be determined as already shown in the remark following equation (11.) The examples which are given will be found to comprehend every form of rectilinear orifice which occurs in practice; but for the greater number of orifices, sunk to any depth below the surface, the discharge will be found with sufficient accuracy by multiplying the area by the velocity due to the centre of gravity.

CIRCULAR AND SEMICIRCULAR ORIFICES.

The discharge through circular and semicircular orifices in thin plates can only be represented by



means of infinite series. Represent by s_1 the sum of the series

$$\left\{ \frac{1}{2} - \left(\frac{1}{2} \cdot \frac{1}{4} \right) \left(\frac{1}{2} \cdot \frac{1}{4} \right) \frac{r^3}{h^2} - \left(\frac{1}{2} \cdot \frac{1}{4} \cdot \frac{3}{6} \cdot \frac{5}{8} \right) \left(\frac{1}{2} \cdot \frac{1}{4} \cdot \frac{3}{6} \right) \frac{r^4}{h^4} - \left(\frac{1}{2} \cdot \frac{1}{4} \cdot \frac{3}{6} \cdot \frac{5}{8} \cdot \frac{7}{10} \cdot \frac{9}{12} \right) \left(\frac{1}{2} \cdot \frac{1}{4} \cdot \frac{3}{6} \cdot \frac{5}{8} \right) \frac{r^5}{h^5} - \&c. \right\} :$$

Also represent by s_2 the sum of the series

$$\frac{2}{3 \cdot 1416} \left\{ \left(\frac{1}{2} \cdot \frac{1}{3} \right) \frac{r}{h} + \left(\frac{1}{2} \cdot \frac{1}{4} \cdot \frac{3}{6} \right) \left(\frac{1}{3} \cdot \frac{2}{5} \right) \frac{r^3}{h^3} + \left(\frac{1}{2} \cdot \frac{1}{4} \cdot \frac{3}{6} \cdot \frac{5}{8} \cdot \frac{7}{10} \right) \left(\frac{1}{3} \cdot \frac{2}{5} \cdot \frac{4}{7} \right) \frac{r^5}{h^5} + \&c. \right\} :$$

then the discharge from the semicircle G, Fig. 7, with the diameter upwards and horizontal, is

$$(17.) \quad D = c_d \sqrt{2gh} \times 3 \cdot 1416 r^3 (s_1 + s_2).$$

And the discharge from the semicircle I, with the diameter downwards and horizontal, is,

$$(18.) \quad D = c_d \sqrt{2gh} \times 3 \cdot 1416 r^3 (s_1 - s_2).$$

If A be put for the area, then also for the discharge from a circle H,

$$(19.) \quad D = c_d \sqrt{2gh} \times 2A s_1.$$

In each of these three equations (17), (18), and (19), h is the depth of the centre of the circumference below the surface, and r the radius.

When the orifices rise to the surface, then for the discharge from a semicircular notch G_0 , with the diameter horizontal and at the surface,

$$(20.) \quad D = c_d \sqrt{2gr} \times \cdot 9586 r^3 = c_d \sqrt{2gr} \times \cdot 6103 A ;$$

when the circumference of the semicircle is at the surface, and the diameter horizontal, as at I_0 ,

$$(21.) \quad D = c_d \sqrt{2gr} \times \frac{4}{15} (\sqrt{128} - 7) r^3 = c_d \sqrt{2gr} \times \cdot 7324 A ;$$

when the horizontal diameter of the semicircle is uppermost, and at the depth r below the surface,

$$(22.) \quad D = c_d \sqrt{2gr} \times 1 \cdot 8667 r^3 = c_d \sqrt{2gr} \times 1 \cdot 1884 A ;$$

and when the circumference of the entire circle is at the surface, as at H_0 ,

$$(23.) \quad D = c_d \sqrt{2 g r} \times 3.0171 r^2 = c_d \sqrt{2 g r} \times .9604 A.$$

If it be desirable to reduce equations (20), (21), and (22), to others in which the depth h of the centre of gravity from the surface is contained, it is only necessary to substitute $\frac{h}{.4244}$ for r in equation (20), and

then the discharge from a semicircle with the diameter at the surface is

$$(24.) \quad D = c_d \sqrt{2 g h} \times .0367 A.$$

Also, by substituting $\frac{h}{.5756}$ for r in equation (21),

the discharge from a semicircle when the circumference is at the surface and the diameter horizontal is

$$(25.) \quad D = c_d \sqrt{2 g h} \times .9653 A;$$

and when the horizontal diameter is uppermost, and at the depth r below the surface $r = \frac{h}{1.4244}$ and

$$(26.) \quad D = c_d \sqrt{2 g h} \times .9957 A.$$

As A stands for the area of the particular orifice in each of the preceding expressions for the discharge, it must be taken of double the value, in equation (23) for instance, where it stands for the area of a circle, that it is in equations (20), (21), or (23), where it represents only the area of a semicircle.

DIFFERENCE OF "MEAN VELOCITIES." HOW MUCH.

The mean velocity is easily found by dividing the area into the discharge per second given in the

preceding equations. For instance, the mean velocity in the example represented in equation (9), is equal $\frac{2}{3} c_d \sqrt{2 g d}$, which is had by dividing the area $l d$ into the discharge; and in like manner the mean velocity in equation (23) is $\cdot 9604 c_d \sqrt{2 g r}$. The velocity at the centre of an orifice is that generally taken by practical men. This differs very little from the other five circular and rectangular forms. Even for notches at the surface it is only in excess by from four to six per cent.

PRACTICAL REMARKS ON THE DISCHARGE FROM CIRCULAR ORIFICES.

It has been shown, equation (19), that, for the discharge from a circle, we have

$$D = c_d \sqrt{2 g h} \times 2 A s_1,$$

in which h is the depth of the centre, A the area, and s_1 the sum of the series

$$\left\{ \frac{1}{2} - \left(\frac{1}{2} \cdot \frac{1}{4} \right) \left(\frac{1}{2} \cdot \frac{1}{4} \right) \frac{r^2}{h^2} - \left(\frac{1}{2} \cdot \frac{1}{4} \cdot \frac{3}{6} \cdot \frac{5}{8} \right) \left(\frac{1}{2} \cdot \frac{1}{4} \cdot \frac{3}{6} \right) \frac{r^4}{h^4} - \&c. \right\} :$$

and it has also been shown, equation (23), that, when the circumference touches the surface, this value becomes

$$D = c_d \sqrt{2 g r} \times \cdot 9604 A.$$

Now when h is very large compared with r , it is easy to perceive that $2 s_1 = 1$, and hence

$$(27.) \quad D = c_d \sqrt{2 g h} \times A.$$

As this is the formula commonly used for finding the discharge, it is clear, if the coefficient c_d remain constant, that the result obtained from it for D would be

too large. The differences, however, for depths greater than three times the diameter, or $6r$, are practically of no importance; for, by calculating the values of the discharge at different depths, it is found, when

$$(28.) \left\{ \begin{array}{l} h = r, \text{ that } D = c_d \sqrt{2gh} \times .960 A; \\ h = \frac{5r}{4}, \text{ ,, } D = c_d \sqrt{2gh} \times .978 A; \\ h = \frac{3r}{2}, \text{ ,, } D = c_d \sqrt{2gh} \times .985 A; \\ h = \frac{7r}{4}, \text{ ,, } D = c_d \sqrt{2gh} \times .989 A; \\ h = 2r, \text{ ,, } D = c_d \sqrt{2gh} \times .992 A; \\ h = 3r, \text{ ,, } D = c_d \sqrt{2gh} \times .996 A; \\ h = 4r, \text{ ,, } D = c_d \sqrt{2gh} \times .998 A; \\ h = 5r, \text{ ,, } D = c_d \sqrt{2gh} \times .9987 A; \\ h = 6r, \text{ ,, } D = c_d \sqrt{2gh} \times .9991 A. \end{array} \right.$$

These results show very clearly that, for circular orifices, the common expression for the discharge $c_d \sqrt{2gh} \times A$ is abundantly correct for all depths exceeding three times the diameter, and that for lesser depths the extreme error cannot exceed four per cent. in reduction of the quantity found by this formula. Hereafter, when discussing the value of c_d , it will be shown that from the sinking of the surface, and perhaps other causes, the discharge at lesser depths is even larger than that exhibited by the expression $c_d \sqrt{2gh} \times A$, the value of the coefficient of discharge, c_d , being found to increase near the surface as the depths h decrease. In fact, *the sides and length of the orifice, the*

rounding of the arrises, and the depth and position with reference to the sides of the vessel, and surface of the water, are of far greater practical importance than extreme accuracy in the mathematical formulæ, which when complex may be of little or no practical value.

PRACTICAL REMARKS ON THE DISCHARGE FROM
RECTANGULAR ORIFICES.

It has been shown, equation (6), that the discharge from rectangular orifices, with two sides parallel to the horizon or surface of the water, is expressed by the equation

$$D = c_d \times \frac{2}{3} \sqrt{2g} \times l \{ h_b^{\frac{3}{2}} - h_t^{\frac{3}{2}} \},$$

in which l is the horizontal length of the orifice, h_b the depth of water on the lower, and h_t the depth on the upper, side. As it is desirable in practice to change this form into a more simple one, in which the height h of the centre and depth d of the orifice only shall be

included, then $h_b = h + \frac{d}{2}$ and $h_t = h - \frac{d}{2}$. By sub-

stituting these values of h_b and h_t in the foregoing equations, and developing the result into a series, the terms of which, after the third, may be neglected, and putting A for the area $l d$, there results

$$(29.) \quad D = c_d \sqrt{2g h} \times A \left\{ 1 - \frac{d^3}{96 h^3} \right\} \text{ very nearly.}$$

Therefore for the accurate theoretical discharge

$$30.) \quad D = c_d \sqrt{2g h} \times \frac{2}{3} A \left\{ \frac{(h + \frac{1}{2}d)^{\frac{3}{2}} - (h - \frac{1}{2}d)^{\frac{3}{2}}}{d h^{\frac{1}{2}}} \right\};$$

for the approximate discharge

$$D = c_d \sqrt{2gh} \times A \left\{ 1 - \frac{d^3}{96h^3} \right\};$$

and for the discharge by the common formula

$$D = c_d \sqrt{2gh} \times A.$$

When the head (h) is large compared with (d), the height of the orifice, each of the three last equations gives the same value for the discharge; but as the common expression $c_d \sqrt{2gh} \times A$ is the most simple; and as the greatest possible error in using it for lesser depths does not exceed six per cent., viz. when the orifice rises to the surface and becomes a notch, it is evidently that formula best suited for practical purposes. The following table and equations will show more clearly the differences in the results as obtained from *the true, the approximate, and the common formulæ*, applied to "lesser" heads; and they will also explain, to some extent, why "coefficients" determined from the common formula, and that used by Poncelet and Lesbros, should decrease as the orifice approaches the surface.

	1	2	3
$h = \frac{d}{2},$	$D = c_d \sqrt{2gh} \times .9428A.$	$D = c_d \sqrt{2gh} \times .9588A.$	
$h = \frac{5d}{8},$	" "	" $\times .9693A.$	" " " $\times .9733A.$
$h = \frac{3d}{4},$	" "	" $\times .9796A.$	" " " $\times .9815A.$
$h = \frac{7d}{8},$	" "	" $\times .9854A.$	" " " $\times .9864A.$
(31.) $h = d$	" "	" $\times .9890A.$	" " " $\times .9896A.$

■

(31.)

$h = \frac{3d}{2}$	$D = c_d \sqrt{2gh} \times .9953A.$	$D = c_d \sqrt{2gh} \times .9954A.$
$h = 2d$,, ,, ,, $\times .9974A.$,, ,, ,, $\times .9974A.$
$h = \frac{5d}{2}$,, ,, ,, $\times .9988A.$,, ,, ,, $\times .9988A.$
$h = 3d$,, ,, ,, $\times .9988A.$,, ,, ,, $\times .9988A.$
$h = \frac{7d}{2}$,, ,, ,, $\times .9991A.$,, ,, ,, $\times .9991A.$
$h = 4d$,, ,, ,, $\times .9994A.$,, ,, ,, $\times .9994A.$
$h \times 10d$,, ,, ,, $\times .9999A.$,, ,, ,, $\times .9999A.$

In the foregoing Table the first column contains the head at the centre of the orifice expressed in parts of its height d ; the second contains the values of the discharges according to equation (30); and the third column contains the approximate values determined from equation (29), the results in which are something larger than those in column 2, derived from the correct formula. The numerical coefficients of A , at every depth, are less in both than unity, the constant coefficient according to the common formula. This latter, therefore (as in circular orifices), gives results exceeding the true ones, but the excess is inappreciable at greater depths than $h = 3d$, and for lesser depths than this the error cannot exceed six per cent. It may be useful to remark here, that when the orifice rises to the surface and becomes a notch, the "*centre of mean velocity*" is at *four-ninths of the depth*, and the *centre of gravity* at *two-thirds of the depth from the surface*. The former fraction is the square of the latter.

SECTION III.

EXPERIMENTAL RESULTS AND FORMULÆ.—COEFFICIENTS
OF DISCHARGE FOR ORIFICES AND NOTCHES.

HERETOFORE the numerical values of the general coefficient of discharge c_d have been only dwelt upon partially. In order to determine its value under different circumstances more particularly, it will be now necessary to consider some of the experiments which have been made from time to time. These do not always give the same results, even when conducted under the same circumstances and by the same parties, and there appears to exist a certain amount of error, more or less, inseparable from the subject. The experiments with orifices in thin plates afford the most consistent results; but even here the differences are sometimes greater than might be expected. In many of the earlier experiments the value of the coefficient c_d comes out too large, which arises, very probably, from the orifices experimented with not being in thin plates, and partaking, more or less, of the nature of short tubes or mouth-pieces with rounded arrises, which, as it shall be seen, give larger coefficients than simple orifices. When an orifice is in the bottom of a vessel, it would appear more correct to measure the head from the surface to the *vena-contracta* than from the surface to the orifice itself; and as any error in measuring the head in any experiment must affect the value of the coefficient derived

from such experiment, so as to increase it when the error is to make the head less, and *vice versa*, it appears that heads measured to an orifice in the bottom of a vessel, and not to the *vena-contracta*, must give larger coefficients from the experimental results than, perhaps, the true ones. The coefficients in the following pages have been almost all arranged and calculated, by the author, from the original experiments.

In 1739 Dr. Bryan Robinson made some experiments on the discharge through small circular orifices, from one-tenth to eight-tenths of an inch in diameter, with heads of two and four feet,* which give the following coefficients.

COEFFICIENTS FROM DR. B. ROBINSON'S EXPERIMENTS.

Heads.	$\frac{1}{10}$ inch diameter.	$\frac{2}{10}$ inch diameter.	$\frac{3}{10}$ inch diameter.	$\frac{4}{10}$ inch diameter.
2 feet head	·768	·767	·761	·728
4 feet head	·768	·774	·765	·742

These results are pretty uniform, and the values from which they are derived are said to be "means taken from five or six experiments;" as values of c_d they are, however, too high. The apparatus made use of is not described; but it is probable, from the results, that the plate containing the hole or orifice was of some thickness, and that the inner arris was slightly rounded. There is here, however, a very perceptible increase in the coefficients for the smaller orifices, but none for the smaller depth.

* Helsham's Lectures, p. 390. Dublin, 1739.

In a paper in the Transactions of the Royal Irish Academy, vol. ii. p. 81, read March 1st, 1788, Dr. Matthew Young determines the value of the coefficient for an orifice $\frac{3}{16}$ inch in diameter, with a mean head of 14 inches, to be $\cdot 628$. The manner in which this value is determined is very elegant; viz., by comparing the observed with the theoretical time of the water, in the vessel, sinking from 16 inches to 12 inches.

The following experiments by Michelotti, with circular orifices from 1 to about 8 inches diameter, and with from 6 to 23 feet heads, give for the mean value $c_d = \cdot 613$; and for square orifices of from 1 to 9 square inches in area, at like depths, the mean value of $c_d = \cdot 628$. The experiments are given in French feet and inches, according to which standard in feet, $D = 7.77 \sqrt{h} \times t$; t being the time in seconds.* As the time of discharge in these experiments varies from ten minutes to an hour, and as the depths are considerable, the results must be looked upon as pretty accurate; and it is worthy of

* The value of $\sqrt{2gh}$, equation (1), for measures in French feet, is $7.77 \sqrt{h}$, and for measures in French inches, $26.9 \sqrt{h}$; g being equal to 30.2 feet, or 362.4 inches, French measure. One French foot is equal to 1.06578 English feet, and the inches preserve the same proportion. The resulting coefficients must be the same, whatever standards the calculations are made from. Many of the most valuable formulæ and experiments in hydraulics are given in French measures of the old style. As the object, however, in the present section, is to determine from experiment the relation of the experimental to the theoretical discharge, it is not necessary to reduce the experiments to other measures than those in the original; but the value of the force of gravity, g , must, of course, be taken in those measures with which the experiments were made. In the French decimal, or modern style, the

COEFFICIENTS FROM MICHELOTTI'S EXPERIMENTS.

Description and size of orifice, in French inches.	Depth of the centre of the orifices in French feet.	Quantity discharged in cubic feet.	Time of discharge in seconds.	Theoretical time, calculated from $t = \frac{7.77 \Delta \sqrt{\Delta}}{p}$	Resulting coefficients of discharge.
Square orifice, 3" x 3"	6.613	463.604	600	371.3	.619
	6.852	566.458	720	445.6	.619
	11.676	516.785	510	311.4	.610
	11.818	612.118	600	366.6	.611
	21.691	415.437	300	183.7	.612
	21.715	499.222	360	220.6	.613
Mean value of the coefficient ; square orifice 3" x 3"614
Square orifice, 2" x 2"	6.625	329.806	900	594.	.660
	11.426	423.465	900	580.4	.645
	21.442	385.333	600	365.7	.643
Mean value of the coefficient ; square orifice 2" x 2"649
Square orifice, 1" x 1"	6.757	153.549	1800	1585.	.628
	11.889	163.792	1440	880.6	.612
	21.507	562.944	3600	2249.9	.625
Mean value of the coefficient ; square orifice 1" x 1"621
Circular orifice, 3" diameter	6.694	542.85	900	550.1	.611
	11.590	570.972	720	439.6	.610
	21.611	521.299	480	293.8	.612
Mean value of the coefficient ; circular orifice 3" diameter . .					.611
Circular orifice, 2" diameter	6.785	488.687	1800	1108.1	.616
	11.722	589.535	1680	1016.4	.605
	21.903	575.486	1200	725.9	.605
Mean value of the coefficient ; circular orifice 3" diameter . .					.609
Circular orifice, 1" diameter	6.875	247.354	3600	2227.	.619
	11.722	324.11	3600	2233.	.620
	21.903	444.535	3600	2237.2	.621
Mean value of the coefficient ; circular orifice 1" diameter . .					.620

note that here the coefficients are larger for square than for circular orifices.

It may be remarked here in passing how universal the coefficients $\cdot 613$ to $\cdot 628$ are for all forms of orifices in thin plates; or with the outside arrises chamfered. Indeed, the coefficient $\cdot 62$ may always be used with certainty, for practical purposes, for every orifice of this kind, whether at the surface in the form of a notch, or at the sides or bottom of a vessel, if the section of the approaching water be large in proportion to the area of the discharging orifice or notch. By coefficient of course is here meant that decimal which, multiplied by the theoretical value, gives the practical result; and this is substantially the same for notches and orifices sunk below the surface, as will appear further on. There appears, however, an utter want of accuracy in using the coefficient $\cdot 62$ or thereabouts in gauging for all orifices, weirs included, no matter what the thickness or form of the orifice or crest of a weir may be, or area of the approaching channel. These will cause the coefficient to vary from $\cdot 5$ to 1 or more, and hence the necessity for endeavouring to reduce this portion of the subject to rule.

The experiments made by the Abbé Bossut, contained in the following table, give the mean value of c_d for both circular and square orifices, equal to $\cdot 616$

metre is equal to 3.2809 English feet, or 39.371 inches. The tenth part of a metre is the decimetre, and the tenth part of the decimetre the centimetre, as the names imply. TABLE XIV. contains the weights and measures in general use in Great Britain and France, with their general ratios to each other.

nearly; and it may be perceived that, for the small depth in the last experiment, the coefficient rises so high as .649. These and other experiments led the Abbé to construct a table of the discharges, at different

COEFFICIENTS FROM BOSSUT'S EXPERIMENTS.

Description, position, and size of orifice, in French inches.	Depth of the centre of the orifice in French inches.	Number of French cubical inches discharged per minute.	Theoretical discharge per minute. $D = 1614 \sqrt{H}$	Resulting coefficients.
Horizontal and circular, $\frac{1}{2}$ " diameter	140.832	2311	3760.8	.614
Horizontal and circular, 1" diameter	140.832	9281	15043.3	.617
Horizontal and circular, 2" diameter	140.832	37203	60173.1	.618
Horizontal and rectangular, $1" \times \frac{1}{2}"$	140.832	2933	4788.4	.613
Horizontal and square, $1" \times 1"$	140.832	11817	19153.7	.617
Horizontal and square, $2" \times 2"$	140.832	47361	76614.6	.617
Lateral and circular, $\frac{1}{2}$ " diameter	108.	2018	3293.3	.613
Lateral and circular, 1" diameter	108.	8135	13173.3	.617
Lateral and circular, $\frac{1}{2}$ " diameter	48.	1353	2195.5	.616
Lateral and circular, 1" diameter	48.	5436	8782.2	.616
Lateral and circular, 1" diameter	0.5833	628	968.	.649

depths, from a circular orifice 1 inch in diameter, from which the author has determined the following table of coefficients. These increase, as the orifice approaches the surface, from .617 to .621; and at lesser depths

COEFFICIENTS DEDUCED FROM BOSSUT'S EXPERIMENTS.

Heads, in feet.	Coefficients.	Heads, in feet.	Coefficients.	Heads, in feet.	Coefficients.
1	.621	6	.620	11	.619
2	.621	7	.620	12	.618
3	.621	8	.619	13	.618
4	.620	9	.619	14	.618
5	.620	10	.619	15	.617

than 1 foot other experiments show an increase in the coefficient up to $\cdot 650$. The experiments of Poncelet and Lebros show, however, a reduction in the coefficients for square orifices $8'' \times 8''$ as they approach the surface from $\cdot 601$ to $\cdot 572$.

Brindley and Smeaton's experiments, with an orifice 1 inch square placed at different depths, give a mean

COEFFICIENTS CALCULATED FROM BRINDLEY AND SMEATON'S
EXPERIMENTS.

1 foot head : orifice $1'' \times 1''$: coefficient $\cdot 639$	} mean $\cdot 637$.
2 feet head : orifice $1'' \times 1''$: coefficient $\cdot 635$	
3 feet head : orifice $1'' \times 1''$: coefficient $\cdot 648$	
4 feet head : orifice $1'' \times 1''$: coefficient $\cdot 632$	
5 feet head : orifice $1'' \times 1''$: coefficient $\cdot 632$	
6 feet head : orifice $\frac{1}{2}'' \times \frac{1}{2}''$: coefficient $\cdot 557$	

value for c_d of $\cdot 637$. The last experiment, with an orifice only $\frac{1}{2}$ inch by $\frac{1}{2}$ inch, gives so small a coefficient as $\cdot 557$ placed at a depth of 6 feet !

For notches 6 inches wide and from 1 to $6\frac{1}{2}$ inches deep, Brindley and Smeaton's experiments give the mean value of $c_d = \cdot 637$. The coefficients of discharge

COEFFICIENTS FOR NOTCHES, CALCULATED FROM BRINDLEY AND
SMEATON'S EXPERIMENTS.

Ratio of the length to the depth.	Size of notches in inches.	Coefficients.	Ratio of the length to the depth.	Size of notches in inches.	Coefficients.
$\cdot 92$ to 1	$6 \times 6\frac{1}{2}$	$\cdot 638$	$3\cdot 7$ to 1	$6 \times 1\frac{1}{2}$	$\cdot 638$
$1\cdot 07$ to 1	$6 \times 5\frac{1}{2}$	$\cdot 571$	$4\cdot 4$ to 1	$6 \times 1\frac{1}{2}$	$\cdot 654$
$1\cdot 2$ to 1	6×5	$\cdot 609$	$4\cdot 8$ to 1	$6 \times 1\frac{1}{4}$	$\cdot 681$
$1\cdot 92$ to 1	$6 \times 3\frac{1}{2}$	$\cdot 602$	$6\cdot$ to 1	6×1	$\cdot 713$
$2\cdot 4$ to 1	$6 \times 2\frac{1}{2}$ *	$\cdot 636$	Mean value.		$\cdot 637$

* The depth is misprinted $2\frac{5}{10}$ inches in the Encyclopædias, the resulting coefficient for which would be $\cdot 568$ instead of $\cdot 636$ as above, for a depth of $2\frac{1}{2}$ inches.

for notches and orifices appear to differ as little from each other as those for either do in themselves. The results also show a general though not uniform increase in the coefficients for smaller depths.

Du Buât's experiments with notches 18·4 inches long, give the mean value of $c_d = \cdot 682$, which differs very little from the mean value determined from Brindley and Smeaton's experiments.

COEFFICIENTS FOR NOTCHES, CALCULATED FROM DU BUAT'S EXPERIMENTS.

Ratio of the length to the depth.	Size of notches in inches.	Coefficients.	Ratio of the length to the depth.	Size of notches in inches.	Coefficients.
2·72 to 1	18·4 × 6·753	·630	5·75 to 1	18·4 × 3·199	·624
3·94 to 1	18·4 × 4·665	·627	10·3 to 1	18·4 × 1·778	·646

Poncelet and Lesbros' experiments give the coefficients in the following table, for notches 8 inches

COEFFICIENTS FOR NOTCHES, BY PONCELET AND LESBROS.

Ratio of the length to the depth.	Size of notches in inches.	Coefficients.	Ratio of the length to the depth.	Size of notches in inches.	Coefficients.
·9 to 1	8 × 9	·577	3·33 to 1	8 × 2·4	·601
1 to 1	8 × 8	·585	5 to 1	8 × 1·6	·611
1·3 to 1	8 × 6	·590	6·7 to 1	8 × 1·2	·618
2 to 1	8 × 4	·592	10 to 1	8 × 0·8	·625
2·5 to 1	8 × 3·2	·595	20 to 1	8 × 0·4	·636

wide; the mean value of all the coefficients in these experiments is ·603. Here the coefficients increase in every instance as the depths decrease, or as the ratio of the length of the notch to its depth increases. It will be necessary to refer to the valuable experi-

ments made at Metz, on the discharge from differently-proportioned orifices immediately.

Rennie's experiments for circular orifices at depths from 1 foot to 4 feet, and of diameters from $\frac{1}{4}$ inch to 1 inch give the following coefficients. Here the

COEFFICIENTS FOR CIRCULAR ORIFICES, FROM RENNIE'S
EXPERIMENTS.

Heads at the centre of each orifice in feet.	$\frac{1}{4}$ inch diameter.	$\frac{1}{2}$ inch diameter.	$\frac{3}{4}$ inch diameter.	1 inch diameter.	Mean values.
1	·671	·634	·644	·633	·645
2	·653	·621	·652	·619	·636
3	·660	·636	·632	·628	·639
4	·662	·626	·614	·584	·621
Means	·661	·629	·635	·616	·635

increase for the coefficients for lesser orifices and at lesser depths exhibits itself very clearly, notwithstanding a few instances to the contrary. The mean value of the coefficient c_d derived from the whole, is ·635. For small rectilineal orifices the coefficients were as follows:—

COEFFICIENTS FOR RECTANGULAR ORIFICES, FROM RENNIE'S
EXPERIMENTS.

Heads at the centre of gravity, in feet.	Square orifice, 1 inch \times 1 inch.	Rectangular orifice, longer side horizontal, $\frac{3}{4}$ " \times $\frac{1}{4}$ ".	Rectangular orifice, longer side horizontal, $1\frac{1}{2}$ " \times $\frac{1}{4}$ ".	Equilateral triangle of 1 square inch, with base down.	Equilateral triangle of 1 square inch, with base up.
1	·617	·617	·663	„	·596
2	·634	·635	·668	„	·577
3	·606	·606	·606	„	·572
4	·593	·593	·593	·593	·593
Means	·613	·613	·632	·593	·585

The most valuable series of experiments are those made at Metz, by Poncelet and Lesbros. They were made with orifices eight inches wide, nearly, and of different vertical dimensions placed at various depths down to 10 feet. The discrepancies as to any general law in the relation of the different values of the coefficient of discharge c_d to the size and depth of the orifice in the preceding experiments, have been remedied to a great extent by these. They give an increase of the coefficients for the smaller and very oblong orifices as they approach the surface, and a decrease under the same circumstances in those for the larger square and oblong orifices. There are a few depths where maximum and minimum values are obtained: the terms "maximum and minimum values" are used for those which are greater in the one case and less in the other than the coefficients immediately before and after them; and not as being numerically the greatest or least values in the column. These maximum and minimum values are marked with a *, in the arrangement of these coefficients, TABLE I. The heads given in this table were measured to the upper side of the orifices, and by adding half the depth of the orifice to any particular head, the head at the centre will be obtained.

As a perceptible sinking of the surface takes place for heads less than from five to three times the depth of the orifice, the coefficients are arranged in pairs, the first column containing the coefficients for heads measured from the still water surface some distance back from the orifice, and the second obtained when the lesser heads, measured directly at the orifice, were

used. A very considerable increase in the value of the coefficients for very oblong and shallow small orifices, may be perceived as they approach the surface, and the mean value for all rectilinear orifices at considerable depths, seems to approach to $\cdot 605$ or $\cdot 606$.

It is shown, equation (29), that the discharge is

$$D = c_d \times \left\{ 1 - \frac{d^3}{96 h^3} \right\} \times A \sqrt{2 g h},$$

approximately, in which expression d is the depth of the orifice, and h the head at its centre. Now it is to be observed, that it is not the value of c_d simply, which is given in TABLE I., but the value of $c_d \times \left\{ 1 - \frac{d^3}{96 h^3} \right\}$, the coefficient of $A \sqrt{2 g h}$, equation (29). The coefficients in the table are, therefore, less than the coefficients of discharge, strictly so called, by a quantity equal to $\frac{c_d d^3}{96 h^3}$. The value of this ex-


pression is in general very small, and it is easy to perceive from the first of the expressions in equation (31), pp. 49 & 50, that it can never exceed 4·2 per cent., or more correctly $\cdot 0417$ in unity. If it be required to know the discharge from an orifice 4 inches square = $4'' \times 4''$, with its entire 4 feet below the surface, — which is equivalent to a head of 3 feet 10 inches at the upper side. From the table the value of

$c_d \left\{ 1 - \frac{d}{96 h^2} \right\}$ is $\cdot 601$; hence

$$D = \cdot 601 \times A \sqrt{2 g h} = \cdot 601 \times \frac{1}{9} \times 8 \cdot 025 \times 2 =$$

$$\cdot 601 \times \frac{1}{9} \times 16 \cdot 05 = \frac{1}{9} \times 9 \cdot 646 = 1 \cdot 072$$

cubic feet per second. In the absence of any experiments with larger orifices, when they occur, it is best to use the coefficients given in this table; and, in order to do so with judgment, it is only necessary to observe the relations of the sides and heads. For example, if the side of an orifice be $16'' \times 4''$, then seek for the coefficient in that column where the ratio of sides is as four to one, and if the head at the upper side be five times the length of the orifice, the coefficient .626 will be found, which in this case is the same for depths measured behind, or at the orifice. For lesser orifices, the results obtained from the experiments of *Michelotti* and *Bossut*, pages 54 and 56, are most applicable; and also the coefficients of *Rennie*, p. 59. It is almost needless to observe, that all these coefficients are only applicable to orifices



in thin plates, or those having the outside arrises chamfered as in Fig. 8. Very little dependence can be placed on calculations of the quantities of water dis-

charged from other orifices, unless where the coefficients have been already obtained by experiment or correct inference for them. If the inner arris next the water be rounded, the coefficient will be increased.

NOTCHES AND WEIRS.

Some coefficients have been already given at pages

57 and 58, derived from experiments of Du Buât, Brindley and Smeaton, and Poncelet and Lesbros, for finding the discharge over notches in the sides of large vessels; and it does not appear that there is any difference of importance between these and those for orifices sunk some depth below the surface, when the proper formula for finding the discharge for each is used. If Poncelet and Lesbros' coefficients for notches, page 58, be compared with those for an orifice at the surface, TABLE I., there is little practical difference in the results, the head being measured back from the orifice, unless in the very shallow depths, and where the ratio of the length to the depth exceeds five to one. The depths being in these examples less than an inch, it is probable that the larger coefficients found for the *orifice* at the surface, arise from the upper edge attracting the fluid to it and lessening the effects of vertical contraction, as well as from less lateral contraction. Indeed, the results obtained from experiments with very shallow weirs, or notches, have not been at all uniform, and at small depths the discharge must proportionably be more affected by movements of the air, surface adhesion, and external circumstances than when the depths are considerable. It will be seen that in Mr. Blackwell's experiments the coefficient obtained for depths of 1 and 2 inches was $\cdot 676$ for a thin plate 3 feet long, while for a thin plate 10 feet long, it increased up to $\cdot 805$.

The experiments of Castel, with weirs up to about 30 inches long, and with variable heads of from 1 to 8 inches, lead to the coefficient $\cdot 497$ for notches

extending over one-fourth of the side of a reservoir; and to the coefficient $\cdot 664$ when they extend for the whole width. For lesser widths than one-fourth, the coefficients decrease down to $\cdot 584$; and for those extending between one-third of, and the whole width, they increase from $\cdot 600$ to $\cdot 665$ and $\cdot 680$. Bidone found $c_d = \cdot 620$, and Eytelwein $c_d = \cdot 635$. It will be perceived from these and the foregoing results, that the third place of decimals in the value of c_d , and even sometimes the second, is very uncertain; that the coefficient varies with the head and ratio of the notch to the side in which it is placed; and it will soon be shown that the form and size of the weir, weir-basin, and approaches, still further modify its value.

When the sides and edge of a notch increase in thickness, or are extended into a shoot, the coefficients are found to reduce very considerably; and for small heads, to an extent beyond what the increase of resistance, from friction alone, indicates. Poncelet and Lesbros found, *for orifices*, that the addition of a horizontal shoot, 21 inches long, reduced the coefficient from $\cdot 604$ to $\cdot 601$, with a head of 4 feet; but for a head of only $4\frac{1}{2}$ inches, the coefficient fell from $\cdot 572$ to $\cdot 483$, the orifice being $8'' \times 8''$. For *notches* 8 inches wide, with a horizontal shoot 9 feet 10 inches long, the coefficient fell from $\cdot 582$ to $\cdot 479$, for a head of 8 inches; and from $\cdot 622$ to $\cdot 340$, for a head of only 1 inch. Castel found also, for a notch 8 inches wide with a shoot 8 inches long attached and inclined at an angle $4^\circ 18'$, that the mean coefficient for heads from 2 to $4\frac{1}{2}$ inches was only $\cdot 527$. Little dependence can,

therefore, be placed on experimental results obtained for shoots which partake of the nature of short pipes, and should be treated in like manner to find the discharge.*

The author has calculated the following table of coefficients from some experiments made by Mr. Bal-

COEFFICIENTS FOR SHORT WEIRS OVER BOARDS.

Heads measured on the crest.

Depths in inches.	Coefficients.	Depths in inches.	Coefficients.	Depths in inches.	Coefficients.
1	·762	3	·801	5	·733
1½	·662	3½	·765	5½	·713
1¾	·673	3¾	·748	5¾	·735
1¾	·692	3¾	·740	5¾	·729
2	·684	4	·759	6	·727
2½	·702	4½	·731	7	·716
2¾	·756	4¾	·744	8	·726
2¾	·786	4¾	·745	Mean	·732

lard, on the river Severn, near Worcester, “with a weir 2 feet long, formed by a board standing perpendicularly across a trough.”† *The heads or depths were here measured on the weir*, and hence the coefficients are larger than those found from heads measured back to the surface of still water.

Experiments made at Chew-Magna, in Somersetshire, by Messrs. Blackwell and Simpson, in 1850,‡ give the following coefficients.

“The overfall bar was a cast-iron plate 2 inches thick, with a square top.” The length of the over-

* *Traité Hydraulique*, par D'Aubuisson, pp. 46, 94 et 95.

† *Civil Engineer and Architect's Journal* for 1851, p. 647.


‡ *Civil Engineer and Architect's Journal* for 1851, pp. 642 and 645.

COEFFICIENTS DERIVED FROM THE EXPERIMENTS OF BLACKWELL
AND SIMPSON.

Heads in inches.	Coefficients.	Heads in inches.	Coefficients.	Heads in inches.	Coefficients.
1 to $\frac{3}{4}$	·591	$4\frac{1}{2}$	·743	6	·749
1 to $1\frac{1}{10}$	·626	$4\frac{5}{10}$	·760	$6\frac{3}{10}$	·748
$2\frac{1}{10}$ to $2\frac{1}{4}$	·682	$4\frac{7}{10}$	·741	$6\frac{7}{10}$ to $6\frac{1}{2}$	·747
$2\frac{3}{4}$	·665	$4\frac{9}{10}$	·750	$6\frac{9}{10}$	·772
$2\frac{8}{10}$	·670	$4\frac{11}{10}$	·725	$7\frac{1}{10}$	·717
$2\frac{9}{10}$	·665	5	·780	8	·802
$2\frac{11}{10}$	·653	$5\frac{1}{10}$	·781	8 to $8\frac{1}{10}$	·737
$2\frac{12}{10}$	·654	$5\frac{2}{10}$	·749	$8\frac{2}{10}$	·750
3 to $3\frac{1}{10}$	·725	$5\frac{3}{10}$ to $5\frac{4}{10}$	·751	9	·781
4	·745	$5\frac{5}{10}$	·728	Mean	·723

fall was 10 feet. The heads were measured from still water at the side of the reservoir, and at some distance up in it. The area of the reservoir was 21 statute perches, of an irregular figure, and nearly 4 feet deep on an average. It was supplied from an upper reservoir, by a pipe 2 feet in diameter and of 19 feet fall; the distance between the supply and the weir was about 100 feet. The width of the reservoir as it approached the overfall was about 50 feet, and the plan and section, Fig. 9, of the weir and overfall in connection with it, will give a fair idea of the circumstances attending the experiments. For heads over 5 inches the velocity of approach to the weir was "perceptible to the eye," though its amount was not determined. It will be perceived that the coefficient (derived from two experiments) for a depth of 8 inches is ·802, while the coefficient (derived from three experiments) for a depth of $7\frac{3}{10}$ inches is ·717, and for depths from 8 to $8\frac{1}{10}$ inches the mean coefficient is ·748: as all the attendant circumstances appear the

same, these discrepancies and others must arise from some undescribed circumstances of the case: perhaps the supply, and, consequently, the velocity of approach, was increased while making one set of experiments, without affecting the still water near the side where the heads appear to have been taken. By comparing the results with those obtained by one of the same experimenters, Mr. Blackwell, on the Kennet and



Avon Canal, we shall immediately perceive that the velocity of approach, and every circumstance which tends to alter and modify it, has a very important effect on the amount of the discharge, and, consequently, on the coefficient.

The experiments made by Mr. Blackwell, on the Kennet and Avon Canal, in 1850,* afford very valuable instruction, as the form and width of the crest were

* Civil Engineer and Architect's Journal, 1851, p. 642.

COEFFICIENTS FOR THE DISCHARGE OVER WEIRS, ARRANGED AND DERIVED FROM THE EXPERIMENTS OF
MR. BLACKWELL.


*When more than one experiment was made with the same head, and the results were pretty uniform, the resulting coefficients are marked with a *. The effect of the converging wing-boards is very strongly marked.*

NOTE.—Francis' experiments give a coefficient of '565 for a level crest 3 feet wide, and a head slope of $3\frac{1}{4}$ to 1, see p. 125.

Heads in inches, measured from still water in the reservoir.	Thin plates.		Planks 2 inches thick, square on crest.				Crests 3 feet wide.					
	3 feet long.	10 feet long.	3 feet long.	6 feet long.	10 feet long.	10 feet long, wing-boards making an angle of 60°.	3 feet long, level.	3 feet long, fall 1 in 18.	3 feet long, fall 1 in 12.	6 feet long, level.	10 feet long, level.	10 feet long, fall 1 in 18.
1	'677	'809	'467	'459	'435†	'754	'452	'545	'467	...	'381	'467
2	'675	'803	'509*	'561	'585*	'675	'482	'546	'533	...	'479*	'495*
3	'630	'642*	'563*	'597*	'569*	...	'441	'537	'539	'492*
4	'617	'656	'549	'575	'602*	'656	'419	'431	'455	'497*	...	'515
5	'602	'650*	'538	'601*	'609*	'671	'479	'516	...	'507	'518	'543
6	'593	...	'593*	'608*	'576*	...	'501*	...	'531	'497	'513	'543
7	...	'581*	'617*	'608*	'576*	...	'488	'513	'527	'497	'468	'507
8	...	'530	'606*	'590*	'548*	...	'470	'491	'498	'480*	'486	...
9	'600	'569*	'558*	...	'476	'492*	...	'465*	'455	...
10	'614*	'539	'534*	'467*
12	'525	'534*
14	'549*

† The discharge per second varied from '461 to '665 cubic feet in two experiments. The coefficient '485 is derived from the mean value.

varied, and brought to agree more closely with actual weirs across rivers than the thin plates or boards of earlier experimenters. The author has calculated and arranged the coefficients in the following table from these experiments. The variations in the values for different widths of crest, other circumstances being the same, are very considerable; and the differences in the coefficients, at depths of 5 inches and under, for thin plates and crests 2 inches wide, are greater than mere friction can account for; and greater also than the differences at the same depths between the coefficients for crests 2 inches thick, and 8 feet long.



The plan and section, Fig. 10, will give a fair idea of the approach to, and nature of the overfall made use of in these experiments. The area of the reser-

voir was 2A. 1R. 30P., and the head was measured from the surface of the still water in it, which remained unchanged between the beginning and end of each experiment. The width of the approach A B from the reservoir was about 32 feet; the width at *a b* about 13 feet, below which the waterway widened suddenly, and again narrowed to the length of the overfall. The depth in front of the dam appears to have been about 3 feet; the depth on the dam, next the overfall, about 2 feet; and the depth on the sunk masonry in the channel of approach, about 18 inches. Altogether, the circumstances were such as to increase the amount of resistances between the reservoir, from which the head was measured, and the overfall, particularly for the larger heads, and it is accordingly seen that the coefficients become less for heads over six inches, with a few exceptions. The measurements of the quantities discharged appear to have been made very accurately, yet the discharges per second, with the same head and same length of overfall, sometimes vary; for instance, with the plank 2 inches thick and 10 feet long, the discharge per second for 4 inches head varied from 6.098 cubic feet to 6.491 cubic feet, or by about one-sixteenth of the whole quantity. Most of the results, however, are means from several experiments. The quantities discharged varied from one-tenth of a cubic foot to 22 cubic feet per second, and the duration of the experiments from 24 to 420 seconds. If the coefficients for a plank 10 feet long and 2 inches thick in the foregoing table be compared with those for the same overfall at Chew-Magna, it will be seen imme-

diately how much the form of the approaches affects the discharge. Indeed, were the area of the reservoir at Chew-Magna even larger than that for the Kennet and Avon experiments, it would be found, notwithstanding, that the coefficients in the former would still continue the larger, though not fully as large as those found under the particular circumstances.*

The following table gives the mean results of 88 experiments made by Francis, at the Lower Lock, Lowell, Massachusetts, in 1852. The duration of each of these experiments varied from 180 to 822 seconds. The coefficients in column 10 have been calculated by the author, and the other results condensed from the large table given in Francis' Book.† The heads given in the 6th column are those which

* There is a very important omission in all the preceding experiments on weirs and notches. In Fig. 10, for instance, it would have been necessary to obtain the heads at A B and $a b$ in each experiment, above the crest, and also the head on and a few feet above the crest itself. These are, perhaps, best calculated by means of the observed velocity of approach. They would indicate the resistances at the different passages of approach, and enable us to calculate the coefficients correctly, and thereby render them more generally applicable to practical purposes. The coefficients in the two previous tables are not as valuable as they otherwise would be from this omission. The level of still water near the banks is below that of the moving water in the current; therefore, heads measured from still water must give larger coefficients than if taken from the centre of the current. This may account, to some extent, for the larger coefficients in the first table, but apart from this, the short contracted channel immediately above the waterfall, Fig. 9, must increase the velocity of approach, and consequently the coefficients.

† Lowell Hydraulic experiments. New York, 1855.

1	2	3	4	5	6	7	8	9	10
Average experiments.	Length of weir (l) in feet.	Observed mean depth over weir in feet (h_1).	Observed discharge in cubical feet per second.	Observed velocity of approach in feet per second.	Depths (h') corrected for the velocity of approach when $h_a = \frac{v_a^2}{2g}$.	Values of h'' in the formula in column 8.	Value of the formula $D = c \left\{ l + 1.1 h'' \right\} h'^{\frac{3}{2}}$ in cubic feet per second.	Values of the multiplier c in the formula in column 8.	Corresponding values of the coefficient of discharge c_d .
1	9.997	1.55	62.6	.78	1.56	1.56	62.6	3.32	.621
2	9.997	1.24	45.6	.59	1.25	1.25	45.4	3.33	.623
3	9.997	1.00	33.4	.44	1.00	1.00	32.5	3.32	.621
4	7.997	1.01	26.8	.36	1.02	1.02	26.3	3.36	.628
5	9.997	1.05	36.	.97	1.06	1.06	35.8	3.35	.626
6	9.995	0.98	32.6	.54	0.99	.98	32.4	3.34	.624
7	9.995	1.00	33.5	.55	1.01	1.00	33.3	3.33	.623
8	9.997	0.80	23.5	.33	.80	.80	23.4	3.32	.621
9	9.997	0.82	25.	.75	.83	.83	24.8	3.34	.624
10	9.995	0.80	23.9	.40	.80	.80	23.8	3.34	.624
11	9.997	0.62	16.2	.23	.62	.62	16.0	3.33	.623
12	9.997	0.65	17.5	.53	.65	.65	17.2	3.33	.623
13	7.997	0.68	14.6	.45	.68	.68	14.5	3.34	.623

would give the observed discharge from the formula

$$D = \frac{2}{3} c_d (2g)^{\frac{1}{2}} h'^{\frac{3}{2}}.$$

As also from equation (89)

$$D = \frac{2}{3} c_d l (2g)^{\frac{1}{2}} \times \{h + h_a\}^{\frac{3}{2}} - h_a^{\frac{3}{2}}\},$$

therefore,

$$h' = \{(h + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}}\}^{\frac{2}{3}};$$

the values of which are given in column 6. The values of h'' in column 8 are those which would be found by resolving the equation

$$D = c (l + 1.1 h'') h''^{\frac{3}{2}};$$

n being the number of end contractions, and c a multiplier varying from 3.32 to 3.36.

In this table the theoretical head $\frac{v_a^2}{2g} = .0155 v_a^2$ due to the velocity of approach has been used and does not exceed .02 of a foot. However, this head is much greater, and should be taken $= \frac{v_a^2}{c_d^2 \times 2g} = .04 v_a^2$ or thereabouts. This would reduce the values of the coefficient of discharge c_d in the 10th column. The differences between h , h' , and h'' in columns 3, 6, and 7 are here, practically, of little moment, and the value of c_d in column 10 would be nearly the same derived from either. The crest of the weir experimented upon was 1 inch thick. The weir measuring 10 feet \times 13 inches \times 1 inch, the top was rounded off at both arrises, leaving the central horizontal portion one quarter of an inch wide. The general result of these experiments verifies the ordinary coefficient for notches in thin plates from .617 to .628 for the value of c_d .

Professor Thomson's experiments with right-angled triangular notches, in thin plates, give a mean coefficient of .617. *Vide* Note p. 42.

HEAD, AND FROM WHENCE MEASURED.

By referring to TABLE I., it is seen that there is a difference in the coefficients as obtained from heads measured on and above the orifice. This difference is greater in notches, or weirs, than in orifices sunk below the surface; and when the crest of a weir is of some width, the depths upon it vary. In the Kennet

and Avon experiments, the heads measured from the surface of the water in the reservoir, and the depths at the "outer edge" (by which is understood the lower edge) of the crest were as follows:—

DIFFERENCE OF HEADS MEASURED ON AND ABOVE WEIRS.

Heads from reservoir to crest, in inches.	Heads on crests 2 inches thick.		Heads on crests 3 feet wide.					
	3 feet long.	6 feet long.	3 feet long, crest level.	3 feet long, crest slope 1 in 18.	3 feet long, crest slope 1 in 12.	6 feet long, crest level.	10 feet long, crest level.	10 feet long, crest slope 1 in 18.
1	$\frac{3}{8}$...	$\frac{7}{16}$...	$\frac{1}{4}$	$\frac{1}{2}$	$\frac{7}{16}$	$\frac{3}{16}$
2	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{8}$	$\frac{1}{16}$
3	...	$1\frac{1}{16}$	$1\frac{1}{2}$ to $1\frac{1}{4}$
4	3 to $2\frac{1}{16}$	$3\frac{1}{2}$	$1\frac{3}{8}$	$1\frac{3}{8}$	$1\frac{1}{2}$	$1\frac{1}{2}$
5	$3\frac{1}{2}$	$3\frac{5}{8}$	$2\frac{1}{4}$	$1\frac{3}{4}$	$1\frac{1}{2}$...
6	$4\frac{1}{8}$	$4\frac{3}{8}$	$2\frac{3}{8}$	$2\frac{3}{4}$	$2\frac{5}{8}$	$2\frac{1}{4}$
7	$2\frac{1}{4}$	$2\frac{3}{8}$
8	$6\frac{3}{8}$	$3\frac{1}{8}$	$3\frac{1}{2}$
9	$4\frac{1}{8}$	$3\frac{1}{2}$...
10	4	...

No intermediate heads are given, but those registered point out very clearly the great differences which often exist between the heads measured on a weir, or notch, and those measured from the still water above it; and how the form of the weir itself, as well as the nature of the approaches, alters the depth passing over. On a crest 2 feet wide, with $14\frac{1}{2}$ inches depth on the upper edge, we have found that the depth on the lower edge is reduced to $11\frac{1}{2}$ inches, or as 1.26 to 1. The head taken from 3 to 20 feet above the crest, where the plane of the approaching water surface becomes curved, is that in general which is best suited for finding the

discharge by means of the common coefficients, but a correct section of the channel and water-line, showing the different depths upon and for some distance above the crest, is necessary in all experiments for determining accurately by calculation the value of the coefficient of discharge c_d .

Du Buât, finding the theoretical expression for the discharge through an orifice of half the depth h ,

$$D = \frac{2}{3} \sqrt{2g} \times l \left\{ h^{\frac{3}{2}} - \left(\frac{h}{2} \right)^{\frac{3}{2}} \right\},$$

equation (6)

$$= \frac{2}{3} l h \sqrt{2g h} \times \left\{ 1 - \left(\frac{1}{2} \right)^{\frac{3}{2}} \right\} = .646 \times \frac{2}{3} l h \sqrt{2g h},$$

to agree pretty closely with his experiments, seems to have assumed that the head h is reduced to $\frac{h}{2}$ in passing over. This is a reduction, however, which never takes place unless with a wide crest and at its lower edge, or where the head h is measured at a considerable distance above the weir, and when a loss of head due to the distance and obstructions in channel takes place. When there is a clear weir basin immediately above the weir, the author has found that, putting h for the head measured from the surface in the weir basin, and h_w for the depth on the upper edge of the weir, that

$$(32.) \quad h - h_w = .14 \sqrt{h},$$

for measures in feet, and

$$(33.) \quad h - h_w = .48 \sqrt{h},$$

for measures in inches. The comparative values of h and h_w depend, however, a good deal on the particular

circumstances of the case. Dr. Robinson found * $h = 1.111 h_w$, when h was about 5 inches. The expressions given are founded on the hypothesis, that $h - h_w$ is as the velocity of discharge, or as the \sqrt{h} nearly. For small depths, there is a practical difficulty in measuring with sufficient accuracy the relative values of h and h_w . Unless for very small heads the sinking will be found in general to vary from $\frac{h}{10}$ to $\frac{h}{4}$, and in practice it will always be useful to observe the depths on the weir as well as the heads for some distances (and particularly where the widths contract) above it.

In order to convey a more definite idea of the differences between the coefficients for heads measured at the weir, or notch, and at some distance above it, assume the difference of the heads $h - h_w = \frac{h_w}{r}$;

$$\text{then } \frac{h_w}{h - h_w} = r, \text{ and } \frac{1}{r} = \frac{h - h_w}{h_w},$$

$$\text{hence } h = \frac{r + 1}{r} h_w \text{ and } h_w = \frac{r}{r + 1} h.$$

Now the discharge may be considered as that which would take place through an orifice whose depth is h_w with a head over the upper edge equal to $h - h_w = \frac{h_w}{r}$; hence from equation (6) the discharge is equal to

$$\frac{2}{3} l \sqrt{2g} \times c_d \left\{ h^{\frac{3}{2}} - \left(\frac{h_w}{r} \right)^{\frac{3}{2}} \right\},$$

and substituting for $h^{\frac{3}{2}}$ its value $\left(\frac{r + 1}{r} h_w \right)^{\frac{3}{2}}$, then the

* Proceedings of the Royal Irish Academy, vol. iv. p. 212.

value of the discharge is

$$(84.) \quad D = \frac{2}{3} l h_w \sqrt{2 g h_w} \times c_d \left\{ \left(1 + \frac{1}{r} \right)^{\frac{3}{2}} - \left(\frac{1}{r} \right)^{\frac{3}{2}} \right\}.$$

As the value would be expressed by

$$\frac{2}{3} l h_w \sqrt{2 g h_w} \times c_d$$

if the head $h - h_w$ were neglected, it is evident the coefficient is increased, under the circumstances, from c_d to

$$c_d \times \left\{ \left(1 + \frac{1}{r} \right)^{\frac{3}{2}} - \left(\frac{1}{r} \right)^{\frac{3}{2}} \right\};$$

or, more correctly, the common formula has to be multiplied by $\left(1 + \frac{1}{r} \right)^{\frac{3}{2}} - \left(\frac{1}{r} \right)^{\frac{3}{2}}$, to find the true discharge, and the value of this expression for different values of $\frac{1}{r} = n$ will be found in TABLE IV. If it be supposed that

$$h - h_w = \frac{h_w}{10}, \text{ then } \frac{1}{r} = \frac{1}{10} = n;$$

and find from the table $\left(1 + \frac{1}{r} \right)^{\frac{3}{2}} - \left(\frac{1}{r} \right)^{\frac{3}{2}} = 1.1221$.

Now if the value of c_d be taken, for the full head h , to be .628, then will $1.1221 \times .628 = .705$, rejecting the latter figures, be the coefficient when the head is measured at the orifice; and if $\frac{1}{r} = \frac{2}{10} = n$, then in the same manner the new coefficient would be found to be $1.2251 \times .628 = .769$ nearly. The increase of the coefficients determined, page 65, from Mr. Ballard's experiments is, therefore, evident from principle, as the heads were taken at the notch; and it is also pretty

clear that, *in order to determine the true discharge, the heads both on, at, and above a weir should be taken.* Most of the discrepancies in the coefficients determined from experiment have arisen from imperfect and limited observations of the facts. Amongst these the velocity of approach should never be neglected by observers, as its effect on the discharge is often considerable in increasing the quantity. The effect of the form of the weir and approaches is scarcely ever sufficiently considered by professional men. Most of the discussions which arose with reference to the gaugings on the *Metropolitan MAIN DRAINAGE QUESTION* would have been obviated if the calculators, or engineers, had taken into account the different circumstances attendant on it, instead of applying generally a formula suited to a particular case, namely, a thin crest, a small notch, and a large body of water immediately above it; and applied a correct formula for including the effects of the velocity of approach.

The two following tables have been reduced to English feet measures, from Boileau's experiments; they show the relation of the head to the depth on the crest at the upper arris. The coefficient for the head h being known, that due to h_w on the weir, may be calculated from equation (34).

If the head h_w were used instead of h , to calculate the discharge, then when $\frac{h}{h_w} = 1.2$, a coefficient of .628 for the head h would become .769 for the head h_w in equation (34). For $\frac{1}{r} = .2$, and, therefore, TABLE IV., $.628 \times (1.2)^{\frac{3}{2}} - (.2)^{\frac{3}{2}} = .628 \times 1.2251 = .769$.

TABLE showing the ratio of the head, h , to the depth, h_w , on a Plank Weir of the full width of the Channel, immediately at the upper edge, or $\frac{h}{h_w}$, see equation (33), when the sheet of water is free after passing over, with air under it.

Head h in feet.	Values of the head h divided by the thickness of the sheet of water passing over the weir immediately at the upper edge ; average $\frac{h}{h_w} = \frac{6}{5} = 1.2$ between heads of 3 and 14 inches.			
	Height of weir in feet, 36".	Height of weir in feet, 40".	Height of weir in feet, 44".	Height of weir in feet, 48".
1	1.339	1.285
13	1.282	...	1.320	1.250
16	1.260	...	1.285	1.228
20	1.234	1.243	1.249	1.214
23	1.223	1.232	1.231	1.205
26	1.216	1.232	1.223	1.200
3	1.212	1.228	1.218	1.199
33	1.210	1.225	1.217	1.199
39	1.206	1.221	1.212	1.197
46	1.202	1.216	1.206	...
53	1.199	...	1.201	...
59	1.196	...	1.195	...
66	1.192	...	1.191	...
82	1.186
99	1.184
115	1.182

If the head h_w were used instead of h to calculate the discharge, when $\frac{h}{h_w} = 1.25$, TABLE next page, then a coefficient of .628 for the head h would become .799 for the head h_w in equation (34). For $\frac{1}{r} = .25$; and, therefore, the value of $c_d \left\{ \left(1 + \frac{1}{r} \right)^{\frac{3}{2}} - \left(\frac{1}{r} \right)^{\frac{3}{2}} \right\}$, TABLE IV., is .628 $\times (1.25)^{\frac{3}{2}} - (.25)^{\frac{3}{2}} = .628 \times 1.2725 = .799$. And so on we may calculate the value of the coefficient to

be applied to the depth h_w on the weir, for any other ratios between h and h_w by means of equation (84).

TABLE showing the ratio $\frac{h}{h_w}$, equation (83), when the sheet of water passing over is in contact with the crest and with the water immediately below a Plank Weir.

Head h in feet.	Values of $\frac{h}{h_w}$ for different heights of weirs and for different heads; mean value for heads between 3 and 14 inches, equal $\frac{5}{4} = 1.25$.		
	Height of weir in feet, 1.07.	Height of weir in feet, 1.1.	Height of weir in feet, 1.38.
.43	...	1.283	...
.46	...	1.275	1.291
.49	1.256	1.266	1.281
.53	1.250	1.258	1.271
.59	1.236	1.245	1.254
.66	1.225	1.232	1.241
.73	1.216	1.223	...
.79	1.208	1.216	...
.86	1.202	1.208	...
.92	1.198	1.203	...
.99	...	1.198	...

Boileau made some valuable experiments at Metz, which were published in 1854. They give the following results for vertical plank weirs extending from side to side of the channel, when the water passed over without adhering to the crest:—

Height of weir over bottom of channel in feet.	Head above.	Mean coefficient.
3.	.2 to 1.6	.645
1.8	.16 to .5	.622
.6	.15 to .25	.625

When the water passing over adhered to the crest,

and no air between the sheet passing over and the water below the weir, the experiments gave

Height of weir over bottom of channel in feet.	Head above.	Mean coefficient.
2·	1· to 1·6	·694
1·3	·6 to 1·8	·690
·6	·36 to 1·8	·675

When the plank weir leant up-stream 4 inches to a foot, the mean value of c_d was ·620, the height of weir being 1·5 foot, and with heads from ·23 to ·5 foot. When its crest was rounded to a semi-cylinder, the coefficient was, with a head of ·26 foot, ·696, and with a head of ·52 foot, ·848 ; the water adhering to the crest. With a head of ·6 foot the coefficient was ·867, and with a head of ·85 foot, ·840, when the water passed over without air between it and the water below the crest. The following tables give the experimental and reduced coefficients for vertical plank weirs of different heights, and with different heads, when the water passes over in a full sheet, and also when it adheres to the crest and joins it and the lower water. Also for plank weirs suitable for sluices, leaning up-stream with a slope of one-third horizontal to one vertical.

COEFFICIENTS of Vertical Plank Weirs at right angles to the Channel, when the edge is chamfered at the lower side, and when the water is free and not in contact with the slope, or water below; derived from Boileau's experiments.

Heights of weirs, in feet, over the bottom of the channel, and corresponding values of c_d in the formula $v = c_d \times \frac{1}{2} \sqrt{2g\lambda}$																			
Head λ In feet	66'	32"	99'	1'15"	1'32"	1'48"	1'65"	1'81"	1'98"	2'14"	2'31"	2'47"	2'64"	2'80"	3'07"	3'13"	3'30"	3'46"	3'60"
1'3"	.631	.637	.639	.636	.627	.616	.612	.607	.603	.603	.606	.610	.619	.630	.637	.634	.627	.619	.612
1'6"	.628	.633	.634	.633	.628	.622	.613	.606	.598	.595	.597	.603	.613	.628	.634	.631	.624	.616	.609
2'0"	.624	.630	.633	.630	.621	.610	.606	.600	.597	.597	.597	.600	.606	.615	.628	.633	.630	.624	.616
2'3"	.627	.630	.633	.630	.622	.613	.606	.600	.597	.597	.597	.600	.606	.615	.628	.633	.630	.624	.616
2'6"	.627	.635	.636	.631	.622	.613	.607	.603	.598	.598	.598	.601	.607	.616	.628	.633	.630	.624	.616
3'0"636	.634	.633	.628	.624	.618	.612	.609	.610	.613	.619	.628	.628	.628	.624	.619	.613
3'3"637	.637	.636	.633	.627	.621	.615	.613	.613	.615	.619	.625	.628	.628	.624	.621	.616
3'6"642	.643	.640	.637	.631	.625	.616	.613	.613	.615	.618	.624	.630	.630	.628	.624	.619
4'0"643	.636	.636	.627	.619	.615	.615	.612	.615	.624	.633	.637	.636	.630	.621
4'6"651	.645	.645	.637	.627	.618	.613	.612	.615	.627	.639	.640	.637	.630	.622
5'3"654	.648	.642	.636	.628	.624	.622	.625	.633	.642	.640	.636	.630	.624
5'9"646	.641	.636	.628	.624	.622	.625	.633	.642	.643	.639	.633	.627
6'6"652	.649	.648	.643	.640	.639	.642	.643	.645	.643	.639	.633	.627
7'2"657	.652	.651	.648	.645	.644	.648	.649	.655	.651	.642	.636	.628
7'9"667	.662	.661	.658	.658	.661	.665	.661	.648	.643	.639	.634
8'6"665	.664	.665	.667	.668	.668	.666	.655	.646	.642	.637
9'2"665	.667	.668	.668	.668	.666	.661	.650	.645	.640	.632
9'9"668	.669	.669	.669	.667	.666	.655	.648	.640	.630
1'05"667	.667	.667	.663	.652	.640	1'05"
1'12"664	.664	.664	.661	.651	.640	1'12"
1'18"660	.660	.660	.656	.646	.636	1'18"
1'25"661	.663	.661	.657	.648	.638	1'25"
1'32"664	.663	.660	.654	.648	.642	1'32"
1'39"667	.664	.660	.655	.649	..	1'39"
1'45"670	.663	.657	.651	..	1'45"
1'52"673	.666	.660	.654	..	1'52"
1'58"676	.670	1'58"
1'65"681	1'65"

COEFFICIENTS of Vertical Plank Weirs at right angles to the Channel, when the edge is chamfered at the lower arris, and when the head passing over is in contact with the water at and below the Weir; or when the water immediately below the Weir rises to the crest. The maximum coefficient .733 appears to obtain when the height of the Weir is double the depth passing over the crest.

Head h in feet.	Heights of weirs, in feet, over the bottom of the channel, and corresponding values of the coefficient of discharge c_d in the formula $v = c_d \times \frac{1}{2} \sqrt{2gh}$.									Head h in feet.
	.66'	.82'	.99'	1.15'	1.32'	1.48'	1.65'	1.81'	1.98'	
.30	.72730
.33	.72433
.36	.72136
.39	.71839
.43	.71443
.46	.70946
.49	.702	.708	.715	.72449
.53	.694	.699	.708	.71853
.56	.687	.693	.700	.712	.72956
.59	.679	.687	.694	.705	.72159
.63	.676	.682	.689	.700	.71763
.66	.672	.678	.684	.696	.71466
.73	.667	.672	.678	.690	.708	.73373
.79	.661	.666	.673	.685	.705	.72979
.86	.655	.660	.669	.681	.700	.72486
.92	.648	.655	.666	.678	.699	.72092
.99	.640	.652	.666	.678	.693	.703	.712	.720	.729	.99
1.05	.631	.645	.657	.669	.681	.691	.702	.711	.720	1.05
1.12	.627	.636	.646	.657	.667	.679	.690	.700	.711	1.12
1.19	.625	.636	.646	.657	.666	.675	.685	.694	.703	1.19
1.25	.625	.636	.646	.657	.666	.675	.682	.690	.696	1.25
1.32	.625	.636	.646	.657	.666	.673	.679	.685	.691	1.32
1.39666	.672	.678	.682	.684	1.39
1.45664	.670	.675	.679	.684	1.45
1.52661	.667	.672	.676	.681	1.52
1.58658	.663	.669	.672	.675	1.58
1.65655	.658	.663	.666	.667	1.65

The effect of the form of the crest in increasing the coefficients is distinctly observable in the next table, although the weirs experimented on overhung the water above, between the crest and the bottom of the channel.

The following table gives the result of experiments on chamfered plank weirs, for gauging, extending across a channel at right angles to it, when the back-water

TABLE of Experimental Coefficients for Plank Weirs leaning up-stream, when the crest has the down-stream arris rounded to a quadrant; and when the crest is cylindrical and projecting up-stream in the form of a knob.

Head h in feet.	Plank weir leaning up-stream one-third to one; the lower arris of crest rounded off to a quadrant of a circle with a radius the full thickness of the plank.		Plank weir leaning upwards one-third to one, the crest rounded and projecting in front beyond the plank, so as to be thicker than it.	
	Water free from curve of crest 13 foot thick.	Water in contact with curve of crest 17 foot thick.	Water in contact with curve of crest 3 foot thick.	Water in contact with curve of crest 33 foot thick.
16	589	651
20	589	672
23	594	697
26	612	697
30	633	721	...	670
33	642	747	604	686
36	649	766	625	700
39	655	768	648	714
43	661	795	669	727
46	667	802	687	741
49	675	...	702	753
53	679	...	715	765
56	685	...	729	775
59	741	786
63	753	795
66	762	802
69	808
72	813

below was joined to the head-water at passing over, and when there was no air between:—

Height of weir over the bottom of the channel below	feet	feet	feet	feet	feet	feet	feet	feet
	66	33	1 00	1 16	1 32	1 48	1 65	2 00
Heads passing over the weir in each case, when absorbed at the crest into the back-water	23	31	38	45	51	59	66	72

which shows that the head was drowned (*noyée*) when the depth of the lower channel below the crest of the weir was less than $2\frac{1}{2}$ times the head passing over, taking a general average.

It is necessary here to protest against the notation adopted by Boileau, Morin and others, of giving only two-thirds of the coefficient of discharge, c_d , for notches and weirs, instead of the full and true value. The correct formula for the discharge from a notch or

weir is $D = \frac{2}{3} l h \sqrt{2 g h}$. Now they assume a coefficient due to an incorrect formula $D = l h \sqrt{2 g h}$, which reduces c_d to $\frac{2}{3} c_d$ to give the same final results.


This leads also to an unnecessary distinction between the coefficients of orifices at the surface, or notches, and orifices sunk to some depth, which, practically, have the same, or nearly the same, general value. Mr. Hughes, at p. 328 of his useful treatise on Water-works, first edition, falls into the same error, for the theoretical discharge per minute over a weir one foot long is $321 h^{\frac{3}{2}}$, and not $481 h^{\frac{3}{2}}$, as he sanctions. In the edition of 1872, however, p. 376, he gives both, with a common factor m , giving Mr. Blackwell as an authority for the former. The factor m must be the coefficient of discharge and cannot, in the same case, have two different values. *The coefficients for a notch and an orifice are substantially the same if correct formulæ for the theoretical discharges be adopted.*

SECTION IV.

VARIATIONS IN THE COEFFICIENTS FROM THE POSITION OF THE ORIFICE.—GENERAL AND PARTIAL CONTRACTION.—VELOCITY OF APPROACH.—CENTRAL AND MEAN VELOCITIES.—PRACTICAL FORMULÆ FOR THE DISCHARGE OVER WEIRS AND NOTCHES.

A glance at TABLE I. will show that the coefficients increase as the orifices approach the surface, to a certain depth dependent on the ratio of the sides, and that this increase increases with the ratio of the length to the depth: some experimenters have found the increase to continue uninterrupted for all orifices up to the surface, but this seems to hold only for depths taken at or near the orifice when it is square or nearly so: it has also been found that the coefficient increases as the orifice approaches to the sides or bottom of a vessel: as the contraction becomes imperfect the coefficient increases. These facts probably arise from the velocity of approach being more direct and concentrated under the respective circumstances. The lateral orifices A, B, C, D, E, F, G, H, I, and K, Fig. 11, have coefficients differing more or less from each other. The coefficient for A is found to be larger than either of those for B, C, E, or D; that for G or K larger than that for H or I; that for H larger than that for I; and that for F, where the contraction is general, least of all. The contraction of the fluid on entering the orifice F removed from the bottom and sides is complete; it is

termed, therefore, "*general contraction*;" that at the orifices A, E, G, H, I, K, and D, is interfered with by the sides; it is therefore incomplete, and termed "*partial contraction*." The increase in the coefficients for the same-sized orifices at the same mean depths may be



assumed as proportionate to the length of the perimeter at which the contraction is partial, or from which the lateral flow is shut off; for example, the increase for the orifice G is to that for H as $cd + de : de$; and in the same manner the increase for G is to that for E as $cd + de : cd$. If n be put for the ratio of the contracted portion cde to the entire perimeter, and, as before, c_a for the coefficient of general contraction, then the coefficient of partial contraction is equal to

$$(85.) \quad c_a + .09 n = c_a + .1 n \text{ nearly,}$$

for rectangular orifices. The value of the second term $.09 n$ is derived from various experiments. If $.617$ be taken for the mean value of c_a , the expression may be changed into the form $(1 + .146 n) c_a$. When $n = \frac{1}{4}$, this becomes $1.036 c_a$; when $n = \frac{1}{2}$, it becomes $1.073 c_a$; and when $n = \frac{3}{4}$, contraction is prevented for three-fourths of the perimeter, and the coefficient for

partial contraction becomes $1.109 c_d$. The form which is given in equation (35) is, however, the simplest; but the value of n must not exceed $\frac{3}{4}$. If in this case $c_d = .617$, the coefficient for partial contraction becomes $.617 + .09 \times \frac{3}{4} = .617 + .067 = .684$. Bidone's experiments give for the coefficient of partial contraction $(1 + .152 n) c_d$; and Weisbach's $(1 + .132 n) c_d$.


VARIATION IN THE COEFFICIENTS FROM THE EFFECTS OF THE VELOCITY OF APPROACH.

Heretofore it has been generally supposed that the water in the vessel is almost still, its surface level unchanged, and the vessel consequently large compared with the area of the orifice. When the water flows in a channel to the orifice with a perceptible velocity, the contracted vein and the discharge are both found to be increased, other circumstances being the same. If the area of the vessel or channel in front exceed thirty times that of the orifice, the discharge will not be perceptibly increased by the induced velocity in the conduit; but for lesser areas of the approaching channel, corrections due to the velocity of approach become necessary. It is clear that this velocity may arise from either a surface inclination in the channel, an increase of head, or a small channel of approach supplied in some way.

Equation (6) gives the discharge from a rectangular orifice A, Fig. 12, of the length l , with a head measured from still water

$$D = \frac{2}{3} c_d l \sqrt{2g} \times \{h_1^{\frac{3}{2}} - h_2^{\frac{3}{2}}\},$$

in which h_b and h_c are measured to the surface at some distance back from the orifice, as shown in the section. The water here, however, must move along the channel towards the orifice with considerable velocity. If A be the area of the orifice, and c the area of the channel, it may be supposed, with tolerable accuracy, that this



velocity is equal to $\frac{A}{c}v_o$, in which v_o represents the mean velocity in the orifice. If the velocity of approach be represented by v_a , then

$$(36.) \quad v_a = \frac{A}{c} \times v_o,$$

and consequently the theoretical height due to it—the same as when there is no contraction at the *vena-contracta*—is

$$(37.) \quad \left\{ \begin{array}{l} h_a = \frac{A^2}{c^2} \times \frac{v_o^2}{2g} = .0155 \frac{A^2 v_o^2}{c^2}; \\ \text{and taking the head due to contraction,} \\ \text{\&c., into account} \\ h_a = \frac{A^2}{c^2} \times \frac{v_o}{2g c_d^2} = .0155 \frac{A^2 v_o^2}{c_d^2 c^2}; \end{array} \right\};$$

in feet measures.* The height h_a may be considered

* When the approaching velocity passes through the orifice without contraction, it is evident that the head h_a required to produce that

as an increase of head, converting h_b into $h_b + h_a$, and h_t into $h_t + h_a$. The discharge therefore now becomes

$$(38). \quad D = \frac{2}{3} c_d l \sqrt{2g} \left\{ (h_b + h_a)^{\frac{3}{2}} - (h_t + h_a)^{\frac{3}{2}} \right\};$$

which, for notches or weirs, is reduced to

$$(39.) \quad D = \frac{3}{2} c_d l \sqrt{2g} \left\{ (h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}} \right\}, *$$

as h_t then vanishes. As D is also equal to $A \times v_o$, equation (37) may be changed into

$$(40.) \quad \left\{ \begin{array}{l} h_a = \frac{D^2}{c^2} \times \frac{1}{2g} = \frac{.0155 D^2}{c^2}, \\ \text{and taking the head due to contraction,} \\ \text{\&c., into account,} \\ h_a = \frac{D^2}{c^2} \times \frac{1}{2g c_d^2} = \frac{.0155 D^2}{c_d^2 c^2} \end{array} \right\}$$

in feet measures.

If this value for h_a be substituted in equations (38) and (39), the resulting equations will be of a high order and do not admit of a direct solution; and in

velocity in the orifice, *with contraction outside at the vena-contracta*, must be $h_a = \frac{A^2}{C^2} \times \frac{v_a^2}{2g \times c_d^2}$ instead of $h_a = \frac{A^2}{C^2} \times \frac{v_a^2}{2g}$. In like manner $h_a = \frac{v_a^2}{c_d^2 \times 2g} = .04 v_a^2$ in feet measures when v_a is the velocity of approach and $c_d = .617$.

* The formula for the discharge over weirs, taking into account the velocity of approach, $D = 2.95 c_d l \sqrt{h + .115 v_a^2}$, given by D'Aubuisson, "Traité Hydraulique," seconde édition, pp. 78 et 95, and adopted by some English writers and engineers, is incorrect in principle. In feet measures it becomes $D = 5.35 c_d l h \times \sqrt{h + .03494 v_a^2}$, which form,—with alterations in the numerals and measures, was used for calculating discharges of sewers during the METROPOLITAN MAIN DRAINAGE discussion.

(38) and (39), as they stand, h_a involves implicitly the value of D , which is what is sought for. By finding at first an approximate value for the velocity of approach, the height h_a due to it can easily be found, equation (37); this height, substituted in equation (38) or (39), will give a closer value of D , from which again a more correct value of h_a can be determined; and by repeating the operation the values of D and h_a can be had to any degree of accuracy. In general the values found at the second operation will be sufficiently correct for all practical purposes.

It has been already observed that, for *orifices*, it is advisable to find the discharge from a formula in which only one head, that at the centre, is made use of; and though TABLE IV., as shall be shown, enables us to calculate the discharge with facility from either formula, it will be of use to reduce equation (38) to a form in which only the head (h) at the centre is used. The error in so doing can never exceed six per cent., even at small depths, equation (31), and this is more than balanced by the observed increase in the coefficients for smaller heads.

The formula for the discharge from an orifice, h_a being the head at the centre, is

$$D = c_d \sqrt{2g h} \times A;$$

and when the additional head h_a , due to the velocity of approach, is considered,

$$D = c_d \sqrt{2g (h + h_a)} \times A,$$

which may be changed into

$$(41.)^* \quad D = A \sqrt{2g h} \times c_d \left\{ 1 + \frac{h_a}{h} \right\}^{\frac{1}{2}}.$$

* See equation (41 A), Section VII. *infra*.

equation (39), for notches, may be also changed to the form

$$(42.) \quad D = \frac{2}{3}A \sqrt{2g h_b} \times c_d \left\{ \left(1 + \frac{h_a}{h_b}\right)^{\frac{3}{2}} - \left(\frac{h_a}{h_b}\right)^{\frac{3}{2}} \right\};$$

this is similar in every way to the equation

$$(43.) \quad D = \frac{2}{3}A \sqrt{2gd} \times c_d \left\{ \left(1 + \frac{h_t}{d}\right)^{\frac{3}{2}} - \left(\frac{h_t}{d}\right)^{\frac{3}{2}} \right\},$$

for the discharge from a rectangular orifice whose depth is d , with the head h_t , at the upper edge.

TABLE III. contains the values of $\left\{1 + \frac{h_a}{h}\right\}^{\frac{1}{2}}$ in

equation (41), and TABLE IV. the values of

$\left\{1 + \frac{h_a}{h_b}\right\}^{\frac{3}{2}} - \left(\frac{h_a}{h_b}\right)^{\frac{3}{2}}$ in equation (42), or the similar

expression in (43), $\frac{h_a}{h_b}$ or $\frac{h_t}{d}$ being put equal to n ; and

it may be perceived that the effect of the velocity of approach is such as to increase the coefficient from c_d

to $c_d \left\{1 + \frac{h_a}{h}\right\}^{\frac{1}{2}}$ for orifices sunk some distance be-

low the surface, in which h is the depth of the centre of the orifice; and into

$$c_d \left\{ \left(1 + \frac{h_a}{h_b}\right)^{\frac{3}{2}} - \left(\frac{h_a}{h_b}\right)^{\frac{3}{2}} \right\}$$

for weirs when h_a is the height due to the velocity of approach, and h_b the head on the weir. A few examples, showing the application of the formulæ (41), (42), and (43), and the application of TABLES I., II., III., and IV. to them, will be of use. Suppose, for the present, the velocity of approach v_a to be given, and no extra head required to maintain it through the orifice: in other words, when

$$h_a = \frac{v_a^2}{2g \times .956^2} = .017 v_a^2 \text{ in feet measures nearly.}$$

EXAMPLE I. *A rectangular orifice, 12 inches wide by 4 inches deep, has its centre placed 4 feet below the surface, and the water approaches the head with a velocity of 28 inches per second; what is the discharge?*

For an orifice of the given proportions, and sunk to a depth nearly four times its length, find from TABLE I.

$$c_d = \frac{.616 + .627}{2} = .621 \text{ nearly.}$$

As the coefficient of velocity, equation (2), for water flowing in a channel is about .956, find from column No. 3, TABLE II., the height $h_a = 1\frac{1}{8} = 1.125$ inch nearly, corresponding to the velocity 28 inches. Equation (41),

$$D = A \sqrt{2gh} \times c_d \left\{ 1 + \frac{h_a}{h} \right\}^{\frac{1}{2}},$$

now becomes

$$D = 12 \times 4 \sqrt{2gh} \times .621 \left\{ 1 + \frac{1.125}{48} \right\}^{\frac{1}{2}}.$$

Also find $\sqrt{2gh} = 192.6$ inches, when $h = 48$ inches, in TABLE II.; therefore

$$D = 12 \times 4 \times 192.6 \times .621 \left\{ 1 + \frac{1.125}{48} \right\}^{\frac{1}{2}}$$

$= 9244.8 \times .621 \{1 + .0234\}^{\frac{1}{2}} = 9244.8 \times .621 \times 1.0116$,
(as $\{1.0234\}^{\frac{1}{2}} = 1.0116$ from TABLE III.) $= 9244.8 \times .628$
nearly $= 5805.7$ cubic inches $= 3.36$ cubic feet per second. Or thus: The value of $.621 \times (1.0234)$ being found equal .628, $D = A \times .628 \sqrt{2g \times 48}$. Now for the coefficient .628, and $h = 48$ inches, TABLE II.

gives us $\cdot 628 \sqrt{2g \times 48} = 120\cdot 96$ inches; hence $D = 12 \times 4 \times 120\cdot 96 = 5806\cdot 08$ cubic inches $= 3\cdot 36$ cubic feet, the same as before, the difference of $\cdot 38$ in the cubic inches being of no practical value.

If h_a be found from the formula $h_a = \frac{v_a^2}{2g c_d^2}$, then is $h_a = 2\cdot 6$ inches, and the discharge becomes $D = 3\cdot 40$ cubic feet nearly.

If the centre of the orifice were within 1 foot of the surface, the effect of the velocity of approach would be much greater; for then

$$c_d \times \left\{ 1 + \frac{h_a}{h} \right\}^{\frac{1}{2}} = (\text{from TABLE I.}) \cdot 628$$

$\left\{ 1 + \frac{1\cdot 125}{12} \right\}^{\frac{1}{2}} = (\text{from TABLE III.}) \cdot 628 \times 1\cdot 047 = \cdot 652$ instead of $\cdot 628$. In this case the discharge is $D = 12 \times 4 \times \cdot 652 \sqrt{2g \times 12} = 12 \times 4 \times \cdot 652 \times 96\cdot 8$ (from TABLE II.) $= 12 \times 4 \times 62\cdot 8 = 3014\cdot 4$ cubic inches $= 1\cdot 744$ cubic feet per second. Or find the value of $\cdot 652 \sqrt{2gh}$ directly from TABLE II. thus:

$$\text{The value of } \cdot 628 \sqrt{2g \times 12} = 60\cdot 48 \quad \cdot 628$$

$$\text{The value of } \cdot 666 \sqrt{2g \times 12} = 64\cdot 14 \quad \cdot 652$$

$$\frac{38}{88} : \frac{3\cdot 66}{24} :: 24 : 2\cdot 31.$$

Hence $\cdot 652 \sqrt{2gh} = 60\cdot 48 + 2\cdot 31 = 62\cdot 79$, and the discharge $= 12 \times 4 \times 62\cdot 79 \times 3013\cdot 92$ cubic inches $= 1\cdot 744$ cubic feet per second, the same as before.

If h_a be taken equal to $\frac{v_a^2}{2g c_d^2} = 2\cdot 6$ inches, then the resulting value of $D = 1\cdot 833$ cubic feet nearly.

EXAMPLE II. A rectangular notch, 7 feet long, has a head of 8 inches measured at about 4 feet above the

crest, and the water approaches the over-fall with a velocity of $16\frac{1}{4}$ inches per second; what is the discharge?

For a still head assume $c_d = .628$ in this case, and then from equation (42)

$$D = \frac{2}{3} A \sqrt{2 g h_b} \times c_d \left\{ \left(1 + \frac{h_a}{h_b} \right)^{\frac{3}{2}} - \left(\frac{h_a}{h_b} \right)^{\frac{3}{2}} \right\}.$$

As in the last example, find from TABLE II. (h_a) the height due to the velocity of approach ($16\frac{1}{4}$ inches) to be $\frac{3}{8} = 3.375$ inch, assuming the coefficient of velocity to be .956. Therefore, $h_a = .375$, $h_b = 8$, $c_d = .628$, and $A = 7 \times 12 \times 8$; or for measures in feet $\frac{h_a}{h_b}$

$$= .047, h_b = \frac{2}{3}, \text{ and } A = 7 \times \frac{2}{3}; \text{ hence}$$

$$D = \frac{2}{3} \times 7 \times \frac{2}{3} \sqrt{2 g \times \frac{2}{3}} \times .628 \left\{ (1.047)^{\frac{3}{2}} - (.047)^{\frac{3}{2}} \right\}.$$

The value of $(1.047)^{\frac{3}{2}} - (.047)^{\frac{3}{2}}$ will be found from

TABLE IV. equal to 1.0612; the value of $\sqrt{2 g \times \frac{2}{3}}$ will be found from TABLE II. equal to 6.552, viz. by dividing the velocity 78.680, to be found opposite 8 inches, by 12; hence

$$D = \frac{2}{3} \times 7 \times \frac{2}{3} \times 6.552 \times .628 \times 1.0612$$

$$= \frac{2}{3} \times 7 \times 4.368 \times .628 \times 1.0612$$

$$= \frac{2}{3} \times 7 \times 4.368 \times .666 \text{ nearly.}$$

$$= \frac{2}{3} \times 7 \times 2.909 = 7 \times 1.939$$

$$= 13.573 \text{ cubic feet per second} = 814.98 \text{ cubic feet}$$

per minute. Or thus: From TABLE VI., when the coefficient is $\cdot 628$, the discharge from a weir 1 foot long, with a head of 8 inches, is found to be 109.731 cubic feet per minute. The discharge for a weir 7 feet long, when $\frac{h_a}{h} = \cdot 047$ is therefore $109.731 \times 7 \times 1.0612 = 815.12$ cubic feet per minute. The difference between this value and that before found, 814.38 cubic feet is immaterial, and has arisen from not continuing all the products to a sufficient number of places of decimals.

If $h_a = \frac{v_a^2}{2g c_d^2} = \cdot 87$ inch, then $D = 14.5$ cubic feet per second, or 870 cubic feet per minute nearly.

In equations (36) and (37), the relations between the channel, orifice, velocity of approach, and velocity in the orifice, are pointed out, viz.,

$$v_a = \frac{A}{c} \times v_o, \text{ and } h_a = \frac{A^2}{c^2} \times \frac{v_o^2}{2g} = \frac{D^2}{2g c^2},$$

$$\text{in which } h_a = \frac{v_a^2}{2g}$$

(neglecting, for the present, the coefficient of velocity in passing through the orifice). As v_o is the actual velocity in the orifice, $\frac{v_o}{c_d}$ must be the theoretical velocity due to the head $h + h_a$, and therefore

$$h + h_a = \frac{v_o^2}{c_d^2 \times 2g}, \text{ and } h = \frac{v_o^2}{c_d^2 \times 2g} - \frac{v_a^2}{2g};$$

hence

$$\frac{h_a}{h} = \frac{1}{\frac{v_o^2}{c_d^2 \times 2g} - 1} = \frac{c_d^2 v_a^2}{v_o^2 - c_d^2 v_a^2} = \frac{c_d^2 A^2}{c^2 - c_d^2 A^2}, \text{ for } \frac{v_o^2}{v_a^2} = \frac{c^2}{A^2}.$$

And therefore *

$$(44.) \quad \frac{h_a}{h} = \frac{c_d^2 A^2}{c^2 - c_d^2 A^2} = \frac{c_d^2}{m^2 - c_d^2}$$

substituting this value in equations (41) and (42), there results

$$(45.) \quad \begin{cases} D = A \sqrt{2 g h} \times c_d \left\{ 1 + \frac{c_d^2}{m^2 - c_d^2} \right\}^{\frac{1}{2}} \text{ or,} \\ D = A \sqrt{2 g h} \times \frac{c_d}{\left(1 - \frac{c_d^2}{m^2} \right)^{\frac{1}{2}}} \end{cases}$$

in which $m = \frac{C}{A}$, for the discharge from an orifice at some depth; and for the discharge from a weir,

$$(46.) \quad D = \frac{2}{3} \sqrt{2 g h_b} \times c_d \left\{ \left(1 + \frac{c_d^2}{m^2 - c_d^2} \right)^{\frac{3}{2}} - \left(\frac{c_d^2}{m^2 - c_d^2} \right)^{\frac{3}{2}} \right\}.$$

The last two equations give the discharge when the ratio of the channel to the orifice $\frac{C}{A} = m$ is known, when

$h_a = \frac{v_a^2}{2 g}$, and when at the same time the whole quantity of water passing through the orifice, *that due to the velocity of approach as well as that due to the pressure, is supposed to suffer a contraction whose coefficient is c_d .*

When $h_a = \frac{v_a^2}{2 g \times c_d^2}$, that is when the velocity of approach, v_a , passes through the orifice without contraction, we shall get

$$(44a.) \quad \frac{h_a}{h} = \frac{v_a^2}{v_o^2 - v_a^2} = \frac{A}{c^2 - A^2} = \frac{1}{m^2 - 1};$$

H

consequently, in this case, equation (45) becomes

$$(45a.) \quad D = A \sqrt{2 g h} \times c_d \times \left\{ 1 + \frac{1}{m^2 - 1} \right\}^{\frac{1}{2}} = \\ A \sqrt{2 g h} \times c_d \left\{ \frac{m^2}{m^2 - 1} \right\}^{\frac{1}{2}};$$

and equation (46) in like manner changes into

$$(46a.) \quad D = \frac{2}{3} A \sqrt{2 g h_b} \times c_d \times \left\{ \left(1 + \frac{1}{m^2 - 1} \right)^{\frac{3}{2}} \right. \\ \left. - \left(\frac{1}{m^2 - 1} \right)^{\frac{3}{2}} \right\}.$$

The last multipliers of these two equations,

$$\left(1 + \frac{1}{m^2 - 1} \right)^{\frac{1}{2}} \text{ and } \left(1 + \frac{1}{m^2 - 1} \right)^{\frac{3}{2}} - \left(\frac{1}{m^2 - 1} \right)^{\frac{3}{2}},$$

are the same as the like multipliers in (45) and (46), when c_d , within the brackets = 1; consequently their values are at once found from the coefficient unity, 1, in the last page of TABLE V., for the respective values of $m = \frac{c}{A}$; and also for those of $\frac{h_a}{h_b} = \frac{1}{m^2 - 1}$. When $c_d = 1$, equations (45) and (45a) may be changed into the particular case

$$D = A \left\{ \frac{2 g h}{1 - \left(\frac{1}{m} \right)^2} \right\}^{\frac{1}{2}} = m A \left\{ \frac{2 g h}{m^2 - 1} \right\}^{\frac{1}{2}}$$

which is the equation of DANIEL BERNOULLI.

When $A = c$, or the orifice is equal to the channel, then $\frac{1}{m^2 - 1}$ becomes infinite, and hence h must be zero.

Indeed, this assumption cannot be made consistently, for any given depth of water; and the ratio m can never become so small as unity. A full discussion of the

theoretical question would be out of place here. It is only necessary to observe, that the two last columns in TABLE V. give the multipliers of c in equations (45a) and (46a) to find the coefficients suited to $\frac{c}{\Delta} = m$, which in practice should seldom or never be less than 2.

If $n = \frac{c_d^2}{m^2 - c_d^2}$, the values of $\left\{ 1 + \frac{c_d^2}{m^2 - c_d^2} \right\}^{\frac{1}{2}}$, and of $\left\{ 1 + \frac{c_d^2}{m^2 - c_d^2} \right\}^{\frac{3}{2}} - \left\{ \frac{c_d^2}{m^2 - c_d^2} \right\}^{\frac{3}{2}}$, respectively, can be easily had from TABLES III. and IV. TABLE V. has, however, been calculated for different ratios of the channel to the orifice, and for different values of the coefficient of discharge. This table gives at once the values of

$$c_d \left\{ 1 + \frac{c_d^2}{m^2 - c_d^2} \right\}^{\frac{1}{2}} \text{ and } c_d \left\{ \left(1 + \frac{c_d^2}{m^2 - c_d^2} \right)^{\frac{3}{2}} - \left(\frac{c_d^2}{m^2 - c_d^2} \right)^{\frac{3}{2}} \right\}$$

as new coefficients, and the corresponding value of

$$\frac{h_a}{h} \text{ and } \frac{h_a}{h_b} = \frac{c_d^2}{m^2 - c_d^2}$$

in equations (44) and (46).

It is equally applicable, therefore, to equations (41) and (42) as to equations (45) and (46). For instance, here at once is found the value of $\cdot 628 \times \{ (1\cdot 047)^{\frac{3}{2}} - (\cdot 047)^{\frac{3}{2}} \}$ in EXAMPLE II., p. 95, equal to $\cdot 666$, as $\frac{h_a}{h_b} = \cdot 047$, and the next value to it for the coefficient $\cdot 628$, in the table, is $\cdot 046$, opposite to which is found $\cdot 666$, the new coefficient sought. The sectional area of the channel in this case, as appears from the first

column, must be about three times that of the weir or notch.


When $\frac{h_a}{h_b} = \frac{1}{m^2 - 1} = \frac{A^2}{c^2 - A^2}$, then in Ex-

AMPLE II. $\frac{h_a}{h_b} = .11$ and $\left(1 + \frac{h_a}{h_b}\right)^{\frac{3}{2}} - \left(\frac{h_a}{h_b}\right)^{\frac{3}{2}} = 1.133$,

TABLE IV. (or TABLE V. for the coefficient 1). Hence in this case $.628 \times 1.133 = .712$ the new coefficient suited to the velocity of approach. Here of course $h_a =$

$\frac{v_a^2}{2g c_d^2}$ (see Note, p. 89).


TABLE V. is calculated from coefficients c_d , in still water, which vary from .550 to 1. Those from .606 to .650, and the mean value .628 are most suited for application in practice. When the channel is equal to the orifice, the supply should equal the discharge, and for open channels, with the mean coefficient .628, we find, accordingly, from the table, the new coefficient 1.002 for weirs; or 1 very nearly as it should be. It is also found in the same case,



viz., when $A = c$, and $c_d = .628$, that for short tubes, Fig. 13, the resulting new coefficient becomes .807. This, as will afterwards be seen, agrees very closely

with the experimental results. When the coefficients in still water are less than .628, or more correctly .62725, the orifice, according to this formula, cannot equal the channel unless other resistances take place, such as from friction in tubes longer than one and a half or two diameters, or in wide-crested weirs. For

greater coefficients the junction of the short tube with the vessel must be rounded, Fig. 14, on one or more sides; and in weirs or notches the approaches must slope from the crest and ends to the bottom and sides, and the overfall be sudden. The converging form of the approaches must, however, increase the velocity of approach; and therefore v_a is greater than $\frac{A}{C} \times v_o$ when c is measured between ro and Ro , Fig. 14, to find the discharge, or new coefficient of an orifice placed at ro .



As the coefficients in TABLE V. are best suited for orifices at the end of short cylindrical or prismatic tubes at right angles to the sides or bottom of a cistern, a correction is required when the junction is rounded off as at ro or Ro , Fig. 14. When the channel is equal to the orifice, the new coefficient in equation (45) becomes

$$c_d \left\{ 1 + \frac{c_d^2}{1 - c_d^2} \right\}^{\frac{1}{2}} = c_d \times \left\{ \frac{1}{1 - c_d^2} \right\}^{\frac{1}{2}}.$$

The velocity in the short tube Fig. 14 is to that in the short tube Fig. 13 as 1 to $c_d \left\{ \frac{1}{1 - c_d^2} \right\}^{\frac{1}{2}}$ nearly, or for the mean value $c_d = .628$, as 1 to .807. Now, as $\frac{v_o}{A}$ is assumed equal to $\frac{v_o}{v_a}$ in the cylindrical or prismatic tube, Fig. 13, $\frac{.807 v_o}{A} = \frac{v_o}{v_a}$ in the tube Fig. 14 with the rounded junction, for v_a becomes $\frac{v_o}{.807}$; hence,

in order to find the discharge from orifices at the end of the short tube, Fig. 14, it is only necessary to multiply the numbers representing the ratio $\frac{C}{A}$ in the first column, TABLE V., by .807, or more generally by $c_d \left\{ \frac{1}{1 - c_d^2} \right\}^{\frac{1}{2}}$, and find the coefficient opposite to the product. Thus if $c_d = .628$, then, when $\frac{C}{A} = 1$, $c_d \times \left\{ \frac{1}{1 - c_d^2} \right\}^{\frac{1}{2}} = .807$ in the table. If, again, $\frac{C}{A} = 3$, then $3 \times .807 = 2.421$, the value of $\frac{v_o}{v_a}$ for the tube Fig. 14, and opposite this value of $\frac{C}{A}$, taken in column 1, there is found .651 for the new coefficient. For the cylindrical or prismatic tube, Fig. 13, the new coefficient would be only .642. When the head h_a is however equal to $\frac{v_a^2}{2g c_d^2}$ the results must be modified accordingly (see Note, p. 89).* When h is measured from still water in a cistern, Figs. 13 and 14, and v_a the velocity of approach at c , in a short tube, inserted at the sides, or bottom, then we must take $h - h_a$ for the head, h .

* Professor Rankine gives the value of the coefficient of discharge, or contraction, for varying values of A and C at a diaphragm in a pipe by the empirical formula

$$c_d = \frac{.618}{\left(1 - .618 \times \frac{A^2}{C^2}\right)^{\frac{1}{2}}}$$


When $\frac{A}{C} = 0$, $c_d = .618$; and when $\frac{A}{C} = 1$, $c_d = 1$; as it should be very nearly for an orifice in a *thin* plate, to which only, and to an orifice A at the end of a short tube, Fig. 14, the formula is suited (see SECTION X).

**DIFFERENT EFFECTS OF CENTRAL AND MEAN VELOCITIES
IN A SHORT TUBE AND CHANNEL.**

There is, however, another element to be taken into consideration, and which it is necessary to refer to more particularly hereafter. It is this, that the central velocity, directly facing the orifice, is also the maximum velocity in a short tube, and not the mean velocity. The ratio of these velocities is 1 : $\cdot 835$ nearly; hence, in the example, p. 102, where $\frac{v}{A} = 3$, we get $3 \times \cdot 835 = 2\cdot 505$ for the value of $\frac{v}{A}$ in column 1, TABLE V., opposite to which is found $\cdot 649$, the coefficient for an orifice of one-third of the section of the tube when cylindrical or prismatic, Fig. 13; and $3 \times \cdot 835 \times \cdot 807 = 2\cdot 02$ nearly, opposite to which we shall get $\cdot 661$ for the coefficient when the orifice is at the end of the short tube, Fig. 14, with a rounded junction. Therefore, $\frac{v}{A} \times \cdot 835$ equal to the new value of $\frac{v}{A}$ for finding the discharge from orifices at the end of cylindrical or prismatic tubes, and $\frac{v}{A} \times \cdot 835 \times \cdot 807 = \frac{v}{A} \times \cdot 67$ nearly for the new value of $\frac{v}{A}$ when finding the discharge from orifices at the end of a short tube with a rounded junction.

The ratio of the mean velocity in a tube to that facing the orifice cannot be less than $\cdot 835$ to 1, and varies up to 1 to 1; the first ratio obtaining when the orifice is pretty small compared with the section of

the tube, and the other when they are equal. If the curve $D C_1$, whose abscissæ ($A b$) represent the ratio of



the orifice to the section of the tube, and whose ordinates ($b c$) represent the ratio of the mean velocity in the tube to that facing the orifice, be

supposed to be a parabola, then the following values are found :—


Ratio of the orifice to the channel, or values of $\frac{A}{C} = \frac{A b}{A B}$	Values of $d c$	Ratio of the mean velocity of approach in a tube or channel to that directly opposite the orifice, or values of $b c$.
·0	·165	·835
·1	·163	·837
·2	·158	·842
·3	·150	·850
·4	·139	·861
·5	·124	·876
·6	·106	·894
·7	·084	·916
·8	·059	·941
·9	·031	·969
1·0	·000	1·000

These values of $b c$ are to be multiplied by the corresponding ratio $\frac{C}{A}$ in order to find a new value, opposite to which will be found, in the table, the coefficient for orifices at the ends of short prismatic or cylindrical tubes ; and this new value again mul-

multiplied by .807, or more generally by $c_d \left\{ \frac{1}{1 - c_d^2} \right\}^{\frac{1}{2}}$, will give another new value of $\frac{v}{A}$, opposite to which, in the table, will be found the coefficient for orifices at the ends of short tubes with rounded junction.

EXAMPLE III.—


What shall be the discharge from an orifice A, Fig. 16, 2 feet long by 1 foot deep, when the value of $\frac{v}{A}$ is 3, and the depth of the centre of A 1 foot 6 inches below the surface?



The theoretical discharge is $D = 2 \times 1 \times \frac{117.965}{12}$ (TABLE II.) $= 2 \times 9.829 = 19.658$ cubic feet per second. From the table on last page the coefficient for the mean velocity, facing the orifice, is about .86; hence $\frac{v}{A} \times .86 = 3 \times .86 = 2.58$. If the coefficient be taken from TABLE I., it is found (opposite to 2, the ratio of the length of the orifice to its depth) to be .617; and, for this coefficient, opposite to 2.58, in TABLE V., or the next number to it, the required coefficient .636 is found; hence the discharge is $.636 \times 19.658 = 12.502$ cubic feet per second. If the coefficient in still water be taken at .628, then we shall obtain the new coefficient .647, and the discharge

* See pp. 97 and 98, with reference to the modifications of equations (45) and (46) into (45a) and (46a) suited to $h_a = \frac{v_a^2}{2g c_d^2}$.

would be $\cdot 647 \times 19\cdot 658 = 12\cdot 719$ cubic feet. If the junction of the tube with the cistern be rounded, as shown by the dotted lines, then multiply $2\cdot 58$ by $\cdot 807$, which gives $2\cdot 08$ for the new value of $\frac{C}{A}$, opposite which, in TABLE V., when the first coefficient is $\cdot 628$, the new coefficient $\cdot 659$ is found; and the discharge in this case would be $\cdot 659 \times 19\cdot 658 = 12\cdot 955$ cubic feet per second.



It is not necessary to take out the coefficient of mean velocity facing the orifice to more than two places of decimals. For gauge notches in thin plates placed in streams and millraces, Fig. 17, the mean coefficient $\cdot 628$, for still water, may be assumed; thence the new coefficient suited to the ratio $\frac{C}{A}$ may be found, as in the first portion of EXAMPLE III.

When h_a is taken equal to $\frac{v_a^2}{2g c_d^2}$ then from TABLE V. with a coefficient of 1, and $2\cdot 58$ for the ratio of the channel to the orifice, the value of $\left\{ 1 + \frac{1}{m^2 - 1} \right\}^{\frac{1}{2}}$ in equation (45a) is $1\cdot 085$. Hence the discharge is $19\cdot 658 \times \cdot 617 \times 1\cdot 085 = 19\cdot 658 \times \cdot 6694 = 13\cdot 16$ cubic feet per minute in this case.

EXAMPLE IV. *What shall be the discharge through the aperture A, equal 2 feet by 1 foot, when the channel is to the orifice as 8\cdot 375 to 1, and the depth of the*

centre is 1.25 foot below the surface, taken at about 3 feet above the orifice?

Here the coefficient of the approaching velocity is .85 nearly, whence the new value of $\frac{v}{A}$ is $3.375 \times .85 = 2.87$; and as $c_d = .628$, from TABLE V. the new coefficient is .644. Hence

$$D = 2 \times 1 \times \frac{107.689}{12} \times .644 \text{ (TABLE II.)} = 2 \times 8.972 \times .644 = 17.944 \times .644 = 11.556 \text{ cubic feet per second.}$$

Weisbach finds the discharge, by an empirical formula, to be 11.81 cubic feet. If the coefficient be sought in TABLE I., it is .617 nearly, from which, in TABLE V., the new coefficient is found to be .632: hence $17.944 \times .632 = 11.341$ cubic feet per second. If the coefficient .6225 were used, the new coefficient equals .638, and the discharge 11.468 cubic feet. *Or thus:* The ratio of the head at the upper edge to the depth of the orifice is $\frac{9}{12} = .75$, and from TABLE IV. we find

$(1.75)^{\frac{3}{2}} - (.75)^{\frac{3}{2}} = 1.6655$. Assuming the coefficient to be .644, find from TABLE VI. the discharge per minute over a weir 12 inches deep and 1 foot long

which is $\frac{206.650 + 205.119}{2} = 206.884$ cubic feet nearly; and as the length of the orifice is 2 feet, then $\frac{2 \times 206.884 \times 1.6655}{60}$

$= 11.482$ cubic feet per second, which is the correct theoretical discharge for the coefficient .644, and less than the approximate result, 11.556 cubic feet above found, by only a very small difference. The velocity of approach in this example must be derived from the surface inclination of the stream.

When $h_a = \frac{v_a^2}{2g c_d^2}$, then with a coefficient 1 and 2.87

for the value of $\frac{C}{A}$ the last page of TABLE V. gives 1.067, by interpolation, for the value of $\left\{ 1 + \frac{1}{m^2 - 1} \right\}^{\frac{1}{2}}$ in equation (45a) see pp. 112 and 113. Hence the discharge is $17.944 \times .628 \times 1.067 = 17.944 \times .670 = 12.02$ cubic feet per second.

FOR NOTCHES, OR PONCELET WEIRS, the approaching velocity is a maximum at or near the surface. If the central velocity at the surface facing the notch be 1, the mean velocity from side to side will be .914. Assume therefore the variation of the central to the mean velocity to be from 1 to .914; and hence the ratio of the mean velocity at the surface of the channel to that facing the notch or weir cannot be less than .914 to 1, and varies up to 1 to 1; the first ratio obtaining when the notch or weir occupies a very small portion of the side or width of the channel, and the other when the weir extends for the whole width. Following the same mode of calculation as at p. 104, Fig. 15, the following results will be obtained :—

Ratio of the width of the notch to the width of the channel.	Values of d/c , Fig. 15.	Values of b/c , Fig. 15.
.0	.086	.914
.1	.085	.915
.2	.083	.917
.3	.078	.922
.4	.072	.928
.5	.064	.936
.6	.055	.945
.7	.044	.956
.8	.031	.969
.9	.016	.984
1.0	.000	1.000

These values of $b c$ are to be used as before, in order to find the value of $\frac{C}{A}$, opposite to which in the tables, and under the heading for weirs, will be found the new coefficient.

EXAMPLE V. *The length of a weir is 10 feet; the width of the approaching channel is 20 feet; the head, measured about 6 feet above the weir, is 9 inches; and the depth of the channel 3 feet: what is the discharge?*

Assuming the circumstances of the overfall to be such that the coefficient of discharge for heads, measured from still water in a deep weir basin or reservoir, is $\cdot 617$, then from TABLE VI. the discharge is $128\cdot 642 \times 10 = 1286\cdot 42$ cubic feet per minute; but from the smallness of the channel the water approaches

the weir with some velocity, and $\frac{C}{A} = \frac{20 \times \frac{3}{4}}{10 \times \frac{3}{4}} = 8$. Also

the width of the channel is equal to twice the width of the weir, and hence (small table, p. 108,) $8 \times \cdot 936 = 7\cdot 488$ for the new value of $\frac{C}{A}$. From TABLE V. is

now found the new coefficient $\frac{\cdot 623 + \cdot 634}{2} = \cdot 623$, and hence

the discharge is $\frac{1286\cdot 42 \times \cdot 623}{\cdot 617} = 1298\cdot 98$ cubic feet per

minute. *Or thus:* As the theoretical discharge, TABLE VI., is $2084\cdot 96$ cubic feet, then $2084\cdot 96 \times \cdot 623 = 1298\cdot 98$, the same as before. In this example, however, the mean velocity approaching the overfall bears to the mean velocity in the channel a greater ratio than $1 : \cdot 936$, as, though the head is pretty large in proportion to the depth of the channel, the ratio of

the sections $\frac{A}{O} = \frac{1}{8}$ is small. It is therefore more correct to find the multiplier from the small table, p. 104. By doing so the new value of $\frac{O}{A}$ is $8 \times .888 = 6.704$. From this and the coefficient .617 we shall find, as before from TABLE V., the new coefficient to be .627; hence $2084.96 \times .627 = 1307.27$ cubic feet per minute for the discharge.

The foregoing solution takes for granted that the velocity of approach is subject to contraction before arriving at the overfall, or in passing through it; now, as this reduces the mean velocity of approach from 1 to .784, TABLE V., when the coefficient for heads in still water is .617, it is necessary to multiply the value of $\frac{O}{A} = 6.704$, last found, by .784, and then $6.704 \times .784 = 5.26$ is the value $\frac{O}{A}$ due to this correction, from which the corresponding coefficient in TABLE V. is found to be .629, and hence the corrected discharge is $2084.96 \times .629 = 1311.44$ cubic feet.

By using equation (46a) in the preceding example, the value of $\left(1 + \frac{1}{m^2 - 1}\right)^{\frac{3}{2}} - \left(\frac{1}{m^2 - 1}\right)^{\frac{3}{2}}$ for $\frac{O}{A} = m = 7.488$ is, from the last columns of TABLE V. for a coefficient unity, 1.025. Hence the discharge is $2084.96 \times .617 \times 1.025 = 2085 \times .632 = 1318$ cubic feet per minute in round numbers. If $\frac{O}{A}$ were taken equal to 6.704, then equation (46a) would become $2085 \times .617 \times 1.031 = 2085 \times .636 = 1326$ cubic feet nearly.

It is to be borne in mind that the value of the ratio $\frac{O}{A}$ in TABLE V. is simply an approximate value for the

ratio of the velocity in the channel facing the orifice to the velocity in the orifice itself, and that large differences of value do not always affect the coefficient of discharge materially. The corrections applied in the foregoing examples were for the purpose of finding this ratio of velocity more correctly than the simple expression $\frac{C}{A}$ gives it. The ratio of h_a to h_b also may sometimes vary very considerably without materially affecting the value of c_d ; for instance, if $c_d = \cdot 628$ for still water, the change of $\frac{h_a}{h}$ from 0 to $\cdot 046$, and of $\frac{C}{A}$ from infinity to 3 causes a variation of, only, from $\cdot 628$ to $\cdot 642$ for orifices, and to $\cdot 666$ for notches, which, practically, does not exceed six per cent. The following auxiliary table

AUXILIARY TABLE, TO BE USED WITH TABLE V. FOR MORE NEARLY FINDING THE COEFFICIENT OF DISCHARGE NEARLY SUITED TO EQUATIONS (45a) AND (46a).

Ratio of the orifice, $\frac{A}{A_0}$, to the channel, or $\frac{A_0}{A}$	Multipliers due to the difference of the central and mean velocity only.	Multipliers for finding the new values of $\frac{C}{A}$ in Table V., when the water approaches and passes through the orifice, without contraction or loss of velocity.						
		Coefficient $\cdot 639$	Coefficient $\cdot 628$	Coefficient $\cdot 617$	Coefficient $\cdot 606$	Coefficient $\cdot 595$	Coefficient $\cdot 584$	Coefficient $\cdot 573$
$\cdot 0$	$\cdot 835$	$\cdot 69$	$\cdot 67$	$\cdot 65$	$\cdot 64$	$\cdot 62$	$\cdot 60$	$\cdot 58$
$\cdot 1$	$\cdot 837$	$\cdot 70$	$\cdot 68$	$\cdot 66$	$\cdot 64$	$\cdot 62$	$\cdot 60$	$\cdot 59$
$\cdot 2$	$\cdot 842$	$\cdot 70$	$\cdot 68$	$\cdot 66$	$\cdot 64$	$\cdot 62$	$\cdot 61$	$\cdot 59$
$\cdot 3$	$\cdot 850$	$\cdot 71$	$\cdot 69$	$\cdot 67$	$\cdot 65$	$\cdot 63$	$\cdot 61$	$\cdot 59$
$\cdot 4$	$\cdot 861$	$\cdot 72$	$\cdot 69$	$\cdot 68$	$\cdot 66$	$\cdot 64$	$\cdot 62$	$\cdot 60$
$\cdot 5$	$\cdot 876$	$\cdot 73$	$\cdot 71$	$\cdot 69$	$\cdot 67$	$\cdot 65$	$\cdot 63$	$\cdot 61$
$\cdot 6$	$\cdot 894$	$\cdot 74$	$\cdot 72$	$\cdot 70$	$\cdot 68$	$\cdot 66$	$\cdot 64$	$\cdot 62$
$\cdot 7$	$\cdot 916$	$\cdot 76$	$\cdot 74$	$\cdot 72$	$\cdot 70$	$\cdot 68$	$\cdot 66$	$\cdot 64$
$\cdot 8$	$\cdot 941$	$\cdot 78$	$\cdot 76$	$\cdot 74$	$\cdot 72$	$\cdot 70$	$\cdot 68$	$\cdot 66$
$\cdot 9$	$\cdot 969$	$\cdot 81$	$\cdot 78$	$\cdot 76$	$\cdot 74$	$\cdot 72$	$\cdot 70$	$\cdot 68$
1.0	1.000	$\cdot 831$	$\cdot 807$	$\cdot 784$	$\cdot 762$	$\cdot 740$	$\cdot 719$	$\cdot 699$

finds the correction, and thence the new coefficient, with facility. Thus, if the channel be five times the size of the orifice, and a loss in the approaching velocity takes place equal to that in a short cylindrical tube, then $5 \times .842 = 4.210$ is the new value of $\frac{c}{A}$, opposite to which, in TABLE V., will be found the coefficient sought. If the coefficient for still water be .606, it is found to be .612 for orifices and .623 for weirs. But when the water approaches without loss of velocity, from the auxiliary table, .64 is found for the multiplier instead of .842, and consequently the new value of $\frac{c}{A}$ becomes $5 \times .64 = 3.2$, from which .617 is found to be the new coefficient for orifices and .636 for weirs. The auxiliary table is calculated by multiplying the numbers in the second column (see third column, table, p. 104) by the value of $c \times \left\{ \frac{1}{1 - c_d^2} \right\}^{\frac{1}{2}}$, which will be found from TABLE V., for the different values of c_d in the table, viz.

.689, .628, .617, .606, .595, .584, and .573,

.881, .807, .784, .762, .740, .719, and .699,

to be respectively, as given in the top and bottom lines of figures.

When $\frac{c_d^2}{m^2 - c_d^2}$ in equations (45) and (46) is equal to $\frac{1}{m^2 - 1}$ in equations (45a) and (46a), then must $c_d = 1$, and $c_d \left\{ 1 + \frac{c_d^2}{m^2 - c_d^2} \right\}^{\frac{1}{2}}$ in equation (45) becomes equal to $\left\{ 1 + \frac{1}{m^2 - 1} \right\}^{\frac{1}{2}}$ in equation (45a); and

$c_d \left\{ \left(1 + \frac{c_d^2}{m^2 - c_d^2} \right)^{\frac{3}{2}} - \left(\frac{c_d^2}{m^2 - c_d^2} \right)^{\frac{3}{2}} \right\}$ in equation (46) also becomes equal to $\left\{ \left(1 + \frac{1}{m^2 - 1} \right)^{\frac{3}{2}} - \left(\frac{1}{m^2 - 1} \right)^{\frac{3}{2}} \right\}$ in equation (46a); and therefore the coefficient found from the last three columns of TABLE V. for $c_d = 1$ will give the multiplier for c_d , outside the brackets, in (45a) and (46a), to find the new coefficients. Thus in the last example $m = 5$, and hence TABLE V. for $c_d = 1$, is given $\left\{ 1 + \frac{1}{m^2 - 1} \right\}^{\frac{1}{2}} = 1.021$ and $\left\{ \left(1 + \frac{1}{m^2 - 1} \right)^{\frac{3}{2}} - \left(\frac{1}{m^2 - 1} \right)^{\frac{3}{2}} \right\} = 1.055$. Hence $1.021 \times .606 = .619$ nearly; and $1.055 \times .606 = .639$ nearly, the new coefficients found from the other method being .617 and .636, the difference by both methods being of no great practical importance.

It is necessary to observe, that in equations (45), (46), (45a), and (46a), the head due to the velocity of supply or approach, h_a , must be extra to the head, h , in the formula and no part of it: and that—as is indicated by the equations— m can never be so small as unity, for then $\frac{1}{m^2 - 1}$ would be infinite. These equations are, therefore, only strictly applicable to orifices in the short tubes, Fig. 15 and Fig. 16, when the head h_a due to the velocity of approach is included in the head h measured from still water in a large cistern.

The initial value of the coefficient of discharge, c_d itself, varies considerably with the position and form of the orifice; for a mean value of .707 it changes, in equation (45), according to the relation of c and Δ into

$\frac{.707}{(1 - .5\frac{A^2}{C^2})^{\frac{1}{2}}}$; and for a value of .618 for an orifice,

central in a thin plate, Professor Rankine's empirical formula, note p. 102, is in practice applicable.

PRACTICAL FORMULÆ FOR THE DISCHARGE OVER WEIRS.

In order to reduce the preceding formulæ for weirs and notches to some of the forms in common use, with definite combined numerical coefficients, by substituting 8.025 for $\sqrt{2g}$, equation (39), becomes for feet measures, as $\frac{2}{3} \times 8.025 = 5.35$,

$$(A.) \quad D_s = 5.35 c_d l \{(h_b + h_s)^{\frac{3}{2}} - h_s^{\frac{3}{2}}\}.$$

For inch measures, as $\sqrt{2g} = 27.8$, the discharge, taken also in cubic feet, becomes

$$(B.) \quad D = .01072 c_d l \{(h_b - h_s)^{\frac{3}{2}} - h_s^{\frac{3}{2}}\}.$$

When the length l is taken in feet and the depth in inches, it is

$$(C.) \quad D = .1287 c_d l \{(h_b - h_s)^{\frac{3}{2}} - h_s^{\frac{3}{2}}\}.$$

The last three equations being for seconds of time, *when the time is taken at one minute*, for all measures in feet the discharge in cubic feet is

$$(D.) \quad D = 321 c_d l \{(h_b + h_s)^{\frac{3}{2}} - h_s^{\frac{3}{2}}\}.$$

This when c_d is taken at .614 becomes

$$(D_1.) \quad D_s = 197 l \{(h_b' + h_s)^{\frac{3}{2}} - h_s^{\frac{3}{2}}\}.$$

For a coefficient of .617

$$(D_2.) \quad D_s = 198 l \{(h_b + h_s)^{\frac{3}{2}} - h_s^{\frac{3}{2}}\}$$

For a coefficient of .623

$$(D_3.) \quad D_a = 200 \, l \{ (h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}} \}.$$

For a coefficient of .628

$$(D_4.) \quad D_a = 201.6 \, l \{ (h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}} \}.$$

For a coefficient of .648

$$(D_5.) \quad D_a = 208 \, l \{ (h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}} \}.$$

For a coefficient of .667

$$(D_6.) \quad D_a = 214 \, l \{ (h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}} \}.$$

For a coefficient of .712

$$(D_7.) \quad D_a = 228.6 \, l \{ (h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}} \}.$$

And for a coefficient of .810

$$(D_8.) \quad D_a = 260 \, l \{ (h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}} \}.$$

For inch measures the discharge in cubic feet is

$$(E.) \quad D_a = .6433 \, c_d \, l \{ (h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}} \}.$$

And for lengths (l) in feet and depths (h_b) in inches the discharge also in cubic feet becomes

$$(F.) \quad D_a = 7.72 \, c_d \, l \{ h_b + h_a^{\frac{3}{2}} - h_a^{\frac{3}{2}} \}.$$

The latter equation, when the coefficient of discharge, c_d , is taken at .614 becomes

$$(F_1.) \quad \left\{ \begin{array}{l} D_a = 4.74 \, l \{ h_b + h_a^{\frac{3}{2}} - h_a^{\frac{3}{2}} \}, \text{ and} \\ D = 4.74 \, l \, h_b^{\frac{3}{2}}, \text{ when the velocity of ap-} \\ \quad \text{proach vanishes.} \end{array} \right.$$

For a coefficient of .617

$$(F_2.) \quad \left\{ \begin{array}{l} D_a = 4.76 \, l \{ (h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}} \}, \text{ and} \\ D = 4.76 \, l \, h_b^{\frac{3}{2}} \text{ when the velocity of ap-} \\ \quad \text{proach vanishes.} \end{array} \right.$$

For a coefficient of $\cdot 623$

$$(F_3.) \begin{cases} D = 4.81 \, l \, \{(h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}}\}, \text{ and} \\ D = 4.81 \, l \, h_b^{\frac{3}{2}} \text{ with no perceptible approach.} \end{cases}$$

For a coefficient of $\cdot 628$

$$(F_4.) \begin{cases} D_a = 4.85 \, l \, \{(h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}}\}, \text{ and} \\ D = 4.85 \, l \, h_b^{\frac{3}{2}} \text{ with no perceptible approach.} \end{cases}$$

For a coefficient of $\cdot 648$

$$(F_5.) \begin{cases} D_a = 5 \, l \, \{(h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}}\}, \text{ and} \\ D = 5 \, l \, h_b^{\frac{3}{2}} \text{ with no perceptible approach.} \end{cases}$$

For a coefficient of $\frac{2}{3}$ or $\cdot 667$

$$(F_6.) \begin{cases} D_a = 5.14 \, l \, \{(h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}}\}, \text{ and} \\ D = 5.14 \, l \, h_b^{\frac{3}{2}} \text{ with no perceptible approach.} \end{cases}$$

For a coefficient of $\cdot 712$

$$(F_7.) \begin{cases} D_a = 5.5 \, l \, \{(h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}}\}, \text{ and} \\ D = 5.5 \, l \, h_b^{\frac{3}{2}} \text{ with no perceptible approach.} \end{cases}$$

And finally for a coefficient of $\cdot 81$

$$(F_8.) \begin{cases} D_a = 6.3 \, l \, \{(h_b + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}}\}, \text{ and} \\ D = 6.3 \, l \, h_b^{\frac{3}{2}} \text{ when the velocity of approach} \\ \text{vanishes.} \end{cases}$$

The theoretical value of h_a in each of the foregoing equations is in terms of the velocity of approach v_a

$$h_a = \frac{v_a^2}{2g},$$

in which $2g$ must be taken equal to 64.403 for heads in feet, and equal to 772.84 for heads in inches. But it is evident that in order to produce the velocity per second v_a passing through the notch with a nearly still-water basin above it, that h must be increased from its

theoretical value $\frac{v_a^2}{2g}$ to $\frac{v_a^2}{c_d^2 2g}$, in which expression c_d is the coefficient of discharge due to the particular notch, or weir, and its attendant circumstances; whence

$$h_a = \frac{v_a^2}{c_d^2 2g} = \frac{\text{Theoretical head}}{c_d^2}.$$

Now, unquestionably the most general coefficient both for notches and submerged orifices, in thin plates, for gauging whether triangular, rectangular, or circular, is .617, when the orifice or notch is small compared with the approaching channel; whence for measures in feet

$$h_a = .0408 v_a^2, \text{ and } v_a = 4.95 \sqrt{h_a}.$$

For measures in inches,

$$h_a = .0084 v_a^2, \text{ and } v_a = 17.2 \sqrt{h_a}.$$

And for measures in which v_a is expressed in feet per second, and h_a in inches

$$h_a = .49 v_a^2, \text{ and } v_a = 1.43 \sqrt{h_a};$$

which shows that *half the square of the approaching velocity in feet is equal to the head h_a in inches; very nearly.* By substituting these values of h_a , found in terms of the approaching velocity, according to the standards used in the equations from (A) to (F) inclusive, and also in equation (F_2), we shall be enabled to find the proper discharge from a notch in a *thin plate*. The values of h_a , as given above, can be found at once in inches from the observed values of v_a , to be also taken in inches, for coefficients varying from .584 to .974, by means of TABLE II. Thus, with a coefficient of .617, we shall find, for an approaching velocity of 36 inches per second, that h_a becomes $4\frac{2}{3} = 4.4$ inches

nearly, while for a coefficient of $\cdot 666$, it is only $3\frac{3}{4} = 3\cdot 8$ inches; and for a coefficient of 1, the theoretical head is but $1\frac{1}{2} = 1\cdot 7$ inch nearly.

For the very nature of the case the approaching velocity must continue nearly unimpaired through the notch with but a very slight reduction arising from the viscosity of the water when it enters the aperture, and separates from the lateral fluid. But in order to give this unimpaired velocity by means of an extra head h_a , it is evident that h_a must be increased above the theoretical value by the amount due to the coefficient of discharge; or, as before stated, h_a must be increased from $\frac{v_a^2}{2g}$ to $\frac{v_a^2}{c_d^2 2g}$. This value of h_a is, perhaps, something too large, owing to the reduction of v_a at the moment it enters the notch and is acted upon by the overfall, drawing it away, as it were, from the lateral water above the crest.

The numerical results of the respective formulæ from (A) to (F₈), inclusive, can be obtained by modifying the form as in equation (42) into

$$\begin{cases} D_a = D \times \left\{ \left(1 + \frac{h_a}{h_b} \right)^{\frac{3}{2}} - \left(\frac{h_a}{h_b} \right)^{\frac{3}{2}} \right\} \text{ or,} \\ D_a = c_d \times \frac{2}{3} l h_b \sqrt{2g h_b} \times \left\{ \left(1 + \frac{h_a}{h_b} \right)^{\frac{3}{2}} - \left(\frac{h_a}{h_b} \right)^{\frac{3}{2}} \right\} \end{cases}$$

in which D is the discharge found, when there is no velocity of approach, by the common form $D = 5\cdot 35 \times c_d l h^{\frac{3}{2}}$, for which separate values are given in equations from (F₁) to (F₈) inclusive; and numerical values in TABLE VI.; and $\left\{ \left(1 + \frac{h_a}{h_b} \right)^{\frac{3}{2}} - \left(\frac{h_a}{h_b} \right)^{\frac{3}{2}} \right\}$ a multiplier suited to the velocity of approach, the values of which

can be found from TABLE IV. Suppose, for example, $D = 158.1$ cubic feet per minute, $h_b = 10$ inches, and $h_a = 4$ inches, which is that due to an approaching velocity of 3 feet per second with a coefficient of .648; then the multiplier becomes $(1 + .4)^{\frac{3}{2}} - .4^{\frac{3}{2}} = 1.4035$, TABLE IV. Hence the discharge due to an approaching velocity of 3 feet is $158.1 \times 1.4035 = 221.9$ cubic feet, or an increase of about 40 per cent. Also, if the common formula were used, it is plain that the coefficient .648 should be increased to $.648 \times 1.4035$, or to .909 nearly, which approximates within 10 per cent. of the theoretical value. Nothing can show more clearly THE NECESSITY FOR VARYING THE COEFFICIENTS WHEN THE ORDINARY FORMULAE ARE USED, EVEN FOR A NOTCH IN A THIN PLATE: for other notches the coefficients, even for still water above the crest, vary considerably.

The form of the equation used by D'Aubuisson and several other writers is

$$D_a = c l \sqrt{h_b^3 + c v_a^2 h_b^2}$$

in which c and c are numerical coefficients, and v_a the velocity of approach. This form is incorrect in principle, although the values of c and c can be so taken as to give resulting values for D_a approximately correct. For feet measures, and time in seconds, Professor Downing makes, after D'Aubuisson, p. 37 of his translation,

$$D_a = c_d \times 5.85 l \sqrt{h_b^3 + .08494 v_a^2 h_b^2}.$$

Doctor Robinson* gives for like measures and time, values varying from

* Proceedings Royal Irish Academy, vol. iv. p. 212. $.1895 v_a^2$ is nine times the theoretical head, and too much.

$$D_a = 3.55 l \sqrt{h_b + .1395 v_a^2 h_b^3}, \text{ to}$$

$$D_a = 3.2 l \sqrt{h_b^3 + .1395 v_a^2 h_b^3}.$$

Mr. Taylor finds (for the Government Referees, see Report on the Main Drainage of the Metropolis, 13th July, 1858, p. 32) the discharge in cubic feet, per minute, when the depth is taken in inches, and the length in feet to be,

$$D_a = 5.5 l \sqrt{h_b^3 + .8 v_a^2 h_b^3};$$

and the Messrs. Hawksley, Bidder, and Bazalgette assume, (p. 33 *ibid.*) for like measures,

$$D_a = 5 l \sqrt{h_b^3 + .1875 v_a^2 h_b^3},$$

which they consider is in "*excess.*" The following table, copied and extended from the report just referred to, shows the results of the last two formulæ, and of our equations (F_6) and (F_7), in which the depth,

Formula.	Mean velocities approaching the notch in feet per second, and discharges in cubic feet per minute.						
	0	.5	1	1.5	2	2.5	3
$D_a = 5 \sqrt{h_b^3 + .1875 v_a^2 h_b^3}$. .	158.1	158.5	159.5	161.4	164	167	171
Equation (L) when the head, h_a , due to the velocity of approach is taken at only its theoretical value	158.1	159.2	163.1	166.8	173	180	189
Equation (r_6) when the head, h_a , due to the velocity of approach is increased for the coefficient of velocity .648 . .	158.1	160	167	177	190	205	222
Equation (r_7) when the head, h_a , due to the velocity of approach is taken at only its theoretical value	173.9	175.1	178.3	183.5	190.1	198.3	207.5
Equation (r_7) when the head due to the velocity of approach is increased for the coefficient of velocity .712	173.9	176	182	192	204	218	234
$D_a = 5.5 \sqrt{h_b^3 + .8 v_a^2 h_b^3}$. .	173.9	175.7	180.8	188.9	199.3	213	228

h_b , must be taken equal to 10 inches, and the length, l , equal to 1 foot.

In equations (L) and (N) we can get, TABLE II., the values of the head, h_a , due to velocity of approach v_a , as follows :

$v_a = \cdot 5, \cdot 1, 1\cdot 5, \cdot 2, 2\cdot 5, 3\cdot 0$; in feet per second.

$h_a = \cdot 047, \cdot 186, \cdot 419, \cdot 745, 1\cdot 16, 1\cdot 68$; theoretical head in inches.

Then

$h_a = \cdot 111, \cdot 447, \cdot 997, 1\cdot 77, 2\cdot 76, 4\cdot$; for a coefficient of $\cdot 648$,

and

$h_a = \cdot 093, \cdot 366, \cdot 833, 1\cdot 47, 2\cdot 29, 3\cdot 31$; for a coefficient of $\cdot 712$.

Whence as $h_b = 10$ inches, we shall have in equation (42),

$\frac{h_a}{h_b} = \cdot 011, \cdot 045, \cdot 1, \cdot 18, \cdot 28, \cdot 4$; for a coefficient of 648 ,

and

$\frac{h_a}{h_b} = \cdot 009, \cdot 037, \cdot 083, \cdot 15, \cdot 23, \cdot 33$; for a coefficient of 712 ;

and hence, by means of TABLE IV. $\left(1 + \frac{h_a}{h_b}\right)^{\frac{3}{2}} - \left(\frac{h_a}{h_b}\right)^{\frac{3}{2}}$

becomes of the following respective values suited to the above velocities,

$1\cdot 015, 1\cdot 059, 1\cdot 122, 1\cdot 205, 1\cdot 3, 1\cdot 403$; for a coefficient of $\cdot 648$, and

$1\cdot 013, 1\cdot 049, 1\cdot 104, 1\cdot 175, 1\cdot 254, 1\cdot 344$; for a coefficient of $\cdot 712$. These latter values multiplied, in order, by the initial values of the discharges, $158\cdot 1$ and $173\cdot 9$, in the above table, give the discharges in the third and fifth lines corresponding ; due to the respective velocities of approach.

The accordance between the results in the last two lines of the table is remarkable. TABLE V. shows that if the coefficient be $\cdot 667$ when the water above the crest is still, it will be increased to $\cdot 712$ when the ap-

TABLE showing the actual discharges per foot in length over a weir gauge 4 f at long in a sewer: and the discharges by different formulae brought forward during the Metropolitan Sewage Discussion. In these formulae D is THE DISCHARGE IN CUBIC FEET PER MINUTE, A THE HEAD IN INCHES, and V₀ THE VELOCITY OF APPROACH IN FEET PER SECOND. See p. 22, Letter to the Right Hon. Lord John Manners, M.P., from the Government Referees, dated 16th August, 1868. The manner of obtaining the experimental values is not stated in the Letter. The experimental discharges give values for the coefficient of discharge, c_d, from '005 to '737 nearly.

Heads, initial velocities, and corresponding discharges in cubic feet per minute for each foot in length of weir.																	
1 inch, '083 foot.	2 inches, '167 foot.	3 inches, '25 feet.	4 inches, '333 feet.	5 inches, '417 feet.	6 inches, '5 feet.	7 inches, '583 feet.	8 inches, '667 feet.										
'083	'71	'092	'08	'16	'73	'18	1'02	'32	1'27	'43	2'8	'53	1'81				
5.5	6.5	15.5	18.3	28.6	30.5	44.1	48.3	61.9	68.8	81.4	115.5	103.5	119.4	125.6	150.2		
5.5	6.5	15.6	18.5	28.7	30.7	44.2	48.8	62.2	69.6	82.1	114.0	104.0	120.5	125.0	151.6		
4.8	5.0	13.5	14.1	24.9	25.3	33.4	39.3	53.7	54.9	70.9	78.7	89.1	92.72	108.9	110.6		
5.7	6.7	16.8	18.3	26.0	29.9	43.8	48.2	61.1	67.6	82.7	119.0	105.0	118.0	125.0	159.8		
Values of the coefficients, z, in the formula																	
$D = z \sqrt{A^3 + 8 A^2 v_0^2}$																	
as obtained from the actual quantities discharged																	
5.7	5.66	5.53	5.50	5.37	5.38	5.46	5.48	5.43	5.41	5.56	5.38	5.59	5.45	5.47	5.61		

proaching channel is about 1.83 times the section of the water in the notch, and this only when $\frac{h_a}{h}$ is taken as in equation (44). If the arrises of the two-inch thick waste board be rounded, the coefficient must also be considerable, although uncertain; but as the equation $D_a = 5.5 \sqrt{h_b^3 + .8 v_a^2 h_b^2}$ appears to have been framed by Mr. Taylor, to express special experiments made for Mr. Simpson, in which the quantities varied from 5 to 152 cubic feet per minute, and for heads on a four-foot weir varying from 1 inch to 8 inches,* it must be concluded that the coefficient for heads measured from still water above the crest in those experiments suited to the form of the weir used, and to its attendant circumstances, is .712.

Equations (39) and those from (A) to (F₈) may be easily changed into forms in which only the depth h_b , the velocity of approach, and the coefficient of velocity (in this case equal to that of discharge) c_d , are introduced. It is, however, only necessary here to reduce the general form (A) p. 114, for feet measures, which becomes, after substituting for h_a its value $\frac{v_a^2}{c_d^2 \times 2g}$ and making some reductions,

$$(A_1) \begin{cases} D_a = 5.35 c_d \times \left(\frac{1}{c_d^2 \times 64.4} \right)^{\frac{3}{2}} l \{ (c_d^2 \times 64.4 h_b + v_a^2)^{\frac{3}{2}} - v_a^3 \} \\ D_a = \frac{.01034}{c_d^2} l \{ (64.4 c_d^2 h_b + v_a^2)^{\frac{3}{2}} - v_a^3 \}; \end{cases}$$

and for time in minutes the discharge is

* Vide p. 22, Letter dated 16th August, 1858, from the Government Referees to the Right Hon. Lord John Manners, on the subject of the Metropolitan Main Drainage.

$$(A_2.) \quad D_s = \frac{.621}{c_d^2} l \{ (64.4 c_d^2 h_b + v_s^2)^{\frac{3}{2}} - v_s^3 \};$$

in which v_s still continues the velocity in feet per second, as determined from observation. These formulæ may be again reduced to many others. If h_b be taken in inches (A_2) becomes

$$(A_3.) \quad D_s = \frac{.621}{c_d^2} l \{ (5.37 c_d^2 h_b + v_s^2)^{\frac{3}{2}} - v_s^3 \}.$$

Mr. Pole, in a letter to Mr. Simpson and Captain Galton, already referred to, gives the special value,

$$D_s = 1.06 l \{ (3 h_b + v_s^2)^{\frac{3}{2}} - v_s^3 \},$$

which corresponds very closely with the experiments made for Mr. Simpson. If $c_d = .712$, which also closely corresponds with those experiments, our equation (A_3) becomes for them

$$(A_4.) \quad D_s = 1.225 l \{ (2.72 h_b + v_s^2)^{\frac{3}{2}} - v_s^3 \};$$

but the amount of the discharge must always depend on the coefficient c_d , equation (A_3) suited to the special circumstances of the case under consideration.

The form of equation for the discharge proposed by Mr. Boyden* includes the effects of the end contractions: it is

$$D = c \{ l - b n h_b \} h_b^{\frac{3}{2}}$$

in which $c = \frac{2}{3} c_d \sqrt{2g}$, n the number of end contractions, l the length of the weir, h_b the head measured from the surface of the water above the curvature of approach, and b a coefficient due to the nature of the end contractions. The mean numerical expression for this formula, derived by Francis from his experiments, is for feet measures, per second,

* Francis's Lowell Hydraulic Experiments, p. 74.

$$D = 3.33 (1 - .1 n h_b) h_b^{\frac{3}{2}}, *$$

but the value of c varied from 3.303 to 3.3617. These results give corresponding values of $c_d = .617$ to $.628$, and when $c = 3.33$, $c_d = .623$. The experimental results compared with this formula have been referred to at p. 71.

Francis's Lowell experiments on a wooden dam 10 feet long, level and 3 feet wide at the crest, with a head slope of $3\frac{1}{2}$ to 1 in a channel 10 feet wide, give, for heads between 6 and 20 inches, a mean coefficient of .663 or .565. This for feet measures would give for the discharge per second

$$D = 3.02 h^{\frac{3}{2}}.$$

For greater depths, on this width of crest, the discharge would probably rise as high as $3.1 h^{\frac{3}{2}}$ or $3.3 h^{\frac{3}{2}}$. The section of the dam was the same as that erected by the Essex Company across the Merrimack River, at Lawrence, Massachusetts. See, also, TABLE OF COEFFICIENTS, p. 68.

In equation (19), p. 42, there is given a general expression for the value of D through a triangular notch. Professor Thomson, of the University of Glasgow, in a paper read at the British Association at Leeds in 1858, says:—

“The ordinary rectangular notches, accurately experimented on as they have been, at great cost and with high scientific skill, in various countries, with the view of determining the necessary formulas and coefficients for their application in practice, are for many purposes suitable and convenient. They are, however, but ill adapted for the measurement of very

* Francis's Lowell Hydraulic Experiments, p. 119.

variable quantities of water, such as commonly occur to the engineer to be gauged in rivers and streams. If the rectangular notch is to be made wide enough to allow the water to pass in flood times, it must be so wide that for long periods, in moderately dry weather, the water flows so shallow over its crest, that its indications cannot be relied on. To remove, in some degree, this objection, gauges for rivers or streams are sometimes formed, in the best engineering practice, with a small rectangular notch cut down below the general level of the crest of a large rectangular notch. If now, instead of one depression being made for dry weather, we use a crest wide enough for use in floods, we conceive of a large number of depressions extending so as to give the crest the appearance of a set of steps of stairs, and if we conceive the number of such steps to become infinitely great, we are led at once to the conception of the triangular instead of the rectangular notch. The principle of the triangular notch being thus arrived at, it becomes evident there is no necessity for having one side of the notch vertical, and the other slanting; but that, as may in many cases prove more convenient, both sides may be made slanting, and their slopes may be alike. It is then to be observed, that by the use of the triangular notch, with proper formulas and coefficients derivable by due union of theory and experiments, quantities of running water from the smallest to the largest may be accurately gauged by their flow through the same notch. The reason of this is obvious, from considering that in the triangular notch, when the quantity flowing is very small, the flow is confined to a small

space admitting of accurate measurement; and that the space for the flow of water increases as the quantity to be measured increases, but still continues such as to admit of accurate measurement.

“Further, the ordinary rectangular notch, when applied for the gauging of rivers, is subject to a serious objection from the difficulty or impossibility of properly taking into account the influence of the bottom of the river on the flow of the water to the notch. If it were practicable to dam up the river so deep that the water would flow through the notch as if coming from a reservoir of still water, the difficulty would not arise. This, however, can seldom be done in practice, and although the bottom of the river may be so far below the crest as to produce but little effect on the flow of the water when the quantity flowing is small, yet when the quantity becomes great, the velocity of approach comes to have a very material influence on the flow of the water, but an influence which is usually difficult, if not impracticable, to ascertain with satisfactory accuracy. In the notches now proposed of a triangular form, the influence of the bottom may be rendered definite, and such as to affect alike (or at least by some law that may be readily determined by experiment) the flow of the water when very small, or when very great, in the same notch. The method by which I propose that this may be effected consists in carrying out a floor, starting exactly from the vertex of the notch, and extending both up-stream and laterally, so as to form a bottom to the channel of approach, which will both be smooth and will serve as the lower bounding surface of a passage of approach

unchanging in form while increasing in magnitude, at the places at least which are adjacent to the vertex of the notch. The floor may be either perfectly level, or may consist of two planes, whose intersection would start from the vertex of the notch, and would pass upstream perpendicularly to the direction of the weir board; the two planes slanting upwards from their intersection more gently than the sides of the notch. The level floor, although theoretically not quite so perfect as the floor of two planes, would probably for most practical purposes prove the more convenient arrangement.

“With reference to the use of the floor it may be said, in short, that by a due arrangement of the notch and the floor, a discharge orifice and channel of approach may be produced, of which (the upper surface of the water being considered as the top of the channel and orifice) the form will be unchanged or but little changed, with variations of the quantity flowing; very much less certainly than is the case with rectangular notches.

“Whatever may be the result in this respect, the main object must be to obtain, for a moderate number of triangular notches of different forms, and both with and without floors at the passage of approach, the necessary coefficients for the various forms of notches and approaches selected, and for various depths in any one of them, so as to allow of water being gauged for practical purposes, when in future convenient, by means of similarly formed notches and approaches. The utility of the proposed system of gauging it is to be particularly observed, will not depend upon a

perfectly close agreement of the theory described with the experiments, because a table of experimental coefficients for various depths, or an empirical formula slightly modified from the theoretical one, will serve all purposes.

“To one evident simplification in the proposed system of gauging, as compared with that by rectangular notches, I would here advert, namely, that in the proposed system the quantity flowing comes to be a function of only one variable—namely, the measured head of water—while in the rectangular notches it is a function of at least two variables, namely, the head of water, and the horizontal width of the notch; and is commonly also a function of a third variable very difficult to be taken into account, namely, the depth from the crest of the notch down to the bottom of the channel of approach, which depth must vary in its influence with all the varying ratios between it and the other two quantities of which the flow is a function.

“The proposed system of gauging also gives facilities for taking another element into account which often arises in practice—namely, the influence of back water on the flow of the water in the gauge, when, as frequently occurs in rivers, it is found impracticable to dam the river up sufficiently to give it a clear overfall free from the back or tail water. For any given ratio of the height of the tail water above the vertex of the notch to the height of head water above the vertex of the notch, I would anticipate that the quantities flowing would still be approximately at least, proportional to the $\frac{2}{3}$ power of the

head, as before ; and a set of coefficients would have to be determined experimentally for different ratios of the height of the head water to the height of the tail water above the vertex of the notch.

"I have got some preliminary experiments made on a right-angled notch in a vertical plane surface, the sides of the notch making angles of 45° with the horizon, and the flow being from a deep and wide pool of quiet water, and the water thus approaching the notch uninfluenced by any floor or bottom. The principal set of experiments as yet made were on quantities of water varying from about 2 to 10 cubic feet per minute ; and the depths or heads of the water varied from 2 inches to 4 inches in the right-angled notch. From these experiments I derive the formula

$$q = 0.317 H^{\frac{5}{2}}$$


where q is the quantity of water in cubic feet per minute, and H the head as measured vertically in inches from the still water level of the pool down to the vertex of the notch. This formula is submitted at present temporarily as being accurate enough for use for ordinary practical purposes for the measurement of water by notches similar to the one experimented on, and for quantities of water limited to nearly the same range as those in the experiments ; but as being, of course, subject to amendment by more perfect experiments extending through a wider range of quantities of water."

In the first edition of this book we gave the general form of the equation for the discharge through triangular notches, and also showed the general application of the coefficients .617 to .628 for all forms of

orifices and notches in thin plates. 617, as shown in note p. 42, gives a result identical with the practical results of Professor Thomson's experiments. The great advantage of the triangular notch for gauging is, that the sections for all depths flowing over are similar triangles, and therefore the coefficient probably remains constant, or nearly so, not only for one but for all species of triangles, when the depth at the apex is not very small indeed in proportion to the width flowing over at the surface.

The disadvantage of the proposed triangular form of depression, if permanent in a dam, would be that the angular point should be at a lower level than the top of a horizontal crest to maintain the same level, above of the water, during floods; and therefore the power of the water and head would be reduced at the period when most required for mill-power or navigation purposes; that is, during dry weather. For drainage purposes the winter level or that during floods, must evidently be kept down, unless when the banks are steep, and along rapids; but these remarks do not apply to dams erected across millraces or streams where the banks are, generally, considerably above floods; they only refer to occasions for permanent gauging, to find the relations of evaporation, absorption, and discharge for large catchment areas. For notch gauging, to determine the useful effect of water engines, rectangular forms in thin plates have the coefficients already well determined, and the calculations are easy. Rivers and large quantities of flowing water in the absence of a weir, are best gauged by selecting some portion where the section and velocity are nearly

uniform and determining each of these from the soundings, and the observed velocities between them, from bank to bank. The jagged, loose and irregular crests on most mill-weirs are unfit to gauge from.



In weirs at right angles to channels with parallel sides, the sectional area can never equal that of the channel unless it be mea-

sured at or above the point A, where the sinking of the overfall commences; and unless also the bed C D and surface A B have the same inclination. In all open channels, as millraces, streams, rivers, the supply is derived from the surface inclination of A B, and this inclination regulates itself to the discharging power of the overfall. When the overfall and channel have the same width, and the latter is considerable, then, as shall appear hereafter, $91 \sqrt{h s}$ is the mean velocity in the channel, where h is the depth in feet and s the rate of inclination of the surface A B. Also $\frac{2}{3} \sqrt{2 g h}$ is the theoretical velocity of discharge at the overfall, of equal depth with the channel, and, when both velocities are equal,


$$\frac{2}{3} \sqrt{2 g h} = 5.35 \sqrt{h} = 91 \sqrt{h s};$$

from which is found

$$s = \frac{1}{289} = .00346,$$

the inclination of B A when the supply is equal to the theoretical discharge at the overfall. If the coefficient

at the overfall were $\cdot 628$, or, which is nearly the same thing, if a large and deep weir basin intervene between the weir and channel, Fig. 19, Δa would be level, the



velocity of approach would be destroyed, and then

$$5.85 \times \cdot 628 \sqrt{h} = 3.36 \sqrt{h} = 91 \sqrt{hs};$$


and thence the inclination of $B A$ is

$$s = \frac{1}{734} = \cdot 00136$$

very nearly. When discussing the surface inclination of rivers, it will be seen that the conditions here assumed and the resulting surface inclinations would produce velocities that would destroy the regimen and involve a considerable loss of head. If the quantity discharged under both circumstances be the same, and h be the depth in the first case, Fig. 18, then the head in the latter case, Fig. 19, is equal $\left(\frac{5.35}{3.36}\right)^3 h = 1.36 h$ very nearly, from which and the surface inclination the extent of the backwater may be found with sufficient accuracy. When, in Fig. 19, the inclination of $A B$ exceeds $\frac{1}{734}$, the head at a must exceed the depth of the river above A . Further on, SECTION X., some remarks will be found on the backwater curve.

SECTION V.

SUBMERGED ORIFICES AND WEIRS.—CONTRACTED RIVER CHANNELS.



The available pressure at any point in the depth of the orifice A, Fig. 20, is equal to the difference of the pressures on each side.


This difference is equal to the pressure due to the height h , between the water surfaces on each side of the orifice; in this case, the velocity is

$$(47.) \quad v = c_d \sqrt{2 g h};$$

and the discharge

$$(48.) \quad D = l d c_d \sqrt{2 g h};$$

in which, as before, l is the length, and d the depth of the rectangular orifice A.



When the orifice is partly submerged, as in Fig. 21, $h_b = h = d_2$ may be put for the submerged depth, and $h - h_i = d_1$, the remaining

portion of the depth; whence $d_1 + d_2 = d$ is the entire depth. The discharge through the submerged depth

d_2 is $c_d l d_2 \times \sqrt{2 g h}$, and the discharge through the upper portion d_1 is

$$\frac{2}{3} c_d l \sqrt{2 g} \{h^{\frac{3}{2}} - h_1^{\frac{3}{2}}\};$$

whence the whole discharge—assuming the coefficient of discharge c_d is the same for the upper and lower depths—is

$$(49.) \quad D = c_d l \sqrt{2 g} \left\{ d_2 \sqrt{h} + \frac{2}{3} (h^{\frac{3}{2}} - h_1^{\frac{3}{2}}) \right\}$$

We may, however, equation (31), assume that

$$\frac{2}{3} c_d l \sqrt{2 g} (h^{\frac{3}{2}} - h_1^{\frac{3}{2}}) = c_d d l \sqrt{2 g} \left(h - \frac{d_1}{2} \right)$$

very nearly, and hence

$$(50.) \quad D = c_d l d_2 \sqrt{2 g h} + c_d l d \sqrt{2 g \left(h_1 - \frac{d_1}{2} \right)}.$$

As $h_1 + \frac{d_1}{2} = h - \frac{d_1}{2}$ this equation may be changed into

$$(51.) \quad D = c_d l d_2 \sqrt{2 g h} + c_d l d_1 \sqrt{2 g \left(h_1 + \frac{d_1}{2} \right)}.$$


In either of these forms the values of

$$c_d \sqrt{2 g h}, c_d \sqrt{2 g \left(h - \frac{d_1}{2} \right)}, \text{ and } c_d \sqrt{2 g \left(h_1 + \frac{d_1}{2} \right)}$$

can be had from TABLE II., and the value of the discharge D thence easily found. When $h - h_a = h_b - h$, the mean value of c_d may be taken at about .585; that is when the backwater rises to the centre of the orifice.

When the water approaches the orifice with a determinate velocity, the height h_a due to that velocity can be found from TABLE II., and the discharge is

then found by substituting $h+h_s$ and h_t+h_s for h and h_t in the above equations.



In the submerged weir, Fig. 22, h becomes equal to d_1 , and $h_t=0$; the discharge, equation (49), then becomes

$$(52.) \begin{cases} D = c_d l d_2 \sqrt{2g d_1} + \frac{2}{3} c_d l d_1 \sqrt{2g d_1}, \text{ or} \\ D = c_d l \sqrt{2g d_1} \left\{ d_2 + \frac{2}{3} d_1 \right\}. \end{cases}$$

When the water approaches with a velocity due to the height h_s , then h becomes $h+h_s$, $h_t=h_s$, and equation (49) becomes

$$(53.) D = c_d l \sqrt{2g} \left\{ d_2 \sqrt{d_1 + h_s} + \frac{2}{3} (d_1 + h_s)^{\frac{3}{2}} - h_s^{\frac{3}{2}} \right\}.$$

IN THE IMPROVEMENT OF THE NAVIGATION OF RIVERS, it is sometimes necessary to construct weirs so as to raise the upper waters by a given depth, d_1 . The discharge D is in such cases previously known, or easily determined, then from the values of d_1 , and D , and equation (52), the value of the rise over the crest,

$$(54.) d_2 = \frac{D}{c_d l \sqrt{2g d_1}} - \frac{2}{3} d_1;$$

or, by taking the velocity of approach into account,

$$(55.) d_2 = \frac{D}{c_d l \sqrt{2g (d_1 + h_s)}} - \frac{2}{3} \frac{(d_1 + h_s)^{\frac{3}{2}} - h_s^{\frac{3}{2}}}{\sqrt{d_1 + h_s}}.$$

This value of d_2 must be the depth of the top of the weir below the original surface of the water, in order

that this surface should be raised by a given depth, d_1 . When h_a is small compared with d_2 , $\frac{2}{3} (d_1 + h_a)$ may be put for $\frac{2}{3} \times \frac{(d_1 + h_a)^{\frac{3}{2}} - (h_a)^{\frac{3}{2}}}{\sqrt{d_1 + h_a}}$ in equation (55).

EXAMPLE VI.—*A river whose width at the surface is 70 feet, whose hydraulic mean depth is 4.4 feet, and whose cross sectional area is 325 feet, has a surface inclination of 1 foot per mile; to what depth below, or height above the surface must a weir at right angles to the channel be raised, so that the depth of water immediately above it shall be increased by $3\frac{1}{2}$ feet?*

When the hydraulic mean depth is 4.4 feet, and the fall per mile 1 foot, from TABLE VIII. the mean velocity of the river is 29.98 or 30 inches very nearly per second. The discharge is, therefore, $325 \times 2\frac{1}{2} = 812.5$ cubic feet per second, or 48750 cubic feet per minute. Hence, $\frac{48750}{70} = 696.4$ cubic feet, must pass over each foot in length of the weir per minute. Assuming the coefficient $c_d = .628$ in the first instance, from TABLE VI. the head passing over a weir corresponding to this discharge is 27.4 inches; but as the head is to be increased by $3\frac{1}{2}$ feet, or 42 inches, it is clear that the weir must be *perfect*; that is, have a clear overfall, and rise $42 - 27.4 = 14.6$ inches over the original water surface. In order that the weir may be submerged, or *imperfect*, the head could not be increased by more than 27.4 inches. *Therefore, assume the EXAMPLE, that the increase shall be only 18 instead of 42 inches; the weir then becomes submerged, and, from equation (54),*

$$d_1 = \frac{696.4}{.628 \sqrt{18'' \times 2g}} - \frac{2}{3} \times 18'' \text{ (as } l = 1 \text{ foot).}$$

The value of the first part of this expression is found from TABLE VI. or TABLE II. equal to

$$\frac{696.4}{\frac{12}{18} \times \frac{2}{3} \times 370.841} = \frac{696.4}{370.841} = 1.88 \text{ feet} = 22.56 \text{ in.};$$

$$\text{hence } 22.56 - \frac{36}{3} = 10.56 \text{ inches is the value of } d_1;$$

that is, the submerged weir must be built within 10.56 inches of the surface to raise the head 18 inches above the former level. If, however, the velocity of approach be taken into account, it is equal to $\frac{812.5}{480} = 2$ feet per second very nearly; and the height, or value of h_v , due to this velocity, taken from TABLE II., is $\frac{2}{4} = .75$ inch nearly; therefore, from equation (55),

$$d_2 = \frac{696.4}{.628 \sqrt{2g \times 18.75}} - \frac{2}{3} \times \frac{(18.75)^{\frac{3}{2}} - (.75)^{\frac{3}{2}}}{\sqrt{18.75}}.$$

$$\text{The value of } \frac{696.4}{.628 \sqrt{2g \times 18.75}} = \text{(from TABLE VI.)}$$

$$\text{is } \frac{696.4}{\frac{2}{3} \times \frac{12}{18.75} \times 399.75} = \frac{696.4}{378.8^*} = 1.84 \text{ feet} = 22.08 \text{ in.};$$

$$\begin{aligned} \text{also } \frac{2}{3} \times \frac{(18.75)^{\frac{3}{2}} - (.75)^{\frac{3}{2}}}{\sqrt{18.75}} &= \frac{2}{3} \times 18.75 - \frac{2}{3} \times \frac{(.75)^{\frac{3}{2}}}{\sqrt{18.75}} \\ &= 12.5 - \frac{2}{3} \times \frac{.65}{4.89} = 12.5 - .1 = 12.4. \end{aligned}$$

Hence $d_2 = 22.08 - 12.4 = 9.68$ inches, or about 1 inch less than the value previously found from equa-

* This is found from TABLE II. more readily.

tion (54). The mean coefficient of discharge was here assumed to be $\cdot 628$. Experiments on submerged weirs show that the value of c_d varies from $\cdot 5$ up to $\cdot 8$, but as this coefficient would reduce the value of d_2 , or the depth of the top of the weir below the surface, it is safer (where a given depth above a weir must be obtained) to use the lesser and ordinary coefficients of perfect weirs, with a clear overfall, for finding the crest levels of submerged weirs, when it is necessary to construct them. If the coefficient $\cdot 8$ were used in the previous calculation, then would have been found $d_2 = \frac{\cdot 628 \times 22\cdot 08}{\cdot 8} - 12\cdot 4 = 17\cdot 33 - 12\cdot 4 = 4\cdot 93$ in., or

not much more than half the previous value; and this would only increase the whole height of the weir by $9\cdot 68 - 4\cdot 93 = 4\cdot 75$ inches.

As $D = \frac{2}{3} c_d l \sqrt{2g} \{(d_1 + h_s)^{\frac{3}{2}} - h_s^{\frac{3}{2}}\}$ for a perfect weir with a free overfall, it is clear that when D is greater than $\frac{2}{3} c_d l \sqrt{2g} \{(d_1 + h_s)^{\frac{3}{2}} - h_s^{\frac{3}{2}}\}$, the weir is imperfect or submerged. For backwater curve see SECTION X.

In the following table of coefficients from Lesbros* d_2 is measured from that point below the weir where its value is a minimum. On examining equation (52), it will be seen that the equation $D = c_d l (d_1 + d_2) \sqrt{2g d_1}$ adopted by Lesbros is incorrect, and can only be safely used within the limits of his experiments.

* *Vide* p. 84, deuxième édition, Hydraulique, par Arthur Morin, Paris, 1858.

COEFFICIENTS FOR SUBMERGED NOTCHES.

Values of $\frac{d_1}{d_1 + d_2}$	Values of the coefficient c_d in the formula $D = c_d l (d_1 + d_2)$ $\times \sqrt{2 g d_1}$	Values of $\frac{d_1}{d_1 + d_2}$	Values of the coefficient c_d in the formula $D = c_d l (d_1 + d_2)$ $\times \sqrt{2 g d_1}$
·001	·227	·060	·519
·002	·295	·080	·517
·003	·363	·100	·516
·004	·430	·150	·512
·005	·496	·200	·507
·006	·556	·250	·502
·007	·597	·300	·497
·008	·605	·350	·492
·009	·600	·400	·487
·010	·596	·450	·480
·015	·580	·500	·474
·020	·570	·550	·466
·025	·557	·600	·459
·030	·546	·700	·444
·035	·537	·800	·427
·040	·531	·900	·409
·045	·526	1·000	·390
·050	·522	„	„

The experimental values are those shown between the horizontal lines, the others above the upper ones, and below the lower ones, were deduced from calculation by Lesbros.

The true value of the discharge is expressed by the equation $D = c_d l \left\{ \frac{2}{3} d_1 + d_2 \right\} \times \sqrt{2 g d_1}$, and the values of c_d in the above table are, therefore, too small, applied to the correct formula. When $d_1 = d_2$ the table gives $c_d = \cdot 474$. Now for weirs in which the sheet passing over is "drowned," the general value of the coefficient is about $\cdot 67$; this would give the coefficient for the lower portion d_2 , in the true formula, equal to $\cdot 503$, and a mean coefficient c_d in the correct formula (52) equal to $\cdot 569$ nearly. When $d_2 = 200 d_1$, the apparent limits of the experiments on the other side, then

the mean value of $c_d = .496$ nearly in equation (52). These results would show that the coefficient due to the submerged depth d_2 , in the first and last experiments, is equal to about .5 nearly, (but varies to .6 nearly in some of the middle experiments,) or thereabouts, and, therefore, equation (52) for submerged weirs, as the coefficient for the upper part d_1 is .67, would become

$$(52A.) \quad D = l \times \{.445 d_1 + .5 d_2\} \times \sqrt{2 g d_1};$$


which for feet measures would become again

$$(52B.) \quad D = l \times \sqrt{d_1} \times \{3.56 d_1 + 4 d_2\},$$

for the discharge in cubic feet per second over a submerged weir, Fig. 22.

CONTRACTED RIVER CHANNELS.

When the banks of a river, whose bed has a uniform inclination, approach each other, and contract the width of the channel in any way, as in Fig. 23, the



water will rise in the channel above the contracted portion A, until the increased velocity of discharge compensates for the reduced cross section. If, as before, d_1 be put for the increase of depth immediately above the contracted width, and d_2 for the previous depth of the channel, the quantity of water passing through the lower depth, d_2 , is equal to $c_d l d_2 \sqrt{2 g d_1}$, in which l

is the width of the contracted channel at A, and the quantity of water overflowing through d_1 equal to $\frac{2}{3} \times c_d l d_1 \sqrt{2 g d_1}$; and hence the whole discharge through A is

$$(56.) \quad D = c_d l \sqrt{2 g d_1} \left(d_2 + \frac{2}{3} d_1 \right).$$

When the object is to find the width l of the contracted channel, so that the depth of water in the upper stretch shall be increased by a given depth d_1 , then shall

$$(57.) \quad l = \frac{D}{c_d \sqrt{2 g d_1} \left(d_2 + \frac{2}{3} d_1 \right)}$$

When the velocity of approach is considerable, or when the height h_a due to it becomes a large portion of d_1 , its effect must not be neglected. In this case, as before, the discharge through the depth d_2 is equal to $c_d l d_2 \times \sqrt{2 g (d_1 + h_a)}$; and the discharge through the depth d_1 equal to $\frac{2}{3} c_d l \sqrt{2 g} \{ (d_1 + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}} \}$; and hence the whole discharge is

$$(58.) \quad D = c_d l \sqrt{2 g} \left\{ d_2 (d_1 + h_a)^{\frac{1}{2}} + \frac{2}{3} [(d_1 + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}}] \right\};$$

from which may be found

$$(59.) \quad l = \frac{D}{c_d \sqrt{2 g} \left\{ d_2 (d_1 + h_a)^{\frac{1}{2}} + \frac{2}{3} [(d_1 + h_a)^{\frac{3}{2}} - h_a^{\frac{3}{2}}] \right\}}.$$

If the projecting spur or jetty at A be itself submerged, these formulæ must be extended; the manner of doing so, however, presents no difficulty, as it is only necessary to find the discharges of the different sections according to the preceding formulæ, and then add them together; but the resulting formula so

found is too complicated to be of much practical value.

HEADS ARISING FROM PIERS AND BACKWATER ABOVE BRIDGES.

Equations (56), (57), (58), and (59), are applicable to cases of contraction of river channels caused by the construction of bridge-piers and abutments, when the width l is put for the sum of the openings between them. The value of the coefficient c_d will depend on the peculiar circumstances of each case; it was shown that it rises from $\cdot 5$ to $\cdot 7$ in some cases of submerged weirs, and for cases of contracted channels it rises sometimes as high as $\cdot 8$, particularly when they are analogous to those for the discharge through mouth-pieces and short tubes. When the heads of the piers are square to the channel, the coefficient may be taken at about $\cdot 6$; when the angles of the cut-waters or sterlings are obtuse, it may be taken at about $\cdot 7$; and when curved and acute, at $\cdot 8$. With this coefficient, a head of $2\frac{1}{2}$ inches will give a velocity of very nearly 36 inches, or 3 feet per second; but as a certain amount of loss takes place from the velocity of the tail-water being in general less than that through the arch, also from obstructions in the passage, and from square-headed and very short piers, the coefficient may be so small in some cases as $\cdot 5$, which would require a head of $6\frac{1}{2}$ inches to obtain the same velocity. This head is to the former as 54 to 21. The selection of the proper coefficient suited to any particular case is, therefore, a matter of the first importance in determining the effect

of obstructions in river channels : this subject shall be referred to again, but it is necessary to observe here, that the form of the approaches, the length of the piers compared with the distance between them, or span, and the length and form of the obstruction compared with the width of the channel, must be duly considered before the coefficient suited to the particular case can be fixed upon. Indeed, the coefficients will always approximate towards those, given in the next section, for mouth-pieces, shoots, and short tubes similarly circumstanced. For some further remarks on contracted channels, see SECTION X.


SECTION VI.

SHORT TUBES, MOUTH-PIECES, AND APPROACHES.—ALTERATION IN THE COEFFICIENTS FROM FRICTION BY INCREASING THE LENGTH.—COEFFICIENTS OF DISCHARGE FOR SIMPLE AND COMPOUND SHORT TUBES.—SHOOTS.

The only orifices heretofore referred to were those in thin plates or planks, with a few incidental exceptions. It has been shown, page 36, Fig. 4, that a rounding off, next the water, of the mouth-piece increases the coefficient ; and when the curving assumes the form of the *vena-contracta*, the coefficient increases to .986, or nearly unity for the outer orifice. The discharge from a short cylindrical tube A, Fig. 24, whose length is from one and a half to three times the diameter, is found to be very nearly an arithmetical mean between

the theoretical discharge and the discharge through a circular orifice in a thin plate of the same diameter as the tube, or $\cdot 814$ nearly. If, however, the inner arris be rounded, or chamfered off in any way, the coefficient will increase until, in the tube B, Fig. 24, with a properly-rounded junction, it becomes unity very nearly.

Fig. 24.



In the conical short tubes c and d the coefficients are found to vary according to some function of the converging or diverging angles θ , θ , and according as the lesser or greater diameter is taken to calculate from. When the length of the tube exceeds twice the diameter, the friction of the water against the sides may be taken into account.

The following table, calculated, for a coefficient of friction $\cdot 00699$, due to a discharging *velocity of about eighteen inches per second*, see SECTION VIII., shows the resistance arising from friction in pipes of different lengths in relation to the diameter, and will be found of considerable practical value. It will be perceived that the calculations are made for three different orifices of entry. First, when the arrises are rounded, as in B, Fig. 24, with a coefficient of $\cdot 986$; secondly,

COEFFICIENTS FOR SHORT AND LONG TUBES.

Velocities about 1·5 foot per second.

Number of diameters in the length of the pipe.	Corresponding coefficients of discharge, showing the effects of friction.			Number of diameters in the length of the pipe.	Corresponding coefficients of discharge, showing the effects of friction.		
2 diameters	·986	·814	·715	650 diameters	·228	·225	·223
5 "	·986	·779	·690	700 "	·220	·217	·215
10 "	·884	·747	·668	750 "	·213	·211	·209
15 "	·840	·720	·649	800 "	·206	·205	·203
20 "	·801	·695	·630	850 "	·201	·199	·197
25 "	·767	·673	·615	900 "	·195	·193	·192
30 "	·737	·653	·598	950 "	·190	·189	·187
35 "	·711	·634	·584	1000 "	·186	·184	·183
40 "	·693	·617	·570	1100 "	·177	·176	·175
45 "	·665	·601	·558	1200 "	·170	·169	·168
50 "	·646	·586	·546	1400 "	·158	·157	·156
100 "	·513	·480	·458	1600 "	·148	·147	·146
150 "	·439	·418	·403	1800 "	·139	·139	·138
200 "	·389	·375	·364	2000 "	·132	·132	·131
250 "	·354	·345	·334	2200 "	·126	·126	·125
300 "	·327	·318	·311	2400 "	·120	·120	·120
350 "	·304	·297	·292	2600 "	·116	·116	·116
400 "	·287	·280	·276	2800 "	·112	·112	·112
450 "	·271	·266	·262	3000 "	·108	·108	·108
500 "	·258	·254	·250	3200 "	·105	·105	·104
550 "	·247	·243	·240	3400 "	·102	·102	·101
600 "	·237	·234	·231	3600 "	·099	·099	·099

See p. 199.

when the arrises are square, as in A, with a coefficient of ·815; and, thirdly, when the pipe projects into the vessel, when the coefficient of entry becomes reduced to ·715. The velocity is

$$v = c_d \sqrt{2gh},$$

h being measured to the centre; lower end of the tube.

It is seen from this table, that the effect of adding to the length of the pipe is greatest next the orifice of entry. The effect of a few diameters added to the length in long pipes is, practically, immaterial; but in short pipes it is considerable.

As for orifices in thin plates, so also for short tubes, the coefficients are found to vary according to the depth of the centre below the surface of the water, and to increase as the depths and diameter of the tube decrease. Poleni first remarked that the discharge through a short tube was greater than that through a simple orifice, of the same diameter, in the proportion of 133 to 100, or as $\cdot 617$ to $\cdot 821$.

CYLINDRICAL SHORT TUBES, A, FIG. 24.

The experiments of Bossût, as reduced by Prony, give the following coefficients, at the corresponding depths, for a cylindrical tube A, Fig. 24, 1 inch in diameter and 2 inches long. The depths are given in

COEFFICIENTS FOR SHORT TUBES, FROM BOSSÛT.

Heads in feet.	Coefficients.	Heads in feet.	Coefficients.	Heads in feet.	Coefficients.
1	$\cdot 818$	6	$\cdot 806$	11	$\cdot 805$
2	$\cdot 807$	7	$\cdot 806$	12	$\cdot 804$
3	$\cdot 807$	8	$\cdot 805$	13	$\cdot 804$
4	$\cdot 807$	9	$\cdot 805$	14	$\cdot 804$
5	$\cdot 806$	10	$\cdot 805$	15	$\cdot 803$

Paris feet in the original, but the coefficients remain the same, practically, for depths in English feet.

Venturi's experiments give a coefficient $\cdot 823$ for a short tube A, $1\frac{1}{2}$ inch in diameter and $4\frac{1}{2}$ inches long, at a depth of 2 feet $8\frac{1}{2}$ inches, the coefficient through an orifice in a thin plate of the same diameter and at the same depth being $\cdot 622$. The author has calculated these coefficients, from the original experiments. The measures were in Paris feet and inches, from which the calculations were directly made; and as the differ-

ence in the coefficient for small changes of depth or dimensions is immaterial or vanishes, as may be seen by the foregoing small table, and as 1 Paris inch or foot is equal to 1.0658 English inches or feet, the former measures exceed the latter by only about $\frac{1}{15}$ th. It may therefore be assumed that the coefficient for any orifice, at any depth, is the same, whether the dimensions be in Paris or English feet, or inches. This remark will be found generally useful in the consideration of the older continental experiments, and will prevent unnecessary reductions from one standard to another where the coefficients only have to be considered.

The mean value derived from the experiments of Michelotti, at depths from 3 to 20 feet, and with short tubes A from $\frac{1}{2}$ inch to 3 inches in width, is $c_d = .814$. Buff's experiments* give the following results for a tube $\frac{1}{8}$ of an inch wide and $\frac{1}{10}$ of an inch long nearly.

BUFF'S COEFFICIENTS FOR SMALL SHORT TUBES.

Head in inches.	Coefficient.	Head in inches.	Coefficient.	Head in inches.	Coefficient.
1 $\frac{1}{2}$.855	6	.840	23	.829
2 $\frac{1}{2}$.861	14	.840	32	.826

The increase for smaller tubes and for lesser depths appears by comparing these results with the foregoing, and from the results in themselves, generally. Weisbach's experiments give a mean value for $c_d = .815$, and for depths of from 9 to 24 inches the coefficients .843, .832, .821, .810 respectively, for tubes $\frac{4}{10}$, $\frac{8}{10}$, $\frac{12}{10}$ and $\frac{16}{10}$ of an inch wide, the length of each tube being three times the

* Annalen der Physik und Chemie von Poggendorff, 1839, Band 46, p. 248.

diameter. D'Aubuisson and Castel's experiments with a tube .61 inch diameter and 1.57 inch long, give .829 for the coefficient at a depth of 10 feet. When a pipe projects into a cistern and has a sharp edge, the coefficient falls so low as .715.

The coefficients in the following two short tables were calculated by the author from Rennie's experiments with glass orifices and tubes, TABLE 7, p. 435, Philosophical Transactions for 1831. The form of the orifices, or length of the shorter tubes is not stated, but it is probable from the result, that the arrises of the ends were in some way rounded off; it is stated they were "enlarged." Indeed, the discharges from the short tube or orifice of $\frac{1}{4}$ inch

COEFFICIENTS FOR SHORT TUBES, THE ENDS ENLARGED.

Head in feet.	$\frac{1}{4}$ inch diameter.	$\frac{1}{2}$ inch diameter.	$\frac{3}{4}$ inch diameter.	1 inch diameter.
1	1.231	.831	.766	.912
2	1.261	.839	.820	.920
3	1.346	.838	.821	.880
4	1.261	.831	.829	.991

diameter exceed the theoretical ones in the proportion of 1.261 to 1, and 1.346 to 1. These results could not have been derived from a simple cylindrical tube, but might have arisen from the arrises being more or less rounded at both ends, and the orifice partaking of the nature of a compound tube, which may be constructed, as shall hereafter be shown, so as to increase the theoretical discharge from 1 up to 1.553. The resulting coefficients for the $\frac{1}{2}$ and $\frac{3}{4}$ inch tubes, approach very closely to those obtained by other

experimenters, but those for the inch tube are too high, unless the arris at the ends was also rounded. The coefficients derived from the experiments with a cylindrical glass tube 1 foot long, as here given, are very variable; like the others they are,

COEFFICIENTS DERIVED FROM EXPERIMENTS WITH A GLASS TUBE
ONE FOOT LONG.

Heads in feet.	$\frac{1}{2}$ inch diameter.	$\frac{3}{4}$ inch diameter.	$\frac{7}{8}$ inch diameter.	1 inch diameter.
1	.892	.703	.691	.760
2	.914	.734	.718	.749
3	.831	.723	.709	.777
4	.914	.725	.677	.815

however, valuable, as exhibiting the uncertainty attending "experiments of this nature," and the necessity for minutely observing and recording every circumstance which tends to alter and modify them. Indeed, for small tubes, a very slight difference in the measurement of the diameter must alter the result a good deal, particularly when it is recollected that measurements are seldom taken more closely than the sixteenth of an inch, unless in special cases. As the author, however, states, p. 433 of the work referred to, that the "diameters of the tubes at their extremities were carefully enlarged to prevent wire edges from diminishing the sections;" this circumstance alone must have modified the discharges, and would account for most of the differences.

The coefficient for rectangular short tubes differs in no way materially from those given for cylindrical ones, and may be taken on an average at .814 or .815.

SHORT TUBES WITH A ROUNDED MOUTH-PIECE, B,
FIG. 24.

When the junction of a short tube with a vessel takes the form of the contracted vein, Figs. 3 and 4, pp. 35 and 36, the mean value of the coefficient $c_d = \cdot 956$, and the actual discharge is found to be from 93 to 99 per cent. of the theoretical discharge. Weisbach, for a tube $1\frac{1}{2}$ inch long and $\frac{1}{16}$ inch diameter, rounded at the junction, found at 1 foot deep $c_d = \cdot 958$, at 5 feet deep $c_d = \cdot 969$, and at 10 feet deep $c_d = \cdot 975$. These experiments show an increase in the coefficients, in this particular case, for an increase of depth. Any other form of junction than that of the contracted vein, will reduce the discharge, and the coefficients will vary from $\cdot 715$ to $\cdot 814$, and to $\cdot 986$, according to the change in the junction from the cylindrical, projecting into the vessel, to the square and properly curved forms. The coefficients derived from Venturi's experiments will be given hereafter.

SHORT CONICAL CONVERGENT TUBES, C, FIG. 24.

The experiments of D'Aubuisson and Castel lead to the following coefficients of discharge and velocity* from a conically convergent tube c at a depth of 10 feet. The original angles and coefficients are here interpolated so as to render the table more convenient to refer to, for practical purposes, than the original. The diameter of the tube at the smaller or discharging orifice in the experiments was $\cdot 61$ inches, and the

* *Traité d'Hydraulique*, Paris, p. 60.

COEFFICIENTS FOR CONICAL CONVERGENT TUBES.

Con- verging angle ϕ .	Coefficient of dis- charge.	Coefficient of velocity.	Con- verging angle ϕ .	Coefficient of dis- charge.	Coefficient of velocity.
1°	·858	·858	14°	·943	·964
2°	·873	·873	16°	·937	·970
3°	·908	·908	18°	·931	·971
4°	·910	·909	20°	·922	·971
5°	·920	·916	22°	·917	·973
6°	·925	·923	26°	·904	·975
8°	·931	·933	30°	·895	·976
10°	·937	·950	40°	·869	·980
12°	·942	·955	50°	·844	·985

length of the axis 1·57 inch; that is, the length was 2·6 times the smaller diameter of the tube. The coefficient became ·829 for the cylindrical tube, *i. e.* when the angle at ϕ was nothing. The angle of convergence ϕ determines, from the proportions, the length of the inner and longer diameter of the tube. The coefficients of discharge increase up to ·943 for an angle of $13\frac{1}{2}$ or 14 degrees, after which they again decrease; but the coefficients of velocity increase as the angle of convergence, ϕ , increases from ·829, when the angle is zero up to ·985 for an angle of 50 degrees.

When D is the discharge and A the area of the section, as before shown, $D = c_d A \sqrt{2gh}$; but as, in conically convergent or divergent tubes, the inner and outer areas (or, as they may be called, the receiving and discharging sections) vary, it is clear that, the discharge being the same, and also the theoretical velocity $\sqrt{2gh}$, the coefficient c_d must vary inversely with the sectional area A , and that $c_d \times A$ must be constant. For the coefficients tabulated, the sectional

area to be used is that at the smaller or outside end of a convergent tube *c*, Fig. 24.

For a short tube *c*, whose length is .92 inch, lesser diameter 1.21 inch, and greater diameter 1.5 inch, the author has found, from Venturi's experiments, that $c_d = .607$ if the larger diameter be used in the calculation, and $c_d = .934$ when the lesser diameter is made use of, the discharge taking place under a pressure of 2 feet $8\frac{1}{2}$ inches.

The earlier experiments of Poleni, when reduced, furnish us with the following coefficients: A tube 7.67 inches long, 2.167 inches diameter at each end, gave $c_d = .854$; the like tube with the inner or receiving orifice increased to $2\frac{3}{4}$ inches, $c_d = .903$; increased to 3.5 inches, $c_d = .898$; increased to 5 inches, $c_d = .888$; and increased to 9.83 inches, $c_d = .864$. The depth or head was 21.33 inches, the discharging orifice 2.167 inches diameter, and the length 7.67 inches, in each case.

In the conically divergent tube *d*, Fig. 24, the coefficient of *discharge* is larger than for the same tube *c*, convergent, when the water fills both tubes, and the smaller sections, or those at the same distances from the centres *o o*, are made use of in the calculations. A tube whose angle of convergence, *o*, is 5, nearly, with a head of from 1 to 10 feet, whose axial length is $3\frac{1}{2}$ inches, smaller diameter 1 inch, and larger diameter 1.3 inch, gives, when placed as at *c*, .921 for the coefficient; but when placed as at *d*, the coefficient increases to .948. In the first case the smaller area, used in both calculations, being the receiving, and in the other the discharging, orifice.

The coefficient of *velocity* is, however, larger for the tube *c* than for the tube *d*, and the discharging jet of water has a greater amplitude in falling. The effects of conically diverging tubes will, however, be better perceived from the experiments on compound short tubes.


EFFECTS OF COMPOUND ADJUTAGES AND ADMISSION OF AIR INTO SHORT TUBES.

If the tube *A* Fig. 24, be pierced all round with small holes at the distance of about half its diameter from the reservoir, the discharge will be immediately reduced in the proportion of $\cdot 814$ to $\cdot 617$. Venturi found the reduction for a tube $1\frac{1}{2}$ inch diameter and $4\frac{1}{2}$ inches long, at a depth of 2 feet $10\frac{1}{2}$ inches, as 41 to 31, or as $\cdot 823$ to $\cdot 622$. As long as one hole remained open, the discharge continued at the same reduced rate; but when the last hole was stopped, the discharge again increased to the original quantity. If a small hole be pierced in a tube 4 diameters long, at the distance of $1\frac{1}{2}$ or 2 diameters at nearest to the junction, the discharge will remain unaffected. This shows that the contraction in the cylindrical tube extends only a short distance from the junction, probably $1\frac{1}{2}$ or $1\frac{1}{2}$ diameter, including the whole curvature of the contraction.

The contraction at the entrance into a tube from a reservoir accounts for the coefficients for a short tube *A*, Fig. 24, and the short tubes, diagrams 1 and 2, Fig. 25, being each the same decimal nearly, when $oR : or :: 1 : \cdot 8$, or when *or* is not less than $oR \times \cdot 79$,

and is at the distance of nearly $\frac{OR}{2}$ from $O R$. The form of the junction $o o r R$ remaining as described, the following coefficients will enable us to judge of the discharging powers of differently formed short mouth-pieces. They have been deduced and calculated, principally, from Venturi's experiments.*

Fig. 25.



These coefficients show very clearly that any calculations from the mere head of water and size of the orifice, without taking into consideration the form of the discharging tube and its connection with the reservoir, are very uncertain; and that the discharge can only be correctly obtained when all the circumstances of the case, including the form of the discharging orifice and its approaches have been duly considered.


When a tube similar to diagram 5, Fig. 25, has the junction $o o r R$ rounded, as in Fig. 4, page 36, the outer extremity $s t s T$, such that $s t = o r$, $s s = 9 s t$, and the diameter $s T = 1.8$ times the diameter $s t$, with a short central cylindrical piece $o r s t$ between, the

* See Nicholson's translation of Venturi's Experimental Inquiries, published in the Tracts on Hydraulics, London, 1836. The coefficients in the table, next page, were all calculated for the first time by the Author.

TABLE OF COEFFICIENTS FOR SHORT TUBES AND MOUTH-PIECES.

Description of orifice, mouth-piece, or short tube.	Coefficients for the diameter O R.	Coefficients for the diameter o r.
1. An orifice $1\frac{1}{2}$ inch diameter in a thin plate	·622	·974
2. A cylindrical tube $1\frac{1}{2}$ inch diameter and $4\frac{1}{2}$ inches long, A, Fig. 24	·823	·823
3. A short tube with a sharp end projecting into the cistern	·715	·715
4. A cylindrical tube, B, Fig. 24, having the junction rounded, as in Fig. 4, page 36	·611	·956
5. A short conical convergent mouth-piece, C, Fig. 24, of the proportions of O O R R, Fig. 25	·607	·934
6. The like tube divergent, with the smaller diameter at the junction with the reservoir; length $3\frac{1}{2}$ inches, lesser diameter 1 inch, and greater diameter $1\frac{3}{4}$ inch	·561	·948
7. The tube, O O U V R R, diagram 2, Fig. 25, when O R = $1\frac{1}{2}$ inch, O r = $1\cdot21$ inch, u v = $1\cdot21$ inch, and O u = r v = 2 inches, the cylindrical portion being shown by dotted lines	·600	·923
8. The same tube when O u = 11 inches	·567	·873
9. The same tube when O u = 23 inches	·531	·817
10. The tube, O O S S T T R R, diagram 2, Fig. 25, in which O r = s t = $1\frac{1}{2}$ inch, from O to s $1\frac{1}{2}$ inch, and s s = 3 inches, gives the same coefficient as the cylindrical tube, result No. 2 (see No. 19), viz.	·823	1·266
11. The tube, diagram 1, Fig. 25, O R = $1\frac{1}{2}$ inch	·804	1·237
12. The same tube, having the spaces O S O and T T R between the mouth-piece O O R R and the cylindrical tube O S T R open to the influx of the water	·785	1·209
13. The double conical tube, O O S T T R, diagram 3, Fig. 25, when O R = s t = $1\frac{1}{2}$ inch, O r = $1\cdot21$ inch, O s = $\cdot92$ inch, and O s = $4\cdot1$ inches	·923	1·428
14. The like tube when, as in diagram 4, Fig. 25, O O R R = O S T R, and O O S = $1\cdot84$ inch	·823	1·266
15. The like tube when, s t = $1\cdot46$ inch, and O s = $2\cdot17$ inches	·823	1·266
16. The like tube when s t = 3 inches, and O s = $9\frac{1}{2}$ inches	·911	1·400
17. The like tube when O s = $6\frac{1}{2}$ inches, and s t enlarged to $1\cdot92$ inch	1·020	1·569
18. The like tube when s t = $2\frac{1}{2}$ inches, and O s = $12\frac{1}{2}$ inches	1·215	1·855
19. A tube, diagram 5, Fig. 25, when O s = r t = 3 inches, O r = s t = $1\cdot21$ inch, and the tube O S T R the same as described in No. 12, viz. s t = $1\frac{1}{2}$ inch, and s s = $4\cdot1$ inches	·895	1·377
20. The tube, diagram 2, Fig. 25, when s t is enlarged to $1\cdot97$ inch, and s s to 7 inches, the other dimensions remaining as in No. 9	·945	1·454
21. When the junction of O S T R with s s r t, diagram 2, Fig. 25, is improved, the other parts remaining as described in No. 9	·850	1·309
22. Another experiment gives	·847	1·303

coefficient of discharge, corresponding to the diameter $or = rs$ will increase to 1.493 or 1.555; that is, the discharge is $\frac{1.493}{.622} = 2.4$, or $\frac{1.555}{.622} = 2.5$ times as much as through an orifice (whose diameter is or) in a thin plate; and $\frac{1.555}{.822} = 1.9$ times as much as through a short cylindrical tube A , Fig. 24, whose diameter is also or . Venturi was of opinion that this discharge continued even when the central cylindrical portion $orst$ was of considerable length; but this was a mistake, as the maximum discharge is obtained when it is reduced so that $oorR$ and $sstT$ shall join, as in diagram 3, Fig. 25. It is seen from No. 16 of the foregoing coefficients that $\frac{1.569}{.622} = 2.52$ and $\frac{1.569}{.822} = 1.91$ are, perhaps, nearer to the maximum results obtainable by comparing the discharge from a compound tube $oostRR$, diagram 3, Fig. 25, with those through an orifice in a thin plate, and through a short cylindrical tube. When the form of the tube becomes curvilinear throughout, as in Fig. 26, $st = 1.8 or$ and $os = 9 or$, the coefficient suited to the diameter or will be 1.57 nearly, and the discharge will be $\frac{1.57}{.622} = 2.52$ times as much as through an orifice or in a thin plate.



The whole of the preceding coefficients have been determined from circumstances in which the coefficient for an orifice in a thin plate was .622, and for a short cylindrical tube .822 or .823. When the circumstances of head and approaches in the reservoir

are such as to increase or decrease those primary coefficients, the other coefficients for compound adjutages will have to be increased or decreased proportionately.

After examining the foregoing results, it appears sufficiently clear that the utmost effect produced by the formation of the compound mouth-piece *o o s t r r*, with the exception of No. 17, is simply a restoration of the loss effected by contraction in passing through the orifice *o r* in a thin plate, and that the coefficient 2.5 applied to the contracted section at *o r* is simply equal to the theoretical discharge, or the coefficient unity, applied to the primary orifice *o r*; for, as orifice *o r* : orifice *o r* :: 1 : .64, very nearly, when *o o r r* takes the form of the *vena-contracta*, and the coefficient of discharge for an orifice *o r* in a thin plate is .622, then the ratio of the theoretical discharge through the orifice *o r*, is to the actual discharge through an orifice *o r*, so is 1 to $.622 \times .64$, so is 1 : .39808 :: 1 : .4 very nearly; and as $.4 \times 2.5 = 1$, it is clear that the form of the tube *o o s t r r*, when it produces the foregoing effect, simply restores the loss caused by contraction in the *vena-contracta*. Venturi's sixteenth experiment, from which the coefficients in No. 17 of the Table are derived, gives the coefficient 1.215 for the orifice *o r*. This indicates that a greater discharge than the theoretical through the receiving orifice may be obtained. It is, however, observable that Venturi, in his seventh proposition, does not rely on this result, and Eytelwein's experiments do not give a larger coefficient than 2.5 applied to the contracted orifice *o r*, which, as above shown, is equal to the theoretical discharge through *o r*.

SHOOTS.

When the sides and under edge of an orifice or notch increase in thickness, so as to be converted into a shoot or small channel, open at the top, the coefficients reduce very considerably, and to some extent beyond what the increased resistance from friction, particularly for small depths, appears to indicate. Poncelet and Lesbros* found for orifices $8'' \times 8''$, that the addition of a horizontal shoot 21 inches long reduced the coefficient from $\cdot 604$ to $\cdot 601$, with a head of about 4 feet; but for a head of $4\frac{1}{2}$ inches the coefficient fell from $\cdot 572$ to $\cdot 483$. For notches $8''$ wide, with the addition of a horizontal shoot $9' 10''$ long, the coefficient fell from $\cdot 582$ to $\cdot 479$ for a head of $8''$; and from $\cdot 622$ to $\cdot 340$ for a head of $1''$. Castel also found for a notch $8''$ wide, with the addition of a shoot $8''$ long, inclined $4^\circ 18'$, the mean coefficient for heads from $2''$ to $4\frac{1}{2}''$, to be $\cdot 527$ nearly. The effects arising from friction alone will be perceived from the short table at the beginning of this section, p. 146.

The orifice of entry into a shoot and its position with reference to the sides and bottom modify the discharge, the head remaining constant. Lesbros† has given the coefficients suited to different positions of shoots both within and without a cistern, and from notches and submerged orifices; but, however valuable these are in some respects, they are of little practical use to the engineer. The general principles which are involved in the modification of these coefficients


* *Traité d'Hydraulique*, pp. 46 et 94.

† *Vide* Morin's *Hydraulique*, deuxième édition, pp. 29 et 40.

have, however, been already pointed out when discussing the effects of the position of the orifice, and the addition of short tubes, on the discharge. Equation (74B), p. 196, is here applicable.

SECTION VII.

LATERAL CONTACT OF THE WATER AND TUBE.—ATMOSPHERIC PRESSURE.—HEAD MEASURED TO THE DISCHARGING ORIFICE.—COEFFICIENT OF RESISTANCE.—FORMULA FOR THE DISCHARGE FROM A SHORT TUBE.—DIAPHRAGMS.—OBLIQUE JUNCTIONS.—FORMULA FOR THE TIME OF THE SURFACE SINKING A GIVEN DEPTH.—LOCK CHAMBERS.—SLUICES.—TIDAL SLUICES.



The contracted vein *or* is about $\cdot 8$ times the diameter *or*; but it is found, notwithstanding, that water, in passing through a short tube of not less than $1\frac{1}{2}$

diameter in length, fills the whole of the discharging orifice *s t*. This is partly effected by the outflowing column of water carrying forward and exhausting the air between it and the tube, and by the external air then pressing on the column so as to enlarge its diameter and fill the whole tube. When once the water approaches closely to the tube, or is caused to

approach, it is attracted and adheres with some force to it. The water between the tube and the *vena-contracta* is, however, rather in a state of eddy than of forward motion, as appears from the experiments, with the tube, diagram 2, Fig. 25, giving the same discharge as the simple cylindrical tube. If the entrance be contracted by a diaphragm, as at o r, Fig. 27, the water will also generally fill the tube, if it be only sufficiently long. Short cylindrical tubes do not fill when the discharge takes place in an exhausted receiver; but even diverging tubes, D, Fig. 24, will be filled, under atmospheric pressure, when the angle of divergence, o, does not exceed 7 or 8 degrees, and the length be not very great nor very short.

When a tube is fitted to the bottom or side of a vessel, it is found that the discharge is that due to the head measured from the surface of the water to the lower or discharging extremity of the tube. It must, however, be sufficiently long, and not too long, to get filled throughout. Guiglielmini first referred this effect to atmospheric pressure, but the first simple explanation is that given by Dr. Mathew Young, in the Transactions of the Royal Irish Academy, vol. vii., p. 56. Venturi, also, in his fourth proposition, gives a demonstration.

The values of the coefficients for short cylindrical tubes, which are given p. 156, have been derived from experiments. Coefficients which agree pretty closely with them, and which are derived from the coefficients for the discharge through an orifice in a thin plate, may, however, be calculated as follows: Let c be the area of the approaching section, Fig. 27, A the area of

the discharging short tube, and a the area of the orifice OR which admits the water from the vessel into the tube : also put, as before, h for the head measured from the surface of the water to the centre of the tube, and diaphragm OR ; v for the actual velocity of discharge at ST ; v_a for the velocity of approach in the section c towards the diaphragm OR ; and c_c for the coefficient of contraction in passing from OR to or ; then $c \times v_a = A \times v$, the contracted section $or = c_c \times a$, and consequently the velocity at the contracted section is equal to $\frac{A v}{a c_c} = \frac{c v_a}{a c_c}$. Now a theoretical head equal to

$$\frac{v^2 - v_a^2}{2g} = \frac{v^2 \left(1 - \frac{A^2}{c^2}\right)}{2g}$$

is necessary to change the velocity v_a into v by the action of gravity; but as the water at the contracted section or , moving with a velocity $\frac{A v}{a c_c}$, strikes against the water between it and TS , moving, from the nature of the case, with a slower velocity,* a certain loss of effect takes place from the impact. If this be, supposed, sudden, then writers on mechanics have shown that a loss of head, equal to that due to the difference of the velocities, $\frac{A v}{a c_c} - v$, before and after the impact must take place. This loss of head is therefore equal to

$$\frac{\left(\frac{A}{a c_c} - 1\right)^2 v^2}{2g},$$

* *Vide* Sir Robert Kane's translation of Rühlman's book on Horizontal Water Wheels, p. 49.

whence the whole head,

$$(60.) \quad h = \frac{\left(1 - \frac{\Lambda^2}{c^2}\right)v^2 + \left(\frac{\Lambda}{a c_o} - 1\right)^2 v^2}{2g},$$

from which the velocity from a short tube, is found to be

$$(61.) \quad v = \sqrt{2gh} \left\{ \frac{1}{1 - \frac{\Lambda^2}{c^2} + \left(\frac{\Lambda}{a c_o} - 1\right)^2} \right\}^{\frac{1}{2}}.$$

Now, as $\sqrt{2gh}$ would be the velocity of discharge were there no resistances, or loss sustained, it is

evident that $\left\{ \frac{1}{1 - \frac{\Lambda^2}{c^2} + \left(\frac{\Lambda}{a c_o} - 1\right)^2} \right\}^{\frac{1}{2}}$ becomes as it

were a coefficient of velocity. When the diameter of the diaphragm $o r$ becomes equal to the diameter $s r$ of the tube, $\Lambda = a$, and as the coefficient of velocity becomes equal to the coefficient of discharge when there is no contraction, in such case this coefficient, which we call $c o f$, is expressed by the formula

$$(62.) \quad c o f. = \left\{ \frac{1}{1 - \frac{\Lambda^2}{c^2} + \left(\frac{\Lambda}{c_o} - 1\right)^2} \right\}^{\frac{1}{2}}, *$$

* When the diaphragm is placed in a tube of uniform bore, then $c = \Lambda$, and

$$c o f. = \frac{1}{\frac{\Lambda}{a c_o} - 1} = \frac{c_o}{a - c_o},$$

and the loss of head, in passing the diaphragm, becomes

$$h = \left(\frac{\Lambda}{a c_o} - 1\right)^2 \times \frac{v^2}{2g}.$$

It is evident from the equations that $\frac{\Lambda}{a}$ and c_o depend mutually on

and when the approaching section c is very large compared with the area A ,

$$(63.) \quad c o f. = \left\{ \frac{1}{1 + \left(\frac{1}{c_0} - 1 \right)^2} \right\}^{\frac{1}{2}}.$$

If $c_0 = \cdot 64$, the last equation gives $c o f. = \cdot 872$; if $c_0 = \cdot 601$, $c o f. = \cdot 833$; if $c_0 = \cdot 617$, $c o f. = \cdot 847$; and if $c_0 = \cdot 621$, $c o f. = \cdot 856$. These results are in excess of those derived from experiment with cylindrical short tubes, perfectly square at the ends and of uniform bore. As some loss, however, takes place in the eddy between $o r$ and the tube, and from the friction at the sides, not taken into account in the above calculation, they will account for the differences of not more than from 4 to 6 per cent. between the calculation and experiment. If c_0 be assumed for calculation equal $\cdot 590$, then $c o f. = \cdot 821$; and as this result agrees very closely with the experimental one, c_0 should be taken of this value in using the foregoing formulæ, from (60) to (63), for practical purposes. The thickness of the diaphragm itself and the relation of that thickness to the diameter, as well as the form of the orifice a , are necessary elements in the consideration of this question.

COEFFICIENT OF RESISTANCE. — LOSS OF MECHANICAL POWER IN THE PASSAGE OF WATER THROUGH THIN PLATES AND PRISMATIC TUBES.

The coefficients of contraction, velocity, and discharge, and that they cannot be assumed arbitrarily. See equations (66), (67), (123), (124), and (125), with the corresponding remarks.

charge have been already defined. *The coefficient of resistance is the ratio of the head due to the resistance, to the theoretical head due to the actual or final velocity.* If v be this latter velocity, the theoretical head due to it is $\frac{v^2}{2g}$; and if c_r be the coefficient of resistance, then the head due to the resistance itself is, from our definition, $c_r \times \frac{v^2}{2g}$. Now if c_v be the coefficient of velocity, the theoretical velocity of discharge must be $\frac{v}{c_v}$, and the head due to it is equal $\frac{v^2}{c_v^2 \times 2g}$; but as the theoretical head due to v is $\frac{v^2}{2g}$, then

$$\frac{v^2}{c_v^2 \times 2g} - \frac{v^2}{2g} = \left(\frac{1}{c_v^2} - 1 \right) \frac{v^2}{2g}$$

is the head due to the resistance; and, therefore, from the definition, the coefficient of resistance is

$$(64.) \quad c_r = \frac{1}{c_v^2} - 1;$$

from which the coefficient of velocity is found

$$(65.) \quad c_v = \left\{ \frac{1}{c_r + 1} \right\}^{\frac{1}{2}}.$$

These equations enable us to calculate the coefficient of resistance from the coefficient of velocity, and *vice versa*. If $c_v = 1$, $c_r = 0$, as it should be. The following short table, calculated from equation (65), will be of use. In short tubes, the coefficient of velocity c_v is equal to the coefficient of discharge c_d .* The coefficient of velocity for an orifice in a thin

* See the tables of resistances, discharge, and contraction, pp. 169 and 171.

COEFFICIENTS OF VELOCITY AND RESISTANCE.

Coefficient of velocity.	Coefficient of resistance.	Coefficient of velocity.	Coefficient of resistance.	Coefficient of velocity.	Coefficient of resistance.
·990	·020	·910	·208	·830	·452
·970	·063	·890	·263	·820	·488
·950	·109	·870	·320	·814	·508
·930	·156	·850	·383	·810	·525

plate, or for a mouth-piece, Fig. 4, is ·974; while that for a short prismatic tube, A, Fig. 24, is ·814 nearly. The coefficient of resistance in the former case is ·054, and in the latter ·508; there is, therefore, 9·4 times as great a loss of mechanical power in the passage through short prismatic tubes, as through orifices in thin plates or tubes with a rounded junction, as in Fig. 4, the quantities of water discharged and the discharging orifices being the same.

If the quantities discharged and the heads be the same in both cases, then

$$\frac{v_t^2}{2g \times \cdot 814^3} = \frac{v_o^2}{2g \times \cdot 974^3} \text{ is equal to the head;}$$

that is, $\frac{v_t^2}{\cdot 663 \times 2g} = \frac{v_o^2}{\cdot 949 \times 2g}$, or $\cdot 949 v_t^2 = \cdot 663 v_o^2$; whence we get $v_t^2 = \cdot 698 v_o^2$ and $v_o^2 = 1\cdot 431 v_t^2$ for the relation of the discharging velocities, v_o , from an orifice, and, v_t , from a short tube. The height due to the resistance is therefore, $\left(\frac{1}{\cdot 814^3} - 1\right) \frac{v_t^2}{2g}$ for short prismatic tubes, and $\left(\frac{1}{\cdot 974^3} - 1\right) \frac{1\cdot 431 v_t^2}{2g}$ for orifices in thin plates. These are to each other as ·508 to $\cdot 054 \times 1\cdot 431$, or as 5·08 to ·773, that is to say,

the loss of mechanical power arising from the resistance in passing through short tubes is 6.57 times as great as when the water passes through thin plates or mouth-pieces, as in Fig. 4; and the discharging mechanical power in plates, is to that in tubes as 1.431 to 1, or as 1 : .698, the heads and quantities discharged being the same.

The whole loss of mechanical power in the passage is 5.4 per cent. for the plates, and about 51 per cent. for short tubes. If the loss compared with the whole head be sought, then, when v is the discharging velocity, $\frac{v}{.814}$ is the theoretical velocity due to the head in short tubes, and its square $\frac{v^2}{.814^2} = \frac{v^2}{.663}$ is as the whole head; therefore, the whole head is to the head due to the discharging velocity as $\frac{v^2}{.663}$ to v^2 , or as 1 to .663; and as .508 is the coefficient of resistance* for the discharging velocity, $.508 \times .663 = .337$ is the coefficient of resistance due to the whole head; this is equal to a loss of 34 per cent. nearly, or about one-third. In like manner, $.974^2 \times .054 = .0512$ is found for the coefficient when the discharge takes place through thin plates, or $5\frac{1}{8}$ per cent. of the whole head.

DIAPHRAGMS.

When a diaphragm, OR, Fig. 27, is placed at the entrance of a short tube, it is shown, page 162, that

* Table, p. 166.

a loss of head equal $\frac{\left(\frac{A}{a c_o} - 1\right)^2 v^2}{2 g}$ takes place when v is the discharging velocity, whence the coefficient of resistance is equal to $\left(\frac{A}{a c_o} - 1\right)^2$, * according to the definition. The coefficient of contraction c_c , as before shown, page 164, should be taken equal to .590 in the application of formula (63); and, as it must also be taken equal to about .621 when the area of the tube A is very large compared with the area a of the orifice OR in the diaphragm, it may be assumed that when $\frac{a}{A}$ is equal to

$\left\{ \begin{array}{cccccccccccc} 0, & 1, & 2, & 3, & 4, & 5, & 6, & 7, & 8, & 9, & \text{and } 1 \\ \text{successively, the coefficient } c_o \text{ must be taken equal to } \end{array} \right\}$
 $\left\{ \begin{array}{cccccccccccc} .621, & .618, & .615, & .612, & .609, & .606, & .603, & .600, & .597, & .593, & \text{and } .590, \end{array} \right\}$

taken in the same order. As the approaching section c may be considered exceedingly large, the value of the coefficient of discharge or velocity, as the tube $ORST$ is supposed full, in equation (61), becomes

$$(66.) \quad c_d = \left\{ \frac{1}{1 + \left(\frac{A}{a c_o} - 1\right)^2} \right\}^{\frac{1}{2}},$$

and the coefficient of resistance

$$(67.) \quad c_r = \left(\frac{A}{a c_o} - 1\right)^2;$$

* For the sudden alteration in the velocity passing through a diaphragm, we must reject the hypothesis of D'Aubuisson, *Traité d'Hydraulique*, p. 238, and adopt that of Navier, taking the loss of head to correspond to the square of the difference and not to the difference of the squares of the velocities *in* and *after* passing the orifice. The coefficient of contraction must, however, be varied to suit the ratio of the channels, as it is in this and the following pages.

from which equations and the above values of c_o , corresponding to $\frac{a}{A}$, the following values of the coefficients of discharge and resistance through the tube *o r s t*, Fig. 27 have been calculated.

COEFFICIENTS OF CONTRACTION, DISCHARGE, AND RESISTANCE FOR DIAPHRAGMS.

Ratio $\frac{a}{A}$	Coefficient c_o	Coefficient c_d for the orifice A	Coefficient c_r	Ratio $\frac{a}{A}$	Coefficient c_o	Coefficient c_d for the orifice A	Coefficient c_r
0.0	.621	.000	infinite.	0.6	.603	.493	3.115
0.1	.618	.066	231.	0.7	.600	.587	1.907
0.2	.615	.139	50.8	0.8	.597	.675	1.198
0.3	.612	.219	19.8	0.9	.593	.753	.762
0.4	.609	.307	9.6	1.0	.590	.821	.483
0.5	.606	.399	5.3

In this table c_o is the coefficient of contraction, c_d the coefficient of discharge, suited to the larger section of the pipe A , at *s t*; and c_r the coefficient of resistance. The discharge is found from equation (61), as c is here very large compared with A , to be

$$(67A.) \quad D = A \sqrt{2gh} \left\{ \frac{1}{1 + \left(\frac{A}{a c_o} - 1 \right)^2} \right\}^{\frac{1}{2}}$$

$$= A \sqrt{2gh} \left\{ \frac{1}{1 + c_r} \right\}^{\frac{1}{2}} = c_d A \sqrt{2gh}.$$

The coefficient of resistance c_r is here equal $\left(\frac{A}{a c_o} - 1 \right)^2$,

and the coefficient of discharge $c_d = \frac{1}{(1 + c_r)^{\frac{1}{2}}}$. *

* For the loss sustained by contraction in the bore of a pipe by a diaphragm, see equations (123), (124), and (125). The actual value of

The tube must be so placed, that the water, after passing the diaphragm, shall fill it; for instance, between two cisterns, when the height h must be measured between the water surfaces, or when the tube is sufficiently long to be filled; in this case, however, *the height must be determined from the discharging velocity*, as a portion of the head is required to overcome the friction, which shall be referred to more particularly in the next section.


The table shows that the head due to the resistance is 5.3 times that due to the discharging velocity, when the area of the diaphragm is half the area of the tube; that is, the whole head required is 6.3 times that due to the velocity, and that the coefficient of discharge is reduced to .399. In order to find the coefficients suited to the smaller area of the orifice in the diaphragm α , when it is to be used in calculations of the discharge, divide the numbers corresponding to $\frac{\alpha}{A}$ into those of c_d , opposite to them in the table.

Thus, when $\frac{\alpha}{A} = .8$, then the coefficient of discharge suited to the area α , is equal $\frac{.675}{.8} = .844$, and so of other values of the ratio $\frac{\alpha}{A}$. The coefficients in the table, page 169, are for the larger orifice A in the formula $D = A c_d \sqrt{2 g h}$.

c_d in equation (67A) depends on the thickness of the diaphragm as well as on the relation of α and A . The form of the orifice α also affects the value of c_d .

SHORT TUBES OBLIQUE AT THE JUNCTION.

When a tube is attached obliquely, as in Fig. 28, the author has found that if the number of degrees in the angle TOS , formed by the direction of



the tube $o s$, with the perpendicular $o t$, be represented by ϕ , then $\cdot 814 - \cdot 0016 \phi$ will give the coefficient of discharge corresponding to the obliquely attached short tube in the Figure. This formula is, however, empirical, but it is simple, and agrees pretty closely with experimental results. As the coefficient of resistance is equal $\frac{1}{c_r^2} - 1$, equation (64), then here

$c_r = \frac{1}{(\cdot 814 - \cdot 0016 \phi)^2} - 1$; from these equations the following table for heads measured to the middle of the outside orifice has been calculated:—


COEFFICIENTS OF DISCHARGE AND RESISTANCE FOR OBLIQUE JUNCTIONS.

ϕ in degrees.	Coefficient of discharge.	Coefficient of resistance.	ϕ in degrees.	Coefficient of discharge.	Coefficient of resistance.
0°	·814	·508	35°	·758	·740
5	·806	·539	40	·750	·778
10	·798	·569	45	·742	·816
15	·790	·602	50	·734	·856
20	·782	·635	55	·726	·897
25	·774	·669	60	·718	·940
30	·766	·704	65	·710	·984

The coefficient of resistance for a tube at right angles

to the side, is to the like coefficient when it makes an angle of 45 degrees as $\cdot 508$ to $\cdot 816$, or as 1 to 1.6 nearly; and the loss of head is greater in the same proportion. If the short tube be more than three or four diameters in length, friction will have to be taken into account. The head h is measured to the centre of the outside orifice.

FORMULA FOR FINDING THE TIME THE SURFACE OF WATER IN A CISTERN TAKES TO SINK A GIVEN DEPTH.—DISCHARGE FROM ONE VESSEL OR CHAMBER INTO ANOTHER.—LOCK CHAMBERS.



In experiments for finding the value of the coefficients of discharge, one of the best methods is to observe the time the water discharged from the orifice takes to

sink the surface in a prismatic cistern a given depth; the ratio of the observed to the theoretical time will then give the coefficient sought. A formula for finding the time is, therefore, of much practical value. In Fig. 29, the theoretical time of falling from $s t$ to $s T$, in seconds, is

$$(68.) t = \frac{A}{4.0125 a} \{ (h + f)^{\frac{1}{2}} - h^{\frac{1}{2}} \} = .249 \frac{A}{a} \{ (h + f)^{\frac{1}{2}} - h^{\frac{1}{2}} \}$$

in which a is the area of the orifice $o r$, and A the area of the prismatic vessel at $s t$ or $s T$: this formula is for measures in feet. For measures in inches, we have

$$(69.) t = \frac{A}{18.9 a} \{ h + f)^{\frac{1}{2}} - h^{\frac{1}{2}} \}.$$

This time is double the time required to discharge the same quantity if the head at the orifice remained constant.

EXAMPLE VII.—*A cylindrical vessel 5·74 inches in diameter has an orifice ·2 inch in diameter at a depth of 16 inches below the surface, measured to the centre ; it is found that the water sinks 4 inches in 51 seconds ; what is the coefficient of discharge ?*


The theoretical time t is found from equation (69), equal

$$\frac{5\cdot74 \times \cdot7854}{13\cdot9 \times \cdot2^2 \times \cdot7854} \{16\frac{1}{2} - 12\frac{1}{2}\} = \frac{32\cdot9476}{\cdot556} \{4 - 3\cdot4641\} \\ = \frac{17\cdot6566}{\cdot556} \times \cdot5359 = 31\cdot8 \text{ seconds ; hence, } \frac{31\cdot8}{51} = \cdot624$$

is the coefficient sought. When the orifice o R and the horizontal section of the vessel are similar figures, $\frac{A}{a}$ is equal $\frac{S T^2}{O R^2}$; and therefore, for circular cisterns and orifices, it is unnecessary to introduce the multiplier ·7854.

Formulae for the time water in a prismatic vessel takes to fall a given depth, when discharged from an

Fig. 29a.



orifice at the side or bottom are given above. The time the surface s T , diagram 1, Fig. 29a, takes to rise

to s t , when supplied through an orifice or tube o R , from an upper large chamber or canal, whose surface s' t' remains always at the same level, is $\frac{2 \Lambda f^{\frac{1}{2}}}{c_d a \sqrt{2g}}$,* and thence the time of rising from R to s for measures in feet is

$$(69A.) \quad t = \frac{\Lambda}{4.0125 c_d a} \{h_1^{\frac{1}{2}} - f^{\frac{1}{2}}\}$$

and for measures in inches

$$(69B.) \quad t = \frac{\Lambda}{18.9 c_d a} \{h_1^{\frac{1}{2}} - f^{\frac{1}{2}}\},$$

in which Λ is the area of the horizontal section at s T ; a the sectional area of the communicating channel or orifice o R ; c_d the coefficient of discharge suited to it, and h_1 and f , as shown in the diagram.

In order to find the time of filling the lower vessel to the level s T , supposing it at first empty, the contents of the portion below o R are equal to Λh_2 , and the time of filling it equal to

$$(69C.) \quad \frac{\Lambda h_2}{8.025 c_d a h_1^{\frac{1}{2}}}$$

then the time of filling up to any level s T , for measures in feet, is equal to the sum of (69A) and (69C); that is,

$$(69D.) \quad T = \frac{\Lambda h_1^{\frac{1}{2}}}{8.025 c_d a} \left\{ 2 + \frac{h_2}{h_1} - \frac{2 f^{\frac{1}{2}}}{h_1^{\frac{1}{2}}} \right\} \\ = \frac{\Lambda (2h_1 + h_2 - 2 f^{\frac{1}{2}} h_1^{\frac{1}{2}})}{8.025 c_d a h_1^{\frac{1}{2}}},$$

and for measures in inches

* The time of rising from s to s' (diagram 1) is exactly double the time it would take to fill the same depth *below* R , if the pressure f remained uniform.

$$(69E.) \quad T = \frac{\Delta h_1^{\frac{1}{2}}}{27.8 c_d a} \left\{ 2 + \frac{h_2}{h_1} - \frac{2 f^{\frac{1}{2}}}{h_1^{\frac{1}{2}}} \right\} \\ = \frac{\Delta (2h_1 + h_2 - 2 f^{\frac{1}{2}} h_1^{\frac{1}{2}})}{27.8 c_d a h_1^{\frac{1}{2}}}.$$

When s T coincides with s t

$$(69F.) \quad T = \frac{\Delta (2h_1 + h_2)}{8.025 c_d a h_1^{\frac{1}{2}}},$$

for measures in feet, and

$$(69G.) \quad T = \frac{\Delta (2h_1 + h_2)}{27.8 c_d a h_1^{\frac{1}{2}}},$$

for measures in inches. These equations are exactly suited to the case of a closed lock-chamber filled from an adjacent canal.

When the upper level s' T' is also variable, as in Diagram 2, the time which the water in both vessels takes to come to the same uniform level s' t' s t , which is known or easily found, is

$$(69H.) \quad t = \frac{2 \Delta A_1 (h_1 + f_1 - h)^{\frac{1}{2}}}{c_d a (\Delta + A_1) \sqrt{2g}} = \frac{2 \Delta A_1 (f + f_1)^{\frac{1}{2}}}{c_d a (\Delta + A_1) \sqrt{2g}};$$

in which $h_1 + f_1 - h = f + f_1$ is the difference of levels at the beginning of the flow; A_1 the horizontal section of the upper chamber; and the other quantities as in Diagram 1. As $A_1 \cdot f_1 = A \cdot f$, then

$$f + f_1 = \frac{A_1 + A}{A} f_1 = \frac{A_1 + A}{A_1} f.$$

Now, in order to find the time of falling a given depth f_x below the first level s' T' , the head above s' t' s t is equal to $f_1 - f_x$ in the upper vessel, and the depth below it in the lower vessel is equal to $\frac{A_1 (f_1 - f_x)}{A}$; whence the difference of levels in the two vessels at the end of the fall d , is

$$f_1 - d + \frac{A_1(f_1 - f_x)}{A} = \frac{A + A_1}{A} (f_1 - f_x).$$

The time of falling through any given depth, f_x is, therefore, from equation (69H),

$$\begin{aligned} (69I.) \quad t &= \frac{2 A A_1 (f + f_1)^{\frac{1}{2}}}{c_d a (A + A_1) \sqrt{2g}} - \frac{2 A A_1 \left\{ \left(\frac{A_1 + A}{A} \right) (f_1 - f_x) \right\}^{\frac{1}{2}}}{c_d a (A + A_1) \sqrt{2g}} \\ &= \frac{2 A A_1}{c_d a (A + A_1) \sqrt{2g}} \left\{ (f + f_1)^{\frac{1}{2}} - \left(\frac{(A + A_1)(f_1 - f_x)}{A} \right)^{\frac{1}{2}} \right\}, \end{aligned}$$

When $f_x = f_1$ this is reduced to $t = \frac{2 A A_1 (f + f_1)^{\frac{1}{2}}}{c_d a (A + A_1) \sqrt{2g}}$,

and farther when $A = A_1$ this last is again farther

$$\text{reduced to } t = \frac{A_1 f_1^{\frac{1}{2}}}{c_d a \sqrt{g}} = \frac{1.4142 A_1 f_1}{c_d a \sqrt{2g f_1}}.$$

in which $\sqrt{2g} = 8.025$ for measures in feet, and equal 27.8 for measures in inches. The whole time of filling to a level the lower *empty vessel*, is found by adding the time of filling the portion below R, determined in a manner similar to equations (68), to be

$$(69K.) \quad \frac{2 A_1}{c_d a \sqrt{2g}} \left\{ (h_1 + f_1)^{\frac{1}{2}} - \left(h_1 + f_1 - \frac{h_2 A}{A_1} \right)^{\frac{1}{2}} \right\},$$

to the time of filling above R, given in equation (69H), when h is taken equal to zero. Equations (69H), (69I), and (69K) are applicable to the case of the upper and lower chambers of a double lock, after making the necessary change in the diagrams.

The above equations require further extensions when water flows into the upper vessel while also flowing from it into the lower; such extensions are, however, of little practical value, and we therefore omit them. For sluices in flood-gates with square

arrises, c_d may be taken at about '545, but with rounded arrises, the coefficient will rise much higher. See SECTIONS III. and VI.

SLUICE OPES.—FLOOD AND TIDAL SLUICE OPES.

Equations (41), (42), (43), (48), (49), (50), and (51) give the discharge from sluice opes under different circumstances when fully open, submerged, or partly submerged. Rejecting the velocity of approach, and measuring the depth, h to the centre, or centre of gravity, of the orifice, whose area is a , equation (41), becomes, for the case in Fig. 12, with any form of section, rectangular or circular, entirely open and without back water.

$$(41A.) \begin{cases} D = c_d a \sqrt{2gh} = 8.025 c_d a \sqrt{h}, \text{ for one second; or} \\ D = 481.5 c_d a \sqrt{h}, \text{ for one minute; or} \\ D = 4.95 a \sqrt{h} \text{ when } c_d = .617 \text{ in one second; and} \\ D = 297 a \sqrt{h} \text{ in one minute.} \end{cases}$$

All in feet measures.

In the case, Fig. 20, in which the sluice is covered, or entirely submerged, then the discharge in one minute, in feet measures, equation (48) becomes also

$$(47A.) \quad D = 60 c_d a \sqrt{2gh} = 297 a \sqrt{h};$$

in which, however, h is now the difference of level between the surfaces of the upper and lower waters.

If c_d be taken '582 instead of '617 then

$$(47B.) \quad D = 280 a \sqrt{h}.$$

But if the coefficient run up to '712 then

$$(47C.) \quad D = 343 a \sqrt{h}.$$

When the sluice-ope is partly submerged, as in

Fig. 21, putting a_1 for the area of the open portion and a_2 for that portion submerged, then for time in minutes, equation (50) or (51) becomes

$$(50 \text{ \& } 51A.) \quad D = 60 \left(c_d a_2 \sqrt{2gh} + c_d a_1 \sqrt{2g \frac{h+h_t}{2}} \right) \\ = 297 \left(a_2 \sqrt{h} + a_1 \sqrt{\frac{h+h_t}{2}} \right)$$

for $c_d = .617$ as a mean value in both a_2 and a_1 . It however generally differs in both. For a coefficient of .582 it becomes

$$(50 \text{ \& } 51B.) \quad D = 280 \left(a_2 \sqrt{h} + a_1 \sqrt{\frac{h+h_t}{2}} \right).$$

And for an average coefficient of .712 in A_1 and A_2 it is

$$(50 \text{ \& } 51C.) \quad D = 343 \left(a_2 \sqrt{h} + a_1 \sqrt{\frac{h+h_t}{2}} \right).$$

In these formulæ the pressure at the sluice remains unchanged and the acting heads constant.

WHEN THE HEADS VARY. The general differential equation for the discharge, whatever be the law of the rise and fall, f is evidently

$$(70.) \quad dD = c_d a \sqrt{2g} \times dt \sqrt{f} = c_d a \sqrt{2g} \times dt \sqrt{h_1 - h}.$$

The integration of this equation depends on the relation between f and t . For the ordinary cases of filling prismatic ponds from upper levels the preceding equations from (68) to (69K) may be used as follows to find D . If the upper surface remain at the same level as in 1, Fig. 29a; while the surface of the water below rises from the discharge through the sluice, and if the lower pond be a prism, whose horizontal section is A , then dividing $h A$, the quantity by the time t as given in equation (69A), the average discharge in average seconds of the whole time t is

$$(70A.) \quad D = \frac{4.0125 c_d a h}{h_1^{\frac{1}{2}} - f^{\frac{1}{2}}}. \quad \text{And for the time } t;$$

$$D = \frac{4.0125 c_d h t}{h_1^{\frac{1}{2}} - f_1^{\frac{1}{2}}} = A h.$$

which are independent of the area A of the lower vessel. When $h = h_1$ then $f = 0$ and this becomes

$$(70B.) \quad D = 4.0125 c_d a h_1^{\frac{1}{2}} t = A h_1$$

which is exactly *one-half what it would be in the same time if the head h_1 remained constant, $h = 0$, and therefore the lower level not rising higher than $O R$.*

If the lower level remain unchanged and the upper varies, then, calling the section of the upper prism A_1 , the difference of level h_1 , and f the fall in the time t , the average discharge in one second is found in a similar manner to be

$$(70C.) \quad D = \frac{4.0125 c_d a f}{h_1^{\frac{1}{2}} - (h_1 - f)^{\frac{1}{2}}}. \quad \text{And for the time } t;$$

$$D = \frac{4.0125 c_d a f t}{h_1^{\frac{1}{2}} - (h_1 - f)^{\frac{1}{2}}} = f A_1,$$

when $f = h_1$ this is reduced to

$$(70D.) \quad D = 4.0125 c_d a h_1^{\frac{1}{2}} t = h_1 A_1$$

the whole discharge in the time of falling through h_1 . In fact the values (70B) and (70D) for the relations between the time, discharge, and head are the same, when either level, above or below, is fixed and the water rises or falls in the prismatic pond. When the pond or cistern is of any irregular shape and section the contents can be divided by horizontal sections into any suitable number of parts of equal height, when the whole time of filling or emptying will be the sum of the times calculated for each horizontal lamina, and

the greater the number of lamina the more correct the result.

When the levels of both ponds vary by the water passing from one into the other, diagram 2, Fig. 29a. Measuring f and f_1 from the common level and calling f_x the height fallen in any time t , then from equation (69i) by dividing into $f_x A$ and multiplying by t

$$(70E.) D = \frac{c_d a A^{\frac{1}{2}} (A + A_1) \sqrt{2 g f_x} t}{2 A \left\{ \{A (f + f_1)\}^{\frac{1}{2}} - \{(A + A_1) (f_1 - f_x)\}^{\frac{1}{2}} \right\}} = f_x A_1.$$

When $f_x = f_1$ and the water is one level in both ponds this becomes

$$(70F.) D = \frac{c_d a (A + A_1) \sqrt{2 g f_1} t}{2 A (f + f_1)^{\frac{1}{2}}} = f_1 A_1.$$

And when A is infinitely large, h and $f = 0$ this is farther reduced to

$$(70G.) D = \frac{c_d a \sqrt{2 g f_1} \times t}{2} = f_1 A_1$$

as it should be. In each of the last three equations the factor $\frac{\sqrt{2 g}}{2} = 4.0125$ for feet measures. It may

be said of these formulæ that the product $f_x A_1$, or $f_1 A_1$, gives the quantity at once, but in many problems f_x , f_1 and t have to be found from each other.

Assuming the form of the ordinary formula

$$D = c_d a \sqrt{2 g f_1} = 8.025 c_d a \sqrt{f_1}$$

in one second, or $481.5 c_d a \sqrt{f_1}$ in one minute for a steady head f_1 . Then for a variable head as in Fig. 29, and 1 Fig. 29a, the time of discharging a given quantity is doubled: or, which is the same thing, the coefficient c_d becomes now $.5 c$ in the first form.

In the case of two equal ponds equation (70F) would become

$$D = .707 c_d a \sqrt{2 g f_1} \times t,$$


and the time 1.4142 times that required to discharge a quantity equal to $f_1 A$ with an invariable head f_1 . But as the head at the beginning was $f_1 + f = 2f_1$ if this latter head were used, the quantity being the same,

$$D = \frac{.707 c_d a \sqrt{4 g f_1} \times t}{4} = .177 c_d a \sqrt{2 g \cdot 2 f_1} \times t,$$

or a little over one-sixth of what it would be if the head at the beginning $2f_1$, remained invariable for the same time t .

FLOOD AND TIDAL SLUICES.

The opes for these are intended for the drainage of low embanked lands. They are fitted with gates, or doors, generally hung on their upper side and self-



acting so as to shut when the outside water rises over the inside level, and to open when it sinks to or below it, so as to pass off the inside water. The effective head is reduced during the time the water takes to

rise, between the bottom of the aperture—or low water if over the aperture,—and the inside level of the water on the lands. During the time of fall a like reduction takes place; and, therefore, the discharging power of the sluice is considerably reduced. The relations between the times and the heads risen or fallen through being known, the integration of equation (70) can be effected directly or by approximation, h being any function of t . When the rise or fall of the flood is everywhere proportionate to the time, as in H L I, diagram 3, Fig. 29b; where H L represents the fall and H I the time; then in diagrams 1 and 2, if t be the time of rising through $h + f = h_1$, the time of rising through h is $\frac{h t}{h_1}$ and integrating equation 70 accordingly,

$$(70A.) \quad D = \frac{2 t h}{3 h_1} c_a a \sqrt{2 g h};$$

for the discharge in the time of rising through h , which when $h_1 = h$ becomes

$$(70B.) \quad D = \frac{2}{3} c_a t a \sqrt{2 g h_1} = .667 c_a t a \sqrt{2 g h_1}.$$

The coefficient c_a is therefore reduced one-third when $h_1=f$, when $h_1=2 f$ or at half flood, and indeed through-out h_1 , for either diagram 1 or 2, the coefficient $\frac{2}{3} c_a$

remains constant. The gate or door at o is supposed shut in the time of rising and falling through f_1 and fully open in the time of rise or fall through $h + f = h_1$. When not fully open the discharge becomes still further reduced.

TIDES.—If the whole fall H L be that of a tide from high to low water, then on the assumption that when

$H t_1 o_1 L$ is the arc of a semicircle it represents time, T , of rising or falling through HL , the time of rising through oL is represented by the arc Lo_1 , and the time of rising through To by the arc $o_1 t_1$ the direct integration of equation (70), which then becomes by reduction

$$(70c.) dD = c_d a \sqrt{2g} \times d t_h \sqrt{h_1 - \frac{(h_1 + f_1)}{2} \left(1 - \cos. \frac{180^\circ t_h}{T}\right)}$$

in which t_h is the time of rising through h ; and $\frac{h_1 + f_1}{2}$, the semirange of the tide, gives the discharge. Putting the angle $Lo_1 o_1 = \theta$ this may be changed into

$$(70d.) dD = c_d a \sqrt{2g} \times \frac{T}{180^\circ} \times d\theta \sqrt{h_1 - \frac{h_1 + f_1}{2} (1 - \cos \theta)}.$$

Or as it can be otherwise expressed, putting $2 \sin^2 \frac{\theta}{2}$ for $1 - \cos \theta$

$$(70E.) dD = c_d a \sqrt{2g} \times \frac{2T}{\pi} \times d\left(\frac{\theta}{2}\right) \sqrt{h_1 - (h_1 + f_1) \sin^2 \frac{\theta}{2}}$$

The integration of any of these forms can only be effected approximately. With tides from 20 feet to 6 feet, inside heights, or values of h_1 , from 14 feet to 1 foot, and times of rising through those heights from 235 to 53 minutes, Mr. Cotton calculated the coefficients from (70E) and found them to vary from .748 to .785. If applied to the common form these give

$$(70F.) D = (.748 \text{ to } .785) c_d t a \sqrt{2g h_1},$$

for the discharge within the limits of the calculations. These "TIDAL COEFFICIENTS," as I shall call them, are too high for most cases occurring in practice, and require the sluice to be placed at or below low water of a

6h. 13m. tide, as in diagram 1, Fig. 29b. The fall and rise of the tide at the end of the ebb and beginning of the flow would, for several minutes, be practically nothing, and the coefficient would then be unity, which is the limit for a very small value of h at low water in diagram 1. At semirange for a small rise h , and an orifice placed there, the rise would be as the times and the coefficient would be $\cdot 667$; both giving $\cdot 833$ for an arithmetical mean, which is evidently too high, as the coefficient unity holds only for a comparatively small height. If, however, in diagram 2, Fig. 29b, the sluice or mouth of the culvert be high up, and near below the semirange of the tidal wave, which is the more common case in practice, then the coefficient would reduce to $\frac{2}{3} = \cdot 667$ for its limit. All this supposes the surface of the inside water or reservoir at τ in both diagrams to remain constant, and as it should reduce something in the outflow until the tide rises for some height up h_1 there is still a greater reason for selecting $\frac{2}{3}$ rds. or the minimum coefficient of the range, and to represent the discharge from a tidal sluice fully open by

(70G.) $D = \frac{2}{3} c_d a \sqrt{2g h_1} \times t = 5.35 c_d a \sqrt{h_1} \times t$,
for feet measures and time in seconds ; or

(70H.) $D = 321 c_d a \sqrt{h_1} \times t$
for measures in feet and time in minutes.

The value of c_d is best taken from the table calculated from equation (74B), SECTION VIII. If the length of the culvert* or pipe under an embankment at

* The orifice O is, in practice, generally a pipe or culvert of some length built under an embankment.

the mouth of which the sluice is placed be 20 diameters or 80 mean radii $c_d = .731$ then (70g) becomes

$$(70i.) \quad D = 234.6 a \sqrt{h_1} \times t.$$

If the length of the culvert be 40 diameters or 160 mean radii then $c_d = .668$ and the discharge would be

$$(70k.) \quad D = 214 a \sqrt{h_1} \times t.$$

And for a coefficient of .623

$$(70l.) \quad D = 200 a \sqrt{h_1} \times t.$$

The time of rise or fall of the tide may be taken at 6h. 13m. in diagram 1, and the time of rising through h_1 be represented by the arc $L o_1 t_1$, diagram 3, but in diagram 2 the time corresponding to h_1 is the arc $o_1 t_1$. For a uniform rise these times would be represented by $1 t$, and $1 o$.

Sluice-doors when self-acting should open fully so as to be free above the top of the ope; and not to fall below it until the rising water is at the level of the surface of the inside reservoir; when it should shut if well constructed. They hang in the greater number of executed works at an angle θ , with the vertical which varies with the force of the outflow. The aperture, a , in this case is no longer the cross section of the culvert, but the orifice now may be supposed as made up of a plane the width of the culvert, at right angles to the door, equal to $a \sin. \theta$, having two vertical triangular *open cheeks* of the height of the culvert one on each side, between the vertical plane on the sloping door and the top. These triangular cheeks vary in area from zero to their maximum value, which is when the door hangs at an angle of 45° . If the door be set back in the culvert these cheeks are stopped and the

outlet becomes $a \sin. \theta$. Further formulæ for such contractions would be mere waste, practically considered; and they are therefore not given. A good sluice gate, with its mountings, from the axis of suspension downwards, should have the same specific gravity as the outside water, should act in a cistern so as to be entirely immersed at all times, and the centre of pressure a little below the centre of gravity. But this is no place for questions of construction, or the application of hydrodynamical principles to them. If the object were to calculate, at first, the sectional area of a culvert required for a given discharge it should not be made less, in practice, than double those easily derived from the above formulæ, which would vary with the ratio of the lengths to the hydraulic mean depth of the culvert.

In these sluices, flood or tidal, the time of rising and falling through f_1 is lost in each flood, or in each tide; but as sea water is more dense than fresh water the time lost is a little more. There is also a back leakage through the sluice when shut. When the sluice can be placed at or below low water springs there is an advantage if not overbalanced by the expense; but in general it is sufficient to place it at or below the low water in the tail-race which, itself, must have a surface fall to the low water of neap and spring tides along the shore, if it be of any length. Otherwise, unless artificially constructed and covered over, it would fill in. The range of the tide varies considerably even in the same place from the lowest neaps to the highest springs. The mid-tide is nearly constant and the velocity of ebb and flow indicated by change of

level is then a maximum for each tide. For 30 degrees on each side comprising the time of falling through the central half of the whole range the times, diagram 3, are nearly as the changes of level. In the remaining half range, comprising one quarter above and the other quarter below, the relation is more complex, and varies with time, wind, and weather. In Dundalk I have known two high waters within a few hours of each other, the first ebb having commenced and continued for some time until it was stopped by a return flow. Hence, in order to estimate approximately the discharge from a tidal sluice, we must calculate the discharge for each tide and each day, suitable to diagram 1, or diagram 2; noting that as the range varies from springs to neaps so must the head, h_1 , when the surface at T of the backwater remains constant. It is necessary to keep this surface at all times from twelve to eighteen inches at least below the adjacent lands, and more if the element of expense permits. This level regulates the depth and size of the sluice or sluices.

Self-acting sluices can be hung on vertical as well as horizontal axes. When at the surface, for weirs across rivers, the centre of pressure for crest sluices is at two-thirds of the depth below the surface. As the water falls below the top so does this centre; but it can never rise higher than half the depth, the position when most deeply immersed. The position of the horizontal axis of such sluices lies therefore below the middle, and is regulated by the circumstances of each case, which are referred to farther on.

SECTION VIII.

FLOW OF WATER IN UNIFORM CHANNELS.—MEAN VELOCITY.—MEAN RADII AND HYDRAULIC MEAN DEPTHS.—BORDER.—TRAIN.—HYDRAULIC INCLINATION.—EFFECTS OF FRICTION.—FORMULÆ FOR CALCULATING THE MEAN VELOCITY.—APPLICATION OF THE FORMULÆ AND TABLES TO THE SOLUTIONS OF THREE USEFUL PROBLEMS.

In rivers the velocity is a maximum along the central line of the surface, or, more correctly, over the deepest part of the channel; and it decreases thence to the sides and bottom: but when backwater arises from any obstruction, either a submerged weir, Fig. 22, or a contracted channel, Fig. 23, the velocity in the channel approaching the obstruction is a maximum at the depth of the backwater, below the surface, and it decreases thence to the surface, sides, and bottom. When water flows in a pipe of any length, the velocity at the centre is greatest, and it decreases thence to the sides or circumference of the pipe. If the pipe be supposed divided into two portions in the direction of its length, the lower portion or channel will be analogous to a small river or stream, in which the velocity is greatest at the central line of the surface, and the upper portion will be simply the lower reversed. A pipe flowing full may, therefore, be looked upon as a double stream, and it will soon appear that the formulæ for the discharge from each kind are all but identical,

though a pipe may discharge full at all inclinations, while the inclinations in rivers or streams, having uniform motion, never exceed a few feet per mile.

MEAN VELOCITY.

It is found, by experiment, that the mean velocity is nearly independent of the depth or width of the channel, the central or maximum velocity being the same. From a number of experiments, Du Buât derived empirical formulæ equivalent to

$$v = \frac{v_b + v}{2} = v - v^{\frac{1}{2}} + \frac{1}{2}, \quad v_b = (v^{\frac{1}{2}} - 1)^2, \quad \text{and} \quad v = (v^{\frac{1}{2}} + 1)^2;$$

in these equations v is the mean velocity, v the maximum surface velocity, and v_b the velocity at the sides, or bottom, expressed in French inches. Tables calculated from these formulæ do not give correct results for measures in English inches, though they are those generally adopted. Disregarding the difference in the measures, which are as 1 to 1.0678, it will be found that, in the generality of channels, the mean velocity is not an arithmetical mean between the velocity at the central surface line and that at the bottom, though nearly so between the mean bottom and mean surface velocities. Dr. Young,* modifying Du Buât's formula, assumes for English inches that $v + v^{\frac{1}{2}} = v$, and hence $v = v + \frac{1}{2} - (v + \frac{1}{2})^{\frac{1}{2}}$. This gives results very nearly the same as the other formula for v , but something less, particularly for small surface velocities. For instance, Du Buât's formula gives .5 inch for the mean velocity when the central surface velocity is 1

* Philosophical Transactions, 1808, p. 487.

inch, whereas Dr. Young's makes it .38 inch. For large velocities both formulæ agree very closely, disregarding the difference between the measures, which is only seven per cent. They are best suited to very small channels or pipes, but unless at mean velocities of about 3 feet per second, they are wholly inapplicable to rivers.

Prony found, from Du Buât's experiments, that for measures in metres $v = \left(\frac{2.37187 + v}{3.15312 + v} \right) v$, in which v is also the maximum surface velocity. This, reduced for measures in English feet, becomes

$$(71.) \quad v = \left(\frac{7.783 + v}{10.845 + v} \right) v;^*$$

and for measures in English inches,

$$(71A.) \quad v = \left(\frac{98.39 + v}{124.14 + v} \right) v.$$

For medium velocities $v = .81 v$. The experiments from which these formulæ were derived were made with small channels. The author has calculated the values of v from that of v , equation (71A), and given the results in columns 3, 6, and 9 in TABLE VII. Ximenes, Funk, and Brünnig's experiments in larger channels give the mean velocity at the centre of the depth equal .914 v , when the central or maximum surface velocity

* Francis, Lowell Experiments, p. 150, finds this formula to give 15 per cent. less than the result found by weir measurement from the formula $D = 3.33 (l - .1 n h) h^{\frac{3}{2}}$, the quantity discharged being about 250 cubic feet per second, and the velocity about 3.2 feet. It appears, however, that Francis uses the mean surface velocity, and not the maximum surface velocity required by the formula: if the latter were used, the difference would be reduced to 6 per cent., or thereabouts, in equation (72).


is v ; but as the velocity also decreases in nearly the same ratio at the surface from the centre to the sides of the channel, we shall get the mean velocity in the whole section equal $\cdot 914 \times \cdot 914 v = \cdot 835 v$; and hence, for large channels,

$$(72.) \quad v = \cdot 835 v,$$

in which equation v is the *maximum velocity at the surface*. The author has also calculated the values of v from this formula, and given the results in columns 2, 5, and 8 of TABLE VII. This table will be found to vary considerably from those calculated from Du Buât's formula in French inches, hitherto generally used in this country, and much more applicable for all practical purposes.

MEAN RADIUS.—HYDRAULIC MEAN DEPTH.—BORDER.—
COEFFICIENT OF FRICTION.

If, in the diagrams 1 and 2, Fig. 30, exhibiting the sections of cylindrical and rectangular tubes filled with flowing water, the areas be divided respectively by the



perimeters $A C B D A$ and $A B D C A$, the quotients are termed "*the mean radii*" of the tubes, diagrams 1 and 2; and the wetted perimeters in contact with the flowing water are termed "*the borders*." In the diagrams 3 and 4, the surface $A B$ is not in contact with the channel, and the width of the bed and sides, taken together, $A C D B$, becomes "*the border*." "*The mean radius*" is equal to the area $A B D C A$ divided by the length of

the border A C D B. "*The hydraulic mean depth*" is the same as "*the mean radius*," this latter term being perhaps most applicable to pipes flowing full, as in diagrams 1 and 2; and the former to streams and rivers which have a surface line A B, diagrams 3 and 4. Throughout the following equations, the value of the "mean radius," "hydraulic mean depth," or quotient, $\frac{\text{area A B D C A}}{\text{border B D C A}}$,* is designated by the letter r , remarking here that *for cylindrical pipes flowing full, or rivers with semicircular beds, it is always equal to half the radius, or one-fourth of the diameter.*

Du Buât was the first to observe that the head due to the resistance of friction for water flowing in a uniform channel increased directly as the length of the channel l , directly as the border, and inversely† as the

* M. Girard has conceived it necessary to introduce the coefficient of correction 1.7 as a multiplier to the border for finding r , to allow for the increased resistance from aquatic plants; so that, according to his reduction,

$$r = \frac{\text{area}}{1.7 \text{ border}}.$$

See Rennie's First Report on Hydraulics as a branch of Engineering; Third Report of the British Association, p. 167; also, equation (85), p. 216. The Author has known cases in very irregular channels in which for this sort of correction

$$r = \frac{\text{area}}{4 \text{ border}}.$$


In other words, where the velocity found from the common formula, from the fall per mile, required to be reduced one-half to find the actual mean velocity.

† Pitot had previously, in 1726, remarked that the diminution arising from friction in pipes is, *ceteris paribus*, inversely as the diameters.

area of the cross-flowing section, very nearly; that is, as $\frac{l}{r}$. It also increases as the square of the velocity, nearly; therefore the head due to the resistance must be proportionate to $\frac{v^2 l}{2 g r}$. If $c_t \times \frac{v^2 l}{2 g r} = h_t$, then c_t is the coefficient for the head due to the resistance of friction, as h is the head necessary to overcome the friction at the given velocity; c_t is therefore termed "*the coefficient of friction.*" It is found to increase as the velocity decreases.


HYDRAULIC INCLINATION.—TRAIN.

If l be the length of a pipe or channel, and h_t the height due to the resistance of friction of water flowing in it, then $\frac{h_t}{l}$ is the *hydraulic inclination*. In Fig. 81 the tubes A B, C D, of the same length l , and whose



discharging extremities B and D are on the same horizontal plane B D, will have the same hydraulic inclination and the same discharge, no matter what the actual inclinations or the depth of the entrances at A and C may be, if they are of the same kind and bore; and as the velocities in A B and C D are the same, the height

h due to them must be the same when the circumstances of the orifices of entry A and C are alike. The whole head is $H = h + h_f$ (see pp. 161 and 162, &c.) The hydraulic inclination is not therefore the whole head H , divided by the length l of the pipe, as it is sometimes mistaken for, but the height h_f (found by subtracting the height h , due to the entrance at A or C , and the velocity in the pipe, from the whole height) divided by the length l . When the height h is very small compared with the head h_f due to friction, or to the whole height H , as it is in very long tubes with moderate heads; $\frac{H}{l}$ may be substituted for $\frac{h_f}{l}$ without error; but for short pipes up to 1000 diameters in length the latter only should be used in applying Du Buât's and some other formulæ, which only allow for the head due to friction; otherwise the results will be too large, and only fit to be used approximately in order to determine the height h from the velocity of discharge thus found. When the horizontal pipe $C D$, Fig. 32, is equal in every way



to the inclined pipe $A B$, and the head at A is that due to the velocity in $C D$, the discharge from the pipe $A B$ will be equal to that from $C D$; but a peculiar property belongs to the pipe $A B$ in the position in which it is

here placed ; for if it be cut short at any point *e*, or lengthened to any extent, to *E*, the discharge will remain the same and equal to that through the horizontal pipe *C D*. The velocity in *A B* at the angle of inclination *A B C*, when $A C = h_t$, and $A B = C D$, is therefore such that it remains unaffected by the length *A E* or *A e*, to which it may be extended or cut short ; and at this inclination the water in the pipe *A B* is said to be “in train.” In like manner a river or stream is said to be “in train” when the inclination of its surface bears such a relation to the cross section that the mean velocity is neither accelerated nor retarded by the length of the channel ; and it can be perceived from this that the acceleration that would be caused by the inclination is exactly counterbalanced by the resistances to the motion when the moving water in a pipe or river channel is in train.

Some writers and engineers appear to confound the inclination of a pipe, simply so called, or the head divided by the length, with the hydraulic inclination ; and consequently have fallen into error in applying such of the known formulæ as take into consideration only the head due to the resistance of friction. When pipes are of considerable length, and the water is supplied from a reservoir at one end, the inclination, found as above, and the hydraulic inclination, may be taken equal to each other without sensible error ; but for shorter pipes, of say up to 800 or 1000 diameters long, the greater number of formulæ, as Du Buât's and others, do not directly apply ; and it is necessary to take into consideration the head due to the orifice of entry, the velocity in the tube, and also to the

impulse of supply when there are junctions. These separate elements, and their effects, will be now considered; but it will be of use to refer a little farther on to some experiments, and the imperfect application of formulæ to them, first premising that a *pipe may be horizontal, or even turn upwards, and yet have a considerable hydraulic inclination.*

As $h = (1 + c_r) \frac{v^2}{2g}$ where c_r is the coefficient of the height due to the resistance at the orifice of entry A or C, and $h_t = c_t \frac{v^2 l}{2g r}$, therefore

$$(73.) \quad H = (1 + c_r) \frac{v^2}{2g} + c_t \times \frac{l v^2}{2g r} = \left(1 + c_r + c_t \frac{l}{r}\right) \frac{v^2}{2g},$$

and hence the mean velocity of discharge is found to be

$$(74.) \quad v = \left\{ \frac{2gH}{1 + c_r + c_t \frac{l}{r}} \right\}^{\frac{1}{2}} = \left\{ \frac{\frac{r}{c_t} \times 2gH}{(1 + c_r) \frac{r}{c_t} + l} \right\}^{\frac{1}{2}};$$

or,

$$(74A.) \quad v = \left\{ \frac{2gH}{\frac{1}{c_d^2} + c_t \frac{l}{r}} \right\}^{\frac{1}{2}} = \left\{ \frac{2gHr}{\frac{r}{c_d^2} + c_t l} \right\}^{\frac{1}{2}};$$

as $c_d^2 = \frac{1}{c_r + 1}$, equation (65). Also this last equation by another change of form becomes

$$(74B.) \quad v = \sqrt{2gH} \times \left\{ \frac{1}{\frac{1}{c_d^2} + c_t \times \frac{l}{r}} \right\}^{\frac{1}{2}};$$

* See equations (152) and (152A) for a still more general expression for the velocity; and page 229, for the value of c_t suited to various velocities.

the values of the second member on the right-hand side of this equation, or of

$$\left\{ \frac{1}{\frac{1}{c_d^2} + c_t \times \frac{l}{r}} \right\}^{\frac{1}{2}}$$

are given, for different values of c_t , c_d , and $\frac{l}{r}$, in the small table at p. 146, and below at p. 199.

When h is small compared with h_t , or, which comes to the same thing, $1 + c_t$ small compared with $c_t \times \frac{l}{r}$,

$$(75.) \quad H = c_t \times \frac{l v^2}{2 g r},$$

and

$$(76.) \quad v = \left\{ \frac{2 g r \frac{H}{l}}{c_t} \right\}^{\frac{1}{2}}.$$

In the last equation, if s be substituted for $\frac{H}{l}$, equal the sine of the angle of inclination $\triangle B C$, then

$$(77.) \quad v = \left\{ \frac{2 g r s}{c_t} \right\}^{\frac{1}{2}}.$$

The average value of c_t for all pipes with straight channels, with velocities of about 1.5 foot per second, may be taken at .0069914, from which equation (77) becomes, for measures in feet,

$$(78.) \quad v = 96 \sqrt{r s}.$$

As the mean value of the coefficient of resistance c_t for the entrance into a tube is .508, and as $2 g = 64.408$, and $c_t = .0069914$, equation (74), for measures in feet, becomes

$$(79.) \quad \left\{ \begin{array}{l} v = \left\{ \frac{64 \cdot 403 \, H}{1 \cdot 508 + \cdot 0069914 \frac{l}{r}} \right\}^{\frac{1}{2}}, \text{ or} \\ v = \left\{ \frac{H r}{\cdot 0234 r + \cdot 0001085 l} \right\}^{\frac{1}{2}}, \text{ or} \\ v = 100 \left\{ \frac{H r}{234 r + 1 \cdot 085 l} \right\}^{\frac{1}{2}}, \text{ or} \\ v = 50 \left\{ \frac{H d}{58 d + 1 \cdot 085 l} \right\}^{\frac{1}{2}}. \end{array} \right.$$

This, multiplied by the section, gives the discharge.

For velocities between 2 and $2\frac{1}{2}$ feet per second, $c_t = \cdot 0064403$, and therefore

$$v = \left\{ \frac{H r}{\cdot 0234 r + \cdot 0001 l} \right\}^{\frac{1}{2}} = 50 \left\{ \frac{H d}{58 d + l} \right\}^{\frac{1}{2}},$$

in which $d = 4r =$ diameter of a pipe.

The following table is calculated from equation (74B) for a velocity of about 20 feet per second,* when $c_t = \cdot 004556$, and for different orifices of entry, in which c_d varies from $\cdot 986$ for a rounded orifice, to $\cdot 715$ when the pipe projects into the vessel. It gives directly the coefficient, which, multiplied by $\sqrt{2 g H}$, gives the velocity in the pipe, taking friction into account.

The small table SECTION VI., p. 146, gives the like coefficients of $\sqrt{2 g H}$ in equation (74B), when $c_t = \cdot 00699$ suited to a velocity of about 18 inches per second, and can be applied in like manner. The value of $\sqrt{2 g H}$ is given, in inches, in column 2, TABLE II. For feet it is equal $8 \sqrt{H}$ nearly.

Mr. Provis's valuable experiments† with $1\frac{1}{2}$ -inch

* See p. 146.

† Transactions of the Institution of Civil Engineers, vol. ii. pp. 201—210.

$$\text{VALUES OF } \left\{ \frac{1}{\frac{1}{c_d^2} + c_t \times \frac{l}{r}} \right\}^{\frac{1}{2}}$$

FOR VELOCITIES OF ABOUT 20 FEET PER SECOND.*

Number of diameters in the length of the pipe.	Corresponding coefficients of discharge.			Number of diameters in the length of the pipe.	Corresponding coefficients of discharge.		
2 diameters	·986	·814	·715	900 diameters	·239	·236	·233
5 "	·957	·791	·698	950 "	·234	·230	·227
10 "	·919	·769	·683	1000 "	·228	·225	·222
15 "	·886	·749	·669	1050 "	·233	·220	·217
20 "	·855	·731	·656	1100 "	·218	·215	·213
25 "	·828	·713	·643	1200 "	·209	·207	·205
30 "	·804	·698	·632	1400 "	·194	·192	·191
35 "	·781	·683	·620	1600 "	·182	·180	·179
40 "	·760	·668	·610	1800 "	·172	·171	·170
45 "	·741	·655	·600	2000 "	·163	·162	·161
50 "	·723	·643	·590	2200 "	·156	·155	·154
55 "	·706	·632	·580	2400 "	·149	·149	·148
100 "	·595	·548	·514	2600 "	·144	·143	·142
150 "	·518	·485	·462	2800 "	·139	·138	·137
200 "	·464	·440	·422	3000 "	·134	·133	·133
250 "	·424	·405	·391	3200 "	·130	·129	·129
300 "	·392	·378	·366	3400 "	·126	·125	·125
350 "	·367	·356	·345	3600 "	·122	·121	·121
400 "	·346	·336	·329	3800 "	·119	·119	·118
450 "	·329	·319	·314	4000 "	·116	·116	·115
500 "	·314	·307	·300	4210 "	·113	·113	·113
550 "	·301	·295	·289	4400 "	·111	·111	·111
600 "	·289	·283	·278	4600 "	·108	·108	·108
650 "	·279	·273	·269	4800 "	·106	·106	·106
700 "	·269	·265	·261	5000 "	·104	·104	·104
750 "	·261	·257	·253	5200 "	·102	·102	·102
800 "	·253	·249	·246	5400 "	·100	·100	·100
850 "	·246	·242	·239	5600 "	·098	·098	·098

pipes, from 20 to 100 feet long, have been used in a published work† for the purpose of testing the accuracy of Du Buât's and some other formulæ ; but the head

* See p. 146.

† Researches in Hydraulics. Weale's Quarterly Papers on Engineering.

divided by the length is assumed to be the hydraulic inclination throughout, and no allowance is made for the head due to the orifice of entry and velocity in the pipe. Of course the writer's conclusions are erroneous. It is shown, SECTION I., page 16, how very nearly the formulæ and experiments agree.

The formulæ appear to have been also misunderstood by the surveyor who experimented for the General Board of Health; for the inclination of the pipe in itself is assumed to be the hydraulic inclination, and no allowance is made for the head due to the impulse of supply. In the *CIVIL ENGINEER AND ARCHITECT'S JOURNAL*, Vol. XV., page 366, it is stated that "the chief results as respect the house drains are thus described in the examination of the surveyor appointed to make the trials."*

"What quantity of water would be discharged through a 3-inch pipe on an inclination of 1 in 120?—Full at the head it would discharge 100 gallons in three minutes, the pipe being 50 feet in length. This is with stone-ware pipe manufactured at Lambeth. This applies to a pipe receiving water only at the inlet, the water not being higher than the head of the pipe.

"What water was this?—Sewage-water of the full consistency, and it was discharged so completely that the pipe was perfectly clean.

"At the same inclination what would a 4-inch pipe discharge with the same distances?—Twice the amount (that I found from experiment); or, in other words, 100 gallons would be discharged in half the time. This likewise applies to a pipe receiving water only at the inlet, and of not greater height than the head. In these cases the section of the stream is diminished at the outlet to about half the area of the pipe.

"Before these experiments were made, were there not various hypothetical formulæ† proposed for general use?—Yes.

* Minutes of Information with reference to Works for the removal of Soil, Water, or Drainage, &c., &c. Presented to both Houses of Parliament, 1852.

† It is a mistake to call those formulæ hypothetical, unless so far as

"What would these formulæ have given with a 3-inch pipe, and at an inclination of 1 in 100? and what was the result of your experiments with the 3-inch pipe?—The formulæ would give 7 cubic feet, the actual experiment gave $11\frac{1}{2}$ cubic feet; converting it into time, the discharge, according to the formulæ, compared with the discharge found by actual practice, would be as 2 to 3.

"How would it be with a 4-inch pipe?—The formulæ would give about 14·7 cubic feet per minute, whereas practice gave 23 cubic feet per minute.

"Take the case of a 6-inch pipe of the same inclination?—The results, according to Mr. Hawksley's formula, would be $40\frac{1}{2}$ cubic feet per minute; from experiment it was found to be $63\frac{1}{2}$ cubic feet per minute.

"Then with respect to mains and drainage over a flat surface, the result of course becomes of much more value, as the difference proved by actual practice increases with the diminution of the inclination!—Certainly, to a very great extent. For example, the tables give only 14·2 cubic feet per minute as the discharge from a pipe 6 inches diameter, with a fall of 1 in 800; practice shows that, under the same conditions, 47·2 cubic feet will be discharged.

"Will you give an example of the practical value of this when it is required to carry out drainage works over a very flat surface?—An inclination of 1 in 800 gives only 14 cubic feet per minute, according to theory, while, according to actual experiment, and with the same inclination, 47 cubic feet are given.

"Then this difference may be converted either into a saving of water to effect the same object, or into power of water to remove feculent matter from beneath the site of any houses or town!—It may be so.

"And also the power of small inclinations properly managed?—Yes; for example, if it was required to construct a water course that

the hypothesis is founded on observed facts. Every formula in practical use is founded on experiments, and has been deduced from them, but those formulæ are too often hypothetically applied to short tubes without the necessary corrections. It will be seen in this SECTION that the experiments from which the formulæ given were derived, were in every way greatly more extensive than those made by the directions of the Board of Health. The formula named as Mr. Hawksley's is, substantially, Eytelwein's algebraically transformed.

should discharge, say 200 feet per minute, the formula would require an inclination of 1 in 60 = 2 inches in 10 feet; whereas, experiment has shown that the same would be discharged at an inclination of 1 in 200 = $\frac{1}{2}$ inch in 10 feet, thus effecting a considerable saving in excavation, or a smaller drain would suffice at the greater inclination."

The results given above are calculated in the following Table, and also eight of the experiments made for the Metropolitan Commissioners of Sewers* ; assuming for the present, with the surveyor, examined by the Commissioners, that the inclinations of the pipes and hydraulic inclinations of the formulæ are the same, *which is incorrect*, the calculated discharges, found by means of TABLES VIII. and IX., are given in the last column of the Table.

Diameter of pipe in inches.	Inclination of pipe.	Discharge in cubic feet per minute by experiment.	Hypothetical discharge by Du Buât's formula.
3	1 in 120	5.3	6.6
4	1 in 120	10.7	14
3	1 in 100	11.2	7.5
4	1 in 100	23	15.6
6	1 in 100	63.5	43.8
6	1 in 800	47.2	13.3
6	1 in 60	75	59.3
6	1 in 100	63	43.8
6	1 in 160	54	33.4
6	1 in 200	52	29.2
6	1 in 320	49	21.8
6	1 in 400	48.5	19.6
6	1 in 800	47.2	13.3
6	Level.	46	00

Du Buât's formula, therefore, gives larger results than the experiments in the two first cases, because the water received at one end only barely filled it, and

* Adcock's Engineer's Pocket Book, 1852, pp. 261 and 262.

the pipe was not full at the lower end ; but less in the others. If in these the head due to the impulse of entry, at the upper end, and at the side junctions, were known, and the proper hydraulic inclination determined by the experiments, the formulæ would be found to give larger approximate results in every case, as might have been expected from the sewage-water used. In the last eight experiments it is stated,* that “the water was admitted at the head of the pipe, and at *five junctions or tributary pipes* on each side, so regulated as to keep the main pipe full,” and that “without the addition of junctions the transverse sectional area of the stream of water near the discharging end was reduced to one-fifth of the corresponding area of the pipe, *and that it required a simple head of water of about 22 inches to give the same result as that accruing under the circumstances of the junctions.*” It is also stated, that “in the case of the 6-inch pipe, which discharged 75 cubic feet per minute, the lateral streams had a velocity of a few feet per minute.”

Now, the head of “about 22 inches” is wholly neglected in the foregoing calculations, *though in a pipe 100 feet long it would be equal to an inclination of 1 in 55!* It however includes three elements at least, viz., the portion due to the orifice of entry, the portion due to the velocity in the pipe, and the portion due to friction. Assume the case of *the horizontal pipe, which discharged 46 cubic feet per minute.*† This is

* Adcock's Engineer's Pocket Book, 1852, pp. 261 and 262.

† The horizontal pipe would discharge equally at both ends, unless there was a head of water at either, or an equivalent in the velocity of

equal to a mean velocity of 46·9 inches per second; with this velocity, we find from TABLE VIII. the hydraulic inclination of a 6-inch pipe to be 1 in 94, and, therefore, the head due to friction in a pipe 100 feet long is 12·7 inches. Assuming the coefficient for the orifice of entry and velocity to be ·815, we also find from TABLE II. a head of $4\frac{1}{4}$ inches due to these. We then have,

Head due to the velocity and orifice of entry	4·25 inches
Head due to the resistance of friction	12·70 „
Radius of pipe	3·00 „
<hr/>	
Total	19·95

which is about 2 inches less than the observed head: this, however, is not stated definitely. *It is therefore evident, that the formula gives, if anything, larger results than these experiments,* as might have been expected, instead of less in the ratio of 2 to 3, as is stated in the Report.*

Wherever junctions are applied, as in the examples above referred to, the formulæ in general use require correction; for the quantity of water then flowing below each junction is increased. A certain amount of error is, perhaps, inseparable from every calculation of this kind; but before formulæ deduced from experiment by men every way qualified for the task are condemned, it would be well that their critics should learn to understand and properly apply them.

approach. Of course, a smaller pipe with a fall, must be better than the larger one with none at all, in preventing deposits.

* This is also true of the other formulæ, for finding the discharge from pipes, given in this work.

The diameter of a short pipe gives in itself the means of increasing very considerably the surface inclination of the fluid stream, by reducing the section at the lower end. Assume a horizontal pipe 50 feet long and 6 inches in diameter, then if the receiving end be full, and the discharging end one-third full, this inclination will be $\frac{6-2}{50 \times 12} = \frac{1}{150}$; and that the discharging end cannot be kept full unless a head of several inches be maintained at the receiving end, or an equivalent from a lateral supply. When the pipe is about two diameters long it becomes a short tube; and when the length vanishes, the transverse section becomes, simply, a discharging orifice.

DU BUÂT'S FORMULA.

The coefficient of friction c_f is not, however, constant, as it varies with the velocity. That given, p. 198, viz., $c_f = .004556$ answers for pipes when the velocity is 20 feet per second. For pipes and rivers it is found to increase as the velocity decreases; that is, the loss of head is proportionately greater for small than for large velocities. Du Buât found the loss of head to be also greater for small than large channels, and applied a correction accordingly in his formula. This, expressed in French inches, is

$$(80.) \quad v = \frac{297 (r^{\frac{1}{2}} - .1)}{\left(\frac{1}{s}\right)^{\frac{1}{2}} - \text{hyp. log.} \left(\frac{1}{s} + 1.6\right)^{\frac{1}{2}}} - .3 (r^{\frac{1}{2}} - .1),$$

maintaining the preceding notation, in which $s = \frac{h}{l}$.

In this formula $\cdot 1$, in the numerator of the first term, is deducted as a correction due to the hydraulic mean depth, as it was found that $297(r^{\frac{1}{2}} - 0.1)$ agreed more exactly with experiment than $297r^{\frac{1}{2}}$ simply. The second term $\text{hyp. log.} \left(\frac{1}{s} + 1.6 \right)^{\frac{1}{2}}$, of the denominator is also deducted to compensate for the observed loss of head being greater for less velocities, and the last term $\cdot 3(r^{\frac{1}{2}} - \cdot 1)$ is a deduction for a general loss of velocity sustained from the unequal motions of the particles of water in the cross section as they move along the channel. These corrections are empirical; they were, however, determined separately, and after being tested by experiment, applied, as above, to the radical formula $v = 297 \sqrt{r s}$.

Du Buât's formula was published in his *Principes d'Hydraulique*, in 1786. It is, as we have seen, partly empirical, but deduced by an ingenious train of reasoning and with considerable penetration from about 125 experiments, made with pipes from the 19th part of an inch to 18 inches in diameter, laid horizontally, inclined at various inclinations, and vertical; and also from experiments on open channels with sectional areas from 19 to 40,000 square inches, and inclinations of from 1 in 112 to 1 in 36,000. The lengths of the pipes experimented with varied from 1 to 3, and from 3 to 3,600 feet.

In several experiments by which the author has tested this formula, the resulting velocities found from it were from 1 to 5 per cent. too large for small pipes, and too small for straight rivers in nearly the same

proportion. As the experiments from which it was derived were made with great care, those with pipes particularly so, this was to be expected. Experiments with pipes of moderate or short lengths should have the circumstances of the orifice of entry from the reservoir duly noted; for the close agreement of this formula with them must depend a great deal, in such pipes, on the coefficient due to the height h , which must be deducted from the whole head H before the hydraulic inclination, $\frac{h_f}{l} = s$, can be obtained; but for very long pipes and uniform channels this is not necessary.

The experiments from which Du Buât's formula was constructed are given in full by the late Dr. Robinson in his able article on "rivers" in the *Encyclopædia Britannica*, pp. 268, 269, and 270, where the calculated and observed velocities are placed side by side in French inches per second. In all these experiments Du Buât carefully deducted the head due to the velocity and orifice of entry before finding the hydraulic inclination s , and those who attempt to calculate the velocity from the head and length of the channel only, without making this deduction, will find their calculated results very different from those there given. If there were bends, curves, or contractions, deductions would have to be made for these in like manner before finding s .

Under all the circumstances, and after comparing the results obtained from various other formulæ, the author originally preferred calculating tables for the values of v from this formula reduced for measures in English inches, which is

$$v = \frac{306.596 (r^{\frac{1}{2}} - .1032)}{\left(\frac{1}{s}\right)^{\frac{1}{2}} - \text{hyp. log.} \left(\frac{1}{s} + 1.6\right)^{\frac{1}{2}}} - .2906 (r^{\frac{1}{2}} - .1032),$$

or more simply,

$$(81.) \quad v = \frac{307 (r^{\frac{1}{2}} - .1)}{\left(\frac{1}{s}\right)^{\frac{1}{2}} - \text{hyp. log.} \left(\frac{1}{s} + 1.6\right)^{\frac{1}{2}}} - .3 (r^{\frac{1}{2}} - .1).$$

This gives the value of v a little larger than the original formula, but the difference is immaterial. For measures in English feet it becomes

$$(82.) \quad v = \frac{88.51 (r^{\frac{1}{2}} - .03)}{\left(\frac{1}{s}\right)^{\frac{1}{2}} - \text{hyp. log.} \left(\frac{1}{s} + 1.6\right)^{\frac{1}{2}}} - .084 (r^{\frac{1}{2}} - .03).$$

The results of equation (81.) are calculated for different values of s and r , and tabulated in TABLE VIII.,* the first eight pages of which contain the velocities for values of r varying from $\frac{1}{16}$ th inch to 6 inches; or if pipes, diameters from $\frac{1}{4}$ inch to 2 feet, and of various inclinations from horizontal to vertical. The last five pages contain the velocities for values of r from 6 inches to 12 feet, and with falls from 6 inches to 12 feet per mile.

EXAMPLE VIII. *A pipe, $1\frac{1}{2}$ inch diameter and 100 feet long, has a constant head of 2 feet over the discharging extremity; what is the velocity of discharge per second?*

* When this TABLE was first calculated, the author's formula (119A) was not known, and as a development of Du Buat's valuable but complex expression the table is retained. Others have since given TABLES calculated from (119A), but the formula itself is easily remembered, and results for any particular case easily calculated; especially so by using the last column of the table attached to it.

The mean radius $r = \frac{1\frac{1}{2}}{4} = \frac{3}{8}$ inches, and $\frac{100}{2} = 50 = \frac{1}{s}$, is the approximate hydraulic inclination. At page 2 of TABLE VIII., in the column under the mean radius $\frac{3}{8}$, and opposite to the inclination 1 in 50, is found 30·69 inches for the velocity sought. This, however, is but approximative, as the head due to the velocity should be subtracted from the whole head of 2 feet, before finding the true hydraulic inclination. This head depends on the coefficient of resistance at the entrance orifice, or the coefficient of discharge for a short tube. In all Du Buât's experiments this latter was taken at ·8125, but it will depend on the nature of the junction, as, if the tube runs into the cistern, it will become as small as ·715; and, if the junction be rounded into the form of the contracted vein, it will rise to ·974, or 1 nearly. In this case, the coefficient of discharge may be assumed ·815,* from which, in TABLE II., the head due to a velocity of 30·69 inches is $1\frac{7}{8} = 1·87$ inch nearly, which is the value of h ; and hence, $H - h = h_1 = 24 - 1·87 = 22·13$ inches; and $\frac{l}{h_1} = \frac{100 \times 12}{22·13} = 54·2 = \frac{1}{s}$, the hydraulic inclination, more correctly. With this new inclination and the mean radius $\frac{3}{8}$, the velocity by interpolating between the inclinations 1 in 50 and 1 in 60, given in the table, is $30·69 - 1·34 = 29·35$ inches per second. This operation may be repeated until v is found to any degree of accuracy according

* See EXAMPLE 16, pp. 14, 15.

to the formula; but it is, practically, unnecessary to do so. The discharge per minute in cubic feet, is now easily found from TABLE IX., in which, for an inch and a half pipe,

		Inches.			Cubic feet.
For a velocity of 20·00			per second,		1·22718 per minute.
„	„	9·00	„	„	·55223 „ „
„	„	·30	„	„	·01841 „ „
„	„	·04	„	„	·00245 „ „
		<hr/>		<hr/>	
„	„	29·34	„	„	1·80027 „ „

The discharge found experimentally by Mr. Provis, for a tube of the same length, bore, and head, was 1·745 cubic foot per minute.

If the coefficient of discharge due to the orifice of entry and stop-cock in Mr. Provis's 208 experiments* with $1\frac{1}{2}$ inch lead pipes of 20, 40, 60, 80, and 100 feet lengths, be ·715, the results calculated by the tables will agree with the experimental results with very great accuracy, and it is very probable, from the circumstances described, that the ordinary coefficient ·815 due to the entry was reduced by the circumstances of the stop-cock and fixing to about ·715; but even with ·815 for the coefficient, the difference between calculation and experiment is not much, the calculation being then in excess in every experiment, the average being about 5 per cent., and not so much in the example we have given.

TABLE VIII. gives the velocity, and thence the discharge, immediately, for long pipes, and TABLE X.

* Transactions of the Institution of Civil Engineers, vol. ii. pp. 201, 210,

enables us to calculate the cubic feet discharged per minute, with great facility. For rivers, the mean velocity, and thence the discharge, is also found with quickness. See also TABLES XI., XII., and XIII., and the TABLES at pp. 28 and 29.

EXAMPLE IX. *A watercourse is 7 feet wide at the bottom, the length of each sloping side is 6·8 feet, the width at the surface is 18 feet, the depth 4 feet, and the inclination of the surface 4 inches in a mile; what is the quantity flowing down per minute?*

$$\text{Here } \frac{(18 + 7) \times \frac{4}{2}}{7 + 2 \times 6\cdot8} = \frac{50}{20\cdot6} = 2\cdot4272 \text{ feet} = 29\cdot126$$

inches = r , is the hydraulic mean depth; and as the fall is 4 inches per mile, at the 11th page of TABLE VIII., the velocity $v = 12\cdot08 - \cdot16 = 11\cdot87$ inches per second; the discharge in cubic feet per minute is, therefore,

$$50 \times \frac{11\cdot87}{12} \times 60 = 2967\cdot5.$$

$$\begin{aligned} \text{If } 94\cdot17 \sqrt{rs} &= v, \text{ then } v = 94\cdot17 \sqrt{2\cdot427 + \frac{1}{15840}} \\ &= 94\cdot17 \times \sqrt{\frac{1}{6526}} = \frac{94\cdot17}{80\cdot7} = 1\cdot17 \text{ feet} = 14\cdot04 \text{ inches.} \end{aligned}$$

Watt, in a canal of the fall and dimensions here given, found the mean velocity about $13\frac{1}{2}$ inches per second. This corresponds to a fall of 5 inches in the mile, according to the formula. Du Buât's formula is less by $12\frac{1}{2}$ per cent. or $\frac{1}{8}$ th; the common formula too much by 5 per cent.

In one of the original experiments with which the formula was tested on the canal of Jard, the measurements accorded very nearly with those in this example,

viz. $\frac{1}{8} = 15360$, and $r = 29.1$ French inches; the observed velocity at the surface was 15.74, and the calculated mean velocity, from the formula, 11.61 French inches.* TABLE VII. will give 12.29 inches for the mean velocity, corresponding to a superficial velocity of 15.74 inches. This shows that the formula also gives too small a value for v in this case, by about $\frac{1}{17}$ th of the result, it being about $\frac{1}{8.3}$ part in the other. The probable error in the formula *applied to straight clear rivers* of about 2 feet 6 inches hydraulic mean depth is nearly $\frac{1}{12}$ th or 8 per cent. of the tabulated velocity, and this must be added for the more correct result; the watercourse being supposed straight and free from aquatic plants.

Notwithstanding the differences above remarked on, the results of this formula, as calculated and tabulated, may be pretty safely relied on when applied to *general practical purposes*. Many of the others which we shall proceed to lay before our readers are more partial in their application. Rivers or watercourses are seldom straight or clear from weeds, and even if the sections, during any improvements, be made uniform, they will seldom continue so, as "*the regimen*," or adaptation of the velocity to the tenacity of the banks, must vary with the soil and bends of the channel, and can seldom continue permanent for any length of time unless protected. From these causes a loss of velocity takes place, difficult, if not impossible,

* These measures reduced to inches, give $r = 31.014$, $v = 12.374$; and the surface velocity 16.775 inches; reduced for mean velocity 13.101 inches.

to estimate accurately, but which may be taken at from 10 to 100 per cent. of that in the clear unobstructed direct channel; but be this as it may, *it is safer to calculate the drainage or mechanical results obtainable from a given fall and river channel, from formulæ which give lesser, than from those which give larger velocities.* This is a principle engineers cannot too much observe.

It was before remarked, that for both pipes and rivers the coefficient of resistance increases as the velocity decreases. This is as much as to say, in the simple formula for the velocity, $v = m \sqrt{rs}$, that m must increase with v , and as some function of it. This is the case in TABLE VIII., throughout which the velocities increase faster than \sqrt{r} , the \sqrt{s} , or the \sqrt{rs} . In all formulæ made use of by engineers, but the author's, Weisbach's, Du Buât's and Young's, *the velocity found is constant when \sqrt{rs} or $r \times s$ is constant.* In Du Buât's formula for $r \times s$ constant, v obtains maximum values between $r = \frac{3}{8}$ inch and $r = 1$ inch; the differences of the velocities for different values of r above 1 inch, $r \times s$ being constant, are not much. The maximum value, or nearly so, may always be found by assuming $r = \frac{3}{8}$ inch, and finding the corresponding inclination from the formula $\frac{4rs}{8}$, which is equal to it. For example, if $r = 12$ inches, and $s = \frac{1}{10680}$, the velocity is found equal 9.52 inches; but when rs is constant, the inclination s corresponding to $r = \frac{3}{8}$ inch is $\frac{4 \times 12^2}{3 \times 10680} = \frac{1}{860}$, from which, is found from the table, $v = 10.25$

inches, for the maximum velocity, making a difference of fully 7 per cent.

When $r = .01$ of an inch, or a pipe is $\frac{1}{25}$ th part of an inch in diameter, Du Buât's formula fails, but it gives correct results for pipes $\frac{1}{8}$ th of an inch in diameter, and two of the experiments from which it was derived were made with pipes 12 inches long and only $\frac{1}{16}$ th part of an inch in diameter.

TABLE VIII. is extended so as to make it directly available for hydraulic mean depths, from $\frac{1}{16}$ th of an inch to 12 feet, and for various hydraulic inclinations, even up to vertical, for pipes. The fall in rivers seldom exceeds 2 or 3 feet per mile, or the velocity 5 or 6 feet per second. The extension of the Table for great inclinations, and consequently great velocities, was made for the purposes of calculation, and to include pipes. It must be understood throughout this TABLE that the velocities are those which continue unchanged for any length of channel, viz., when the resistance of friction is equal to the acceleration of gravity, the moving water and channel being then *in train*. Several of Du Buât's experiments were made with small vertical pipes. This TABLE is equally applicable to pipes and rivers, and gives directly either the hydraulic inclination, the hydraulic mean depth, or the velocity when any two of them are known.

The mean velocity is given in preference to the discharge itself in TABLE VIII., because, while an infinite number of channels having the same hydraulic inclination (s) and the same hydraulic mean depth (r) must have the same velocity (v), yet the sectional

areas, and consequently the discharges, may vary upwards from $6.2832r^3$, the area of a semicircular channel, to any extent; and the operation of multiplying the area by the mean velocity, to find the discharge, is so very simple that any tabulation for that purpose is unnecessary. Besides this, the banks of rivers, unless artificially protected, remain very seldom at a constant slope, and therefore any TABLES of discharge for particular side slopes are only of use so far as they apply to hypothetical cases. Indeed, in new river cuts, the banks, cut first to a given slope, alter very considerably in a few months; while the necessary regimen between the velocity of the water and the channel is in the course of being established. The velocity suited to the permanency of any proposed river channel, though too often entirely neglected, is the very first element to be considered.

COULOMB having shown that the resistance opposed to a disc revolving in water increases as the function $a v + b v^2$ of the velocity v , we may assume that the height due to the resistance of friction in pipes and rivers is also of this form; and that

$$(83.) \quad h_f = (a v + b v^2) \frac{l}{r},$$

and consequently,

$$(84.) \quad r s = a v + b v^2, \text{ and } v = \left\{ \frac{r s}{b} + \frac{a^2}{4 b^2} \right\}^{\frac{1}{2}} - \frac{a}{2 b}.$$

GIRARD first gave values to the coefficients a and b . He assumed them equal, and each equal to .0003104 for measures in metres, and thence the velocity in canals,

(85.) $v = (3221 \cdot 016 \, r s + \cdot 25)^{\frac{1}{2}} - \cdot 5$; *
which reduced for measures in English feet becomes

$$(86.) \quad \begin{cases} v = (10567 \cdot 8 \, r s + 2 \cdot 67)^{\frac{1}{2}} - 1 \cdot 64, \text{ or} \\ v = 103 \sqrt{r s} - 1 \cdot 64, \text{ nearly.} \end{cases}$$

The value of $a = b = \cdot 0003104$ was obtained by means of twelve experiments by Du Buât and Chezy. Of course the value is four times this in the original, as the mean radius is used in all the formulæ instead of the diameter. This formula is only suited for very small velocities in canals, between locks, containing aquatic plants; it is inapplicable to rivers and channels in which the velocity exceeds an inch per second.

PRONY found from thirty experiments on canals, that $a = \cdot 000044450$ and $b = \cdot 000309314$,† for measures in metres, from which

$$(87.) \quad v = (3232 \cdot 96 \, r s + \cdot 00516)^{\frac{1}{2}} - \cdot 0719;$$

this reduced for measures in English feet is,

$$(88.) \quad \begin{cases} v = (10607 \cdot 02 \, r s + \cdot 0556)^{\frac{1}{2}} - \cdot 236; \text{ or} \\ v = 103 \sqrt{r s} - \cdot 24 \text{ nearly:} \end{cases}$$

the velocities did not exceed 3 feet per second in the experiments from which this was derived. See also note, p. 192.

For pipes, Prony found,‡ from fifty-one experiments made by Du Buât, Bossut, and Couplet, with pipes from 1 to 5 inches in diameter, from 80 to 7,000 feet in length, and one pipe 19 inches diameter and nearly

* See Brewster's *Encyclopædia*, Article Hydrodynamics, p. 259.

† *Recherches Physico-Mathématiques sur la Théorie des Eaux Courantes*.

‡ *Recherches Physico-Mathématiques sur la Théorie du Mouvement des Eaux Courantes*, 1804.

TABLE of the fifty-one Experiments referred to in Equation (89), the value of g in the sixth being taken at 9.8088 metres.

It will be perceived that Prony did not take into calculation, in framing his formula, the head due to the velocity in the pipe and to the orifice of entry.

Number of selected experiments.	Names of Experimenters.	Heads measured to the lower orifice in metres.	Diameters of pipes in metres.	Length of the pipes in metres.	Values of $\frac{p}{\rho} + \frac{v^2}{2g}$ in metres.	Experimental values of the velocity v in metres.	Calculated velocity from formula (89) in metres.
1	Du Buât	.0041	.0271	19.95	.000814	.0430	.0427
2	Couplet	.1511	.1353	2280.37	.000404	.0544	.0591
3	Couplet	.3068	.13.3	2280.37	.000523	.0654	.0921
4	Du Buât	.0135	.02707	19.95	.000459	.0980	.0926
5	Couplet	.4534	.1333	2280.37	.000590	.1117	.1263
6	Couplet	.5105	.1333	2280.37	.000638	.1301	.1330
7	Couplet	.6497	.1333	2280.37	.000670	.1411	.1433
8	Couplet	.6767	.1333	2280.37	.000683	.1441	.1467
9	Du Buât	.0189	.0271	3.75	.001426	.2352	.2895
10	Du Buât	.1137	.0271	3.75	.001133	.2826	.3088
11	Du Buât	.1137	.0271	3.75	.001309	.2888	.3088
12	Bossut	.1083	.0271	16.24	.001337	.3308	.3359
13	Bossut	.3248	.0361	58.47	.001446	.3400	.3553
14	Du Buât	.1605	.0271	19.95	.001482	.3604	.3713
15	Bossut	.3248	.0361	48.73	.001549	.3807	.3915
16	Du Buât	.2106	.0271	19.95	.001713	.4091	.4287
17	Bossut	.3248	.0361	38.98	.001687	.4366	.4402
18	Du Buât	.2425	.0271	19.95	.001830	.4408	.4618
19	Bossut	.3248	.0544	58.47	.001672	.4433	.4416
20	Du Buât	.2425	.0271	19.95	.001793	.4500	.4618
21	Bossut	.3248	.0544	48.73	.001795	.4955	.4860
22	Bossut	.6497	.0361	58.47	.001922	.5115	.5122
23	Bossut	.3248	.0361	29.23	.001918	.5128	.5122
24	Du Buât	.3335	.0271	19.95	.002050	.5411	.5450
25	Bossut	.3248	.0544	38.98	.001981	.5605	.5458
26	Du Buât	.3709	.0271	19.95	.002174	.5676	.5766
27	Bossut	.6497	.0361	48.73	.002073	.5693	.5694
28	Du Buât	.3952	.0271	19.95	.002223	.5916	.5961
29	Bossut	.3248	.0271	26.24	.002201	.6032	.5990
30	Bossut	.3248	.0361	19.49	.002333	.6323	.6327
31	Bossut	.3248	.0544	29.23	.002300	.6444	.6344
32	Bossut	.6497	.0361	38.98	.002267	.6498	.6323
33	Bossut	.6497	.0544	58.47	.002214	.6695	.6344
34	Bossut	.6497	.0544	48.73	.002392	.7486	.6972
35	Bossut	.6497	.0361	29.23	.002538	.74	.7343
36	Du Buât	.6416	.0271	19.95	.002750	.7761	.7660
37	Bossut	.3248	.0544	19.49	.002812	.7908	.7823
38	Du Buât	.1624	.0271	3.75	.003420	.7943	.8930
39	Bossut	.4497	.0544	38.98	.002456	.8363	.7810
40	Bossut	.3248	.0361	9.74	.003287	.8976	.9048
41	Bossut	.65	.0361	19.49	.003161	.9332	.9048
42	Bossut	.65	.0544	29.23	.003062	.9681	.9071
43	Couplet	3.9274	.4873	1169.42	.003785	1.0600	1.0592
44	Bossut	.3248	.0544	9.74	.004073	1.0915	1.1164
45	Bossut	.6497	.0544	19.49	.003821	1.1640	1.1164
46	Bossut	.6497	.0361	9.74	.004491	1.3138	1.2896
47	Du Buât	.4873	.0271	3.17	.006470	1.5784	1.7045
48	Du Buât	.6671	.0271	3.75	.006307	1.5919	1.6898
49	Bossut	.6497	.0544	9.74	.005578	1.5945	1.5890
50	Du Buât	.7219	.0271	3.17	.007838	1.9301	2.0798
51	Du Buât	.9745	.0271	3.17	.008382	2.2994	2.4205

4,000 feet long, that $a = \cdot 00001733$, and $b = \cdot 0003483$, from which values

(89.) $v = (2871 \cdot 09 \, r s + \cdot 0006192)^{\frac{1}{2}} - \cdot 0249$,
for measures in metres, and for measures in English feet,

$$(90.) \quad \begin{cases} v = (9419 \cdot 75 \, r s + \cdot 00665)^{\frac{1}{2}} - \cdot 0816; \text{ or} \\ v = 97 \sqrt{r s} - \cdot 08 \text{ nearly.} \end{cases}$$

Prony also gives the following formula applicable to pipes and rivers. It is derived from fifty-one selected experiments with pipes, and thirty-one with open channels :

(91.) $v = (3041 \cdot 47 \, r s + \cdot 0022065)^{\frac{1}{2}} - \cdot 0469734$,*
for measures in metres, which, reduced for measures in English feet, is

$$(92.) \quad \begin{cases} v = (9978 \cdot 76 \, r s + \cdot 02375)^{\frac{1}{2}} - \cdot 15412; \text{ or} \\ v = 100 \sqrt{r s} - \cdot 15 \text{ nearly.} \end{cases}$$

EYTELWEIN, following the method of investigation pursued previously by Prony, found from a large number of experiments, $a = \cdot 0000242651$, and $b = \cdot 000365543$ in rivers, for measures in metres; and, therefore,

$$(93.) \quad v = (2735 \cdot 66 \, r s + \cdot 001102)^{\frac{1}{2}} - \cdot 0332.$$

This reduced for measures in English feet, is

* *Recherches Physico-Mathématiques sur la Théorie des Eaux Courantes*. A reduction of this formula into English feet is given at page 6, Article Hydrodynamics, *Encyclopædia Britannica*; at page 164, Third Report, British Association, by Rennie, and at pages 427 and 533, Article Hydrodynamics, Brewster's *Encyclopædia*. This reduction $v = -0 \cdot 1541 + (\cdot 02375 + 32806 \cdot 6 \, r s)^{\frac{1}{2}}$ is entirely incorrect; and being the same in each of those works, appears to have been copied one from the other.

† *Mémoires de l'Académie de Berlin*, 1814 et 1815. See equation (110).

$$(94.) \begin{cases} v = (8975 \cdot 48 \, r \, s + \cdot 0118858)^{\frac{1}{2}} - \cdot 1089; \text{ or} \\ v = 94 \cdot 5 \sqrt{r \, s} - \cdot 11 \text{ nearly, or} \\ v = \sqrt{1 \cdot 7 \, f \, r} - \cdot 11 = 1 \cdot 3 \sqrt{f \, r} - \cdot 11 \end{cases}$$

when f is the fall in feet per mile. He also shows,* that $\frac{1}{4}$ ths of a mean proportional between the fall in two English miles and the hydraulic mean depth, gives the mean velocity very nearly. This rule for measures in inches is equivalent to

$$(95.) \quad v = 324 \sqrt{r \, s};$$

and for measures in feet

$$(96.) \quad v = 93 \cdot 4 \sqrt{r \, s}.$$

For the velocity of water in pipes he found,† from the fifty-one experiments of Du Buât, Bossut, and Couplet, that $a = \cdot 0000223$, and $b = \cdot 0002803$, from which for measures in metres,

$$(97.) \quad v = (3567 \cdot 29 \, r \, s + \cdot 00157)^{\frac{1}{2}} - \cdot 0397;$$

which reduced for measures in English feet becomes

$$(98.) \begin{cases} v = (11703 \cdot 95 \, r \, s + \cdot 01698)^{\frac{1}{2}} - \cdot 1303; \text{ or} \\ v = 108 \sqrt{r \, s} - \cdot 13 \text{ nearly.} \end{cases}$$

Another formula given by Eytelwein for pipes, which includes the head due to the velocity for the orifice of entry, is reducible to

* Handbuch der Mechanik und der Hydraulik, Berlin, 1801.

† Mémoires de l'Académie des Sciences de Berlin, 1814 et 1815.

Eytelwein's formula is $v = 90 \cdot 8 \sqrt{r \, s}$ for Prussian feet, and for pipes

$$v = 6 \cdot 42 \sqrt{\frac{50 \, d \, h}{l + 50 \, d}} = 46 \cdot 1 \sqrt{\frac{d \, h}{l + 50 \, d}}; \text{ which he changed}$$

afterwards to $v = 6 \cdot 41 \sqrt{\frac{54 \, d \, h}{l + 54 \, d}} = 47 \cdot 9 \sqrt{\frac{d \, h}{l + 54 \, d}}$. The Prussian foot is here equal to 1·0297 English feet.

$$(99.) \quad v = 50 \left(\frac{dh}{l + 50d} \right)^{\frac{1}{2}};$$

nearly, in which h is the head, l the length, and d the diameter of the pipe, all expressed in English feet. This is a particular value of equation (74) suited to velocities of about $2\frac{1}{2}$ feet per second. It must be here mentioned, that much of the valuable information presented by Prony and Eytelwein is but a modification of what Du Buât had previously given, and to whom, only, for much that is attributed to the two former, we are primarily indebted.

In the foregoing as well as in the following equations for the velocity, unless otherwise stated, one class of standards has been maintained. It is evident, if these standards be changed in part, or in whole, that apparently different forms of the equations will arise; thus—if for s , the hydraulic inclination, we substitute

$\frac{m}{5280}$, the fall m in feet per mile is then used in place of the inclination s ; so that equation (94), for instance, would become

$v = (1.7 m r + .012)^{\frac{1}{2}} - .11 = (1.7 m r)^{\frac{1}{2}} - .11$ nearly, in which v is the velocity, in feet per second, m the fall in feet per mile, and r the “hydraulic mean depth” in feet. In like manner equation (98) would become

$$v = (2.2 m r + .02)^{\frac{1}{2}} - .13 = (2.2 m r)^{\frac{1}{2}} - .13.$$

The first of these reductions, viz. :—

$$v = (1.7 m r + .0119)^{\frac{1}{2}} - .109,$$

is given in a book of tables calculated for river channels for the Commissioners of Public Works,

Ireland, the original equation being Eytelwein's, and not D'Aubuisson's, who merely copied it. It is suited for velocities averaging about 1·3 foot per second. Again

Mr. Hawksley, by changing the form of an old result, gives for pipes the formula

$$v = \cdot 77 \left\{ \frac{d H}{l + 1\cdot 5 d} \right\}^{\frac{1}{2}},$$

in which l is the length in yards, H the head in inches, d the diameter in inches, and v the velocity in yards per second. For uniform feet measures, for, v , d , and H , this becomes

$$v = 48\cdot 045 \left\{ \frac{d H}{l + 54 d} \right\}^{\frac{1}{2}},$$

which is only an alteration in form of Eytelwein's equation, note to (93). Eytelwein's equation expressed in the measures used by Mr. Hawksley would be very nearly

$$v = \cdot 8 \left\{ \frac{d H}{l + 1\frac{1}{2} d} \right\}^{\frac{1}{2}},$$

which is the simpler of the two; both, however, are but particular cases of the general equation (74), and only suited for velocities of about $2\frac{1}{2}$ feet per second.

DR. THOMAS YOUNG* also derives his formula from the supposition, that the head due to the resistance of friction assumes the form of equation (88); calling the diameter of a pipe d , he takes

$$h_f = (a v + b v^2) \frac{l}{d},$$

* Philosophical Transactions for 1808. Young also translated Eytelwein's Handbuch.

and the whole height $H = h_1 + \frac{v_1^2}{586}$, expressed in inches, which corresponds with a coefficient of $\cdot 871$, nearly, for the orifice of entry. He found from some experiments of his own, those collected by Du Buât, and some of Gerstner's, that

$$(100.) \quad a = \cdot 0000002 \left\{ \frac{900 d^2}{d^2 + 1136} + \frac{1}{d^{\frac{1}{2}}} \left(1085 + \frac{13 \cdot 21}{d} + \frac{1 \cdot 0563}{d^2} \right) \right\};$$

and

$$(101.) \quad b = \cdot 0000001 \left\{ 413 + \frac{75}{d} - \frac{1440}{d + 12 \cdot 8} - \frac{180}{d + \cdot 355} \right\};$$

then as $\frac{1}{586} = \cdot 00171$, the value of the velocity becomes

$$(102.) \quad v = \left\{ \frac{H d}{b l + \cdot 00171 d} + \left(\frac{a l}{2 b l + \cdot 00341 d} \right)^2 \right\}^{\frac{1}{2}} - \frac{a l}{2 b l + \cdot 00341 d}.$$

When the length l of the pipe is very great compared with the head due to the orifice of entrance and velocity, $\cdot 00171 v^2$, then

$$(103.) \quad v = \left\{ \frac{H d}{b l} + \frac{a^2}{4 b^2} \right\}^{\frac{1}{2}} - \frac{a}{2 b};$$

or by substituting for $\frac{H}{l}$ its value s , equal the sine of the inclination,

$$(104.) \quad v = \left\{ \frac{s d}{b} + \frac{a^2}{4 b^2} \right\}^{\frac{1}{2}} - \frac{a}{2 b}.$$

The values of a and b are for measures in inches. For most rivers he finds for French inch measures, $v = \sqrt{20000 d s}$, in which d must be taken equal $4 r$; this reduced for English inches is

TABLE OF THE VALUES OF a , b , $\frac{a}{2b}$, AND $\frac{a^3}{4b^3}$, IN EQUATION (104).

d in inches.	r in inches.	a .	b .	$\frac{a}{2b}$.	$\frac{a^3}{4b^3}$.	d in inches.	r in inches.	a .	b .	$\frac{a}{2b}$.	$\frac{a^3}{4b^3}$.
1	.025	.000337	.000066	6.341	40.207	6	1.5	.000094	.000032	1.468	2.155
2	.05	.000336	.000035	7.657	58.629	7	1.75	.000090	.000033	1.363	1.857
3	.075	.000406	.000028	7.250	52.562	8	2	.000087	.000033	1.318	1.737
4	.100	.000356	.000025	7.120	50.694	9	2.25	.000084	.000034	1.235	1.526
5	.125	.000316	.000025	6.320	39.942	10	2.50	.000083	.000034	1.220	1.489
6	.150	.000287	.000024	5.979	35.750	11	2.75	.000083	.000034	1.220	1.489
7	.175	.000264	.000024	5.500	30.250	12	3.00	.000084	.000035	1.200	1.440
8	.200	.000247	.000025	4.940	24.408	15	3.75	.000086	.000035	1.228	1.509
9	.225	.000232	.000025	4.640	21.529	20	5	.000096	.000036	1.333	1.777
1	.250	.000220	.000025	4.400	19.360	40	10	.000140	.000038	1.842	3.393
1.5	.375	.000179	.000027	3.315	10.988	50	12.5	.000154	.000039	1.974	3.898
2	.500	.000155	.000028	2.767	7.661	60	15	.000165	.000039	2.115	4.474
2.5	.625	.000139	.000028	2.482	6.161	80	20	.000177	.000040	2.212	4.895
3.0	.750	.000127	.000029	2.189	4.794	100	25	.000184	.000040	2.300	5.290
3.5	.875	.000119	.000030	1.983	3.933	300	75	.000190	.000041	2.317	5.369
4	1.000	.000111	.000031	1.790	3.205	500	125	.000189	.000041	2.305	5.312
5	1.250	.000101	.000031	1.629	2.653	Infinite.	Infinite.	.000180	.000041	2.195	4.818

$$(105.) \quad v = 292 \sqrt{rs};$$

which again reduced for feet measures, becomes

$$(106.) \quad v = 84.8 \sqrt{rs};$$

These latter values, for rivers, are even smaller than those found from Du Buât's formula; less than the observed velocities, and less than those found from any other formula, with the exception of Girard's. The values of the coefficients a and b vary in this formula with the value of $d = 4r$; they are expressed generally in equations (101) and (102), from which the preceding table for different values of d and r has been calculated.

An examination of this table will show that a obtains a minimum value when d is between 10 and 11 inches; and b when the diameter is between $\frac{1}{2}$ and $\frac{3}{4}$ of an inch. Now, it appears from equation (102), that v increases with $\sqrt{\frac{Hd}{bl}}$ nearly, or, which is the same thing, as b decreases, there must, *cæteris paribus*, be a maximum value of v for a given value of $\frac{Hd}{l}$

or rs , when d is between $\frac{1}{2}$ and $\frac{3}{4}$ inch; but as $\frac{a}{2b}$ has a minimum value when d is nearly 12 inches, the maximum value of v referred to will be found between values of d from $\frac{3}{4}$ inch to 12 inches; in fact, when $d = 10$ inches nearly. A similar peculiarity has already been pointed out in Du Buât's general theorem, at page 213. *It will not be necessary to take out the values of $\frac{a}{2b}$ and $\frac{a^2}{4b^2}$ to more than one place of decimals.*

The values of $\frac{a}{2b}$ are also given in the table, and may be used in equation (104) for finding the discharge from long pipes. It is, however, necessary to remark, that this equation is sometimes misapplied in finding the velocity from short pipes, and those of moderate lengths. It is necessary to use equation (102), which takes into consideration the head due to the velocity and orifice of entry for such pipes.

For a pipe 11 inches in diameter, the expression for the velocity, equation (104), becomes for inch measures,

$$v = \left\{ \frac{s d}{.000034} + 1.49 \right\}^{\frac{1}{2}} - 1.22:$$

and for feet measures, also substituting 4 r for d ,

$$(106A.) \quad v = \left\{ \frac{s r}{.000102} \right\}^{\frac{1}{2}} - .1 = 100 (r s)^{\frac{1}{2}} - .1$$

very nearly. For a pipe .7 inch in diameter would be found in a like manner for feet measures,

$$(106B.) \quad v = 118 (r s)^{\frac{1}{2}} - .5,$$

which is only suitable for very high velocities.

SIR JOHN LESLIE states,* that the mean velocity of a river in miles per hour, is $\frac{1}{8}$ ths of the mean proportional between the hydraulic mean depth and the fall in two miles in feet. This rule is equivalent, for measures in feet, to

$$(107.) \quad v = 100 \sqrt{r s};$$

and is applicable to rivers with velocities of about 2 $\frac{1}{2}$ feet per second.

D'AUBUISSON, from an examination of the results obtained by Prony and Eytelwein, assumes† for mea-

* Natural Philosophy, p. 423.

† *Traité d'Hydraulique*, p. 224.

asures in metres that $a = \cdot 0000189$, and $b = \cdot 0003425$ for pipes, substituting these in equation (84) and resolving the quadratic

$$(108.) \quad v = (2919 \cdot 71 \, r s + \cdot 00074)^{\frac{1}{2}} - \cdot 027 ;$$

which reduced for measures in English feet becomes

$$(109.) \quad \begin{cases} v = (9579 \, r s + \cdot 00813)^{\frac{1}{2}} - \cdot 0902, \text{ or} \\ v = 98 \sqrt{r s} - \cdot 1 \text{ nearly.} \end{cases}$$

For rivers he assumes with Eytelwein,* $a = \cdot 000024123$ and $b = \cdot 0003655$, for measures in metres, and hence

$$(110.) \quad v = (2795 \cdot 98 \, r s + \cdot 0011)^{\frac{1}{2}} - \cdot 033 ;$$

which for measures in English feet is

$$(111.) \quad \begin{cases} v = (8976 \cdot 5 \, r s + \cdot 012)^{\frac{1}{2}} - \cdot 109, \text{ or} \\ v = 94 \cdot 5 \sqrt{r s} - \cdot 11 \text{ nearly.} \end{cases}$$

When the velocity exceeds two feet per second, he assumes, from the experiments of Couplet, $a = 0$, and $b = \cdot 00035875$; these values give

$$(112.) \quad v = \sqrt{2787 \cdot 46 \, r s},$$

for measures in metres, and

$$(113.) \quad v = 95 \cdot 6 \sqrt{r s} = \sqrt{9145 \, r s}$$

for measures in English feet. Equations (110) and (111) are the same as (93) and (94), found from Eytelwein's values of a and b , and it may be remarked that D'Aubuisson's equations for the velocity generally, are simply those of Prony and Eytelwein.

The values which are found to agree best with the general run of experiments on clear straight rivers of uniform section are $a = \cdot 0000035$, and $b = \cdot 0001150$ for measures in English feet, from which we find

$$(114.) \quad \begin{cases} v = (8695 \cdot 6 \, r s + \cdot 00023)^{\frac{1}{2}} - \cdot 0152, \text{ or} \\ v = 93 \sqrt{r s} - \cdot 02, \end{cases}$$

* *Traité d'Hydraulique*, p. 133. See Equation (93).

which for an average velocity of $1\frac{1}{2}$ foot per second will give $v = 92.3 \sqrt{rs}$ nearly, and for larger velocities $v = 98.3 \sqrt{rs}$; for smaller velocities than $1\frac{1}{2}$ foot per second, the coefficients of \sqrt{rs} decrease pretty rapidly. This formula will be found to agree more accurately with observation and experiment than any other of this form.*

WEISBACH is perhaps the only writer who has modified the form of the equation $rs = av + bv^2$. In Dr. Young's formula, a and b vary with r , but Weisbach assumes that $h_t = \left(a + \frac{b}{v^{\frac{1}{2}}}\right) \frac{l}{a} \times \frac{v^2}{2g}$, and finds from the fifty-one experiments of Couplet, Bossut, and Du Buât, before referred to, one experiment by Guemard, and eleven by himself, all with pipes varying from an inch to five and a half inches in diameter, and with velocities varying from $1\frac{1}{2}$ inch to 15 feet per second, that $a = .01439$, and $b = .0094711$ for measures in metres; hence for the metrical standard

$$(115.) \quad h_t = \left(.01439 + \frac{.0094711}{v^{\frac{1}{2}}}\right) \frac{l}{a} \times \frac{v^2}{2g}.$$

This reduced for the mean radius r is

$$(116.) \quad h_t = \left(.003597 + \frac{.0023678}{v^{\frac{1}{2}}}\right) \frac{l}{r} \times \frac{v^2}{2g};$$

* In a stream (the Muddock), with a curved channel, jagged and irregular banks, variable depths averaging about 1 foot, aquatic plants growing on the bed, varying velocity, and an average cross section of about 16.50 feet, the flow was only 18 cubic feet per second, the formula giving 35 cubic feet. In such cases the application of a formula investigated for a uniform channel and a uniform slope is inadmissible; yet we have heard evidence in the Four Courts, Dublin, founded on such mistaken applications. See note, p. 192.

from which for measures in English feet

$$(117.) \quad h_f = \left(.003597 + \frac{.0042887}{v^{\frac{1}{2}}} \right) \frac{l}{r} \times \frac{v^3}{2g},$$

and thence

$$(118.) \quad r s = \left(.003597 + \frac{.0042887}{v^{\frac{1}{2}}} \right) \frac{v^3}{2g};$$

and by substituting for $2g$, its value 64.408 ,

$$(119.) \quad r s = \left(.00005585 + \frac{.00006659}{v^{\frac{1}{2}}} \right) v^3.$$

In equation (117), $\left(.003597 + \frac{.0042887}{v^{\frac{1}{2}}} \right) = c_f$ is the

coefficient of the head due to friction. The equation does not admit of a direct solution, but the coefficient should be first determined for different values of the velocity v and tabulated, after which the true value of v can be determined by finding an approximate value, and thence taking out the corresponding coefficient from the table, which does not vary to any considerable extent for small changes of velocity. In the following small table the author has calculated the coefficients of friction, and also those of v^3 , in equation (119), for different values of the velocity v .

TABLE OF THE COEFFICIENTS OF FRICTION IN PIPES.

Velocity in feet.	c_f	$\frac{c_f}{64 \cdot 4}$	$\frac{64 \cdot 4}{c_f}$	$\sqrt{\frac{64 \cdot 4}{c_f}}$	Velocity in feet.	c_f	$\frac{c_f}{64 \cdot 4}$	$\frac{64 \cdot 4}{c_f}$	$\sqrt{\frac{64 \cdot 4}{c_f}}$
1	017159	0002664	3078.07	55.5	2.4	006365	0000988	10121.5	100.5
2	013186	0002047	4885.1	69.9	2.5	006309	0000979	10214.5	101.0
3	011427	0001774	5836.9	75.08	2.6	006257	0000972	10288.1	101.4
4	010378	0001611	6270.3	78.8	2.7	006207	0000964	10373.4	101.8
5	009662	0001500	6666.6	81.6	2.8	006160	0000956	10460.2	102.2
6	009138	0001418	7052.2	84.0	2.9	006115	0000949	10537.4	102.6
7	008723	0001354	7385.5	85.9	3	006073	0000943	10604.4	102.9
8	008391	0001303	7674.6	87.6	3.5	005890	0000914	10940.9	104.6
9	008117	0001260	7936.5	89.1	4	005741	0000891	11223.3	105.9
10	007886	0001224	8169.2	90.4	5	005514	0000856	11682.2	108.0
11	007686	0001193	8382.2	91.5	6	005348	0000830	12048.2	109.7
12	007512	0001166	8576.3	92.6	7	005218	0000810	12345.6	111.1
1.25	007433	0001154	8665.5	93.1	8	005113	0000794	12632.2	112.4
1.3	007358	0001142	8756.5	93.5	9	005026	0000780	12820.5	113.3
1.4	007221	0001121	8920.6	94.4	10	004953	0000769	13003.9	114.0
1.5	007098	0001102	9074.4	95.2	15	004704	0000730	13698.6	117.0
1.6	006987	0001085	9216.5	96.0	16	004669	0000725	13793.1	117.4
1.7	006886	0001069	9354.5	96.7	20	004556	0000707	14144.2	118.9
1.75	006839	0001062	9416.2	97.03	25	004455	0000691	14471.7	120.3
1.8	006794	0001054	9487.6	97.4	30	004380	0000680	14705.9	121.2
1.9	006715	0001042	9596.9	97.9	35	004322	0000671	14903.1	122.0
2	006629	0001029	9718.2	98.5	40	004275	0000664	15060.2	122.7
2.1	006556	0001018	9823.2	99.1	45	004236	0000658	15197.5	123.3
2.2	006488	0001007	9930.5	99.6	50	004208	0000653	15313.8	123.7
2.3	006424	0000997	10003	100	100	004200	0000625	16000.0	126.4

If the value of $\frac{64 \cdot 4}{c_f}$ here found, be substituted in the equation $v = \sqrt{\frac{64 \cdot 4}{c_f}} r s$, we shall have the value of v . According to this table the coefficient of friction for a velocity of six inches is more than twice that for a velocity of twenty feet, and the velocity is less in the proportion of 81.6 to 118.9, or of $81.6 (rs)^{\frac{1}{2}}$ to $118.9 (rs)^{\frac{1}{2}}$. On comparing these coefficients and those for pipes in the preceding formulæ, with those for rivers of the same hydraulic depth, it will be perceived that the loss from friction is greatest in the latter, as might have been anticipated; but this evidently arises from lesser velocities.

It has been remarked that the coefficient of friction decreases as the velocity increases. The only general formula which properly meets this defect in the common formulæ is Weisbach's, but it does not give the velocity v directly, as this quantity is involved in both sides of his equation. As for several hydraulic works it is necessary to convey water through pipes to work machines under high heads, and for which the common formula would give results considerably under the true ones, it appeared to the author desirable to obtain some simple expression for the velocity which might be easily remembered and applied, which would be equally correct with other formulæ for medium velocities of from one to two and a half feet, and which at the same time would give practically correct results for lesser and greater velocities within the limits of experiment. By reducing the velocity found from experiment to the form $v = m \sqrt{rs}$ for every case, and afterwards applying a correction of the form $n \sqrt[3]{rs}$ to meet the increasing value of m as v increased, the following expression was discovered:—

$$(119A) \quad v = 140 (rs)^{\frac{1}{2}} - 11 (rs)^{\frac{1}{3}}$$

which gives results not differing more from experiments than these frequently do from each other. The following table exhibits the velocities compared with those obtained from the experiments made by Du Buât, Couplet, Watt, Mr. Provis, and Mr. Leslie, in the Minutes of the Institution of Civil Engineers for February 1855. The last experiment was furnished by Mr. Hodson of Lincoln. Numbers 34 and 35 were made as stated, and give the mean results of several experiments made with great care; the coefficient of

TABLE showing the Experimental Results of observed Velocities in Water Channels, with the Author's general formula for Pipes and Rivers (119A) viz.

$$v = 140 (rs)^{\frac{1}{2}} - 11 (rs)^{\frac{1}{2}} \cdot *$$

No.	Heads in feet (H).	Lengths in feet (L).	Values of r.	Values of s.	Values of rs.	Velocities from experiment.	Velocities from the formula.	Velocities expressed in the form $v = m \sqrt{rs}$.	Experimenter's Names.
1	0.8333	1086	0.052083	0.000076	0.0000396	1.00	1.05	52.6 \sqrt{rs}	Mr. Leslie
2	0.1332	65.37	0.022204	0.00196	0.0000434	1.40	1.18	54.0	Couplet
3	1.4583	1086	0.052083	0.00133	0.0000693	1.18	1.57	60.0	Mr. Leslie
4	4.9586	7482	0.111000	0.00066	0.0000134	1.78	1.67	61.5	Couplet
5	2.0833	1086	0.052083	0.00190	0.0000989	2.17	2.06	65.0	Mr. Leslie
6	4.5833	1086	0.052083	0.00417	0.0002170	3.61	3.45	74.1	"
7	1.48768	7482	0.111000	0.00198	0.0002220	3.66	3.48	74.1	Couplet
8	1.44900	1086	0.052083	0.01321	0.000688	7.15	7.11	85.7	Mr. Leslie
9	2.78125	1086	0.052083	0.02538	0.001322	1.085	1.050	91.3	"
10	"	"	2.427200	0.00063	0.001532	1.166	1.143	92.4	Watt
11	5.0000	100	0.081250	0.04741	0.001482	1.023	1.122	92.2	Mr. Provis
12	2.78125	1086	0.052083	0.04348	0.002265	1.461	1.438	95.5	Mr. Leslie
13	4.76042	1086	0.052083	0.06410	0.003340	1.725	1.798	98.3	"
14	1.06580	127.9	0.044630	0.07748	0.003458	1.839	1.840	98.9	Bossut
15	5.0000	40	0.031250	0.10810	0.003378	1.711	1.816	98.7	Mr. Provis
16	1.06580	95.92	0.044630	0.10050	0.004485	2.111	2.124	100.3	Bossut
17	1.5	100	0.031250	0.14156	0.004422	2.005	2.103	100.5	Mr. Provis
18	9.9896	1086	0.052083	0.09174	0.004779	2.095	2.185	100.6	Mr. Leslie
19	8.575	40	0.031250	0.18042	0.005638	2.330	2.414	101.7	Mr. Provis
20	2.1816	191.9	0.044630	0.10548	0.004708	2.463	2.183	100.6	Bossut
21	2.1316	159.9	0.044630	0.12524	0.005589	2.440	2.404	101.7	"
22	"	"	0.052083	0.14286	0.007440	2.800	2.823	103.5	Mr. Leslie
23	2.1316	127.9	0.044630	0.15350	0.006851	2.744	2.896	103.0	Bossut
24	"	"	0.044630	0.27921	0.012465	3.819	3.760	106.5	"
25	"	"	0.052083	0.25000	0.013021	3.783	3.852	106.7	Mr. Leslie
26	3.27416	40	0.031250	0.18040	0.002093	5.054	5.006	109.8	Mr. Provis
27	2.3684	10.39155	0.022204	0.18669	0.0029679	6.322	6.048	111.0	Du Buat
28	3.27416	20	0.031250	0.11200	0.0034750	6.723	6.572	111.5	Mr. Provis
29	3.4525	20	0.031250	0.113900	0.003594	7.086	6.668	111.9	"
30	7.135	62.8822	0.029605	0.08861	0.0029268	6.157	5.999	110.9	Couplet
31	14.270	125.7644	0.029605	0.106151	0.0031426	6.151	6.239	111.3	"
32	21.405	188.6466	0.029605	0.108579	0.00321455	6.145	6.316	111.4	"
33	3.1974	10.39155	0.022204	0.176991	0.0039292	7.544	7.039	112.3	Du Buat
34	11.125	9.292	0.021250	0.18000	0.01515125	14.588	14.518	117.9	Mr. Neville
35	20.8	19.2	0.021250	0.14000	0.01729750	15.667	15.617	118.4	"
36	150	100	0.020833	1.400000	0.0291667	21.7	20.6	120.3 \sqrt{rs}	Mr. Hodson

* The form in which this formula was first found was as follows :-

$$v = \left\{ 140 - \frac{10.6}{(rs)^{\frac{1}{2}}} \right\} \times \sqrt{rs}. \text{ For measures in metres it becomes } 77.3 (rs)^{\frac{1}{2}} - 4.9 (rs)^{\frac{1}{2}}.$$

the orifice of entry was found to be $\cdot 860$.* The measures have been all reduced to English feet. The results found by the same experimenters, at the same time, with the same apparatus, sometimes differ by three or four per cent., as may be seen by referring to Mr. Provis' experiments (Transactions of the Institution of Civil Engineers, vol. II., p. 203), and the difference in the experiments shown in the table are apparent. The difference in the velocities found from the experiments, do not exceed those inseparable from practical investigations, and they differ as much in themselves as from the formula, which for cylindrical pipes of diameter d may be thus expressed,

$$(119B.) \quad \begin{cases} v = 70 (ds)^{\frac{1}{2}} - 6\cdot93 (ds)^{\frac{1}{2}}, \text{ or} \\ v = 70 (ds)^{\frac{1}{2}} - 7 (ds)^{\frac{1}{2}} \text{ nearly.} \end{cases}$$

The expression fails when $70 (ds)^{\frac{1}{2}}$ is equal to or less than $6\cdot93 (ds)^{\frac{1}{2}}$, but as this only happens when $rs = \left(\frac{11}{140}\right)^6 = \cdot 000000235$, and for velocities below one inch per second, its practical value is not thereby affected. The expression of Du Buât fails with a tube of one twenty-fifth part of an inch in diameter, no matter what the head may be, as it then makes the velocity equal to nothing, although some of the experiments from which it was derived were made with tubes but the eighteenth part of an inch diameter. The following expression is free from this defect :

$$(119C.) \quad v = 60 (rs)^{\frac{1}{2}} + 120 (rs)^{\frac{3}{2}},$$

* The coefficient for the orifice of entry was found by cutting off the pipe at two diameters from the cistern at the conclusion of the experiments, and finding the time of emptying. *Vide* p. 172.

and will give results approximating very closely to those found from Du Buât's formula, and, therefore, with those experiments with which it most nearly coincides, but agreeing much more closely with Watt's and other experiments, on rivers. It gives higher results than the previous formula for velocities below six inches, but the results found by different experimenters differ very much in those. For higher velocities it appears to differ occasionally only about one-twentieth from observation, being in general less, as far as twenty feet per second, where it coincides very closely with Mr. Hodson's experiment. As the errors appear to be of an opposite kind generally, in the two last expressions, combining them is found

$$(119D.) \quad v = 100 (rs)^{\frac{1}{2}} + 60 (rs)^{\frac{3}{2}} - 5.5 (rs)^{\frac{1}{2}},$$

an expression which, however, wants simplicity for ready practical application. When the length of the pipe does not exceed from 1000 to 2000 diameters, a correction is due to the velocity in it, and to the orifice of entry before finding the "hydraulic inclination" (s). The coefficient used in reducing the foregoing experiments for the orifice of entry was .815, which gives $1.508 \frac{v^2}{2g}$ for the height due to the joint effects of velocity and orifice. This must be deducted from the head (H) before dividing it by the length (l) to find the inclination (s) in our table.

The following table, calculated from the formula (119A), $v = 140 (rs)^{\frac{1}{2}} - 11 (rs)^{\frac{3}{2}}$, gives the corresponding values of rs and v , so that when one is known the other is immediately found from inspection. Thus, if $rs = .08125$, then we shall have

TABLE for finding the Velocity in feet per second, from the product of the hydraulic mean depths and hydraulic inclinations, and the reverse calculated from the Author's formula $v = 140 (rs)^{\frac{1}{2}} - 11 (rs)^{\frac{1}{3}}$, in which r , s , and v are feet measures.

Values of rs .	Velocity v .	Values of rs .	Velocity v .	Values of rs .	Velocity v .	Values of rs .	Velocity v .
00000296	083	0001302	104	000689	270	003559	667
00000332	091	0001322	105	000710	275	003599	671
00000395	104	0001420	109	000744	283	003630	674
00000427	111	0001482	112	000758	285	003788	690
00000543	133	0001532	114	000789	291	003929	704
00000592	142	0001578	116	000805	294	003946	705
00000690	158	0001610	117	000833	300	003977	708
00000734	167	0001657	119	000852	304	004104	720
00000947	198	0001736	121	000900	313	004167	727
00000989	206	0001776	124	000947	322	004356	744
00001184	231	0001815	126	001042	340	004546	762
00001263	241	0001894	130	001105	351	004630	769
00001420	261	0002052	135	001136	357	004785	778
00001578	280	0002181	138	001231	373	005556	849
00001677	292	0002265	143	001246	376	006944	961
00001894	316	0002367	147	001263	378	007576	100
00001973	325	0002552	150	001302	385	008333	105
00002170	345	0002604	155	001326	389	009259	111
00002367	365	0002652	157	001420	404	010417	118
00002565	385	0002778	161	001515	418	011905	127
00002841	411	0002841	163	001576	428	013889	138
00003255	448	0003030	169	001610	432	015151	145
00003354	457	0003157	173	001667	441	016667	153
00003551	473	0003220	175	001705	446	017297	156
00003748	489	0003314	179	001735	451	020633	171
00003946	505	0003378	180	001799	460	027778	203
00004143	521	0003409	181	001894	473	029167	206
00004340	536	0003551	185	001989	487	041666	247
00004632	558	0003630	189	002052	494	055556	288
00005130	594	0003706	190	002083	498	062500	306
00005327	608	0003788	192	002093	500	072916	332
00005524	622	0003946	198	002178	510	088333	356
00005919	648	0004022	110	002210	514	104167	400
00006314	674	0004103	202	002273	522	125	439
00006708	699	0004261	206	002375	535	145583	476
00006688	711	0004419	210	002462	546	166667	511
00007102	724	0004485	212	002533	553	208333	573
00007694	760	0004546	214	002652	568	229167	602
00008049	781	0004708	218	002683	572	250000	630
00008523	808	0004735	218	002841	590	270833	657
00008661	828	0004893	223	002968	605	312500	707
00009270	849	0005051	227	002999	608	333333	732
00009470	861	0005208	231	003030	611	354167	755
00010259	908	0005303	233	003143	623	375000	777
00010654	923	0005638	241	003157	625	395833	800
00011048	945	0006061	252	003214	631	416667	821
00011364	960	0006155	254	003220	632	437500	842
00011837	983	0006313	257	003314	642	458333	862
00012232	100	0006440	260	003409	651	479166	883
00012627	102	0006629	264	003475	658	500000	902

$$v = 20\cdot6 \quad \text{when} \quad rs = \cdot029167$$

$$v = 24\cdot7 \quad \text{when} \quad rs = \cdot041666$$

Difference 4·1 corresponds to ·012499

·08125

·02917

Difference ·00208

Whence $\cdot0125 : 4\cdot1 :: \cdot00208 : \cdot7$ nearly, and $20\cdot6 + 7 = 21\cdot3$ is the velocity sought; the same practically as found in **EXAMPLE 26**, p. 24. If allowance is to be made for the head due to the orifice of entry and velocity, this head can be determined from the velocity due to the value of rs in the table next less than the given value with sufficient accuracy. In this case, this velocity is 20·6 feet per second = 247 inches nearly. If the orifice of entry be square, the coefficient is ·815, and the head due to the velocity and this coefficient is, **TABLE II.**, 10 feet nearly. If r be known separately, and also s , as well as the head H , and the length of the pipe l , at first

$$\frac{H}{l} = s, \text{ and, therefore, } \frac{H - 10}{l} = \frac{h}{l} = s.$$

In **EXAMPLE 26**, p. 24, $H = 150$, and $l = 100$ feet, therefore, the new value of $\frac{h}{l} = \frac{140}{100}$ is 1·4; and as r must be equal ·020833, $rs = \cdot02917$: the value corresponding to which, in the table, is 20·6, the velocity when allowance is made for the head due to the velocity and orifice of entry.

In general, by taking the value of v for the next less value of rs in the table, the velocity will be found

with sufficient accuracy, and also the value of rs from that of v by taking it as the next greater. If $rs = .0008523$, the table would give $v = 3.04$ feet, the same practically as already found in **EXAMPLE 27**, p. 25.

The value of rs , when known, determines and fixes the value of v . If r be assumed of any convenient dimensions, s is then determined; and, in like manner, any suitable value of s determines r ; thus:

$$\frac{rs}{r} = s, \text{ and } \frac{rs}{s} = r.$$

It is well to remark, here again, that for pipes the value of r is the fourth part of the diameter d , and that

$$r = \frac{d}{4}, \text{ and } 4r = d.$$

M. DARCY in 1857, inspecteur des ponts et chaussées, published his "*Recherches expérimentales relatives au Mouvement de l'Eau dans les Tuyaux*,"* the result of 198 experiments, in which the velocities varied from .03 to 5 or 6 metres per second, or from $1\frac{1}{4}$ inch to 16 or 19 feet, and with pipes varying from $\frac{1}{2}$ inch to 20 inches diameter. The formula by which he presents the results is, in metres,

$$(a.) \quad R J = b_1 u^2,$$

in which R is the radius of the pipe, J the hydraulic inclination, b_1 a variable coefficient dependent on the circumstances, and u the velocity per second. For wrought and cast iron pipes of the same state of bore,

* *Mémoires présentés par divers savants à l'Académie des Sciences de l'Institut impérial de France*, tome XV., Paris, 1858.

the value of b_1 is expressed by M. Darcy, by the equation

$$(b.) \quad b_1 = \cdot 000507 + \frac{\cdot 00000647}{R},$$

the agreement between which and experiment is shown in the following table.

Diameters in English inches.	Diameters in metres.	Value of b_1 from experiments.	Value of b_1 by the formula.	Remarks.
·5	·0122	·001673	·001568	Well polished bore.
1	·0266	·000918	·000993	
1·5	·0395	·000785	·000835	
3·2	·0819	·000695	·000665	
5·4	·1370	·000553	·000601	
7·4	·1880	·000584	·000576	{ Pipe already in use, but the bore cleaned.
11·7	·2970	·000612	·000551	
19·7	·5000	·000509	·000532	

For iron coated with bitumen, the value of b_1 in a pipe ·196 metres in diameter was ·0004334; for a newly cast pipe of ·188 metres, b_1 was ·000584; and for a pipe ·2492 metres in diameter, b_1 was ·001168; the relative proportions of b_1 in these three instances, being as

1·1 to 1·5 and to 3;

and, therefore, the velocities, or discharges, would be inversely as the square roots of these, or as

·95 to ·82 and to ·58.

By substituting the notation used in this work for that of M. Darcy, then for measures in metres, from equations (a) and (b),

$$rs = \frac{b_1}{2} v^2 = \left\{ \cdot 0002535 + \frac{\cdot 0000016175}{r} \right\} v^2;$$

which for feet measures becomes (as 1 metre = 3·281 feet)

$$rs = \left\{ \cdot 0002535 + \frac{3 \cdot 281 \times \cdot 0000016175}{r} \right\} \times \frac{v^2}{3 \cdot 281} :$$

hence

$$v^2 = \frac{rs}{\cdot 00007726 + \frac{\cdot 00000162}{r}},$$

and, therefore,

$$v = \left\{ \frac{rs}{\cdot 00007726 + \frac{\cdot 00000162}{r}} \right\}^{\frac{1}{2}}.$$

For all half-inch pipes this becomes

$$v = \left\{ \frac{rs}{\cdot 00023278} \right\}^{\frac{1}{2}} = 65 \cdot 5 \sqrt{rs};$$

for all inch pipes,

$$v = \left\{ \frac{rs}{\cdot 00015502} \right\}^{\frac{1}{2}} = 80 \cdot 8 \sqrt{rs};$$

for all two-inch pipes,

$$v = \left\{ \frac{rs}{\cdot 00011614} \right\}^{\frac{1}{2}} = 92 \cdot 8 \sqrt{rs};$$

for all four-inch pipes,

$$v = \left\{ \frac{rs}{\cdot 0000967} \right\}^{\frac{1}{2}} = 101 \cdot 7 \sqrt{rs};$$

for all six-inch pipes,

$$v = \left\{ \frac{rs}{\cdot 00009022} \right\}^{\frac{1}{2}} = 105 \cdot 3 \sqrt{rs};$$

for all nine-inch pipes,

$$v = \left\{ \frac{rs}{\cdot 0000859} \right\}^{\frac{1}{2}} = 107 \cdot 8 \sqrt{rs};$$

for all twelve-inch pipes,

$$v = \left\{ \frac{rs}{\cdot 00008374} \right\}^{\frac{1}{2}} = 109 \cdot 3 \sqrt{rs};$$

for all eighteen-inch pipes,

$$v = \left\{ \frac{rs}{\cdot 00008158} \right\}^{\frac{1}{2}} = 110\cdot7 \sqrt{rs};$$

for all twenty-four inch pipes,

$$v = \left\{ \frac{rs}{\cdot 0000805} \right\}^{\frac{1}{2}} = 111\cdot5 \sqrt{rs};$$

and when r is large, as for very large pipes and channels, the velocity

$$v = \left\{ \frac{rs}{\cdot 00007726} \right\}^{\frac{1}{2}} = 113\cdot8 \sqrt{rs}$$

is obtained.

There is evidently, on an examination of these results, a great error in the formula of M. Darcy. As long as the diameter of a long pipe continues constant, the velocity is always represented by a given fixed multiple of \sqrt{rs} , or of the square root of the product of the hydraulic inclination and hydraulic mean depth, no matter how small or great the velocity in the pipe may be. For an inch pipe this multiplier for feet measures is 80·8. Now with a lead pipe the author has found, from several experiments, for a velocity of about 15 feet per second, the multiplier to be 117 or 118; and for a velocity of about 22 feet per second, Mr. Hodson's experiment gives a multiplier of about 120. Taking the other extreme for large pipes, the multiplier derived from M. Darcy's formula is 113·8, no matter how small the velocity may be. But there are experiments in abundance to prove that for velocities of about 12 or 18 inches per second, the multiplier cannot exceed 95. We, therefore, look upon these researches of M. Darcy as partial and defective, and his formula as a representation, at best, of a limited

range of velocities, in which those at either side are omitted or not perceived.

For small pipes, any obstruction arising from defective bore, decomposition, encrustation, or from diminished bore, affects the discharge much more considerably than the same obstructions in a large pipe. In order to compare correctly the effects of the state of the bore on the discharge, pipes of exactly the same diameter must be used, and the value of b_1 determined from experiments in which the velocity is the same, otherwise the results, as deduced by M. Darcy and given by Morin, cannot be depended upon.

A few examples, taken at discretion, are given to show how limited this formula must be in its application.

1. Couplet's experiment, No. 48, p. 217, reduced to feet, gives $r = \cdot 3997$ feet, $s = \cdot 0035$, $rs = \cdot 001339$, and the observed velocity $v = 3\cdot 478$ feet $= 95 \sqrt{rs}$ nearly. Darcy's formula would give $v = 110\cdot 8 \sqrt{rs}$, the author's formula $106 \sqrt{rs}$ nearly, and Weisbach's $105 \sqrt{rs}$ nearly. The pipe was probably an old one, and a deduction of about 10 per cent. might be made for the state of the bore. Here, however, there is no means of judging the effect of a change of inclination on the multiplier m , table page, 231.

2. From Du Buât's experiments with an inch pipe, nearly, Nos. 50 and 51, p. 217, after reducing them to feet, in experiment 50, $r = \cdot 0222$, $s = \cdot 228$ and $v = 6\cdot 33$ feet $= 89\cdot 2 \sqrt{rs}$; or, after making the necessary deductions in the head for the velocity and the orifice of entry with the coefficient $\cdot 815$, $s = \cdot 147$

and $v = 6.33$ feet $= 111.4 \sqrt{rs}$. In experiment 51, in feet $r = .0222$, $s = .3074$, and $v = 7.54 = 92 \sqrt{rs}$; or, by making allowance for the head due to the velocity and the orifice of entry, as before, $s = .179$, and $v = 7.54$ feet $= 119.7 \sqrt{rs}$. Here it is seen how the velocity, or value of the inclination, s , affects the value of the multiplier, the diameter remaining constant. M. Darcy's formula, in each case, would only make $v = 80.2 \sqrt{rs}$.

3. In the excerpt proceedings of the Institution of Civil Engineers, p. 4, 6th February, 1855, James Simpson, president, in the chair, there is given for the "Colinton pipe" 16 inches diameter, eight or nine years in use, three observations. First, 29,580 feet long, a head of 420 feet and a discharge of 571 cubic feet per minute: these give $v = 6.816$ feet $= 99.2 \sqrt{rs}$ nearly. Secondly, a length of 25,765 feet a head of 184 feet, and a discharge of 440 cubic feet per minute: these give $v = 5.252$ feet $= 96.3 \sqrt{rs}$. And thirdly, a length of 3,815 feet a head of 184 feet, and a discharge of 1,215 cubic feet per minute: these give $v = 14.5$ feet $= 115 \sqrt{rs}$ nearly. In these three examples, the diameter, castings, and age of the pipes are the same. Yet it is seen, clearly, that the inclination affects the multiplier of \sqrt{rs} , which increases with the inclination, s , although M. Darcy's formula would make the multiplier the same in each case, and for all inclinations, viz. $v = 110 \sqrt{rs}$. Making those allowances inseparable from the state of the pipe, and all experimental observations, these results, as well as those from Du Buât's experiments, confirm the accuracy

of the author's general formula (119A), page 230, and those others that have been given following it, as well also as that of Weisbach.

Dr. Young's formula, page 222, bears a resemblance to that of M. Darcy, in making the multiplier of \sqrt{rs} depend only on the diameter; but it works in a contrary manner: for the high velocities being derived from pipes with small diameters, in the experiments at his command, the value of c in $v = c \sqrt{rs}$, reduced from his formula, becomes larger in general for small than for larger diameters. No doubt an allowance should be made in small pipes for a thin film of water adjoining the pipe with little or no velocity; but within the limits with which the engineer has to deal, this may be neglected. Its effect, as well as that of all the other resistances, junctions, contractions, deposits, &c., is greater in pipes of small bore than in larger ones.

COEFFICIENTS DUE TO THE ORIFICE OF ENTRY.—
THREE PROBLEMS.

Unless where otherwise expressed, the head due to the velocity and orifice of entry is not considered in the preceding equations. In equation (74), where it is taken into calculation generally,

$$v = \left\{ \frac{2gH}{1 + c_r + c_v \times \frac{l}{r}} \right\}^{\frac{1}{2}}$$

in which $1 + c_r$ is equal to $\left(\frac{1}{c_v}\right)^2$, c_r being the coefficient of resistance due to the orifice of entry, and c_v the coefficient of velocity or discharge from a short tube.

If the tube project into the reservoir, and be of small thickness, c_v will be equal $\cdot 715$ nearly, and therefore $c_r = \cdot 956$; if the tube be square at the junction, the mean value of c_v will be $\cdot 814$, and therefore $c_r = \cdot 508$; and if the junction be rounded in the form of the contracted vein, c_v is equal to unity very nearly, and $c_r = 0$. For other forms of junction the coefficients of discharge and resistance will vary between these limits, and particular attention must be paid to their values in finding the discharge from shorter tubes and those of moderate lengths; but in very long tubes

$1 + c_r$ becomes very small compared with $c_r \times \frac{l}{r}$, and may be neglected without practical error. These remarks are necessary to prevent the misapplication of the tables and formulæ, as the height due to the velocity and orifice of entry is an important element in all calculations for short tubes.

It is considered unnecessary to give any formulæ for finding the discharge itself, because, the mean velocity once determined, the calculation of the discharge from the area of the section is one of simple mensuration; and the introduction of this element into the three problems to which this portion of hydraulic engineering applies itself, renders the equations of solution complex, though easily derived; and presents them with an appearance of difficulty and want of simplicity which excludes them, nearly altogether, from practical application. The three problems are as follows:—

I. *Given the fall, length, and diameter of a pipe or hydraulic mean depth of any channel, to find the discharge.*

Here all that is necessary is to find the mean velocity of discharge, which, multiplied by the area of the section (equal $d^2 \times .7854$ in a cylindrical pipe), gives the discharge sought. TABLE VIII. gives the velocity at once for long channels, according to Du Buat, or it can be found from equation (119A) by calculation. TABLE IX. gives the discharge in cubic feet per minute for different diameters of pipes, and velocities in inches per second, when found from TABLE VIII., or formula (119A). See also TABLES XI. and XII. FOR A PIPE 6 INCHES IN DIAMETER, THE VELOCITY PER SECOND IS PRACTICALLY EQUAL TO THE DISCHARGE IN CUBIC FEET PER MINUTE. See also the tables at pp. 28, 29, 270, and 271.

II. *Given the discharge and cross section of a channel, to find the fall or hydraulic inclination.*

If the cross section be circular, as in most pipes, the hydraulic mean depth is one-fourth of the diameter; in other channels it is found by dividing the water and channel line of the section, wetted perimeter, or border, into the area. The velocity is found by dividing the area into the discharge, and reducing it to inches per second; then in TABLE VIII., under the hydraulic mean depth, find the velocity, corresponding to which the fall per mile will be found in the first column, and the hydraulic inclination in the second. This result can be corrected by trial and error to accord with formula (119A), and the table for the values of $r s$ and v , p. 284, calculated from it. See also the tables, pp. 28, 29, 270, and 271.

III. *Given the discharge, length, and fall, to find*

the diameter of a pipe, or hydraulic mean depth and dimensions of a channel.

This is the most useful problem of the three. Assume any mean radius r_a , and find the discharge D_a by Problem I. Then for cylindrical pipes

$$r_a^{\frac{5}{2}} : r^{\frac{5}{2}} :: D_a : D :: 1 : \frac{D}{D_a};$$

and as r_a , D , and D_a , are known, $r^{\frac{5}{2}}$ becomes also known, and thence r . TABLE XIII. will then assist to find r with great facility. Thus, if $r_a = 1$ and D_a was found 15, D being 33, then

$$1 : r^{\frac{5}{2}} :: 1 : \frac{33}{15} :: 1 : 2.2, \text{ therefore } r^{\frac{5}{2}} = 2.2;$$

and thence by TABLE XIII., $r = 1.37$, the mean radius required, four times which or 5.48 is the diameter of the pipe. For other channels, the quantity thus found must be the hydraulic mean depth; and all channels, however varied in the cross section, will have the same velocity of discharge, when the fall, length, and hydraulic mean depth are constant. IF r_a BE ASSUMED EQUAL TO $1\frac{1}{2}$ INCH, THE VELOCITY FOUND FROM TABLE VIII. WILL THEN BE THE DISCHARGE IN CUBIC FEET PER MINUTE NEARLY, and this "mean radius" can always be assumed for the first term of the proportion. See also the tables, pp. 28, 29, 270, and 271.

In order to find the dimensions of any polygonal channel whatever, which will give a discharge equal to D , assume any channel similar to that proposed, one of whose known sides is s_a , and find the corresponding discharge, D_a , by Problem I., or from TABLES XI. and XII.; then, if the like side of the required channel,

be s , there results the equation $s = s_a \left(\frac{D}{D_a} \right)^{\frac{5}{2}}$, and thence the numerical value from TABLE XIII. The result can be corrected, as before, to accord with any of the formulæ by the method of trial and error.

As it frequently happens that deposits in and encrustations on a pipe take place from time to time, which diminish the flowing section considerably, it is always prudent, when calculating the necessary diameter, to take the largest coefficient of friction, c_f , or to double its mean value, particularly for small pipes, when calculating the diameter from any of the formulæ. Some engineers, increase the quantity of water by one-half to find the diameter; but much must depend on the peculiar circumstances of each case, as sometimes less may be sufficient, or more necessary. The discharge increases in similar figures, nearly as $r^{\frac{5}{2}}$ or as $d^{\frac{5}{2}}$, that is, as the square root of the fifth power of the diameter, and the corresponding increase in the diameter for any given or allowed increase in the discharge can be easily found by means of TABLE XIII., as shown above. If the dimensions be increased by one-sixth, the discharge will be increased by one-half nearly; and by doubling the dimensions the discharge is increased in the proportion of $5\frac{3}{4}$ to 1.

For shorter pipes, it is necessary to take into consideration the head due to the velocity and orifice of entry. Taking the mean coefficient of velocity or discharge, the head due to the velocity and orifice of entry, if it be known is found from TABLE II.; this subtracted from the whole head, H , leaves the head, h_f , due to the hydraulic inclination, which is that to be

made use of in TABLE VIII. If the velocity be not given, it can be found approximately; then the head found for this velocity, due to the orifice of entry, when deducted, as before, will give a close value of h_t , from which the velocity may be determined with greater accuracy, and so on to any degree of approximation. In general, one approximation to h_t will be sufficient, unless the pipes be very short, in which case it is best to use equation (74). EXAMPLE VIII., p. 208, and the explanation of the use of the tables, SECTION I., may be usefully referred to.

TABLES XI., XII., and XIII. assist to solve with considerable facility all questions connected with discharge, dimensions of channel, and the ordinary surface inclinations of rivers. The discharge corresponding to any intermediate channels or falls to those given in TABLES XI. or XII., will be found with abundant accuracy, by inspection and simple interpolation; and in the same manner the channels from the discharges. Rivers have seldom greater falls than those given in TABLE XII., but in such a case, it is only to divide the fall by 4, then twice the corresponding discharge will be that required. TABLE XIII. gives the comparative discharging powers of all similar channels, whether pipes or rivers, and the comparative dimensions from the discharges. It will be perceived from it, that an increase of one-third in the dimensions doubles, and a decrease of one-fourth reduces the discharge to one-half. By means of this table, and by a simple proportion, the dimensions of any given form of channel when the discharge is known can be determined. See EXAMPLE 17, p. 17. See also the tables pp. 28, 29, 270, and 271.

The mean widths in TABLES XI. and XII. are calculated for rectangular channels, and those having side slopes of $1\frac{1}{2}$ to 1. Both these tables are, however, practically, equally applicable to any side slopes from 0 to 1 up to 2 to 1, or even higher when the mean widths are taken and not those at top or bottom. A semihexagon of all trapezoidal channels of equal area has the greatest discharging power, and the semi-square and all rectangles exactly the same as channels of equal areas and depths with side slopes of $1\frac{1}{2}$ to 1. The maximum discharge is obtained between these for the semihexagon with side slopes of nearly $\frac{1}{2}$ to 1, but for equal areas and depths *the discharge decreases afterwards as the slope flattens*. The question of "HOW MUCH?" is here, however, a very important one; for, as already pointed out in equations (28) and (31), the differences for any practical purposes may be immaterial. This is particularly so in the case of channels with different side slopes, if, instead of the top or bottom, the mean width is made use of to calculate from. Then it is only to subtract the ratio of the slope multiplied by the depth to find the bottom, and add it to find the top. If the mean width be 50 feet, the depth 5 feet, and the side slopes 2 to 1, then $50 - (2 \times 5) = 40$ for the bottom, and $50 + (2 \times 5) = 60$ for the top width.

Side slopes of 2 to 1 present a greater difference from the mean slope of $1\frac{1}{2}$ to 1, than any others in general practice when new cuts are to be made. A triangular channel having slopes of 2 to 1, and bottom equal to zero, differs more in its discharging power from the half square, equal to it in depth and area,

than if the bottom in each was equally increased, yet even here it is easy to show that this maximum difference is only $5\frac{1}{2}$ per cent. If the bottom be increased so as to equal the depth, it is only $4\frac{1}{2}$ per cent.; when equal to twice the depth, 3·8 per cent.; and when equal to four times the depth, to 2 per cent.; while the differences in the dimensions taken in the same order are only 2·2, 1·8, 1·5, and 0·8 per cent. For greater bottoms in proportion to the depth the differences become of no comparative value. It therefore appears pretty evident, that TABLES XI. and XII. will be found *equally applicable to all side slopes from 0 to 1 up to 2 to 1, by taking the mean widths*. When new cuts are to be made, there is no reason whatever in starting from bottom rather than mean widths, to calculate the other dimensions; indeed the necessary extra tables and calculations involved ought entirely to preclude us from doing so. Besides, the formulæ for finding the discharge vary in themselves, and for different velocities the coefficient of friction also varies.* Added to which the inequalities in every river channel, caused by bends and unequal regimen, preclude altogether any regularity in the working slopes and bottom, though the mean width would continue pretty uniform under all circumstances.

* The coefficient m in the formula $v = m (rs)^{\frac{1}{2}}$ in rivers for velocities from 3 inches to 3 feet per second, varies from about 72 to 103; yet, strange to say, most tables are calculated from one coefficient alone; or, rather, from a formula equivalent to $94\cdot17 (rs)^{\frac{1}{2}}$, which gives results suited to a velocity of 16 inches only. Dimensions of channels calculated by means of this formula are too small in one case, and too large in the other. In pipes, the variation of the coefficients is shown in the small tables, pp. 229 and 231.

The quantities in TABLE XII. are calculated, from the velocities found from TABLE VIII., to correspond to a channel 70 feet wide and of different depths, the equivalents to which are given in TABLE XI. In order to apply these tables generally to all open channels, the latter are to be reduced to rectangular ones of the same depth and mean width, or the reverse, as already pointed out. If the dimensions of the given channel be not within the limits of TABLE XI., divide the dimensions of the larger channels by 4, and multiply the corresponding discharge found in TABLE XII. by 32; for smaller channels, multiply the dimensions by 4, and divide by 32. In like manner, if the discharge be given and exceed any to be found in TABLE XIII., divide by 32, and multiply the dimensions of the suitable equivalent channel found in TABLE XI. by 4. If it be desirable to find equivalent channels of less widths than 10 feet for small discharges, multiply the discharge by 32, and divide the dimensions of the corresponding equivalent by 4. Many other multipliers and divisors as well as 4 and 32 may be found from TABLE XIII., such as 3 and 15.6, 6 and 88.2, 7 and 130, 9 and 243, 10 and 316, 12 and 499, &c. The differences indicated at pages 212 and 213, must be expected in the application of these rules, which will give, however, dimensions for new channels which can be depended on for doing their duty. The TABLES, pp. 270, 271, are also applicable.

It will be seen from TABLE XIII. that a very small increase in the dimensions increases the discharging power very considerably. TABLE XII. also shows that a small increase in the depth alone adds very much to


the discharge. If in this latter case a *small increase* in the depth, d , be expressed by $\frac{d}{n}$, then it is easy to prove that the corresponding increase in the velocity, v , will be $\frac{v}{2n}$; and that in the discharge D , $\frac{3D}{2n}$, if the surface inclination continue unchanged; but as it is always observable in rivers that the surface inclinations increase with floods, the differences in practice will be found greater than these expressions make it. As in a large river the surface inclination must be very small, four times the fall will add very little to the sectional area; yet this increase of fall would double the discharge, and thence may be perceived how tributaries can be absorbed into the main channel without any great increase to its depth.

SECTION IX.

BEST FORMS OF THE CHANNEL.—REGIMEN.—VELOCITY.—
EQUALLY DISCHARGING CHANNELS.

THE determination of the hydraulic mean depth does not necessarily determine the section of the channel. If the form be a circle, the diameter is four times the mean radius; but, though this form be almost always adopted for pipes, the beds of rivers take almost every curvilinear and trapezoidal shape. Other things being the same, that form of a river channel, in which the area of the cross section divided by the border is a maximum, is the best. This is a

semicircle having the diameter for the surface line, and in the same manner, half the regular figures, an



octagon, hexagon, and square, in Fig. 33, are better forms for the channel, the areas and side slopes being constant, than any others of the same number of

sides. Of all rectangular channels, Diagram 4, in which $A B C D$ is half a square, is the best cross section; and in Diagram 3, $A C D B$, half a hexagon, is the best trapezoidal form of cross section. When the width of the bottom, $C D$, Diagram 3, is given, and the slope $\frac{A a}{C a} = n$, then, in order that the discharge may be the greatest possible,

$$C a = \left\{ \frac{A}{2 (n^2 + 1)^{\frac{1}{2}} - n} \right\}^{\frac{1}{2}}, \text{ and}$$

$$C D = \frac{A}{C a} - n \times C a$$

$$= \{ [2 (n^2 + 1)^{\frac{1}{2}} - n] \times A \}^{\frac{1}{2}} - n \left\{ \frac{A}{2 (n^2 + 1)^{\frac{1}{2}} - n} \right\}^{\frac{1}{2}},$$

in which A is the given area of the channel. As, however, a river has never been known in which the slope of the natural banks continued uniform, even although made so for any improvements, it is not necessary to give tables for different values of n . If, notwithstanding, ϕ be put for the inclination of the slope $A c$, equal angle $C A a$; then as $\cot. \phi = n$, and $\sqrt{n^2 + 1} = \frac{1}{\sin. \phi}$, the foregoing equations become

$$(120.) \quad c a = \left\{ \frac{A \sin. \phi}{2 - \cos. \phi} \right\}^{\frac{1}{2}} = \frac{c D}{2 \{(n^3 + 1)^{\frac{1}{2}} - n\}};$$

and

$$(121.) \quad c D = \frac{A}{c a} - c a \times \cot. \phi, *$$

which will give the best dimensions for the channel when the angle of the slope for the banks is known.

When the discharge from a channel of a given area, with given side slopes, is a maximum, it is easy to prove that THE HYDRAULIC MEAN DEPTH MUST BE HALF OF THE CENTRAL OR GREATEST DEPTH. This simple principle gives the construction of the best form of channel with great facility. *Describe any circle on the drawing-board; draw the diameter and produce it on both sides, outside the circle; draw a tangent to the lower circumference parallel to this diameter, and draw the side slopes at the given inclinations, touching the circumference also on each side and terminating on the parallel lines: the trapezoid thus formed will be the best form of channel, and the width at the surface will be equal to the sum of the two side slopes.* It is easy to perceive that this construction may be, simply, extended for finding the best form of a channel having any polygonal border whatever of more sides than three and of given inclinations.

Commencing with the best discharging form of channel, which in practice will have the mean width, about double the depth; an equally discharging section of double the width of the first will have the contents

* When $c D = 0$. The channel is triangular; and $A = c a^2 \times \cot. \phi$ and $c a = \left(\frac{A}{\cot. \phi} \right)^{\frac{1}{2}}$.

one-eleventh greater, and the depth less in the proportion of 1 to 1.85. A channel of double the mean width of the second must have the sectional area further increased by about one-fifth, and a further decrease in the depth from 1.67 to 1 nearly. The greater expanse of the excavation at greater depths will, in general, more than counterbalance these differences in the contents of the channel. When the banks rise above the flood line, and are unequal in their section, the wider channel involves further upper extra cutting, but there is greater capacity to discharge extra and extraordinary flooding, the banks are less liable to slip or give way, the slopes may be less, and the velocity being also less, the regimen will, in general, be better preserved. The table of equally discharging channels, p. 270, will afford the means of calculating the difference of the cubical contents.

When the sectional area is given, the following table shows that the semicircle is the best discharging channel, and the complete circle the worst; the latter is so, however, only compared with the *open* channels given in the table, it being the best form for an *enclosed* channel flowing full. *The best form of an open channel is particularly suited for new cuts in flat, marsh, callow, and fen lands, in which it is also often advisable to cut them with a level bed, up from the discharging point, in order to increase the hydraulic mean depth, and consequently the velocity and discharge.*


As the quantity of water coming down a river channel in a season varies very considerably,—the author has observed it in one case to vary from one to

TABLE OF THE RELATIVE DIMENSIONS OF MAXIMUM DISCHARGING CHANNELS.

Angle of slope.	Engineering slope.	Depth in terms of the area.	Bottom in terms of the area.	Top in terms of the area.	Hydraulic mean depth in terms of the area.	Ratio of bottom to depth.	Ratio of top to depth.	Area in terms of the depth d .
90° 0'	0 to 1	$\cdot 707\sqrt{A}$	$1\cdot 414\sqrt{A}$	$1\cdot 414\sqrt{A}$	$\cdot 354\sqrt{A}$	2· to 1	2· to 1	$2d^2$
63 26	$\frac{1}{2}$ to 1	$\cdot 759\sqrt{A}$	$\cdot 938\sqrt{A}$	$1\cdot 697\sqrt{A}$	$\cdot 379\sqrt{A}$	1·236 to 1	2·236 to 1	$1\cdot 736d^2$
48 34½	$\frac{2}{3}$ to 1	$\cdot 748\sqrt{A}$	$\cdot 675\sqrt{A}$	$1\cdot 996\sqrt{A}$	$\cdot 374\sqrt{A}$	·902 to 1	2·667 to 1	$1\cdot 784d^2$
55 0	1 to 1	$\cdot 740\sqrt{A}$	$\cdot 613\sqrt{A}$	$2\cdot 093\sqrt{A}$	$\cdot 370\sqrt{A}$	·828 to 1	2·828 to 1	$1\cdot 828d^2$
36 52	$1\frac{1}{3}$ to 1	$\cdot 707\sqrt{A}$	$\cdot 471\sqrt{A}$	$2\cdot 357\sqrt{A}$	$\cdot 354\sqrt{A}$	·667 to 1	3·333 to 1	$2d^2$
33 41½	$1\frac{1}{2}$ to 1	$\cdot 689\sqrt{A}$	$\cdot 417\sqrt{A}$	$2\cdot 484\sqrt{A}$	$\cdot 345\sqrt{A}$	·605 to 1	3·605 to 1	$2\cdot 105d^2$
30 53	$1\frac{2}{3}$ to 1	$\cdot 671\sqrt{A}$	$\cdot 372\sqrt{A}$	$2\cdot 608\sqrt{A}$	$\cdot 336\sqrt{A}$	·554 to 1	3·888 to 1	$2\cdot 221d^2$
26 34	2 to 1	$\cdot 636\sqrt{A}$	$\cdot 300\sqrt{A}$	$2\cdot 844\sqrt{A}$	$\cdot 318\sqrt{A}$	·472 to 1	4·472 to 1	$2\cdot 472d^2$
Semicircle	Curved	$\cdot 798\sqrt{A}$	·000	$1\cdot 596\sqrt{A}$	$\cdot 399\sqrt{A}$	·000 to 1	2 to 1	$1\cdot 571d^2$
Circle	Curved	$1\cdot 128\sqrt{A}$	·000	·000	$\cdot 282\sqrt{A}$	·000 to 1	0 to d	$\cdot 785d^2$

NOTE.—Half the top will give the length of the side slope. The top itself is the sum of the side slopes, and the border the sum of the top and bottom. The sum of the side slopes in any channel whatever is equal to the number corresponding to the slope in the eighth column multiplied by the depth; and the sum of the triangular side areas, corresponding to the slopes, is equal to the square of the depth multiplied by the numbers corresponding to the ratio in column 2. The bottom multiplied by the depth added to this gives the area of the section. The top of the best form of channel should be at the level of the extraordinary flood line, and not at that of the mean annual surface.

thirty, and occasionally in the same channel from one to seventy-five,—the proportion of the water section to the channel itself must also vary, and those relations of the depth, sides, and width to each other, above referred to, cease to hold good, and be the best under such circumstances. If the object be to construct a mill-race, temporary drain for unwatering a river, or other small channel, in which the depth remains nearly constant, channels of the form of a half hexagon, diagram 3, Fig. 33, will be, perhaps, the best, if the tenacity of the banks permit the slope; but rivers, in which the quantity of water varies considerably, require wider channels in proportion to the depth; and also, that the velocity be so proportioned to the tenacity of the soil, or as it is termed "*the regimen*," that the banks and bed shall not vary from time to time to any injurious extent, and that any deposits made during their summer state, and during light freshes, shall be carried off periodically by floods. Another circumstance, also, modifies the effects of the water on the banks. It is this, that at curves, and turns, the current acts with greatest effect



against the bank, concave to the direction in which it is moving; deepening the channel there; undermining also the bank, as at A, Fig. 34; and raising the bed to the opposite side B. The reflection of the current to the opposite bank from A acts also

in a similar manner, lower down, upon it; and this natural operation proceeds, until the number of turns, increased length of channel, and loss of head from reflexion and unequal depths, bring the currents into regimen with the material in the bed and banks. At all bends it is, therefore, prudent to widen the channel on the convex side B, and protect the concave side A, Fig. 84, in order to reduce the velocity and its effects; and if the bed be here also sunk below its natural inclination, as it may be seen in most rivers at bends, the velocity will be farther reduced, and the permanence of the bed better established.

The circumstances to be considered in deciding on the dimensions and fall of a new river course, after the depth to which the surface of the water is to be brought has been decided on, are the following:—

The mean velocity must not be too slow, or aquatic plants will grow, and deposits take place, reducing the sectional area until a new and smaller channel is formed within the first with just sufficient velocity to keep itself clear. This velocity should not in general be less than from ten to fourteen inches per second. The velocity in a canal or river is increased very considerably by cutting or removing reeds or aquatic plants growing on the sides or bottom.*

* “ M. Girard a fait observer, avec raison, que les plantes aquatiques, qui croissent toujours sur le fond et sur les berges des canaux, augmentent considérablement le périmètre mouillé, et par suite la résistance; il a rapellé que Du Buat, ayant mesuré la vitesse de l'eau dans le canal du Jard, avant et après la coupe des roseaux dont il était garni, avait trouvé un résultat bien moindre avant qu'après. En conséquence, il a presque doublé la pente donnée par le calcul . . .”—*Traité*

The mean velocity must not be too quick, and should be so determined as to suit the tenacity and resistance of the channel, otherwise the bed and banks will change continually, unless artificially protected; it should not exceed

25 feet per minute in soft alluvial deposits.			
40	„	„	clayey beds.
60	„	„	sandy and silty beds.
120	„	„	gravelly.
180	„	„	strong gravelly shingle.
240	„	„	shingly.
300	„	„	shingly and rocky.
400 and upwards in rocky and shingly.*			

d'Hydraulique, p. 135. When the fall does not exceed a few inches per mile, the velocity, as determined from the inclination, is very uncertain, and for this reason it is always prudent to increase the depths and sectional areas of channels in flat lands, as far as the regimen will permit. In such cases the section of the channel should approximate towards the best form. See pp. 192 and 255.

* TABLE OF VELOCITIES OF SOME MOVING BODIES COMPARED WITH THOSE OF RIVERS

Objects in motion.	Miles per hour.	Feet per second.	Objects in motion.	Miles per hour.	Feet per second.
Current of slow rivers .	$\frac{1}{2}$	$\frac{1}{2}$	Railway trains, German	24	53 $\frac{1}{2}$
Currents of ordinary rivers up to . . .	$1\frac{1}{2}$	21	Sound when atmosphere is at 32° Fahr. . . .	743	1,090
Currents of rapid rivers	7	10 $\frac{1}{2}$	Ditto 60° Fahr. . . .	765	1,122
Man walking	3	4 $\frac{1}{2}$	Air rushing into vacuum	850	1,247
Horse trotting	7	10 $\frac{1}{2}$	Ditto when the baro- meter stands at 30 inches.	917	1,344
Swiftest race-horse . .	60	88	Common musket-ball .	850	1,247
Moderate winds . . .	7	10 $\frac{1}{2}$	Rifle-ball	1,000	1,467
Storms	36	52 $\frac{1}{2}$	Cannon-ball	1,091	1,600
Hurricanes	80	117 $\frac{1}{2}$	Bullet discharged from air-gun, air being compressed into the hundredth part of its volume	477	700
Swift English steam- boats navigating the channels	14	20 $\frac{1}{2}$	A point on earth's sur- face at the equator moving round the axis	1,040	1,525
Swift American river steamers	18	26 $\frac{1}{2}$	Earth moving round sun	68,182	100,000
Fast sailing vessels . .	12	17 $\frac{1}{2}$			
Railway trains, English	32	47			
„ „ American	18	26 $\frac{1}{2}$			
„ „ Belgian.	25	36 $\frac{1}{2}$			
„ „ French.	27	39 $\frac{1}{2}$			

A velocity of 180 feet per minute will remove angular stones the size of an egg. Mr. Phillips, under the Metropolitan Commissioners of Sewers, states that $2\frac{1}{2}$ feet per second, or 150 feet per minute, is sufficient to prevent soil depositing in sewers.

The fall per mile should decrease as the hydraulic mean depth increases, and both be so proportioned that floods may have sufficient power to carry off the deposits, if any, periodically. The proportion of the width to the depth of the channel should not be derived, for new cuts or river courses, from any formula, but taken from such portions of the old channel as approximate in depth and in the inclination of the surface to that proposed. When the depth is nearly half the width, the formula shows, *cæteris paribus*, that the discharge will be a maximum; but as (altogether apart from the question of expense) the quantity of water discharged daily, at different seasons, may vary from one to seventy, and more, and "*the regimen*," has to be maintained, the best proportion between the width and depth of a new cut should be obtained, as stated, from some selected portion of the old channel, whose general circumstances and surface inclination approximate to those of the one proposed; and the side slopes of the banks must be such as are best suited to the soil. The resistance of the banks to the current being in general less than that of the beds, which get covered with gravel, and the necessary provision required for floods, appears to be the principal reason why rivers are in general so very much wider than about twice the depth, the relation which gives the minimum of friction.

The following Table is given by Rennie, as an approximation, generally, to the actual state of rivers.* The surface inclinations, however, given in this table for the first and second classes, are very considerable for large rivers, and would give velocities which would effectually scour them. For a hydraulic mean depth of 12 feet, the velocity, with a fall of $\frac{1}{12000}$, would be 2 feet 8 inches per second by Du Buât's formula; and 3.3 feet per second by our formula. The description, therefore, can only apply to smaller channels. In fact, 4 inches to a mile, or $\frac{1}{15740}$, is a considerable inclination for a large river. From Carrick-on-Shannon to Killaloe, a distance of 110 miles, the average fall is only about 4 inches per mile on the river Shannon; and the portion between Athlone and the river Suck below Shannon bridge the fall varies from .7 to $1\frac{1}{2}$ inch per mile. The Table of the "Falls on the Shannon" (p. 262) explains practically the defects in Rennie's Table, or of any tabular arrangement that omits the size and hydraulic mean depth of the river channel. The mean velocity and quantity flowing remaining the same, the hydraulic mean depth increases as the surface inclination decreases, and in the same ratio. The increase of surface inclination and of velocity are the indices of obstructions in the channel, with this difference, that the obstructions are caused by the velocity where the surface inclination is generally steep; but the obstructions cause the increase of velocity where the inclination is generally flat.

* Report to the British Association, 1834

DISTINCTIVE ATTRIBUTES OF THE VARIOUS KINDS OF RIVERS.	Rates of classes of rivers and flowing waters.	Comparative degrees of the mean veloci- ties of currents.	Seconds of time in which currents run 20 fathoms.	Fathoms run by the current per minute of time.	Ratios of declivity compared with horizontal length.	Fathoms of length for each one-twelfth inch of declivity.
Channels wherein the resist- ance from the bed, and other obstacles, equal the quantity of current acquired from the de- clivity; so that the waters would stagnate therein, were it not for the compression and impulsion of the upper and back waters . . }	1st.	0	0"	0	$\frac{1}{12000}$	14
Artificial canals in the Dutch and Austrian Netherlands . . }	2nd.	$\frac{2}{3}$	180	$6\frac{2}{3}$	$\frac{1}{7000}$	8
Rivers in low, flat countries, full of turns and windings, and of a very slow current, subject to frequent and lasting inunda- tions }	3rd.	1	120	10	$\frac{1}{1900}$	6
Rivers in most countries that are a mean between flat and hilly, which have good currents, but are subject to overflow; also the upper parts of rivers in flat countries }	4th.	$1\frac{1}{2}$	80	15	$\frac{1}{2000}$	$4\frac{2}{3}$
Rivers in hilly countries with a strong current, and seldom subject to inundations; also all rivers near their sources have this declivity and velocity, and often much more }	5th.	$2\frac{1}{8}$	55	$21\frac{3}{8}$	$\frac{1}{2000}$	$3\frac{3}{8}$
Rivers in mountainous coun- tries having a rapid current and straight course, and very rarely overflowing }	6th.	3	40	30	$\frac{1}{2000}$	3
Rivers in their descent from among mountains down into the plains below, in which plains they run torrent-wise . . }	7th.	5	24	50	$\frac{1}{1000}$	$2\frac{1}{2}$
Absolute torrents among mountains }	8th.	8	15	80	$\frac{1}{1700}$	2

FALLS THE 22ND AUGUST, 1861 (BY MR. BATEMAN), ON THE SHANNON
BETWEEN ATHLONE AND VICTORIA LOCK, MEELICK.

Report, May, 1863.

	Height over upper sill of Victoria Lock.	Fall.	Distance.	Fall per Mile.
	ft. in.	ft. in.	miles	inches
Athlone	16 2	1 6	14½	1·263
Shannon bridge	14 8	2 5	8½	3·411
Banagher	12 3	3 5	4½	9·111
Victoria Lock, Meelick	8 10			

NATURAL FALLS ON THE RIVER SHANNON (BY MR. LYNAM).

Report, April, 1867.

Names of Places.	Falls.		Distances.	Fall per mile.
	In the river.	Over the weirs in moderate floods.		
	ft. in.	ft. in.	miles	inches
From Carrick on Shannon to Jamestown Bridge	0 9	..	5½	1·64
Thence to Jamestown Weir	1 0	..	½	6·00
Fall over Jamestown Weir	2 4	..	6·57
Thence to Albert Lock	1 11	..	3½	6·57
Thence to the head of Roosky Fall	0 2½	..	7	0·36
Thence to Roosky Weir	0 6	..	¾	4·00
Fall over Roosky Weir	1 5
From Roosky Weir to Tarmonbarry Weir	2 6	..	7½	4·00
Fall over Tarmonbarry Weir	5 6
From Tarmonbarry Weir to Lanesboro	1 3	..	7½	2·07
Thence to Athlone, head of the Fall	0 3	..	17½	0·17
Thence to the Weir	0 4	..	2	2·00
Fall over Athlone Weir	2 4
From Athlone Weir to River Suck	0 10½	..	15	0·70
Thence to Banagher	1 11½	..	8	2·94
Thence to Counsellor's Ford	0 9	..	2	4·50
Thence to Meelick Weir	1 1	..	2	6·50
Fall over Meelick Navigation and Eel Weirs	6 8	¾	..
From Meelick to Portumna	0 7	..	8	0·87
Thence to Killaloe Pier head	0 5½	..	23½	0·23
Thence to Killaloe Weir head	0 3	..	¾	18·00
Fall over Killaloe Weir at the head, 2 ft. 6 in.	2 9
Fall over Killaloe Weir at the lower end, 3 ft. 3 in.
Thence to Killaloe Bridge	1 1	..	¾	6·50
Total	15 9	21 0	111	..
In river	15 9
Additional fall at Tarmonbarry left out above to suit the heights of the water there	1 1
Whole fall	37 10

See above.

The fall from Killaloe to Limerick is about 97 feet in about 15 miles.

The following information with reference to the surface inclinations of the Thames, is also from Rennie's Report on Hydraulics,* as a branch of engineering science.

Names of places	Length.	Fall.	Fall in feet per mile.	Ratio of inclinations.
	miles fur.	feet in.		
From Lechlade at St. John's Bridge to Oxford at Folly Bridge	28 0	47 0	1.68	$3.1\frac{1}{4}3$
From Oxford to Abingdon Bridge	9 0	13 11	1.73	$3.0\frac{1}{2}2$
From Abingdon to Wallingford Bridge.	14 0	27 4	1.95	$2.7\frac{1}{8}8$
From Wallingford to Reading Bridge	18 0	24 1	1.31	$2.0\frac{1}{3}0$
From Reading to Henley Bridge	9 0	19 3	2.14	$2.2\frac{1}{2}7$
From Henley to Marlow Bridge	9 0	12 2	1.35	$3.9\frac{1}{11}$
From Marlow to Maidenhead Bridge	8 0	15 1	1.86	$2.8\frac{1}{3}9$
From Maidenhead Bridge to Windsor Bridge	7 0	13 6	1.93	$2.7\frac{1}{3}6$
From Windsor to Staines Bridge	8 0	15 8	1.96	$2.6\frac{1}{9}4$
From Staines to Chertsey Bridge	4 6	6 6	1.44	$3.6\frac{1}{6}7$
From Chertsey to Teddington-Lock	13 6	19 8	1.45	$3.6\frac{1}{11}$
From Teddington-Lock to London Bridge	19 0	2 9	.145	$26.4\frac{1}{14}$
From London to Yantlet Creek.	40 0	2 1	.052	$101.5\frac{1}{3}7$
From Lechlade to Yantlet Creek	186 4	218 0		
Deduct.	40 0			
From Lechlade to London .	146 4			

For enclosed channels, the circular form of sewer

* Report, for 1834, of the British Association.

will have the largest scouring power, at a given hydraulic inclination. For then the area of the sections being the same, the velocity in the circular channel will be a maximum. When the supply is intermittent, and the channel too large, the egg-shaped form with the smaller end for the bottom,—or the sides vertical with an inverted ridge-tile or V bottom for drains,—will have a hydrostatic flushing power to remove soil and obstructions, which a cylindrical channel, only partly full, does not possess; because a given quantity of water rises higher against the same obstruction, or obstacle, to the flow in the pipe. It must be confessed, however, that for small drains and house-sewage, this gain is immaterial, and is at best but effected by a sacrifice of space, material, and friction in the upper part of drains, from 6 to 12 inches in diameter. Besides this, the mere hydrostatic pressure is only intermittent, and during an ordinary, or heavy, fall of rain, the hydrodynamic power is always more efficient in scouring properly-proportioned cylindrical drains; and the workmanship in the form and joints is less imperfect than for more compound forms, as those with egg-shaped and inverted tile bottoms. The moulds and joints of cylindrical stone-ware drains, exceeding 12 inches in diameter, are seldom, however, in large quantities perfect; and the expense would exceed that of brick, stone, or other sufficient drains in many localities.

As to the increased discharging power which it is asserted by some, stone-ware cylindrical drains possess over other ordinary drains, no doubt it is true for small sizes, because the form, jointing, and surface are

in general more smooth and circular; and for *sewage matter*,* the friction and adherence to the sides and bottom is less; any advantage from these causes becomes, however, immaterial for the larger sizes, as these can be constructed of brick or stone abundantly perfect to any form, and sufficiently smooth for all practical purposes, for in the larger properly-proportioned sizes the same amount of surface roughness opposed to the sewage matter is, comparatively, of no effect. The judicious inclination and form of the bottom, and properly curved junctions, are the principal points to be attended to. Smaller drains tile-bottomed, with brick or stone sides, and flat-covered, have one great advantage over circular pipes.† They can be opened up, for examination and repairs at any time with facility, and at the smallest expense; but greater certainty must be attached to the working of *small* stone-ware drains than to equally-sized small brick or stone drains, and they will be found, in general, also cheaper. This, however, depends on the locality.


It may be observed in numerous experiments, that

* Weisbach found the coefficient of resistance 1.75 times as great for small wooden as for metallic pipes. All *permeable* pipes present greater resistance than *impermeable* ones; hence the principle advantage derived from glazing.

† Half-socket joints at bottom would remedy this imperfection in small pipes, and they could be better laid and cemented. A semi-circular flange laid on at top would effectually protect the joint on the upper side. Latterly Doulton has cut off an upper segment from the pipe, which can be removed for cleaning. And it may be demonstrated, that when this is a segment of $78\frac{1}{2}$ degrees, the lower portion will discharge more than a full pipe at the same inclination.

water flowing from a pipe does not entirely fill the orifice of exit, when the velocities are not considerable, and yet the results are found to be but slightly affected if a little more than three-fourths of the circumference be full. It is easy to demonstrate that the full circle does not give the maximum discharging velocity as has been generally believed, but when

Fig. 34a.



filled to the height of the chord ac of arc aec of $78\frac{1}{2}$ degrees, and where the velocity is $9\frac{1}{2}$ per cent. over that due to the full circle, for then the $\frac{\text{area } adc}{\text{arc } ade}$ is a maximum, and the length of the arc adc is equal to the tangent of the supplemental arc


aec , as may be without difficulty demonstrated. The hydraulic mean depths of the circle and larger segment are to each other as $\cdot 5$ to $\cdot 6$, and their square roots, which are as the velocities or scouring powers, are as 1 to 1.095. The discharging powers are to each other as 1×3.1416 to 1.095×2.946 , or as 1 to 1.026, which shows that the segment adc has also a greater discharging power than the whole circle of nearly three per cent. These facts, which were first pointed out by the author, are not unimportant in matters connected with drain-pipes and sewerage. The effects of greater velocity and discharge here pointed out, are sometimes increased, in short pipes, from the fall between the surface ac , and the surface from which

the head is measured, being greater than the fall to the top of the pipe at e , or from the inclination of the surface of the water in the pipe being greater than the inclination of the pipe itself.

EQUALLY DISCHARGING CHANNELS.

In order that different channels should have the same discharging power, the inclination of the surface being the same, the areas must be inversely as the square roots of the hydraulic mean depths. The channel $a d c B$, Fig. 35, will have the same discharge as the channel $A D C B$ if they be to each other

$$\text{as } \left\{ \frac{A D C B}{A D + D C + C B} \right\}^{\frac{1}{2}} \text{ to } \left\{ \frac{a d c B}{a d + d c + c B} \right\}^{\frac{1}{2}},$$



and hence the square root of the cube of the channel area, divided by the border, must be constant. With a fall of one or more feet to a mile, two channels, one 70 feet wide and 1 foot deep, and the other 20 feet wide and $2\frac{1}{2}$ feet deep, will have the same discharge. If w be put for the width and d for the depth of any rectangular channel, then

$$\left\{ \frac{w^3 d^3}{w + 2d} \right\}^{\frac{1}{2}} = m; \text{ and thence the cubic equation}$$

$$(122.) \quad d^3 - \frac{2m^2}{w^3}d = \frac{m^2}{w^2}$$

for finding the depth d of any other rectangular channel whose width is w , of the same discharging power. The depths d for different widths of channel have been calculated from this equation, assuming a width of 70 feet and different depths to find m from. The results are given in TABLE XI., which will be found sufficiently accurate for all practical purposes, when the banks are sloped, by taking the mean width. This table is equally applicable to any measures whatever, to their multiples, and sub-multiples.

If the hydraulic inclinations vary, then the \sqrt{rs} must be inversely as the areas of the channels when $\sqrt{rs} \times$ channel or the discharge is constant; and if the area of the channel and discharge be each constant, r must vary inversely as s ; and rs be also constant. For instance, a channel which has a fall of four feet per mile, and a hydraulic mean depth of one foot, will have the same discharge as another channel of equal area, having a hydraulic mean depth of four feet, and a fall per mile of only one foot. If in TABLE XII. the same discharge be taken from the columns for different inclinations, the mean rectangular dimensions corresponding to them in the first column will be found, and thereby an engineer be enabled to select an equally discharging channel from TABLE XI., suited to an increase or decrease of the hydraulic inclination.*

The next table at p. 270, of equally discharging

* Tables by the Author similar to numbers XI., XII., and XIII. but on a much more extended scale, have been printed and published on a separate sheet for office use, and may be had from the publisher.

river channels, with a primary channel having a mean width of 100, instead of 70, as in TABLE XI. has been calculated; and in the table at p. 271 are given the discharges at different inclinations from this new primary channel, to find those from its equivalents. The tables at pp. 28, 29, 271, and TABLE VIII., have also been calculated from Du Buât's formula. For slow velocity of only a few inches per second, the dimensions should be increased by about one-sixth, and the discharges by about one-half.

With reference to pipes, it is apparent that a given depth of roughness or contraction arising from any cause will have a greater effect the smaller the diameter becomes. Now in practice, it is necessary to increase the diameter beyond what is found by calculation. For small service pipes half-an-inch is the smallest diameter in general use. For mains and sub-mains the value of c in equation (74B), or at p. 196, should at least be doubled, or the discharge taken at one and a half times its amount to find the diameter. By enlarging the diameter by one-seventh, one-half the amount will be added to the discharge, very nearly; and by increasing the diameter by one-third, the discharge will be doubled. In a broad and practical sense, and considering the losses arising from depositions,* pipes under two inches should have one-third

* Mr. Bateman formerly in giving evidence, says:—"He wished to mention a circumstance which might be useful with regard to the spongillæ found in the Dublin water pipes. At Manchester, before the introduction of soft water, the city was supplied with hard water, which favoured the growth of a small fresh-water mussel, which thickly line the reservoirs and pipes. There were myriads of them, and they lay in the pipes as thick as paving stones. These were

TABLE of mean widths and depths of equally discharging trapezoidal River-channels, or Sewers, with side slopes up to $2\frac{1}{2}$ to 1. Practically all river-channels may be reduced to rectangular sections of equal areas and depths to find the discharge. See TABLE XI.

Primary Channel.	Mean rectangular dimensions of equally discharging water-channels or sewers, in any measures whatever, inches, feet, yards, fathoms, or their aliquot parts, or multiples.											Primary Channel.
Mean width 100	Mean width 90	Mean width 80	Mean width 70	Mean width 60	Mean width 50	Mean width 40	Mean width 30	Mean width 20	Mean width 15	Mean width 10	Mean width 100	
1	11	12	13	14	16	18	22	29	35	47	1	
125	13	14	16	17	20	23	28	37	45	60	125	
2	21	23	25	28	32	37	45	60	73	98	2	
25	27	29	32	35	40	46	56	75	92	125	25	
3	32	35	38	42	48	56	68	90	111	152	3	
375	40	44	48	53	60	70	85	113	140	194	375	
4	43	46	51	56	64	74	91	121	150	208	4	
5	54	58	64	71	80	93	114	153	190	267	5	
6	64	70	76	85	96	112	137	185	231	328	6	
625	67	73	79	88	100	116	143	193	242	344	625	
7	75	81	89	99	112	131	161	217	273	392	7	
75	80	87	95	106	120	141	173	234	295	425	75	
8	86	93	102	113	129	150	185	251	317	459	8	
875	94	102	112	124	140	164	202	276	350	510*	875	
9	97	105	115	127	145	169	208	284	361	528	9	
10	107	116	127	142	161	188	232	318	407	599	10	
1125	121	131	143	160	181	213	263	362	464	692	1125	
12	129	140	153	170	194	227	281	388	500	750	12	
125	135	146	160	178	202	237	294	406	524	789	125	
13	140	151	166	185	210	247	306	424	548	829	13	
1375	148	160	176	196	223	262	325	451	585	889	1375	
14	150	163	179	199	227	266	331	460	597	910	14	
15	161	175	192	214	243	286	356	497	647	992	15	
16	172	186	205	228	260	306	381	534	698	1078	16	
1625	175	189	208	232	264	311	387	543	711	1100	1625	
17	183	198	217	243	276	326	406	572	750*	1106	17	
175	188	204	224	250	285	336	419	591	777	1210	175	
18	193	210	230	257	293	345	432	609	803	1254	18	
1875	202	219	240	268	305	360	451	638	848	1323	1875	
19	204	222	243	271	310	365	457	648	857	1346	19	
20	215	233	256	286	326	386	483	687	911	1439	20	
21	226	245	269	301	343	406	509	727	967	1535	21	
22	237	257	282	315	360	426	536	766	1023	1632	22	
23	247	269	295	330	377	446	562	807	1080	1731	23	
24	258	280	308	344	394	467	589	848	1138	1833	24	
25	269	292	321	359	411	487	616	879	1197	1935	25	
26	280	304	334	374	428	508	642	931	1257	2040	26	
27	291	316	347	388	455	538	679	973	1317	2146	27	
28	301	327	360	403	462	549	697	1016*	1378	2252	28	
29	312	339	373	418	479	570	724	1059	1440	2363	29	
30	323	351	386	442	496	591	752	1102	1503	2475	30	
31	334	363	399	447	513	612	779	1146	1568		31	
32	345	375	413	462	530	633	807	1190	1632		32	
33	355	386	420	477	548	654	835	1235	1697		33	
34	366	398	439	492	565	675	864	1280	1763		34	
35	377	410	452	506	582	696	892	1326	1829		35	
36	388	422	465	521	600	718	921	1371	1896		36	
37	399	434	478	536	617	739	949	1418	1965		37	
38	409	446	491	551	635	760	978	1465	2034		38	
39	420	458	505	566	652	782	1007	1512			39	
40	431	469	518	581	670	804	1036	1559			40	
41	442	481	531	596	687	825	1066	1607			41	
42	453	493	544	611	705	847	1095	1655			42	
43	464	505	557	626	723	869	1125	1704			43	
44	474	517	571	641	740	891	1155	1753			44	
45	485	529	584	656	758	913	1185	1792			45	
46	496	547	597	672	776	935	1215	1852			46	
47	507	558	610	687	794	957	1245	1902			47	
48	518	564	624	702	812	979	1275	1953			48	
49	529	576	637	717	829	1002	1306	2004			49	
50	540	588	650	732	847	1024	1337				50	

* A semi-hexagon has the greatest discharging power of all trapezoids of equal depth and area. All rectangles have the same discharging power as trapezoids of the same depth and area, with side slopes of 1 to 1. The differences for other side slopes are immaterial in practice.

* A semi-hexagon has the greatest discharging power of all trapezoids of equal depth and area. All rectangles have the same discharging power as trapezoids of the same depth and area. The difference for other side slopes are in material in practice.

TABLE of the Discharges in cubic feet per minute from the primary Channel in the opposite page, taken in feet; and from the corresponding equivalent Channels, also taken in feet. See TABLE XII.

Depths of the primary channel in opposite table, having a mean width of 100, in feet.	Discharges in cubic feet per minute. Interpolate for intermediate falls or inclinations: divide greater falls or inclinations by 4, and double the corresponding discharges. If the dimensions be in inches, divide the discharges here given by 500; if in tenths, by 516; if in eighths, by 531; if in sixths, by 548; if in fifths, by 566; if in quarters, by 582; if in thirds, by 599; and if in halves, by 616. Reverse the operation and multiply for like multiples.											Depths of the primary channel in opposite table, having a mean width of 100, in feet.
	4 inches per mile, in 1340.	6 inches per mile, in 1000.	9 inches per mile, in 700.	12 inches per mile, in 520.	15 inches per mile, in 424.	18 inches per mile, in 332.	21 inches per mile, in 307.1.	24 inches per mile, in 250.	30 inches per mile, in 212.	36 inches per mile, in 176.		
.1	110	140	176	207	235	260	284	305	345	383		.1
.125	157	198	250	294	332	373	402	433	490	543		.125
.2	325	409	515	606	686	760	828	891	1,009	1,117		.2
.25	455	575	725	853	966	1,070	1,166	1,256	1,422	1,574		.25
.3	601	760	957	1,125	1,275	1,412	1,539	1,658	1,876	2,076		.3
.375	844	1,068	1,344	1,582	1,793	1,985	2,162	2,329	2,637	2,919		.375
.4	931	1,178	1,484	1,745	1,977	2,189	2,386	2,569	2,900	3,220		.4
.5	1,308	1,653	2,081	2,447	2,775	3,071	3,347	3,606	4,083	4,513		.5
.6	1,721	2,178	2,743	3,227	3,657	4,047	4,410	4,752	5,401	5,956		.6
.625	1,830	2,316	2,917	3,431	3,887	4,303	4,690	5,053	5,795	6,332		.625
.7	2,177	2,750	3,463	4,072	4,614	5,109	5,568	5,999	6,936	7,516		.7
.75	2,414	3,029	3,844	4,520	5,123	5,674	6,180	6,660	7,567	8,342		.75
.8	2,660	3,363	4,236	4,982	5,646	6,253	6,811	7,340	8,309	9,194		.8
.875	3,044	3,850	4,846	5,703	6,463	7,157	7,770	8,401	9,513	10,527		.875
.9	3,175	4,017	5,060	5,951	6,743	7,467	8,082	8,765	9,926	10,984		.9
1.0	3,731	4,711	5,933	6,973	7,903	8,750	9,513	10,273	11,634	12,877		1.0
1.125	4,441	5,614	7,071	8,313	9,421	10,430	11,369	12,216	13,867	15,347		1.125
1.2	4,889	6,186	7,791	9,163	10,381	11,494	12,521	13,494	15,280	16,914		1.2
1.25	5,207	6,582	8,291	9,752	11,048	12,232	13,336	14,361	16,261	18,000		1.25
1.3	5,529	6,981	8,793	10,357	11,718	12,974	14,146	15,234	17,246	19,091		1.3
1.375	6,004	7,591	9,561	11,245	12,734	14,107	15,386	16,576	18,752	20,756		1.375
1.4	6,167	7,797	9,821	11,544	13,087	14,491	15,794	17,031	19,262	21,318		1.4
1.5	6,844	8,653	10,898	12,818	14,524	16,081	17,523	18,917	21,376	23,658		1.5
1.6	7,538	9,520	12,002	14,115	15,994	17,709	19,296	20,829	23,539	26,053		1.6
1.625	7,705	9,741	12,273	14,428	16,348	18,102	19,724	21,286	24,061	26,631		1.625
1.7	8,252	10,432	13,139	15,432	17,509	19,360	21,126	22,780	25,769	28,523		1.7
1.75	8,617	10,893	13,719	16,134	18,282	20,241	22,060	23,776	26,907	29,784		1.75
1.8	8,993	11,369	14,318	16,851	19,079	21,124	23,024	24,821	28,081	31,055		1.8
1.875	9,561	12,088	15,226	17,905	20,287	22,463	24,476	26,372	29,860	33,052		1.875
1.9	9,741	12,316	15,515	18,245	20,672	22,890	24,946	26,872	30,426	33,682		1.9
2.0	10,515	13,297	16,753	19,702	22,320	24,718	26,935	29,019	32,852	36,558		2.0
2.1	11,307	14,300	18,020	21,192	23,991	26,561	29,074	31,213	35,334	39,106		2.1
2.2	12,110	15,314	19,297	22,689	25,708	28,467	31,024	33,424	37,838	41,878		2.2
2.3	12,935	16,357	20,608	24,235	27,456	30,407	33,134	35,694	40,410	44,724		2.3
2.4	13,781	17,425	21,954	25,816	29,250	32,302	35,299	38,022	43,048	47,643		2.4
2.5	14,647	18,520	23,332	27,436	31,087	34,425	37,516	40,407	45,750	50,634		2.5
2.6	15,538	19,645	24,747	29,100	32,974	36,514	39,794	42,856	48,526	53,706		2.6
2.7	16,430	20,773	26,167	30,770	34,867	38,610	42,078	45,316	51,311	56,789		2.7
2.8	17,333	21,915	27,605	32,462	36,784	40,733	44,390	47,809	54,131	59,913		2.8
2.9	18,257	23,084	29,076	34,193	38,744	42,905	46,755	50,359	57,017	63,110		2.9
3.0	19,203	24,280	30,581	35,963	40,750	45,127	49,175	52,968	59,968	66,379		3.0
3.1	20,167	25,498	32,120	37,767	42,794	47,392	51,640	55,634	62,986	69,709		3.1
3.2	21,146	26,737	33,673	39,600	44,871	49,692	54,148	58,327	66,033	73,097		3.2
3.3	22,118	27,969	35,225	41,425	46,939	51,978	56,640	61,017	69,077	76,465		3.3
3.4	23,106	29,220	36,798	43,275	49,036	54,302	59,171	63,745	72,164	79,879		3.4
3.5	24,115	30,497	38,407	45,166	51,180	56,675	61,758	66,534	75,322	83,371		3.5
3.6	25,139	31,795	40,040	47,086	53,356	59,084	64,384	69,366	78,526	86,915		3.6
3.7	26,182	33,116	41,702	49,041	55,572	61,532	67,058	72,249	81,779	90,524		3.7
3.8	27,233	34,446	43,379	51,013	57,807	64,009	69,753	75,158	85,088	94,162		3.8
3.9	28,287	35,777	45,060	52,989	60,046	66,489	72,455	78,061	88,371	97,810		3.9
4.0	29,356	37,128	46,766	54,994	62,318	69,006	75,197	81,012	91,710	101,512		4.0
4.1	30,438	38,495	48,492	57,024	64,616	71,553	77,973	83,999	95,093	105,259		4.1
4.2	31,538	39,884	50,246	59,086	66,950	74,141	80,793	87,033	98,535	109,065		4.2
4.3	32,654	41,294	52,027	61,180	69,327	76,769	83,655	90,116	102,025	112,930		4.3
4.4	33,776	42,712	53,816	63,283	71,709	79,406	86,529	93,209	105,531	116,811		4.4
4.5	34,908	44,138	55,613	65,394	74,100	82,052	89,413	96,318	109,050	120,700		4.5
4.6	36,041	45,579	57,429	67,527	76,500	84,725	92,327	99,460	112,614	124,647		4.6
4.7	37,193	47,034	59,262	69,682	78,955	87,426	95,271	102,633	116,209	128,625		4.7
4.8	38,363	48,514	61,128	71,874	81,438	90,173	98,266	105,860	119,862	132,672		4.8
4.9	39,544	50,009	63,011	74,087	83,944	92,946	101,289	109,119	123,559	136,758		4.9
5.0	40,725	51,507	64,895	76,298	86,450	95,726	104,313	112,376	127,248	140,841		5.0

or more added to their calculated dimensions, and larger pipes from one-third to one-seventh — even after making allowance for junctions, bends, and contractions. For large conduits or channels the allowance need not be so large, if the maximum quantity to be conveyed has been duly estimated.


SECTION X.

EFFECTS OF ENLARGEMENTS AND CONTRACTIONS. BACK-WATER WEIR CASE.—LONG AND SHORT WEIRS.—THE SHANNON.

When the flowing section in pipes or rivers expands or contracts suddenly, a loss of head always ensues; this is probably expended in forming eddies at the sides, or in giving the water its new section. A side current, moving slowly sometimes *upwards*, may be frequently observed in the wide parts of rivers, when the channel is unequal, though the downward current, at the centre, be pretty rapid; and though it may be assumed generally that the velocities are inversely as the sections, when the channels are uniform, this cannot properly be done when they are not, and the

caused by the large quantity of lime in the water. He was curious to see what would be the effect of passing water without lime. This was done ten or eleven years ago, and the result was that these mussels had entirely disappeared. There was no longer anything from which they could make their shells, and for years, on their discharge, the small pipes were found choked with them. If soft water were supplied to Dublin in place of the present hard water, which probably favoured the growth of spongillæ, they would probably disappear." This has been since done, and Dublin has been supplied, from the Vartry, with most satisfactory results as to quality, quantity, and cost.

motions so uncertain as those referred to. When a pipe is contracted by a diaphragm at the orifice of entry, Fig. 27, it was shown (equation 60), that the loss of head is,



$$(123.) \quad h = \frac{\left(1 - \frac{A^2}{C^2}\right)v^2 + \left(\frac{A}{a c_d} - 1\right)^2 v^2}{2g}.$$

When the diaphragm is placed in a uniform pipe, Fig. 36, then $A = C$, and the loss of head is

$$(124.) \quad h = \frac{\left(\frac{A}{a c_d} - 1\right)^2 v^2}{2g};$$

and the coefficient of resistance

$$(125.) \quad c_r = \left(\frac{A}{a c_d} - 1\right)^2,$$

as in equation (67). The coefficient of discharge c_d is here equal to the coefficient of contraction c_c , or very nearly. Now it is shown in equation (45), and the remarks following it, that the value of the coefficient of discharge, c_d , varies according to the ratio of the sections, $\frac{A}{a}$,* and in TABLE V. we have calculated the

* The empirical value of c_d as given by Professor Rankine, is $\cdot 618$
 $c_d = \frac{\cdot 618}{\left(1 - \cdot 618 \frac{a^2}{A^2}\right)^{\frac{1}{2}}}$, which is equal to unity when $a = A$, as it

should be; and equal to $\cdot 618$, when a is very small, compared with A , as it also should be when the diaphragm is a thin plate, *but not otherwise*. If the thickness of the diaphragm be twice the diameter of the orifice a , the coefficient of discharge would be $\cdot 815$; and if the higher arris be rounded, this would be increased to 1, in which cases the expression would clearly fail; the thickness of the diaphragm and the form of the aperture a must also be considered.

T

new coefficients for different values of the ratios, and different values of the primary coefficient c_d . If c_d , when A is very large compared with a , be $\cdot 628$, then by attending to the remarks at pp. 101 and 103, it is found, that the different values of c_d corresponding to $\cdot 807 \times \frac{A}{a}$, taken from TABLE V., are those in columns Nos. 2 and 5 of the next small table, the values of the

TABLE OF COEFFICIENTS FOR CONTRACTION, BY A DIAPHRAGM
IN A PIPE.

$\frac{a}{A}$	c_d	c_r	$\frac{a}{A}$	c_d	c_r
$\cdot 0$	$\cdot 628$	infinite	$\cdot 6$	$\cdot 713$	$1\cdot 790$
$\cdot 1$	$\cdot 630$	$221\cdot 2$	$\cdot 7$	$\cdot 753$	$\cdot 807$
$\cdot 2$	$\cdot 636$	$47\cdot 1$	$\cdot 8$	$\cdot 807$	$\cdot 801$
$\cdot 3$	$\cdot 647$	$17\cdot 2$	$\cdot 85$	$\cdot 845$	$\cdot 154$
$\cdot 4$	$\cdot 661$	$7\cdot 7$	$\cdot 9$	$\cdot 890$	$\cdot 062$
$\cdot 5$	$\cdot 683$	$3\cdot 7$	1	$1\cdot 000$	$\cdot 000$

coefficient of resistance, in columns 3 and 6, being calculated from equation (125) for the respective new values of the coefficient of discharge thus found. The table shows that when the aperture in a diaphragm is $\frac{1}{10}$ ths of the section of the pipe, that 47 times the head due to the velocity is lost thereby. If the aperture in the diaphragm be rounded at the arrises, the loss will not be so great, as the primary coefficient c_d will then be greater than that due to an orifice in a thin plate: see the TABLE OF COEFFICIENTS, p. 169.

When there are a number of diaphragms in a tube, the loss of head for each must be found separately, and all added together for the total loss. If the


diaphragms, however, approach each other, so that the water issuing from one of the orifices *a*, Fig. 36, shall pass into the next before it again takes the velocity due to the diameter of the pipe, the loss will not be so great as when the distance is sufficient to allow this change to take place. This view is fully borne out by the experiments of Eytelwein with tubes 1·08 inch in diameter, having apertures in the diaphragms of ·51 inch in diameter.

Venturi's twenty-fourth experiment, with tubes varying from ·75 inch to ·934 inch in diameter at the junction with the cistern, so as to take the form of the contracted vein, and expanding and contracting along the length from ·75 to 2 inches and from 2 inches to ·75 inch alternately, shows the great loss of head sustained by successive enlargements and contractions of a channel, even when the junction of the parts is gradual. Calling the coefficient for the short tube, with a junction of nearly the form of the contracted vein, 1, then the following coefficients are derivable from the experiment:—

Short tube with rounded junction	1·
One enlargement	·741
Three enlargements	·569
Five enlargements	·454
Simple tube with a rounded junction of the same length, 36 inches, as the tube with the five enlarged parts	·736

The head, in the experiment, was $32\frac{1}{2}$ inches. Venturi states that no observable differences occurred in the times of discharge when the enlarged portions were lengthened from $3\frac{1}{8}$ to $6\frac{1}{2}$ inches. See tables, pp. 146 and 199.

With reference to this experiment, so often quoted, it is necessary to remark that the diameters of the enlarged portions were 2 inches each, while the lengths varied only from $3\frac{1}{2}$ to $6\frac{1}{2}$ inches, and consequently were at most only $3\frac{1}{2}$ times the diameter. Now with



such a large ratio of the width to the length of the enlarged portions, *aABb*, Fig. 37, it is pretty clear that a good deal of the head is lost by the im-

compact of the moving water on the shoulders at *A* and *B*. That this is so is evident from the fact, stated by the experimenter, of the time of discharge remaining the same when *aA*, in five different enlargements, was increased from $3\frac{1}{2}$ to $6\frac{1}{2}$ inches; though this must have lengthened the whole tube from 36 to 50 inches,* thereby increasing the loss from friction proportionately, but which happened to be compensated for by the reduction in the resistances from impact at *A* and *B*, and in the eddies, by doubling the lengths from *a* to *A*.

If, however, the length from *a* to *A* be very large compared with the diameter, and the junctions at *a*, *A*, *B*, and *b*, be well grafted, less loss will arise from the enlargement than if the smaller diameter continued all along uniform. The explanation is clear, as the resistance from friction is inversely as the square roots of the mean radii; and the length being the

* The dimensions throughout this experiment are given as in the original, viz., in French inches.

same, the loss must be less with a large than a small diameter.

These remarks, *mutatis mutandis*, apply equally to rivers as to pipes. The effects of submerged weirs and contracted river channels has been already pointed out at pp. 134 and 141, and formulæ given for calculating them.

BACKWATER FROM CONTRACTIONS IN RIVERS.

A river may be contracted in width or depth, by jetties or by weirs; and when the quantity to be discharged is known, equations from which the increase of head may be found are given in formulæ (9), (55), and (57). The effect of a weir, jetty, or contracted channel of any kind, is to increase the depth of water above; and this is sometimes necessary for navigation purposes, or to obtain a head for mill power. When a weir is to rise over the surface, then from the length, the discharge per minute, the coefficient due to the crest, and the coefficient due to the ratio of the sections, on and above the weir, found from TABLE V., the head can be found from TABLE VI. For submerged weirs and contracted widths of channel, the head can be best calculated, by approximation, from the equations above referred to.

The head once determined, the extent of the backwater is a question of some importance. If $F C O D$, Fig. 38, be the original surface of a river, and $a A B F$ the raised surface by backwater from the weir at a , then the extent $a F$ of this backwater, in a regular channel, will be from 1.5 to 1.9 times $a c$ drawn parallel to the

head equal $\frac{v_1^2 - v^2}{2g}$, and if c_f be the coefficient of friction, there is a loss of head from this cause equal $c_f \times \frac{l}{r_m} \times \frac{(v_1 + v)^2}{2g}$; hence the whole change of head in passing from B to A is equal to $c_f \times \frac{l}{r_m} \times \frac{(v_1 + v)^2}{8g} - \frac{v_1^2 - v^2}{2g}$. But this change of head is equal to BE - AD

$$(126.) \quad h_1 - h = d_1 - d = c_f \times \frac{l}{r_m} \times \frac{(v_1 + v)^2}{8g} - \frac{v_1^2 - v^2}{2g} - ls;$$

or as $v_1 = \frac{A}{A_1} v$, and $r_m = \frac{A + A_1}{2b_m}$, by a few reductions and change of signs,

$$(127.) \quad h - h_1 = \left(s - c_f \times b_m \times \frac{A + A_1}{2A_1^2} \times \frac{v^2}{2g} \right) l + \frac{A^2 - A_1^2}{A_1^2} \times \frac{v^2}{2g};$$

and therefore

$$(128.) \quad l = \frac{h - h_1 - \frac{A^2 - A_1^2}{A_1^2} \times \frac{v^2}{2g}}{s - c_f \times \frac{b_m \times (A + A_1)}{2A_1^2} \times \frac{v^2}{2g}},$$

from which the length l corresponding to any assumed change of level between A and B can be calculated. Then, by a simple proportion the change of level for any smaller length can be found. To find the change of level directly from a given length does not admit of

a direct solution, for the value of $h - h_1$ in equation (127) involves A_1 , which depends again on $h - h_1$, and further reduction leads to an equation of a higher order; but the length corresponding to a given rise, h_1 , is found directly by equation (128).

When the width of the channel, w , is constant, and the section equal to $w \times d$ nearly, the above equations admit of a further reduction for $A_1 = d_1 w$ and $A = d w$; by substituting these values in equation (127) it becomes, after a few reductions,

$$(129.) \quad h - h_1 = d - d_1 \\ = \left(s - c_f \times b_m \times \frac{d + d_1}{2 d_1^2 w} \times \frac{v^2}{2g} \right) l + \frac{d^2 - d_1^2}{d_1^2} \times \frac{v^2}{2g};$$

or, as it may be further reduced,

$$(130.) \quad h - h_1 = \frac{s - c_f \times \frac{b_m}{d_1 w} \times \frac{d + d_1}{2 d_1} \times \frac{v^2}{2g}}{1 - \frac{d + d_1}{d_1^2} \times \frac{v^2}{2g}} \times l.$$

Now, in this equation, for all practical purposes,

$$\frac{d + d_1}{2 d_1} \times \frac{b_m}{d_1 w} = \frac{b}{d w},$$

approximately, b being the border of the section at $A H$; and also, $\frac{d + d_1}{d_1^2} = \frac{2}{d}$, approximately, therefore

$$(131.) \quad h - h_1 = \frac{s - c_f \times \frac{b}{d w} \times \frac{v^2}{2g}}{1 - \frac{2}{d} \times \frac{v^2}{2g}} \times l;$$

and

$$(132.) \quad l = \frac{(h - h_1) \times \left(1 - \frac{2}{d} \times \frac{v^2}{2g} \right)}{s - c_f \times \frac{b}{d w} \times \frac{v^2}{2g}}.$$

Now, as $\frac{b}{dw} = \frac{1}{r}$, $2g = 64.4$, and the mean value of the coefficient of friction for small velocities $c_f = .0078$, then

$$(133.) \quad h_1 = h - \frac{64.4 \, d \, s - .0078 \frac{d}{r} v^2}{64.4 \, d - 2 \, v^2} \times l;$$

and

$$(134.) \quad l = \frac{(h - h_1) \times (64.4 \, d - 2 \, v^2)}{64.4 \, d \, s - .0078 \frac{d}{r} v^2},$$

very nearly. Having by means of these equations found AB from BO or BE , and BO from AB , we can in the same manner proceed up the channel and calculate B_1C , B_2C_1 , &c., until the points B , B_1 , B_2 in the curve of the backwater shall have been determined, and until the last nearly coincides with the original surface of the river. When $h_1 = 0$, then

$$h = \frac{64.4 \, d \, s - .0078 \frac{d}{r} v^2}{64.4 \, d - 2 \, v^2} \times l.$$

If equation (134) be examined, it appears that when $64.4 \, d = 2 \, v^2$, l must be equal to zero; or when $\frac{d}{2} = \frac{v^2}{64.4}$, equal the height due to the velocity v . When l is infinite, $64.4 \, d$ must exceed $2 \, v^2$, and $64.4 \, d \, s$ equal to $.0078 \frac{d}{r} v^2$;

$$\text{or, } \frac{64.4 \, r \, s}{.0078} = v^2, \text{ and } v = 90.9 \sqrt{r \, s}.$$

This is the velocity due to friction in a channel of the depth d , hydraulic mean depth r , and inclination s ;

and, as in wide rivers $r = d$ nearly, $v = 90.9 \sqrt{d s}$, but when the numerator was zero we had from it $v = \sqrt{32.2 d}$; equating these values of v , $s = \frac{1}{256}$ nearly: see p. 133. Now, the larger the fraction s is, the larger will the velocity v become; and the larger v becomes, the more nearly, in all practical cases, will the terms

$$64.4 d - 2 v^2 \text{ and } 64.4 d s - .0078 \frac{d}{r} v^2,$$

in the numerator and denominator of equation (134), approach zero; when $64.4 d - 2 v^2$ becomes zero first, $l = 0$; when $64.4 d s - .0078 \frac{d}{r} v^2$ becomes zero first,

l equals infinity; and when they both become zero at the same time, $l = h - h_1$, and $s = \frac{1}{256}$: see p. 133;

if s be larger than this fraction, the numerator in equation (134) will generally become zero before the denominator, or negative, in which cases l will also be zero, or negative; and the backwater will take the form $r c_2 b_2 b_1 b a_1 a$, Fig. 38, with a hollow at c_2 . Bidone first observed a hollow, as $F c_2 b_2$, when the inclination s was $\frac{1}{30}$. When the inclination of a river channel changes from greater to less, the velocity is obstructed, and a hollow similar to $r c_2 b_2$ sometimes occurs. When the difference of velocity is considerable, the upper water at b_2 falls backwards towards c_2 and F , and forms a *bore*, a splendid instance of which is the *pororoca*, on the Amazon, which takes place where the inclination of the surface changes from six inches to one-fifth of an inch per mile, and the velocity from about 22 feet to $4\frac{1}{2}$ feet per second.

WEIR CASE, LONG AND SHORT WEIRS.

When a channel is of very unequal widths, above a weir, the following simple method of calculating the backwater will be found sufficiently accurate, and the results to agree with observation. *Having ascertained the surface fall due to friction in the channel at a uniform mean section, add to this fall the height which the whole quantity of water flowing down would rise on a weir having its crest on the same level as the lower weir, and of the same length as the width of the channel in the contracted pass. The sum will be the head of water at some distance above such pass very nearly.* A weir was formerly constructed on the river Blackwater, at the bounds of the counties Armagh and Tyrone, half a mile below certain mills, which, it was asserted, were injuriously affected by backwater thrown into the wheel-pits. The crest of the weir, 220 feet long, was 2 feet 6 inches below the pit; the river channel between varied from 50 and 57 feet to 123 feet in width, from 1 foot to 14 feet deep; and the fall of the surface, with 3 inches of water passing over the weir and the sluices down, was nearly 4 inches in the length of half a mile. Having seen the river in this state in summer, the Author had to calculate the backwater produced by different depths passing over the weir in autumn and winter, which in some cases of extraordinary floods were known to rise to 3 feet. The width of the channel about 60 feet above the weir averaged 120 feet. The width, 2050 feet above the weir and 550 feet below the mills, was narrowed by a slip in an adjacent canal bank, to 45 feet at the level of the top of the weir, the

average width at this place as the water rose being 55 feet. The channel above and below the slip widened to 80 and 123 feet. Between the mills and the weir there were, therefore, two passes; one at the slip, averaging 55 feet wide; another above the weir, about 120 feet wide. Assuming as above, that the water rises to the heights due to weirs 55 and 120 feet long, at these passes, then, by an easy calculation, or by means of TABLE X., the heads in columns two and four of the table on the next page were found, corresponding to the assumed ones on the weir, given in the first column.

As the length of the river was short, and the hydraulic mean depth pretty large, the fall due to friction for 60 feet above the weir was very small, and therefore no allowance was made for it; even the distance to the slip was comparatively short, being less than half a mile, and as the water approached it with considerable velocity, this was conceived, as the observations afterwards showed, to be a sufficient compensation for the loss of head below by friction. The observations were made by a separate party, over whom the Author had no control, and it is necessary to remark, that with the same head of water on the weir, they often differed more from each other than from the calculation. This, probably, arose from the different directions of the wind, and the water rising during one observation, and falling during another.

The true principle for determining the head at g , Fig. 39, apart from that due to friction, is that pointed out at pp. 136 and 141, but when the passes are very near each other, or the depth d_2 , Fig. 28, is small, the effect of the discharge through d_2 is inconsiderable in

reducing the head, as the contraction and loss of *vis-viva* are then large, and the head d_1 becomes that due to a weir of the width of the contracted channel at A, nearly. The reduction in the extent of the backwater,

TABLE OF CALCULATED AND OBSERVED HEIGHTS ABOVE M'KEAN'S WEIR, NEAR BENBURG, ON THE RIVER BLACKWATER.

Heights at M'Kean's weir 220 feet long, in inches.	Heights 60 feet above the weir channel 120 feet wide.		Heights 2050 feet above the weir channel 55 feet wide; average.	
	Calculated inches.	Observed inches.	Calculated inches.	Observed inches.
1½	2½	2½	4½	5½
2
3	4½	...	7½	7
4	6	...	10	9
5	7½	...	12½	11½
6	9	9	15	16½
7	10½	10½	17½	18½
8	12	...	20	20½
9	13½	12½	22½	20½
10	15	...	24½	20
11	16½	...	27½	24
12	18	17	30½	31
13	19½	18½	32½	33
15	22½	21	37½	40
18	27	25	45½	46
21	31½	29½	53	54
24	36	34	60½	62

by lowering the head on a longer weir, is found by taking the difference of the amplitudes due to the heads at *g*, Fig. 39, in both cases, as determined from equations (56), (128), *et seq.* This will seldom exceed a mile up the river, as the surface inclination is found to be considerably greater than that due to mere friction and velocity, and hence the general failure of drainage works designed on the assumption that the lowering


of the head below, by means of long weirs, extends its effects all the way up a channel. It is necessary to treble the length of a weir before the head passing over can be reduced by one-half, TABLE X., even supposing the circumstances of approach to be the same : surely several engineering appliances for shorter weirs, during periods of flood, would be found far more effective and much less expensive than this alternative, with its extra sinking up channel and enlarged weir basin for drainage purposes.*

The advocates for the necessity of weirs longer than the width of the channel, for drainage purposes, must show that the reduction of the head and extent of backwater above *g*, Fig. 39, is not small, and that the effects extend the whole way up the channel, or at least as far as the district to be benefited. Practice has heretofore shown, that long weirs have failed (unless after the introduction of sluices or other appliances) in producing the expected arterial drainage results, notwithstanding the increased leakage from increased length, which must accompany their construction.

The deepening in the weir basin *a b B E A* is mostly of use in reducing the surface inclination between *a b* and *A B* by increasing the hydraulic mean depth ; but, thereby, the velocity of approach is lessened, and therefore the head at *E* increased. When the length of a

* When this was first written, in 1849, the Author was not acquainted with the good common sense appliances of moveable weirs used by the French, which raised the levels at low water to admit of navigation ; and being removed, or falling level with the bottom bed in floods, permitted the full drainage of the upper riparian lands, when most required.

weir basin $a E$ exceeds that point where these two opposite effects balance each other, there will be a gain by the difference of the surface inclinations in favour of the long weir : but unless $a E$ exceeds half a mile, this difference cannot amount to more than one or two inches, unless the river be very small indeed ; and if



the channel be sunk for the long weirs $B A$ or $b a$, it should also be sunk to at least the same depth and extent for the short weirs $B e$, $b a$, otherwise there is no fair comparison of their separate merits. The effect of the widening between $a b$ and $A B$, the depth being the same, is also to reduce the surface inclination from a to E ; but, as before, unless $a E$ be of considerable length, this gain will also be small. Now $A B$, at best, is but a weir the direct width of the new channel at $A B$, and if the length $a E$ be considerable, there is an entirely new river channel with a direct weir at the lower end, and the saving of head effected arises entirely from the larger channel, with as it were a *direct* transverse weir at the lower end.

By referring to TABLE VIII., it will be found that for a hydraulic mean depth of 5 feet a fall of $7\frac{1}{2}$ inches

per mile will give a velocity of 2 feet per second; if of double the depth, a fall of 4 inches will give the same velocity; and for a depth of only 2 feet 6 inches, a fall of $12\frac{1}{2}$ inches is necessary. This is a velocity much larger than we have ever observed in a deep weir basin, yet it is easily perceived that the difference in the inclinations for a short distance, *E a* of a few hundred feet, must be small. If one section be double the other, the hydraulic mean depth remaining constant, the velocity must be one-half, and the fall per mile, one-fourth, nearly. This would leave $7\frac{1}{4} - 2 = 5\frac{1}{4}$ inches per mile, or 1 inch per 1000 feet nearly, as the gain with a hydraulic mean depth of 5 feet for a double water channel. For greater depths the gain would be less, and the contrary for lesser depths.

Is the saving of head and amplitude of backwater here estimated worth the increased cost of long weirs and the consequent necessity and expense of sinking and widening the channels for such long distances? Certainly not; indeed, *any extra sinking in the basin immediately at the weir is absolutely injurious by destroying the velocity of approach*, and increasing the contraction. The gradual approach of the bottom towards the crest, shown by the upper dotted line *b E* in the section, Fig. 39, and a sudden overfall, will be found more effective in reducing the head, unless so far as leakage takes place, that any depth of sinking for nearly 80 or 100 feet above long weirs.

In most instances, the extra head will be only perceived by an increased surface inclination, which may extend for a mile or more up the channel, according to the sinking and widening.

It is a general rule that, for shorter weirs, the coefficients of discharge decrease; this arises from the greater amount of lateral contraction, and is more marked in notches or Poncelet weirs, than for weirs extending from side to side of the channel; but for weirs exceeding 10 feet in length the decrease in the coefficients from this cause is immaterial, unless the head passing over bear a large ratio to the length; and it may be seen from the coefficients, page 68, derived from Mr. Blackwell's experiments, that with 10 inches head passing over a 2-inch plank, the coefficient for a length of 3 feet was .614; for a length of 6 feet .539; and for a length of 10 feet .534; showing a decrease as the weir lengthens, but which may, in the particular cases, be accounted for. Other circumstances which modify the coefficients were before referred to, yet it may be assumed generally, without any error of practical value, that the coefficients are the same for different weirs extending from side to side of a river. If, then, w and w_1 be put for the lengths of two such weirs, the relation of the heads d and d_1 for the same quantity of water passing over is given by the following proportion:—

$$d : d_1 :: w_1^{\frac{3}{2}} : w^{\frac{3}{2}};$$

and therefore

$$(135.) \quad d_1 = \left(\frac{w}{w_1}\right)^{\frac{2}{3}} \times d.$$

By means of this equation, TABLE X. has been calculated; the ratio $\frac{w}{w_1}$ being given in columns 1, 3, 5 and 7, and the value of $\left(\frac{w}{w_1}\right)^{\frac{2}{3}}$, or the coefficient by which

d is to be multiplied, to find d_1 in columns 2, 4, 6 and 8. It appears also, that *if the heads passing over any weir in a river be taken in an arithmetical progression, the heads then passing over any other weir in the same river must also be in arithmetical progression, unless the quantity flowing down varies from erogation or supply, such as drawing off by millraces, &c.* If c_d be the coefficient for a direct weir, $\cdot 94 c_d$ will answer for an obliquity of 45° , and $\cdot 91 c_d$ for an angle of 65° .

In the first edition of this work though not specially mentioned, the observations on this subject had general reference to the weirs constructed across the Shannon at Killaloe, Meelick, and Athlone, and elsewhere. Since then the failure of these works is admitted by all, although previously the author stood alone in asserting that they should fail. To expect that lowering the head by extending the weir would extend its results for miles up the river, showed ignorance of the first principles of river-engineering; but when the surface was shown actually level on the sections from Killaloe to Meelick, and Meelick to Athlone on distances of 32 miles, and 27 miles, without any fall to give velocity to and convey off the waters something like wonder must be felt.* The French had and have several expedients for keeping up the summer levels, all founded on one sound principle, viz.: the removal of these obstructions before and during floods. In *Les Barrages a Hausses Mobiles*,† the separate panels or

* See Plan 39, Second Report, and Plans Nos. 12 and 13 in Fourth Report of the Shannon Commissioners.

† *Vide Mémoire sur les barrages a Hausses Mobiles* par MM. Chanoine ingénieur en chef et De Lagrène, ingénieur ordinaire des ponts et chaussées, Paris, 1862.


doors of which the weir is made up, are laid lying at the bottom, during floods; admitting the free navigation of the main channel. These are raised in summer, and the navigation carried on by means of a lateral lock. When the navigation of the main channel cannot be maintained at any time, sluices which lift entirely out of the water are perhaps best, as they can, for most rivers, be made up to 30 feet in width, as in patent of Mr. F. G. M. Stoney. The advantage of both these designs is, that the fall at the site is available in full, not only to discharge the water freely through its own depth, but also to give extra velocity and discharge to the under water thence down to the bottom, as in Fig. 22, if the weir were removed. The use of the syphon (see equations (154 to 154 *b*) *infra*,) assumes the necessity for the fixed weir; but this appliance can at no time discharge a greater amount of water than that due to the head or difference of levels, but always less; and it has no effect in increasing the discharge between the lower surface of the water and the bottom, which both the other designs have, and very considerably augment. See SECTION V.

SECTION XI.

BENDS AND CURVES. — BRANCH PIPES. — DIFFERENT LOSSES OF HEAD. — GENERAL EQUATION FOR FINDING THE VELOCITY. — HYDROSTATIC AND HYDRAULIC PRESSURE. — PIËZOMETER. — SYPHONS.

The resistance or loss of head due to bends and curves has now to be considered. If a bent pipe,

F B C D E G, Fig. 40, be fixed between two cisterns, so



as to be capable of revolving round in collars at F and G, the time the water takes to sink a given distance from *f* to F in the upper cist-

tern is found to be the same, whether the tube occupy the position shown in the figure or the horizontal position shown by the dotted line *F b c d e G*. This shows that the resistances due to friction and to bends are independent of the pressure. If the tube were straight, the discharge would depend on the length, diameter and difference of level between *f* and *G*, and may be determined from the mean velocity of discharge, found from TABLE VIII. or equation (79). Here, however, it is necessary to take into consideration the loss sustained at the bends and curves, and our illustration shows that it is unaffected by the pressure.

The experiments of Bossut, Du Buât, and others, show that the loss of head from bends and curves—like that from friction—increases as the square of the velocity; but when the curves have large radii, and the bends are very obtuse, the loss is very small. With a head of nearly 8 feet, Venturi's twenty-third experiment, when reduced, gives—for a short straight tube 15 inches long, and $1\frac{1}{4}$ inch in diameter, having the junction of the form of the contracted vein very nearly .873 for the coefficient of discharge. When of the same length and diameter, but bent as in Diagram

I., Fig. 40, the coefficient is reduced to .785; and when bent at a right angle as at H, Fig. 40, the coefficient is further reduced to .560. In these respective cases we have therefore *

$$1. \quad v = .873 \sqrt{2gh}, \text{ and } h = 1.312 \times \frac{v^2}{2g};$$

$$2. \quad v = .785 \sqrt{2gh}, \text{ and } h = 1.623 \times \frac{v^2}{2g};$$

$$3. \quad v = .560 \sqrt{2gh}, \text{ and } h = 3.188 \times \frac{v^2}{2g};$$


showing that the loss of head in the tube H, Fig. 40, from the bend, is $1.876 \times \frac{v^2}{2g}$, or nearly double the theoretical head due to the velocity in the tube. The loss of head by the circular bend is only $.311 \frac{v^2}{2g}$, or not quite one-sixth of the other.

Mr. Mallet's experiments with a syphon tube 6" \times 1½", about 3 feet long, suited for weir-crests and a straight tube of the same dimensions every way gives coefficients from .860 to .874 due to the bend.

Du Buât deduced, from about twenty-five experiments, that the head due to the resistance in any bent tube A B C D E F G H, diagram 1, Fig. 41, depends on the number of deflections between the entrance at A and the departure at H; that it increases at each deflection as the square of the sine of the deflected

* It is stated that the time necessary for the discharge of a given quantity of water through a straight pipe being 1, the time for an equal quantity through a curve of 90° would be 1.11, with a right angle 1.57; two right angles would increase the time to 2.464, and two curved junctions to only 1.23. *Vide* REPORT ON THE SUPPLY OF WATER TO THE METROPOLIS, P. 237, APPENDIX No. 3.

angle, $\angle B R$ for instance, and as the square of the velocity; and that if $\phi, \phi_1, \phi_2, \phi_3, \&c.$, be the number of degrees in the angles of deflection at $B, C, D, E, \&c.$,



then for measures in French inches the height h_b , due to the resistance from curves, is

$$(136.) \quad h_b = \frac{v^2(\sin.^2\phi + \sin.^2\phi_1 + \sin.^2\phi_2 + \sin.^2\phi_3 + \&c.)}{3000}$$

which for measures in English inches becomes

$$(137.) \quad h_b = \frac{v^2(\sin.^2\phi + \sin.^2\phi_1 + \sin.^2\phi_2 + \sin.^2\phi_3 + \&c.)}{3197}$$

and for measures in English feet,

$$(138.) \quad h_b = \frac{v^2(\sin.^2\phi + \sin.^2\phi_1 + \sin.^2\phi_2 + \sin.^2\phi_3 + \&c.)}{266.4}$$

or, as it may be more generally expressed for all measures,

$$(139.) \quad h_b = (\sin.^2\phi + \sin.^2\phi_1 + \sin.^2\phi_2 + \sin.^2\phi_3 + \&c.) \times \frac{v^2}{8.27g}, \text{ in which } \frac{v^2}{8.27g} = \frac{v^2}{266.4} = .00375 v^2 \text{ in feet.}$$

The angle of deflection, in the experiments from which equation (136) is derived, did not exceed 36° . It has already been shown that the loss of head from the circular bend in diagram I., Fig. 40, where the

angle of deflection is nearly 45° , is $\cdot 311 \frac{v^2}{2g} = \cdot 00483 v^2$, but as the $\sin. 45^\circ = \cdot 707$; $\sin.^2 45^\circ = \cdot 5$ then $\cdot 00483 v^2 = \cdot 00966 v^2 \times \sin.^2 45^\circ$, or more than two and a half times as much as Du Buât's formula would give; and if it be compared with Rennie's experiments,* with a pipe 15 feet long, $\frac{1}{2}$ inch diameter, bent into 15 curves, each $3\frac{1}{4}$ inches radius, it would be found that the formula gives a loss of head not much more than one half of that which may be derived from the observed change, $\cdot 419$ to $\cdot 370$ cubic feet per minute in the discharge. See p. 298.

Dr. Young† first perceived the necessity of taking into consideration the length of the curve and the radius of curvature. In the twenty-five experiments made by Du Buât, he rejected ten in framing his formula, and the remaining fifteen agreed with it very closely. Dr. Young found

$$(140.) \quad h_b = \frac{\cdot 0000045 \phi \rho^{\frac{1}{2}} \times v^2}{\rho};$$

where ϕ is the number of degrees in the curve $N P$, diagram 2, Fig. 41, equal the angle $N O P$; $\rho = O N$ the radius of curvature of the axis; h_b the head due to the resistance of the curve, and v the velocity, all expressed in French inches. This formula reduced for measures in English inches is

$$(141.) \quad h_b = \frac{\cdot 0000044 \phi \rho^{\frac{1}{2}} \times v^2}{\rho};$$

and for measures in English feet,

* Philosophical Transactions for 1831, p. 438.

† Philosophical Transactions for 1808, pp. 173—175.

$$(142.) \quad h_b = \frac{.000006 \phi \rho^{\frac{1}{2}} \times v^3}{\rho}.$$

Equation (140) agrees to $\frac{1}{35}$ th of the whole with twenty of Du Buât's experiments, his own formula agreeing, so closely, with only fifteen of them. The resistance must evidently increase with the number of bends or curves; but when they come close upon, and are grafted into each other, as in diagram 1, Fig. 41, and in the tube F B C D E G, Fig. 40, the motion in one bend or curve immediately affects those in the adjacent bends or curves, and this law does not hold.

Neither Du Buât nor Young took any notice of the relation that must exist between the resistance and the ratio of the radius of curvature to the radius of the pipe. Weisbach does, and combining Du Buât's experiments with some of his own, found for circular tubes,

$$(143.) \quad h_b = \frac{\phi}{180} \times \left\{ .131 + 1.847 \left(\frac{d}{2\rho} \right)^{\frac{7}{2}} \right\} \times \frac{v}{2g};$$

and for quadrangular tubes,

$$(144.) \quad h_b = \frac{\phi}{180} \times \left\{ .124 + 3.104 \left(\frac{d}{2\rho} \right)^{\frac{7}{2}} \right\} \times \frac{v}{2g};$$

in which ϕ is equal the angle N O P = N I R, diagram 2, Fig. 41; d the mean diameter of the tube, and ρ the radius N O of the axis. When $\frac{d}{2\rho}$ exceeds .2, the value

of $.131 + 1.847 \left(\frac{d}{2\rho} \right)^{\frac{7}{2}}$ exceeds $.124 + 3.104 \left(\frac{d}{2\rho} \right)^{\frac{7}{2}}$,

and the resistance due to the quadrangular tube exceeds that due to the circular one. The author arranged and calculated the following table of the

numerical values of these two expressions for the more easy application of equations (143) and (144).

This table will be found of considerable use in calculating the values of equations (143) and (144), as the second and fifth columns contain the values of $\cdot 181 + 1\cdot 847 \left(\frac{d}{2\rho} \right)^{\frac{7}{2}}$, and the third and sixth columns the values of $\cdot 124 + 3\cdot 104 \left(\frac{d}{2\rho} \right)^{\frac{7}{2}}$, corresponding to different values of $\frac{d}{2\rho}$; and it is carried to twice the extent of those given by Weisbach.

TABLE OF THE VALUES OF THE EXPRESSIONS.

$$\cdot 181 + 1\cdot 847 \left(\frac{d}{2\rho} \right)^{\frac{7}{2}} \text{ and } \cdot 124 + 3\cdot 104 \left(\frac{d}{2\rho} \right)^{\frac{7}{2}}.$$

$\frac{d}{2\rho}$.	Circular tubes.	Quadrangular tubes.	$\frac{d}{2\rho}$.	Circular tubes.	Quadrangular tubes.
·1	·181	·124	·6	·440	·648
·15	·183	·128	·65	·540	·811
·2	·188	·135	·7	·661	1·015
·25	·145	·148	·75	·806	1·258
·3	·158	·170	·8	·977	1·545
·35	·178	·203	·85	1·177	1·881
·4	·206	·250	·9	1·408	2·271
·45	·244	·314	·95	1·674	2·718
·5*	·294	·398	1·00	1·978	3·228

For bent tubes, diagrams 3, 4, and 5, Fig. 41, the loss of head is considerably greater than for rounded tubes. If, as before, the angle NIR be put equal to

* The values corresponding to $\frac{d}{2\rho} = \cdot 55$ are ·350 and ·507 for circular and quadrangular tubes.

ϕ , IR being at right angles to IO the line bisecting the angle or bend, then, by decomposing the motion, the head $\frac{v^2}{2g}$ becomes $\frac{v^2}{2g} \times \cos.^2 \phi$ from the change of direction; and therefore a loss of head

$$(145.) h_b = (1 - \cos.^2 2\phi) \frac{v^2}{2g} = \sin.^2 2\phi \frac{v^2}{2g}$$

must take place. When the angle is a right angle, as in diagram 4, $\cos. 2\phi = 0$, and $h_b = \frac{v^2}{2g}$; that is to say, the loss of head is exactly equal to the theoretical head. When the angle or bend is acute, as in diagram 5, the loss of head is $(1 + \cos.^2 2\phi) \frac{v^2}{2g}$, for then $\cos. 2\phi$ becomes negative. Weisbach does not find the loss of head in a right angular bend greater than $.984 \frac{v^2}{2g}$; while Venturi's twenty-third experiment, made with extreme care, p. 293, shows the loss to be $1.876 \frac{v^2}{2g}$. When the pipes are long, however, the value of $\frac{v^2}{2g}$ is in general small, and this correction does not affect the final results in any material degree.

Rennie's experiments,* with a pipe 15 feet long, $\frac{1}{2}$ inch in diameter, and with 4 feet head, give the discharge per second

- | | |
|--------------------------------------|-------------|
| | Cubic Feet. |
| 1. Straight, see table, p. 146 . . . | .00699 |
| 2. Fifteen semicircular bends . . . | .00617 |

* Philosophical Transactions for 1831, p. 438.

3. One bend, a right angle $8\frac{1}{2}$ inches

from the end of the pipe . . . 00556

4, Twenty-four right angles . . . 00253

From these data may be found consecutively, the theoretical discharge being 021885 cubic feet per second, and the theoretical head $H = \frac{v^2}{2g}$, that

$$1. \quad v = .319 \sqrt{2gH}, \text{ and therefore } H = 9.82 \times \frac{v^2}{2g};$$

$$2. \quad v = .282 \sqrt{2gH}, \quad ,, \quad ,, \quad H = 12.58 \times \frac{v^2}{2g};$$

$$3. \quad v = .254 \sqrt{2gH}, \text{ and therefore } H = 15.50 \times \frac{v^2}{2g};$$


$$4. \quad v = .116 \sqrt{2gH}, \quad ,, \quad ,, \quad H = 74.84 \times \frac{v^2}{2g}.$$

The loss of head, therefore, by the introduction of 15 semicircular bends, is $2.76 \frac{v^2}{2g}$; by the introduction of one right angle, $5.68 \frac{v^2}{2g}$; and by the introduction of 24 right angles, $64.52 \frac{v^2}{2g}$, or about 12 times the loss due to one right angle. This shows that the resistance does not increase as the number of bends, as was before remarked, p. 275, when they are close to each other. The loss of head from one right angle, $5.68 \frac{v^2}{2g}$, is more than double the loss from 15 semicircular bends, or $2.76 \frac{v^2}{2g}$. The loss of head for a right angular bend, determined from Venturi's experiment, is $1.876 \frac{v^2}{2g}$; formula (145) makes it $\frac{v^2}{2g}$; and

Weisbach's empirical formula, $(.9457 \sin. \phi + 2.047 \sin.^4 \phi) \frac{v^2}{2g}$, makes it only $.984 \frac{v^2}{2g}$. The formulæ now in use give, therefore, results considerably under the truth. It appears therefore, that the amount of the *velocity* of the water moving directly towards the bend must be taken into consideration, and also the loss of mechanical effect from contraction, and eddies at it, as well as the loss arising from the mere change of direction.

BRANCH PIPES.

When a pipe is joined to another, the quantity of water flowing below the junction B, diagram 1, Fig. 42, must be equal to the sum of the quantities flowing in



the upper branches in the case of supply; and when the branch pipe draws off a portion of the water, as in diagram 2, the quantity flowing above the junction must be equal to the quantities flowing in the lower branches. Both cases differ only in the motion being *from* or *to* the branches, which, in pipes, are generally grafted at right angles to the main, for practical convenience, as shown at *b b*, and then carried on in any given direction. The loss of head arising from change

of direction, equation (145), is $\sin.^2 2\phi \frac{v^2}{2g}$, in which $2\phi = \text{angle } ABO$; but as in general 2ϕ is a right angle for branches to mains, this source of loss becomes then simply $\frac{v^2}{2g}$. In addition to this, a loss of head is sustained at the junction, from a certain amount of force required to unite or separate the water in the new channel. In the case of drawing off, diagram 2, this loss was estimated by D'Aubisson, from experiments by G3nieys, to be about twice the theoretical head due to the velocity in the branch, or $\frac{2v^2}{2g}$, so that the whole loss of head arising from the junction is $\frac{v^2}{2g} + \frac{2v^2}{2g} = \frac{3v^2}{2g}$, or three times the theoretical head due to the velocity. In the case of supply, the loss is probably nearly the same. The actual loss is, however, very uncertain; but, as was before observed when discussing the loss of head occasioned by bends, two or three times $\frac{v^2}{2g}$ is in general so comparatively small, that its omission does not materially affect the final results. A loss also arises from contraction, &c. See pp. 171, 172.

The calculations for mains and branches become often very troublesome, but they may always be simplified by rejecting at first any minor corrections for contraction at the orifice of entry, bends, junctions, or curves. If, in diagram 2, Fig. 42, h be put for the head at B, or height of the surface of the reservoir over it; h_a for the fall from B to A; h_d for the fall

from B to D; l equal the length of pipe from B to the reservoir; l_a equal the length B A; l_d equal the length B D; r equal the mean radius of the pipe B C; r_a the mean radius of the pipe B A; r_d the mean radius of B D; v the mean velocity in B C; v_a the velocity in B A; and v_d the velocity in B D, we then find, by means of equation (73), the fall from the reservoir to A equal to

$$(146.) \quad h + h_a = \left(c_r + c_t \times \frac{l}{r} \right) \frac{v^2}{2g} + \left(1 + c_t \times \frac{l_a}{r_a} \right) \frac{v_a^2}{2g};$$

the fall from the reservoir to D equal to

$$(147.) \quad h + h_d = \left(c_r + c_t \times \frac{l}{r} \right) \frac{v^2}{2g} + \left(1 + c_t \times \frac{l_d}{r_d} \right) \frac{v_d^2}{2g};$$

and, as the quantity of water passing from C to B is equal to the sum of the quantities passing from B to A and from B to D,

$$(148.) \quad v r^2 = v_a r_a^2 + v_d r_d^2.$$

By means of these three equations any three of the quantities h , h_a , h_d , r , r_a , r_d , b , b_a , b_d , can be found, the others being given. Equations (146) and (147) may be simplified by neglecting c_r , the coefficient due to the orifice of entry from the reservoir, and 1, the coefficient of velocity. They will then become

$$(148A.) \quad h + h_a = c_t \times \left(\frac{l}{r} \times \frac{v^2}{2g} + \frac{l_a}{r_a} \times \frac{v_a^2}{2g} \right),$$

and

$$(149.) \quad h + h_d = c_t \times \left(\frac{l}{r} \times \frac{v^2}{2g} + \frac{l_d}{r_d} \times \frac{v_d^2}{2g} \right).$$

The mean value of c_t for a velocity of 4 feet per second is .005741, and of $\frac{c_t}{2g}$, .0000891. The values for any other velocities may be had from the table of

coefficients of friction given at p. 229. When l , h , and r are given, the velocity v can be had from the equation, $v = \left(\frac{2g}{c_f} \times \frac{r h}{l} \right)$, or more immediately from TABLE VIII.

GENERAL EQUATION FOR THE MEAN VELOCITY.

A general equation for finding the whole head H , and the mean velocity v , in any channel; and to extend equations (73) and (74) so as to comprehend the corrections due to bends, curves, &c., can now be given. Designating, as before, the height due to the resistance at the orifice of entry by

- h_r , and the corresponding coefficient by c_r ;
- h_f , the head due to friction, and c_f the coefficient of friction;
- h_b , the head due to bends, and c_b the coefficient of bends;
- h_c , the head due to curves, and c_c the coefficient of curves;
- h_e , the head due to erosion, and c_e the coefficient of erosion;
- h_x , the head due to other resistances, and c_x their mean coefficient

then evidently

$$(150.) H = h_r + h_f + h_b + h_c + h_e + h_x + \frac{v^2}{2g};$$

that is to say, by substituting for h_r , h_f , &c., their values as previously found,

$$H = (1 + c_r) \frac{v^2}{2g} + c_f \frac{l}{r} \times \frac{v^2}{2g} + c_b \times \frac{v^2}{2g} \\ + c_c \times \frac{v^2}{2g} + c_e \times \frac{v^2}{2g} + c_x \times \frac{v^2}{2g};$$

or, more briefly,

$$(151.) \quad H = \left(1 + c_r + c_t \times \frac{l}{r} + c_b + c_o + c_e + c_x \right) \frac{v^2}{2g};$$

from which may be found

$$(152.) \quad v = \left\{ \frac{2gH}{1 + c_r + c_t \times \frac{l}{r} + c_b + c_o + c_e + c_x} \right\}^{\frac{1}{2}}.$$

It is to be observed here, that for very long uniform channels, the value of the mean velocity will be found in general equal to $\left\{ \frac{2grH}{c_t l} \right\}^{\frac{1}{2}}$, as the other resistances and the head due to the velocity are all trifling compared with the friction, and may be rejected without error; but, as before stated, it is advisable in practice, when determining the diameter of pipes, p. 246, to increase the value of c_t , table, p. 229, or to increase the diameter found from the formula by one-sixth, which will increase the discharging power by one-half. See TABLE XIII.

In equations (74) and (151), the coefficient of friction c_t depends on the velocity v , and its value can be found from an approximate value of that velocity from the small table at p. 229. If, however, both powers of the velocity be used, as in equation (83), then, when H is the whole head, and h the head from the surface to the orifice of entry

$$(a v + b v^2) \frac{l}{r} + (1 + c_r) \frac{v^2}{2g} + h = H,$$

a quadratic equation from which is found

$$v = \left\{ \frac{(H-h) 2gr}{(1+c_r)r+2gb l} + \left(\frac{gal}{(1+c_r)r+2gb l} \right)^2 \right\}^{\frac{1}{2}} - \frac{gal}{(1+c_r)r+2gb l}$$

for a more general value of the velocity than that given in equation (74). If now c_s be put equal to $c_r + c_b + c_o + c_e + c_x$, in equation (151) we shall find

$$(152a.) \quad v = \left\{ \frac{(\pi - h) 2gr}{(1 + c_s)r + 2gb l} + \left(\frac{gal}{(1 + c_s)r + 2gb l} \right)^2 \right\}^{\frac{1}{2}} - \frac{gal}{(1 + c_s)r + 2gb l}$$

for a more general expression of equation (152), when the simple power of the velocity, as in equation (83), is taken into consideration. For measures in English feet, $a = .0000228$ and $b = .0000854$, may be taken, which correspond to those of Eytelwein, in equation (97). The value of a is the same in English as in French measures; but the value of b in equation (83), for measures in metres, must be divided by 3.2809 to find its corresponding value for measures in English

feet. In considering the head $\frac{v^2}{2g} c_r$, due to contraction at the orifice of entry as not implicitly comprised in the primary values of a and b , equation (83), Eytelwein is certainly more correct than D'Aubuisson, *Traité d'Hydraulique*, pp. 223 et 224, as this head varies with the nature of the junction, and should be considered in connection with the head due to the velocity, or separately. It can never be correctly considered as a portion of the head due to friction. In all Du Buat's experiments, this head was considered as a portion of that due to the velocity, and the whole head, $(1 + c_r) \frac{v^2}{2g}$, deducted to find the head due to friction and thence the hydraulic inclination. The following values of a and b were those taken in the equations referred to.

VALUES OF a AND b FOR MEASURES IN ENGLISH FEET.

	a .	b .
Equation (88.)	·0000445	·0000944
„ (90.)	·0000173	·0001061
„ (94.)	·0000243	·0001114
„ (98.)	·0000223	·0000854
„ (109.)	·0000189	·0001044
„ (111.)	·0000241	·0001114
„ (114.)	·0000035	·0001150
Mean values for all straight channels, pipes, or rivers .	·0000221	·0001040

These mean values of a and b give the equation

$$r s = \cdot 0001040 v + \cdot 0000221 v,$$

from which we find

$$9615 r s = v + \cdot 21 v,$$

and thence

$$(153.) v = (9615 r s + \cdot 011)^{\frac{1}{2}} - \cdot 105 = 98 \sqrt{r s} - \cdot 1,$$


very nearly, suited to velocities of about 2 feet, p. 231.

HYDROSTATIC AND HYDRAULIC PRESSURE.—PIEZOMETER.

When water is at rest in any vessel or channel, the pressure on a unit of surface is proportionate to the head at its centre,* measured to the surface, and is expressed in lbs. for measures in feet, by $62\cdot5 H s$, in

* This is only correct when the surface is small in depth compared with the head. If H be the depth of a rectangular surface in feet, and also the head of water measured to the lower horizontal edge, then the pressure in lbs. is expressed by $31\frac{1}{2} H^2$; and the centre of pressure is at $\frac{2}{3}$ rds of the depth.

which H is the head, and s the surface exposed to the pressure, both in feet measures. This is the *hydrostatic pressure*. In the pipe $A B C D F E$, Fig. 43, the pressure at the points B, C, D, F , and E , on the sides of the tube will be respectively as the heads $B b, C c, D d, F f$, and $E e$, if all motion in the tube be prevented by



stopping the discharging orifice at E . In this case the pressure is a maximum and hydrostatic; but if the discharging orifice at E be partially or entirely open, a portion of each pressure at B, C, D, F , &c., is absorbed in overcoming the different resistances of friction, bends, &c., between it and the orifice of entry at A , and also by the velocity in the tube, and the difference is the *hydraulic pressure*.

Bernoulli first showed that *the head due to the pressure at any point, in any tube, is equal to the effective head at that point, minus the head due to the velocity*. When the resistances in a tube vanish, the effective head becomes the hydrostatic head, and by representing the former by h_{ef} and, adopting the notation in equation (150),

$$h_{ef} = H - (h_r + h_f + h_o + \&c.),$$

x 2

and consequently the head due to the hydraulic pressure equal

$$(153A.) \quad h_p = h_a - \frac{v^2}{2g} = H - (h_r + h_t + h_b + \&c.) - \frac{v^2}{2g}.$$

If small tubes be inserted, as shown in Fig. 43, at the points B, C, D, and F, the heights B b^1 , C c^1 , D d^1 , F f^1 , to which the water rises, will be represented by the corresponding values of h_p in the preceding equation; and the difference between the heights C c^1 , F f^1 , at C and F, for instance, added to the fall from C to F will, evidently, express the head due to all the resistances between C and F. When $H = E e$, and the orifice at E is open, from equation (150), $H = h_r + h_t + h_b + h_o + \&c. + \frac{v}{2g}$, and therefore $h_p = 0$, that is, the pressure at the discharging orifice is nothing.

The vertical tubes at B, C, D, F, when properly graduated, are termed *piézometers* or *pressure gauges*; they not only show the actual pressure at the points where placed, but also the difference between any two; D d^1 - B b^1 , for instance, added to the difference of head between D and B, or D d^2 will give D d^1 - B b^1 + D d^2 for the head or pressure due to the resistances between B and D. This instrument affords, perhaps, the very best means of determining the loss of head due to bends, curves, diaphragms, &c. The loss of head due to friction, bend, diaphragm, &c., between K and L, Fig. 43, is equal to K k - L l + K v . If M be the same distance from L as K is, L l - M m will be the height due to the friction (L and M being on the same level); therefore K k - L l + K v - L l + M m

$= \kappa k + \kappa v + m m - 2 l l$ is the head due to the diaphragm and bend both together. If the diaphragm be absent, the head due to the bend is found, and if the bend be absent, the head due to the diaphragm is had in like manner.

When the discharging orifice, as at *E*, is quite open, we have seen that the pressure there is zero; but when, as at *G*, it is only partly open, this is no longer the case, and the hydraulic pressure increases from zero to hydrostatic pressure, as the orifice decreases from the full section to one indefinitely small compared with it. A piëzometer, placed a short distance inside *G*, will give this pressure; and the difference between it and the whole head will be the head due to the resistances and velocity in the pipe: from which, and also the length and diameter, the discharge may be calculated as before shown. Again, by means of the head $m m^1$, and that due to the velocity of approach, the discharge may be found through the diaphragm *G*; see equation (45) and the remarks following it. This result must be equal to the other; and in this way the formulæ may be tested anew or corrected by the observed results.

The velocity of discharge of the tube *A C D E*, may be calculated by means of any piëzometric height $c c^1$; for by putting the whole fall from c^1 to *E* equal

to H_c^1 , then, disregarding bends, $v = \left\{ \frac{2 g r H_c^1}{c_f l_o^5} \right\}^{\frac{1}{2}}$, in

which $l_o^1 = c E$. This is evident from equation (152), as it is supposed that no part of the head is absorbed in generating velocity, or in overcoming the resistance


of bends. If the bend at D were taken into considera-

$$\text{tion, then } v = \left\{ \frac{2 g H_o^1}{c_t \times \frac{l_o^1}{r} + c_b} \right\}^{\frac{1}{2}}.$$

SYPHONS.

If one end of an open tube be placed in water and the air withdrawn, the water will rise and fill the tube to a height corresponding to the atmospheric pressure at the time, but in practice it is advisable to reduce this to about 26 feet. When the tube is bent, as *o c r* in diagrams 1, 2, 3 and 4, Fig. 43a, water can be raised to this height over the level of that on the side *c o* and discharged at any lower level on the side *c r*. The available head or pressure *f* is the difference of level between the upper and lower water when the latter rises over the end *r*; and when below *r*, $h_1 = h + f$, or the difference of level between the upper water and the lower end of the bent tube or syphon is the head. It is advisable to have the lower end *r* immersed, and hence *c r* longer than *c o*, but this is not essential; as long as there is an effective head the arms may be of the same or unequal lengths, and the water will flow off at *r*, from the syphon *o c r*, as well as at *r* from the syphon *o c R*, but with the difference of velocity due to the heads at *r* and *R*. The lengths of the arms *c o*, *c r*, are however made to suit the circumstances of each case. In diagram 1 the upper water is at the top of the syphon; in 2 below it; in 3 above it. In diagram 4 the arms of the syphon are of the same length and the orifice of entry

o and of discharge R at the same level. The water in both vessels finally settles at a common level $T T'$, and fills the syphon all round in which it is maintained at



rest by the atmospheric pressure on the surface of the common level $T T'$.

In calculating the discharge the circumstances to be considered are: The available or effective head f ; the form of the orifices of entry at o and of discharge at R; the length; the hydraulic mean depth of the section,—rectangular or circular; and the bend at c with any smaller bends adjoining o and R to suit the form o c R of the weir. If, as like in formula (68) to (70L), a be put for the area of the section, then

$$(154.) \quad D = \begin{cases} c_a a \sqrt{2 g f}, \text{ or} \\ 481.5 c_a a \sqrt{f}, \text{ feet measures in one} \\ \text{minute,} \end{cases}$$

in which the value of c_a depends on the preceding con-

siderations. At pp. 146 and 199 the values of c_d for velocities of about eighteen inches, and twenty feet, are given, and by interpolation intermediate values for intermediate or even higher velocities can be determined; the effects of bends are considered pp. 291 to 300, and taking both together c_d can be found suited to the form and dimensions of the given syphon.

If the length of the syphon—which is generally rectangular for engineering works—be 50 times the hydraulic mean depth, that is equivalent to $12\frac{1}{2}$ mean diameters, then the table p. 199 gives .759 for the value of c_d in a straight tube. Taking the coefficient due to the bend at about .867, the value of c_d due to the length of this syphon and to the bend at the crest of the weir, is $.759 \times .867$ or .658. Hence eqn. (154) becomes in round numbers

$$(154A.) \left\{ \begin{array}{l} D = 317 a \sqrt{f} \text{ for a length of 50 mean} \\ \text{radii; also may be found} \\ D = 298 a \sqrt{f} \text{ for a length of 100 mean} \\ \text{radii; and} \\ D = 268 a \sqrt{f} \text{ for a length of 200 mean} \\ \text{radii,} \end{array} \right.$$

for the discharge in cubic feet per minute. If the syphon were longer in proportion to the hydraulic mean depth, these results would become still less, and more if the orifice of entry were rounded.

IN WEALE'S QUARTERLY PAPERS OF ENGINEERING, vol. vi., p. 51, Mr. Mallet, in a letter dated 10th Aug., 1843,* addressed to Major-General Sir John F. Bur-

* At this time Sir John evidently appears to have lost faith in long solid weirs as a panacea for the Shannon drainage, and in the self-esteem of the Shannon Commissioners on this hobby of theirs.

goyne, R.E., then Chairman of the Board of Public Works in Dublin, gives the result of experiments on a rectangular syphon tube with a section of six inches wide by one-and-a-half inch deep, or area of nine square inches. The length of the syphon is not given, but from the drawings given we infer it to be 30 inches, and of the general form given in diagrams 1, 2 and 3, Fig. 43a, but "slightly bell-mouthed" at the "entrance and discharging terminations." A straight tube of the same length and form was made, and the time of discharging 24 cubic feet of water from each with the same heads was as follows:—

Heads in inches.	Time in seconds for syphon.	Time in seconds for straight tube.
10½	78	67
13½	67½	59

The head of 10½ inches gives by calculation from these experiments, .860 for the coefficient of discharge due to the bend over the crest; and the head of 13½ inches, a coefficient of .874; which shows that the resistance from the bend was less for a greater velocity. Mr. Mallet also found that with an effective head of 8 inches, 24 cubic feet were discharged in 89 seconds. This gives, by calculation, the coefficient .658 for all the resistances due to the orifice of entry friction in the tube and bends. Taking the coefficient of the bend here at .850 as due to a lesser head, this gives .774 for that due to friction and the orifice of entry. Another experiment, with a head of 11½ inches, gave a discharge of 24 cubic feet in 78 seconds. This is

equivalent to a coefficient of $\cdot 636$ for all resistances, and dividing by $\cdot 860$ for the bend, $\cdot 740$ is found for the friction and orifice of entry. Again

Experiments, discharge of 24 cubic feet.		Calculated results.		
Heads in inches.	Time in seconds.	General coefficient.	Coefficient for bend.	Coefficient for friction and orifice.
12½	75½	·632	·860	·738
13	73	·631	·860	·734
14½	67½	·640	·874	·732

The effective head here to calculate the results from, exceeds by $\frac{3}{4}$ inch or half the depth of the tube, that taken by Mr. Mallet, as in the effective head taken by him this is omitted, but the 8-inch head agrees with that he has taken, the error being eliminated by taking a difference. Taking the mean general coefficient of these results at $\cdot 636$, the discharge is expressed by the equation

$$(154B.) D = 481.5 \times \cdot 636 a \sqrt{f} = 306 a \sqrt{f},$$

the discharge in cubic feet per minute for feet measures. This is less than that before given by our eqn. (154A) by about $9\frac{1}{2}$ per cent.

The application of the syphon for the discharge of surplus waters is of great value, and the head can be increased to any extent not exceeding the difference of level between the upper and lower water. It is not the object here to enter into the question of construction, or the means of withdrawing the air or putting the apparatus to work, but a comparison between its advantages, lifting-sluices, and *Les Barrages Hausses Mobiles* has been already entered into at p. 291.

SECTION XII.

RAIN-FALL.—CATCHMENT BASINS.—DISCHARGES INTO CHANNELS.—DISCHARGE FROM SEWERS.—LOSS FROM EVAPORATION, ETC.

A catchment basin is a district which drains itself into a river and its tributaries. It is bounded generally by the summits of the neighbouring hills, ridges, or high lands forming the water-shed boundary; and may vary in extent from a few square miles to many thousands; that of the Shannon is 4,544 square miles. The average quantity of water which discharges itself into a river will, *ceteris paribus*, depend on the extent of its catchment basin, and the whole quantity of rain discharged on the area of the catchment basin, including lakes and rivers.

THE QUANTITY OF RAIN which falls annually varies with the district and the year; and it also varies at different parts of the same district. The average quantity in Ireland may be taken at about 34 inches deep, that which falls in Dublin being 27 inches, in Armagh, average of 14 years, 35 inches; in Killaloe, average of 17 years, 43 inches; in Galway, average of 11 years, 46 inches; and that in Cork 41 inches nearly. The average yearly fall in Dublin for seven years, ending with 1849, was 26·407 inches; and the maximum fall in any month took place in April, 1846, being 5·082 inches. “The average fall in inches per month for seven years, ending with 1849, was as follows:—October, 3·060; August, 2·936; January,

TABLE of some Catchment Basins in Ireland.

Names of Drainage districts, or Rivers.	Counties or Towns.	Area of Catchment in acres.	Area of Catchment in square miles.
Avonmore	Wicklow and Wexford	123,000	200
Avoca River	Wicklow	179,840	281
Ballinasloe	Mayo	70,000	110
Barrow, Nore, and Suir	Waterford	2,176,000	3400
Blackwater and Boyne	Meath, &c.	695,040	1086
Blackwater	Waterford, Youghal	780,160	1219
Blackwater	Armagh	336,640	526
Blackwater	Meath and Kildare	50,000	78.1
Bandon River	Cork	145,920	228
Bann, Upper and Lower, and the Main	Down, Antrim	810,240	1266
Boyne	Meath, Westmeath, Kildare, and King's	804,139	478.2
Brusna (Ferbane)	King's	389,120	608
Ballyteigue	Wexford	26,752	41.8
Ballinamore and Ballyconnel	Cavan, Fermanagh, Leitrim, and Roscommon	101,455	158.5
Breeogue	Sligo	180,408	282
Ballinhaslig	Cork	23,500	36.7
Cappagh	Galway	34,856	54.4
Coolaney	Sligo	90,744	141.8
Camoge	Limerick	61,184	95.6
Dunmore	Galway, Mayo, and Roscom- mon	96,161	150.2
Dodder	Dublin	35,200	55
Deel	Meath and Westmeath	64,000	100
Dee	Louth and Meath	78,000	121.9
Erne	Belturbet, Enniskillen	1,014,400	1585
Foyle	Londonderry	944,640	1476
Fergus	Clare and Galway	134,400	210
Fane	Louth	87,400	136.6
Glyde	Louth, Meath, Monaghan, and Cavan	176,813	276.3
Inny	Meath, Westmeath, Long- ford, and Cavan	231,116	361.1
Kilbeggan	Westmeath and King's	83,030	137.5
Liffey and Tolka	Dublin, &c.	323,320	513.0
Lee	Cork	470,400	735
Lough Gara and Mantua	Roscommon, Mayo, and Sligo	128,000	200
Lougha Oughter and Gowna and River Erne	Cavan, Leitrim, and Longford	260,480	407
Lough Neagh and Bann	Londonderry, Antrim, Down, and Armagh	1,411,320	2205.2
Lough Mask and River Robe	Mayo and Galway	225,000	351.5
Loughs Corrib, Mask, and Carra	Galway and Mayo	780,000	1218.7
Longford	Longford	72,320	113.0
Moy	Mayo, Ballina	661,120	1033
Main	Antrim	37,600	90
Monivea	Galway	54,000	84.4
Maghera	Down	19,000	29.7
Nobber	Meath	40,000	62.3
Quoile	Down	57,000	89.1
Rinn and Black River	Leitrim and Longford	74,000	115.6
Strokestown	Roscommon	70,000	109.4
Shannon above Killaloe	Different counties, towns of Athlone, Limerick	2,908,160	4544
Slaney	Wexford	521,600	815

TABLE showing Summer Discharges of some English Rivers, as collected from various authorities, re-arranged, showing to some extent the effect of Springs in supplying Channels in different places.

NAMES OF RIVERS.	Height above sea in feet.		Catchment in square miles.	Discharge in cubic feet per minute.	Discharge per square mile in cubic feet per minute.	Representing inches of rainfall per annum.	Total average rainfall in inches per annum.
	Valley.	Hill.					
Gade, at Hunton Bridge, chalk .	150 to 500		69.5	2,500	36.2	8.19	...
Lea, at Lea Bridge, chalk. (Rennie, April, 1796) .	30 to 600		570.0	8,880	15.58	3.53	...
Loddon (Feb. 1850), green sand . .	110 to 700		221.8	3,000	13.53	3.01	25.4
Medway, driest seasons (Rennie, 1787), clay		481.5	2,209	4.59	1.04	...
Medway, ordinary summer run (Rennie, 1787), clay		481.5	2,520	5.23	2.19	...
Mimram, at Panshanger, chalk .	200 to 500		29.2	1,500	51.4	11.58	26.6
Nene, at Peterborough, oolites, Oxford clay, and lias . . .	10 to 600		620.0	5,000	8.45	1.88	23.1
Plym, at Sheepstor, granite . . .	800 to 1,500		7.6	500	71.4	15.10	45.0
Severn, at Stonebench, silurian .	400 to 2,600		3,900	33,111	8.49	1.98	...
Thames, at Staines, chalk, green sand, Oxford clay, oolites, &c. . .	40 to 700		3,086	40,000	12.98	2.93	24.5
Trent, at its mouth, oolites and Oxford clay .	100 to 600		3,921
Verulam, at Bushey Hall, chalk .	150 to 500		120.8	1,800	14.9	3.37	...
Wandle, below Carsehalton, chalk .	70 to 350		41.0	1,800	43.9	9.93	24.0

2·544 ; April, 2·503 ; November, 2·300 ; July, 2·116 ; June, 2·005 ; December, 1·938 ; September, 1·860 ; May, 1·814 ; March, 1·739 ; February, 1·534.”* A gauge at Londonderry, 1795 to 1801, gives 31 inches average ; one at Belfast, from 1836 to 1841, gives 35 inches ; at Mountjoy, Phoenix Park, 182 feet above low water, 1839 and 1840, there is an average of 33 inches ; and at the College of Surgeons, 52 feet over low water, the average is 30 inches for the same two years. Sir Robert Kane assumes that 36 inches is the average fall in Ireland, and that out of that depth 12 inches, or one-third, passes on to the sea, two-thirds being evaporated and taken up by plants. The quantity varies a good deal with the altitude of the district. In parts of Westmoreland it rises sometimes to 140 inches ; in London, an average of 20 years’ observations gives a fall of nearly 25 inches.

The tabular information has been obtained from Mr. Hughes’ book, from Rennie’s reports, and other sources. The effect of the geology and fissures in the chalk and mountain limestone formations on the springs of a catchment basin, and on the summer discharge, should be carefully noted as one of the elements entering into catchment basin statistics. Indeed, the maximum and minimum discharges from catchments are of as much importance to the engineer as the averages, and, for many purposes, more important. There was abundant opportunity of acquiring this information for all our Irish rivers, but we are not aware if it was turned to any useful account for science.

* Proceedings of the Royal Irish Academy, vol. v., p. 13.

Thorough-drainage increases the supply and discharge. *Every catchment basin has, however, its own peculiar data, and a knowledge of these is necessary before we can draw any correct conclusions for new waterworks in connection with it.* It may be remarked, however, that any conclusions drawn from experiments on the supply of tributaries, particularly in high districts, are wholly inapplicable to the main channel into which they flow. The flow into tributaries and mountain streams, or rivers, is always more rapid than into main channels and rivers in flat districts, and the supply from springs often forms a large portion of the water flowing in them. Heretofore, however, little dependence can be placed on gaugings unless the manner in which they were obtained was fully described.

Forty years' observation at Greenwich, Kent, at 155 feet above the level of the sea, gives the following results :—

Description of fall.	Winter.	Spring.	Summer.	Entire years.
	inches	inches	inches	inches
Mean annual fall	7·86	7·25	10·47	{ 25·48 25·58
Maximum fall ; being a mean of five of the wettest years during forty years	11·05	10·86	14·96	{ 34·00 36·87
Minimum fall ; being a mean of five of the driest years during forty years	5·22	4·05	6·80	{ 18·40 16·07

In this table Winter comprises November, December, January, and February ; Spring, the next four months ; and Summer, the months of July, August, September,

and October. The last column contains means of two classes of years: the first figures showing the ordinary years from January to December, and the second, under the first, years from November to October.* We see here that the mean maximum is fully double of the mean minimum, and about one-and-a-half times the mean annual fall, and therefore the necessity for calculating from the minimum fall for all water works in which it is an element, and from the maximum for sewerage works where it is not intended to pass off a portion on the surface or through other available channels.

In the district surrounding the Upper Bann reservoirs in the County Down, the average fall for thirteen years has been 46 inches at a level of 6 feet over the top water of Lough Island Reavy Reservoir; and Mr. John Smith, the engineer of the work, says that there is a loss of one-third in absorption and evaporation; but as the rainfall is greater on the higher ground than at the gauge, only one-half of the whole rainfall is probably available. Mr. Manning found for the Woodburne river, with a rainfall of 36 inches, a flow of 21·5 inches was produced, or about three-fifths, which was distributed as follows:—

Six months, November to May, 14·766 fall, and 14·851 flow;

Six months, May to November, 21·101 fall, and 7·357 flow.

In Keswick, the average fall is said to be $67\frac{1}{2}$ inches, and in Upminster, Essex, only $19\frac{1}{2}$ inches. Indeed, it

* See Mr. James Simpson in the Metropolitan Main Drainage Report, 1857, p. 115.

is requisite to obtain the fall from observation for any particular district, when it is necessary to apply the results to scientific purposes; and not the mean average fall alone, but also the maximums and minimums in a series of years and months in each year.

Mr. Symons gives (see *Builder* for 1860, p. 230) the following heavy falls of rain during 1859:—*Wandsworth*, June 12th, 2·17 inches in two hours; *Manchester*, August 7th, 1·849 inches in twenty-four hours; *Southampton*, September 26th, 2·05 inches in two-and-a-quarter hours; *Truro*, October 25th, during the day, 2·4 inches. The mean falls in the *South Western Counties*, 39·1 inches; in the *South Eastern Counties*, 30·2 inches; in the *West Midland Counties*, 28 inches; in the *Eastern Counties*, 25·4 inches; in the *North Midland Counties*, 24 inches; in the *North Western Counties*, 39 inches; in the *Northern Counties*, 55 inches; and the average of all England, 31·857 inches.

As an instance of extraordinary rain-fall, in connection with the sewage question, it is stated that 4 inches of rain fell in one hour in the Holborn and Finsbury sewers' district, on the 1st of August, 1846; at Highgate, 3·5 to 3·3 inches; and at Greenwich, 0·95 inches.* In India, the intensity of the rain-fall varies from half an inch to 5 inches in an hour.

In the upland districts about Manchester, Mr. Homersham† gives the result of observations at Fairfield, Bolton, Rocksdales, Marple, Comlis reservoir, Belmont, Chapel-en-le-Frith, and Whiteholme

* Metropolitan Main Drainage Report, p. 16.

† Report on the Supply of Water to Manchester.—WEALE.

reservoir, for four years. These give a maximum fall of 61·4 inches at Belmont Sharples in 1847, and a minimum of 24·8 at Whiteholme reservoir in 1844, the general average for the four years being 42·49 inches.

April is the driest month, and October, or about it, the wettest month, and the fall during different years varies sometimes as much as two to one in the same district.

The proportion between the quantity which falls, and that which passes from a catchment basin into its river, also varies very considerably. When the sides of a catchment basin are steep and staunch, and the water passes off rapidly into the adjacent river or tributaries, there is less loss by evaporation and percolation than when they are nearly flat. The soil, subsoil, and stratification have also considerable effect on the proportion. Reservoirs being generally constructed adjacent to steep side falls, give a much larger proportion of the quantity fallen than can be obtained from rivers in flatter districts ; besides, the quantity of rain which falls on the high summits, near reservoirs, almost always considerably exceeds the average fall. As 640 acres is equal to 1 square mile, and one acre is equal to 48,560 square feet, a fall of one inch of rain is equal to 3,680 cubic feet per acre, and to $3,680 \times 640 = 2,323,200$ cubic feet per square mile : the proportion of this fall, for each acre, or square mile of the catchment basin, which enters the river, must depend entirely on the district and local circumstances, the full or maximum quantity being retained on lakes. A stream delivering 53 cubic feet per minute constantly

for twelve months supplies an equivalent to 12 inches of rain-fall collected per square mile, and 1 inch of rain collected from each square mile of catchment gives a supply of 4.42 cubic feet per minute, and 6.9 cubic feet for each 1000 acres, flowing in both cases for twelve months.

FLOW EQUIVALENT TO A RAIN-FALL OF ONE INCH ON EACH SQUARE MILE, AND 1000 ACRES, FLOWING REGULARLY, WITHOUT LOSS, FOR ONE MONTH TO ONE YEAR.

For	Sq. mlie.	1000 acres.	For	Sq. mlie.	1000 acres.	For	Sq. mlie.	1000 acres.
One month .	53	82.8	Five months .	10.6	16.6	Nine months .	5.9	9.2
Two months .	26.5	41.4	Six months .	8.8	13.8	Ten months .	5.3	8.3
Three months .	17.7	27.6	Seven months .	7.6	11.8	Eleven months .	4.8	7.5
Four months .	13.2	20.7	Eight months .	6.8	10.3	Twelve months	4.4	6.9

It is too often taken for granted that the discharge from a catchment basin takes place, into the conveying channels, in nearly the same time that a given quantity of rain falls. Perhaps the largest registry on record in Great Britain is a fall of four inches in an hour. The maximum fall in any hour of any year seldom

QUANTITY PER ACRE FOR A GIVEN DEPTH OF FALL.

Fall in inches.	Cubic feet per acre.	Fall in inches.	Cubic feet per acre.	Fall in inches.	Cubic feet per acre.	Fall in inches.	Cubic feet per acre.
2	7260	$\frac{1}{2}$	1815	$\frac{1}{8}$	454	$\frac{1}{16}$	181
$1\frac{1}{2}$	6352	$\frac{3}{4}$	1361	$\frac{3}{8}$	403	$\frac{3}{16}$	121
$1\frac{1}{4}$	5445	$\frac{1}{4}$	907	$\frac{1}{4}$	363	$\frac{1}{8}$	91
$1\frac{1}{2}$	4537	$\frac{1}{2}$	726	$\frac{1}{2}$	302	$\frac{1}{4}$	73
1	3630	$\frac{3}{4}$	605	$\frac{3}{4}$	259	$\frac{3}{8}$	61
$\frac{3}{4}$	2723	$\frac{1}{4}$	519	$\frac{1}{8}$	227	$\frac{1}{16}$	52

exceeds half of this amount, and then perhaps only once in several years. The quantity which falls will not be discharged into the channels in the same time. The quantity discharged, and time, will depend a good deal on the season and district. The arterial channel receives the supply at different places and from different distances, and the water in passing into and from it does not encounter the same amount of resistance as if it all passed first into the upper end. Less sectional area is therefore necessary than if the whole discharge had to pass through the whole length of the channel and during the time of fall. The relation of the quantity of rain-fall to the portion which flows into the main channel, as well as the time which it takes to arrive at it, and the places of arrival, must be known before the proper size of a new channel can be determined, particularly sewers in urban districts. A pipe sufficient to discharge the water from 200 acres need not be 20 times the discharging power of one exactly suited to 10 acres of the same district, for the discharge from the outlying 190 acres will not arrive at the main in the same time as that from the adjacent 10 acres.

The following table of rain-fall, at Athlone, central in Ireland, was furnished to the Royal Irish Academy by General Sir H. D. Jones, and is printed in the *Proceedings*.* The average for four years gives 29 inches, and the effect on the Upper and Lower Sills of the Lock as affecting the rise and fall of the Shannon, affords valuable data, although not analysed. The rise and fall on the sills is the sum of the

* Vol. iv.

YEARS.	RAIN.				RIVER SHANNON.				WIND.											
	Quantity which fell each year.			Greatest fall in one successive Day and Night.	Number of days without rain.	Greatest number of successive Days.	Upper Sill.		Lower Sill.		Number of days in which the Wind was									
							Rise.	Fall.	Rise.	Fall.										
	Days.	Nights.	Total.	Inches.	Inches.	No.	No.	With Rain.	Without Rain.	Ft. in.	Ft. in.	Ft. in.	Ft. in.	North.	North E.	East.	South E.	South.	South W.	West.
1845	59.40	56.89	116.29	1.45	1.18	177	9	14	14 11	11 8½	24 4	18 9	60	20	24	47½	52½	31	41	89
1846	14.87	17.50	32.37	1.45	1.45	174	15	12	12 8½	15 0½	19 7	24 0	58	15	15	56	58	47	47	69
1847	12.85	10.65	23.50	0.89	0.89	183	11	8	17 2	14 8	22 11½	21 1½	51	21	22	49	67	39	49	67
1848	17.66	15.77	33.43	1.11	1.11	165	13	14	17 5½	19 0	24 0	27 4	45	27	16	43	67	48	57	63
Amount for four years .						709			62 3	60 5	90 10½	91 2½	214	83	77	195½	244½	165	104	288
Averages for one year .						177½			15 6½	15 1½	22 8½	22 9½	53½	20½	19½	48½	61½	41½	48½	72

monthly risings and fallings for each year, and must be divided by 12 to get the average monthly rise and fall. In 1845 the greatest rise was in January, 2 feet 9 inches at the upper sill, and 3 feet 11½ inches at the lower sill. In 1846 the greatest rise was 2 feet 5 inches in October, at the upper sill; and 5 feet 6½ inches on the lower sill, in August.

Upper Sill.			Lower Sill.		
Maximum rise in one month.			Maximum rise in one month.		
1845	. . .	2 ft. 9 in. January	. . .	3 ft. 11½ in. January.	
1846	. . .	2 ft. 5 in. October	. . .	5 ft. 6½ in. January.	
1847	. . .	3 ft. 1 in. November	. . .	4 ft. 6 in. May.	
1848	. . .	3 ft. 3 in. February	. . .	4 ft. 11 in. February.	

The sum of the risings and fallings for each month, taken as a mean of four years, is nearly the same at either sill. The general average of the rise and fall for the upper sill, is about 1 foot 3½ inches each way, and 1 foot 10¾ inches at the lower sill. These would give 2 feet 7 inches for the average difference of level in the Shannon above, and 3 feet 9½ inches for that in the Shannon below. In Lough Allen catchment of 146 square miles, the maximum rise was sometimes 6 inches in 24 hours, calculated at .568 inch of depth of rain, over the catchment area. Above Killaloe, the catchment is 3611 square miles, and the floods about once a year rose 6 inches in 24 hours, or .296 inch in depth of rain over the catchment. Once, in 1840, it is reported to have risen 12 inches, or .6 inch of rain over the catchment in one day. "The greatest observed flood in the Shannon occurred in January, 1853, when the dis-

charge of Killaloe marked 1,617,000 cubic feet per minute, or 699 cubic foot per acre of catchment. The large floods in the Armagh river, county Galway, yield from 8 to 10 cubic feet, and a summer flood in 1851 gave 13·02 cubic feet per minute for each acre.”*

MAXIMUM DISCHARGES OF THE SHANNON AND ERNE, AND A
TRIBUTARY OF THE LATTER, THE WOODFORD RIVER.

RIVERS IN IRELAND.	Extent of catchment, statute acres.	Square miles.	Maximum discharge per minute in cubic feet.	Cubic feet per minute from each acre.	Cubic feet per minute from each square mile.
Shannon at Killaloe, measured previous to the commencement of Shannon Works, about	3,000,000	4637·5	1,000,000	0·33	211
Lower Erne, measured during the very high floods of Jan. 1851, at Belleek	974,000	1521·9	657,511	0·67	429
Upper Erne, measured during the very high floods of Jan. 1851, at Balturbet	309,000	482·8	257,771	0·83	531
Woodford River, Counties of Leitrim and Cavan, measured during the very high floods of Jan. 1851, at Ballyconnell	90,000	140·6	101,035	1·12	717
Yellow River, or upper portion of the Woodford River, measured during the very high floods of Jan. 1851, Co. Leitrim	5,000	7·8	52,125	10·43	6675·

These results show how difficult it is to draw any inference from discharge and area of catchment alone, as the discharge, per minute per acre, must vary with the contour and elevation of the district in the same course; and with the climate, also, in different

* *Vide* Proceedings of the Institution of Civil Engineers, Ireland, vol. v. pp. 165 and 166, and Paper read by Thomas J. Mulvany, 11th February, 1851, vol. iv. p. 21.

countries. We have ourselves observed the maximum discharges to vary up to 6 cubic feet per minute per acre, the lesser maximums being due to broad flat districts, and the greater maximums to higher and steeper districts, near the sources. In the Proceedings of the Institution of Civil Engineers, Ireland, vol. iv., from which we have collected and arranged some of the foregoing information, it is stated, p. 96, that the ratio of the discharge to the rain-fall, on a catchment on the Glyde, of 79,433 acres, for three months, ending March 13th, 1851, was 1·49 to 1 up to January 13th; 1·39 to 1 up to February 13th; and 3·86 to 1 up to March 13th, making a general average of 1·59 to 1; the whole rain-fall for the three months being only 5·89 inches, while the discharge was 9·35 inches! We fancy there is a mistake here. The whole catchment of the Glyde is 176,813 acres, and there is no data to show the discharge previous to or after the rain-fall from which to calculate the difference due to it *per se* for the three months; *nor is the place or method of gauging stated.* The supply from springs and the actual discharge before and after rain-fall must be correctly gauged before the proportion passing into the main channel in a given time, can be properly estimated; the results just stated clearly contradict themselves. The following anomalous results from p. 47 of the same work are also worthy of note. In five different districts the discharge is gauged, or estimated, greater than the fall, as shown in the following table. It is not stated, however, if the depths passed off, estimated over the catchments, include the flow before the commencement

of the rain. If so the results are so far useless; and if they do not include it, there must be an error some-

READ 11TH MARCH, 1851.

District.	River.	Catchment in Acres.	DECEMBER 1850.		JANUARY 1851.	
			Total fall of rain by gauge in inches.	Total depth of discharge of catchment in inches.	Total fall of rain by Castlebar gauge in inches.	Total depth of discharge of catchment in inches.
Saleen . .	Saleen .	2,625	3.55	6.26	6.33	9.20
Lannagh . .	Castlebar.	20,640		5.46		8.55
Balla . .	Manulla .	33,500		5.46		8.18
Mask and Robe	Robe .	70,000	4.00	"	"	7.39
Dalla . . {	Dalla .	3,200		6.527		"
	Owenmore	32,000		5.705		"

where. Indeed, in the Robe we have evidence that not more than 58 per cent. passed from the catchment to the river, from Mr. Betagh's valuable paper, the results of which are arranged below. Also, in July, 1850, it is shown that in the Lannagh district only .53 inch in depth passed off the catchment from a fall of 1.83 inches, or about one-third of the depth. The method of determining this was unobjectionable. Where such discrepancies as above exhibited exist, it is important that the method of gauging, and the whole calculation, should be shown, in order that other engineers should be able to judge of their accuracy; otherwise the results should be rejected, no matter under whose authority they may be published. But during the operations of the Arterial Drainage

Commission in Ireland, from 1845 up to the year 1853, science was at a discount.

The following information has been collected and arranged by us from a paper by Mr. Betagh, in the Proceedings of the Institution of Civil Engineers, Ireland, vol. iv. In January 1851, 3·41 inches of rain fell in seven days, producing the maximum discharge of 85,836 cubic feet; while in December 1852, 3·17 inches, also falling in seven days, produced 115,656 for the maximum. At the beginning of the first fall

TABLES showing in detail, for the years 1851 and 1852, the Monthly Fall of Rain and the corresponding Discharge of the River Robe, at Ballinrobe, County Mayo; the catchment basin being 70,000 acres, or 110 square miles; the lower end 100 feet, the upper end 336 feet; and the average height of the surface about 180 feet above the level of the sea. The average fall of the river, not including the rapids, is from one to two feet per mile; the catchment is about 20 miles long, about one-tenth of the area bog or low marsh, and nine-tenths clayey and gravelly. The river is about 33 miles long.

RIVER ROBE OBSERVATIONS IN 1851.

MONTHS.	Rain-fall each month in inches.	Discharge each month of rain-fall in inches.	Discharge in cubic feet per minute, from a catch- ment of 70,000 acres, for each month.			Discharge in cubic feet per minute, per acre, for each month.		
			Maximum.	Minimum.	Average.	Maximum.	Minimum.	Average.
January .	9·2	7·4	85,836	20,133	43,373	1·158	·287	·620
February .	6·8	4·7	72,448	18,420	30,410	1·034	·263	·434
March . .	4·4	2·6	49,137	10,860	20,945	·703	·155	·300
April . .	3·4	2·5	24,200	5,760	14,355	·345	·082	·205
May . . .	1·0	0·8	5,820	4,125	5,001	·083	·059	·071
June . . .	3·8	0·8	7,040	1,114	4,230	·100	·016	·060
July . . .	3·8	0·5	4,920	1,500	2,558	·070	·021	·036
August . .	2·4	0·9	17,055	1,240	4,866	·243	·017	·069
September	1·9	0·5	4,746	1,200	2,854	·067	·017	·040
October . .	5·0	1·6	23,980	6,940	12,588	·342	·099	·179
November .	1·3	1·2	12,852	6,000	7,827	·183	·085	·111
December .	2·6	2·5	44,715	6,210	14,373	·638	·088	·205
Total .	45·6	27·	352,749	83,502	163,380	4·965	1·189	2·33

RIVER ROBE OBSERVATIONS IN 1852.

Continued from last page.

MONTHS.	Rain-fall, each month, in inches.	Discharge, each month, of rain-fall, in inches.	Discharge in cubic feet per minute, from a catchment of 70,000 acres, for each month.			Discharge in cubic feet per minute, per acre, for each month.		
			Maximum.	Minimum.	Average.	Maximum.	Minimum.	Average.
January	7·5	5·2	41,600	12,852	28,730	·594	·183	·410
February	4·8	4·3	56,400	8,190	25,296	·805	·117	·361
March	1·0	0·7	9,600	2,737	6,702	·137	·039	·095
April	1·1	0·5	3,931	1,468	2,477	·056	·020	·035
May	1·9	0·4	3,931	1,050	1,861	·056	·015	·028
June	6·6	1·2	22,764	1,400	6,547	·325	·020	·093
July	2·5	1·0	15,439	3,172	6,057	·220	·045	·087
August	4·5	0·6	3,856	2,236	3,070	·055	·032	·043
September	1·8	0·5	3,427	2,642	2,874	·043	·037	·041
October	3·9	1·0	32,040	1,114	5,932	·457	·016	·084
November	5·5	5·2	45,360	17,000	30,742	·648	·242	·439
December	12·0	9·5	115,656	23,232	54,846	1·657	·331	·783
Total	53·1	30·1	354,004	77,093	175,134	5·058	1·097	2·497

there was flowing 26,640 feet, leaving the effects of the seven days' rain $85,836 - 26,640 = 59,196$ cubic feet, while in the second year the quantity flowing at first was 75,360 cubic feet, leaving the effects of the seven days' rain-fall equal to $115,656 - 75,360 = 40,296$ cubic feet. The effect of the previous state of the weather on the catchment must always modify, to a considerable extent, the discharge from a given rain-fall, and this has more to do with the results than the effect of arterial drainage itself, unless so far as one is a result of the other. Taking the mean of 1851 and 1852, it appears that the evaporation and absorption in the Ballinrobe catchment were to the rain-fall as 41·6 to 98·7, or about 42 per cent. This is certainly, from the nature of the catchment, less than the average through Ireland, which cannot be less than 60 per

cent. In high, steep districts, fully three-fourths, or 75 per cent., of the rain-fall can be collected, and at times, when the catchment is saturated, nearly the whole; even in some few limited cases, when springs or hidden supplies are re-tapped, a larger discharge may take place than that due to the catchment and rain-fall; but these do not affect the general question.

The effects of absorption and evaporation are very variable; sometimes 58 or 60 per cent. of the annual fall is carried off in this way from ordinary flat tillage soils, and other estimates are much higher; much, however, depends on the soil, subsoil, inclination, stratification, geological formation, and season. The evaporation from water surfaces exceeds the annual fall in these countries by about one-third; and that from flat, marsh, and callow lands exceeds the evaporation from ordinary tillage, porous, and high lands. When the flat lands along the banks of rivers extend considerably on both sides, an extra fall is necessary into the main channel, along the normal drains, otherwise such lands must suffer from excessive evaporation as well as floods. Evaporation and absorption also vary with the climate, but in this country we may safely assume that one-third of the whole rain-fall passes on to the sea.

The absorption and evaporation must not, however, be taken as proportionate to the rain-fall. From 14 to 16 inches from land (and about 33 inches from water) may be taken in this country as the allowance to be made; equivalent to an average of about 15 inches. The evaporation from the surface of

reservoirs is said to be about 4 feet in India. But it is probably greater.

In a paper in the Journal of the Royal Agricultural Society of England, vol. v. part 1, 1844, Mr. Josiah Parkes shows, that $42\frac{1}{2}$ per cent. of the whole annual rain of England filters through the soil, and $57\frac{1}{2}$ per cent. evaporated, being the mean results of eight years' observations, from 1836 to 1843, both included. The mean evaporation and filtration for each month during this period are shown and arranged by us in the following table:—

MONTHS.	Total falling.	Evaporated.		Remaining.		Deposited in tons and cubic feet per acre.	
	Inches.	Inches.	Per cent.	Inches.	Per cent.	Cubic feet.	Tons.
January . . .	1·847	·540	29·3	1·307	70·7	4,744	132
February . . .	1·971	·424	21·6	1·547	78·4	5,616	156
March . . .	1·617	·540	33·4	1·077	66·6	3,910	109
April . . .	1·456	1·150	79·0	0·306	21·0	1,111	39
May . . .	1·856	1·748	94·2	0·108	5·8	392	11
June . . .	2·213	2·174	98·3	0·039	1·7	142	4
July . . .	2·287	2·245	98·2	0·024	1·8	87	2·4
August . . .	2·427	2·391	98·6	0·036	1·4	131	3·6
September . . .	2·639	2·270	86·1	0·369	13·9	1,339	37
October . . .	2·823	1·423	50·5	1·400	49·5	5,082	141
November . . .	3·837	0·579	15·1	3·258	84·9	11,826	328
December . . .	1·641	0·164	00·0	1·477	100·0	6,552	182
Yearly averages	26·614	15·320	57·6	11·294	42·4	40,932	1145

The maximum quantity, 32·10 inches, fell in 1841, and the minimum in 1837, 21·10 inches. The maximum and minimum quantities respectively which fell in January were 3·95 and ·31 inches; in February 2·85 and 1·02 inches; in March 3·65 and 0·34 inches; in, April 2·57 and ·34 inches; in May 5·00 and ·70 inches;

in June 3·81 and 1·33 inches; in July 4·36 and 1·30 inches; in August 3·65 and 0·95 inches; in September 4·50 and 0·63 inches; in October 4·82 and 1·41 inches; in November 5·77 and 2·05 inches; and in December 3·02 and ·40 inches. The greatest quantities fall in September, October, and November, and the least in February, March, and April. The general mean fall for England is said to be $31\frac{1}{4}$ inches, and near London 25 inches.

The amount of rain varies, not only at different places and different elevations, but also at different elevations in the same place. The following table shows the amount of rain collected in each month in 1855 at Greenwich Observatory, at different elevations:—

Month in 1855.	Osler's anemometer gauge, inches.	On the roof of the library.	Cylinder partly sunk in the ground.
January	0·2	1·0	1·5
February	0·2	1·4	1·0
March	0·5	1·3	2·0
April	0·1	0·1	0·1
May	0·5	1·5	1·8
June	0·5	0·7	0·9
July	3·1	4·8	5·3
August	0·6	0·8	1·4
September	0·8	1·1	2·0
October	2·6	4·5	5·2
November	0·5	1·1	1·5
December	0·4	0·9	1·1
Totals	10·0	19·2	23·8

The cylinder gauge was placed 155 feet above the level of the sea; the gauge on the roof of the library 22 feet over the cylinder gauge, and Osler's anemo-

meter gauge 28 feet higher than the gauge on the roof of the library. In the valleys in the lake districts of Westmoreland and Cumberland, the annual fall varies occasionally from 50 to 100 inches, and the maximum fall is said to obtain at about 2000 feet above the level of the sea on high catchments.

At Ballinrobe, a gauge placed on the church tower, 60 feet above the ground, indicated 42 per cent. less rain than one on the ground; and another experiment with a change of gauges, gave 68 per cent. less at the greater elevation!

At Kinfauns Castle, Scotland, a gauge 600 feet high on a hill, gave $41\frac{1}{2}$ inches, while one at the base, 580 feet lower, gave only $25\frac{1}{2}$ inches. In Keswick, the fall is $65\frac{1}{2}$ inches, and in Carlisle only 30 inches. At Kendal the fall is 60 inches; at Manchester 38 inches; at Lancaster 45 inches; at Liverpool 34 inches.

From the 23rd of February to the 6th of June, 1860, the rain at Dublin was 8 inches. At the Leefin Mountain, which is 2000 feet high, the rain was 13·1 inches. From the 23rd of February to the 9th of July, the rain at Dublin was 10·674 inches; and at the same time, on the Leefin Mountains (over Ballysmutten), 18·1 inches; that is, an increase of nearly 80 per cent. in that time. From the 23rd February to the 21st August, inclusive, the rain-fall at Dublin was 17 inches; at Blessington 21 inches; at Ballysmutten, on the site of a proposed reservoir, 27 inches. This showed an increase over Dublin of 10 inches. It would appear that from 50 to nearly 80 per cent. more rain fell at Ballysmutten than at Dublin. It would

however have been more correct to compare the rain-fall at Kingstown or Bray with that on the adjacent mountains than the rain-fall of Dublin.

Experiments were made at York in 1832, 1833, and 1834, for the British Association, with three gauges—the first placed on a large grass plot in the grounds of the Yorkshire Museum; the second at a higher elevation, 43 feet 8 inches, on the roof of the Museum; and the third on a pole 9 feet above the battlements of the great tower of the Minster, at an elevation over the gauge on the ground of 212 feet 10½ inches. The quantities received were as follows:—

	Depth for three years.	Average depth for one year.
First gauge . . .	64·430 inches . . .	21·477 inches
Second gauge . . .	52·169 „ . . .	17·389 „
Third gauge. . .	38·972 „ . . .	12·991 „

Professor Phillips gives the following formula for calculating the difference between the ratios of rain falling on the ground and at any height h in the same place— t° the temperature of the season, and c a coefficient dependent upon it; then the difference d is

$$d = c h \frac{t^{\circ}}{110}.$$

The mean height at which rain begins to be formed by this formula is 1,747 feet over the ground; and at 356 feet high, the depth which falls is one-half of what falls on the ground.*

A discussion of the mean temperature in connexion with the fall of rain, was completed at Greenwich for the years 1852, 1853, and 1854; and at Oxford for

* *Vide* Civil Engineer and Architect's Journal for 1860, p. 167.

the years 1855, 1856, and 1857. The result shows an average of 160·3 rainy days at Greenwich for each year, and 146·6 at Oxford. The difference of the mean temperatures of the day of rain and the day before is less than that of the day of rain and the day after.

	Mean temperature, day before rain.	Mean temperature, day of rain.	Mean temperature, day after rain.
Greenwich observations	49·25° . .	49·27° . .	48·98°
Oxford do.	49·50 . .	49·63 . .	49·44

Dividing the winds into two groups, northerly and southerly, the Oxford observations give the direction for 218·5 days' fair weather. The wind was northerly for 131·5 days, and southerly for 87 days. For the remaining 146·5 rainy days, the wind was northerly for 64·5 days, and southerly for 82 days.

SEWERAGE.

“The future population of the suburbs of London is calculated at 80,000 inhabitants per square mile. According to the following data, some of the densest portions of our large towns have a population of 220 persons to an acre. The population on the north side of the Thames is about 75 persons per acre, and on the south side 28 persons per acre. Taking the average density of population in our twenty-one principal towns, there appear to be 5045 inhabitants to the square mile; but, from the following table, extracted from Dr. Duncan's report on Liverpool, it will be seen that if we select five of our most populous cities, the average in these is much greater, while in others, it is equally certain that the crowding is

far less than the general standard to which we have referred :—

Towns.	Inhabitants to a Square Mile.	
	Total Area.	Builded Area.
Leeds	20,892 . . .	87,256
London	27,423 . . .	50,000
Birmingham . . .	33,669 . . .	40,000
Manchester	83,224 . . .	100,000
Liverpool	100,899 . . .	138,224

Dr. Duncan, however, states that there is a district in Liverpool containing 12,000 inhabitants crowded together on a surface of only 105,000 square yards, which gives a ratio of 460,000 inhabitants to the geographical square mile. In the East and West London Unions, Mr. Farr has estimated that there are nearly 248,000 inhabitants to a geographical square mile ; but, great as this overcrowding is, the maximum density of Liverpool is nearly double that of the metropolis." *

GREAT TOWNS.—The Registrar-General estimates the population of the metropolis in the middle of the year 1870 at 3,214,707, being 41·2 persons to an acre. This is London with the suburbs, from Hampstead to Streatham, and from Woolwich to Hammersmith. He estimates the population of Liverpool in the middle of the year 1870 at 517,567, or 101·3 persons to an acre; Manchester, 374,998, or 83·6 per acre; and Salford, 121,580, or 23·5 per acre; Birmingham, 369,604, or 47·2 per acre; Leeds, 259,527, or 12 per acre; Sheffield, 247,378, or 10·8 per acre; Bristol, 171,382, or 36·6 per acre; Bradford, 148,197, or 21·7 per acre; Newcastle-upon-Tyne, 138,367, or 25 per acre; Hull,

* Illustrated News, September 8th, 1855.

130,869, or 36·7 per acre; Portsmouth, 122,084, or 12·8 per acre; Leicester, 97,427, or 30·4 per acre; Sunderland, 94,257, or 19·6 per acre; Nottingham, 88,888, or 44·5 per acre; Norwich, 81,087, or 10·9 per acre; Wolverhampton, 72,990, or 21·5 per acre. The area taken is the municipal boundary in all cases except London. The population of Edinburgh is estimated at 178,970, or 40·4 per acre; of Glasgow, 468,189, or 92·5 per acre; of Dublin, with some suburbs, 321,540, or 33 per acre. The population of these twenty towns of the United Kingdom is thus estimated at 7,209,603. The population of Paris is estimated at 1,889,842; of Vienna, 605,200; of Berlin, 702,437.

The amount of sewage is calculated at about FIVE CUBIC FEET PER PERSON, including the supply from manufactories, breweries, distilleries, &c. So high as SEVEN FEET PER HEAD has been recommended as data to calculate from by Captain Galton and Messrs. Simpson and Blackwell, in their Report on the Main Drainage, and it has been found that about half of the estimated quantity of sewage would be passed off in six or eight hours.

In calculating the size of sewers, however, the rainfall must be provided for, in addition to the sewage matter from houses and public establishments. Mr. Bazalgette calculated this for the London sewerage at $\frac{1}{4}$ th of an inch fall in 24 hours in the urban districts, and $\frac{1}{8}$ th of an inch for the suburban districts. Captain Galton and Messrs. Simpson and Blackwell assumed $\frac{3}{8}$ ths of an inch fall during eight hours' maximum flow. This would be 1,452 feet per acre.

Assuming the highest data, we shall have to provide sewers to discharge in eight hours

1,452 cubic feet of rain water per acre,

$3\frac{1}{2}$ cubic feet of sewage nearly per person.

Assuming a population of 80 persons per acre, then these figures would become

1,452 cubic feet for rain,	$\left\{ \begin{array}{l} \text{in eight hours, or} \\ \text{about } 3\frac{1}{2} \text{ cubic feet} \\ \text{per minute, per acre,} \end{array} \right.$
280 cubic feet for sewage,	

which shows that the sewage is not more than $\frac{1}{4}$ th of the rain water; and that, in calculations for the size of sewers, the surface water is the most important element to be considered. If we had assumed a larger fall of rain, the difference between sewage and rain would be greater. On the 20th June, 1857, the day after heavy rain, the referees on the Metropolitan Drainage question found the Norfolk-street sewer to discharge 3 feet; the Essex-street sewer $5\frac{1}{4}$ feet; the Northumberland-street sewer $3\frac{1}{2}$ feet; and the Savoy-street sewer $20\frac{1}{2}$ feet per minute per acre; but the last result has been controverted.

It appears that the daily amount of sewage varies from 4·8 cubic feet per head in the more thickly inhabited portions of London, occupied by a larger portion of the poorer classes, to 8 cubic feet per head in the western districts, where the value of water is more appreciated, and the cost less a matter of consideration; and the average of the whole metropolitan districts appears to be 5·8 cubic feet per head per diem. If the day be divided into three periods of eight hours each, the amount of the maximum flow is between nine A.M. and five P.M. and 49 per cent. of the

whole ; whilst only 18 per cent. flows during the eight hours of minimum flow, which occur between eleven P.M. and seven A.M.* The advantage of storm flows in flushing is shown by the heavy rain which occurred on the 20th of June, causing a flow in the Savoy-street sewer which was equivalent to 20 times the ordinary flow at the time. This was six times the maximum flow, and *although the sewer had been scoured, to a considerable extent, by a heavy fall of rain on the previous night, the sample contained more than double the amount of total impurity contained in specimens of ordinary sewage.*

In a town district, such as that drained by the Savoy and Northumberland-street sewers, the quantity running off into sewers, within six hours after the fall, varies from 10 to 60 per cent. of the quantity fallen. Of the rain during the storm of the 20th June, 1857, nearly one inch-and-a-quarter in an hour, 65 per cent. ran off within 15 hours of the fall, viz. :—

46 per cent. in 45 minutes after the rain ceased,

14 „ in the next $6\frac{3}{4}$ hours,

5 „ in the next $7\frac{1}{2}$ hours.

In a suburban locality, such as the Counter Creek sewer drain, the quantity reaching the sewers would vary from 0 to 30 or 40 per cent. in 24 hours after the rain.†

In the Holborn and Finsbury divisions Mr. Roe calculated that an 18-inch cylindrical pipe, laid at an inclination of 1 in 80, is sufficient for 20 acres of house sewage, while a 5-inch pipe, laid at an inclination of 1 in 20, is necessary for 1 acre, and a 3-inch

* Metropolitan Main Drainage Report, pp. 15, 17.

† Ibid., pp. 75, 76.

pipe, laid also at 1 in 20, for $\frac{1}{4}$ acre. A pipe 30" in diameter, laid with an inclination of 1 in 200, would discharge 1700 cubic feet per minute, and perfectly drain 200 acres of urban land covered with houses to the extent of 4000 or upwards, and each house having a water supply of 150 gallons per diem. In each of these cases, however, the discharge must depend on the head and length of the pipe as well as the inclination at which it is laid. Assuming the inclination of those pipes to correspond with the hydraulic inclination, we have calculated their discharging powers with water to be respectively 807, 72, 20, and 1700 cubic feet per minute, the areas to be drained being 20, 1, $\frac{1}{4}$, and 200 acres. *In all calculations of this kind it is necessary to ascertain not only the maximum rain-fall per hour, but also the proportions discharged per hour, according to the season and district, into the main channel, as well as the junctions or places of arrival.* In urban districts, 1500, 2100, and sometimes 3600 cubic feet per hour per acre, have to be discharged after extraordinary rain-falls. These may be taken as maximum results. The gaugings of the Westminster sewers in summer give 53 cubic feet per hour for the urban, and 17 cubic feet for the suburban, according to Mr. Hawkins.

In urban districts, however, a much larger quantity of water is conveyed more rapidly, *cæteris paribus*, to the mains, than in suburban districts and catchment basins generally, in which the maximum discharge per acre per hour, even in the steeper and higher districts, seldom exceeds 700 cubic feet, and varies from about 20 cubic feet for the larger and flatter

districts upwards. This arises from the impervious nature of the surfaces it falls upon in towns, and the lesser waste in passing to the drains, as well as a large portion of the supply being often artificial. From 70 to 90 cubic feet * per acre per hour, is generally taken for the maximum discharge from the average number of catchment basins ; this is nearly equal to a supply of one-fiftieth part of an inch in depth from the whole area.

SECTION XIII.

WATER SUPPLY FOR TOWNS.—STRENGTH OF PIPES.—
SEWERAGE ESTIMATES AND COST. — THOROUGH-
DRAINAGE.—ARTERIAL DRAINAGE.

SUPPLY.—QUALITY.

The supply of water to towns has become latterly a subject of considerable importance. Three points have to be considered ;—**FIRSTLY**, a sufficient and constant supply at high pressure, when it can be obtained within a reasonable expenditure ; **SECONDLY**, the quality ; and, **THIRDLY**, the cost. The advantages in towns of high pressure are now apparent to all in overcoming fire ; fronts of houses and pavements may also be cleaned, and streets watered if the supply be abundant. The highest apartments can be supplied, and even mechanical power can be obtained for many purposes, as grinding coffee, at a reasonable cost. Mr. Glynn says,† “ In many parts of London water is

* Some interesting observations on rain-fall and flood discharges are given in the Transactions of the Institution of Civil Engineers, Ireland, for 1851, pp. 19–33, and pp. 44–52.

† Power of Water.—WEALE.

supplied at 4*d.* for 1000 gallons, at a pressure of 150 feet: a gallon of water weighs 10 lbs., so that 1000 gallons of water falling 150 feet, are equal to 1,500,000 lbs. falling one foot; and if 1500 gallons of water be used in one hour, they are equal to 37,500 lbs. falling one foot in one minute, or somewhat more than a horse's power, which is 33,000; therefore, it may be assumed, that the cost of a horse's power for an hour in such cases, is only 6*d.*"

The number of gallons of water required for the supply of each person, including all collateral uses, has been differently estimated, and varies in almost every town, and even in the same city—London, for instance, when supplied by different companies and under different systems. 44 gallons per head, per diem, were supplied by the several companies of London in 1853, while evidence has been given to show that the actual average consumption for all purposes did not exceed 10 gallons per head, per diem; the remainder having been wasted under an imperfect system of distribution. It is asserted that when the supply is 25 gallons per head, per diem, that 5 gallons of it are used for purposes requiring filtration, 10 gallons for purposes not requiring filtration, and 10 gallons wasted, or two-fifths of the supply. As there must be a considerable loss under even the best system of supply, we may assume, with the Board of Health, that a *minimum supply* of 75 gallons per house, per diem, or 15 gallons per person, per diem, is necessary.

The following is an abstract of the average number of gallons of water furnished per diem, by different

water companies in London, during the year 1853, to each house, including manufactories and public establishments as houses :—

	Gallons.	
	Per house.	Per person.
New River Company	193	38·3·5
East London Water Works	187	37·2·5
West Middlesex Water Works	204	40·4·5
Grand Junction Water Works	{ 319	{ 63·4·5
	{ 336	{ 67·1·5
Southwark and Vauxhall Companies' Houses	175	35
Ditto average houses, manufactories, public establishments	209	41·4·5
Chelsea Water Works	227	45·2·5
Hampstead Water Works	111	22·1·5
Kent Water Works	270	54
	2231	446·1·5
Mean values	223·1·10	44·3·5

These quantities have been calculated from the parliamentary returns made in 1854 ; and if there be any truth in the calculations and returns of the quantities actually consumed per person—said to be 10 gallons—we get the proportion, as 10 is to 34 so is the quantity consumed to the quantity wasted. But, even assuming the quantity consumed to be 20 gallons per head, what an immense loss is here exhibited from want of a suitable system of check and distribution.

For large towns it is safe to provide for many purposes, besides present personal or house wants ; and it is safer, *where it can be done without much extra cost*, to provide for a supply of 40 gallons to each inhabitant, even if this quantity should not be used or raised.

For high pressure, the supply required will generally vary from 15 to 40 gallons, or from 2·5 to 6·5 cubic feet to each inhabitant, or for an average of about 28 gallons, including the supply to stables, offices, manufactories, and breweries.

The storage in reservoirs should be for about 120 or 160 days' supply, including the quantity necessary for mills and riparian occupiers lower down. This latter is taken very often at about half the former; so that two-thirds of the storage may be available for the town, and one-third for mills and riparian lands. The actual relation, however, depends on local circumstances.

The quality of water for drinking, washing, or cooking, is also an important element in selecting a source of supply. Hardness is measured by the number of grains of chalk or carbonate of lime to a gallon of water, each called a degree. The average hardness of spring water is about 26°, that is, 26 grains of carbonate of lime to one gallon of water. Rivers and brooks have an average hardness of 13°, and water derived from surface drainage 5°; hence the great advantage of the latter kinds of water in washing. The average hardness of the London pipe waters is from 10° to 16°. The following extracts from a report and analyses furnished to me, in 1855, by Professor Sullivan, of the Museum of Irish Industry, Dublin, will show what is generally required on this head:—

“On the annexed page you will find the numerical results of my analyses of the four samples of water which you left with me for examination. From the table you will perceive that the water of the Mattock River appears to be the purest, so far as the nature

and the amount of the foreign substances held dissolved in it is concerned. The water of the Boyne comes next in quality to that of the Mattock River, the pump water being in every sense the worst, so far as amount of ingredients can be taken as a test of the quality of a water ; in this respect, indeed, it resembles the water of the deep wells of London and elsewhere.

“As the ordinary mode in which the quality of a water, for drinking and for culinary and like purposes, is judged of is, by the comparative amount of organic matter, the total amount of dissolved matter, and its hardness, according to the ‘soap test,’ I shall give in the following table the numbers representing each of these qualities :—

TABLE showing the number of grains of Organic Matter, and the number of grains of Solid Matter, in an Imperial Gallon of

Water from	Number of Grains of Organic Matter, per Imperial Gal.	Number of Grains of Solid Matter, per Imperial Gal.	Degree of Hardness according to the Soap Test.
No. 1. Tullyescar . . .	8·975 grs.	31·175	15 8-10ths.
„ 2. River Mattock . .	2· (about)	15·360	9 1-10th.
„ 3. River Boyne . . .	3·250	22·700	14 9-10ths.
„ 4. Burn's Pump . . .	7·100	76·850	34 4-10ths.

“In order to render this table more instructive, it may be well to subjoin a few of the results obtained from the analyses of the waters of other localities.

TABLE showing the number of grains of Solid Matter contained in one gallon of the following Water :

Thames at Greenwich	27·9 grains.
„ London	28·0 „
„ Westminster	24·4 „
„ Twickenham	22·4 „
„ Teddington	17·4 „

New River (London)	19·2 grains.
Lea „ „	23·7 „
Trafalgar Square Fountain, Deep Well	68·9 „
Well in St. Giles's, Holborn	105·0 „
Artesian Well at Grenelle (Paris)	9·86 „

“The following are some of the results obtained from an examination of the waters in the neighbourhood of Dublin, or which have been proposed as a source of supply :*—

Locality from whence Water was obtained.	Total Number of Grains per Imperial Gallon.	Total Number of Grains of Organic Matter.	Degree of Hardness according to the Soap Test.
			degs.
Royal Canal (12th Lock)	21·0	2·80	14·0
Grand Canal (7th Lock)	16·300	2·30	10 3·4ths.
River Liffey, at Kippure	3·522	1·90	0 2·10ths.
Phoulaphouca	5·125	1·50	0 2·10ths.
Lough Dan, Co. Wicklow	2·800	1·225	0 8·10ths.
River Dodder, at City Weir	8·350	1·625	1 8·10ths.
Lough Owel	10·225	1·550	6 7·10ths.

* Dr. Apjohn gave the following analyses :—

	Total matter dissolved.	Organic matter.	Hardness.
Grand Canal—mean of seven analyses	20·78	·95	15·9
Royal Canal—mean of five analyses	20·76	1·64	14·1
Liffey—mean of eleven analyses	8·62	1·77	6·1

Analysis of the deposition on pipes from the Portobello basin :—

Water.	2·20
Organic Matter	9·71
Sand	10·20
Peroxide of Iron and Alumina	3·50
Carbonate of Lime	74·20
Carbonate of Magnesia	·19

100·

Professor Apjohn gave the following analyses of waters furnished to the city of Dublin in 1860. It shows how necessary it is to distinguish the time of taking specimens for analysis, and the previous state of the weather as affecting the foreign matters in the water. The specimens were collected on the 5th and 19th of May, 1860. The quantity operated upon in each instance was an imperial gallon, or 277·273 cubic inches :—

CITY WATER COURSE, DODDER.

	5th May.	19th May.	
Carbonate of lime . . .	4·056	7·308	Specific gravity of specimen (5th May) 1·00011.
Carbonate of magnesia	0·700	
Sulphate of lime and chlorides of sodium and magnesium . . .	2·269	2·171	Specific gravity of specimen (19th May) 1·00014.
Silex	0·166	0·526	
Organic matter	1·811	1·101	
	<hr/> 8·302	<hr/> 11·806	

PORTOBELLO BASIN.

Carbonate of lime . . .	7·687	11·660	Specific gravity of specimen (5th May) 1·00023.
Carbonate of magnesia	0·764	
Sulphate of lime and chlorides of sodium and magnesium . . .	4·058	3·751	Specific gravity of specimen (19th May) 1·00031.
Silex	0·073	0·194	
Organic matter	3·308	2·289	
	<hr/> 15·126	<hr/> 18·658	

It will be observed that the quantities of saline and other ingredients found in specimens of the same water collected at the two separate periods above mentioned are materially different; those obtained at the later date (May 19) containing the larger portion of foreign matters. The extent of this variation is very considerable, and it appears to Dr. Apjohn to have been the

consequence of a very considerable fall of rain, which took place in the interval between the periods at which the specimens were taken up for analysis.

When the means of the preceding analyses are taken, we obtain the following results :—

	City Water Course.	Portobello Basin.
Mean amount of saline matter	. 8·598	. 14·094
„ „ organic matter	. 1·456	. 2·798

The quality of a water for drinking purposes depends in a great degree upon the condition in which the organic matter is found, much more than upon its quantity. This is, however, a question outside of the domain of chemistry, and can only be solved by the aid of the microscope.

As a general rule, the water of clear flowing rivers, even though it may contain a large amount of solid matter, and even of organic matter, will be found wholesomer than well water, especially in towns.

The whole of the lime and magnesia existing as carbonates is precipitated by boiling, the water being thus proportionably rendered less hard; lime and magnesia existing as sulphates or chlorides, on the other hand, are not precipitated. This difference is of great consequence in culinary operations, as where boiled water is used, the carbonates of lime and magnesia are not injurious, and if no sulphates or chlorides be present, the water may be soft after boiling. The same observation applies to water used for washing clothes when boiled. And lastly, sulphate of lime forms one of the worst elements of fur or deposit upon steam boilers.

Tabular Results of the Special Analyses of Four Samples of Water from the neighbourhood of Drogheda.

Nature of dissolved matter.	No. 1. Tully- scar.	No. 2. Mattock River.	No. 3. Boyne River.	No. 4. Burn's pump water.	Observations.
Carbonate of lime . .	9.350	7.302	11.648	21.475	Inclusive of a very small quantity of phosphate of lime and iron not separated from the lime.
Carbonate of magnesia	0.429	0.510	0.888	0.585	
Sulphate of lime . . .	9.043	2.514	4.459	4.568	
Chloride of magnesium	0.743	1.258	1.685	3.445	
Chloride of calcium	0.991	..	9.524	
Chloride of sodium	
Magnesia existing as oreate, &c., in the water	0.464	
Lime do. do.	0.548	
Silica do. do.	0.627	..	0.322	2.212	
Potash and soda exist- ing in water, as ni- trates, crenates, and other organic salts. . .	1.544	2.785	0.448	22.398	
Organic matter . . .	8.975	..	3.250	7.100	
Total number of grains per Imperial gallon . .	31.175	15.860	22.700	76.850	

The saving in soap effected by a reduction of 10 degrees in hardness, is found to be over 50 per cent.

Some of the metropolitan waters analysed by Dr. Robert Dundas Thomson, F.R.S., were found, in May, 1860, much more impure than others, the samples of which had been taken at the beginning of the month, before the impurities conveyed by the rains had contaminated them. The supply afforded by large and small rivers, as in London, in this table, contrasts most unfavourably with that afforded by the drainage of mountain ridges, as at Glasgow and Manchester. The specimens of water from the two latter cities were taken by the instructions of Mr. Bateman, F.R.S., the engineer, from the main pipes during the month. It

should be the object of the London Companies to avoid pumping the water in its most impure state, and to store it when in the condition of the greatest purity.

	Total Impurity per gallon.	Organic Impurity per gallon.
	Gra., or °.	Gra., or °.
Distilled water	0·0	0·0
Loch Katrine water, new supply to Glasgow	3·16	0·96
Manchester water supply	4·32	0·64
THAMES COMPANIES :—Chelsea	17·84	1·48
Southwark	17·08	1·64
Grand Junction	20·72	2·00
West Middlesex	20·08	2·08
Lambeth	20·80	2·40
OTHER COMPANIES :—New River	18·52	1·56
East London	23·64	3·20
Kent	21·68	2·96

The table is read thus :—Loch Katrine water contains in the gallon 3·16 degrees, or grains, of foreign matter in solution, of which ·96 degrees, or grains, are of vegetable or animal origin.

SOURCES AND GATHERING GROUNDS.

The sources from which a water supply for towns may be derived are lakes, rivers, and streams, springs, wells, and gathering grounds. Of the latter it may be said that, however ably put forward under the auspices of the Board of Health, it is far safer to resort to good river waters than trust to what has been termed, with some satirical truth, “new-fangled schemes of pot-piped gathering grounds.” Springs and wells afford, at best, but a partial supply unless for villages or manufactories; and we must almost always trust to lakes, rivers, or

TABLE showing the Quantities of Gathering Ground and Reservoir Room to supply a given population with 15, 30, and 40 gallons of water per head per diem. The reservoir room is calculated to hold 12 inches in depth of rain-fall per mile as a guide for lesser depths. For 4 inches the results are to be divided by 3; and for 6 inches by 2.

Population can be supplied at 15 gallons per head per diem.	Population can be supplied at 30 gallons per head per diem.	Population can be supplied at 40 gallons per head per diem.	Cubic feet per minute required for the supply. To find the net size and inclination of a pipe to convey it, see table, pp. 26 & 29.	Millions of gallons per diem required for the supply.	Gathering ground in square miles required for the supply for a depth of 12 inches col- lected, equal to a supply of 33 cubic feet per minute per mile.	Reservoir room required in millions of cubic feet per square mile of catchment, to hold a supply of 12 inches of rainfall.
2,500	1,250	987	4·179	·0375	·0789	2·196
5,000	2,500	1,875	8·358	·075	·1577	4·393
7,500	3,750	2,812	12·536	·1125	·2366	6·589
10,000	5,000	3,750	16·715	·15	·3154	8·786
12,500	6,250	4,687	20·894	·1875	·3942	10·982
15,000	7,500	5,625	25·072	·225	·4731	13·179
17,500	8,750	6,562	29·251	·2625	·5519	15·375
20,000	10,000	7,500	33·430	·300	·6308	17·572
25,000	12,500	9,375	41·788	·375	·7885	21·965
30,000	15,000	11,250	50·145	·45	·9462	26·358
35,000	17,500	13,125	58·5	·525	1·1039	30·75
40,000	20,000	15,000	66·9	·6	1·2616	35·144
45,000	22,500	16,875	75·217	·675	1·4193	39·537
50,000	25,000	18,750	83·57	·75	1·577	43·93
55,000	27,500	20,625	91·932	·825	1·734	48·32
60,000	30,000	22,500	100·29	·9	1·8924	52·716
65,000	32,500	24,375	108·65	·975	2·0501	57·109
70,000	35,000	26,250	117·	1·05	2·2078	61·502
75,000	37,500	28,125	125·36	1·125	2·3655	65·895
80,000	40,000	30,000	133·72	1·2	2·5232	70·288
85,000	42,500	31,875	142·1	1·275	2·6809	74·681
90,000	45,000	33,750	150·435	1·35	2·8386	79·074
95,000	47,500	35,625	158·8	1·425	2·970	83·467
100,000	50,000	37,500	167·15	1·5	3·154	87·86
105,000	52,500	39,375	175·5	1·57	3·311	92·25
110,000	55,000	41,250	183·86	1·65	3·469	96·64
115,000	57,500	43,125	192·22	1·72	3·62	101·10
120,000	60,000	45,000	200·58	1·8	3·785	105·48

streams, with reservoirs, for stowage, for a sufficient supply for large towns. The Croton aqueduct, conveying water with an average of three degrees of hardness, to New York, is perhaps the noblest work for water supply of modern times. The length of the aqueduct is about 44 miles, with a channel inclination of about 15 inches per mile. The receiving reservoir is about two miles higher up the channel than the distributing reservoir, which latter is 115 feet over the level of the sea, and commands the highest buildings of the city. In the driest weather the supply is equal to 28,000,000 gallons.* The cost of the work, including the purchase of land and water rights, was 8,575,000 dollars, or £8 per lineal foot nearly. The cost of distributing pipes was 1,800,000 dollars. We have had also the Loch Katrine and Glasgow aqueduct, a noble work, constructed after this model by Mr. Bateman, notwithstanding the previous supply of that city, or a portion of it, the Gorbals, from gathering grounds at a high level. The Vartry supply for Dublin, carried out under the same engineer and Mr. P. Neville, the city surveyor, is derived by embanking and storing the waters of the River Vartry. It is, however, sometimes necessary to make use of such grounds, particularly when flanking or lying above glens where an embankment may be easily thrown across, and the supply stored for use, which would otherwise pass quickly off. The table, page 353, gives the areas of reservoirs and gathering grounds according to a collection of one foot in depth from the catchment ; it can be easily modified

* Schramke's Croton Aqueduct, New York.

when the storage or required supply exceeds or falls short of this depth. *One acre of gathering ground with a collection of twelve inches of rain-fall from it annually will give a daily supply of five cubic feet per head to twenty-four inhabitants; or of four cubic feet, or twenty-five gallons, to thirty inhabitants.*

The next table will be of use in showing the actual quantities which have been collected, or could have been collected, for storage. Homersham, Hughes, and Beardmore's books have been consulted in arranging it.

The various methods employed for purification may be classed under three heads: mechanical, by filtering or straining; chemical, or antiseptic media, such as peat and animal charcoal, and precipitation by the use of lime water; and the natural precipitation of impurities when the water is at rest, as well as the purification which takes place from oxidation and neutralization on thorough exposure by the ozone of the atmosphere. This latter plan has, however, been tried, and signally failed. Filter beds may be constructed to have a surface area of one square yard for every 800 gallons filtered in twenty-four hours. For executed works the proportions vary from 1 in 460 to 1 in 1140.

COST.

With reference to cost, the following tables, arranged by us from various sources, will afford information from works executed.

The estimated cost of the water supply for Dublin from the Vartry was £300,000 for 12,000,000 gallons

TABLE showing information with reference to size of Reservoirs, Catchment Areas, &c., collected and arranged from various authorities. The first, fifth, and sixth columns contain information with reference to reservoirs and the collecting areas; the second, third, and fourth, show for different districts the whole rainfall, and the portions or per centage flowing off and available.

Names of Drainage Areas and names of Reservoirs.	Drainage area in square miles.	Rainfall in inches per annum.	Depth of rain in inches per annum flowing off the surface.	Per centage of rainfall which flows off the surface.	Reservoir room per square mile in millions of cubic feet of water.	Contents of Reservoir in millions of cubic feet.
Ashton	59	40.0	15.5	89	21.0	12
Albany Works, U.S.	29				1.1	32
Ballinrobe, Ireland	11.0	49.3	28.5	58
Belmont (moorland), mean of four years	2.81	54.5	39.6	72	26.8	75
Bolton	30				25.6	20
Bute (low country)	..	45.4	23.9	53
Bateman's evidence on the drainage area of Longdendale:—						
First half of 1845, very dry	..	21.2	13.5	64
Second half of 1845	..	38.6	27.25	71
First half of 1846	..	22.5	17.5	78
Oct., Nov., and Dec., 1846	..	10.2	8.67	85
Bann Reservoir (moorland)	..	72	48.0	66
Drainage areas on south side of Longridge Fell, near Preston, May, 1852, to April, 1853	15.5	29
	..	54	18.0	33
	22.0	43
Dilworth Reservoir of Preston Works, Lancashire	.092	54.0	5
Glenoorse	6.00	87.0	22.3	60	7.66	46
Greenock	7.88	60.0	41.0	68	38	300
Homersham's estimate of 24,000 cubic feet of Reservoir to each acre of drainage	.1	15.36	15.36
Longdendale	28.8	12.3	292
Proposed Reservoir for Wolverhampton Works	2247	16
Rivington Pike	16.25	55.5	24.25	44	29.6	481
Sheffield	1.42	36.5	52
Turton and Entwistle	3.18	46.2	41.0	89	31.43	100

daily. It is said to have cost £1 17s. 6d. a head, Glasgow £3, Manchester £2 18s., and Birmingham £3. The annual cost of filtering 1,000,000 gallons daily, capitalized, is put down at £1,250 by Sir John Hawkshaw in his report on the Dublin supply. This would be £62 10s. yearly. It varies from £40 to £120 under different circumstances. The works of construction and the first cost of the filters may be taken at about £2,000 for each 1,000,000 gallons to be filtered daily.

The supply to the suburbs of Dublin is given at a charge of about $9\frac{1}{2}$ pence for each 1,000 gallons.*

The actual cost of all works for house service varies very much in different towns, and with the quantities supplied, from a general average of 1d. per house per week, to 2d., and from an annual rate of 9d. in the pound to 1s. 6d., and higher. The cost of raising and supplying 1,000 gallons from a height of 135 feet in Nottingham is said to be 3d., and the charge for house service to vary from 5s. to 60s. annually. In Rugby, the average cost per house is 19s. per year, $4\frac{1}{2}$ d. per week, or an annual charge of 3s. 3d. per year, or $\frac{3}{4}$ d. per week per head of the population, and for a bare supply of 13 gallons. In Croydon, for a supply of only 14 gallons per head, the cost of works varied from $1\frac{1}{2}$ d. to $2\frac{1}{2}$ d. per house per week. The parliamentary returns, showing the number of houses supplied, and cost of supply, by different water companies of London, in 1884, give the following results :—

* In December, 1874, the quantity sent into the city and accounted for is stated to have been 7,226,000 gallons, and the waste 6,631,000 gallons daily ! District waste water meters are here essential.

COMPANIES.	Number of Houses.	Daily average Supply in Gallons.	Height of Supply over Thames.	Amount of charge per Company.
				£ s. d.
New River . .	73,212	241	145	1 6 6
Chelsea . .	13,891	168	135	1 13 3
West Middlesex	16,000	185	155	2 16 10
Grand Junction .	11,140	350	152	2 8 6
East London . .	46,421	120	107	1 2 9
South London . .	12,046	100	80	0 15 0
Lambeth . .	16,682	124	185	0 17 0
Southwark . .	7,100	156	60	1 1 3

Cost of house apparatus for private supply from street mains, as averaged by the Board of Health, for first-rate houses, is £3 13s. 2d.; second-rate houses, £2 18s. 6d.; third-rate, £2 3s. 3d.; fourth-rate and cottages, 17s. 5d.; average cost for houses and cottages, £2 8s. 1d.

The actual cost of private works—to take water from mains for the supply of cottages—is shown in the following table :—

Work executed in	Name of Place.	Mean Expense of Private Works for each Cottage.	Annual Value of each Cottage.
		£ s. d.	£ s. d.
Jan. 1852	Rugby, mean of 6 Cottages	1 12 11	5 10 0
Mar. 1852	Croydon . . 10 „	2 0 0	4 0 0
„ 1852	Barnard Castle 11 „	1 18 1½	3 2 6
Aug. 1852	Tottenham . . 6 „	2 11 10½	10 0 0
Mean values for each Cottage . . .		2 0 9	5 13 1½

The water rate charged by the Local Board at Tottenham is given as follows :—

	In the Special District Rate Assessment.		Water Rate per week.	Water Rate per annum.
	Above	And not exceeding		
On Premises assessed.	£ s. d.	£ s. d.	£ s. d.	£ s. d.
"	10 0 0	10 0 0	"	0 2 6
"	15 0 0	15 0 0	"	0 3 9
"	20 0 0	20 0 0	"	0 5 0
"	25 0 0	25 0 0	"	0 6 3
"	30 0 0	30 0 0	"	0 8 0
"	40 0 0	40 0 0	"	0 11 0
"	50 0 0	50 0 0	"	0 14 0

and 3s. for every additional rate of £10.

PUBLIC WORKS OF WATER SUPPLY, PRESTON.

Yards. Cost of Pipes. £ s. d.

44 of 2-in. iron pipes, including valves, fire-plugs, outlet pipes, and all appurtenances, at 1s. 7d.	3	9	8
1,496 of 3-in. ditto, at 3s. 4d.	249	6	8
321 of 4-in. ditto, at 4s. 9d.	76	4	9
625 of 5-in. ditto, at 6s.	187	10	0
30 of 9-in. ditto, at 9s. 6d.	14	5	0

2,516

£530 16 1

Water Supply and its Cost for some Cities and Towns, from a Paper read to the British Association at Leeds, in 1858, by Dr. Strang, of Glasgow. Vide Builder, for 1858, p. 653.

TOWNS.	Population within bounds of Supply.	Daily Supply.	Daily Supply for each inhabitant.	Cost of undertaking.	Daily Supply for every £1 expended.	Prospective Supply daily in addition.
		Gallons	Gallons	£	Gallons	Gallons
London	2,667,917	81,025,842	30·3	7,102,823	11·4	..
Paris	1,100,000	26,350,000	24·	800,000	33·	20,000,000
Hamburg	160,000	5,000,000	31·25	170,000	29·50	..
New York	713,000	28,000,000	39·27	1,300,000	15·5	..
Manchester	500,000	11,000,000	22·	1,300,000	8·5	14,000,000
Liverpool	500,000	11,000,000	22·	1,640,000	7·	..
Leeds	153,000	1,850,000	12·	283,871	7·	..
Edinburgh	215,000	4,800,000	22·3	456,000	10·5	2,000,000
Aberdeen	65,000	1,200,000	18·4	50,000	24·	..
Dundee	96,000	1,750,000	18·2	139,000	12·5	..
Greenock	40,000	2,112,500	52·8	90,000	23·4	..
Paisley	48,000	1,021,452	21·	60,000	17·	..
Glasgow	420,000	16,710,000	39·8	651,199	26·	20,000,000

TABLE SHOWING THE AVERAGE CHARGE PER ANNUM FOR HOUSE SUPPLY IN LONDON,
ARRANGED FROM THE PARLIAMENTARY RETURNS OF 1855.

No.	Companies.	Houses containing 2 Rooms.	Houses containing 3 Rooms.	Houses containing 4 Rooms.	Houses containing 6 Rooms.	Houses containing 8 Rooms.	Houses containing 10 Rooms.	Houses containing 12 Rooms.	Houses containing 16 Rooms.	1st Rate Houses.	2nd Class Houses.	3rd Class Houses.	4th Class Houses.	5th Class Houses.	Horses.	Stables.	Water Closets.	Per centage paid on Capital expended.
1	New River . .	£. d. 10 0	£. d. 15 0	£. d. 1 0 0	£. d. 4 0 1	£. d. 1 10 0	£. s. d. 1 18 0	£. s. d. . .	£. s. d. 4 13 0	£. s. d. 4 0 3	£. s. d. . .	£. s. d. . .	£. s. d. . .	£. s. d. . .	£. s. d. 3 6	£. s. d. . .	£. s. d. . .	£. s. d. 4 7 6
2	East London	£. s. d. 1 0 0	£. s. d. 1 12 0	..	£. s. d. 3 3 0	£. s. d. 3 18 0	£. s. d. 4 13 0	£. s. d. 4 0 3	£. s. d. 0 2 10	£. s. d. 0 2 0	£. s. d. 0 0	£. s. d. . .	£. s. d. 5 0	£. s. d. . .	£. s. d. . .	£. s. d. 5 7 0
3	{ Southwark and Vauxhall . . }	£. s. d. 0 14 0	£. s. d. 1 11 0	..	£. s. d. 2 10 0	£. s. d. 3 3 0	£. s. d. 5 1 0	£. s. d. 3 13 0	£. s. d. 2 6 8	£. s. d. 1 5 0	£. s. d. 12 6 0	£. s. d. 6 11	£. s. d. . .	£. s. d. . .	£. s. d. . .	£. s. d. 4 17 0
4	West Middlesex	£. s. d. 4 10 0	£. s. d. 3 10 0	£. s. d. 2 10 0	£. s. d. 1 15 0	£. s. d. 0 18 6	£. s. d. . .	£. s. d. . .	£. s. d. . .	£. s. d. 6 0 0
5	Lambeth . .	£. s. d. 7 6	£. s. d. 11 0	£. s. d. 0 15 0	£. s. d. 1 2 6	£. s. d. 10 3 0	on ann.	value on Houses	above 6 Rooms	£. s. d. 7 0	£. s. d. 10 0	£. s. d. 2 7 6	£. s. d. 7 6
6	Chelsea . .	£. s. d. 13 0	£. s. d. 17 0	£. s. d. 1 2 0	£. s. d. 10 0	£. s. d. 15 0	£. s. d. 1 7 6	£. s. d. 7 6
7	Grand Junction	£. s. d. 4 15 0	£. s. d. 1 5 0	..	£. s. d. 2 2 0	£. s. d. 2 15 0	£. s. d. 4 4 0	£. s. d. 10 0	£. s. d. . .	£. s. d. 6 2 6	£. s. d. 2 6
8	Kent	£. s. d. 2 0 0	£. s. d. 1 13 0	£. s. d. 1 0 0	£. s. d. 16 0	..	£. s. d. 10 0	£. s. d. . .	£. s. d. 5 0 0	£. s. d. 5 0 0
9	Hampstead . .	£. s. d. 10 0	£. s. d. 15 0	£. s. d. 1 0 0	£. s. d. 1 10 0	£. s. d. 2 0 0	£. s. d. . .	£. s. d. . .	£. s. d. 1 13 0	£. s. d. 13 0
{ Average Annual Charge . . }		£. s. d. 10 1½	£. s. d. 14 6	£. s. d. 0 18 0	£. s. d. 1 7 5	£. s. d. 15 0 2	£. s. d. 8 8	£. s. d. 3 5 4	£. s. d. 4 12 8	£. s. d. 3 10 6	£. s. d. 2 12 5	£. s. d. 1 16 6	£. s. d. 5 10½	£. s. d. 0 12 8½	£. s. d. 4 3	£. s. d. 9 8	£. s. d. 12 6 4	£. s. d. 2 6

The cost of pumping varies with circumstances ; we believe that pumping engines cannot be put down at less than from £60 to £100 per horse power, dependent on the size of the engine, although the Board of Health adopted a standard of £50 per horse power. For the town of Drogheda we estimated for two engines at £75 per horse power. The following information respecting the cost of the Waterworks, Cork, was kindly furnished to the author by Sir John Benson, the engineer, who designed and carried out the works.

CORK WATER WORKS.

		£	s.	d.
Steam engine 100-horse power.	Direct acting Cornish Engine with three cylindrical flue boilers, including engine and boiler house, setting boilers, chimneys, &c., &c., per horse power	55	0	0
Two 50-horse power turbines.	Two turbines completed with four 11 in. ram pumps on each, including buildings, cisterns, sluices, gates, screens, per horse power	44	0	0
Reservoirs—				
One of 3,500,000 gallons.	One reservoir on a level of 186 ft. over weir	4,900	0	0
One of 563,000 gallons.	One reservoir on a level of 360 ft. over weir			
Cost per head.	The inhabitants in 1851, 86,000	0	15	3½
	The inhabitants in 1861, 100,000	0	13	0
	City valuation, £112,000	0	11	7
Valuation standard per pound on the valuation.				
Yearly cost per five inhabitants.	Distribution per house of every five persons	0	5	0
Water supplied.	Quantity supplied, including manufacturing, to one person per day	30		gallons.

The total estimated cost of engines, including pumps, engine houses, wells, &c., for raising the London sewage, is £70 per horse power, and the annual cost £20 per horse power.*

* Main Drainage Report, 1857, p. 29.

When coals are 10*s.* per ton, the cost of an engine exceeding 100-horse power, single acting Cornish, working night and day, will be £10 per horse power; when coals are 15*s.* per ton, the cost would be £13 per horse power; when coals are 20*s.* per ton, the cost would be £16 per horse power; when coals are 25*s.* per ton, the cost would be £19 per horse power. These estimates have been given by Mr. Hughes, and include every expense of coals, wages, oil, tallow, materials for packing, cleaning, &c., but none for interest of capital or depreciation of machinery.*

At Ely the cost of pumping is stated by a writer in the *Builder* to be as follows:—

To pump one million gallons 140 feet high, the old engine consumes:—

	£	s.	d.
Four tons of coal, at 16 <i>s.</i> per ton	3	4	0
Oil, tallow, and packing	0	12	0
Wages	0	9	0

Total cost of pumping one million gallons 4 5 0
 which gives 1*d.* per 1,000 gallons pumped 140 feet high (not a very high price).

The new engine requires:—

Five and a half tons of coal at 16 <i>s.</i>	4	8	0
Oil tallow, and packing	1	10	0
Wages	1	2	0

Total cost of pumping one million gallons 140 feet high 7 0 0
 which is 65 per cent. more money than the old engine requires.

While another writer in the same periodical states, that the cost of pumping 1,000,000 gallons with the old engine was £4 18*s.* 8¼*d.*, and with the new engine,

* Main Drainage Report, 1857, p. 447.

ESTIMATED COST OF ENGINES FOR PUMPING AND OTHER INFORMATION.

Description of Works, and Engineers' estimates, with short description of engines.	Millions of Gallons daily.	Height to be raised in feet.	Millions of Gallons to be raised 1 foot in 24 hours.	Estimated cost in £s.	Work to be done in units of 33,000 lbs. raised 1 foot high per minute, or horse power	Cost for each unit of 33,000 lbs. raised 1 foot high per minute, or horse power, in £s.
Daglish's estimate for Liverpool Works, exclusive of buildings—one engine and pumps	2	300	600	8470	126-26	67-1
Ditto Two engines and pumps	2	300	600	9850	126-26	78-0
Ditto For one engine and pump	1	75	75	3400	15-78	215-4
Homersham, for Watford supply	8	174	1392	35,357	292-92	120-7
Forester & Co.'s estimate for Liverpool engines, one or two, exclusive of buildings	2	200	600	9700	126-26	76-8
Ditto ditto ditto	1	75	75	3200	15-78	202-8
Hurry and Bateman's estimate, Wolverhampton Water Works	1 1/4	314	471	1188	349-11	101-4
Harvey and West's for ditto, exclusive of buildings, 84 inch cylinder engine	1 1/2	306	459	11,000	96-59	113-9
Ditto ditto 64 inch cylinder engine	1 1/2	180	270	7000	56-82	123-2
Ditto ditto 38 inch cylinder engine	1 1/2	140	210	6500	44-19	147-1
Messrs. Hawthorne for ditto, double power expansive condensing beam engines, exclusive of engines	1 1/2	314	471	6055	99-11	61-1
Ditto	1 1/2	163	244 1/2	2520	61-45	48-9
Messrs. Hawthorne's high-pressure double acting horizontal engines, to be raised in 6 hours	1 1/2	22	132	1170	27-78	42-1
Ditto to be raised in 9 hours	1 1/2	22	108	780	22-73	34-3
Ditto to be raised in 12 hours	1 1/2	22	66	570	13-89	41-0
Mr. Hocking's estimate for Wolverhampton, single acting Cornish	1 1/2	500	750	20,800	157-83	131-8
Ditto exclusive of buildings	1 1/2	500	750	13,200	157-83	83-6
Ditto to be raised in 12 hours, by two 60 inch, two 45 inch, and one 36 inch cylinder	1 1/2	500	1500	32,000	315-65	103-3
Ditto exclusive of buildings	1 1/2	500	1500	21,500	315-65	69-0
Mr. Quick's estimate, for Grand Junction Works, one 64, or two 45 inch cylinders, single acting Cornish	5	46	230	7000	48-40	144-6
Ditto for Southwark and Vauxhall	8	40	320	7000	67-34	103-9
Ditto for West Middlesex	5	46	230	10,000	48-40	206-6
Sandys, Vivian & Co., two engines for Liverpool, exclusive of buildings	2	300	600	8000	126-26	63-4
Ditto one engine, exclusive of buildings	1	75	75	1800	15-78	114-1
Seaward & Capel's, for Wolverhampton, exclusive of buildings	1 1/2	566	849	25,000	178-65	123-2
West's estimate, 65 inch cylinder, exclusive of buildings	1 1/2	314	471	6000	99-11	69-5
Ditto 50 inch cylinder, including buildings	1 1/2	163	244 1/2	7100	51-45	138-0
Ditto exclusive of buildings	1 1/2	163	244 1/2	5000	51-45	97-2
Ditto raised in 6 hours, by a 35 inch cylinder engine	1 1/2	22	132	4600	27-78	165-5
Ditto exclusive of buildings	1 1/2	22	132	3100	27-78	111-6
Ditto including duplicate engines	1 1/2	566	849	38,200	158-66	240-8
Ditto 65 inch cylinder engine, including buildings (?)	1 1/2	314	471	8400	99-11	84-8
AMERICAN ESTIMATES AND WORKS.						
Mr. McAlpine's, for Brooklyn, double acting, expansive, high-pressure, condensing engine, 72 inch cylinder engine, to be raised in 12 hours, exclusive of buildings	5	190	1950	18,000	399-83	45-0
Ditto non-condensing 30 inch cylinder engine, raised in 24 hours, exclusive of buildings	5	190	1035	3000	199-92	15-0
Ditto in 12 hours, exclusive of buildings	10	190	3800	39,000	799-66	48-7
Ditto exclusive of buildings	20	190	7600	73,000	1599-23	33-1
Ditto ditto	30	190	11,400	85,000	2398-99	35-4
Ditto Albany Water Works, 58 inch condensing beam engine, and one duplicate not condensing, working for day only	2	156	624	13,200	231-48	57-5
Ditto Chicago Works, as in last, including buildings, 46 inch cylinder condensing engine and duplicate, as in last	1	238	476			
Ditto 48 inch cylinder, &c.	3	107	642	11,258	135-10	83-3
	3	116	696	11,642	146-46	79-5

£4 10s. 7d. In the preceding table, arranged from information in Mr. Hughes' book,* the estimated cost of pumping engines for various works, English and American, is given.

In EXAMPLE 28, pages 25 to 27, we have pointed out the method of calculating the increase of horse power required in raising water through pipes from friction, and also the great increase of this extra head if the velocity increases; the increase being nearly as the square of the velocity. In addition to this, an allowance of horse power must be made for bends, curves, junctions, and other obstructions, for the effects of which see SECTION XI. The more slowly the water is pumped, the less will the loss be from these causes through the same pipe. It is therefore, so far, advisable to give as large a diameter to the pipes supplying a reservoir from a pumping engine as other aspects of the question, cost, and engine power, will admit.

A report by the Water Committee of Plymouth, printed in a local newspaper of 13th October, 1864, contains much useful information respecting the water supply of the following places at that time:—

BRISTOL (population 140,000).—This city is supplied by a company drawing its water from the Mendip-hills; the pipes being too small and quantity deficient, it is not continuous, nor is the quality good. The scale of rates ranges from 5 per cent. on low rentals to 3 per cent. on rentals of £100, and $2\frac{1}{2}$ per cent. on rentals of £200 and upwards. For trade purposes the water

* WEALE, London.

rate is 6*d.* per 1,000 gallons the minimum, to 1*s.* 6*d.* per 1,000 gallons the maximum. Water closets, stables, baths, &c., charged extra to domestic supply and reduced rates—no overflow or waste pipe permitted to communicate with any cistern or bath unless supplied by meter. No cistern for closet containing more than two gallons allowed without extra payment. The company undertakes plumbers' work on moderate terms.

GLOUCESTER (population 30,000).—The Local Board of Health hold the water works in trust for this city. For domestic purposes the rates are moderate, houses under £10 paying 8*s.* 8*d.* per annum; from £10 to £60, 5 per cent.; £60 to £70, 3½ per cent.; £70 to £80, 3½ per cent.; above £80, 3½ per cent. Meter rates were only determined on in December, 1862; range from 6*d.* per 1,000 gallons on the million and upwards, to 1*s.* per thousand gallons under 100,000 gallons. Service box cisterns are not enforced, although generally adopted by the better class of consumers.

DERBY (population 45,000).—A private company supplies this city. The supply is constant at high pressure, and is of good quality. All house apparatus and fittings are in accordance with the regulations of the company, and subject to the inspection of their officers. Service box cisterns to closets are strictly enforced. No overflow or waste pipes are permitted to cisterns without meters, and rain water carefully excluded therefrom. The scale of rates for domestic use and by meter is moderate. The Local Board of Health contracts for the supply of baths and wash-

houses, at the rate of 3*d.* per 1,000 gallons. Water for streets, when not drawn from the river, is charged at the lowest meter rate. The consumption is rather above 19 gallons per head per day, including numerous wells and large manufactories.

NOTTINGHAM (district population, 76,000). — We cannot say too much in commendation of the superior arrangement and management of the water works of this town, for whilst the greatest economy is used, an abundant amount of contentment is manifested by the consumers: the consumption averaging 17 galls. per head per day. A constant high pressure supply has been maintained by the company for the last 20 years. Overflow or waste pipes to cisterns are prohibited, but warning pipes in exceptional cases fitted with the approval of inspectors. All water closet cisterns are fitted with service boxes, and in no case is rain water allowed to flow into any such cisterns. No supply is allowed to be laid on or apparatus fixed by any other than an authorised plumber or the workmen of the company. The rates vary according to the level supplied: consumers by meter pay—

		Price per 1,000 gallons.		
		Lower.	Middle.	Higher.
		<i>d.</i>	<i>d.</i>	<i>d.</i>
Not exceeding	50,000 galls.	6	9	12
„ „	400,000 galls.	4½	6¾	9
Exceeding	1,600,000 galls.	3	4½	6

Tanks with meters affixed are placed in suitable parts of the town for supplying carts for street watering, a cart being filled in three minutes, the Local Board paying the lowest meter rate. The company have

adopted call-books for complaints, repairs, &c., plumber's book for instruction, and issue cards for securing attention to the work required to be done.

NORWICH (population 75,000).—The water works of this city furnish another example of good management. The average consumption for private and public purposes is $14\frac{1}{2}$ gallons only. A beneficial change is due entirely to the zealous care in distribution, seconded in a praiseworthy manner by a discriminating public. The company does a large portion of the plumbing and water fittings, the best feeling exists between the various tradesmen and the officers of the company. The service box cisterns here provided for closets are very simple, effective, and not liable to get out of order; iron rods take the place of wire. The cost is also so small as to be within reach of the poorer classes. Patterns of those and cast-iron street or courtyard stand pipes will be submitted to the inspection of the Plymouth Water Committee. The same regulations are in force here as at Nottingham as to domestic supply, &c. The rates are moderate, commencing at 4*s.* 4*d.* per annum for tenements under £5 per annum; above £5 and under £100, 5 per cent.; above £100, $4\frac{1}{2}$ per cent. This is exclusive of water closets, which, with stables, gardens, &c., are charged extra. Meter rate—Not exceeding 200,000 gallons per annum, 1*s.* per 1,000 gallons; not exceeding 1,000,000 gallons per annum, 10*d.* per 1,000 gallons; exceeding 1,000,000 gallons per annum, 8*d.* per 1,000 gallons; Local Board for street watering, if amounting to 7,000,000 gallons per annum, 7*d.* per 1,000 gallons. It might be noticed that the Town Council of this city

guaranteed the Water Company 5 per cent. on their outlay, after which the Council was to receive a moiety of the profits. The civic authorities of Edinburgh have adopted the arrangements carried out in this city, and we heartily recommend their application where, necessary, for Plymouth.

LEICESTER (population 69,000).—The supply of water to this town is in the hands of a private company, who have expended the sum of £90,000. The Local Board of Health holds 680 shares, and is entitled to half the profits after a dividend of 5 per cent. shall have been paid to the shareholders. The water is at high pressure and continuous. Storing cisterns for house purposes are not much used, but if adopted must be without waste pipes, or inlet of rain water. Water closets in all cases are fitted with flushing service boxes, or must be self-acting apparatus. The scale of rates ranges from 5 per cent. on low rentals to $8\frac{1}{2}$ per cent. up to £100, and 3 per cent. above £200. Water rates range from *5d.* per 1,000 gallons the minimum to *10d.* per 1,000 the maximum. The Local Board of Health is charged $2\frac{1}{2}d.$ per 1,000 for street watering, having meters attached to the mains. The company's regulations to prevent waste of water are strictly enforced.

GREAT YARMOUTH (population 30,000).—This town has the benefit of a well-governed water company. There is a constant supply at high pressure. The scale of rates is 6 per cent. on the rental up to £100 per annum, with 5 per cent. on the excess in addition—this including one water closet only—*5s.* per annum is charged for all others in addition, and *10s.* for baths.

The meter rate is also high, ranging from 2s. per 1,000 gallons to 1s. 3d. The Local Board has an especial rate for watering the streets. Water-closets are in all cases fitted with double-valve service boxes ; but few cisterns for domestic supply are in use (not being needed), but in these overflow and waste pipes are prohibited. The manager of the company will, however, permit detective or warning pipes where necessary. The company is willing to execute all plumbers' work if required, but all such work must be done under inspection. We have during our tour of inspection kept in view the object for which it was proposed, namely, that of ascertaining the means by which a constant supply of water may be secured to the inhabitants of this borough, and to suggest the practical application of such means. The attainment of so desirable an object can be secured very speedily by the submission of water consumers to the absolute control of appointed officers over all fittings, and the adjustment of apparatus of every kind. Having witnessed the beneficial effect of such wholesome regulations as have been referred to in the preceding remarks, we cannot but anticipate similar advantages by their adoption.

IN PLYMOUTH.—We desire therefore to recommend the general application of the rules and regulations as adopted in Nottingham and Norwich, which embody among them the following provisions—1st, that all applications for the supply of water, notice of insufficient supply, and other complaints, be recorded in a call book ; that visiting cards be issued authorising the attendance of the workmen necessary, and a com-

plete registry being kept of all such work performed ; 2nd, that wherever practicable, cheap water closets be recommended in lieu of open privies ; 3rd, that all water closets be fitted with full and complete apparatus for flushing by means of service cisterns, or such other description of closets as shall be approved, and that valves be worked by rods instead of wires or chains ; 4th, that cisterns be without overflow or waste pipes, but, with the approval of officers, detective or warning pipes be substituted ; 5th, that high pressure taps be introduced with new fittings, and all drawing and ball taps to be of the approved kinds : in open court yards and exposed places, taps to be protected with iron casing, and be made to open with keys supplied to the ratepayers only ; 6th, that wire gauze screens, in the absence of filtration, be placed where desired by your surveyor. We also further recommend that as soon as practicable the condition of all the fittings and premises at present supplied with water be duly registered, with a view to an early repair and correction where necessary. It is not necessary, in adopting the preceding recommendations, that the supply of water shall in any degree be stinted, but *the exercise of a moderate amount of economy would enable a constant supply to be given*, and would doubtless tend to the development of many branches of manufacture in the town in which water forms an essential. The domiciliary visits for the inspection of premises would be in no way offensive, but would be of the same nature as those now made for inspection of gas apparatus, and we have the evidence of numerous householders in towns we have visited that the greatest

respect and civility are manifested. It is not our aim or desire to abolish cisterns now in use, *but the CONSTANT SUPPLY SYSTEM will render so large an expenditure unnecessary in future*, cisterns for flushing closets being then only necessary.

THICKNESS OF PIPES FOR WATER WORKS.

It is evident that the thickness of a pipe should be at least sufficient to bear the pressure of the atmosphere, and therefore the whole pressure in a pipe is best expressed by a determinate number of pressures, each equal to that of a column of water 33 feet high. If n be the number of such pressures, or the number of units each equal to 33 feet high, d the diameter of the pipe in inches, and t the thickness, also in inches, we shall have for

(A.)	1.	Iron pipes, plate	$t = \cdot 0009 \, n \, d + \cdot 13$
	2.	Iron pipes cast horizontally	$t = \cdot 0024 \, n \, d + \cdot 33$
	3.	Iron pipes cast vertically	$t = \cdot 0016 \, n \, d + \cdot 32$
	4.	Copper pipes, plate	$t = \cdot 0015 \, n \, d + \cdot 16$
	5.	Lead pipes	$t = \cdot 0024 \, n \, d + \cdot 19$
	6.	Zinc pipes	$t = \cdot 0051 \, n \, d + \cdot 16$
	7.	Artificial stone	$t = \cdot 0054 \, n \, d + 1 \cdot 60$

For cast-iron pipes the engineer of the Paris water works, M. Dupuis, adopted in his practice a formula which is equivalent to

$$(B.) \quad t = \cdot 0016 \, n \, d + \cdot 32 + \cdot 013 \, d$$

in the foregoing measures. This formula may also be expressed as follows:—

$$(C.) \quad t = (\cdot 0016 \, n + \cdot 013) \, d + \cdot 32.$$

If d be 12 inches, and $n = 9$, corresponding to a pressure of 297 feet, we shall find from the last equation, $t = (\cdot 0144 + \cdot 013) \times 12 + \cdot 32 = \cdot 3336 + \cdot 32$

= .6536 inch. All pipes should however be proved with ten atmospheres, or 330 feet, and in practically applying the above formulæ in equation (A), for finding the thickness of pipes, the value of n should always have 10 added to it. Hence, applying formula (A), No. 3, to our example, we get $t = .0016 \times 19 \times 12 + .32 = .6848$ inch, which is the same practically as found from equation (C).

SEWERAGE COST.

As for water-works, the minimum rain-fall of a district should be calculated upon; so the maximum fall must be considered for sewerage and drainage works. We have already shown, page 340, that for a population of 80 persons per statute acre, and a discharge of two-fifths of an inch in eight hours, sewers should be calculated to discharge about $3\frac{1}{2}$ cubic feet per minute, the rain supply being about seven times the house supply, or sewage, including house water supply. Instances are quoted in which the discharge, after a heavy rain-fall, amounted to $20\frac{1}{2}$ cubic feet per minute per acre, as in the Savoy-street sewer, which of course was principally surface water, as the sewage of 80 persons at 7 cubic feet per person, one-half of which, if discharged in eight hours, would only be $\frac{80 \times 7}{8 \times 2} = 35$ cubic feet per hour, or $\frac{35}{60} = .59$ feet nearly per minute, which is only about the thirty-third part of $20\frac{1}{2}$ feet. In other words, the storm waters were thirty-three times the amount of house sewage. It would be waste to provide drainage for so much

surface water considered in itself, where it can be passed off from the surface channels. But sewage is not water, and it is essential, in the greater number of cases, that sewers should be flushed occasionally. It is absurd to calculate the size of sewers, as if the sewage matter were thoroughly diluted or passed off like water. In fact, the sewage in part lies at the bottom of the sewer, or is deposited there in nine cases out of ten, while the house supply of water passes on and escapes over it, removing only diluted and detached portions. It is, therefore, of importance, where artificial flushing and cleansing out are not provided, that storm waters should occasionally pass through and flush a system of sewers, particularly the main or arterial lines. An engineer must be guided, in calculating the dimensions, &c., of main sewers, by the circumstances of each case. The inclinations to be obtained, the form of the bottom or invert, the rain-fall, the amount of sewage which will not affect the size to any considerable extent, the material and the cost consistent with permanency.

The discharging power of a water channel is more than doubled by increasing its dimensions by one-third; and it is increased in the proportion of 5·7 to 1 by doubling the dimensions. By giving four times the fall, the same channel will only double the discharge. Now a pipe 2 feet in diameter with a fall of 1 in 200, would discharge fully 1000 cubic feet of water flowing full with a velocity of 5·4 feet per second: at $3\frac{1}{2}$ cubic feet per minute per acre, for a population of 80 to the acre, the thoroughly diluted sewage of 280 acres would be passed off by one such pipe; that is,

the sewage from 20,400 persons, on 280 acres, and also two-fifths of an inch of rain falling for eight hours, can be conveyed off by a 2 feet pipe, with a fall of 1 in 200. But as this rain supply is about seven times the house supply, passing $2\frac{1}{2}$ feet per person off in eight hours, made up of fæces and used-up water supply, it is apparent that such a pipe would convey about eight times the sewage alone of the district, if flowing as water; and, under any circumstances, would be abundantly large for the duty, even when assuming the whole quantity to pass in at the upper end. For a fall of 1 in 800, two such pipes would be required, or one pipe 32 inches in diameter; for a fall of 1 in 3,200, four 2 feet pipes would be required, or one pipe 3 feet 6 inches.

House drains should not be less than 6 inches in diameter, and should have facilities for being cleaned, either by using half-flange joints, or by having a moveable upper segment. The inclination for these drains should be uniform, but the amount is not so important as some appear to think, if proper provision be made for cleaning. Where flushing is used, cast-iron pipes are the best, but they are also the most expensive. House drains of brick with a V tile bottom covered with flags or bricks are perhaps the best, as the capacity can be considerably augmented by adding to the height of the sides, and they can be at all times easily opened and cleaned. If inclinations from 1 in 50 to 1 in 20 can be had, so much the better. The following items as to cost have been selected from the "Builder":—

COST OF SEWERS, NEWPORT, MONMOUTHSHIRE.

Total lengths.	Average depths.	Sizes of sewers.	Thicknesses.	Cost per foot lineal.
feet.	ft. in.	ft. in. ft. in.	in.	s. d.
1,322	15 6	4 6 by 3 6	9	11 8
2,217	13 0	4 6 by 3 0	9	10 1½
6,110	12 0	3 0 by 2 2	9	7 7½
12,354	11 8	3 0 by 2 2	6	5 3½
1,953	9 3	2 6 by 1 10	6	4 7
9,663	10 0	2 6 by 1 10	4½	3 8½
690	10 2	2 3 by 1 9	4½	3 5½
3,264	8 6	1 2 diameter	4½	2 4½

COST OF SEWERS AND PIPES IN PRESTON.

The following extract from a published summary of public works executed during the year ending April 30th, 1859, contains some useful information:—

Yards.	£	s.	d.	£	s.	d.
60 of Brick Sewers, 2 ft. 6in. diameter at 7s.	21	0	0			
538 3ft. by 2ft., at 17s. 6d.	470	15	0			
294 3ft. 6in. by 2ft. 4in., at 28s.	412	12	0			
372 3ft. 9in. by 2ft. 6in., at 28s.	520	16	0			
250 4ft. 3in. by 2ft. 10in., at 41s. 9d.	521	17	6			
56 4ft. 6in. by 3ft., at 75s. 7d.	211	12	8			
66 4ft. 6in. diameter, at 40s. 9d.	134	9	6			
				2,293	2	8
1,636						
42 of Cast-iron Sewer, 2ft. diameter, at 36s.				75	12	0
22 of Earthenware Pipe Sewer, 6in. diameter, at 4s.	4	8	0			
1,129 9in. diameter, at 7s. 5d.	418	13	5			
565 12in. diameter, at 8s. 9d.	247	3	9			
88 15in. diameter, at 11s. 3d.	49	10	0			
98 18in. diameter, at 13s.	63	14	0			
145 21in. diameter, at 18s. 6d.	134	2	6			
				917	11	8
2,089						
Total, including superintendence, also man-holes, street gullies, and all appurtenances	£3,286	6	4			

TABLE showing the prices of Tubular Drains as made by the Board of Health in 1852, fifty per cent. being added for profit, &c. ; and the sale prices in the market.

Diameter in inches.	Lengths.	Red earthenware pipes made by the Board.	Red pipes at Sale prices.	Stoneware glazed at Sale prices.	Assumed gain.			
					On red ware pipes.		Over glazed stoneware pipes.	
5	For 1,000 feet	£ 6 15 0	£ 20 16 8	£ 25 0 0	£ 14 1 8	£ 18 5 0		
6	For 1,000 feet	9 14 0	25 0 0	29 3 4	15 6 0	19 9 4		
9	For 1,000 feet	15 1 6	37 10 0	50 0 0	22 8 6	34 18 6		

Did the Board of Health here add the cost of their own establishment and staff to the cost of production? The manufacturer and salesman must surely live, at least the Author thinks so.

The following estimates were made for laying pipes at Tottenham, not including their cost :—

Diameter of pipe in inches.	Depth 6 feet.	Depth 8 feet.	Depth 10 feet.
6	8½d.	11d.	12d.
9	9½d.	14½d.	15½d.
12	11½d.	15½d.	19½d.

The cost of laying alone at St. Thomas's, Exeter, was—

6 inch pipes	5d. per foot lineal	3 to 4 feet deep.
9 "	5d. "	3 to 4 feet deep.
12 "	8d. "	5 feet deep.
15 "	9d. "	5 feet deep.
18 "	11d. "	5 feet deep.
2d. per foot lineal for relaying pitching ; 4d. for macadamised roads ; and 6d. for pavements.		

Relative Cost of Earthenware Pipe Drainage on executed works previous to 1852. From Minutes of Information collected by the General Board of Health, pp. 179 and 180, ordered to be printed for the use of Local Boards and their officers. [W. have altered the cost to the next penny where half-pence and farthings are stated in the original. The cost of junctions is not shown, but it is stated to amount to one-eighth in two of the towns, and one-tenth in two others.]

Diameter of pipes in inches	CLAYTON. Pipes laid 9 feet deep.			BARNSLEY GARRA. Pipes laid 9 feet deep.			SOUTHAMPTON. Pipes laid 9 feet deep.			HITCHIN. Pipes laid 8 feet deep.			OAKMARK. Pipes laid 8 feet deep.		
	Cost of pipes per yard delivered.	Cost of laying pipes per yard run.	Total cost of pipes laid per yard.	Cost of pipes per yard delivered.	Cost of laying pipes per yard run.	Total cost of pipes laid per yard.	Cost of pipes per yard delivered.	Cost of laying pipes per yard run.	Total cost of pipes laid per yard.	Cost of pipes per yard delivered.	Cost of laying pipes per yard run.	Total cost of pipes laid per yard.	Cost of pipes per yard delivered.	Cost of laying pipes per yard run.	Total cost of pipes laid per yard.
21	10 0	3 3	19 3	8 9	5 0	13 9	7 0	1 8	8 8
20	8 0	3 3	11 3	7 3	2 9	10 0	6 0	1 8	7 8
18	6 0	3 2	9 2	5 5	2 6	7 11	4 3	1 7	5 10
15	3 6	3 1	6 7	5 0	1 10	6 10	6 0	3 7	9 7	3 3	2 4	5 7	2 6	1 7	4 1
12	2 2	2 9	4 11	3 2	1 10	5 0	3 6	3 5	6 11	2 0	2 3	4 3	1 5	1 6	2 11
9	1 3	2 6	3 9	1 3	1 8	2 11	1 4	2 8	4 0	1 3	2 2	3 5	0 11	1 6	2 5
6	0 10	2 2	3 0	0 11	1 8	2 7	0 11	2 2	3 1	0 8	1 6	2 2
4
	RUSSY. Pipes laid 9 feet deep.			BARNDALE. Pipes laid 6 feet deep.			TOTTENHAM. Pipes laid 5 to 13 feet deep.			ST. THOMAS'S, KENT. Pipes laid 3 to 7 1/2 feet deep.			ORRY ST. MARY. Pipes laid 8 feet deep.		
	Cost of pipes per yard delivered.	Cost of laying pipes per yard run.	Total cost of pipes laid per yard.	Cost of pipes per yard delivered.	Cost of laying pipes per yard run.	Total cost of pipes laid per yard.	Cost of pipes per yard delivered.	Cost of laying pipes per yard run.	Total cost of pipes laid per yard.	Cost of pipes per yard delivered.	Cost of laying pipes per yard run.	Total cost of pipes laid per yard.	Cost of pipes per yard delivered.	Cost of laying pipes per yard run.	Total cost of pipes laid per yard.
24	3 6	3 3	13 3
21	8 5	2 9	11 2	8 0	2 9	10 9
20	7 2	2 9	9 11	7 4	2 5	9 9	6 0	2 3	8 8	6 6	2 5	8 11
18	5 5	2 6	7 11	5 5	1 8	7 1	6 0	2 3	8 3
15	3 3	2 6	5 9	3 11	1 9	5 8	3 5	1 5	4 10	3 8	2 0	5 8	3 3	2 2	5 5
12	2 0	2 0	4 0	2 5	1 9	4 2	2 1	1 0	3 1	2 3	1 3	3 6	2 0	1 4	3 4
9	1 8	0 11	2 7
7 1/2	1 2	0 9	1 11	1 4	1 3	2 7	1 2	1 2	2 4
6	1 2	2 0	3 2	1 5	1 6	2 11	1 0	1 0	2 0	0 11	1 1	2 0
4	0 11	1 9	2 6	0 11	1 6	2 7	0 10	1 0	1 10
3	0 9	1 9	2 8	0 8	1 0	1 8
2

ESTIMATE FOR SEWERS AT BRIGHTON.

DESCRIPTION OF SEWERS.	Length in yards.		Price per yard.	Amount.	
<i>Brick Sewers :—</i>					
Diameter.			£ s.	£ s.	
6 ft.	4,850		3 10	16,975	0
4 ft. 6 in.	350		2 10	875	0
4 ft. 6 in. by 3 ft.	4,000		2 8	9,600	0
3 ft. 9 in. by 2 ft. 6 in.	1,890		2 2	3,969	0
3 ft. by 2 ft.	2,820		1 16	5,076	0
2 ft. 8 in. by 1 ft. 6 in.	8,580		0 18	7,722	0
Total brick sewers		22,490			
<i>Earthenware Pipe Sewers :</i>			s. d.		
15 inches diameter	9,466		13 6	6,389	11
12 " " " "	44,430		10 0	22,215	0
Total earthenware pipe sewers		53,896			
<i>Cast-iron Pipe Sewers :—</i>			£ s.		
3 in. diameter	750		7 0	5,250	0
1 ft. 6 in. " "	1,260		3 0	3,780	0
Total cast-iron pipe sewers		2,010			
Total length of sewers		78,396			
Or 44 miles 956 yards					
Man holes and ventilating shafts		Number			
Lamp-holes		600	20 0	12,000	0
Gullies		600	4 0	2,400	0
Outlet works, overflows, and extra work on steep gradients, &c.		3,000	3 10	10,500	0
Contingencies, including repairs, &c., of existing sewers, 10 per cent.				5,000	0
				11,178	9
Total				£122,930	0

The author has constructed a large quantity of main sewers, from 18 inches to 2 feet and 2 feet 6 inches wide, and 4 feet 6 inches high; the side walls built with rubble masonry, 9-inch segment invert laid with

4½-inch courses in cement; the top sometimes flagged, when flags of sufficient length could be procured, and sometimes arched with rough rubble arches. The invert was laid on, well bedded, well rammed, rubble to prevent subsidence, and preserve the bottom inclination uniform. The cost, at an average depth of about 9 feet, was 9s. per running foot, the side walls being about 18 inches thick. Upright side walls, where rubble is cheap, have many advantages in giving a considerable increase of capacity for a small outlay. The tenement and house drains were of earthenware pipes. Cast-iron gully grates and traps, weighing 3 cwt., cost 30s. each; the grate fastened by a wrought-iron chain.

The following regulations were laid down for Cambridge and Carlisle :—

STIPULATIONS FOR CAMBRIDGE DRAINAGE.

“Water from the rear of premises should not be conveyed to the front under the basement floor.

“Rain-water from the roofs should not be conveyed into the basement, but conducted into the sewer by shallow drains.

“Cast-iron pipes may be used for basement drains in some instances.

“The scullery sink should be kept as high as possible, and approached by a step. A flat trap should be fixed between the sink and sewer.

“There should be no water-closet on the basement floor; if it cannot be arranged elsewhere, the soil-pipe should have a flap trap, or similar contrivance, to prevent the influx of sewage water.”

FOR CARLISLE DRAINAGE.

“STIPULATION 1.—If water-closets are to be generally used, the description of such to be sanctioned by the Board, the same to be fixed to the satisfaction of the Surveyor.

"2.—All down-spouts to be connected with the sewers where it may be proper to connect the same ; in all cases where they are not connected with the sewer they are to be connected with the channel.

"3.—All stench traps to be similar to samples furnished by the Surveyor, or others approved by him, and properly fixed to his satisfaction.

"4.—All sewers to water-closets not to be less than six inches diameter.

"5.—All sewers to yards, stables, kitchens, and sculleries, not to be less than four inches diameter.

"6.—In every case the whole of the fall to be made available from the junction with the main sewer to the end of the private drain, that is to say, only one inclination to be used from the junction with the public sewer to the end of the private drain ; and all branches from the private drain to sinks, water-closets, &c., to have one inclination from the junction of such drain. None of the above instructions to be departed from without the express sanction of the Surveyor.

"7.—In no case must a private drain be put in with a less fall than one in fifty, without the sanction of the Surveyor.

"8.—No pipes, water-closets, stench traps, gullies, kitchen sinks, bends, junction or tapering pipes, to be used without being approved by the Surveyor.

"9.—All ash pits and dung depôts to be raised to the level of the adjoining ground, to be properly paved and drained as the Surveyor may direct.

"10.—All buildings, outhouses, &c., to be properly spouted, and the water conveyed into the sewers where approved of by the Surveyor."

THOROUGH LAND DRAINAGE.

The following instructions and general specifications, have been prepared by the Commissioners of Public Works in Ireland, for the use of the district inspectors, and persons reporting on thorough-drainage. The drains are made in general parallel, and to suit the fall of the ground. The depths must alter in order that the bottoms should have an uninterrupted fall, and may vary from 2 feet to 4 feet 6 inches in practice,

averaging, say about 3 feet 6 inches, but dependent on circumstances. The portions printed in italics are from specifications prepared by officers of the Board, and are varied according to each particular case :—

GENERAL OBSERVATIONS.

“No drainage works should be undertaken until it has been clearly ascertained that the surface level of the maximum floods in the main drain can be discharged at a level that will admit of the submain drains venting the waters from the lowest point of the lands proposed to be thorough-drained, at a level sufficiently below the surface of such land, that the highest floods shall not prevent the free discharge of such submain.

“When sufficient out-fall can be obtained, no open main drain should be of a less depth than five feet, and in all cases a greater depth is desirable, in order to insure a permanent and efficient drainage, and at the same time to prevent cattle, &c., from crossing.

“As it has been found by practical experiments on different varieties of soils, that deep drains, say from four to five feet deep, are more effective than shallow ones : they should always be estimated for, when the open main drains admit of their being cut to that depth, or when, by a moderate outlay per acre, the main drains can be cut to a sufficient depth ; the distance between the parallel drains must necessarily vary with the texture of the soil,—forty feet may be taken as a general rule.

OPEN MAIN DRAINS.

“Main drains should have gradients of such inclination, and be sunk to a depth that will admit of the above stipulations, as to the discharge of the submain drains being carried out. They should have such width at bottom and side slopes as may be necessary ; and be free of sharp angles, projecting stones, and other impediments to the quick discharge of the waters.

“The spoil or material raised in sinking and improving the drains, where not available for filling up useless holes or drains, should be removed to a proper distance from the edge of the main drains, and dressed off in a workmanlike manner.

“The abutments and piers of such bridges as have sufficient breadth of water-way, should, if necessary, be carefully under-pinned ; and

those bridges which are insufficient to discharge floods, should be taken down and rebuilt of suitable dimensions.

COVERED MAIN DRAINS.

“Whenever, from the nature of the lands, the extent of the district under drainage, and the quantity of water to be voided, it may be necessary to form covered main drains to receive the water discharged from the submains, their dimensions must be proportional to the amount of water to be voided, well flagged or paved at bottom, the sides built of stone or brick, and covered with a flag or arch at top.

SUBMAINS.

“The submains to be of such depth and width at top and bottom as may be necessary. The fall in each to be as great as the above-described main drainage of the district will allow, and not to be allowed to run beyond a suitable length without discharging itself into a covered or open main drain.

THE MINOR DRAINS

“To be of such depth, width at top and bottom, and at such distance apart, as will secure the perfect drainage of the land, to be run in a straight direction parallel to each other, directly up and down the declivity, unless where the declivity happens to be very steep, and then to be carried across the fall at such an angle as to secure a free discharge for the water. The fall in each minor drain to be as great as the main drainage and submain drainage, previously described, will admit.

“In filling in the stones, great care should be taken that the bottom of the drain be clean, and that no clay or dirt be put in with them; a sod, grass side down, or a few inches of tough clay, to be placed on the surface of the stones, and trodden firmly. The drain should then be filled up with the stuff previously shovelled out, observing to keep the active soil for the top. The putting in of the stones to be commenced at the highest part or head of the drain.

“In using draining pipes or other tiles, care should be taken that they be laid firmly on the bottom for their entire length, so as to prevent them being deranged by the filling of the drain, and that the points be fitted as closely together as possible.

“In cases of unfavourable ground, caused by running sand or other-

wise, whereby the level of the conduit might be deranged, collared pipe tiles offer considerable advantages in the way of remedy.

"When grips may be necessary on the sides of farm roads, they should be on the field side of the fences."

SPECIFICATION FOR MAIN DRAINAGE.

OPEN MAIN DRAINS.

"The deepening and improving of the main drain, No. —, is to be commenced at the point — on the accompanying map, and from thence a gradient carried up to the point —, having an inclination of at least — feet per statute mile, and sunk to the depth of — feet. It shall be — feet wide at bottom, and the side slopes shall average — at least, unless in rock cutting, when the side slopes may be diminished to six inches to one foot; all sharp angles, projecting stones, and other impediments to the free discharge of the water, must be carefully removed. The spoil or material raised in sinking and improving the drain, when not immediately used for top-dressing the adjoining lands, or for filling useless holes or drains, is to be removed to a distance of — feet from the edge of the main drain, and dressed off in a workmanlike manner.

"The bridge marked at the point — on the accompanying map to be —.

"The whole to be executed in a proper and workmanlike manner, and the works to be maintained in good order for so long as any interest shall be payable for the money advanced on account of its execution."

SPECIFICATION FOR THOROUGH-DRAINAGE (WITH TILES).

COVERED MAIN DRAINS.

"These shall be cut *fifty-four* inches deep, *thirty-six* inches wide at top, *twenty-four* inches wide at bottom; the materials used in them shall be *double row of three-inch pipe tiles*.

"The side walls shall be — inches in height, — inches thick, and well — at bottom. They shall be covered with a flag not less than — in thickness.

SUBMAINS.

"These shall be cut *fifty* inches deep, *thirty* inches wide at top, *eighteen* inches wide at bottom. They shall be carried along the low side of the fields, or portions of land to be drained, at a distance from the fence of *fifteen* feet, and through natural hollows where necessary. No submain to be allowed to run beyond a length of *two hundred* yards without discharging itself into a covered or open main drain.

MINOR DRAINS.

"These shall be cut *forty-eight* inches deep, *sixteen* inches wide at top, *five* inches wide at bottom, and at a distance of *forty* feet apart. They shall be run in a straight direction, parallel to each other, directly up and down the declivity (when possible). No minor drain to be allowed to run beyond a length of *two hundred* yards without discharging itself into a submain.

FILLING IN.

"All the drains (or a large number of them) having been opened and cut in a workmanlike manner, and it being ascertained that no water is standing in any of them, the filling in may be commenced.

MINOR DRAINS.

"Into each minor drain shall be put *pipe* tiles *twelve* inches in length, *one-and-a-half* inch in the ope, for *one hundred* yards, commencing from the upper end of the drain, and *pipe* tiles *twelve* inches in length, *one-and-three-quarter* inch in the ope, in continuation from thence to the submains.

SUBMAINS.

"Into each submain shall be put *pipe* tiles *twelve* inches in length, *two* inches in the ope, for *one hundred* yards, commencing from the upper end of the drain, and *pipe* tiles *twelve* inches in length, *three* inches in the ope, in continuation to the end or point where they discharge themselves.

GENERAL RULES.

"All tiles to be of good sound material, and well burned. The tiles shall be laid firmly on the bottoms of the drains for their entire length; the joints fitted as closely as possible, they shall be carefully covered with a *thin grassy sod or screen*. The stuff previously taken out of the drains shall then be returned, observing to keep the active soil uppermost.

"The mouths of the covered main or submain drains shall be built about with solid masonry set in mortar, carried up with the same slope as the sides of the open main drain, into which they discharge themselves.

"Before laying the tiles, great care must be taken that the bottom of the drains be clean. The putting in of the tiles to be commenced at the highest point or head of the drains.

"In case of an entire field being thorough-drained, a drain shall be cut at the top of it, parallel to the fence, and running at a distance from it equal to one-half of the distance between each of the minor drains, into one or more of which (as may be necessary) it shall discharge itself. The remainder of the minor drains to be discontinued at a distance from this drain equal to one-half the entire distance between each of the minor drains; this drain to be of the same dimensions, and filled with the same materials, and in like manner, as the above described.

"No open drain shall run into a closed one.

"In passing through unfavourable ground, caused by running sand or otherwise, whereby the level of the conduit might be deranged, and where pipe tiles are the materials used for forming the conduit, collars must be used, so as to connect the ends of the tiles, and they must be fitted as closely as possible.

"Soles must, in all cases, be used when laying single D tiles, and they must be so laid that the ends of the tiles shall rest equally on them; when inverted D tiles are used, they shall also be connected from end to end by placing one-half of the upper tiles on one-half of the adjoining tiles below them.

"The whole to be executed in a proper and workmanlike manner; and the work to be maintained in like good order as when approved of at its completion, for so long as any interest shall be payable for the money advanced on account of its execution." [*Collars for up to 4-inch pipes can be had at the Florence Court Tillery.*]

SPECIFICATION FOR THOROUGH-DRAINAGE (WITH BROKEN STONES).

COVERED MAIN DRAINS.

"These shall be cut *forty-two* inches deep, *thirty* inches wide at top, *twenty-four* inches wide at bottom; the materials used in them shall be —.

"The side walls in them shall be twelve inches in height, six inches thick, and well — at bottom. They shall be covered with —.

SUBMAINS.

"These shall be cut *forty-two* inches deep, *eighteen* inches wide at top, *fourteen* inches wide at bottom. They shall be carried along the low side of the fields, or portions of land to be drained, at a distance from the fences of *thirteen* feet, and through natural hollows, where necessary. No submain to be allowed to run beyond the length of *one hundred and fifty* yards, without discharging itself into a covered or open main drain.

MINOR DRAINS.

"These shall be cut *thirty-six* inches deep, *fifteen* inches wide at top, *four* inches wide at bottom, and at a distance of *twenty-six* feet apart. They shall be run in a straight direction, parallel to each other, directly up and down the declivity (when possible). No minor drain to be allowed to run beyond the length of *two hundred* yards without discharging itself into a submain.

FILLING IN.

"All the drains (or a large number of them) having been opened and cut in a workmanlike manner, and it being ascertained that no water is standing in any of them, the filling in may be commenced.

MINOR DRAINS.

"Into each minor drain shall be put *ten* inches of broken stones in depth, the stones having been broken to a size not exceeding two-and-a-half inches in diameter. Great care should be taken that the bottom of the drain be clean, and that no clay or dirt be put in along with the stones; a sod (or clay, as may be convenient) *three* inches thick shall be placed carefully on top, and the whole trampled upon or rammed hard. The drain shall then be filled up with the stuff previously shovelled out, observing to keep the active soil for covering the top.

The putting in of the stones shall invariably be commenced at the highest part or head of the drain.

FILLING IN SUBMAINS.

"In each submain a conduit shall be formed of *six* inches in height, *four* inches wide, and the filling in completed as above described.

GENERAL RULES.

"The mouths of the covered main or submain drains shall be built about with solid masonry set in mortar, carried up with the same slope as the sides of the open main drain into which they discharge themselves.

"Before filling in the stones, great care must be taken that the bottom of the drains be clean, and that no clay or dirt be put in along with them. The putting in of the stones to be commenced at the highest part or head of the drains.

"In case of an entire field being thorough-drained, a drain shall be cut at the top of it, parallel to the fence, and running at a distance from it equal to one-half the distance between each of the minor drains, into one or more of which (as may be necessary) it shall discharge itself. The remainder of the minor drains to be discontinued at a distance from this drain, equal to one-half the entire distance between each of the minor drains; this drain to be of the same dimensions, to be filled with the same material, and in like manner, as the above described.

"No open drain shall run into a closed one.

"The whole to be executed in a proper and workmanlike manner, and the work to be maintained in like good order as when approved of at its completion, for so long as any interest shall be payable for the money advanced on account of its execution."

One of the officers of the Commissioners of Public Works, Ireland, the Inspector of Drainage for Roscommon, a gentleman residing in that county, wrote to us as follows, with reference to tile and broken-stone drains on the carboniferous formation:—

"With respect to tile drainage, my experience ha

not been very extensive, as the proprietors of the district, with scarcely any exception, give a decided preference to broken stones; but from what I have seen, I am very much inclined to prefer good well-burnt pipes to any other draining material, provided that collars be used, but not otherwise. As to the best diameters, I have found the $1\frac{1}{4}$ " collared pipes of the Clonbrock Tile Works (now closed) very satisfactory; but when the length of minor drains exceeded 100 yards, I should like an increase to $1\frac{1}{2}$ or $1\frac{3}{4}$. For submains (say 150 or 180 yards long) I have recommended pipes of 2 inches, $2\frac{1}{2}$, and 3 inches in succession, all of which were to be had with collars: if 4-inch pipes were to be had with collars, I should have recommended longer submains. The larger-sized pipes are not provided with collars in our present tileries, *and on this account I generally put a note on the margin of the printed form, suggesting that a stone duct of the ordinary size of submain, say 6 inches in height and 4 inches wide, be substituted for the tile filling.*

"I decidedly prefer an open duct to broken-stone filling; and in nine-tenths of my own drainage I have made the minor drains on the same plan as the submain, with an open stone conduit; the only difference being, that the minor drains are a few inches shallower, with a smaller duct. The increase of expense is a mere trifle, and when the substratum (as very frequently occurs here) is a fine calcareous gravel, containing 40 to 60 per cent. of carbonate of lime, the additional spoil is a very cheap fertilizer for the land.

“With respect to depths and distances apart, the two most commonly used in my specification are $3\frac{1}{2}$ feet deep, 33 feet apart,—and 4 feet deep, 42 feet apart. These arrangements will not suit all cases, and I vary accordingly. Thus, in one case of exceedingly retentive land of peculiar texture, 4-foot drains, 27 feet apart, produced the required result, while in another, $3\frac{1}{2}$ -foot drains, 66 feet apart, effected all that was required. In the latter case there was a mixed soil, which might be described as ‘half wet;’ yet the water lingered sufficiently long to make the land unsound for sheep, and greatly to injure the crops in quality as well as quantity.”

Mr. Josiah Parkes says, in 1843 :—“Experiment and experience have rapidly induced the adoption of a system of parallel drains, considerably deeper, and less frequent, than those commonly advocated by professed drainers, or in general use. I gave several instances of this practice in Kent in the Report of last year, 1843, already alluded to, and it is rapidly extending. Mr. Hammond stated to you that he drained ‘stiff clays 2 feet deep, and 24 feet between the drains, at £3 4s. 3d. per acre, and porous soils 3 feet deep, $33\frac{1}{2}$ feet asunder, at £2 5s. 2d. per acre.’ I now find him continuing his drainage at 4 feet deep, wherever he can obtain the outfall, from a conviction founded on the experience of a cautious progressive practice as to the depth and distance, that depth consists with economy of outlay as well as with superior effect. He has found 4-foot drains to be efficient, at 50 feet asunder, in soils of varied texture—not uniform clays—and executes them at a cost of

about £2 5*s.* per acre, being 18*s.* 4*d.* for 871 pipes, and £1 6*s.* 6*d.* for 53 rods of digging. Communications have been recently made to me by several respectable Kentish farmers, of the satisfactory performance of drains deeply laid in the Weald clays, at distances ranging from 30 to 40 feet, but I have not had the opportunity of personally inspecting these drainages.

“The following little table shows the actual and respective cost of the above three cases of under-

Depth of drains, in feet.	Distance between the drains, in feet.	Mass of soil drained per acre, in cubic yards.	Mass of soil drained for one penny, in cubic yards.	Surface of soil drained for one penny, in square yards.
2	24	3226½	4·1	6·27
3	33½	4840	8·93	8·93
4	50	6453	12·00	8·96

draining, calculated on the effects really produced, that is, on the masses of earth effectively relieved of their surplus water at an equal expense. I conceive this to be the true expression of the work done, as a mere statement of the cost of drainage per acre of surface conveys but an imperfect, indeed a very erroneous, idea of the substantive and useful expenditure on any particular system. This will be apparent on reference to the two last columns of the table, which give the cost in cubic yards and square yards of soil drained for one penny, at the above-mentioned prices, depths, and distances.

“I may here observe, that Mr. Hammond, when draining tenacious clays, chooses the month of

February for the work, when he lays his pipes (just covering them with clay to prevent crumbs from getting in), and leaves the trenches open through March, if it be drying weather, by which means he finds the cracking of the soil much accelerated, and the complete action of the drains advanced a full season. The process of cracking may, doubtless, be hastened both by a choice of the period of the year in which drains are made, and by such a management of the surface as to expose it to the full force of atmospheric evaporation."

With reference to drains, we have known a case in the Queen's County in which inch pipes had to be taken up, and pipes of $2\frac{1}{2}$ -inch bore substituted. The drains were 40 feet apart, and 4 feet deep, and the pipes had collars. The minor drains should discharge into submains at convenient distances, say 100 yards, on flat grounds. Small pipes will choke unless the velocity in them be sufficient to carry off deposits, and the diameters should vary according to the inclinations of the ground, and distance apart of the drains.

Mr. Mechi, in 1844, laid down the following rules:—

"1st.—That it is not the size or form of the drains that regulate perfect drainage; but the *depth at which they are placed*. The depth also governs the distances at which the drains should be cut according to the quality of the soil.

"2nd.—The pipes of 1-inch bore, without stones, are amply sufficient, placed at 4 feet deep and 30 feet wide in dense soils, and the same depth and 50 feet wide in mixed soils.

"3rd.—The deep drains receive more water than shallow ones, and consequently lay dry a greater extent of ground.

"4th.—The deep drains *begin and end running sooner than shallow ones*, and carry off more water in a given time.

"5th.—That where shallow drains are made and deep ones cut below them, the shallow ones no longer act, all the water passing to the deeper drains.

"6th.—That when round stones are used as well as pipes, the latter should always be placed at the bottom, as I find, practically, water flows more quickly through pipes than amongst stones.

"Before persons begin draining, I would recommend their perusing attentively the facts developed by Mr. Parkes, at pages 39 and 40, and my remarks at page 36 of Letters on Agricultural Improvements.

"Pipes made to socket into each other (by Ford's Patent Socketing Machine) are best adapted to loose or mixed soils."

Pipes laid, however, too near the surface, are frequently choked with the roots of plants. The principal advantage of submains alongside open mains is, that the mouths of the minor drains should not be choked from vegetation, and that the water from them, flowing into and taken up by this submain, may be discharged by a few apertures only, and thereby keep themselves open, or as much so as the nature of the case will admit. The following tables show the cost per statute acre, in Ireland, of thorough-drainage, which must vary with circumstances, locality, and the value of labour.

The average cost per statute acre for Sir Richard O'Donnell's Gold Medal was £3 5s.7d., and £4 13s. 10d.

TABLE showing a Return of the number of Acres thorough-drained in the years 1843 and 1844, by the different Competitors for Sir Richard O'Donnell's Gold Medal, together with the Average Prices per Perch, and Cost per Acre respectively. (Given in Reports to the Royal Agricultural Improvement Society of Ireland.)

Competitors.	Number of statute acres.			Number of statute perches.	Average price per statute perch.	Average price per statute acre.	Cost to the tenants.	Rate of wages per day and by task work.
Marquess of Waterford	A.	R.	P.	P.	9d. in 1842, reduced to 5½d. in 1845.	£5 in 1842, reduced to £3 2s. 8d. in 1845.	5 per cent. charged to the rent.	..
Viscount Templetown.	564	0	25	54,351	4½d.	£1 14 4	£500 0 0	..
Sir R. O'Donnell, Bart.	551	0	0	53,478	4d.	1 12 4	408 6 0	8d. a day.
The Earl of Caledon .	821	0	19	47,183	4d.	2 9 5	396 9 9	10d. to 1s. a day.
J. L. W. Naper, Esq. .	254	1	29	34,483	9½d.	5 8 3	700 7 4	7d. a day in winter, and 10d. in summer.
Lord Blayney . . .	201	2	30	34,634	5d.	3 12 0	427 18 0	10d. to 1s. a day.

TABLE showing a Return of the number of Acres thorough-drained by Proprietors, for the Society's Gold Medal, and the Average Prices per Perch and per Acre respectively.

	A.	R.	P.	P.		£ s. d.		
The Earl of Erne . .	110	0	37	3 12 3
Lord Dufferin and Clanboye . . .	203	1	0	29,478	10½d.	6 11 9	..	1s. per day.
Messrs. Andrews . .	117	1	4	16,614	9½d.	5 15 0	..	15d. per day.
Dr. O'Neill . . .	115	0	12	2 16 3	..	7d. to 8d. a day.

for the Society's Gold Medal ; average of both, £4 per statute acre nearly.

The average number of acres annually improved in Ireland, about the year 1860, was about 5530, at an average cost per acre of £4 17s.

In Ireland, thorough-drainage is almost generally carried out by loan, under the Commissioners of Public Works, and there is no branch of the public service which has given more satisfaction to owners of property. The works are, we believe, always executed within the estimates, *and the owner having the expenditure in his own hands, can satisfy himself of its proper application.* How different from the Arterial Drainage, when the Board executed the works themselves, a system now so happily changed! No loans are made unless where immediately, or prospectively, a return of $6\frac{1}{2}$ per cent. is estimated on the expenditure, a rent-charge for this amount being made for 22 years.

ARTERIAL DRAINAGE.

The effect of thorough-drainage on the arterial channels of a district, is to discharge the rain-fall into the main channels in a shorter time than before, particularly during wet seasons. This frequently causes floods to rise higher as well as more rapidly. During dry seasons the supply is less, and so far, when it is limited, an injury is done to the adjacent districts requiring it for use. The effect of obstructions in the main channel is to impound the upland water, sometimes made available for water power or navigation purposes, but in general to the injury of the drainage of adjacent lands, and the regimen of the

TABLE showing Estimates of the Quantities and General Cost for the Thorough-Drainage of a Statute Acre of Land, with broken Stones or Tiles, with the distances apart for different class soils.

Description of land, section of parallel drain, and cost.	Distance between the parallel drains.	Lineal perches of drains per statute acre.	Cubic yards per acre.		Expense per statute acre.			Number of feet of tiles per statute acre.
			Of clay excav.	Of broken stones.				
Hard subsoil stiff and sandy clay drains, from 12 to 20 feet apart, at 8d. per lineal perch.	Feet	Perches	Cu. yds.	Cu. yds.	£	s.	d.	No.
	12	220	277	38·5	7	6	8	3,630
	13	203	255½	35·5	6	15	4	3,351
	14	188½	237	33·0	6	5	8	3,111
	15	176	221	30·8	5	17	4	2,904
	16	165	207	28·9	5	10	0	2,722
	17	155½	195½	27·2	5	3	6½	2,562
	18	146½	184	25·9	4	17	6½	2,420
	19	139	175	24·3	4	12	0	2,293
	20	132	166½	23·1	4	8	0	2,178
Freestone bottom drains, from 20 to 30 feet apart, at 9d. per lineal perch.	21	125½	182½	29·3	4	14	6	2,074
	22	120	174½	28·1	4	10	0	1,971
	23	115	167	26·9	4	6	3	1,894
	24	110	159½	25·7	4	2	6	1,815
	25	105½	153½	24·7	3	19	1½	1,742
	26	101½	147½	23·7	3	16	1½	1,675
	27	97½	142	22·9	3	13	4	1,613
	28	94	136½	22·0	3	10	6	1,556
	29	91	132½	21·3	3	8	3	1,502
	30	88	127½	20·6	3	6	0	1,452
Beds of gravel, sand, and rocky stratification, from 30 to 100 feet apart, at 10d. per lineal perch.	31	85	151½	24·7	3	10	10	1,405
	32	82½	147	24·0	3	8	9	1,361
	33	80	142½	23·2	3	6	8	1,320
	34	77½	138½	22·6	3	4	8½	1,280
	35	75½	134	21·9	3	2	9½	1,245
	36	73½	130½	21·3	3	1	1½	1,210
	37	71	126½	20·6	2	19	2	1,177
	38	69	123	20·0	2	17	6	1,146
	39	67½	119½	19·6	2	16	1½	1,117
	40	65½	116½	19·1	2	14	8½	1,089
	100	27	47	8·0	1	2	6	436

Estimates and Expenditure for some Works in Ireland, arranged from the Parliamentary Report and Papers of June 16, 1853.

No.	Name of District.	Original Estimate, exclusive of Works proposed to be omitted and of County Works, but including Interest up to the time the Works were stopped for Second Assents.	Total Cost of the Works, exclusive of Interest on Borrowed Money and of County Works.	Area of Land to be Drained and Improved.	Average Cost per Acre, exclusive of Interest on Borrowed Money and of County Works.	Original Estimate, Average Cost per Acre, exclusive of Works proposed to be omitted and of County Works, but including Interest up to the time the Works were stopped for Second Assents.
1	Kilbeggan . .	£ 8,850 15 0	£ 24,055 5 9	Acres. 5,970	£ 4 0 7	£ 1 9 8
2	Brosna (Ferbane) . .	40,085 1 1	71,986 9 1	15,723	4 11 6	2 11 0
3	Dunkellin . .	16,943 16 11	29,602 14 0	7,921	3 14 9	2 2 9
4	Cappagh . .	8,133 3 8	13,415 6 6	3,621	3 14 1	2 4 11
5	Lavally . .	9,763 1 10	12,740 4 7	2,167	5 17 7	4 10 1
6	Fergus . .	37,359 3 5	44,568 0 3	8,419	5 5 10	4 8 9
7	Shanagolden . .	7,393 12 2	10,299 10 9	1,000	10 6 0	7 7 10
8	Inny . .	29,191 4 5	44,471 4 4	14,770	3 0 2	1 19 6
9	Rinn and Black River . .	17,205 17 9	21,998 10 7	5,691	3 17 4	3 0 5
10	Lough Gara and Mantua . .	10,719 11 8	18,380 2 6	4,374	4 4 0	2 9 0
11	Kill . .	2,145 19 11	2,035 5 6	1,025	1 19 8	2 1 10
	Total . .	186,916 5 0	293,532 18 10	70,681	4 3 0	2 12 10

TABLE of Expenditure and Cost of Works on Eleven Arterial Drainage Works in Ireland.

NAME OF WORK.	Quantity of Earthwork Gravel	Cost.			Quantity of Rockwork.			Cost.			Cost of Unwatering.			Cost of Superintendence, not including Engineers' Establishments.			Cost of Plant, Tools, and Materials not used in the Works.			Analysis of Cost per Cube Yard in Pence.																	
		Cu. yds.			Cu. yds.			£ s. d.			£ s. d.			£ s. d.			£ s. d.			Gravel		Rock		Unwatering.		Implements.		Superintendence.		Total							
		£	s. d.		£	s. d.		£	s. d.		£	s. d.		£	s. d.		Pence	Gravel	Pence	Rock	Pence	Gravel	Pence	Rock	Pence	Gravel	Pence	Rock	Pence	Gravel	Pence	Rock					
Kilcolgan .	80,992	1,984	9 11	22,572	868	7 4½	144	1 11	500	2 10	374	18 8	588	9 23	777	9 23	0 30	0 87	1 15	8 20	11 55	12 98	8 78	5 43	7 36	14 75	5 85	19 54	6 04	9 31	14 02	17 41	26 32	26 66	14 51	9 94	12 74
Craughwell .	51,491	600	18 10	2,006	100	0 0	8	6 2	193	0 0	88	0 0	280	12 00	0 04	0 39	0 55	0 39	0 55	8 78	5 43	7 36	14 75	5 85	19 54	6 04	9 31	14 02	17 41	26 32	26 66	14 51	9 94	12 74			
Strongfort .	17,475	285	12 8	400	12	0 0	13	17 11	55	0 0	38	0 0	400	7 20	0 18	0 51	0 73	0 51	0 73	5 43	7 36	14 75	5 85	19 54	6 04	9 31	14 02	17 41	26 32	26 66	14 51	9 94	12 74				
Ballymore .	75,610	1,771	16 11	9,350	509	1 0	7	5 10	360	0 0	255	0 0	561	13 00	0 02	0 72	1 01	0 72	1 01	7 36	14 75	5 85	19 54	6 04	9 31	14 02	17 41	26 32	26 66	14 51	9 94	12 74					
Raford .	64,100	1,151	10 2	800	60	9 0	47	18 3	315	0 0	150	0 0	431	18 00	0 18	0 56	0 80	0 56	0 80	5 85	19 54	6 04	9 31	14 02	17 41	26 32	26 66	14 51	9 94	12 74							
Ballykeeran.	17,033	285	9 9½	60	9	10 0	17	5 6	55	0 0	38	0 0	400	38 00	0 24	0 53	0 77	0 54	0 59	5 85	19 54	6 04	9 31	14 02	17 41	26 32	26 66	14 51	9 94	12 74							
Dunsandle .	35,724	669	15 9½	3,526	114	5 0	35	12 2	130	0 0	89	0 0	450	7 77	0 21	0 54	0 79	0 54	0 79	6 04	9 31	14 02	17 41	26 32	26 66	14 51	9 94	12 74									
St. Clerans .	40,843	745	8 7	850	44	0 0	29	9 5½	147	15 0	101	0 0	438	12 42	0 17	0 58	0 85	0 58	0 85	5 98	14 02	17 41	26 32	26 66	14 51	9 94	12 74										
Loughrea .	89,296	1,512	12 8	2,700	180	18 4	12	19 0	297	10 0	205	0 0	406	16 08	0 03	0 53	0 77	0 53	0 77	5 39	17 41	26 32	26 66	14 51	9 94	12 74											
Monksfield .	61,122	594	2 8	320	83	14 0	9	18 7	157	15 0	110	0 0	333	23 25	0 04	0 42	0 61	0 42	0 61	8 40	26 32	26 66	14 51	9 94	12 74												
Lackafinna .	48,790	864	6 9	522	53	14 0	15	19 1	108	0 0	77	0 0	425	24 69	0 08	0 37	0 52	0 37	0 52	5 23	26 66	14 51	9 94	12 74													
Carra .	74,850	1,186	5 6½	7,900	444	0 0	25	8 2	198	0 0	136	0 0	880	13 48	0 07	0 39	0 57	0 39	0 57	4 38	14 51	9 94	12 74														
Raruddy .	38,854	888	9 8½	3,060	113	12 0	4	3 7	79	0 0	56	10 0	322	8 90	0 03	0 42	0 59	0 42	0 59	4 36	9 94	12 74															
	686,179	12,041	0 0	54,066	2,543	10 9	372	5 7½	2,426	2 10	1,718	8 8	421	11 29	0 12	0 55	0 78	0 55	0 78	5 66	12 74																

river, particularly in flat districts. The arterial drainage in Ireland has effected a vast amount of good, but up to 1853 the estimates appear to have been usually doubled; those for eleven of these works being £186,916, and the expenditure £293,532. The average cost per acre, on the land improved by these projects, varied from £1 19s. 8d. to £10 6s., the average of the eleven districts being £4 3s., which is about the average for thorough-drainage.*

The following table affords valuable information of the cost of arterial drainage works in Ireland: it is extracted from the Report of the Commissioners of Inquiry presented to the House of Commons, June 16th, 1853.

The abstract of 84 arterial drainage awards, made by the Commissioners of Public Works in Ireland, in 1854, gives for different years, 1849 to 1854—

Number of districts drained.	Total combined catchment acreage of districts.	Area of flooded lands.	Average cost of arterial drainage per acre improved by drainage.		
			£	s.	d.
12 districts	90,332	9,453	3	14	2
27 „	95,582	11,579	3	16	7
19 „	237,466	13,707	4	17	3
16 „	374,427	29,452	3	13	4
2 „	49,840	3,275	5	0	0
8 „	266,420	21,033	3	9	4
84 „	1,114,067	88,501	3	17	7

The last line gives the general average, and shows that in these 84 districts, about 1 acre in 13 is the

* See Parliamentary Report, by Sir Richard Griffith, Sir W. Cubitt, and Jas. M. Rendel, June 16th, 1853, pp. 14, 15.

average of flooded lands to the catchment area, or 8 per cent. nearly. The original and revised estimates for these works were considerably exceeded in almost every case, and the landowners having justly resisted any payments *exceeding their original assents*, they succeeded. See REPORT OF THE COMMISSIONERS OF INQUIRY INTO THE WORKS OF ARTERIAL DRAINAGE IN ELEVEN DISTRICTS IN IRELAND, presented to the House of Commons, June 16th, 1858.

SECTION XIV.

WATER AND HORSE POWER.—FRICTION BRAKE, OR DYNAMOMETER.—CALCULATION OF THE EFFECTIVE POWER OF WATER WHEELS.—OVERSHOT, UNDERSHOT, AND BREAST VERTICAL WHEELS.—HORIZONTAL WHEELS AND TURBINES.—HYDRAULIC RAM.—WATER ENGINE.

Taking the representative of a horse's power at 33,000 foot-pounds, or 33,000 lbs. raised one foot high in one minute, the theoretical horse-power of an overfall is expressed by the fall in feet, multiplied by the discharge in cubic feet per minute, the product multiplied by $62\frac{1}{2}$ (the weight in lbs., nearly, of a cubic foot of water), and divided by 33,000. The following table (page 400) gives the weight in air of a cubic foot of pure water at different temperatures, Fahrenheit's thermometer.

WEIGHT OF A CUBIC FOOT OF WATER.

The weight of 36 cubic feet of water is one ton, nearly.

Temperature, in degrees.	Weight of a cubic foot of water. Pounds Avoirdupois.	Temperature, in degrees.	Weight of a cubic foot of water. Pounds Avoirdupois.	Temperature, in degrees.	Weight of a cubic foot of water. Pounds Avoirdupois.
32	62·375	51	62·365	69	62·278
33	62·377	52	62·363	70	62·272
34	62·378	53	62·359	71	62·264
35	62·379	54	62·356	72	62·257
36	62·380	55	62·352	73	62·249
37	62·381	56	62·349	74	62·242
38	62·381	57	62·345	75	62·234
39	62·382	58	62·340	76	62·225
40	62·382	59	62·336	77	62·217
41	62·381	60	62·331	78	62·208
42	62·381	61	62·326	79	62·199
43	62·380	62	62·321	80	62·190
44	62·379	63	62·316	81	62·181
45	62·378	64	62·310	82	62·172
46	62·376	65	62·304	83	62·162
47	62·375	66	62·298	84	62·152
48	62·373	67	62·292	85	62·142
49	62·371	68	62·285	86	62·132
50	62·368			87	62·122

16,500 foot-pounds, or one half of the above, is much nearer the average power of a horse, working for 10 hours only, as the work is ordinarily done through the country; 33,000 lbs. raised one foot per minute is equivalent to 884 tons, nearly, raised one foot in an hour, and 14·73 tons in a minute. Therefore, a river discharging 884 tons, over a fall one foot high in an hour, or 884 tons, over a fall 24 feet high in 24 hours, has also a horse-power. The drainage of 10 square miles, with an average collection of 12 inches in depth of rain annually, will give an unceasing one-horse power for each foot of fall in a receiving channel; or five square miles will give the same

result, if the collection amounts to 24 inches in depth. The collection of 10 square miles, one foot deep, yearly, is nearly equal to the delivery of 530 cubic feet per minute, for the same period; or to one-horse power theoretical, working day and night. See pp. 322 & 323.

The effective power of a fall depends on the nature, proportions, and construction of the wheel or machine, and also upon the manner in which the theoretical power is applied. When the velocity of a stream acting on a wheel only is known, the theoretical head, h , due to it is found in feet from the formula $h = \cdot 0155 v^2$, v being the velocity in feet per second.

In order to gauge the quantity of water applied to a wheel, and thereby determine with accuracy its effective power, the water used must be passed through an orifice, or over a notch or a weir, the coefficients for which has been previously ascertained from experiment. Greater accuracy can be obtained from gaugings through thin plates, or planks having the downstream arrises chamfered off, than with any other form of orifice or notch; and when it can be effected, the channel above should be sufficiently enlarged to prevent the effects of an approaching current. We have already in the body of this work dwelt in detail on the various formulæ required for gauging under different circumstances. The accuracy of results, showing the effective powers of wheels, depends in the first place, on the accuracy of the gaugings or estimates of the quantity of water used, and next on the fall employed. The loss of head in passing through the penstock sluice, or orifice, and until the water acts on the wheel, requires to be estimated also,


D D

and deducted from the fall or head, to find the effective fall, and the effective power of a wheel.

FRICTION BRAKE, OR DYNAMOMETER.

The power applied to a revolving shaft through a water wheel of any construction, is the weight of water multiplied by the fall. It is evident that the portion of this power available to turn a shaft and machinery, or the effective power, must depend on the construction of the wheel, as portion of the theoretical power is lost mechanically, in applying it; in

FIG. 44.
FRICTION BRAKES, OR DYNAMOMETERS.



changes of direction, friction, eddies, and discharging currents. The greater the effective power conveyed

to a shaft, the greater becomes the power of the wheel, or medium through which the original power is transmitted. The mechanical effect produced by a revolving shaft is best measured by a friction brake, the principle of which is as follows. In diagram 1, Fig. 44, let the friction pulley *AA* be firmly fixed to the revolving shaft or axis of the wheel; *E* and *E*, two wooden clamps grasping the friction pulley by means of the screw bolts, delineated, which can be tightened on the axis, and also to the arm *F*, by means of suitable nuts. The more tightly the bolts are screwed, the greater will be the friction between the friction pulley *AA*, and the clamping pieces *EE*. If, while the axis and friction pulley *AA*, are revolving in the direction indicated by the arrow, a weight be applied in the scale at *I*, so that the arm *F* shall not be carried round, but remain fixed; it is clear that the work done by the revolving shaft in one revolution, will be measured by the circumference of the friction pulley, multiplied by the friction due to the pressure on it, or by its equivalent, the weight in the scale *I*, multiplied by the circumference of a circle whose radius is *L*, or by $2 L \times 3.14159 \times w$, in which expression *w* is the weight in lbs. in the scale *I*. If *n* be the number of revolutions in a given time, say one minute, we shall therefore have the useful effect of the wheel on the shaft in foot-pounds per minute, equal to

$$2 L \times 3.14159 \times w \times n.$$

We have also the power of the water acting on the wheel, equal to

$$h \times D \times 62.37,$$

in which *h* is the head and *D* the discharge in cubic

$$D D^2$$

feet per minute; therefore we shall have for the ratio of the effect to the power the expression

$$\frac{2 L \times 3.14159 \times w \times n}{h \times D \times 62.37} = \frac{L w n}{9.926 D h}.$$

If the revolving shaft be horizontal, the weight of the arm r , acting at its centre of gravity and reduced to the length L , where the weight w is suspended, will have to be included in the weight w . If the weight w be suspended at the end of a connection of levers, or other mechanical powers, the length L will have to be determined accordingly. Diagram 2, Fig. 44, shows the Armstrong brake; Diagram 3, the common form; and Diagram 4, Egen's brake.

Fig. 45, is a general representation of the brake used by Francis, in the Lowell experiments. The length of the arm of the brake L , was 9.745 feet; the length of the vertical arm l of the bell crank 4.5 feet; and the length of the horizontal arm l' 5, feet. The following detailed description is by Francis:—


“*The Friction Pulley A* is of cast-iron, 5.5 feet in diameter, two feet wide on the face, and three inches thick. It is attached to the vertical shaft by the spider B , the hub of which occupies the place on the shaft intended for the bevel gear.

“The friction pulley has, cast on its interior circumference, six lugs, $c c$, corresponding to the six arms of the spider. The bolt holes in the ends of the arms are slightly elongated in the direction of the radius, for the purpose of allowing the friction pulley to expand a little as it becomes heated, without throwing much strain upon the spider. When the spider and friction pulley are at the same temperature,

the ends of the arms are in contact with the friction

FIG. 45.

**DYNAMOMETER FOR DETERMINING THE USEFUL EFFECT OF THE TREMONT
TURBINE.**



pulley. The friction pulley was made of great thick-

ness for two reasons. When the pulley is heated, the arms cease to be in contact with the interior circumference of the pulley, consequently they would not prevent the pressure of the brake from altering the form of the pulley. This renders great stiffness necessary in the pulley itself. Again, it is found that a heavy friction pulley insures more regularity in the motion, operating, in fact, as a fly-wheel, in equalizing small irregularities.

“ *The brakes E and F* are of maple wood; the two parts are drawn together by the wrought-iron bolts G G, which are two inches square.

“ *The bell crank F'*, carries at one end the scale I, and at the other the piston of the hydraulic regulator K; this end carries also the pointer L, which indicates the level of the horizontal arm. The vertical arm is connected with the brake F, by the link M.

“ *The hydraulic regulator K*, shown in the figures, is a very important addition to the Prony dynamometer, first suggested to the author by Mr. Boyden, in 1844. Its office is to control and modify the violent shocks and irregularities, which usually occur in the action of this valuable instrument, and are the cause of some uncertainty in its indications.

“ The hydraulic regulator used in these experiments, consisted of a cast-iron cylinder K, about 1.5 feet in diameter, with a bottom of plank, which was strongly bolted to the capping stone of the wheel pit, as represented in figure 1. In this cylinder, moves the piston N, formed of plate-iron 0.5 inches thick, which is connected with the horizontal arm of the bell crank by the piston rod O. The circumference of the piston is

rounded off, and its diameter is about $\frac{1}{8}$ inch less than the diameter of the interior of the cylinder. The action of the hydraulic regulator is as follows. The cylinder should be nearly filled with water, or other heavy inelastic fluid. In case of any irregularity in the force of the wheel, or in the friction of the brake, the tendency will be, either to raise or lower the weight, in either case the weight cannot move, except with a corresponding movement of the piston. In consequence of the inelasticity of the fluid, the piston can move only by the displacement of a portion of the fluid, which must evidently pass between the edge of the piston and the cylinder; and the area of this space being very small, compared to the area of the piston, the motion of the latter must be slow, giving time to alter the tension of the brake screws before the piston has moved far. It is plain that this arrangement must arrest all violent shocks, but, however violent and irregular they may be, it is evident, that, if the mean force of them is greater in one direction than in the other, the piston must move in the direction of the preponderating force, the resistance to a slow movement being very slight. A small portion of the useful effect of the turbine must be expended in this instrument, probably less, however, than in the rude shocks the brake would be subject to without its use.

“For the purpose of ascertaining the velocity of the wheel, a counter was attached to the top of the vertical shaft, so arranged, that a bell was struck at the end of every fifty revolutions of the wheel.

“To lubricate the friction pulley, and at the same time to keep it cool, water was let on to its surface in

four jets, two of which are shown. These jets were supplied from a large cistern, in the attic of the neighbouring cotton mill, kept full, during the working hours of the mill, by force pumps. The quantity of water discharged by the four jets was, by a mean of two trials, 0·0288 cubic foot per second.


“In many of the experiments with heavy weights, and consequently slow velocities, oil was used to lubricate the brake, the water, during the experiment, being shut off. It is found, that, with a small quantity of oil, the friction between the brake and the pulley is much greater than when the usual quantity of water is applied; consequently, the requisite tension of the brake screws is much less with the oil, as a lubricator, than with water. This may not be the whole cause of the phenomenon, but, whatever it may be, the ease of regulating in slow velocities is incomparably greater with oil as a lubricator, than with water applied in a quantity sufficient to keep the pulley cool. The oil was allowed to flow on in two fine continuous streams; it did not, however, prevent the pulley from becoming heated sufficiently to decompose the oil, after running some time, which was distinctly indicated by the smoke and peculiar odour. When these indications became very apparent, the experiment was stopped, and water let on by the jets, until the pulley was cooled. As the pulley became heated, the brake screws required to be gradually slackened. Water, linseed oil, and resin oil, were each used for lubrication.”

Fig. 46 is a representation of a brake used by Professor Thomson, at Crawford and Lindsay's mill, to determine the power of a turbine put up there, by Mr.

Gardner, of Armagh. One of the common causes of the swinging or vibratory jumps of the arms F , in Figs. 44, 45, and 46 is, that very often the friction pulley, or drum A , must be made in two parts, so as to be fixed

FIG. 46.

FRICITION BRAKE, USED AT CRAWFORD AND LINDSAY'S MILL, BY PROFESSOR JAMES THOMSON, TO DETERMINE THE POWER OF THE TURBINE.



Length of the brake, I , Fig. 45, adjusted . . . 9.745 feet.
 Effective length of vertical arm l . . . 4.5 ,,
 Effective length of horizontal arm l' . . . 5.0 ,,

to its place on the shaft. This fixing is liable to give an oval shape, and causes an irregular action with the clamps E, E. Oil gives greater regularity of motion than water, but without the use of the latter abundantly, the friction pulley would usually get too much heated. The following calculations from practical operations will point out pretty clearly the use of the brake, and the manner of determining the useful effect in the tables of experiments, by Francis and Thomson, pp. 383 and 392:—

The effective length of the brake was therefore $\frac{9.745 \times 5}{4.5} = 2 \times 10.827778$ feet; and the circumference of a circle of this radius $= 10.827778 \times 3.14159 = 68.0329$ feet.

In the first experiment on the Tremont turbine, page 429, the number of revolutions of the wheel per second was .89374, and the weight in the scale 1443.34 lbs. The useful effect of the brake was therefore in foot-pounds per second $68.0329 \times .89374 \times 1443.34 = 87680.3$ lbs. raised one foot per second. The quantity of water which passed the gauge-weir in cubic feet per second was 139.4206, and the total fall acting on the wheel 12.864 feet; therefore, the total power of the water acting on the wheel was $12.864 \times 139.4206 \times 62.375 = 111870$ foot-pounds per second, 62.375 being taken as the weight in lbs. of a cubic foot of water at 32° Fahrenheit. The ratio of the useful effect, at the given velocity of the wheel (viz. 450 revolutions in 503.5 seconds), to the power expended, is therefore $\frac{87680.3}{111870} = .784$, or about 78½ per cent. The effect in the ex-

periments generally appears to have been a maximum, when the velocity of the interior circumference of the wheel was about 66 per cent. of the velocity due to the fall; and this was about half of the maximum velocity, which was 1·333 times that due to the fall alone, when the turbine was doing no work.

In Thomson's brake for determining the useful effect of the vortex turbine, erected from his designs at Ballysillan, Ireland, $L = 4$ ft. 2 in., and the circumference of a circle that would be described by the arm $3\cdot14159 \times 8$ feet 4 inches $= 26\cdot18$ feet. In the first experiment, taken from the tabulated results, page 419, we get $26\cdot18$, the circumference multiplied by $46\cdot31$, the weight in lbs., and the product by $323\cdot3$, the number of revolutions per minute, equal to 391,967 foot-pounds, for the effect transmitted from the turbine or work done. We have also $354\cdot4$, the number of cubic feet of water passed to the wheel per minute, multiplied by $62\cdot37$, the weight of a cubic foot of water in lbs., multiplied by $23\cdot73$ feet, the available fall, equal to 524,526 foot-pounds: therefore $\frac{391,967}{524,526} = \cdot747$ is the useful effect, that in the table being $\cdot7481$, which probably arose from taking a different weight per cubic foot for the water. Of course the difference is immaterial. The drum attached to the vortex wheel shaft for fixing the brake to, was in two parts, bolted together, and firmly enclosing the shaft. It was of cast-iron, 20 inches diameter, and 8 inches wide; the shaft to which it was attached was $2\frac{3}{8}$ inches diameter. The arm of the brake was $5\cdot4'' \times 6'' \times 4''\frac{1}{2}$, of timber, and extending 1 foot 2 inches beyond the centre of the shaft

and drum. The clamping pieces were about 2 feet 5 inches long externally.

FOR OVERSHOT WHEELS the ratio of the power to the effect may be taken as 3 to 2, and therefore the effective horse-power,—taking 88,000 foot-pounds per minute, or 530 cubic feet falling one foot, as a standard,—will be 49,500 lbs. of water, or 795 cubic feet, falling one foot in one minute. The maximum effect varies with the construction of the wheel. Smeaton found it $\cdot 76$ times the theoretical power; Weisbach $\cdot 78$ times for the wheel of a Stamp Mill at Frieberg, which was 23 feet high, 3 feet wide, carrying 48 buckets.* To find the effective horse-power, the theoretical horse-power must be here divided by the coefficient of effect $\cdot 76$ or $\cdot 78$, which will give 48,600 foot-pounds, or 48,300 foot-pounds per minute. The following experimental results from a model wheel are by Smeaton.

In this table the effective power of the water must be reckoned upon the whole descent, because it must be raised that height, in order to be in a condition of producing the same effect a second time.

The ratios between the *powers* so estimated, and the *effects* at the *maximum*, deduced from the several sets of experiments, are exhibited at one view, in column 9, of Table II. ; and from hence it appears, that those ratios differ from that of 10 to $7\cdot 6$ to that of 10 to $5\cdot 2$, that is, nearly from 4 to 3 to 4 to 2. In those experiments where the heads of water and quantities expended

* Some valuable experiments on the power of water wheels are given by Rennie, in Weale's Quarterly Papers on Engineering, vol. vi. They however require reduction. An effect of $\cdot 75$ requires a flow of 707 cubic feet per minute, with a fall of one foot, for a horse power.

are least, the proportion is nearly as 4 to 3, but where the heads and quantities are greatest, it approaches nearer to that of 4 to 2; and by a medium of the whole,

TABLE containing the Result of Sixteen Experiments, on a Model Overshot Wheel, by Smeaton.

No.	Whole descent, in inches.	Water expended in a minute, in lbs.	Turns at the maximum in a minute.	Weight raised at the maximum in lbs.	Power of the whole descent.	Power of the Wheel.	Effect.	Ratios of the whole effect to the power.	Ratios of the effect to the power or coefficient of effect.	Mean Ratios.
1	27	30	19	6½	810	720	556	·69	·77	·81
2	27	56	16½	14½	1530	1360	1060	·69	·78	
3	27	56	20½	12½	1530	1360	1167	·76	·84	
4	27	63	20½	13½	1710	1524	1245	·73	·82	
5	27	76	21½	15½	2070	1840	1500	·73	·82	
6	28½	73	18½	17½	2090	1764	1476	·70	·84	·82
7	28½	96	20½	20½	2755	2320	1868	·68	·80	
8	30	90	20	19½	2700	2160	1755	·65	·81	·82
9	30	96	20½	20½	2900	2320	1914	·66	·82	
10	30	113½	21	23½	3400	2720	2221	·65	·82	
11	33	56½	20½	13½	1870	1360	1230	·66	·90	·85
12	33	106	22½	21½	3520	2560	2153	·61	·84	
13	33	146	23	27½	4840	3520	2846	·59	·81	
14	35	65	19½	16½	2275	1560	1466	·65	·95	·85
15	35	120	21½	25½	4200	2880	2467	·59	·86	
16	35	163½	25	26½	5728	3924	2981	·52	·76	

the ratio is that of 3 to 2, nearly. We have seen before, in our observations upon the effects of undershot wheels, that the general ratio of the power to the effect, when greatest, was 3 to 1; the effect, therefore, of over-

shot wheels, under the same circumstances of quantity and fall, is at a medium double to that of the undershot ; and, as a consequence thereof, that non-elastic bodies, when acting by their impulse or collision, communicate only a part of their original power ; the other part being spent in changing their figure, in consequence of the stroke.

The powers of water, computed from the height of the wheel only, compared with the effects as in column 10, appear to observe a more constant ratio : for, if we take the medium of each class, which is set down in column 11, we shall find the extremes to differ no more than from the ratio of 10 to 8·1 to that of 10 to 8·5 ; and as the second term of the ratio gradually increases from 8·1 to 8·5, by an increase of head from 3 inches to 11, the excess of 8·5 above 8·1 is to be imputed to the greater impulse of the water at the head of 11 inches, above that of 3 inches : so that if we reduce 8·1 to 8, on account of the impulse of the 3-inch head, *we shall have the ratio of the power, computed upon the height of the wheel only, to the effect at a maximum, as 10 to 8 or as 5 to 4, nearly ;* and from the equality of the ratio between power and effect subsisting, where the constructions are similar, we must infer, *that the effects, as well as the powers, are respectively as the quantities of water and perpendicular heights, multiplied together.*

FOR BREAST WHEELS, the ratio of the theoretical power to the effective power must vary considerably, the mean value being about ·5 and, therefore, the effective horse-power would be 66,000 foot-pounds, or 1,060 cubic feet falling 1 foot in one minute. Morin

gives an efficiency of from $\cdot 52$ to $\cdot 7$. Egen, with a wheel 23 feet in diameter, $4\frac{1}{2}$ feet wide, having 69 ventilated buckets, very well constructed, found at best an efficiency of only $\cdot 52$, under ordinary circumstances

TABLE containing the Result of Twenty-seven Experiments, on a Model Undershot Wheel, by Smeaton.

	Height of water in the cistern in inches.		Turns of the wheel unloaded.		Virtual head deduced therefrom in inches.		Turns at the maxi- mum.		Load at the equilibrium, in lbs. and oza.		Load at the maximum, in lbs. and oza.		Water expended in a minute.		Power.		Effect.		Ratio of the Effect to the power or coefficient of effect.		Ratio of the velocity of the wheel and water.		Ratio of the load at the equilibrium, to the load at the maximum.	
1	33	88	15	85	30	13	10	10	9	275	4358	1411	324	340	775									
2	30	86	15	0	30	12	10	9	6	264	3070	1266	320	350	740									
3	27	82	13	7	28	11	2	8	6	243	3329	1044	315	340	750									
4	24	78	12	3	27	9	10	7	5	235	2890	901	312	355	753									
5	21	75	11	4	25	8	10	6	5	214	2439	735	302	345	732									
6	18	70	9	95	23	6	10	5	5	199	1970	561	285	336	802									
7	15	65	8	54	23	5	2	4	4	178	1524	442	290	360	880									
8	12	60	7	29	22	3	10	3	5	161	1173	328	280	377	910									
9	9	52	5	47	19	2	12	2	8	134	733	213	290	365	910									
10	6	42	3	55	16	1	12	1	10	114	404	117	282	380	930									
11	24	84	14	2	30	13	10	10	14	342	4890	1505	307	366	790									
12	21	81	13	5	29	11	10	9	6	297	4009	1223	301	362	805									
13	18	73	10	5	26	9	10	8	7	285	3993	975	325	360	875									
14	15	69	9	6	25	7	10	6	14	277	2659	774	292	362	900									
15	12	63	8	0	25	5	10	4	14	234	1872	549	294	397	870									
16	9	56	6	37	23	4	0	3	13	201	1230	390	305	410	950									
17	6	46	4	25	21	2	8	2	4	167	712	212	298	455	900									
18	15	72	10	5	29	11	10	9	6	357	3748	1210	323	402	805									
19	12	66	8	75	26	8	10	7	6	330	2387	878	305	405	810									
20	9	58	6	8	24	5	8	5	0	255	1734	541	301	422	910									
21	6	48	4	7	23	3	2	3	0	228	1064	317	299	490	960									
22	12	68	9	3	27	9	2	8	6	359	3338	1036	302	397	917									
23	9	58	6	8	26	6	2	5	13	332	2257	686	304	452	950									
24	6	48	4	7	24	3	12	3	8	263	1231	385	313	510	935									
25	9	60	7	29	27	6	12	6	6	355	2588	785	303	455	945									
26	6	50	5	03	24	4	6	4	1	307	1544	450	292	490	930									
27	6	50	5	03	26	4	15	4	9	360	1811	534	295	520	925									

$\cdot 48$, the mean amount being $\cdot 5$. Very wide wheels give a larger effect, sometimes as high as $\cdot 7$; but a

great deal depends on the manner of bringing on the water and the construction of the wheel and buckets.

PONCELET'S WHEEL is seldom if at all used in these countries. The effective power is $\cdot 5$, or 1,060 cubic feet of water falling one foot for the standard horse-power.

FOR UNDERSHOT WHEELS the mean effect may be taken at one-third, or $\cdot 33$, or 100,000 foot-pounds, or 1,590 cubic feet falling one foot in one minute, for an effective horse's power; a maximum effect of $\cdot 5$ is sometimes approached, and a minimum of $\cdot 26$ or less. The following results, obtained from a model, are given by Smeaton. The *virtual* or *effective* head is here termed the theoretical head due to the velocity of the wheel, at the circumference, which was 75 inches girth.

Smeaton derived the following "maxims" from the foregoing experiments. Their truth, independent of any experiment, will be apparent:—

- I.—That the virtual or effective head being the same, the effect will be nearly as the quantity of water expended.*
- II.—That the expense of water being the same, the effect will be nearly as the height of the virtual or effective head.*
- III.—That the quantity of water expended being the same, the effect is nearly as the square of the velocity.*
- IV.—The aperture being the same, the effect will be nearly as the cube of the velocity of the water.*

FOR TURBINES OR HORIZONTAL WHEELS, a useful effect of two-thirds or $\cdot 67$ may be assumed, or 49,500 foot-pounds in a minute for a horse-power, and the efficiency varies from $\cdot 5$ to $\cdot 8$, or less.* Poncelet's

* In our first edition we gave an efficiency of $\cdot 821$, on the authority

turbine gives an efficiency of $\cdot 5$ to $\cdot 6$. Floating wheels $\cdot 38$, impact wheels from $\cdot 16$ to $\cdot 4$, and Barker's mill from $\cdot 16$ to $\cdot 35$. We believe that the efficiency of the turbine has been too often over-estimated, and that the great advantage of this wheel, as a medium of power, is derived from its capability of employment for all falls, whether large or small, without any considerable loss of effect. In Ireland, Mr. Gardner, of Armagh, was amongst the first, if not the first, to apply this wheel to practical purposes; and Professor Thomson has, in his vortex wheels, produced, we believe, the highest efficiencies which have yet been obtained in practice. In the experiments on the Ballysillan wheel higher efficiencies would probably have been attained with a supply pipe of larger diameter. It will be seen from the remarks, at pp. 164 to 167, and the tables, at pp. 146 and 199, that quite apart from bends, &c., a loss of mechanical power always results from the passage through orifices and pipes; and that it is necessary to take this loss into account, before the head acting on the wheel can be accurately used to determine its effective power. The table, p. 419, contains the experiments on the Ballysillan turbine.

The following remarks on the vortex turbine, read at the meeting of the British Association at Belfast, in 1852, are also by Professor Thomson:—

of a paper by Dr. Robinson, Armagh, in the Proceedings of the Royal Irish Academy, vol. iv., p. 214. On again glancing over this paper, we believe there are mistakes, which vitiate the results there given; first, in the formula for calculating the discharge over the weir, and next, in the formula for finding the effect of the brake. Francis gives an efficiency of $\cdot 88$, p. 3, in his book.

R E .

“Numberless are the varieties, both of principle and of construction, in the mechanisms by which motive power may be obtained from falls of water. The chief modes of action of the water are, however, reducible to three, as follows:—First, the water may act directly by its weight on a part of the mechanism which descends while loaded with water, and ascends while free from load. The most prominent example of the application of this mode is afforded by the ordinary bucket water wheel. Secondly, the water may act by fluid pressure, and drive before it some yielding part of a vessel by which it is confined. This is the mode in which the water acts in the water pressure engine, analogous to the ordinary high-pressure steam-engine. Thirdly, the water, having been brought to its place of action subject to the pressure due to the height of fall, may be allowed to issue through small orifices with a high velocity, its inertia being one of the forces essentially involved in the communication of the power to the moving part of the mechanism. Throughout the general class of water wheels called turbines, which is of wide extent, the water acts according to some of the variations of which this third mode is susceptible. In our own country, and more especially on the Continent, turbines have attracted much attention, and many forms of them have been made known by published descriptions. The subject of the present communication is a new water wheel, which belongs to the same general class, and which has recently been invented and brought successfully into use by the author.

“In this machine the moving wheel is placed within

TABULATED STATEMENT of Experiments made on March 20th, 1854, by Professor James Thomson, C. E., University of Glasgow; on the Vortex Wheel at Ballygullan, to determine its Efficiency. The Radius of the Friction Brake was 4 feet 2 inches. The corresponding Circumference is 26.18 feet. In this Table the quantity of Water passing over the Weir is calculated by means of M. M. Poncett and Lesbrou Coefficients for Notches.

Number of Experiments.	Total weight on cord of Break in pounds.	Time of each Experiment.	Number of Revolutions of Shaft during Experiment.	Number of Revolutions of Shaft per minute.	Total height of fall in feet.	Height in feet of Water over Weir, length of Weir being 3 feet.	Number of cubic feet of Water per minute over Weir.	Number of cubic feet of Water per minute, supposed to the Wheel, 1.39 being deducted to wet the Break.	Work given out at Friction Brake, in foot pounds per minute.	Horse Power given out by the Wheel.	Work due to the fall of water in foot-pounds per minute.	Efficiency of the Wheel or Work given out by the Wheel, the Work being 100.	Remarks entered at the time of the experiments, and relating to the supposed accuracy of the experiments.
1	46-31	5 34	1800	323.3	23-73	-718	355.8	354.4	392000	11.88	523900	74.81	Satisfactorily accurate.
2	46-31	5 38	1800	319.5	23-71	-718	355.8	354.4	387400	11.73	523500	73.99	Satisfactorily accurate.
3	53-31	6 11	1800	201.	23-72	-718	355.8	354.4	406100	12.31	523700	77.55	Good.
4	60-31	7 9	1800	251.7	23-71	-718	355.8	354.4	397400	12.04	523500	75.91	Water supposed running over.
5	53-31	6 12	1800	290.3	23-71	-718	355.8	354.4	406100	12.27	523500	77.39	One of the best, no water lost.
6	39-31	5 26	1800	351.2	23-21	-718	355.8	354.4	340800	10.33	512400	66.51	{ Some water lost at water case, and water too low part of time.
7	46-31	6 9	1800	292.7	23-77	-665	318.1	316.7	354900	10.75	469000	75.66	Good.
8	46-31	6 13	1800	289.5	23-75	-665	318.1	316.7	351000	10.63	468600	74.90	Good, one of the best.
9	52-31	5 8	1800	350.6	23-75	-665	318.1	316.7	296600	8.99	468600	63.28	Very good.
10	36-31	5 24	1800	333.3	23-75	-665	318.1	316.7	310800	9.59	468600	67.61	Very good.
11	36-31	5 21	1800	336.4	23-75	-665	318.1	316.7	319800	9.69	468600	68.24	Excellent.
12	53-31	7 5	1800	254.1	23-75	-663	316.7	315.3	354600	10.74	466500	75.01	Arm not very steady.
13	53-31	7 14	1800	248.8	23-75	-663	316.7	315.3	347200	10.52	466500	74.43	Arm not very steady.

Abstract of the Data and Calculations according to which the Vortex Wheel was designed.

Total Height of Fall = 24 feet, Standard quantity of Water = 420 cubic feet per minute. Calculated speed 232.5 revolutions per minute. Effective Standard Power at an efficiency of 75 per cent = 16.25 Horse Power. Supply pipe, 21 inch bore. Diameter of wheel, 1 ft. 8½ ins.

REMARKS.—It is to be observed, that as the experiments happened to be made in dry weather, the stream in none of them supplied the standard quantity of water for which the wheel was more particularly adapted. Even with the diminished quantity of water, the efficiencies experimentally found were very high. It is also to be observed, that in some of the experiments the resistance to the wheel was purposely made less than what was most suitable for the water supply. The wheel thus ran considerably too fast in those experiments, and consequently the efficiencies in them came to be not so high as in the others that were more properly arranged. Also, from information received after the time of the experiments, it appeared that during the experiments the Joint Rings of the Vortex were not screwed properly close to the rings of the Water Wheel; and that on their being afterwards screwed, the power of the wheel was sensibly increased. It is therefore probable that still higher efficiencies are attainable than those shown by the above experiments.

a chamber of a nearly circular form. The water is injected into the chamber tangentially at the circumference, and thus it receives a rapid motion of rotation. Retaining this motion it passes onwards towards the centre, where alone it is free to make its exit. The wheel, which is placed within the chamber, and which almost entirely fills it, is divided by thin partitions into a great number of radiating passages. Through these passages the water must flow on its course towards the centre ; and in doing so it imparts its own rotatory motion to the wheel. The whirlpool of water acting within the wheel chamber, being one principal feature of this turbine, leads to the name *Vortex* as a suitable designation for the machine as a whole.

“ The vortex admits of several modes of construction, but the two principal forms are the one adapted for high falls and the one for low falls. The former may be called the High-pressure Vortex, and the latter the Low-pressure Vortex. Examples of these two kinds are in operation at two mills near Belfast.

“ The height of the fall for the first vortex is about 37 feet, and the standard or medium quantity of water, for which the dimensions of the various parts of the wheel and case are calculated, is 540 cubic feet per minute. With this fall and water-supply the estimated power is 28 horse-power, the efficiency being taken at 75 per cent. The proper speed of the wheel, calculated in accordance with its diameter and the velocity of the water entering its chamber, is 355 revolutions per minute. The diameter of the wheel

is $22\frac{1}{2}$ inches, and the extreme diameter of the case is 4 feet 8 inches.

“In the second vortex, the fall being taken at 7 feet, the calculated quantity of water admitted, at the standard opening of the guide-blades, is 2,460 cubic feet per minute. Then, the efficiency of the wheel being taken at 75 per cent., its power will be 24 horse-power. Also, the speed at which the wheel is calculated to revolve is 48 revolutions per minute.

“The two examples which have now been described of vortex water wheels, adapted for very distinct circumstances, will serve to indicate the principal features in the structural arrangements of these new machines in general. Respecting their principles of action some further explanations will next be given. In these machines the velocity of the circumference is made the same as the velocity of the entering water, and thus there is no impact between the water and the wheel; but, on the contrary, the water enters the radiating conduits of the wheel gently, that is to say, with scarcely any motion in relation to their mouths. In order to attain the equalization of these velocities, *it is necessary that the circumference of the wheel should move with the velocity which a heavy body would attain, in falling through a vertical space equal to half the vertical fall of the water, or in other words, with the velocity due to half the fall; and that the orifices through which the water is injected into the wheel-chamber should be conjointly of such area that when all the water required is flowing through them,*

it also may have a velocity due to half the fall. Thus one-half only of the fall is employed in producing velocity in the water; and, therefore, the other half still remains acting on the water within the wheel-chamber at the circumference of the wheel, in the condition of fluid pressure. Now, with the velocity already assigned to the wheel, it is found that this fluid pressure is exactly that which is requisite to overcome the centrifugal force of the water in the wheel, and to bring the water to a state of rest at its exit; the mechanical work due to both halves of the fall being transferred to the wheel during the combined action of the moving water and the moving wheel. In the foregoing statements, the effects of fluid friction, and of some other modifying influences, are, for simplicity, left out of consideration; but in the practical application of the principle, the skill and judgment of the designer must be exercised in taking all such elements, as far as possible, into account. To aid in this, some practical rules, to which the author as yet closely adheres, were made out by him previously to the date of his patent. These are to be found in the specification of the patent, published in the *Mechanics' Magazine* for January 18 and January 25, 1851 (London).

“In respect to the numerous modifications of construction and arrangement which are admissible in the vortex, while the leading principles of action are retained, it may be sufficient here merely to advert,—first, to the use of straight instead of curved radiating passages in the wheel; secondly, to the employment,

for simplicity, of invariable entrance orifices, or of fixed instead of moveable guide-blades; and lastly, to the placing of the wheel at any height, less than about thirty feet, above the water in the tail-race, combined with the employment of suction pipes descending from the central discharge orifices, and terminating in the water of the tail-race, so as to render available the part of the fall below the wheel.

“In relation to the action of turbines in general, the chief and most commonly recognized conditions, of which the accomplishment is to be aimed at, are that the water should flow through the whole machine with the least possible resistance, and that it should enter the moving wheel without shock, and be discharged from it with only a very inconsiderable velocity. The vortex is in a remarkable degree adapted for the fulfilment of these conditions. The water moving centripetally (instead of centrifugally, which is more usual in turbines), enters at the period of its greatest velocity (that is, just after passing the injection orifices) into the most rapidly moving part of the wheel, the circumference; and, at the period when it ought to be as far as possible deprived of velocity, it passes away by the central part of the wheel, the part which has the least motion. Thus, in each case, that of the entrance and that of the discharge, there is an accordance between the velocities of the moving mechanism and the proper velocities of the water.

“The principle of injection from without inwards, adopted in the vortex, affords another important

advantage in comparison with turbines having the contrary motion of the water; as it allows ample room, in the space outside of the wheel, for large and well-formed injection channels, in which the water can be made very gradually and regularly to converge to the most contracted parts, where it is to have its greatest velocity. It is as a concomitant also of the same principle, that the very simple and advantageous mode of regulating the power of the wheel, by the moveable guide-blades already described, can be introduced. This mode, it is to be observed, while giving great variation to the areas of the entrance orifices, retains at all times very suitable forms for the converging water channels.

“Another adaptation in the vortex is to be remarked as being highly beneficial, that, namely, according to which, by the balancing of the contrary fluid pressures due to half the head of water and to the centrifugal force of the water in the wheel, combined with the pressure due to the ejection of the water backwards from the inner ends of the vanes of the wheel when they are curved, only one-half of the work due to the fall is spent in communicating *vis viva* to the water, to be afterwards taken from it during its passage through the wheel; the remainder of the work being communicated through the fluid pressure to the wheel, without any intermediate generation of *vis viva*. Thus the velocity of the water, where it moves fastest in the machine, is kept comparatively low; not exceeding that due to half the height of the fall, while in other turbines the

water usually requires to act at much higher velocities. In many of them it attains at two successive times the velocity due to the whole fall. The much smaller amount of action, or agitation, with which the water in the vortex performs its work, causes a material saving of power by diminishing the loss necessarily occasioned by fluid friction.

“In the vortex, further, a very favourable influence on the regularity of the motion proceeds from the centrifugal force of the water, which, on any increase of the velocity of the wheel, increases, and so checks the water supply; and on any diminution of the velocity of the wheel, diminishes, and so admits the water more freely; thus counteracting, in a great degree, the irregularities of speed arising from variations in the work to be performed. When the work is subject to great variations, as for instance in saw-mills, in bleaching works, or in forges, great inconvenience often arises with the ordinary bucket water-wheels and with turbines which discharge at the circumference, from their running too quickly when any considerable diminution occurs in the resistance to their motion.

“The first vortex which was constructed on the large scale was made in Glasgow, to drive a new beetling-mill of Messrs. C. Hunter and Co., of Dunadry, in County Antrim. It was the only one in action at the time of the meeting of the British Association in Belfast; but the two which have been particularly described in the present article, and one for an unusually high fall, 100 feet, have since been

completed and brought into operation. There are also several others in progress; of which it may be sufficient to particularize one of great dimensions and power, for a new flax-mill at Ballyshannon in the West of Ireland. It is calculated for working at 150 horse-power, on a fall of 14 feet, and it is to be impelled by the water of the River Erne. This great river has an ample reservoir in the Lough of the same name; so that the water of wet weather is long retained, and continues to supply the river abundantly even in the driest weather. The lake has also the effect of causing the floods to be of long duration, and the vortex will consequently be, through a considerable part of the year, and for long periods at a time, deeply submerged under backwater. The water of the tail-race will frequently be seven feet above its ordinary summer level; but as the water of the head-race will also rise to such a height as to maintain a sufficient difference of levels, the action of the wheel will not be deranged or impeded by the floods. These circumstances have had a material influence in leading to the adoption in the present case of this new wheel in preference to the old breast or undershot wheels."

The next tables have been arranged by us from Mr. Francis' valuable experiments. They show the ratio of the effect to the power in two wheels, the first a centre-vent wheel, erected at the Boott Cotton Mills, and the second a turbine, erected at the Tremont Mills, Lowell, Massachusetts.

The maximum effect .794 was obtained from the

Tremont turbine experiments, when the velocity of the interior circumference of the wheel was to that due to the whole fall as $\cdot 63$ to 1; and an effect of 78 per cent. was obtained when these velocities were as $\cdot 51$ to 1. In the Boott centre-vent wheel the maximum effect $\cdot 797$ was obtained when the velocity of the exterior circumference was to that due to the fall as $\cdot 64$ to 1; and a like effect was produced when this ratio was $\cdot 708$ to 1. Indeed, between these ratios the useful effect was nearly the same; an effect of $\cdot 78$ to $\cdot 79$ was obtained for all such ratios between limits of $\cdot 59$ and $\cdot 71$ to 1, averaging a ratio of $\cdot 65$ to 1. If a turbine have a variable fall, say from 2 to 1, and be of sufficient capacity to give the required power always, the dimensions should be determined from the lesser fall, and if correctly so determined, it will not have sufficient velocity for the greater fall. When the fall is greatest the quantity in the same place is generally least, giving thereby a lessened effect when most is required. For such cases two turbines may be used with advantage.

TABLE showing the Results of Experiments upon a Model of a Centre-vent Water Wheel, and also upon a Centre-vent Water Wheel at the Boot Cotton Mills, Lowell, Massachusetts, arranged from Mr. Francis' valuable Experiments. Diameter of Wheel to the outside of the Buckets, about 9'3 feet. Depths of External Guide Curves about 75 foot. External height of Wheel about 15 feet. Number of Buckets, 40. Mean height of the orifices between the Guides, 1 foot. Diameter of Supply Pipe, 8 feet. The first Seven Experiments were made on a Model, the Exterior Diameter of the Wheel being 22½ inches, Interior Diameter 19½ inches, height between the Crowns 2½ inches, and the number of Buckets 36. The Construction of the Wheel is shown in Mr. Francis' Book, and all necessary Details. The general principle of the Centre-vent Wheel of Francis' and Thomson's Vortex Wheel appears to be the same; the Guide Blades being fewer in the latter, and capable of adjustment.

Numbers of the Experiments.	Falls acting on the Wheels.	Depths on the Weirs in feet.	Cubic feet of Water acting on the Wheel per second.	Number of pounds avoirdupois, if raised one foot per second.	Revolutions of the Wheel per second.	Weight in the scale in pounds avoirdupois.	Ratio of the effect to the power calculated by means of Prony's Brake.	Velocity due to the fall acting on the Wheel, in feet per second.	Velocity of the outside circumference of the wheel, in feet per second.
1	2	3	4	5	6	7	8	9	10
1	2'52	365	2'15	337.7	1'14	16'	679	12'73	6'83
2	2'46	366	2'16	331.5	1'34	14'	711	12'58	8'03
3	2'50	367	2'17	338.0	1'54	12'5	716	12'68	9'23
4	2'60	372	2'21	358.2	1'70	12'	705	12'93	10'03
5	2'60	373	2'22	361.3	1'73	11'5	692	12'95	10'36
6	2'60	373	2'22	359.6	1'71	11'5	689	12'93	10'26
7	2'60	374	2'23	360.8	1'90	10'0	648	12'93	11'15
8	14'60	1'296	67'53	61493.4	.59	575'6	377	30'65	17'39
9	14'67	1'262	64'39	59364.4	.88	202'1	203	30'72	25'77
10	14'57	1'282	66'43	60347.0	.72	407'2	332	30'61	21'21
11	14'16	1'284	66'61	58821.6	.54	606'0	382	30'18	15'97
12	14'20	1'290	67'03	59351.7	.50	666'3	381	30'22	14'65
13	14'14	1'288	66'89	59002.2	.45	720'5	373	30'16	13'18
14	14'24	1'294	67'37	59858.1	.25	931'9	269	30'27	7'46
15	14'30	1'211	61'08	54486.4	1'01	30'33	29'75
16	14'29	1'514	85'	75732.8	1'01	334'1	303	30'32	29'63
17	14'23	1'531	86'35	76608.0	.96	441'2	376	30'25	28'16
18	14'20	1'539	87'08	77093.2	.93	501'8	413	30'22	27'55
19	14'19	1'547	87'68	77607.2	.90	562'6	444	30'21	26'43
20	14'19	1'554	88'28	78143.8	.86	656'6	489	30'22	25'12
21	13'78	1'576	90'17	77480.4	.69	955'5	582	29'77	20'37
22	13'61	1'594	91'70	77812.1	.60	1140'9	596	29'58	17'54
23	13'94	1'418	77'11	67076.7	1'18	29'9	34'51
24	13'52	1'642	95'76	80736.3	1'05	263'0	245	29'49	32'44
25	13'37	1'673	98'49	82145.2	.99	531'8	437	29'33	29'14
26	13'37	1'695	100'42	83728.2	.90	786'8	576	29'32	26'43
27	13'40	1'718	102'42	85571.4	.82	1001'5	657	29'35	24'20
28	13'38	1'723	102'82	85800.0	.79	1107'4	690	29'34	23'07
29	13'34	1'731	103'52	86138.0	.75	1205'0	710	29'30	21'69
30	13'32	1'734	103'77	86218.8	.79	1259'2	720	29'27	21'26
31	13'33	1'733	103'70	86229.3	.71	1297'3	728	29'29	20'66
32	13'30	1'739	104'23	86483.7	.70	1329'8	731	29'25	20'50
33	13'70	1'598	92'02	78648.0	1'25	29'70	36'78
34	13'40	1'832	112'52	94057.5	.71	1554'2	797	29'36	30'81
35	13'43	1'837	112'99	94662.2	.70	1584'0	796	29'39	29'51
36	13'33	1'832	112'56	93603.9	.68	1613'9	797	29'28	19'93
37	13'38	1'837	113'00	94296.4	.67	1644'4	797	29'33	19'71
38	13'39	1'838	113'07	94415.2	.66	1675'1	796	29'34	19'36
39	13'38	1'839	113'16	94471.1	.65	1705'5	796	29'34	19'03
40	13'36	1'838	113'09	94219.0	.64	1735'9	797	29'31	18'67
41	13'38	1'844	113'67	94881.9	.62	1768'4	791	29'34	18'32
42	13'40	1'851	114'29	95571.2	.61	1802'1	787	29'36	18'00
43	13'32	1'848	113'97	94703.1	.59	1836'2	781	29'27	17'38
44	13'54	1'809	110'45	93270.1	..	3155'3	..	29'51	..
45	13'57	1'807	110'32	93422.4	..	2793'3	..	29'55	..
46	13'60	1'688	99'79	84635.0	1'29	29'57	37'70

TABLE showing the Results of Experiments upon the Turbine at Tremont Mills, Lowell, Massachusetts, arranged from Mr. Francis' valuable Experiments. Diameter, measured to the Exterior Circumference of Crowns of the Wheel, 8'333 feet. Height of Buckets from top of the Disc to the bottom of the Garniture, 31 feet. Number of Buckets, 44. Width of the Buckets, 8 foot nearly. Width of Guide Curves, 2'3 feet nearly. Number of Ditto, 33. A Double Weir with 4 end constructions, and 16'98 feet long, used for gauging the Water, the Crest being 6'5 feet above the floor of the Wheel Pit. The Falls show the difference of heads in the Forebay and Wheel Pit. For further details, see Francis' Lowell Hydraulic Experiments, pp. 1 to 43. The supply pipe is fully a quadrant, and varies from 6 to 9 feet in diameter.

Numbers of the Experiments.	Falls acting on the Wheel.	Depth on the Weir in feet.	Cubic feet of Water acting on the Wheel per second.	Number of pounds acting on the wheel one foot per second.	Number of revolutions of the Wheel per second.	Weight in the scale in pounds avoirdupois.	Ratio of the effect to the power, calculated by means of Prony's brake or dynamometer.	Velocity due to the Fall acting on the Wheel, in feet per second.	Velocity of the interior circumference of the Wheel, in feet per second.
1	2	3	4	5	6	7	8	9	10
1	12'864	1'88	139'42	111870'0	'891	1443'34	'784	28'76	18'95
2	12'869	1'88	139'47	111951'2	'894	1443'34	'784	28'77	18'96
3	12'611	2'02	154'40	121444'3	1'532	411'48	'353	28'48	32'49
4	12'696	1'97	149'46	118363'5	1'382	638'36	'507	28'58	29'32
5	12'777	1'94	146'02	116373'2	1'245	854'87	'622	28'67	26'40
6	12'819	1'92	143'91	115067'3	1'125	1057'49	'703	28'71	23'86
7	12'856	1'91	142'52	114284'2	1'067	1156'27	'735	28'76	22'63
8	12'888	1'90	142'04	114187'1	1'024	1229'41	'750	28'79	21'71
9	12'896	1'90	141'28	113640'9	'970	1319'22	'766	28'80	20'57
10	12'883	1'89	140'08	112568'7	'923	1397'12	'779	28'79	19'57
11	12'899	1'88	139'90	112563'3	'902	1433'43	'781	28'80	19'13
12	12'905	1'88	139'01	111893'5	'892	1454'24	'789	28'81	18'92
13	12'899	1'88	139'03	111859'4	'885	1464'80	'788	28'80	18'77
14	12'902	1'87	138'85	111740'3	'880	1474'37	'790	28'81	18'66
15	12'906	1'87	138'51	111504'9	'866	1498'66	'792	28'81	18'37
16	12'915	1'87	138'27	111384'0	'836	1552'44	'794	28'82	17'73
17	12'984	1'87	138'23	111521'1	'813	1597'08	'792	28'84	17'25
18	12'939	1'86	137'71	111139'7	'742	1794'40	'781	28'85	15'74
19	12'940	1'84	135'14	109077'1	'646	1911'45	'770	28'85	13'69
20	12'963	1'84	135'34	109433'4	'647	1911'45	'769	28'88	13'72
21	12'977	1'83	133'75	108265'8	'532	2167'38	'725	28'89	11'29
22	12'948	1'82	133'43	107764'7	'454	2367'88	'679	28'86	9'63
23	12'964	1'87	138'62	112009'3	'833	1565'21	'791	28'86	17'64
24	12'932	1'87	138'50	111720'6	'817	1590'50	'791	28'84	17'32
25	12'951	1'87	138'37	111777'2	'789	1641'34	'788	28'86	16'74
26	12'758	1'92	143'33	114060'7	1'483	390'95	'346	28'65	31'45
27	12'909	1'86	137'75	110917'6	1'142	963'30	'675	28'82	24'21
28	12'950	1'86	137'00	110664'7	1'025	1150'77	'725	28'86	21'73
29	12'965	1'84	135'10	109252'2	'930	1293'63	'750	28'88	19'74
30	12'999	1'82	133'30	108082'5	'865	1396'11	'760	28'92	18'35
31	13'026	1'81	131'99	107246'3	'844	1494'68	'763	28'95	17'05
32	13'028	1'80	130'89	106366'6	'708	1656'98	'750	28'95	15'01
33	13'077	1'68	118'55	96699'5	1'351	316'08	'300	29'00	28'66
34	13'134	1'66	116'10	96112'0	1'219	519'69	'453	29'06	25'84
35	13'216	1'63	113'24	95346'0	1'004	832'26	'609	29'15	21'28
36	13'282	1'59	109'71	90898'3	'843	1033'30	'652	29'28	17'88
37	13'310	1'58	107'95	89620'7	'776	1115'02	'656	29'26	16'44
38	13'362	1'54	103'85	86556'6	'616	1277'98	'619	29'32	13'06
39	13'683	1'86	137'36	110380'8	'855	1482'56	'781	28'79	18'13
40	13'396	1'86	136'97	110176'6	'822	1544'37	'784	28'80	17'43
41	12'912	1'85	136'55	109973'0	'789	1604'85	'783	28'82	16'73
42	13'369	1'27	78'84	66746'8	1'146	118'59	'141	29'32	24'30
43	13'396	1'25	76'62	64018'1	'960	325'39	'332	29'35	20'36
44	13'435	1'22	74'05	62062'0	'772	519'86	'440	29'40	16'37
45	13'478	1'19	71'87	60424'6	'672	612'22	'463	29'44	14'25
46	13'613	1'17	70'01	59006'4	'560	704'44	'455	29'48	11'87
47	13'559	1'11	64'50	54554'9	'300	882'02	'330	29'53	6'36
48	13'985	'78	38'22	33340'8	'620	118'59	'150	29'99	13'14
49	14'001	'78	38'57	33663'5	'669	73'14	'102	30'01	14'61
50	14'020	'76	37'17	32508'0	'388	296'39	'240	30'03	8'22

TABLE for Turbines of different Diameters, modified from Francis, operating with different Falls; assuming the useful effect is seventy-five per cent. of the power expended, that the Velocity of the Interior Circumference is fifty-six per cent. of the Velocity due to the Fall, and that also the Height between the Crowns is one-tenth of the Outside Diameter.

Fall in feet.	Outside diameter 2 ft. Inside " 1'56" Number of buckets 36.			Outside diameter 3 ft. Inside " 2'38" Number of buckets 36.			Outside diameter 4 ft. Inside " 3'24" Number of buckets 42.			Outside diameter 5 ft. Inside " 4'11" Number of buckets 45.		
	Water discharged in cubic feet per second.	Horse-power.	Revolutions per minute.	Water discharged in cubic feet per second.	Horse-power.	Revolutions per minute.	Water discharged in cubic feet per second.	Horse-power.	Revolutions per minute.	Water discharged in cubic feet per second.	Horse-power.	Revolutions per minute.
5	4.5	1.9	123	10.1	4.3	80	17.88	7.6	59	27.9	11.9	47
6	4.9	2.5	135	11.0	5.6	88	19.6	10.0	65	30.6	15.6	51
7	5.3	3.1	148	11.9	7.1	95	21.17	12.6	70	33.1	19.7	55
8	5.7	3.8	156	12.7	8.7	102	22.63	15.4	75	35.3	24.0	59
9	6.0	4.6	165	13.5	10.3	108	24.00	18.4	79	37.5	28.7	63
10	6.3	5.4	174	14.2	12.1	114	25.30	21.5	84	39.5	33.6	66
11	6.6	6.2	183	14.9	13.9	119	26.53	24.8	88	41.5	38.8	69
12	6.9	7.1	191	15.6	15.9	125	27.71	28.3	92	43.3	44.2	72
13	7.2	8.0	199	16.2	17.9	130	28.84	31.9	95	45.1	49.8	75
14	7.5	8.9	206	16.8	20.0	135	29.93	35.6	99	46.8	55.7	78
15	7.7	9.9	213	17.4	22.2	139	30.98	39.5	103	48.4	61.7	81
16	8.0	10.9	220	18.0	24.5	144	32.00	43.5	106	50.0	68.0	83
17	8.2	11.9	227	18.5	26.8	148	32.99	47.7	109	51.5	74.5	86
18	8.5	13.0	234	19.1	29.2	153	33.94	51.9	112	53.0	81.1	88
19	8.7	14.1	240	19.6	31.7	157	34.87	56.3	115	54.5	88.0	91
20	8.9	15.2	247	20.1	34.2	161	35.78	60.8	118	55.9	95.0	93
21	9.2	16.4	253	20.6	36.8	165	36.66	65.4	121	57.3	102.2	96
22	9.4	17.5	259	21.1	39.5	169	37.52	70.2	124	58.6	109.6	98
23	9.6	18.7	264	21.6	42.2	172	38.37	75.0	127	59.9	117.2	100
24	9.8	20.0	270	22.0	45.0	176	39.19	79.9	130	61.2	124.9	102
25	10.0	21.2	276	22.5	47.8	180	40.00	85.0	132	62.5	132.8	104
26	10.2	22.5	281	22.9	50.7	183	40.79	90.1	135	63.7	140.9	106
27	10.4	23.8	286	23.4	53.7	187	41.57	95.4	138	65.0	149.1	108
28	10.6	25.2	292	23.8	56.7	190	42.33	100.7	140	66.1	157.4	110
29	10.8	26.5	297	24.2	59.7	194	43.08	106.2	143	67.3	165.9	112
30	10.9	27.9	302	24.6	62.8	197	43.82	111.7	145	68.5	174.6	114
31	11.1	29.3	307	25.0	66.0	200	44.54	117.4	147	69.6	183.4	116
32	11.3	30.8	312	25.5	69.2	203	45.25	123.1	150	70.7	192.3	118
33	11.5	32.2	317	25.8	72.5	207	45.96	128.9	152	71.8	201.4	120
34	11.7	33.7	321	26.2	75.8	210	46.65	134.8	154	72.9	210.6	122
35	11.8	35.2	326	26.6	79.2	213	47.33	140.8	157	73.9	220.0	123
36	12.0	36.7	331	27.0	82.6	216	48.00	146.9	159	75.0	229.5	125
37	12.2	38.3	335	27.4	86.1	219	48.66	153.0	161	76.0	239.1	127
38	12.3	39.8	340	27.7	89.6	222	49.32	159.3	163	77.0	248.9	129
39	12.5	41.4	344	28.1	93.2	225	49.96	165.6	165	78.1	258.8	130
40	12.6	43.0	349	28.5	96.8	227	50.60	172.0	167	79.1	268.8	132

TABLE of Turbines of different Diameters, modified from Francis, operating with different Falls; assuming the useful effect is seventy-five per cent. of the power expended, that the Velocity of the Interior Circumference is fifty-six per cent. of the Velocity due to the Fall, and that also the Height between the Crowns is one-tenth of the Outside Diameter.

Fall in feet.	Outside diameter 6 ft. Inside " 5 Number of buckets 48.			Outside diameter 7 ft. Inside " 6.90 Number of buckets 51.			Outside diameter 8 ft. Inside " 6.81 Number of buckets 54.			Outside diameter 10 ft. Inside " 8.67 Number of buckets 60.		
	Water discharged in cubic feet per second.	Horse-power.	Revolutions per minute.	Water discharged in cubic feet per second.	Horse-power.	Revolutions per minute.	Water discharged in cubic feet per second.	Horse-power.	Revolutions per minute.	Water discharged in cubic feet per second.	Horse-power.	Revolutions per minute.
5	40.2	17.1	38	54.8	23.3	32.5	71.5	30.4	28.1	111.8	47.5	22.1
6	44.1	22.5	42	60.0	30.6	35.6	78.4	40.0	30.8	122.5	62.5	24.2
7	47.6	28.3	45	64.8	38.6	38.4	84.7	50.4	33.3	132.3	78.7	26.2
8	50.9	34.6	48	69.3	47.1	41.1	90.5	61.5	35.6	141.4	96.2	28.0
9	54.0	41.3	51	73.5	56.2	43.6	96.0	73.4	37.8	150.0	114.7	29.7
10	56.9	48.4	54	77.5	65.9	46.0	101.2	86.0	39.8	158.1	134.4	31.3
11	59.7	55.8	57	81.3	76.0	48.2	106.1	99.2	41.7	165.8	155.0	32.8
12	62.4	63.6	59	84.9	86.6	50.3	110.8	113.1	43.6	173.2	176.7	34.3
13	64.9	71.7	62	88.3	97.6	52.4	115.4	127.5	45.4	180.3	199.2	35.7
14	67.3	80.1	64	91.7	109.1	54.4	119.7	142.5	47.1	187.1	222.6	37.0
15	69.7	88.9	66	94.9	121.0	56.3	123.9	158.0	48.7	193.6	246.9	38.3
16	72.0	97.9	69	98.0	133.3	58.1	128.0	174.1	50.3	200.0	272.0	39.6
17	74.2	107.2	71	101.0	146.0	59.9	131.9	190.6	51.9	206.2	297.9	40.8
18	76.4	116.8	73	103.9	159.0	61.7	135.8	207.7	53.4	212.1	324.6	42.0
19	78.5	126.7	75	106.8	172.5	63.3	139.5	225.3	54.9	217.9	352.0	43.1
20	80.5	136.8	77	109.6	186.3	65.0	143.1	243.3	56.3	223.6	380.1	44.3
21	82.5	147.2	79	112.3	200.4	66.6	146.6	261.7	57.7	229.1	409.0	45.4
22	84.4	157.9	80	114.9	214.9	68.2	150.1	280.7	59.0	234.5	438.5	46.4
23	86.3	168.8	82	117.5	229.7	69.7	153.5	300.0	60.4	239.8	468.8	47.5
24	88.2	179.9	84	120.0	244.8	71.2	156.8	319.8	61.7	244.9	499.7	48.5
25	90.0	191.2	86	122.5	260.3	72.7	160.0	340.0	62.9	250.0	531.2	49.5
26	91.8	202.8	87	124.9	276.1	74.1	163.2	360.6	64.2	254.9	563.4	50.5
27	93.5	214.6	89	127.3	292.2	75.5	166.3	381.6	65.4	259.8	596.3	51.4
28	95.2	226.7	91	129.6	308.5	76.9	169.3	403.0	66.6	264.6	629.7	52.4
29	96.9	238.9	92	131.9	325.2	78.3	172.3	424.8	67.8	269.3	663.7	53.3
30	98.6	251.4	94	134.2	342.2	79.6	175.3	446.9	68.9	273.9	698.3	54.2
31	100.2	264.1	95	136.4	359.4	80.9	178.2	469.5	70.1	278.4	733.5	55.1
32	101.8	277.0	97	138.6	377.0	82.2	181.0	492.4	71.2	282.8	769.3	56.0
33	103.4	290.0	98	140.7	394.8	83.5	183.8	515.6	72.3	287.2	805.7	56.9
34	105.0	303.3	100	142.9	412.9	84.7	186.6	539.2	73.4	291.5	842.6	57.7
35	106.5	316.8	101	144.9	431.2	86.0	189.3	563.2	74.5	295.8	880.0	58.5
36	108.0	330.5	103	147.0	449.8	87.2	192.0	587.5	75.5	300.0	918.0	59.4
37	109.5	344.3	104	149.0	468.7	88.4	194.6	612.2	76.6	304.1	956.5	60.2
38	111.0	358.4	106	151.0	487.8	89.6	197.3	637.1	77.6	308.2	995.5	61.0
39	112.4	372.6	107	153.0	507.2	90.8	199.8	662.5	78.6	312.2	1035.1	61.8
40	113.8	387.1	108	154.9	526.8	91.9	202.4	688.1	79.6	316.2	1075.2	62.6

THE HYDRAULIC RAM has been applied with advantage in raising water to a considerable height by the momentum of a larger quantity at a lower level. The shock of the valves, and vibration of the machine, require heavy and strong setting, and considerable strength in all the parts. This limits its application, and prevents its use for raising large quantities of water. The work done by the ram, in over one thousand experiments by Eytelwein, did not exceed in any of them 1480 lbs. raised one foot in one minute; and in France, the ram put up by the younger Montgolfier, said to be the largest constructed, raised only 7400 lbs. one foot high per minute, and had a useful effect, it is reported, of $\cdot 65$. This ram was put up at Mello, near Clermont-sur-Oise. Its dimensions were—

Length of the body pipe or injection pipe	108 feet.
Diameter	4·3 inches.
Weight of body pipe.	3190 lbs.
Weight of head	440 lbs.
Contents of air-chamber	1½ gallons.

This ram worked under a head of 37 feet, discharging in use 81½ gallons each minute, and raising 3·85 gallons a height of 195 feet.

The largest ram employed by Eytelwein in his experiments had the following dimensions—

Length of the body pipe or injection pipe	43 feet 9 inches.
Diameter of ditto	0 feet 2½ inches.
Contents of air-chamber	1·94 gallons.
Area of tail or escape valve	3·74 square inches.

and his experiments led to the following practical formula by D'Aubuisson—

$$\frac{d}{D} \frac{h'}{h} = 1.42 - .28 \sqrt{\frac{h'}{h}} :$$

in which D is the water used per minute in gallons, d the quantity raised in gallons, h the head used, and h' the lift of the quantity d . By a slight reduction we get

$$d h' = 1.42 D (h - .28 \sqrt{h h'})$$

for the effect produced, which is reduced nearly one-sixth for practical application, giving the formula

$$d h' = 1.2 D (h - .2 \sqrt{h h'})$$

for the work done.

EXPERIMENTAL RESULTS—HYDRAULIC RAM.

Number of strokes per minute.	Height in feet of		Ratio of heights.	Gallons of water per minute.		Ratio $\frac{d h'}{D h}$		Ratio $\frac{D}{d}$
	Fall h	Elevation h'	$\frac{h'}{h}$	Ex- pended D	Raised d	Experi- ments.	For- mula.	
66	Ft. 10' 0"	In. 26' 4"	2.63	10.65	3.39	.9	.97	2.92
54	10 2	32 4	3.18	13.97	3.83	.873	.92	3.67
50	9 11	38 8	3.9	12.01	2.622	.85	.87	4.58
52	8 0	32 4	4.	8.16	1.687	.847	.85	4.72
45	8 9	38 8	4.4	10.85	2.09	.845	.84	5.2
42	7 5	38 8	5.21	9.92	1.5	.787	.78	6.62
36	6 0	38 8	6.5	8.89	1.05	.754	.71	8.62
26	4 6½	32 4	7.2	5.23	.495	.672	.67	10.7
31	5 0	38 7	7.7	8.05	.704	.667	.65	11.54
23	4 1	38 8	9.47	11.11	.649	.548	.56	17.2
17	3 0	32 2	10.7	10.8	.479	.473	.51	22.6
15	3 3	38 8	11.9	12.34	.363	.352	.45	33.8
14	2 6	38 8	15.5	11.95	.22	.284	.32	54.6
10	1 11½	38 8	19.3	9.81	.088	.181	.18	106.6

Eytelwein recommends, that the length of the body-

F F

pipe should not be less than three-fourths of the height to which the water is to be raised; its diameter in inches equal $\cdot58 \sqrt{D}$; the diameter of the rising pipe $\cdot3 \sqrt{D}$; and the contents of the air-chamber equal to that of the rising pipe. If D be in cube feet, then diameter, in inches, of the body-pipe may be taken $= 1\cdot5 \sqrt{D}$, and that of the rising pipe $= \cdot75 \sqrt{D}$.

The following table gives the result of experiments made by Montgolfier and his son:—

TABLE OF EXPERIMENTAL RESULTS—HYDRAULIC RAM.

Height.		Water per Minute.		$\frac{d h'}{D h}$	Mean Ratio $\frac{d h'}{D h}$
Fall h	Elevation h	Expended D	Delivered d		
Ft. In.	Ft. In.	Gallons.	Gallons.		
8' 6"	52' 8"	15	1·37	·57	...
37 2	195 0	31	3·85	·653	...
34 9	111 11	18·5	3·74	·651	·65
3 3	14 11	437	59·18	·629	...
22 10	196 10	2·86	0·22	·671	...

In several experiments made by the author in 1866, for the Directors of the Midland Great Western Railway, Ireland, on two rams at work at the Broadstone Terminus, Dublin, where the lifts varied from 22 to 24 feet, the ratio of the effect to the power varied from $\cdot4$ to $\cdot84$; the latter effect having been got with a fall of 8 feet, a lift of 22 feet, and 95 beats in a minute. An effect of $\cdot395$ was got with a fall of 14 feet, a lift of 24 feet, and 45 beats in a minute.

Latterly, the Messrs. Easton and Amos have patented improvements in this machine, and have raised water

to a height of 330 feet. The injection pipe is laid by them at an inclination of about one in four for high falls, and varies down to one in eighteen for smaller falls. The quantities raised in their practice vary up to six gallons per minute.

WATER-PRESSURE ENGINES give a useful effect, varying up to 70 per cent. for the best constructed. An immense amount of mechanical skill and invention has been brought to bear on their construction, and in Weisbach's book* a useful effect of 83 per cent. has been calculated; this is, however, a result seldom obtained in practice, where two-thirds, or 66 per cent., is nearer to the general efficiency. Jordan got a maximum efficiency of .66 from one of the Clausthal engines, making four strokes per minute, and .71 making three strokes per minute. These results were for the combined engine and pumps, from which it was calculated that the efficiency of the engine alone was, in the first case .83, and in the second .85. It would be a great mistake to calculate on such high efficiencies.

CORN MILLS will grind about a bushel of corn per horse-power per hour, but much depends on the state of the stones and of the grain. The value of the work done in an hour being once known, the value of the standard horse-power can be determined accordingly.

* Vol. ii., p. 342.

TABLE I.—Coefficients of Discharge from Square and differently proportioned Rectangular Lateral Orifices in thin Vertical Plates, arranged from Poncelet and Lesbros.

Heads of water measured to the upper sides of the orifices, in English inches.	Ratio of the head to the length of the orifice.	Square orifice 8" x 8". Ratio of the sides 1 to 1.		Rectangular orifice 8" x 4". Ratio of the sides 2 to 1.		Rectangular orifice 8" x 2". Ratio of the sides 4 to 1.	
		Heads taken back from the orifice.	Heads taken at the orifice.	Heads taken back from the orifice.	Heads taken at the orifice.	Heads taken back from the orifice.	Heads taken at the orifice.
0.000			.619		.667		.713
0.197	.025		.597		.630		.668
0.394	.050		.595		.618	.607	.642
0.591	.075		.594	.593	.615	.612	.639
0.787	.100	.572	.594	.596	.614	.615	.638
1.181	.150	.578	.593	.600	.613	.620	.637
1.575	.200	.582	.593*	.603	.612	.623	.636
1.969	.250	.585	.593	.605	.612*	.625	.636
2.362	.300	.587	.594	.607	.613	.627	.635
2.756	.350	.588	.594	.609	.613	.628	.635
3.150	.400	.589	.594	.610	.613	.629	.635
3.545	.450	.591	.595	.610	.614	.629	.634
3.937	.500	.592	.595	.611	.614	.630	.634
4.724	.600	.593	.596	.612	.614	.630	.633
5.512	.700	.595	.597	.613	.614	.630	.632
6.299	.800	.596	.597	.614	.615	.631*	.631
7.087	.900	.597	.598	.615	.615	.630	.631
7.874	1.000	.598	.599	.615	.615	.630	.630
9.843	1.250	.599	.600	.616	.616	.630	.630
11.811	1.500	.600	.601	.616	.616	.629	.629
15.748	2.000	.602	.602	.617	.617	.628	.629
19.685	2.500	.603	.603	.617*	.617*	.628	.628
23.622	3.000	.604	.604	.617	.617	.627	.627
27.560	3.500	.604	.604	.616	.616	.627	.627
31.497	4.000	.605	.605	.616	.616	.627	.627
35.434	4.500	.605*	.605*	.615	.615	.626	.626
39.371	5.000	.605	.605	.615	.615	.626	.626
43.307	5.500	.604	.604	.614	.614	.625	.625
47.245	6.000	.604	.604	.614	.614	.624	.624
51.182	6.500	.603	.603	.613	.613	.622	.622
55.119	7.000	.603	.603	.612	.612	.621	.621
59.056	7.500	.602	.602	.611	.611	.620	.620
62.993	8.000	.602	.602	.611	.611	.618	.618
66.930	8.500	.602	.602	.610	.610	.617	.617
70.867	9.000	.601	.601	.609	.609	.615	.615
74.805	9.500	.601	.601	.608	.608	.614	.614
78.742	10.000	.601	.601	.607	.607	.613	.614
118.112	15.000	.601	.601	.603	.603	.606	.606

* See pages 60, 61, and 62.

TABLE I.—Coefficients of Discharge from Square and differently proportioned Rectangular Lateral Orifices in thin Vertical Plates, arranged from Poncelet and Lesbros.

Rectangular orifice 8" x 1' 18". Ratio of the sides 7 to 1 nearly.		Rectangular orifice 8" x 0' 8". Ratio of the sides 10 to 1.		Rectangular orifice 8" x 0' 4". Ratio of the sides 20 to 1.		Ratio of the head to the length of the orifice.	Heads of water mea- sured to the upper sides of the orifices in English inches.
Heads taken back from the orifice.	Heads taken at the orifice.	Heads taken back from the orifice.	Heads taken at the orifice.	Heads taken back from the orifice.	Heads taken at the orifice.		
	·766		·783		·795		
	·725		·750		·778	·025	0·197
·630	·687	·660	·720	·705	·762	·050	0·394
·632	·674	·660	·707	·697	·745	·075	0·591
·634	·668	·659	·697	·694	·729	·100	0·787
·638	·659	·659	·685	·688	·708	·150	1·181
·640	·654	·658	·678	·683	·695	·200	1·575
·640*	·651	·658	·672	·679	·686	·250	1·969
·640	·647	·657	·668	·676	·681	·300	2·362
·639	·645	·656	·665	·673	·677	·350	2·756
·638	·643	·656	·662	·670	·675	·400	3·150
·637	·641	·655	·659	·668	·672	·450	3·543
·637	·640	·654	·657	·666	·669	·500	3·937
·636	·637	·653	·655	·663	·665	·600	4·724
·635	·636	·651	·653	·660	·661	·700	5·512
·634	·635	·650	·651	·658	·659	·800	6·299
·634	·634	·649	·650	·657	·657	·900	7·087
·633	·633	·648	·649	·655	·656	1·000	7·874
·632	·632	·646	·646	·653	·653	1·250	9·843
·632	·632	·644	·644	·650	·651	1·500	11·811
·631	·631	·642	·642	·647	·647	2·000	15·748
·630	·630	·640	·640	·644	·645	2·500	19·685
·630	·630	·638	·638	·642	·643	3·000	23·622
·629	·629	·637	·637	·640	·640	3·500	27·560
·629	·629	·636	·636	·637	·637	4·000	31·497
·628	·628	·634	·634	·635	·635	4·500	35·434
·628	·628	·633	·633	·632	·632	5·000	39·371
·627	·627	·631	·631	·629	·629	5·500	43·307
·626	·626	·628	·628	·626	·626	6·000	47·245
·624	·624	·625	·625	·622	·622	6·500	51·182
·622	·622	·622	·622	·618	·618	7·000	55·119
·620	·620	·619	·619	·615	·615	7·500	59·056
·618	·618	·617	·617	·613	·613	8·000	62·993
·616	·616	·615	·615	·612	·612	8·500	66·930
·615	·615	·614	·614	·612	·612	9·000	70·867
·613	·613	·612	·612	·611	·611	9·500	74·805
·612	·612	·612	·612	·611	·611	10·000	78·742
·603	·608	·610	·610	·609	·609	15·000	118·112

* See pages 60, 61, and 62.

TABLE II.—For finding the Velocities from the Altitudes, and the Altitudes from the Velocities.—Altitudes 0 feet 0 $\frac{1}{16}$ inch to 0 feet 3 $\frac{1}{4}$ inches.

Altitudes h in feet and inches.	Coefficients of velocity, and the corresponding velocities of discharge in inches per second.					
	1. Values of $v = 27.8 \sqrt{h}$, the theoretical velocity in inches.	2. Values of $v = 27.077 \sqrt{h}$, Coefficient .974.	3. Values of $v = 26.577 \sqrt{h}$, Coefficient .956.	4. Values of $v = 23.908 \sqrt{h}$, Coefficient .860.	5. Values of $v = 22.957 \sqrt{h}$, Coefficient .815.	6. Values of $v = 22.24 \sqrt{h}$, Coefficient .800.
0 0 $\frac{1}{16}$	2.78	2.71	2.66	2.39	2.27	2.22
0 0 $\frac{1}{8}$	3.48	3.38	3.32	2.99	2.83	2.78
0 0 $\frac{1}{4}$	6.95	6.77	6.64	5.98	5.66	5.56
0 0 $\frac{3}{8}$	9.829	9.57	9.40	8.45	8.01	7.86
0 0 $\frac{1}{2}$	12.038	11.72	11.51	10.35	9.81	9.63
0 0 $\frac{5}{8}$	13.900	13.54	13.29	11.95	11.33	11.12
0 0 $\frac{3}{4}$	15.541	15.14	14.86	13.36	12.67	12.43
0 0 $\frac{7}{8}$	17.024	16.58	16.27	14.64	13.87	13.62
0 0 1	18.388	17.91	17.58	15.81	14.99	14.71
0 0 $1\frac{1}{16}$	19.658	19.15	18.79	16.91	16.02	15.73
0 0 $1\frac{1}{8}$	20.850	20.31	19.93	17.93	16.99	16.68
0 0 $1\frac{1}{4}$	21.978	21.41	21.01	18.90	17.91	17.58
0 0 $1\frac{3}{8}$	23.051	22.45	22.04	19.82	18.79	18.44
0 0 $1\frac{1}{2}$	24.076	23.45	23.02	20.70	19.62	19.26
0 0 $1\frac{5}{8}$	25.059	24.41	24.00	21.55	20.42	20.05
0 0 $1\frac{3}{4}$	26.005	25.33	24.86	22.36	21.19	20.80
0 0 $1\frac{7}{8}$	26.917	26.22	25.73	23.15	21.94	21.53
0 0 2	27.800	27.08	26.58	23.91	22.66	22.24
0 0 $2\frac{1}{16}$	29.486	28.72	28.19	25.36	24.03	23.59
0 0 $2\frac{1}{8}$	31.081	30.27	29.71	26.73	25.33	24.87
0 0 $2\frac{1}{4}$	32.598	31.75	31.16	28.03	26.57	26.08
0 0 $2\frac{3}{8}$	34.048	33.19	32.58	29.30	27.75	27.26
0 0 $2\frac{1}{2}$	35.438	34.52	33.88	30.48	28.88	28.35
0 0 $2\frac{5}{8}$	36.776	35.82	35.16	31.63	29.97	29.42
0 0 $2\frac{3}{4}$	38.067	37.08	36.39	32.74	31.02	30.45
0 0 $2\frac{7}{8}$	39.315	38.29	37.59	33.81	32.04	31.45
0 0 3	40.525	39.47	38.74	34.85	33.03	32.42
0 0 $3\frac{1}{16}$	41.700	40.62	39.87	35.86	33.99	33.36
0 0 $3\frac{1}{8}$	42.843	41.73	40.96	36.84	34.92	34.27
0 0 $3\frac{1}{4}$	43.956	42.81	42.02	37.80	35.82	35.16
0 0 $3\frac{3}{8}$	45.041	43.87	43.06	38.74	36.71	36.03
0 0 $3\frac{1}{2}$	46.101	44.90	44.07	39.65	37.57	36.88
0 0 $3\frac{5}{8}$	47.137	45.90	45.06	40.54	38.42	37.71
0 0 $3\frac{3}{4}$	48.151	46.90	46.03	41.41	39.24	38.52
0 0 $3\frac{7}{8}$	49.144	47.87	46.98	42.26	40.05	39.32
0 0 4	50.117	48.81	47.91	43.10	40.85	40.09
0 0 $4\frac{1}{16}$	51.072	49.74	48.82	43.92	41.62	40.86
0 0 $4\frac{1}{8}$	52.009	50.66	49.72	44.73	42.39	41.61
0 0 $4\frac{1}{4}$	52.930	51.55	50.60	45.52	43.14	42.34
0 0 $4\frac{3}{8}$	53.834	52.43	51.47	46.30	43.88	43.07
0 0 $4\frac{1}{2}$	54.725	53.30	52.32	47.06	44.60	43.78

TABLE II.—For finding the Velocities from the Altitudes, and the Altitudes from the Velocities.—Altitudes 0 feet 0 $\frac{1}{16}$ inch to 0 feet 3 $\frac{3}{8}$ inches.

Coefficients of velocity, and the corresponding velocities of discharge in inches per second.						Altitudes h in feet and inches.
7. Values of $v = 19.46 \sqrt{h}$ Coefficient .700.	8. Values of $v = 18.515 \sqrt{h}$ Coefficient .686.	9. Values of $v = 17.458 \sqrt{h}$ Coefficient .668.	10. Values of $v = 17.153 \sqrt{h}$ Coefficient .617.	11. Values of $v = 16.847 \sqrt{h}$ Coefficient .606.	12. Values of $v = 15.935 \sqrt{h}$ Coefficient .584.	
1.95	1.85	1.75	1.72	1.68	1.62	0 0 $\frac{1}{16}$
2.43	2.31	2.18	2.15	2.11	2.03	0 0 $\frac{1}{8}$
4.87	4.63	4.36	4.29	4.21	4.06	0 0 $\frac{1}{4}$
6.88	6.55	6.17	6.06	5.96	5.74	0 0 $\frac{3}{8}$
8.43	8.02	7.56	7.43	7.29	7.03	0 0 $\frac{1}{2}$
9.73	9.26	8.73	8.58	8.42	8.12	0 0 $\frac{5}{8}$
10.88	10.35	9.76	9.59	9.42	9.08	0 0 $\frac{3}{4}$
11.92	11.24	10.69	10.50	10.32	9.94	0 0 $\frac{7}{8}$
12.87	12.25	11.55	11.35	11.14	10.74	0 0 $\frac{1}{2}$
13.76	12.97	12.34	12.13	11.91	11.48	0 0 $\frac{1}{2}$
14.60	13.89	13.09	12.86	12.64	12.18	0 0 $\frac{1}{2}$
15.38	14.64	13.80	13.56	13.32	12.84	0 0 $\frac{1}{2}$
16.14	15.35	14.48	14.22	13.97	13.46	0 0 $\frac{1}{2}$
16.85	16.03	15.12	14.85	14.59	14.06	0 0 $\frac{1}{2}$
17.54	16.69	15.74	15.46	15.19	14.63	0 0 $\frac{1}{2}$
18.20	17.32	16.33	16.04	15.76	15.09	0 0 $\frac{1}{2}$
18.84	17.93	16.90	16.61	16.31	15.72	0 0 $\frac{1}{2}$
19.46	18.51	17.46	17.15	16.85	16.24	0 1
20.64	19.64	18.52	18.19	17.87	17.22	0 1 $\frac{1}{16}$
21.76	20.70	19.52	19.18	18.84	18.15	0 1 $\frac{1}{8}$
22.82	21.71	20.47	20.11	19.75	19.04	0 1 $\frac{1}{8}$
23.85	22.69	21.38	21.01	20.63	19.88	0 1 $\frac{1}{8}$
24.81	23.60	22.26	21.87	21.48	20.70	0 1 $\frac{1}{8}$
25.74	24.49	23.10	22.69	22.29	21.48	0 1 $\frac{1}{8}$
26.65	25.35	23.91	23.49	23.07	22.23	0 1 $\frac{1}{8}$
27.52	26.18	24.69	24.26	23.82	22.96	0 2
28.37	26.99	25.45	25.00	24.50	23.67	0 2 $\frac{1}{16}$
29.19	27.77	26.19	25.73	25.27	24.35	0 2 $\frac{1}{8}$
29.99	28.53	26.91	26.43	25.96	25.02	0 2 $\frac{1}{8}$
30.77	29.27	27.60	27.12	26.64	25.67	0 2 $\frac{1}{8}$
31.53	30.00	28.29	27.79	27.29	26.30	0 2 $\frac{1}{8}$
32.27	30.70	28.95	28.44	27.94	26.92	0 2 $\frac{1}{8}$
33.00	31.39	29.60	29.08	28.57	27.53	0 2 $\frac{1}{8}$
33.71	32.07	30.24	29.71	29.18	28.12	0 3
34.40	32.73	30.86	30.32	29.78	28.70	0 3 $\frac{1}{16}$
35.08	33.38	31.47	30.92	30.37	29.27	0 3 $\frac{1}{16}$
35.75	34.01	32.07	31.51	30.95	29.83	0 3 $\frac{1}{16}$
36.41	34.64	32.66	32.09	31.52	30.37	0 3 $\frac{1}{16}$
37.05	35.25	33.24	32.66	32.08	30.91	0 3 $\frac{1}{16}$
37.68	35.85	33.81	33.22	32.62	31.44	0 3 $\frac{1}{16}$
38.31	36.45	34.37	33.77	33.16	31.96	0 3 $\frac{1}{8}$

TABLE II.—For finding the Velocities from the Altitudes, and the Altitudes from the Velocities.—Altitudes 0 feet 4 inches to 1 foot.

Altitudes h in feet and inches.	Coefficients of velocity, and the corresponding velocities of discharge in inches per second.					
	1. Values of $v = 27.8 \sqrt{h}$, the theoretical velocity in inches.	2. Values of $v = 27.077 \sqrt{h}$, Coefficient .974.	3. Values of $v = 26.577 \sqrt{h}$, Coefficient .966.	4. Values of $v = 25.908 \sqrt{h}$, Coefficient .960.	5. Values of $v = 25.057 \sqrt{h}$, Coefficient .915.	6. Values of $v = 22.34 \sqrt{h}$, Coefficient .800.
0 4	55.600	54.15	53.15	47.82	45.31	44.48
0 4 1	56.462	54.99	53.98	48.56	46.02	45.17
0 4 2	57.311	55.82	54.79	49.29	46.71	45.85
0 4 3	58.148	56.64	55.59	50.01	47.39	46.52
0 4 4	58.973	57.44	56.38	50.72	48.06	47.18
0 4 5	59.786	58.23	57.16	51.42	48.73	47.83
0 4 6	60.589	59.01	57.92	52.11	49.38	48.47
0 4 7	61.368	59.77	58.67	52.78	50.02	49.09
0 5	62.163	60.55	59.43	53.46	50.66	49.73
0 5 1	62.935	61.30	60.17	54.12	51.29	50.35
0 5 2	63.698	62.04	60.90	54.78	51.91	50.96
0 5 3	64.452	62.78	61.62	55.43	52.53	51.56
0 5 4	65.197	63.50	62.33	56.07	53.14	52.16
0 5 5	65.933	64.22	63.03	56.70	53.74	52.75
0 5 6	66.662	64.93	63.73	57.33	54.33	53.33
0 5 7	67.383	65.63	64.42	57.95	54.92	53.91
0 6	68.096	66.33	65.10	58.56	55.50	54.48
0 6 1	69.500	67.69	66.44	59.77	56.64	55.60
0 6 2	70.876	69.03	67.76	60.95	57.24	56.70
0 6 3	72.227	70.35	69.05	62.11	58.86	57.78
0 7	73.552	71.64	70.32	63.25	59.95	58.84
0 7 1	74.854	72.91	71.56	64.37	61.01	59.88
0 7 2	76.133	74.15	72.78	65.47	62.05	60.91
0 7 3	77.392	75.38	73.99	66.56	63.07	61.91
0 8	78.630	76.59	75.17	67.62	64.08	62.90
0 8 1	79.849	77.77	76.34	68.67	65.08	63.88
0 8 2	81.050	78.94	77.48	69.70	66.06	64.84
0 8 3	82.234	80.10	78.62	70.72	67.02	65.79
0 9	83.40	81.23	79.73	71.72	67.97	66.72
0 9 1	84.550	82.35	80.83	72.71	68.91	67.64
0 9 2	85.685	83.46	81.92	73.69	69.83	68.55
0 9 3	86.805	84.55	82.99	74.65	70.75	69.44
0 10	87.911	85.63	84.04	75.60	71.65	70.33
0 10 1	89.004	86.69	85.09	76.54	72.54	71.20
0 10 2	90.082	87.74	86.12	77.47	73.42	72.07
0 10 3	91.148	88.79	87.14	78.39	74.29	72.92
0 11	92.202	89.80	88.15	79.29	75.14	73.76
0 11 1	93.244	90.82	89.14	80.19	75.99	74.59
0 11 2	94.274	91.82	90.13	81.08	76.83	75.42
0 11 3	95.294	92.82	91.10	81.95	77.66	76.23
1 0	96.302	93.80	92.06	82.82	78.49	77.04

TABLE II.—For finding the Velocities from the Altitudes, and the Altitudes from the Velocities.—Altitudes 0 feet 4 inches to 1 foot.

Coefficients of velocity, and the corresponding velocities of discharge in inches per second.						Altitudes h in feet and inches.
7. Values of $v = 19.46 \sqrt{h}$ Coefficient .700.	8. Values of $v = 18.515 \sqrt{h}$ Coefficient .666.	9. Values of $v = 17.458 \sqrt{h}$ Coefficient .628.	10. Values of $v = 17.155 \sqrt{h}$ Coefficient .617.	11. Values of $v = 16.847 \sqrt{h}$ Coefficient .606.	12. Values of $v = 15.935 \sqrt{h}$ Coefficient .584.	
38.92	37.03	34.92	34.31	33.69	32.47	0 4
39.52	37.60	35.46	34.84	34.22	32.97	0 4 $\frac{1}{2}$
40.12	38.17	35.99	35.36	34.73	33.47	0 4 $\frac{1}{2}$
40.70	38.73	36.52	35.88	35.24	33.96	0 4 $\frac{1}{2}$
41.28	39.28	37.03	36.39	35.74	34.44	0 4 $\frac{1}{2}$
41.85	39.82	37.55	36.89	36.23	34.92	0 4 $\frac{1}{2}$
42.41	40.35	38.05	37.38	36.72	35.38	0 4 $\frac{1}{2}$
42.96	40.87	38.54	37.86	37.19	35.84	0 4 $\frac{1}{2}$
43.51	41.40	39.04	38.35	37.67	36.30	0 5
44.05	41.91	39.52	38.83	38.14	36.75	0 5 $\frac{1}{2}$
44.59	42.42	40.00	39.30	38.60	37.20	0 5 $\frac{1}{2}$
45.12	42.92	40.48	39.77	39.06	37.64	0 5 $\frac{1}{2}$
45.64	43.42	40.94	40.23	39.51	38.07	0 5 $\frac{1}{2}$
46.15	43.91	41.41	40.68	39.96	38.51	0 5 $\frac{1}{2}$
46.66	44.40	41.86	41.13	40.40	38.93	0 5 $\frac{1}{2}$
47.17	44.88	42.32	41.58	40.83	39.35	0 5 $\frac{1}{2}$
47.67	45.35	42.76	42.02	41.27	39.77	0 6
48.15	46.29	43.65	42.88	42.12	40.59	0 6 $\frac{1}{2}$
49.61	47.20	44.51	43.73	42.95	41.39	0 6 $\frac{1}{2}$
50.56	48.10	45.36	44.56	43.77	42.18	0 6 $\frac{1}{2}$
51.49	48.99	46.19	45.38	44.57	42.95	0 7
52.40	49.85	47.01	46.18	45.36	43.71	0 7 $\frac{1}{2}$
53.29	50.70	47.81	46.97	46.14	44.46	0 7 $\frac{1}{2}$
54.17	51.54	48.60	47.75	46.90	45.20	0 7 $\frac{1}{2}$
55.04	52.37	49.38	48.51	47.65	45.92	0 8
55.89	53.18	50.15	49.27	48.39	46.63	0 8 $\frac{1}{2}$
56.74	53.98	50.90	50.01	49.12	47.33	0 8 $\frac{1}{2}$
57.56	54.77	51.64	50.74	49.83	48.02	0 8 $\frac{1}{2}$
58.38	55.54	52.38	51.46	50.54	48.71	0 9
59.19	56.31	53.10	52.17	51.24	49.38	0 9 $\frac{1}{2}$
59.98	57.07	53.81	52.87	51.93	50.04	0 9 $\frac{1}{2}$
60.76	57.81	54.51	53.56	52.60	50.69	0 9 $\frac{1}{2}$
61.54	58.55	55.22	54.24	53.27	51.34	0 10
62.30	59.28	55.89	54.92	53.94	51.98	0 10 $\frac{1}{2}$
63.06	60.00	56.57	55.58	54.59	52.61	0 10 $\frac{1}{2}$
63.80	60.70	57.24	56.24	55.24	53.23	0 10 $\frac{1}{2}$
64.54	61.41	57.90	56.89	55.87	53.85	0 11
65.27	62.10	58.56	57.53	56.51	54.45	0 11 $\frac{1}{2}$
65.99	62.79	59.70	58.17	57.13	55.06	0 11 $\frac{1}{2}$
66.71	63.47	59.84	58.80	57.75	55.65	0 11 $\frac{1}{2}$
67.41	64.14	60.48	59.42	58.36	56.24	1 0

TABLE II.—For finding the Velocities from the Altitudes, and the Altitudes from the Velocities.—Altitudes 1 foot 0½ inch to 5 feet 3 inches.

Altitudes h in feet and inches.	Coefficients of velocity, and the corresponding velocities of discharge in inches per second.					
	1. Values of $v = 27.8 \sqrt{h}$, the theoretical velocity in inches.	2. Values of $v = 27.077 \sqrt{h}$, Coefficient .974.	3. Values of $v = 26.577 \sqrt{h}$, Coefficient .966.	4. Values of $v = 26.906 \sqrt{h}$, Coefficient .969.	5. Values of $v = 23.657 \sqrt{h}$, Coefficient .815.	6. Values of $v = 22.24 \sqrt{h}$, Coefficient .800.
1 0½	98.288	95.73	93.96	84.53	80.10	78.63
1 1	100.234	97.63	95.82	86.20	81.69	80.19
1 1½	102.144	99.49	97.65	87.84	83.25	81.71
1 2	104.018	101.31	99.44	89.46	84.77	83.21
1 2½	105.859	103.11	101.20	91.04	86.28	84.69
1 3	107.669	104.87	102.93	92.60	87.75	86.14
1 3½	109.449	106.60	104.63	94.13	89.20	87.56
1 4	111.200	108.31	106.31	95.63	90.63	88.96
1 4½	112.924	109.99	107.96	97.11	92.03	90.34
1 5	114.622	111.42	109.58	98.58	93.42	91.70
1 5½	116.296	113.27	111.18	100.01	94.78	93.04
1 6	117.945	114.78	112.76	101.43	96.13	94.36
1 7	121.177	118.03	115.85	104.21	98.76	96.94
1 8	124.325	121.09	118.86	106.92	101.33	99.46
1 9	127.396	124.08	121.79	109.56	103.83	101.92
1 10	130.394	127.00	124.66	112.14	106.27	104.31
1 11	133.324	129.86	127.46	114.66	108.66	106.66
2 0	136.192	132.65	130.20	117.12	111.00	108.95
2 1½	140.383	136.73	134.21	120.73	114.41	112.31
2 3	144.453	140.70	138.10	124.23	117.73	115.56
2 4½	148.411	144.55	141.88	127.64	120.96	118.73
2 6	152.267	148.31	145.57	130.95	124.10	121.81
2 7½	156.027	151.97	149.16	134.18	127.16	124.82
2 9	159.699	155.55	152.67	137.34	130.15	127.76
2 10½	163.288	159.04	156.10	140.43	133.80	130.63
3 0	166.800	162.46	159.46	143.45	135.94	133.44
3 1½	170.240	165.81	162.75	146.41	138.75	136.19
3 3	173.611	169.10	165.97	149.31	141.49	138.89
3 4½	176.918	172.32	169.13	152.15	144.19	141.53
3 6	180.165	175.48	172.24	154.94	146.83	144.13
3 7½	183.354	178.59	175.29	157.68	149.43	146.68
3 9	186.488	181.64	178.28	160.38	151.99	149.19
3 10½	189.571	184.64	181.23	163.03	154.50	151.66
4 0	192.604	187.60	184.13	165.64	156.97	154.08
4 2	196.576	191.46	187.93	169.06	160.21	157.26
4 4	200.469	195.26	191.65	172.40	163.38	160.37
4 6	204.287	198.98	195.30	175.69	166.49	163.43
4 8	208.036	202.63	198.88	178.91	169.55	166.43
4 10	211.718	206.21	202.40	182.08	172.55	169.37
5 0	215.338	209.74	205.86	185.19	175.50	172.27
5 3	220.656	214.92	210.95	189.76	179.83	176.52

TABLE II.—For finding the Velocities from the Altitudes, and the Altitudes from the Velocities.—Altitudes 1 foot 0½ inch to 5 feet 3 inches.

Coefficients of velocity, and the corresponding velocities of discharge in inches per second.						Altitudes in feet and inches.
7. Values of $v = 19.46 \sqrt{h}$ Coefficient .700.	8. Values of $v = 18.515 \sqrt{h}$ Coefficient .660.	9. Values of $v = 17.458 \sqrt{h}$ Coefficient .628.	10. Values of $v = 17.153 \sqrt{h}$ Coefficient .617.	11. Values of $v = 16.847 \sqrt{h}$ Coefficient .606.	12. Values of $v = 15.935 \sqrt{h}$ Coefficient .584.	
68.80	65.46	61.72	60.84	59.56	57.40	1 0½
70.16	66.76	62.95	61.84	60.74	58.54	1 1
71.50	68.03	64.15	63.02	61.90	59.65	1 1½
72.81	69.28	65.32	64.18	63.03	60.75	1 2
74.10	70.50	66.48	65.32	64.15	61.82	1 2½
75.37	71.71	67.62	66.43	65.25	62.88	1 3
76.61	72.89	68.73	67.53	66.33	63.92	1 3½
77.84	74.06	69.83	68.61	67.34	64.94	1 4
79.05	75.21	70.92	69.67	68.43	65.95	1 4½
80.24	76.34	71.98	70.72	69.46	66.94	1 5
81.41	77.45	73.03	71.75	70.48	67.92	1 5½
82.56	78.55	74.07	72.77	71.47	68.88	1 6
84.82	80.70	76.10	74.77	73.43	70.77	1 7
87.03	82.80	78.08	76.71	75.34	72.61	1 8
89.18	84.85	80.00	78.60	77.20	74.40	1 9
91.28	86.84	81.89	80.45	79.02	76.15	1 10
93.33	88.79	83.73	82.26	80.79	77.86	1 11
95.33	90.70	85.53	84.03	82.53	79.54	2 0
98.27	93.50	88.16	86.62	85.07	81.98	2 1½
101.12	96.21	90.72	89.13	87.54	84.36	2 3
103.89	98.84	93.20	91.57	89.94	86.67	2 4½
106.59	101.41	95.62	93.95	92.27	88.92	2 6
109.22	103.91	97.99	96.27	94.55	91.12	2 7½
111.79	106.36	100.29	98.53	96.78	93.26	2 9
114.30	108.75	102.54	100.75	98.95	95.36	2 10½
116.76	111.09	104.75	102.92	101.08	97.41	3 0
119.17	113.38	106.91	105.04	103.17	99.42	3 1½
121.53	115.62	109.03	107.12	105.21	101.39	3 3
123.84	117.83	111.10	109.16	107.21	103.32	3 4½
126.12	119.99	113.14	111.16	109.18	105.22	3 6
128.35	122.11	115.15	113.13	111.11	107.08	3 7½
130.54	124.20	117.11	115.06	113.01	108.91	3 9
132.70	126.25	119.05	116.97	114.88	110.71	3 10½
134.82	128.27	120.96	118.84	116.72	112.48	4 0
137.60	130.92	123.45	121.29	119.12	114.80	4 2
140.33	133.51	125.89	123.69	121.48	117.07	4 4
143.00	136.06	128.29	126.05	123.80	119.30	4 6
145.63	138.55	130.65	128.36	126.07	121.49	4 8
148.20	141.00	132.96	130.63	128.30	123.64	4 10
150.74	143.42	135.23	132.86	130.49	125.76	5 0
154.46	146.96	138.57	136.14	133.72	128.86	5 3

TABLE II.—For finding the Velocities from the Altitudes, and the Altitudes from the Velocities.—Altitudes 5 feet 6 inches to 17 feet.

Altitudes h in feet and inches.		Coefficients of velocity, and the corresponding velocities of discharge in inches per second.					
		1. Values of $v = 27.8 \sqrt{h}$, the theoretical velocity in inches.	2. Values of $v = 27.077 h^{\frac{1}{2}}$ Coefficient .974.	3. Values of $v = 26.377 h^{\frac{1}{2}}$ Coefficient .966.	4. Values of $v = 25.908 h^{\frac{1}{2}}$ Coefficient .960.	5. Values of $v = 25.467 h^{\frac{1}{2}}$ Coefficient .955.	6. Values of $v = 25.24 h^{\frac{1}{2}}$ Coefficient .950.
5	6	225.848	219.98	215.91	194.23	184.07	180.68
5	9	230.924	224.92	220.76	198.59	188.20	184.74
6	0	235.891	229.76	225.51	202.87	192.25	188.71
6	3	240.755	234.50	230.16	207.05	196.22	192.60
6	6	245.524	239.14	234.72	211.15	200.10	196.42
6	9	250.200	243.69	239.19	215.17	203.91	200.16
7	0	254.791	248.17	243.58	219.12	207.65	203.83
7	3	259.301	252.56	247.89	222.99	211.33	207.44
7	6	263.734	256.88	252.13	226.81	214.94	210.99
7	9	268.093	261.12	256.30	230.56	218.50	214.47
8	0	272.383	265.30	260.40	234.25	221.99	217.91
8	3	276.607	269.41	264.44	237.88	225.43	221.29
8	6	280.766	273.47	268.41	241.46	228.82	224.61
8	9	284.865	277.46	272.33	244.98	232.17	227.89
9	0	288.906	281.39	276.19	248.46	235.46	231.12
9	3	292.897	285.28	280.00	251.89	238.71	234.31
9	6	296.823	289.11	283.76	255.27	241.91	237.46
9	9	300.703	292.88	287.47	258.60	245.07	240.56
10	0	304.534	296.62	291.13	261.90	248.19	243.63
10	3	308.317	300.30	294.75	265.15	251.28	245.65
10	6	312.054	303.94	297.32	268.37	254.32	249.64
10	9	315.747	307.54	301.85	271.54	257.33	252.60
11	0	319.398	311.09	305.34	274.68	260.31	255.52
11	3	323.007	314.61	308.79	277.79	262.25	258.41
11	6	326.576	318.09	312.21	280.86	266.16	261.26
11	9	330.107	321.52	315.58	283.89	269.04	264.09
12	0	333.600	324.93	318.92	286.90	271.88	266.88
12	3	337.057	328.29	322.23	289.87	274.70	269.65
12	6	340.479	331.63	325.50	292.81	277.49	272.38
12	9	343.867	334.93	328.74	295.73	280.25	275.09
13	0	347.222	338.19	331.94	298.61	282.99	277.78
13	3	350.545	341.43	335.12	301.47	285.69	280.44
13	6	353.836	344.64	338.27	304.30	288.38	283.07
13	9	357.097	347.81	341.39	307.10	291.03	285.68
14	0	360.329	350.96	344.47	309.88	293.67	288.26
14	6	363.629	354.17	347.57	312.63	296.29	290.83
15	0	372.976	363.28	356.57	320.76	303.98	298.38
15	6	379.141	369.28	362.46	326.06	309.00	303.31
16	0	385.208	375.19	368.26	331.28	313.94	308.17
16	6	391.181	381.01	373.97	336.42	318.81	312.94
17	0	397.063	386.74	379.50	341.47	323.61	317.65

TABLE II.—For finding the Velocities from the Altitudes, and the Altitudes from the Velocities.—Altitudes 5 feet 6 inches to 17 feet.

Coefficients of velocity, and the corresponding velocities of discharge in inches per second.						Altitudes h in feet and inches.
7. Values of $v = 19.46 \sqrt{h}$ Coefficient .700.	8. Values of $v = 18.515 \sqrt{h}$ Coefficient .686.	9. Values of $v = 17.468 \sqrt{h}$ Coefficient .668.	10. Values of $v = 17.153 \sqrt{h}$ Coefficient .617.	11. Values of $v = 16.947 \sqrt{h}$ Coefficient .606.	12. Values of $v = 15.935 \sqrt{h}$ Coefficient .584.	
158.09	150.41	141.83	139.35	136.86	131.90	5 6
161.65	153.80	145.02	142.48	139.94	134.86	5 9
165.12	157.10	148.14	145.55	142.95	137.76	6 0
168.53	160.34	151.19	148.55	145.90	140.60	6 3
171.87	163.52	154.19	151.49	148.79	143.39	6 6
175.14	166.63	157.13	154.37	151.62	146.12	6 9
178.35	169.69	160.01	157.21	154.40	148.80	7 0
181.51	172.69	162.84	159.99	157.14	151.43	7 3
184.61	175.65	165.62	162.72	159.82	154.02	7 6
187.67	178.55	168.36	165.41	162.46	156.57	7 9
190.67	181.41	171.06	168.06	165.06	159.07	8 0
193.62	184.22	173.71	170.67	167.62	161.54	8 3
196.54	186.99	176.32	173.23	170.14	163.97	8 6
199.41	189.72	178.90	175.76	172.63	166.36	8 9
202.23	192.41	181.43	178.26	175.08	168.72	9 0
205.02	195.07	183.94	180.71	177.49	171.05	9 3
207.78	197.68	186.40	183.14	179.87	173.34	9 6
210.49	200.27	188.84	185.53	182.23	175.61	9 9
213.17	202.82	191.25	187.90	184.55	177.85	10 0
215.82	205.34	193.62	190.23	186.84	180.06	10 3
218.44	207.83	195.97	192.54	189.10	182.24	10 6
221.02	210.29	198.29	194.82	191.34	184.40	10 9
223.58	212.72	200.58	197.07	193.55	186.53	11 0
226.10	215.12	202.85	199.30	195.74	188.64	11 3
228.60	217.50	205.09	201.50	197.91	190.72	11 6
231.07	219.85	207.31	203.68	200.04	192.78	11 9
233.52	222.18	209.50	205.83	202.16	194.82	12 0
235.94	224.48	211.67	207.96	204.26	196.84	12 3
238.34	226.76	213.82	210.08	206.33	198.84	12 6
240.71	229.02	215.95	212.17	208.38	200.82	12 9
243.06	231.25	218.06	214.24	210.42	202.78	13 0
245.38	233.46	220.14	216.29	212.43	204.72	13 3
247.69	235.65	222.21	218.32	214.42	206.64	13 6
249.97	237.83	224.26	220.33	216.40	208.54	13 9
252.23	239.98	226.29	222.32	218.36	210.43	14 0
256.70	244.23	230.29	226.26	222.22	214.16	14 6
261.08	248.40	234.23	230.13	226.02	217.82	15 0
265.40	252.51	238.10	233.93	229.76	221.42	15 6
269.65	256.55	241.91	237.67	233.44	224.96	16 0
273.83	260.53	245.66	241.36	237.06	228.45	16 6
277.94	264.44	249.36	244.99	240.62	231.89	17 0

TABLE II.—For finding the Velocities from the Altitudes, and the Altitudes from the Velocities.—Altitudes 17 feet 6 inches to 40 feet.

Altitudes h in feet and inches.	Coefficients of velocity, and the corresponding velocities of discharge in inches per second.					
	1. Values of $v = 27.8 \sqrt{h}$, the theoretical velocity in inches.	2. Values of $v = 27.077 \sqrt{h}$, Coefficient .974.	3. Values of $v = 26.577 \sqrt{h}$, Coefficient .966.	4. Values of $v = 23.908 \sqrt{h}$, Coefficient .890.	5. Values of $v = 22.657 \sqrt{h}$, Coefficient .815.	6. Values of $v = 23.24 \sqrt{h}$, Coefficient .800.
17 6	402.860	392.39	385.13	346.46	328.33	322.29
18 0	408.575	397.95	390.60	351.37	332.99	326.86
18 6	414.211	403.44	395.99	356.22	337.58	331.37
19 0	419.772	408.86	401.30	361.00	342.11	335.82
19 6	425.258	414.20	406.55	365.72	346.59	340.21
20 0	430.676	419.48	411.73	370.38	351.00	344.54
20 6	436.026	424.69	416.84	374.98	355.36	348.82
21 0	441.311	429.84	421.89	379.53	359.59	353.05
21 6	446.534	434.92	426.89	384.02	363.93	357.23
22 0	451.697	439.95	431.82	388.46	368.13	361.36
22 6	456.801	444.92	436.70	392.85	372.29	365.44
23 0	461.848	449.84	441.53	397.19	376.41	369.48
23 6	466.841	450.70	446.30	401.48	380.48	373.47
24 0	471.782	459.52	451.02	405.73	384.50	377.43
24 6	476.671	464.28	455.70	409.94	388.49	381.34
25 0	481.510	468.99	460.32	414.10	392.43	385.21
25 6	486.301	473.66	464.90	418.22	396.34	389.04
26 0	491.046	478.28	469.44	422.30	400.20	392.84
26 6	495.745	482.86	473.93	426.34	404.03	396.60
27 0	500.400	487.39	478.38	430.34	407.83	400.32
27 6	505.012	491.88	482.79	434.31	411.58	404.01
28 0	509.582	496.33	487.16	438.24	415.31	407.67
28 6	514.112	500.75	491.49	442.14	419.00	411.29
29 0	518.602	505.12	495.78	446.00	422.66	414.88
29 6	523.054	509.45	500.04	449.83	426.29	418.44
30 0	527.468	513.75	504.26	453.62	429.89	421.97
30 6	531.845	518.02	508.44	457.31	433.45	425.48
31 0	536.187	522.25	512.59	461.12	436.99	428.95
31 6	540.494	526.44	516.71	464.82	440.50	432.40
32 0	544.767	530.60	520.80	468.50	443.98	435.81
32 6	549.006	534.73	524.85	472.15	447.44	439.20
33 0	553.213	538.83	528.87	475.76	450.87	442.57
33 6	557.388	542.90	532.86	479.35	454.27	445.91
34 0	561.532	546.93	536.83	482.92	457.65	449.23
34 6	565.646	550.94	540.76	486.46	461.00	452.52
35 0	569.730	554.92	544.66	489.97	464.33	455.78
36 0	577.812	562.79	552.39	496.92	470.92	462.25
37 0	585.782	570.55	560.01	503.77	477.41	468.63
38 0	593.646	578.21	567.53	510.54	483.82	474.92
39 0	601.406	585.77	574.94	517.21	490.15	481.12
40 0	609.067	593.23	582.27	523.80	496.39	487.25

TABLE II.—For finding the Velocities from the Altitudes, and the Altitudes from the Velocities.—Altitudes 17 feet 6 inches to 40 feet.

Coefficients of velocity, and the corresponding velocities of discharge in inches per second.						Altitudes Δ in feet and inches.
7. Values of $v = 119.46 \Delta^{\frac{1}{2}}$ Coefficient .700.	8. Values of $v = 18.515 \Delta^{\frac{1}{2}}$ Coefficient .666.	9. Values of $v = 17.458 \Delta^{\frac{1}{2}}$ Coefficient .628.	10. Values of $v = 17.153 \Delta^{\frac{1}{2}}$ Coefficient .617.	11. Values of $v = 16.847 \Delta^{\frac{1}{2}}$ Coefficient .606.	12. Values of $v = 16.985 \Delta^{\frac{1}{2}}$ Coefficient .584.	
282.00	268.30	253.00	248.56	244.34	235.27	17 6
286.00	272.11	256.59	252.09	247.60	238.61	18 0
289.95	275.86	260.12	255.57	251.01	241.90	18 6
293.84	279.57	263.32	259.00	254.38	245.14	19 0
297.68	283.22	267.06	262.38	257.71	248.35	19 6
301.47	286.83	270.46	265.73	260.99	251.51	20 0
305.22	290.39	273.82	269.03	264.23	254.64	20 6
308.92	293.91	277.08	272.23	267.37	257.67	21 0
312.57	297.39	280.42	275.51	270.60	260.78	21 6
316.19	300.83	283.67	278.70	273.73	263.79	22 0
319.76	304.23	286.87	281.85	276.82	266.77	22 6
323.29	307.59	290.04	284.96	279.88	269.72	23 0
326.79	310.92	293.18	288.04	282.91	272.64	23 6
330.25	314.21	296.28	291.09	285.90	275.52	24 0
333.67	317.46	299.35	294.11	288.86	278.38	24 6
337.06	320.69	302.39	297.09	291.80	281.20	25 0
340.41	323.88	305.40	300.05	294.70	284.00	25 6
343.73	327.04	308.38	302.98	297.57	286.77	26 0
347.02	330.17	311.33	305.87	300.42	289.52	26 6
350.28	333.13	314.25	308.75	303.24	292.23	27 0
353.51	336.34	317.15	311.59	306.04	294.93	27 6
356.71	339.38	320.02	314.41	308.81	297.60	28 0
359.88	342.40	322.86	317.20	311.55	300.24	28 6
363.02	345.39	325.68	319.98	314.27	302.86	29 0
366.14	348.35	328.48	322.72	316.97	305.46	29 6
369.23	351.29	331.25	325.45	319.65	308.04	30 0
372.29	354.21	334.00	328.15	322.30	310.60	30 6
375.33	357.10	336.73	330.83	324.93	313.13	31 0
378.35	359.97	339.43	333.48	327.54	315.60	31 6
381.34	362.81	342.11	336.12	330.13	318.14	32 0
384.30	365.64	344.78	338.74	332.70	320.62	32 6
387.25	368.44	347.42	341.33	335.25	323.08	33 0
390.17	371.22	350.04	343.91	337.78	325.51	33 6
393.07	373.98	352.64	346.47	340.29	327.93	34 0
395.95	376.72	355.23	349.00	342.78	330.34	34 6
398.81	379.44	357.79	351.52	345.26	332.72	35 0
404.47	384.82	362.87	356.51	350.15	337.44	36 0
410.05	390.13	367.87	361.43	354.98	342.10	37 0
415.55	395.37	372.81	366.28	359.75	346.69	38 0
420.98	400.54	377.68	371.11	364.45	351.22	39 0
426.35	405.64	382.49	375.79	369.09	355.70	40 0

TABLE III.—*Square Roots for finding the effects of the Velocity of Approach when the Orifice is small in proportion to the Head. Also for finding the Increase in the Discharge from an Increase of Head. (See pp. 91 to 99).*

No.	Square root.	No.	Square root.	No.	Square root.	No.	Square root.
1.000	1.0000	1.115	1.0559	1.475	1.2141	1.975	1.4053
1.001	1.0005	1.120	1.0583	1.49	1.2207	1.99	1.4107
1.002	1.0010	1.125	1.0607	1.5	1.2247	2.00	1.4142
1.004	1.0020	1.18	1.0630	1.51	1.2288	2.01	1.4177
1.005	1.0025	1.135	1.0654	1.525	1.2349	2.025	1.4230
1.006	1.0030	1.14	1.0677	1.54	1.2410	2.04	1.4283
1.008	1.0040	1.145	1.0700	1.55	1.2450	2.05	1.4318
1.009	1.0044	1.15	1.0723	1.56	1.2490	2.06	1.4353
1.010	1.0050	1.155	1.0747	1.575	1.2550	2.075	1.4405
1.011	1.0055	1.16	1.0770	1.58	1.2570	2.09	1.4457
1.012	1.0060	1.165	1.0794	1.59	1.2610	2.10	1.4491
1.014	1.0070	1.17	1.0817	1.6	1.2649	2.11	1.4526
1.015	1.0075	1.175	1.0840	1.61	1.2689	2.125	1.4577
1.016	1.0080	1.18	1.0863	1.625	1.2748	2.14	1.4629
1.018	1.0090	1.185	1.0886	1.64	1.2806	2.15	1.4663
1.019	1.0095	1.19	1.0909	1.65	1.2845	2.16	1.4697
1.020	1.0100	1.195	1.0932	1.66	1.2884	2.175	1.4748
1.0225	1.0112	1.2	1.0954	1.675	1.2942	2.19	1.4799
1.025	1.0124	1.21	1.1000	1.69	1.3000	2.2	1.4832
1.0275	1.0137	1.22	1.1045	1.7	1.3038	2.21	1.4866
1.03	1.0149	1.23	1.1091	1.71	1.3077	2.225	1.4916
1.0325	1.0161	1.24	1.1136	1.725	1.3134	2.24	1.4967
1.035	1.0174	1.25	1.1180	1.74	1.3191	2.25	1.5000
1.0375	1.0186	1.26	1.1225	1.75	1.3229	2.26	1.5033
1.04	1.0198	1.27	1.1269	1.76	1.3267	2.275	1.5083
1.0425	1.0210	1.28	1.1314	1.775	1.3323	2.29	1.5133
1.045	1.0223	1.29	1.1358	1.79	1.3379	2.3	1.5166
1.0475	1.0235	1.30	1.1402	1.80	1.3416	2.31	1.5199
1.05	1.0247	1.31	1.1446	1.81	1.3454	2.325	1.5248
1.055	1.0271	1.325	1.1511	1.825	1.3509	2.34	1.5297
1.06	1.0296	1.34	1.1576	1.84	1.3565	2.35	1.5330
1.065	1.0320	1.35	1.1619	1.85	1.3601	2.36	1.5362
1.07	1.0344	1.36	1.1662	1.86	1.3638	2.375	1.5411
1.075	1.0368	1.375	1.1726	1.875	1.3693	2.39	1.5460
1.08	1.0392	1.39	1.1790	1.89	1.3748	2.4	1.5492
1.085	1.0416	1.40	1.1832	1.9	1.3784	2.41	1.5524
1.09	1.0440	1.41	1.1874	1.91	1.3820	2.425	1.5572
1.095	1.0464	1.425	1.1937	1.925	1.3875	2.44	1.5621
1.1	1.0488	1.44	1.2000	1.94	1.3928	2.45	1.5652
1.105	1.0512	1.45	1.2042	1.95	1.3964	2.46	1.5684
1.110	1.0536	1.46	1.2083	1.96	1.4000	2.475	1.5737

TABLE III.—*Square Roots for finding the effects of the Velocity of Approach when the Orifice is small in proportion to the Head. Also for finding the increase in the Discharge from an increase of Head. (See pp. 91 to 99.)*

No.	Square root.	No.	Square root.	No.	Square root.	No.	Square root.
2.49	1.5780	3.0000	1.7321	4.5	2.1213	26	5.0990
2.5	1.5811	3.025	1.7393	5.0	2.2361	27	5.1962
2.51	1.5843	3.05	1.7464	5.5	2.3452	28	5.2915
2.525	1.5890	3.075	1.7536	6.0	2.4495	29	5.3852
2.54	1.5937	3.1	1.7607	6.5	2.5495	30	5.4772
2.55	1.5969	3.125	1.7678	7.0	2.6458	31	5.5678
2.56	1.6000	3.15	1.7748	7.5	2.7386	32	5.6569
2.575	1.6047	3.175	1.7819	8.0	2.8284	33	5.7446
2.59	1.6093	3.2	1.7889	8.5	2.9155	34	5.8310
2.6	1.6125	3.225	1.7958	9.0	3.0000	35	5.9161
2.61	1.6155	3.25	1.8028	9.5	3.0822	36	6.0000
2.625	1.6202	3.275	1.8097	10.0	3.1623	37	6.0828
2.64	1.6248	3.3	1.8166	10.5	3.2404	38	6.1644
2.65	1.6279	3.325	1.8235	11.0	3.3166	39	6.2450
2.66	1.6310	3.35	1.8303	11.5	3.3912	40	6.3246
2.675	1.6355	3.375	1.8371	12.0	3.4641	41	6.4031
2.69	1.6401	3.4	1.8439	12.5	3.5355	42	6.4807
2.7	1.6432	3.425	1.8507	13.0	3.6056	43	6.5574
2.71	1.6462	3.45	1.8574	13.5	3.6742	44	6.6332
2.725	1.6508	3.475	1.8641	14.0	3.7417	45	6.7082
2.74	1.6553	3.5	1.8708	14.5	3.8079	46	6.7823
2.75	1.6583	3.525	1.8775	15.0	3.8730	47	6.8557
2.76	1.6613	3.55	1.8841	15.5	3.9370	48	6.9282
2.775	1.6658	3.575	1.8908	16.0	4.0000	49	7.0000
2.79	1.6703	3.6	1.8974	16.5	4.0620	50	7.0711
2.8	1.6733	3.625	1.9039	17.0	4.1231	51	7.1414
2.81	1.6763	3.65	1.9105	17.5	4.1833	52	7.2111
2.825	1.6808	3.675	1.9170	18.0	4.2426	53	7.2810
2.84	1.6852	3.7	1.9235	18.5	4.3012	54	7.3485
2.85	1.6882	3.725	1.9300	19.0	4.3589	55	7.4162
2.86	1.6912	3.75	1.9365	19.5	4.4159	56	7.4833
2.875	1.6956	3.775	1.9429	20.0	4.4721	57	7.5498
2.89	1.7000	3.8	1.9494	20.5	4.5277	58	7.6158
2.9	1.7029	3.825	1.9558	21.0	4.5826	59	7.6811
2.91	1.7059	3.85	1.9621	21.5	4.6368	60	7.7460
2.925	1.7103	3.875	1.9685	22.0	4.6904	61	7.8102
2.94	1.7146	3.9	1.9748	22.5	4.7434	62	7.8740
2.95	1.7176	3.925	1.9812	23.0	4.7958	63	7.9373
2.96	1.7205	3.95	1.9875	23.5	4.8477	64	8.0000
2.975	1.7248	3.975	1.9938	24.0	4.8990	65	8.0623
2.99	1.7292	4.0	2.0000	25.0	5.0000	66	8.1240

TABLE IV.—For finding the Discharge through Rectangular Orifices; in which
 $n = \frac{h}{x}$ Also for finding the effects of the Velocity of Approach to Weirs, and the
 Depression on the Crest. (See pp. 91 to 99.)

$1+n$	$n^{\frac{1}{2}}$	$(1+n)^{\frac{1}{2}}$	$(1+n)^{\frac{1}{2}} - n^{\frac{1}{2}}$	$1+n$	$n^{\frac{1}{2}}$	$(1+n)^{\frac{1}{2}}$	$(1+n)^{\frac{1}{2}} - n^{\frac{1}{2}}$
1.000	.0000	1.0000	1.0000	1.115	.0390	1.1774	1.1384
1.001	.0000	1.0015	1.0015	1.120	.0416	1.1853	1.1437
1.002	.0001	1.0030	1.0029	1.125	.0442	1.1932	1.1491
1.004	.0003	1.0060	1.0058	1.13	.0469	1.2012	1.1543
1.005	.0004	1.0075	1.0072	1.135	.0496	1.2092	1.1596
1.006	.0005	1.0090	1.0086	1.14	.0524	1.2172	1.1648
1.008	.0007	1.0120	1.0113	1.145	.0552	1.2251	1.1700
1.009	.0009	1.0135	1.0127	1.15	.0581	1.2332	1.1751
1.010	.0010	1.0150	1.0140	1.155	.0610	1.2413	1.1803
1.011	.0012	1.0165	1.0154	1.16	.0640	1.2494	1.1854
1.012	.0013	1.0181	1.0167	1.165	.0670	1.2574	1.1904
1.014	.0017	1.0211	1.0194	1.17	.0701	1.2655	1.1955
1.015	.0018	1.0226	1.0207	1.175	.0732	1.2737	1.2005
1.016	.0020	1.0241	1.0221	1.18	.0764	1.2818	1.2054
1.018	.0024	1.0271	1.0247	1.185	.0796	1.2900	1.2104
1.019	.0026	1.0286	1.0260	1.19	.0828	1.2981	1.2153
1.020	.0028	1.0301	1.0273	1.195	.0861	1.3063	1.2202
1.0225	.0034	1.0339	1.0306	1.2	.0894	1.3145	1.2251
1.025	.0040	1.0377	1.0338	1.21	.0962	1.3310	1.2348
1.0275	.0046	1.0415	1.0370	1.22	.1032	1.3475	1.2443
1.03	.0052	1.0453	1.0401	1.23	.1103	1.3641	1.2538
1.0325	.0059	1.0491	1.0433	1.24	.1176	1.3808	1.2632
1.035	.0065	1.0530	1.0464	1.25	.1250	1.3975	1.2725
1.0375	.0073	1.0568	1.0495	1.26	.1326	1.4143	1.2818
1.04	.0080	1.0606	1.0526	1.27	.1403	1.4312	1.2909
1.0425	.0088	1.0644	1.0557	1.28	.1482	1.4482	1.3000
1.045	.0095	1.0683	1.0587	1.29	.1562	1.4652	1.3090
1.0475	.0104	1.0721	1.0617	1.30	.1643	1.4822	1.3179
1.05	.0112	1.0759	1.0648	1.31	.1726	1.4994	1.3268
1.055	.0129	1.0836	1.0707	1.325	.1853	1.5252	1.3399
1.06	.0147	1.0913	1.0766	1.34	.1983	1.5512	1.3529
1.065	.0166	1.0991	1.0825	1.35	.2071	1.5686	1.3615
1.07	.0185	1.1068	1.0883	1.36	.2160	1.5860	1.3700
1.075	.0205	1.1146	1.0940	1.375	.2296	1.6123	1.3827
1.08	.0226	1.1224	1.0997	1.39	.2436	1.6388	1.3952
1.085	.0248	1.1302	1.1054	1.40	.2530	1.6565	1.4035
1.09	.0270	1.1380	1.1110	1.41	.2625	1.6743	1.4118
1.095	.0293	1.1458	1.1166	1.425	.2771	1.7011	1.4240
1.1	.0316	1.1537	1.1221	1.44	.2919	1.7280	1.4361
1.105	.0340	1.1616	1.1275	1.45	.3019	1.7460	1.4442
1.110	.0365	1.1695	1.1330	1.46	.3120	1.7641	1.4521

Values of n from 0 to .46.

[Continued on next page.]

TABLE IV.—For finding the Discharge through Rectangular Orifices; in which
 $n = \frac{h}{d}$ Also for finding the effects of the Velocity of Approach to Weirs, &c.
 (See pp. 91 to 99.)

$1+n$.	$n^{\frac{3}{2}}$.	$(1+n)^{\frac{3}{2}}$.	$(1+n)^{\frac{3}{2}} - n^{\frac{3}{2}}$.	$1+n$.	$n^{\frac{3}{2}}$.	$(1+n)^{\frac{3}{2}}$.	$(1+n)^{\frac{3}{2}} - n^{\frac{3}{2}}$.
1.475	.3274	1.7914	1.4640	1.975	.9627	2.7756	1.8128
1.49	.3430	1.8188	1.4758	1.99	.9850	2.8072	1.8222
1.5	.3536	1.8371	1.4836	2.	1.0000	2.8284	1.8284
1.51	.3642	1.8555	1.4913	2.01	1.0150	2.8497	1.8346
1.525	.3804	1.8832	1.5028	2.025	1.0377	2.8816	1.8439
1.54	.3968	1.9111	1.5143	2.04	1.0606	2.9137	1.8531
1.55	.4079	1.9297	1.5218	2.05	1.0759	2.9352	1.8592
1.56	.4191	1.9484	1.5294	2.06	1.0913	2.9567	1.8653
1.575	.4360	1.9766	1.5406	2.075	1.1146	2.9890	1.8744
1.58	.4417	1.9860	1.5443	2.09	1.1380	3.0215	1.8835
1.59	.4532	2.0049	1.5517	2.10	1.1587	3.0432	1.8895
1.6	.4648	2.0239	1.5591	2.11	1.1695	3.0650	1.8955
1.61	.4764	2.0429	1.5664	2.125	1.1932	3.0977	1.9045
1.625	.4941	2.0715	1.5774	2.14	1.2172	3.1306	1.9134
1.64	.5120	2.1002	1.5882	2.15	1.2332	3.1525	1.9193
1.65	.5240	2.1195	1.5954	2.16	1.2494	3.1745	1.9252
1.66	.5362	2.1388	1.6026	2.175	1.2737	3.2077	1.9340
1.675	.5546	2.1678	1.6132	2.19	1.2981	3.2409	1.9428
1.69	.5732	2.1970	1.6238	2.2	1.3145	3.2631	1.9486
1.7	.5857	2.2165	1.6309	2.21	1.3310	3.2854	1.9544
1.71	.5983	2.2361	1.6379	2.225	1.3558	3.3189	1.9631
1.725	.6173	2.2656	1.6483	2.24	1.3808	3.3525	1.9717
1.74	.6366	2.2952	1.6586	2.25	1.3975	3.3750	1.9775
1.75	.6495	2.3150	1.6655	2.26	1.4143	3.3975	1.9832
1.76	.6626	2.3349	1.6724	2.275	1.4397	3.4314	1.9917
1.775	.6823	2.3648	1.6826	2.29	1.4652	3.4654	2.0002
1.79	.7022	2.3949	1.6927	2.3	1.4822	3.4881	2.0059
1.80	.7155	2.4150	1.6994	2.31	1.4994	3.5109	2.0115
1.81	.7290	2.4351	1.7061	2.325	1.5252	3.5451	2.0200
1.825	.7493	2.4654	1.7161	2.34	1.5512	3.5795	2.0284
1.84	.7699	2.4959	1.7260	2.35	1.5686	3.6025	2.0339
1.85	.7837	2.5163	1.7326	2.36	1.5860	3.6255	2.0395
1.86	.7975	2.5367	1.7392	2.375	1.6123	3.6601	2.0478
1.875	.8185	2.5674	1.7490	2.39	1.6388	3.6948	2.0561
1.89	.8396	2.5983	1.7587	2.4	1.6565	3.7181	2.0616
1.9	.8538	2.6190	1.7652	2.41	1.6743	3.7413	2.0670
1.91	.8681	2.6397	1.7716	2.425	1.7011	3.7763	2.0752
1.925	.8896	2.6709	1.7813	2.44	1.7280	3.8114	2.0834
1.94	.9114	2.7021	1.7907	2.45	1.7460	3.8349	2.0888
1.95	.9259	2.7230	1.7971	2.46	1.7641	3.8584	2.0942
1.96	.9406	2.7440	1.8034	2.475	1.7914	3.8937	2.1023

Values of n from .475 to 1.475

[Continued on next page.]

G G 2

TABLE IV.—For finding the Discharge through Rectangular Orifices; in which
 $n = \frac{h}{d}$ Also for finding the effects of the Velocity of Approach to Weirs, &c.
 (See pp. 91 to 99.)

$1+n$	$n^{\frac{1}{2}}$	$(1+n)^{\frac{1}{2}}$	$(1+n)^{\frac{1}{2}}-n^{\frac{1}{2}}$	$1+n$	$n^{\frac{1}{2}}$	$(1+n)^{\frac{1}{2}}$	$(1+n)^{\frac{1}{2}}-n^{\frac{1}{2}}$
2.49	1.8188	3.9292	2.1104	3.	2.8284	5.1962	2.3677
2.5	1.8371	3.9528	2.1157	3.025	2.8816	5.2612	2.3796
2.51	1.8555	3.9766	2.1211	3.05	2.9352	5.3626	2.3914
2.525	1.8832	4.0123	2.1291	3.075	2.9890	5.3922	2.4032
2.54	1.9111	4.0481	2.1370	3.1	3.0432	5.4581	2.4149
2.55	1.9297	4.0720	2.1423	3.125	3.0977	5.5243	2.4266
2.56	1.9484	4.0960	2.1476	3.15	3.1525	5.5907	2.4382
2.575	1.9766	4.1321	2.1554	3.175	3.2077	5.6574	2.4497
2.59	2.0049	4.1682	2.1633	3.2	3.2631	5.7243	2.4612
2.6	2.0239	4.1924	2.1685	3.225	3.3189	5.7915	2.4726
2.61	2.0429	4.2166	2.1737	3.25	3.3750	5.8590	2.4840
2.625	2.0715	4.2530	2.1815	3.275	3.4314	5.9268	2.4953
2.64	2.1002	4.2895	2.1893	3.3	3.4881	5.9947	2.5066
2.65	2.1195	4.3139	2.1944	3.325	3.5451	6.0630	2.5179
2.66	2.1388	4.3383	2.1996	3.35	3.6025	6.1315	2.5290
2.675	2.1678	4.3751	2.2073	3.375	3.6601	6.2003	2.5401
2.69	2.1970	4.4119	2.2149	3.4	3.7181	6.2693	2.5512
2.7	2.2165	4.4366	2.2200	3.425	3.7763	6.3386	2.5623
2.71	2.2361	4.4612	2.2251	3.45	3.8349	6.4081	2.5732
2.725	2.2656	4.4983	2.2327	3.475	3.8937	6.4779	2.5842
2.74	2.2952	4.5355	2.2403	3.5	3.9528	6.5479	2.5951
2.75	2.3150	4.5604	2.2453	3.525	4.0123	6.6182	2.6059
2.76	2.3349	4.5853	2.2504	3.55	4.0720	6.6887	2.6167
2.775	2.3648	4.6227	2.2579	3.575	4.1321	6.7595	2.6274
2.79	2.3949	4.6602	2.2654	3.6	4.1924	6.8305	2.6381
2.8	2.4150	4.6853	2.2703	3.625	4.2530	6.9018	2.6488
2.81	2.4351	4.7104	2.2753	3.65	4.3139	6.9733	2.6594
2.825	2.4654	4.7482	2.2827	3.675	4.3751	7.0451	2.6700
2.84	2.4959	4.7861	2.2902	3.7	4.4366	7.1171	2.6805
2.85	2.5163	4.8114	2.2951	3.725	4.4983	7.1893	2.6910
2.86	2.5367	4.8367	2.3000	3.75	4.5604	7.2618	2.7015
2.875	2.5674	4.8748	2.3074	3.775	4.6227	7.3346	2.7119
2.89	2.5983	4.9130	2.3147	3.8	4.6853	7.4076	2.7223
2.9	2.6190	4.9385	2.3196	3.825	4.7482	7.4808	2.7326
2.91	2.6397	4.9641	2.3244	3.85	4.8114	7.5542	2.7429
2.925	2.6708	5.0025	2.3317	3.875	4.8748	7.6279	2.7531
2.94	2.7021	5.0411	2.3389	3.9	4.9385	7.7019	2.7634
2.95	2.7230	5.0668	2.3438	3.925	5.0025	7.7761	2.7735
2.96	2.7440	5.0926	2.3486	3.95	5.0668	7.8505	2.7837
2.975	2.7756	5.1313	2.3558	3.975	5.1313	7.9251	2.7838
2.99	2.8072	5.1702	2.3630	4.	5.1962	8.	2.8038

Values of n from 1.49 to 3.

[Continued on next page.]

TABLE IV.—For finding the Discharge through Rectangular Orifices; in which
 $n = \frac{h}{d}$ Also for finding the effects of the Velocity of Approach to Weirs, &c.
 (See pp. 91 to 99.)

$1+n$.	$n^{\frac{1}{2}}$.	$(1+n)^{\frac{1}{2}}$.	$(1+n)^{\frac{1}{2}}-n^{\frac{1}{2}}$.	$1+n$.	$n^{\frac{1}{2}}$.	$(1+n)^{\frac{1}{2}}$.	$(1+n)^{\frac{1}{2}}-n^{\frac{1}{2}}$.
4.5	6.5479	9.5459	2.9980	26.	125.0000	132.5745	7.5745
5.0	8.0000	11.1803	3.1803	27.	132.5745	140.2961	7.7216
5.5	9.5459	12.8986	3.3527	28.	140.2961	148.1621	7.8660
6.0	11.1803	14.6969	3.5166	29.	148.1621	156.1698	8.0077
6.5	12.8986	16.5718	3.6732	30.	156.1698	164.3168	8.1470
7.0	14.6969	18.5203	3.8234	31.	164.3168	172.6007	8.2839
7.5	16.5718	20.5396	3.9678	32.	172.6007	181.0193	8.4186
8.0	18.5203	22.6274	4.1071	33.	181.0193	189.5706	8.5513
8.5	20.5396	24.7815	4.2419	34.	189.5706	198.2524	8.6818
9.0	22.6274	27.0000	4.3726	35.	198.2524	207.0628	8.8104
9.5	24.7815	29.2810	4.4995	36.	207.0628	216.0000	8.9372
10.0	27.0000	31.6228	4.6228	37.	216.0000	225.0622	9.0622
10.5	29.2810	34.0239	4.7429	38.	225.0622	234.2477	9.1855
11.0	31.6228	36.4829	4.8601	39.	234.2477	243.5549	9.3072
11.5	34.0239	38.9984	4.9745	40.	243.5549	252.9822	9.4273
12.0	36.4829	41.5692	5.0863	41.	252.9822	262.5281	9.5459
12.5	38.9984	44.1942	5.1958	42.	262.5281	272.1911	9.6630
13.0	41.5692	46.8722	5.3030	43.	272.1911	281.9699	9.7788
13.5	44.1942	49.6022	5.4080	44.	281.9699	291.8630	9.8931
14.0	46.8722	52.3832	5.5110	45.	291.8630	301.8692	10.0062
14.5	49.6022	55.2144	5.6122	46.	301.8692	311.9872	10.1180
15.0	52.3832	58.0947	5.7115	47.	311.9872	322.2158	10.2286
15.5	55.2144	61.0236	5.8092	48.	322.2158	332.5538	10.3380
16.0	58.0947	64.	5.9053	49.	332.5538	343.0000	10.4462
16.5	61.0236	67.0247	6.0011	50.	343.0000	353.5534	10.5534
17.0	64.	70.0928	6.0928	51.	353.5534	364.2128	10.6594
17.5	67.0247	73.2078	6.1831	52.	364.2128	374.9773	10.7645
18.0	70.0928	76.3675	6.2747	53.	374.9773	385.8458	10.8685
18.5	73.2078	79.5715	6.3637	54.	385.8458	396.8173	10.9715
19.0	76.3675	82.8191	6.4516	55.	396.8173	407.8909	11.0736
19.5	79.5715	86.1097	6.5382	56.	407.8909	419.0656	11.1747
20.0	82.8191	89.4427	6.6236	57.	419.0656	430.3406	11.2750
20.5	86.1097	92.8177	6.7080	58.	430.3406	441.7148	11.3742
21.0	89.4427	96.2341	6.7914	59.	441.7148	453.1876	11.4728
21.5	92.8177	99.6914	6.8737	60.	453.1876	464.7580	11.5704
22.0	96.2341	103.1892	6.9551	61.	464.7580	476.4252	11.6672
22.5	99.6914	106.7269	7.0355	62.	476.4252	488.1885	11.7633
23.	103.1892	110.3041	7.1149	63.	488.1885	500.0470	11.8585
23.5	106.7269	113.9205	7.1936	64.	500.0470	512.0000	11.9530
24.	110.3041	117.5755	7.2714	65.	512.0000	524.0468	12.0468
25.	117.5755	125.	7.4245	66.	524.0468	536.1865	12.1397

Values of n from 3.5 to 65.

TABLE V.—Coefficients of Discharge for Different Ratios of the Channel to the Orifice.—Coefficients for Heads in still water '550 and '573. See equations (44) and (44a) and the observations thereon at p. 99.

Ratio of the channel to the orifice.	Coefficient '550 for heads in still water.			Coefficient '573 for heads in still water.		
	Ratio of the height due to the velocity of approach to the head.	Coefficients for orifices: the heads measured to the centres.	Coefficients for weirs: the heads measured the full depth.	Ratio of the height due to the velocity of approach to the head.	Coefficients for orifices: the heads measured to the centres.	Coefficients for weirs: the heads measured the full depth.
30·	·000	·550	·550	·000	·573	·573
20·	·001	·550	·551	·001	·573	·574
15·	·001	·550	·551	·001	·573	·574
10·	·003	·551	·552	·003	·574	·576
9·	·004	·551	·553	·004	·574	·576
8·	·005	·551	·554	·005	·574	·577
7·	·006	·552	·555	·007	·575	·578
6·	·008	·552	·557	·009	·576	·580
5·5	·010	·553	·558	·011	·576	·582
5·0	·012	·553	·559	·013	·577	·584
4·5	·015	·554	·562	·016	·578	·586
4·0	·019	·555	·565	·021	·579	·589
3·75	·022	·556	·566	·024	·580	·592
3·50	·025	·557	·569	·028	·581	·594
3·25	·029	·558	·572	·032	·582	·598
3·0	·035	·559	·575	·038	·584	·602
2·75	·042	·561	·580	·045	·586	·607
2·50	·051	·564	·586	·055	·589	·614
2·25	·064	·567	·594	·069	·593	·623
2·00	·082	·572	·606	·089	·598	·636
1·95	·086	·573	·609	·094	·599	·639
1·90	·091	·575	·612	·100	·601	·643
1·85	·097	·576	·615	·106	·603	·647
1·80	·103	·578	·619	·113	·604	·651
1·75	·110	·579	·623	·120	·606	·655
1·70	·117	·581	·627	·128	·609	·660
1·65	·125	·583	·632	·137	·611	·666
1·60	·134	·586	·637	·147	·614	·671
1·55	·144	·588	·643	·158	·617	·678
1·50	·155	·591	·649	·171	·620	·685
1·45	·168	·594	·656	·185	·624	·694
1·40	·183	·598	·664	·201	·628	·703
1·35	·199	·602	·673	·220	·633	·713
1·30	·218	·607	·683	·241	·638	·724
1·25	·240	·612	·695	·266	·645	·737
1·20	·265	·619	·707	·295	·652	·753
1·15	·297	·626	·723	·330	·661	·770
1·10	·333	·635	·741	·372	·671	·791
1·05	·378	·646	·762	·424	·684	·816
1·00	·434	·659	·787	·489	·699	·845

See the auxiliary tables, pp. 104, 108, and 111.

TABLE V.—Coefficients of Discharge for different Ratios of the Channel to the Orifice.—Coefficients for heads in still water '584 and '595. See equations (44) and (44a) and the observations thereon at p. 99.

Ratio of the channel to the orifice.	Coefficient '584 for heads in still water.			Coefficient '595 for heads in still water.		
	Ratio of the height due to the velocity of approach to the head.	Coefficients for orifices: the heads measured to the centres.	Coefficients for weirs: the heads measured the full depth.	Ratio of the height due to the velocity of approach to the head.	Coefficients for orifices: the heads measured to the centres.	Coefficients for weirs: the heads measured the full depth.
30.	'000	'584	'584	'000	'595	'595
20.	'001	'584	'585	'001	'595	'596
15.	'002	'584	'585	'002	'595	'596
10.	'003	'585	'587	'004	'596	'598
9.0	'004	'585	'588	'004	'596	'599
1.0	'005	'586	'588	'006	'597	'600
7.0	'007	'586	'590	'007	'597	'601
6.0	'010	'587	'592	'010	'598	'603
5.5	'011	'587	'593	'012	'599	'605
5.0	'014	'588	'595	'014	'599	'607
4.5	'017	'589	'598	'018	'600	'610
4.0	'022	'590	'601	'023	'602	'613
3.75	'025	'591	'604	'026	'603	'616
3.50	'029	'592	'606	'030	'604	'619
3.25	'033	'594	'610	'035	'605	'622
3.0	'039	'595	'614	'041	'607	'627
2.75	'047	'598	'620	'049	'609	'633
2.50	'058	'601	'627	'060	'613	'641
2.25	'072	'605	'637	'075	'617	'651
2.0	'093	'611	'651	'097	'623	'666
1.95	'099	'612	'654	'103	'625	'669
1.90	'104	'614	'660	'109	'627	'673
1.85	'111	'615	'662	'115	'628	'678
1.80	'118	'617	'666	'123	'630	'682
1.75	'125	'620	'671	'131	'633	'687
1.70	'134	'622	'676	'140	'635	'693
1.65	'143	'624	'682	'149	'638	'699
1.60	'154	'627	'689	'160	'641	'706
1.55	'166	'631	'696	'173	'644	'713
1.50	'179	'634	'703	'187	'648	'721
1.45	'194	'638	'712	'202	'652	'730
1.40	'211	'643	'722	'220	'657	'741
1.35	'230	'648	'732	'241	'663	'752
1.30	'253	'654	'745	'265	'669	'765
1.25	'279	'661	'759	'293	'677	'780
1.20	'310	'669	'775	'325	'685	'797
1.15	'348	'678	'794	'366	'695	'818
1.10	'393	'689	'816	'414	'707	'842
1.05	'448	'703	'842	'473	'722	'870
1.00	'518	'719	'874	'548	'740	'905

See the auxiliary tables, pp. 104, 108, and 111.

TABLE V.—*Coefficients of Discharge for different Ratios of the Channel to the Orifice.*—Coefficients for heads in still water '606 and '617. See equations (44) and (44a) and the observations thereon at p. 99.

Ratio of the channel to the orifice.	Coefficient '606 for heads in still water.			Coefficient '617 for heads in still water.		
	Ratio of the height due to the velocity of approach to the head.	Coefficients for orifices: the heads measured to the centres.	Coefficients for weirs: the heads measured the full depth.	Ratio of the height due to the velocity of approach to the head.	Coefficients for orifices: the heads measured to the centres.	Coefficients for weirs: the heads measured the full depth.
30·	·000	·606	·606	·000	·617	·617
20·	·001	·606	·607	·001	·617	·618
15·	·002	·607	·607	·002	·618	·619
10·	·004	·607	·609	·004	·618	·620
9·0	·005	·607	·610	·005	·618	·621
8·0	·006	·608	·611	·006	·619	·622
7·0	·008	·608	·612	·008	·619	·624
6·0	·010	·609	·615	·011	·620	·626
5·5	·012	·610	·616	·013	·621	·628
5·0	·015	·611	·619	·015	·622	·630
4·5	·018	·612	·621	·019	·623	·633
4·0	·023	·613	·625	·024	·624	·637
3·75	·027	·614	·628	·028	·626	·640
3·50	·031	·615	·631	·032	·627	·643
3·25	·036	·617	·635	·037	·628	·647
3·00	·043	·619	·640	·044	·630	·653
2·75	·051	·621	·646	·053	·633	·660
2·50	·062	·625	·654	·065	·637	·668
2·25	·078	·629	·665	·081	·642	·679
2·00	·101	·636	·681	·105	·649	·696
1·95	·107	·638	·685	·111	·650	·700
1·90	·113	·639	·689	·118	·652	·704
1·85	·119	·641	·693	·125	·654	·709
1·80	·128	·644	·698	·133	·657	·714
1·75	·136	·646	·703	·142	·659	·720
1·70	·146	·649	·709	·152	·662	·726
1·65	·156	·652	·716	·163	·665	·733
1·60	·167	·655	·723	·175	·669	·741
1·55	·180	·658	·731	·188	·673	·749
1·50	·195	·662	·739	·204	·677	·759
1·45	·212	·667	·749	·221	·681	·768
1·40	·231	·672	·760	·241	·687	·780
1·35	·252	·678	·772	·264	·694	·793
1·30	·278	·685	·786	·291	·701	·808
1·25	·307	·693	·803	·322	·709	·825
1·20	·342	·702	·821	·359	·719	·845
1·15	·384	·713	·843	·404	·731	·868
1·10	·436	·726	·868	·459	·745	·895
1·05	·499	·742	·898	·527	·763	·928
1·00	·580	·762	·936	·615	·784	·969

See the auxiliary tables, pp. 104, 106, and 111.

TABLE V.—Coefficients of Discharge for different Ratios of the Channel to the Orifice.—Mean Coefficient '628. Coefficients for heads in still water '628 and '639. See equations (44) and (44a) and the observations thereon at p. 99.

Ratio of the channel to the orifice.	Coefficient '628 for heads in still water.			Coefficient '639 for heads in still water.		
	Ratio of the height due to the velocity of approach to the head.	Coefficients for orifices: the heads measured to the centres.	Coefficients for weirs: the heads measured the full depth.	Ratio of the height due to the velocity of approach to the head.	Coefficients for orifices: the heads measured to the centres.	Coefficients for weirs: the heads measured the full depth.
30·	·000	·628	·628	·000	·639	·639
20·	·001	·628	·629	·001	·639	·640
15·	·002	·629	·630	·002	·640	·641
10·	·004	·629	·632	·004	·640	·643
9·0	·005	·630	·632	·005	·641	·644
8·0	·006	·630	·634	·006	·641	·645
7·0	·008	·631	·635	·008	·642	·647
6·0	·011	·631	·638	·011	·643	·649
5·5	·013	·632	·640	·014	·643	·651
5·0	·016	·633	·642	·017	·644	·654
4·5	·020	·634	·645	·021	·646	·657
4·0	·025	·636	·649	·026	·647	·662
3·75	·029	·637	·652	·030	·648	·665
3·50	·033	·638	·656	·034	·650	·668
3·25	·039	·639	·659	·040	·652	·673
3·0	·046	·642	·666	·048	·654	·678
2·75	·055	·645	·672	·057	·657	·686
2·50	·067	·649	·682	·070	·661	·695
2·25	·084	·654	·694	·088	·666	·708
2·0	·109	·661	·711	·114	·674	·727
1·95	·116	·663	·715	·120	·676	·731
1·90	·123	·665	·720	·128	·679	·736
1·85	·130	·668	·725	·135	·681	·741
1·80	·139	·670	·731	·144	·684	·747
1·75	·148	·673	·737	·154	·686	·753
1·70	·158	·676	·743	·165	·690	·760
1·65	·169	·679	·750	·176	·693	·768
1·60	·182	·683	·758	·190	·697	·776
1·55	·196	·687	·767	·205	·701	·786
1·50	·213	·692	·777	·222	·706	·796
1·45	·231	·697	·788	·241	·712	·808
1·40	·252	·703	·800	·262	·718	·820
1·35	·276	·709	·814	·289	·725	·836
1·30	·304	·717	·830	·319	·734	·853
1·25	·338	·726	·846	·354	·743	·872
1·20	·377	·734	·866	·396	·755	·895
1·15	·425	·750	·894	·447	·769	·921
1·10	·484	·765	·924	·509	·785	·953
1·05	·557	·784	·959	·588	·805	·991
1·00	·651	·807	1·002	·690	·831	1·038

See the auxiliary tables, pp. 104, 106, and 111.

TABLE V.—Coefficients of Discharge for different Ratios of the Channel to the Orifice.—Coefficients for heads in still water '650 and '667. See equations (44) and (44a) and the observations thereon at p. 99.

Ratio of the channel to the orifice.	Coefficient '650 for heads in still water.			Coefficient '667 for heads in still water.		
	Ratio of the height due to the velocity of approach to the head.	Coefficients for orifices: the heads measured to the centres.	Coefficients for weirs: the heads measured the full depth.	Ratio of the height due to the velocity of approach to the head.	Coefficients for orifices: the heads measured to the centres.	Coefficients for weirs: the heads measured the full depth.
30·	·000	·650	·650	·000	·667	·667
20·	·001	·650	·651	·001	·667	·668
15·	·002	·651	·652	·002	·667	·669
10·	·004	·651	·654	·004	·668	·671
9·	·005	·652	·655	·006	·669	·672
8·	·007	·652	·656	·007	·669	·673
7·0	·009	·653	·658	·009	·670	·675
6·0	·012	·654	·661	·012	·671	·678
5·5	·014	·655	·663	·015	·672	·680
5·0	·017	·656	·665	·018	·673	·682
4·5	·021	·657	·669	·022	·674	·687
4·0	·027	·659	·674	·029	·676	·692
3·75	·031	·660	·677	·033	·678	·696
3·50	·036	·662	·681	·038	·679	·700
3·25	·042	·663	·686	·044	·681	·705
3·0	·049	·666	·692	·052	·684	·711
2·75	·059	·669	·699	·062	·687	·720
2·50	·073	·673	·709	·077	·692	·731
2·25	·091	·679	·723	·096	·698	·745
2·0	·118	·687	·742	·125	·707	·766
1·95	·125	·689	·747	·132	·709	·771
1·90	·133	·692	·752	·140	·712	·777
1·85	·141	·694	·758	·149	·715	·783
1·80	·150	·697	·764	·159	·718	·790
1·75	·160	·700	·771	·170	·721	·797
1·70	·172	·704	·779	·182	·725	·805
1·65	·184	·707	·786	·195	·729	·814
1·60	·198	·711	·795	·210	·733	·823
1·55	·218	·716	·805	·227	·738	·833
1·50	·231	·721	·816	·246	·744	·846
1·45	·251	·727	·828	·268	·751	·859
1·40	·275	·734	·842	·293	·758	·874
1·35	·302	·742	·858	·322	·764	·888
1·30	·333	·751	·876	·356	·776	·911
1·25	·371	·761	·896	·398	·788	·934
1·20	·415	·773	·920	·446	·802	·961
1·15	·469	·788	·949	·506	·818	·992
1·10	·537	·806	·983	·580	·838	1·030
1·05	·621	·828	1·024	·675	·863	1·076
1·00	·732	·855	1·074	·800	·894	1·133

See the auxiliary tables, pp. 104, 108, and 111.

TABLE V.—Coefficients of Discharge for different Ratios of the Channel to the Orifice.—Coefficients for heads in still water $\sqrt{5} = \cdot 7071$ and 1. See equations (44) and (44a) and the observations thereon at pp. 98 and 99.

Ratio of the channel to the orifice.	Coefficient $\cdot 707$ for heads in still water.			Coefficient 1.000 for heads in still water, and multipliers of c_d in equations (45a) and (46a), which see.		
	Ratio of the height due to the velocity of approach to the head.	Coefficients for orifices: the heads measured to the centres.	Coefficients for weirs: the heads measured the full depth.	Ratio of the height due to the velocity of approach to the head.	Coefficients for orifices: the heads measured to the centres.	Coefficients for weirs: the heads measured the full depth.
30.	$\cdot 001$	$\cdot 707$	$\cdot 708$	$\cdot 001$	1.001	1.002
20.	$\cdot 001$	$\cdot 708$	$\cdot 708$	$\cdot 003$	1.001	1.004
15.	$\cdot 001$	$\cdot 708$	$\cdot 709$	$\cdot 005$	1.002	1.006
10.	$\cdot 005$	$\cdot 709$	$\cdot 712$	$\cdot 010$	1.005	1.014
9.	$\cdot 006$	$\cdot 709$	$\cdot 713$	$\cdot 013$	1.006	1.017
8.	$\cdot 008$	$\cdot 710$	$\cdot 714$	$\cdot 016$	1.008	1.021
7.	$\cdot 010$	$\cdot 711$	$\cdot 717$	$\cdot 021$	1.010	1.028
6.	$\cdot 014$	$\cdot 712$	$\cdot 721$	$\cdot 029$	1.014	1.038
5.5	$\cdot 017$	$\cdot 713$	$\cdot 723$	$\cdot 034$	1.017	1.045
5.0	$\cdot 020$	$\cdot 714$	$\cdot 727$	$\cdot 041$	1.021	1.055
4.5	$\cdot 025$	$\cdot 716$	$\cdot 731$	$\cdot 052$	1.026	1.067
4.0	$\cdot 032$	$\cdot 718$	$\cdot 737$	$\cdot 067$	1.033	1.084
3.75	$\cdot 037$	$\cdot 720$	$\cdot 742$	$\cdot 077$	1.038	1.096
3.50	$\cdot 043$	$\cdot 722$	$\cdot 747$	$\cdot 089$	1.044	1.110
3.25	$\cdot 050$	$\cdot 724$	$\cdot 753$	$\cdot 105$	1.051	1.127
3.00	$\cdot 059$	$\cdot 728$	$\cdot 760$	$\cdot 125$	1.061	1.149
2.75	$\cdot 071$	$\cdot 732$	$\cdot 770$	$\cdot 152$	1.073	1.178
2.50	$\cdot 087$	$\cdot 737$	$\cdot 783$	$\cdot 190$	1.091	1.216
2.25	$\cdot 110$	$\cdot 745$	$\cdot 801$	$\cdot 246$	1.116	1.269
2.00	$\cdot 143$	$\cdot 756$	$\cdot 826$	$\cdot 333$	1.155	1.347
1.95	$\cdot 151$	$\cdot 759$	$\cdot 832$	$\cdot 356$	1.165	1.367
1.90	$\cdot 161$	$\cdot 762$	$\cdot 839$	$\cdot 383$	1.176	1.389
1.85	$\cdot 171$	$\cdot 765$	$\cdot 846$	$\cdot 412$	1.188	1.413
1.80	$\cdot 182$	$\cdot 769$	$\cdot 854$	$\cdot 446$	1.203	1.441
1.75	$\cdot 195$	$\cdot 773$	$\cdot 863$	$\cdot 484$	1.218	1.471
1.70	$\cdot 209$	$\cdot 778$	$\cdot 873$	$\cdot 529$	1.237	1.505
1.65	$\cdot 225$	$\cdot 783$	$\cdot 883$	$\cdot 579$	1.257	1.543
1.60	$\cdot 243$	$\cdot 788$	$\cdot 895$	$\cdot 641$	1.281	1.589
1.55	$\cdot 263$	$\cdot 795$	$\cdot 908$	$\cdot 711$	1.308	1.638
1.50	$\cdot 286$	$\cdot 802$	$\cdot 923$	$\cdot 800$	1.342	1.699
1.45	$\cdot 312$	$\cdot 810$	$\cdot 939$	$\cdot 903$	1.379	1.767
1.40	$\cdot 342$	$\cdot 819$	$\cdot 958$	1.042	1.429	1.854
1.35	$\cdot 378$	$\cdot 830$	$\cdot 980$	1.216	1.489	1.958
1.30	$\cdot 421$	$\cdot 842$	1.003	1.449	1.565	2.088
1.25	$\cdot 471$	$\cdot 857$	1.033	1.778	1.667	2.259
1.20	$\cdot 532$	$\cdot 875$	1.066	2.273	1.810	2.499
1.15	$\cdot 608$	$\cdot 897$	1.107	3.100	2.025	2.844
1.10	$\cdot 704$	$\cdot 923$	1.155	4.762	2.400	3.440
1.05	$\cdot 830$	$\cdot 957$	1.216	9.756	3.280	4.803
1.00	1.000	1.000	1.293	infinite.	infinite.	infinite.

See the auxiliary table, p. 111, also pp. 112, 113.

TABLE VI.—The Discharge over Weirs or Notches of one foot in length, in Cubic feet per minute.—Depths $\frac{1}{2}$ inch to 10 inches. GREATER COEFFICIENTS 667 to 617.—The Formula at the heads of the Columns give the Value of the Discharge, D , in Cubic feet per minute, when l , the length of the Weir, is taken in feet, and the head, h , in inches. For $l \sqrt{h^3}$ we may substitute $l h \sqrt{h}$, retaining the same standards.

Heads in inches.	Theoretical discharge, $D =$ $7.72 l \sqrt{h^3}$	Coefficient 667. $D =$ $5.15 l \sqrt{h^3}$	Coefficient 650. $D =$ $5.02 l \sqrt{h^3}$	Coefficient 639. $D =$ $4.93 l \sqrt{h^3}$	Coefficient 628. $D =$ $4.85 l \sqrt{h^3}$	Coefficient 617. $D =$ $4.76 l \sqrt{h^3}$
.25	.965	.644	.627	.617	.606	.596
.5	2.730	1.821	1.775	1.744	1.714	1.684
.75	5.016	3.345	3.260	3.205	3.150	3.095
1.	7.722	5.151	5.019	4.934	4.849	4.764
1.25	10.792	7.198	7.015	6.896	6.777	6.659
1.5	14.186	9.462	9.221	9.065	8.909	8.753
1.75	17.877	11.924	11.620	11.423	11.227	11.030
2.	21.842	14.569	14.197	13.957	13.717	13.477
2.25	26.062	17.383	16.940	16.654	16.367	16.080
2.5	30.524	20.360	19.841	19.505	19.169	18.833
2.75	35.215	23.489	22.890	22.503	22.115	21.728
3.	40.125	26.763	26.081	25.640	25.199	24.757
3.25	45.244	30.178	29.408	28.911	28.413	27.915
3.5	50.563	33.726	32.866	32.310	31.754	31.197
3.75	56.077	37.403	36.450	35.833	35.216	34.599
4.	61.777	41.205	40.155	39.476	38.796	38.116
4.25	67.658	45.128	43.978	43.233	42.489	41.745
4.5	73.714	49.167	47.914	47.103	46.292	45.482
4.75	79.942	53.321	51.962	51.083	50.203	49.324
5.	86.335	57.585	56.118	55.168	54.218	53.269
5.25	92.891	61.958	60.379	59.357	58.335	57.314
5.5	99.604	66.436	64.743	63.647	62.551	61.456
5.75	106.472	71.017	69.207	68.036	66.864	65.693
6.	113.491	75.698	73.769	72.521	71.272	70.024
6.25	120.657	80.478	78.427	77.100	75.772	74.445
6.5	127.969	85.355	83.180	81.772	80.365	78.957
6.75	135.422	90.326	88.024	86.535	85.045	83.555
7.	143.015	95.391	92.960	91.387	89.813	88.240
7.25	150.744	100.546	97.983	96.325	94.667	93.009
7.5	158.608	105.792	103.095	101.350	99.606	97.861
7.75	166.604	111.125	108.292	106.460	104.627	102.795
8.	174.731	116.546	113.575	111.653	109.731	107.809
8.25	182.984	122.051	118.940	116.927	114.914	112.901
8.5	191.365	127.640	124.387	122.282	120.177	118.072
8.75	199.869	133.313	129.915	127.716	125.518	123.319
9.	208.496	139.067	135.522	133.229	130.935	128.642
9.25	217.243	144.901	141.207	138.818	136.428	134.039
9.5	226.111	150.816	146.972	144.485	141.997	139.510
9.75	235.093	156.807	152.810	150.225	147.639	145.053
10.	244.193	162.877	158.725	156.039	153.353	150.666

See pp. 114 to 133.

TABLE VI.—The Discharge over Weirs or Notches of one foot in length, in Cubic feet per minute.—Depths 10.25 inches to 32 inches. GREATER COEFFICIENTS .667 to .617.—The Formulas at the heads of the Columns give the Value of the Discharge, D , in Cubic feet per minute, when l , the length of the Weir, is taken in feet, and the head, h , in inches. For $l \sqrt{h^3}$ we may substitute $l h \sqrt{h}$, retaining the same standards.

Heads in inches.	Theoretical discharge, $D =$ $7.73 l \sqrt{h^3}$.	Coefficient .667. $D =$ $5.15 l \sqrt{h^3}$.	Coefficient .650. $D =$ $5.02 l \sqrt{h^3}$.	Coefficient .639. $D =$ $4.93 l \sqrt{h^3}$.	Coefficient .628. $D =$ $4.85 l \sqrt{h^3}$.	Coefficient .617. $D =$ $4.76 l \sqrt{h^3}$.
10.25	253.407	169.023	164.715	161.927	159.140	156.352
10.5	262.734	175.244	170.777	167.887	164.997	162.107
10.75	272.173	181.450	176.913	173.919	170.925	167.931
11.	281.723	187.909	183.120	180.921	176.922	173.823
11.25	291.382	194.352	189.398	186.193	182.988	179.782
11.5	301.148	200.866	195.746	192.434	189.121	185.808
11.75	311.024	207.451	202.164	198.743	195.321	191.900
12.	321.	214.107	208.650	205.119	201.588	198.057
12.5	341.275	227.628	221.826	218.072	214.318	210.564
13.	361.950	241.421	235.268	231.286	227.305	223.323
13.5	383.031	255.482	248.970	244.757	240.543	236.330
14.	404.507	269.806	262.930	258.480	254.030	249.581
14.5	426.368	284.387	277.139	272.449	267.759	263.069
15.	448.611	299.223	291.597	286.662	281.728	276.793
15.5	471.228	314.309	306.298	301.115	295.931	290.748
16.	494.212	329.639	321.238	315.801	310.365	304.929
16.5	517.558	345.211	336.413	330.720	325.026	319.833
17.	541.261	361.021	351.820	345.866	339.912	333.958
17.5	565.315	377.065	367.455	361.236	355.018	348.799
18.	589.715	393.340	383.315	376.828	370.341	363.854
18.5	614.443	409.833	399.388	392.629	385.870	379.111
19.	639.533	426.569	415.696	408.662	401.627	394.592
19.5	664.944	443.518	432.214	424.899	417.585	410.270
20.	690.682	460.685	448.943	441.346	433.748	426.151
20.5	716.737	478.064	465.879	457.995	450.111	442.227
21.	743.125	495.664	483.031	474.857	466.683	458.508
21.5	769.823	513.472	500.385	491.917	483.449	474.981
22.	796.832	531.487	517.941	509.176	500.410	491.645
22.5	824.151	549.709	535.698	526.632	517.567	508.501
23.	851.775	568.134	553.654	544.284	534.915	525.545
23.5	879.700	586.760	571.805	562.128	552.452	542.775
24.	907.925	605.586	590.151	580.164	570.177	560.190
25.	965.253	643.824	627.414	616.797	606.179	595.581
26.	1023.748	682.840	665.436	654.175	642.914	631.653
27.	1083.375	722.611	704.194	692.277	680.360	668.442
28.	1144.116	763.125	743.675	731.090	718.505	705.920
29.	1205.950	804.369	783.868	770.602	757.337	744.071
30.	1268.864	846.332	824.762	810.804	796.847	782.889
31.	1332.833	889.000	866.341	851.680	837.019	822.358
32.	1397.842	932.361	908.597	893.221	877.845	862.469

See pp. 114 to 133.

TABLE VI.—The Discharge over Weirs or Notches of one foot in length, in Cubic feet per minute.—Depths 33 inches to 72 inches. GREATER COEFFICIENTS '687 to '617.—The Formulas at the heads of the Columns give the Value of the Discharge, D , in Cubic feet per minute, when l , the length of the Weir, is taken in feet, and the head, h , in inches. For $l \sqrt{h^3}$ we may substitute $l h \sqrt{h}$, retaining the same standards.

Heads in inches.	Theoretical discharge, $D =$ $7.72 l \sqrt{h^3}$.	Coefficient '687. $D =$ $5.15 l \sqrt{h^3}$.	Coefficient '650. $D =$ $5.02 l \sqrt{h^3}$.	Coefficient '639. $D =$ $4.98 l \sqrt{h^3}$.	Coefficient '628. $D =$ $4.85 l \sqrt{h^3}$.	Coefficient '617. $D =$ $4.76 l \sqrt{h^3}$.
33.	1463.875	976.405	951.519	935.416	919.314	903.211
34.	1530.917	1021.122	995.096	978.256	961.416	944.576
35.	1598.951	1066.500	1039.318	1021.730	1004.141	986.553
36.	1667.964	1112.532	1084.177	1065.829	1047.481	1029.134
37.	1737.943	1159.208	1129.663	1110.546	1091.428	1072.311
38.	1808.875	1206.520	1175.769	1155.871	1135.974	1116.076
39.	1880.746	1254.458	1222.485	1201.797	1181.108	1160.420
40.	1953.544	1303.014	1269.804	1248.315	1226.826	1205.337
41.	2027.258	1352.181	1317.718	1295.418	1273.118	1250.818
42.	2101.876	1401.951	1366.219	1343.099	1319.978	1296.857
43.	2177.387	1452.317	1415.302	1391.350	1367.399	1343.448
44.	2253.783	1503.273	1464.959	1440.167	1415.376	1390.584
45.	2331.052	1554.812	1515.184	1489.542	1463.901	1438.259
46.	2409.183	1606.925	1565.969	1539.468	1512.967	1486.466
47.	2488.170	1659.609	1617.311	1589.941	1562.571	1535.201
48.	2568.	1712.856	1669.200	1640.952	1612.704	1584.456
49.	2648.666	1766.660	1721.633	1692.498	1663.362	1634.227
50.	2730.160	1821.021	1774.604	1744.572	1714.540	1684.509
51.	2812.474	1875.920	1828.108	1797.171	1766.234	1735.296
52.	2895.597	1931.363	1882.138	1850.286	1818.435	1786.583
53.	2979.525	1987.343	1936.691	1903.916	1871.142	1838.367
54.	3064.253	2043.857	1991.764	1958.058	1924.351	1890.644
55.	3149.755	2100.887	2047.341	2012.693	1978.046	1943.399
56.	3236.050	2158.445	2103.433	2067.836	2032.239	1996.643
57.	3323.117	2216.519	2160.026	2123.472	2086.917	2050.363
58.	3410.946	2275.101	2217.115	2179.594	2142.074	2104.554
59.	3499.542	2334.195	2274.702	2236.207	2197.712	2159.217
60.	3588.889	2393.789	2332.778	2293.300	2253.822	2214.344
61.	3678.984	2453.882	2391.340	2350.871	2310.402	2269.933
62.	3769.825	2514.473	2450.386	2408.918	2367.450	2325.982
63.	3861.393	2575.549	2509.905	2467.430	2424.955	2382.479
64.	3953.694	2637.114	2569.901	2526.410	2482.920	2439.429
65.	4046.720	2699.162	2630.368	2585.854	2541.340	2496.826
66.	4140.465	2761.690	2691.302	2645.757	2600.212	2554.667
67.	4234.922	2824.693	2752.699	2706.115	2659.531	2612.947
68.	4330.086	2888.167	2814.556	2766.925	2719.294	2671.663
69.	4425.954	2952.111	2876.870	2828.185	2779.499	2730.814
70.	4522.516	3016.518	2939.635	2889.888	2840.140	2790.392
71.	4619.774	3081.389	3002.853	2952.036	2901.218	2850.401
72.	4717.718	3146.718	3066.518	3014.622	2962.727	2910.832

See pp. 114 to 133.

TABLE VI.—The Discharge over Weirs or Notches of one foot in length, in Cubic feet per minute.—Depths $\frac{1}{2}$ inch to 10 inches. LESSER COEFFICIENTS '606 to '518.—The Formula at the heads of the Columns give the Value of the Discharge, D , in Cubic feet per minute, when l , the length of the Weir, is taken in feet, and the head, h , in inches. For $l \sqrt{h^3}$ we may substitute $l h \sqrt{h}$, retaining the same standards.

Heads in inches.	Coefficient '606. $D =$ $4.68 l \sqrt{h^3}$.	Coefficient '595. $D =$ $4.59 l \sqrt{h^3}$.	Coefficient '584. $D =$ $4.51 l \sqrt{h^3}$.	Coefficient '562. $D =$ $4.34 l \sqrt{h^3}$.	Coefficient '540. $D =$ $4.17 l \sqrt{h^3}$.	Coefficient '518. $D =$ $4 l \sqrt{h^3}$.
.25	.585	.574	.564	.542	.521	.500
.5	1.654	1.624	1.504	1.534	1.474	1.414
.75	3.039	2.985	2.929	2.819	2.708	2.598
1.	4.680	4.595	4.510	4.340	4.170	4.000
1.25	6.540	6.421	6.303	6.065	5.828	5.590
1.5	8.597	8.441	8.284	7.973	7.660	7.348
1.75	10.833	10.637	10.440	10.047	9.653	9.260
2.	13.236	12.996	12.756	12.275	11.795	11.314
2.25	15.794	15.507	15.220	14.647	14.073	13.500
2.5	18.498	18.162	17.826	17.155	16.483	15.811
2.75	21.340	20.953	20.556	19.791	19.016	18.241
3.	24.316	23.874	23.433	22.550	21.668	20.785
3.25	27.418	26.920	26.422	25.427	24.432	23.436
3.5	30.641	30.085	29.529	28.416	27.304	26.192
3.75	33.982	33.366	32.749	31.515	30.281	29.048
4.	37.437	36.757	36.078	34.719	33.360	32.000
4.25	41.001	40.256	39.512	38.024	36.535	35.047
4.5	44.671	43.860	43.049	41.427	39.806	38.184
4.75	48.445	47.565	46.686	44.927	43.169	41.410
5.	52.319	51.369	50.420	48.520	46.621	44.722
5.25	56.292	55.270	54.248	52.205	50.161	48.117
5.5	60.360	59.264	58.169	55.977	53.786	51.595
5.75	64.522	63.351	62.180	59.837	57.495	55.153
6.	68.776	67.527	66.279	63.782	61.285	58.788
6.25	73.118	71.791	70.464	67.809	65.155	62.500
6.5	77.549	76.142	74.734	71.919	69.103	66.288
6.75	82.066	80.576	79.086	76.107	73.128	70.149
7.	86.667	85.094	83.521	80.374	77.228	74.082
7.25	91.351	89.693	88.034	84.718	81.402	78.085
7.5	96.116	94.372	92.627	89.138	85.648	82.159
7.75	100.962	99.129	97.297	93.631	89.966	86.301
8.	105.887	103.965	102.043	98.199	94.355	90.511
8.25	110.889	108.876	106.863	102.837	98.812	94.786
8.5	115.967	113.862	111.757	107.547	103.337	99.127
8.75	121.121	118.922	116.723	112.326	107.929	103.532
9.	126.349	124.055	121.762	117.175	112.588	108.001
9.25	131.649	129.259	126.870	122.090	117.311	112.532
9.5	137.023	134.535	132.048	127.074	122.100	117.125
9.75	142.467	139.881	137.294	132.122	126.950	121.778
10.	147.991	145.295	142.609	137.237	131.864	126.492

See pp. 114 to 133.

TABLE VI.—The Discharge over Weirs or Notches of one foot in length in Cubic feet per minute.—Depths 10.25 inches to 32 inches. LESSER COEFFICIENTS 606 to 518.—The Formula at the heads of the Columns give the Value of the Discharge, D , in Cubic feet per minute, when l , the length of the Weir, is taken in feet, and the head, h , in inches. For $l \sqrt{h^3}$ we may substitute $l h \sqrt{h}$, retaining the same standards.

Heads in inches.	Coefficient 606. $D =$ $4.68 l \sqrt{h^3}$.	Coefficient 595. $D =$ $4.59 l \sqrt{h^3}$.	Coefficient 584. $D =$ $4.51 l \sqrt{h^3}$.	Coefficient 562. $D =$ $4.34 l \sqrt{h^3}$.	Coefficient 540. $D =$ $4.17 l \sqrt{h^3}$.	Coefficient 518. $D =$ $4 l \sqrt{h^3}$.
10.25	153.565	150.777	147.990	142.415	136.840	131.265
10.5	159.217	156.327	153.437	147.657	141.876	136.096
10.75	164.937	161.943	158.949	152.961	146.974	140.986
11.	170.724	167.625	164.526	158.328	152.130	145.933
11.25	176.577	173.372	170.167	163.756	157.346	150.936
11.5	182.496	179.183	175.870	169.245	162.620	155.995
11.75	188.479	185.059	181.636	174.794	167.952	161.109
12.	194.526	190.995	187.464	180.402	173.340	166.278
12.5	206.810	203.056	199.302	191.794	184.286	176.778
13.	219.342	215.360	211.379	203.415	195.453	187.490
13.5	232.117	227.903	223.690	215.263	206.837	198.410
14.	245.131	240.682	236.232	227.333	218.434	209.535
14.5	258.379	253.689	248.999	239.619	230.239	220.859
15.	271.858	266.924	261.989	252.119	242.250	232.380
15.5	285.564	280.381	275.197	264.830	254.463	244.096
16.	299.492	294.056	288.620	277.747	266.875	256.001
16.5	313.640	307.947	302.253	290.868	279.481	268.095
17.	328.004	322.050	316.096	304.189	292.281	280.373
17.5	342.581	336.362	330.144	317.707	305.270	292.833
18.	357.367	350.880	344.394	331.420	318.446	305.472
18.5	372.352	365.594	358.835	345.317	331.799	318.241
19.	387.557	380.522	373.487	359.418	345.348	331.278
19.5	402.956	395.642	388.327	373.699	359.070	344.441
20.	418.553	410.959	403.358	388.163	372.968	357.778
20.5	434.343	426.458	418.574	402.806	387.038	371.270
21.	450.334	442.159	433.985	417.636	401.288	384.939
21.5	466.513	458.045	449.577	432.641	415.704	398.768
22.	482.880	474.115	465.350	447.819	430.289	412.759
22.5	499.436	490.370	481.304	463.173	445.042	426.910
23.	517.176	506.806	497.437	478.698	459.959	441.219
23.5	533.098	523.421	513.745	494.391	475.038	455.685
24.	550.208	540.215	530.228	510.254	490.280	470.305
25.	568.493	557.826	546.708	526.272	505.787	485.085
26.	587.056	576.161	564.389	542.446	521.567	500.001
27.	606.897	595.229	583.271	558.776	537.624	515.153
28.	627.026	615.040	603.364	575.261	553.964	530.544
29.	647.443	635.603	623.670	591.901	570.593	546.175
30.	668.148	656.928	644.197	608.696	587.518	562.046
31.	689.141	678.925	664.946	625.646	604.745	578.167
32.	710.422	701.604	685.917	642.751	622.271	594.538

See pp. 114 to 133.

TABLE VI.—The Discharge over Weirs or Notches of one foot in length, in Cubic feet per minute.—Depths 33 inches to 72 inches. LESSER COEFFICIENTS '606 to '518.—The Formula at the heads of the Columns give the Value of the Discharge, D , in Cubic feet per minute, when L , the length of the Weir, is taken in feet, and the head, h , in inches. For $L \sqrt{h^3}$ we may substitute $L h \sqrt{h}$, retaining the same standards.

Heads in inches.	Coefficient '606. $D =$ $4.68 L \sqrt{h^3}$.	Coefficient '595. $D =$ $4.59 L \sqrt{h^3}$.	Coefficient '584. $D =$ $4.51 L \sqrt{h^3}$.	Coefficient '562. $D =$ $4.34 L \sqrt{h^3}$.	Coefficient '540. $D =$ $4.17 L \sqrt{h^3}$.	Coefficient '518. $D =$ $4.1 \sqrt{h^3}$.
33.	887.108	871.006	854.903	822.698	790.493	758.287
34.	927.736	910.896	894.056	860.375	826.695	793.015
35.	968.964	951.376	933.787	898.610	863.434	828.257
36.	1010.786	992.439	974.091	937.396	900.701	864.005
37.	1053.193	1034.076	1014.959	976.724	938.489	900.254
38.	1096.178	1076.281	1056.383	1016.588	976.793	936.997
39.	1139.732	1119.044	1098.356	1056.979	1015.603	974.226
40.	1183.848	1162.359	1140.870	1097.892	1054.914	1011.936
41.	1228.518	1206.219	1183.919	1139.319	1094.719	1050.120
42.	1273.737	1250.616	1227.496	1181.254	1135.013	1088.772
43.	1319.497	1295.545	1271.594	1223.691	1175.789	1127.886
44.	1365.792	1341.001	1316.209	1266.626	1217.043	1167.460
45.	1412.618	1386.976	1361.334	1310.051	1258.768	1207.485
46.	1459.965	1433.464	1406.963	1353.961	1300.959	1247.957
47.	1507.831	1480.461	1453.091	1398.352	1343.612	1288.872
48.	1556.208	1527.960	1499.712	1443.216	1386.720	1330.224
49.	1605.092	1575.956	1546.821	1488.550	1430.280	1372.009
50.	1654.477	1624.445	1594.413	1534.350	1474.286	1414.223
51.	1704.359	1673.422	1642.485	1580.610	1518.736	1456.862
52.	1754.732	1722.880	1691.029	1627.326	1563.622	1499.919
53.	1805.592	1772.817	1740.043	1674.493	1608.944	1543.394
54.	1856.937	1823.231	1789.524	1722.110	1654.697	1587.283
55.	1908.751	1874.104	1839.457	1770.162	1700.868	1631.573
56.	1961.046	1925.450	1889.853	1818.660	1747.467	1676.274
57.	2013.809	1977.255	1940.700	1867.592	1794.483	1721.375
58.	2067.033	2029.513	1991.992	1916.952	1841.911	1766.870
59.	2120.722	2082.227	2043.733	1966.743	1889.753	1812.763
60.	2174.867	2135.389	2095.911	2016.956	1938.000	1859.045
61.	2229.464	2188.995	2148.527	2067.589	1986.651	1905.714
62.	2284.514	2243.046	2201.578	2118.642	2035.706	1952.769
63.	2340.004	2297.529	2255.054	2170.103	2085.152	2000.202
64.	2395.939	2352.448	2308.957	2221.976	2134.995	2048.013
65.	2452.312	2407.798	2363.284	2274.257	2185.229	2096.201
66.	2509.122	2463.577	2418.032	2326.941	2235.851	2144.761
67.	2566.363	2519.779	2473.194	2380.026	2286.858	2193.690
68.	2624.032	2576.401	2528.770	2433.508	2338.246	2242.985
69.	2682.128	2633.443	2584.757	2487.386	2390.015	2292.644
70.	2740.645	2690.897	2641.149	2541.654	2442.159	2342.663
71.	2799.583	2748.766	2697.948	2596.313	2494.678	2393.043
72.	2858.937	2807.042	2755.147	2651.358	2547.568	2443.778

See pp. 114 to 133.

H H

TABLE VII.—For finding the Mean Velocity from the Maximum Velocity at the Surface, in Mill Races, Streams, and Rivers with uniform Channels; and the Maximum Velocity from the Mean Velocity.
For the Velocity in feet per minute, multiply by 5.

Maximum velocity at the surface in inches per second.	Mean velocity in large channels in inches per second.	Mean velocity in smaller channels in inches per second.	Maximum velocity at the surface in inches per second.	Mean velocity in large channels in inches per second.	Mean velocity in smaller channels in inches per second.	Maximum velocity at the surface in inches per second.	Mean velocity in large channels in inches per second.	Mean velocity in smaller channels in inches per second.
1	.84	.75	41	34.24	33.37	81	67.64	68.86
2	1.67	1.51	42	35.07	34.23	82	68.47	69.77
3	2.51	2.27	43	35.91	35.09	83	69.31	70.68
4	3.34	3.04	44	36.74	35.95	84	70.14	71.59
5	4.18	3.81	45	37.58	36.82	85	70.98	72.50
6	5.01	4.58	46	38.41	37.69	86	71.81	73.42
7	5.85	5.36	47	39.25	38.56	87	72.65	74.33
8	6.68	6.14	48	40.08	39.43	88	73.48	75.24
9	7.52	6.92	49	40.92	40.30	89	74.32	76.16
10	8.35	7.71	50	41.75	41.17	90	75.15	77.08
11	9.19	8.50	51	42.59	42.05	91	75.99	77.99
12	10.02	9.29	52	43.42	42.92	92	76.82	78.91
13	10.86	10.09	53	44.26	43.80	93	77.66	79.83
14	11.69	10.88	54	45.09	44.68	94	78.49	80.75
15	12.53	11.69	55	45.93	45.56	95	79.33	81.67
16	13.36	12.49	56	46.76	46.44	96	80.16	82.59
17	14.20	13.30	57	47.60	47.32	97	81.00	83.51
18	15.03	14.11	58	48.43	48.21	98	81.83	84.43
19	15.87	14.92	59	49.27	49.09	99	82.67	85.36
20	16.70	15.73	60	50.10	49.98	100	83.50	86.28
21	17.54	16.55	61	50.94	50.87	101	84.34	87.20
22	18.37	17.37	62	51.77	51.76	102	85.17	88.13
23	19.21	18.19	63	52.61	52.65	103	86.01	89.06
24	20.04	19.02	64	53.44	53.54	104	86.84	89.98
25	20.88	19.85	65	54.28	54.43	105	87.68	90.91
26	21.71	20.68	66	55.11	55.33	106	88.51	91.84
27	22.55	21.51	67	55.95	56.22	107	89.35	92.77
28	23.38	22.34	68	56.78	57.12	108	90.18	93.69
29	24.22	23.18	69	57.62	58.02	109	91.02	94.62
30	25.05	24.02	70	58.45	58.91	110	91.85	95.55
31	25.89	24.86	71	59.29	59.81	111	92.69	96.49
32	26.72	25.70	72	60.12	60.71	112	93.52	97.42
33	27.56	26.54	73	60.96	61.61	113	94.36	98.35
34	28.39	27.39	74	61.79	62.52	114	95.19	99.28
35	29.23	28.24	75	62.63	63.42	115	96.03	100.21
36	30.06	29.09	76	63.46	64.32	116	96.86	101.15
37	30.90	29.94	77	64.30	65.23	117	97.70	102.08
38	31.73	30.79	78	65.13	66.13	118	98.53	103.02
39	32.57	31.65	79	65.97	67.04	119	99.37	103.95
40	33.40	32.51	80	66.80	67.95	120	100.20	104.89

TABLE VIII.—For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.—For a full cylindrical pipe, divide the diameter by 4 to find the hydraulic mean depth.

Diameters of pipes $\frac{1}{8}$ inch to 2 inches. Falls per mile 1 inch to 12 feet.

Falls per mile in feet and inches, and the hydraulic inclinations.		"Hydraulic mean depths," or "mean radii," and velocities in inches per second.				
Falls.	Inclinations one in	$\frac{1}{16}$ inch.	$\frac{1}{8}$ inch.	$\frac{1}{4}$ inch.	$\frac{3}{8}$ inch.	$\frac{1}{2}$ inch.
F. I.						
0 1	63360	·14	·24	·38	·49	·57
0 2	31680	·22	·37	·59	·76	·90
0 3	21120	·28	·48	·75	·97	1·15
0 4	15840	·34	·57	·89	1·15	1·36
0 5	12672	·38	·65	1·02	1·30	1·55
0 6	10560	·42	·72	1·13	1·45	1·72
0 7	9051	·46	·78	1·24	1·58	1·88
0 8	7920	·50	·85	1·33	1·71	2·02
0 9	7040	·53	·90	1·43	1·83	2·16
0 10	6336	·57	·96	1·51	1·94	2·30
0 11	5760	·60	1·01	1·60	1·96	2·42
1 0	5280	·63	1·06	1·68	2·15	2·54
1 3	4224	·71	1·20	1·90	2·43	2·88
1 6	3520	·79	1·33	2·10	2·69	3·19
1 9	3017	·87	1·45	2·29	2·94	3·48
2 0	2640	·93	1·56	2·47	3·16	3·75
2 3	Interpolated.	·99	1·67	2·63	3·37	3·99
2 6	2112	1·05	1·77	2·79	3·58	4·24
2 9	Interpolated.	1·11	1·87	2·94	3·77	4·47
3 0	1760	1·16	1·96	3·09	3·96	4·69
3 3	Interpolated.	1·21	2·05	3·23	4·14	4·91
3 6	1508	1·26	2·14	3·37	4·32	5·12
3 9	Interpolated.	1·31	2·22	3·50	4·48	5·31
4 0	1320	1·36	2·30	3·63	4·65	5·51
4 6	Interpolated.	1·45	2·45	3·87	4·96	5·88
5 0	1056	1·54	2·61	4·11	5·27	6·24
5 6	Interpolated.	1·62	2·75	4·33	5·55	6·58
6 0	880	1·71	2·89	4·55	5·83	6·91
6 6	Interpolated.	1·78	3·02	4·76	6·10	7·22
7 0	754	1·86	3·15	4·97	6·36	7·54
7 6	Interpolated.	1·93	3·27	5·16	6·61	7·83
8 0	660	2·01	3·39	5·35	6·86	8·12
8 6	Interpolated.	2·07	3·51	5·53	7·09	8·40
9 0	587	2·14	3·62	5·72	7·32	8·68
9 6	Interpolated.	2·20	3·74	5·89	7·55	8·94
10 0	528	2·28	3·85	6·07	7·77	9·21
10 6	Interpolated.	2·33	3·95	6·24	7·99	9·47
11 0	480	2·40	4·06	6·40	8·20	9·72
11 6	Interpolated.	2·46	4·16	6·57	8·41	9·97
12 0	440	2·52	4·27	6·73	8·62	10·21

TABLE VIII.—For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.—For a full cylindrical pipe, divide the diameter by 4 to find the hydraulic mean depth.

Diameters of pipes $\frac{1}{8}$ inch to 2 inches. Falls per mile 13 feet to 5280 feet.

Falls per mile in feet, and the hydraulic inclination.		"Hydraulic mean depths," or "mean radii," and velocities in inches per second.				
Falls.	Inclinations one in	$\frac{1}{16}$ inch.	$\frac{1}{8}$ inch.	$\frac{1}{4}$ inch.	$\frac{3}{8}$ inch.	$\frac{1}{2}$ inch.
F.						
13·2	400	2·66	4·50	7·10	9·10	10·78
13·6	Interpolated.	2·71	4·59	7·24	9·27	10·98
14·1	375	2·76	4·67	7·37	9·44	11·18
14·6	Interpolated.	2·82	4·76	7·52	9·63	11·41
15·1	350	2·87	4·85	7·66	9·82	11·63
15·6	Interpolated.	2·94	4·96	7·83	10·03	11·88
16·2	325	3·00	5·07	7·99	10·24	12·13
17·6	300	3·14	5·30	8·37	10·72	12·70
19·2	275	3·30	5·58	8·80	11·27	13·35
21·1	250	3·48	5·89	9·39	11·90	14·10
23·5	225	3·70	6·26	9·87	12·65	14·99
26·4	200	3·96	6·70	10·57	13·54	16·04
30·2	175	4·28	7·24	11·42	14·63	17·33
35·2	150	4·68	7·92	12·49	16·00	18·96
37·7	140	4·88	8·24	13·00	16·66	19·74
42·2	125	5·21	8·81	13·90	17·80	21·09
48·	110	5·62	9·50	14·98	19·19	22·74
52·8	100	5·94	10·05	15·85	20·30	24·06
58·7	90	6·33	10·69	16·87	21·61	25·60
66·	80	6·78	11·47	18·10	23·17	27·46
75·4	70	7·35	12·42	19·59	25·09	29·73
88·	60	8·05	13·61	21·48	27·51	32·60
105·6	50	8·99	15·19	23·96	30·69	36·37
117·3	45	9·57	16·18	25·53	32·70	38·75
132·0	40	10·28	17·37	27·41	35·11	41·60
150·8	35	11·14	18·84	29·71	38·06	45·10
176·	30	12·23	20·68	32·62	41·78	49·51
212·2	25	13·66	23·09	36·43	46·67	55·30
264·	20	15·64	26·44	41·71	53·43	63·30
352·	15	18·61	31·46	49·63	63·57	75·33
528·	10	23·73	40·11	63·28	81·06	96·05
586·7	9	25·26	42·70	67·37	86·29	102·25
660·	8	27·08	45·78	72·22	92·51	109·61
754·3	7	29·29	49·51	78·10	100·04	118·54
880·0	6	32·05	54·15	85·43	109·43	129·66
1056·	5	35·08	60·15	94·89	121·54	144·02
1320·	4	40·40	68·29	107·73	137·99	163·51
1760·	3	47·48	80·25	126·61	162·17	192·16
2640·	2	59·47	100·53	158·59	203·14	240·70
5280·	1	88·13	148·97	235·02	301·04	356·70

See p. 208.

TABLE VIII.—For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.—For a full cylindrical pipe, divide the diameter by 4 to find the hydraulic mean depth.

Diameters of pipes 2½ inches to 5 inches. Falls per mile 1 inch to 12 feet.

Falls per mile in feet and inches, and the hydraulic inclinations.		"Hydraulic mean depths," or "mean radii," and velocities in inches per second.				
Falls.	Inclinations one in	$\frac{1}{8}$ inch.	$\frac{3}{8}$ inch.	$\frac{1}{2}$ inch.	1 inch.	1½ in. interpolated.
F. I.						
0 1	63360	·65	·73	·79	·85	·96
0 2	31680	1·02	1·13	1·23	1·33	1·49
0 3	21120	1·30	1·45	1·58	1·70	1·91
0 4	15840	1·54	1·71	1·87	2·01	2·26
0 5	12672	1·76	1·95	2·13	2·29	2·58
0 6	10560	1·95	2·17	2·36	2·55	2·86
0 7	9051	2·13	2·37	2·58	2·78	3·13
0 8	7920	2·30	2·55	2·78	3·00	3·37
0 9	7040	2·46	2·73	2·98	3·21	3·61
0 10	6336	2·61	2·90	3·16	3·40	3·83
0 11	5760	2·76	3·06	3·33	3·59	4·04
1 0	5280	2·89	3·21	3·50	3·77	4·24
1 3	4224	3·28	3·64	3·97	4·27	4·81
1 6	3520	3·63	4·03	4·39	4·73	5·32
1 9	3017	3·96	4·39	4·79	5·16	5·80
2 0	2640	4·26	4·73	5·16	5·55	6·25
2 3	Interpolated.	4·55	5·04	5·50	5·92	6·66
2 6	2112	4·83	5·35	5·84	6·29	7·07
2 9	Interpolated.	5·09	5·64	6·15	6·12	7·46
3 0	1760	5·34	5·92	6·46	6·96	7·83
3 3	Interpolated.	5·58	6·19	6·75	7·27	8·18
3 6	1508	5·82	6·46	7·04	7·59	8·53
3 9	Interpolated.	6·05	6·71	7·31	7·88	8·86
4 0	1320	6·27	6·95	7·58	8·17	9·19
4 6	Interpolated.	6·69	7·42	8·09	8·71	9·80
5 0	1056	7·10	7·88	8·59	9·25	10·41
5 6	Interpolated.	7·48	8·30	9·05	9·76	10·97
6 0	880	7·86	8·72	9·51	10·25	11·53
6 6	Interpolated.	8·22	9·12	9·94	10·71	12·05
7 0	754	8·57	9·51	10·37	11·17	12·57
7 6	Interpolated.	8·92	9·89	10·78	11·62	13·06
8 0	660	9·24	10·25	11·18	12·04	13·54
8 6	Interpolated.	9·55	10·60	11·56	12·45	14·01
9 0	587	9·87	10·95	11·94	12·86	14·47
9 6	Interpolated.	10·18	11·28	12·31	13·26	14·91
10 0	528	10·48	11·62	12·67	13·65	15·36
10 6	Interpolated.	10·77	11·95	13·03	14·03	15·78
11 0	480	11·06	12·27	13·38	14·41	16·21
11 6	Interpolated.	11·34	12·58	13·72	14·82	16·64
12 0	440	11·62	12·89	14·05	15·22	17·07

TABLE VIII.—For finding the Mean Velocity of Water flowing in Pipes, Drains, Streams, and Rivers.—For a full cylindrical pipe, divide the diameter by 4 to find the hydraulic mean depth.

Diameters of pipes $2\frac{1}{2}$ inches to 5 inches. Falls per mile 18 feet to 5280 feet.

Falls per mile in feet and inches, and the hydraulic inclinations.		"Hydraulic mean depths," or "mean radii," and velocities in inches per second.				
Falls.	Inclinations one in	$\frac{1}{8}$ inch.	$\frac{3}{8}$ inch.	$\frac{1}{2}$ inch.	1 inch.	$1\frac{1}{2}$ in. interpolated.
F.						
13·2	400	12·26	13·60	14·83	15·98	17·98
13·6	Interpolated.	12·49	13·86	15·11	16·28	18·31
14·1	375	12·72	14·11	15·39	16·58	18·65
14·6	Interpolated.	12·98	14·39	15·70	16·91	19·02
15·1	350	13·23	14·68	16·00	17·24	19·40
15·6	Interpolated.	13·52	14·99	16·35	17·62	19·81
16·2	325	13·80	15·31	16·79	17·99	20·23
17·6	300	14·45	16·02	17·48	18·83	21·18
19·2	275	15·19	16·85	18·37	19·79	22·26
21·1	250	16·04	17·80	19·40	20·91	23·52
23·5	225	17·05	18·91	20·62	22·21	24·99
26·4	200	18·25	20·24	22·07	23·78	26·75
30·2	175	19·71	21·87	23·85	25·69	28·90
35·2	150	21·57	23·92	26·09	28·11	31·62
37·7	140	22·45	24·91	27·16	29·26	32·92
42·2	125	23·99	26·62	29·03	31·27	35·18
48·	110	25·87	28·69	31·29	33·71	37·92
52·8	100	27·36	30·35	33·10	35·66	40·11
58·7	90	29·12	32·31	35·23	37·96	42·69
66·	80	31·23	34·64	37·78	40·70	45·79
75·4	70	33·82	37·51	40·91	44·07	49·58
88·0	60	37·08	41·13	44·86	48·33	54·36
105·6	50	41·37	45·78	50·04	53·91	60·65
117·3	45	44·08	48·89	53·32	57·44	64·62
132·	40	47·32	52·49	57·25	61·67	69·37
150·8	35	51·30	56·90	62·06	66·86	75·20
176·	30	56·32	62·47	68·13	73·40	82·56
211·2	25	62·90	69·77	76·09	81·97	92·21
264·	20	72·01	79·87	87·11	93·84	105·56
352·	15	85·68	95·05	103·66	111·67	125·61
528·	10	109·26	121·19	132·17	142·39	160·17
586·7	9	116·31	129·01	140·70	151·58	170·50
660·	8	124·68	138·30	150·83	162·49	182·78
754·8	7	134·84	149·57	163·12	175·73	197·67
880·	6	147·69	163·60	178·42	192·22	216·22
1056·	5	163·82	181·71	198·17	213·50	240·15
1320·	4	185·99	206·31	225·00	242·39	272·66
1760·	3	218·58	242·46	264·42	284·86	320·43
2640·	2	273·79	303·70	331·22	356·82	401·37
5280·	1	405·74	450·07	490·84	528·76	594·82

TABLE VIII.—For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.—For a full cylindrical pipe, divide the diameter by 4 to find the hydraulic mean depth. OPEN DRAINS AND PIPES.—Diameters of pipes 6 inches to 12 inches. Falls per mile 1 inch to 12 feet.

Falls per mile in feet and inches, and the hydraulic inclinations.		"Hydraulic mean depths," or "mean radii," and velocities in inches per second.				
Falls.	Inclinations one in	1½ inch.	1¾ in. interpolated.	2 inches.	2½ inches.	3 inches.
F. I.						
0 1	63360	1·07	1·15	1·24	1·40	1·55
0 2	31680	1·66	1·80	1·94	2·19	2·41
0 3	21120	2·12	2·30	2·48	2·80	3·08
0 4	15840	2·52	2·73	2·94	3·34	3·65
0 5	12672	2·86	3·11	3·35	3·77	4·16
0 6	10560	3·18	3·45	3·72	4·19	4·62
0 7	9051	3·47	3·77	4·06	4·58	5·04
0 8	7920	3·75	4·06	4·38	4·94	5·44
0 9	7040	4·01	4·34	4·68	5·28	5·81
0 10	6336	4·25	4·61	4·97	5·60	6·17
0 11	5760	4·49	4·86	5·24	5·91	6·51
1 0	5280	4·71	5·11	5·51	6·21	6·84
1 3	4224	5·34	5·79	6·24	7·08	7·75
1 6	3520	5·91	6·41	6·91	7·79	8·58
1 9	3017	6·44	6·99	7·53	8·49	9·35
2 0	2640	6·94	7·53	8·11	9·14	10·07
2 3	Interpolated.	7·40	8·03	8·65	9·74	10·74
2 6	2112	7·86	8·52	9·18	10·35	11·40
2 9	Interpolated.	8·28	8·98	9·67	10·90	12·01
3 0	1760	8·70	9·43	10·16	11·45	12·62
3 3	Interpolated.	9·09	9·85	10·62	11·97	13·19
3 6	1508	9·48	10·28	11·08	12·48	13·76
3 9	Interpolated.	9·84	10·67	11·50	12·96	14·29
4 0	1320	10·21	11·07	11·93	13·44	14·81
4 6	Interpolated.	10·89	11·80	12·72	14·34	15·80
5 0	1056	11·56	12·54	13·51	15·23	16·78
5 6	Interpolated.	12·18	13·21	14·24	16·04	17·68
6 0	880	12·80	13·88	14·96	16·86	18·58
6 6	Interpolated.	13·38	14·51	15·64	17·62	19·42
7 0	754	13·96	15·14	16·32	18·39	20·26
7 6	Interpolated.	14·51	15·73	16·95	19·10	21·05
8 0	660	15·05	16·32	17·58	19·82	21·84
8 6	Interpolated.	15·56	16·87	18·18	20·49	22·58
9 0	587	16·07	17·43	18·78	21·17	23·32
9 6	Interpolated.	16·57	17·97	19·36	21·82	24·04
10 0	528	17·06	18·50	19·94	22·47	24·76
10 6	Interpolated.	17·54	19·01	20·49	23·09	25·45
11 0	480	18·01	19·53	21·04	23·72	26·13
11 6	Interpolated.	18·47	20·02	21·57	24·32	26·79
12 0	440	18·92	20·51	22·11	24·91	27·45

TABLE VIII.—For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.—For a full cylindrical pipe, divide the diameter by 4 to find the hydraulic mean depth.

Diameters of pipes 6 inches to 14 inches. Falls per mile 13 feet to 5280 feet.

Falls per mile in feet, and the hydraulic inclinations.		"Hydraulic mean depths," or "mean radii," and velocities in inches per second.				
Falls.	Inclinations, one in	1½ inches	2 inches	2½ inches	3 inches	3½ inches
F.						
13·2	400	19·97	23·34	26·30	28·98	31·44
13·6		20·34	23·77	26·79	29·52	32·03
14·1	375	20·72	24·21	27·28	30·06	32·62
14·6		21·13	24·69	27·83	30·67	33·27
15·1	350	21·55	25·18	28·38	31·27	33·93
15·6		22·01	25·72	28·99	31·94	34·66
16·2	325	22·48	26·27	29·60	32·62	35·39
17·6	300	23·53	27·50	30·99	34·15	37·05
19·2	275	24·74	28·90	32·57	35·89	38·94
21·1	250	26·13	30·53	34·41	37·91	41·14
23·5	225	27·76	32·44	36·56	40·28	43·71
26·4	200	29·72	34·72	39·13	43·12	46·79
30·2	175	32·11	37·52	42·28	46·59	50·55
35·2	150	35·13	41·04	46·26	50·97	55·30
37·7	140	36·57	42·73	48·16	53·07	57·58
42·2	125	39·08	45·66	51·46	56·71	61·53
48·	110	42·13	49·23	55·48	61·13	66·33
52·8	100	44·57	52·07	58·69	64·67	70·17
58·7	90	47·43	55·42	62·46	68·83	74·68
66·	80	50·87	59·44	66·99	73·81	80·09
75·4	70	55·08	64·36	72·50	79·92	86·72
88·	60	60·39	70·57	79·53	87·63	95·09
105·6	50	67·38	78·73	88·73	97·77	106·03
117·8	45	71·79	83·88	94·54	104·17	113·03
132·	40	77·07	90·06	101·50	118·84	121·35
150·8	35	83·55	97·63	110·03	121·24	131·55
176·	30	91·72	107·18	120·79	133·10	144·41
211·2	25	102·44	119·70	134·90	148·65	161·29
264·	20	117·28	137·03	154·44	170·18	184·65
352·	15	139·56	163·06	183·78	202·50	219·72
528·	10	177·95	207·92	234·33	258·21	280·16
586·7	9	189·43	221·34	249·45	274·87	298·24
660·	8	203·07	237·28	267·42	294·67	319·72
754·8	7	219·61	256·61	289·20	318·67	345·77
880·	6	240·22	281·36	316·33	348·57	378·20
1056·	5	266·81	311·75	351·35	387·15	420·07
1320·	4	302·92	353·95	398·91	439·55	476·93
1760·	3	356·00	415·96	468·80	516·57	560·49
2640·	2	445·98	521·04	587·22	647·06	702·08
5280·	1	660·84	772·16	870·23	958·91	1040·44

TABLE VIII.—For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.—For a full cylindrical pipe, divide the diameter by 4 to find the hydraulic mean depth.

Diameters of pipes 14 inches to 22 inches. Falls per mile 1 inch to 12 feet.

Falls per mile in feet and inches, and the hydraulic inclinations.		"Hydraulic mean depths," or "mean radii," and velocities in inches per second.				
Falls.	Inclinations, one in	3½ inches	4 inches.	4½ inches	5 inches.	5½ inches
F. I.						
0 1	63360	1·68	1·80	1·91	2·02	2·13
0 2	31680	2·61	2·81	2·98	3·15	3·32
0 3	21120	3·34	3·59	3·82	4·03	4·24
0 4	15840	3·96	4·25	4·52	4·78	5·02
0 5	12672	4·51	4·84	5·15	5·44	5·72
0 6	10560	5·01	5·37	5·72	6·04	6·35
0 7	9051	5·47	5·87	6·24	6·60	6·94
0 8	7920	5·90	6·33	6·74	7·12	7·48
0 9	7040	6·31	6·77	7·20	7·61	8·00
0 10	6336	6·70	7·18	7·64	8·08	8·49
0 11	5760	7·06	7·58	8·06	8·52	8·96
1 0	5280	7·42	7·96	8·47	8·95	9·41
1 3	4224	8·41	9·02	9·60	10·14	10·66
1 6	3520	9·31	9·99	10·63	11·23	11·80
1 9	3017	10·15	10·89	11·58	12·24	12·86
2 0	2640	10·93	11·73	12·47	13·18	13·86
2 3	Interpolated.	11·65	12·50	13·30	14·05	14·77
2 6	2112	12·37	13·28	14·12	14·93	15·69
2 9	Interpolated.	13·03	13·68	14·88	15·72	16·53
3 0	1760	13·69	14·69	15·63	16·52	17·36
3 3	Interpolated.	14·31	15·35	16·33	17·26	18·14
3 6	1508	14·92	16·01	17·03	18·00	18·92
3 9	Interpolated.	15·50	16·63	17·69	18·70	19·65
4 0	1320	16·07	17·25	18·35	19·39	20·38
4 6	Interpolated.	17·14	18·39	19·56	20·68	21·73
5 0	1056	18·21	19·53	20·78	21·96	23·08
5 6	Interpolated.	19·18	20·58	21·90	23·14	24·32
6 0	880	20·16	21·63	23·01	24·32	25·56
6 6	Interpolated.	21·07	22·61	24·05	25·42	26·72
7 0	754	21·98	23·59	25·09	26·52	27·87
7 6	Interpolated.	22·84	24·50	26·07	27·55	28·96
8 0	660	23·69	25·42	27·04	28·58	30·04
8 6	Interpolated.	24·50	26·29	27·97	29·55	31·06
9 0	587	25·31	27·54	28·89	30·53	32·09
9 6	Interpolated.	26·09	27·99	29·78	31·47	33·08
10 0	528	26·87	28·83	30·67	32·41	34·06
10 6	Interpolated.	27·61	29·62	31·52	33·31	35·01
11 0	480	28·35	30·42	32·37	34·20	35·95
11 6	Interpolated.	29·07	31·19	33·18	35·07	36·86
12 0	440	29·79	31·96	34·00	35·93	37·77

TABLE VIII.—For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.—For a full cylindrical pipe, divide the diameter by 4 to find the hydraulic mean depth.

Diameters of pipes 16 inches to 2 feet. Falls per mile 13 feet to 5280 feet.

Falls per mile in feet and the hydraulic inclinations.		"Hydraulic mean depths," or "mean radii," and velocities in inches per second.				
Falls.	Inclination, one in	4 inches.	4½ inches.	5 inches.	5½ inches.	6 inches.
F.						
13·2	400	33·74	35·89	37·93	39·87	41·72
13·6	Interpolated.	34·37	36·56	38·64	40·61	42·50
14·1	375	35·00	37·23	39·35	41·36	43·28
14·6	Interpolated.	35·70	37·98	40·14	42·19	44·15
15·1	350	36·40	38·73	40·92	43·02	45·01
15·6	Interpolated.	37·19	39·56	41·81	43·94	45·99
16·2	325	37·97	40·40	42·69	44·87	46·96
17·6	300	39·75	42·29	44·69	46·97	49·16
19·2	275	41·78	44·45	46·97	49·38	51·67
21·1	250	44·14	46·95	49·62	52·16	54·58
23·5	225	46·90	49·90	52·72	55·42	58·00
26·4	200	50·20	53·41	56·44	59·32	62·08
30·2	175	54·24	57·71	60·98	64·10	67·07
35·2	150	59·34	63·13	66·71	70·12	73·37
37·7	140	61·78	65·72	69·45	73·00	76·39
42·2	125	66·02	70·23	74·22	78·01	81·64
48·	110	71·17	75·72	80·01	84·10	88·00
52·8	100	75·29	80·09	84·64	88·97	93·10
58·7	90	80·13	85·25	90·08	94·69	99·09
66·	80	85·93	91·42	96·61	101·54	106·26
75·4	70	93·04	98·98	104·60	109·95	115·05
88·	60	102·02	108·54	114·70	120·56	126·16
105·6	50	113·82	121·09	127·96	134·50	140·74
117·3	45	121·27	129·01	136·34	143·30	149·96
132·	40	130·20	138·51	146·38	153·86	161·00
150·8	35	141·14	150·16	158·68	166·79	174·53
176·	30	154·95	164·84	174·20	183·10	191·61
211·2	25	173·05	184·10	194·56	204·50	214·00
264·	20	198·12	210·77	222·73	234·11	244·98
352·	15	235·75	250·80	265·04	278·58	291·52
528·	10	300·60	319·80	337·95	355·22	371·71
586·7	9	320·00	340·43	359·76	378·14	395·70
660·	8	343·04	359·65	385·67	405·37	424·20
754·3	7	370·99	394·68	417·08	438·39	458·76
880·	6	405·79	431·70	456·21	479·52	501·79
1056·	5	450·71	479·49	506·71	532·60	557·34
1320·	4	511·72	544·39	575·30	604·69	632·78
1760·	3	601·38	639·78	676·10	710·64	743·65
2640·	2	753·29	801·39	846·89	890·16	931·50
5280·	1	1116·35	1187·62	1255·04	1319·17	1380·44

TABLE VIII.—For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.—The hydraulic mean depth is found for all channels, by dividing the wetted perimeter into the area.
Hydraulic mean depths 6 inches to 10 inches. Falls per mile 1 inch to 12 feet.

Falls per mile in feet and inches, and the hydraulic inclinations.		"Hydraulic mean depths," or "mean radii," and velocities in inches per second.				
Falls.	Inclinations, one in	6 inches.	7 inches.	8 inches.	9 inches.	10 inches.
F. I.						
0 1	63360	2·23	2·41	2·58	2·75	2·90
0 2	31680	3·47	3·76	4·03	4·28	4·52
0 3	21120	4·43	4·80	5·15	5·47	5·78
0 4	15840	5·26	5·69	6·10	6·49	6·85
0 5	12672	5·98	6·48	6·95	7·39	7·80
0 6	10560	6·65	7·20	7·72	8·20	8·66
0 7	9051	7·26	7·86	8·43	8·96	9·46
0 8	7920	7·83	8·48	9·09	9·67	10·21
0 9	7040	8·37	9·07	9·72	10·33	10·91
0 10	6336	8·88	9·63	10·32	10·97	11·58
0 11	5760	9·37	10·16	10·89	11·57	12·22
1 0	5280	9·84	10·67	11·43	12·15	12·83
1 3	4224	11·16	12·09	12·95	13·77	14·54
1 6	3520	12·35	13·38	14·34	15·25	16·10
1 9	3017	13·46	14·58	15·63	16·61	17·54
2 0	2640	14·50	15·71	16·84	17·90	18·90
2 3	Interpolated.	15·45	16·75	18·24	19·08	20·15
2 6	2112	16·42	17·79	19·64	20·26	21·40
2 9	Interpolated.	17·29	18·74	20·37	21·34	22·54
3 0	1760	18·17	19·69	21·10	22·42	23·68
3 3	Interpolated.	18·99	20·57	22·05	23·43	24·75
3 6	1508	19·80	21·46	23·00	24·44	25·81
3 9	Interpolated.	20·56	22·28	23·88	25·38	26·80
4 0	1320	21·33	23·11	24·77	26·32	27·80
4 6	Interpolated	22·74	24·64	26·41	28·07	29·64
5 0	1056	24·16	26·17	28·05	29·81	31·48
5 6	Interpolated.	25·45	27·58	29·56	31·42	33·17
6 0	880	26·75	28·98	31·06	33·02	34·86
6 6	Interpolated.	27·96	30·29	32·47	34·51	36·44
7 0	754	29·17	31·60	33·87	36·00	38·02
7 6	Interpolated.	30·30	32·83	35·19	37·40	39·50
8 0	660	31·43	34·06	36·50	38·80	40·97
8 6	Interpolated.	32·51	35·22	37·75	40·12	42·37
9 0	587	33·58	36·39	38·99	41·45	43·77
9 6	Interpolated.	34·61	37·50	40·20	42·72	45·11
10 0	528	35·65	38·63	41·40	44·00	46·46
10 6	Interpolated.	36·63	39·69	42·54	45·22	47·75
11 0	480	37·62	40·76	43·69	46·44	49·03
11 6	Interpolated.	38·57	41·79	44·79	47·61	50·27
12 0	440	39·52	42·82	45·90	48·78	51·51

TABLE VIII.—*For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.*—The hydraulic mean depth is found for all channels by dividing the wetted perimeter into the area.
Hydraulic mean depths 11 inches to 21 inches. Falls per mile 1 inch to 12 feet.

Falls per mile in feet and inches, and the hydraulic inclinations.		"Hydraulic mean depths," or "mean radii," and velocities in inches per second.				
Falls.	Inclinations, one in	11 inches	12 inches.	15 inches.	18 inches.	21 inches.
F. I.						
0 1	63360	3·05	3·19	3·57	3·92	4·25
0 2	31680	4·75	4·97	5·57	6·12	6·62
0 3	21120	6·07	6·35	7·12	7·82	8·46
0 4	15840	7·19	7·53	8·44	9·27	10·03
0 5	12672	8·19	8·57	9·61	10·55	11·42
0 6	10560	9·10	9·52	10·67	11·72	12·68
0 7	9051	9·94	10·39	11·66	12·80	13·85
0 8	7920	10·72	11·21	12·57	13·81	14·94
0 9	7041	11·46	11·99	13·44	14·76	15·97
0 10	6336	12·16	12·72	14·27	15·68	16·95
0 11	5760	12·83	13·42	15·05	16·53	17·88
1 0	5280	13·48	14·09	15·81	17·36	18·78
1 3	4224	15·27	15·97	17·91	19·67	21·28
1 6	3520	16·91	17·68	19·83	21·78	23·56
1 9	3017	18·23	19·27	21·62	23·73	25·68
2 0	2640	19·85	20·76	23·28	25·63	27·66
2 3	Interpolated.	21·16	22·13	24·82	27·29	29·49
2 6	2112	22·48	23·51	26·36	28·95	31·32
2 9	Interpolated.	23·68	24·76	27·77	30·49	32·99
3 0	1760	24·88	26·02	29·18	32·04	34·67
3 3	Interpolated.	25·99	27·18	30·47	33·48	36·22
3 6	1508	27·11	28·35	31·77	34·92	37·78
3 9	Interpolated.	28·15	29·45	33·01	36·26	39·23
4 0	1320	29·20	30·54	34·25	37·60	40·69
4 6	Interpolated.	31·13	32·56	36·52	40·10	43·39
5 0	1056	33·07	34·59	38·79	42·59	46·09
5 6	Interpolated.	34·85	36·44	40·87	44·88	48·56
6 0	880	36·62	38·30	42·95	47·16	51·03
6 6	Interpolated.	38·28	40·03	44·90	49·30	53·34
7 0	754	39·93	41·76	46·84	51·43	55·65
7 6	Interpolated.	41·48	43·39	48·66	53·43	57·81
8 0	660	43·04	45·01	50·48	55·42	59·97
8 6	Interpolated.	44·50	46·54	52·20	57·32	62·02
9 0	587	45·97	48·08	53·92	59·21	64·06
9 6	Interpolated.	47·39	49·56	55·58	61·03	66·04
10 0	528	48·80	51·04	57·24	62·85	68·01
10 6	Interpolated.	50·15	52·45	58·83	64·59	69·89
11 0	480	51·51	53·87	60·41	66·33	71·78
11 6	Interpolated.	52·81	55·23	61·94	68·01	73·59
12 0	440	54·11	56·59	63·47	69·68	75·40

TABLE VIII.—For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.—The hydraulic mean depth is found for all channels by dividing the wetted perimeter into the area.
Hydraulic mean depths 24 inches to 4 feet. Falls per mile 1 inch to 12 feet.

Falls per mile in feet and inches, and the hydraulic inclinations.		"Hydraulic mean depths," or "mean radii," and velocities in inches per second.				
Falls.	Inclinations, one in	24 inch.	30 inches.	36 inches.	42 inches.	48 inches.
F. I.						
0 1	63360	4·54	5·09	5·59	6·04	6·47
0 2	31680	7·09	7·94	8·71	9·42	10·08
0 3	21120	9·06	10·15	11·14	12·04	12·89
0 4	15840	10·73	12·03	13·20	14·27	15·27
0 5	12672	12·22	13·69	15·03	16·25	17·39
0 6	10560	13·57	15·21	16·69	18·05	19·31
0 7	9051	14·83	16·61	18·23	19·71	21·09
0 8	7920	15·99	17·92	19·66	21·27	22·76
0 9	7041	17·10	19·16	21·02	22·73	24·33
0 10	6336	18·15	20·33	22·31	24·13	25·82
0 11	5760	19·15	21·45	23·54	25·46	27·24
1 0	5280	20·11	22·53	24·72	26·73	28·61
1 3	4224	22·78	25·53	28·01	30·29	32·42
1 6	3520	25·23	28·27	31·02	33·54	35·90
1 9	3017	27·49	30·81	33·80	36·55	39·12
2 0	2640	29·62	33·18	36·41	39·38	42·14
2 3	Interpolated.	31·57	35·38	38·82	41·98	44·92
2 6	2112	33·53	37·57	41·22	44·58	47·71
2 9	Interpolated.	35·32	39·58	43·43	46·96	50·26
3 0	1760	37·11	41·58	45·63	49·34	52·81
3 3	Interpolated.	38·78	43·45	47·68	51·56	55·18
3 6	1508	40·45	45·32	49·73	53·78	57·55
3 9	Interpolated.	42·00	47·07	51·64	55·85	59·77
4 0	1320	43·56	48·81	53·56	57·92	61·98
4 6	Interpolated.	46·45	52·05	57·11	61·76	66·09
5 0	1056	49·34	55·28	60·66	65·60	70·20
5 6	Interpolated.	51·99	58·25	63·91	69·12	73·97
6 0	880	54·63	61·22	67·17	72·64	77·74*
6 6	Interpolated.	57·11	63·99	70·21	75·93*	81·25
7 0	754	59·58	66·76	73·25	79·21	84·77
7 6	Interpolated.	61·89	69·35	76·09*	82·29	88·06
8 0	660	64·21	71·94	78·94	85·37	91·35
8 6	Interpolated.	66·40	74·40	81·63	88·26	94·47
9 0	587	68·59	76·85*	84·32	91·19	97·59
9 6	Interpolated.	70·60	79·22	86·92	94·00	100·59
10 0	528	72·81	81·58	89·52	96·81	103·60
10 6	Interpolated.	74·83	83·84	91·99	99·49	106·47
11 0	480	76·84*	86·10	94·47	102·17	109·33
11 6	Interpolated.	78·78	88·28	96·86	104·75	112·10
12 0	440	80·72	90·45	99·25	107·33	114·86

TABLE VIII.—*For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.*—The hydraulic mean depth is found for all channels by dividing the wetted perimeter into the area.
Hydraulic mean depths 4 feet 6 inches to 7 feet. Falls per mile 1 inch to 12 feet.

Falls per mile in feet and inches, and the hydraulic inclinations.		"Hydraulic mean depths," or "mean radii," and velocity in inches per second.				
Falls.	Inclinations, one in	54 inch.	60 inches.	66 inches.	72 inches.	84 inches.
F. I.						
0 1	63360	6·86	7·24	7·60	7·94	8·58
0 2	31680	10·70	11·29	11·85	12·38	13·39
0 3	21120	13·68	14·62	15·14	15·83	17·11
0 4	15840	16·21	17·10	17·95	18·76	20·28
0 5	12672	18·46	19·47	20·43	21·35	23·13
0 6	10560	20·50	21·63	22·70	23·72	25·64
0 7	9051	22·39	23·62	24·79	25·90	28·00
0 8	7920	24·16	25·48	26·74	27·95	30·21
0 9	7041	25·83	27·24	28·59	29·88	32·30
0 10	6336	27·41	28·91	30·34	31·71	34·28
0 11	5760	28·92	30·51	32·01	33·46	36·17
1 0	5280	30·37	32·03	33·62	35·13	37·98
1 3	4224	34·41	36·30	38·10	39·81	43·04
1 6	3520	38·10	40·19	42·18	44·08	47·65
1 9	3017	41·52	43·80	45·97	48·04	51·93
2 0	2640	44·73	47·18	49·52	51·75	55·94
2 3	Interpolated.	47·69	50·30	52·79	55·17	59·64
2 6	2112	50·65	53·42	56·07	58·59	63·34
2 9	Interpolated.	53·35	56·28	59·06	61·72	66·72
3 0	1760	56·06	59·13	62·05	64·85	70·10
3 3	Interpolated.	58·57	61·79	64·84	67·76	73·25
3 6	1508	61·09	64·44	67·63	70·67	76·40*
3 9	Interpolated.	63·44	66·92	70·23	73·39	79·35
4 0	1320	65·80	69·41	72·84	76·11*	82·29
4 6	Interpolated.	70·16	74·01	77·67*	81·16	87·74
5 0	1056	74·52	78·61*	82·50	86·21	93·20
5 6	Interpolated.	78·52*	82·83	86·92	90·84	98·20
6 0	880	82·52	87·05	91·35	95·46	103·20
6 6	Interpolated.	86·25	90·98	95·58	99·78	107·87
7 0	754	89·99	94·92	99·62	104·10	112·54
7 6	Interpolated.	93·48	98·61	103·48	108·14	116·91
8 0	660	96·98	102·30	107·35	112·19	121·23
8 6	Interpolated.	100·29	105·79	111·02	116·01	125·42
9 0	587	103·59	109·27	114·68	119·84	129·56
9 6	Interpolated.	106·78	112·64	118·21	123·58	133·55
10 0	528	109·97	116·01	121·74	127·22	137·54
10 6	Interpolated.	113·02	119·22	125·11	130·74	141·34
11 0	480	116·06	122·43	128·48	134·27	145·15
11 6	Interpolated.	119·00	125·52	131·73	137·66	148·82
12 0	440	121·93	128·61	134·97	141·05	152·49

TABLE VIII.—For finding the Mean Velocities of Water flowing in Pipes, Drains, Streams, and Rivers.—The hydraulic mean depth is found for all channels by dividing the wetted perimeter into the area.
Hydraulic mean depths 8 feet to 12 feet. Falls per mile 1 inch to 12 feet.

Falls per mile in feet and inches, and the hydraulic inclinations.		"Hydraulic mean depths," or "mean radii," and velocities in inches per second.				
Falls.	Inclinations, one in	96 inch.	108 inches.	120 inches.	132 inches.	144 inches.
F. I.						
0 1	63860	9·18	9·75	10·28	10·79	11·27
0 2	31680	14·32	15·20	16·03	16·82	17·57
0 3	21120	18·30	19·43	20·49	21·50	22·46
0 4	15840	21·69	23·02	24·28	25·47	26·62
0 5	12672	24·70	26·21	27·64	29·00	30·31
0 6	10560	27·43	29·11	30·70	32·21	33·66
0 7	9051	29·96	31·80	33·53	35·18	36·76
0 8	7920	32·32	34·30	36·18	37·96	39·66
0 9	7041	34·55	36·67	38·67	40·58	42·40
0 10	6336	36·67	38·92	41·04	43·07	45·00
0 11	5760	38·69	41·06	43·31	45·44	47·48
1 0	5280	40·63	43·12	45·48	47·72	49·86
1 3	4224	46·04	48·87	51·54	54·07	56·50
1 6	3520	50·98	54·11	57·06	59·87	62·56
1 9	3017	55·60	58·96	62·18	65·25	68·17
2 0	2640	59·85	63·52	66·98	70·28	73·44*
2 3	Interpolated.	63·80	67·72	71·41	74·93*	78·29
2 6	2112	67·76	71·91	75·84*	79·58	83·15
2 9	Interpolated.	71·38	75·75*	79·89	83·83	87·59
3 0	1760	75·00*	79·59	83·94	88·08	92·03
3 3	Interpolated.	78·37	83·17	87·71	92·03	96·16
3 6	1508	81·74	86·75	91·48	95·99	100·30
3 9	Interpolated.	84·88	90·09	95·01	99·69	104·16
4 0	1320	88·03	93·43	98·53	103·38	108·02
4 6	Interpolated.	93·87	99·62	105·06	110·24	115·18
5 0	1056	99·70	105·82	111·59	117·09	122·34
5 6	Interpolated.	105·06	111·49	117·58	123·38	128·91
6 0	880	110·41	117·17	123·57	129·66	135·48
6 6	Interpolated.	115·40	122·47	129·16	135·53	141·61
7 0	754	120·40	127·76	134·75	141·39	147·73
7 6	Interpolated.	125·07	132·74	139·99	146·88	153·47
8 0	660	129·75	137·70	145·22	152·38	159·21
8 6	Interpolated.	134·18	142·40	150·18	157·57	164·64
9 0	587	138·60	147·10	155·13	162·77	170·07
9 6	Interpolated.	142·87	151·63	159·91	167·78	175·31
10 0	528	147·14	156·16	164·68	172·80	180·55
10 6	Interpolated.	151·21	160·48	169·24	177·58	185·55
11 0	480	155·29	164·80	173·80	182·36	190·54
11 6	Interpolated.	159·21	168·97	178·19	186·97	195·36
12 0	440	163·13	173·13	182·59	191·58	200·17

TABLE IX.—For finding the Discharge in Cubic Feet per Minute, when the Diameter of a Pipe, or Orifice, and the Velocity of Discharge are known; and vice versa.

Diameters of pipes in inches.	Discharge in cubic feet per minute, for different velocities.				
	Velocity of 100 inches per second.	Velocity of 200 inches per second.	Velocity of 300 inches per second.	Velocity of 400 inches per second.	Velocity of 500 inches per second.
$\frac{1}{4}$	170442	3409	5113	6818	8522
$\frac{3}{8}$	68177	13635	20453	27271	34089
$\frac{1}{2}$	153398	30679	46019	61359	76699
1	2727077	54541	81812	109083	136354
$1\frac{1}{4}$	426106	85221	127832	170442	213053
$1\frac{1}{2}$	613593	122718	184080	245437	306797
$1\frac{3}{4}$	835167	167033	250550	334067	417584
2	1090831	211817	327249	436332	545415
$2\frac{1}{4}$	1380583	276117	414175	552233	690291
$2\frac{1}{2}$	1704423	340885	511327	681769	852212
$2\frac{3}{4}$	2062352	412470	618706	824941	1031176
3	2454869	490874	736311	981748	1227185
$3\frac{1}{4}$	2880475	576095	864143	1152190	1440238
$3\frac{1}{2}$	3340669	668134	1002201	1336268	1670335
$3\frac{3}{4}$	3834952	766990	1150486	1533981	1917476
4	4363323	872665	1308997	1745329	2181662
$4\frac{1}{4}$	4925783	985157	1477735	1970813	2462392
$4\frac{1}{2}$	5522331	1104466	1656699	2208932	2761166
$4\frac{3}{4}$	6152968	1230594	1845890	2461187	3076484
5	6817692	1363539	2045308	2727077	3408846
$5\frac{1}{4}$	7516506	1503301	2254952	3006603	3758253
$5\frac{1}{2}$	8249408	1649882	2474822	3299763	4124704
$5\frac{3}{4}$	9016399	1803280	2704920	3606560	4508200
6	9817478	1963495	2945243	3926991	4908739
$6\frac{1}{4}$	10652645	2130529	3195794	4261058	5326323
$6\frac{1}{2}$	1152190	2304380	3456570	4608760	5760950
$6\frac{3}{4}$	12425245	2485049	3727574	4970098	6212623
7	1336268	2672536	4008804	5345072	6681340
$7\frac{1}{4}$	14334199	2866840	4300260	5733630	7167100
$7\frac{1}{2}$	15339809	3067962	4601943	6135924	7669905
$7\frac{3}{4}$	16379507	3275901	4918852	6551803	8189753
8	17453293	3490659	5235988	6981317	8726647
$8\frac{1}{4}$	19703132	3940628	5910940	7881253	9851566
9	22089325	4417865	6626798	8835730	11044663
$9\frac{1}{4}$	24611871	4922374	7383561	9844784	12305936
10	27270771	5454154	8181231	10908308	13635386
$10\frac{1}{4}$	30066025	6013205	9019808	12026410	15033013
11	32997633	6599527	9899290	13199053	16498817
$11\frac{1}{4}$	36065595	7213119	10819679	14426238	18032798
12	39269910	7853982	11780973	15707964	19634955

TABLE IX.—For finding the Discharge in Cubic Feet per Minute, when the Diameter of a Pipe, or Orifice, and the Velocity of Discharge are known; and vice versa.

Discharge in cubic feet per minute, for different velocities.					Diameter of pipes in inches.
Velocity of 600 inches per second.	Velocity of 700 inches per second.	Velocity of 800 inches per second.	Velocity of 900 inches per second.	Velocity in 1000 inches per second.	
1·0227	1·1931	1·3635	1·5340	1·7044	$\frac{1}{4}$
4·0906	4·7724	5·4542	6·1359	6·8177	$\frac{1}{2}$
9·2039	10·7379	12·2718	13·8058	15·3398	$\frac{3}{4}$
16·3625	19·0895	21·8166	24·5437	27·2708	1
25·5664	29·8274	34·0885	38·3495	42·6106	$1\frac{1}{4}$
36·8155	42·9515	49·0874	55·2234	61·3593	$1\frac{1}{2}$
50·1100	58·4617	66·8134	75·1650	83·5167	$1\frac{3}{4}$
65·4499	76·3582	87·2665	98·1748	109·0831	2
82·8350	96·6408	110·4466	124·2525	138·0583	$2\frac{1}{4}$
102·2654	119·3096	136·3538	153·3981	170·4423	$2\frac{1}{2}$
123·7411	144·3646	164·9882	185·6117	206·2352	$2\frac{3}{4}$
147·2621	171·8059	196·3496	220·8933	245·4369	3
172·8235	201·6333	230·4380	259·2428	288·0475	$3\frac{1}{4}$
200·4401	233·8468	267·2535	300·6602	334·0669	$3\frac{1}{2}$
230·0971	268·4467	306·7962	345·1457	383·4952	$3\frac{3}{4}$
261·7994	305·4326	349·0659	392·6991	436·3323	4
295·5470	344·8048	394·0626	443·3205	492·5783	$4\frac{1}{4}$
331·3399	386·5632	441·7865	497·0098	552·2331	$4\frac{1}{2}$
369·1781	430·7077	492·2374	553·7671	615·2968	$4\frac{3}{4}$
409·0615	477·2384	545·4154	613·5923	681·7692	5
450·9904	526·1554	601·3205	676·4855	751·6506	$5\frac{1}{4}$
494·9645	577·4586	659·9526	742·4467	824·9408	$5\frac{1}{2}$
540·9839	631·1479	721·3119	811·4759	901·6399	$5\frac{3}{4}$
589·0486	687·2235	785·3982	883·5730	981·7478	6
639·1587	745·6852	852·2116	958·7381	1065·2645	$6\frac{1}{4}$
691·3141	806·5330	921·7520	1036·9710	1152·1900	$6\frac{1}{2}$
745·5147	869·7672	994·0196	1118·2721	1242·5245	$6\frac{3}{4}$
801·7608	935·3876	1069·0144	1202·6412	1336·2680	7
860·0519	1003·3939	1146·7359	1290·0779	1433·4199	$7\frac{1}{4}$
920·3885	1073·7866	1227·1847	1380·5828	1533·9809	$7\frac{1}{2}$
982·7704	1146·5655	1310·3605	1474·1556	1637·9507	$7\frac{3}{4}$
1047·1976	1221·7305	1396·2634	1570·7964	1745·3293	8
1182·1879	1379·2192	1576·2506	1773·2819	1970·3132	$8\frac{1}{2}$
1325·3595	1546·2528	1767·1460	1988·0393	2208·9325	9
1476·7123	1722·8310	1968·9497	2215·0684	2461·1871	$9\frac{1}{2}$
1636·2463	1908·9540	2181·6617	2454·3694	2727·0771	10
1803·9615	2104·6218	2405·2820	2705·9423	3006·6025	$10\frac{1}{2}$
1979·8580	2309·8343	2639·8106	2969·7870	3299·7633	11
2163·9357	2524·5917	2885·2476	3245·9936	3606·5595	$11\frac{1}{2}$
2356·1946	2748·8937	3141·5928	3534·2919	3926·9910	12

TABLE X.—For finding the depths of Weirs of different lengths, the quantity discharged over each being supposed constant. See pages 289 and 290.

Ratios of lengths.	Coefficients.	Ratios of lengths.	Coefficients.	Ratios of lengths.	Coefficients.	Ratios of lengths.	Coefficients.
·01	·0464	·405	·5474	·605	·7153	·805	·8654
·02	·0737	·410	·5519	·610	·7193	·810	·8689
·03	·0965	·415	·5564	·615	·7232	·815	·8725
·04	·1170	·420	·5608	·620	·7271	·820	·8761
·05	·1357	·425	·5653	·625	·7310	·825	·8796
·06	·1533	·430	·5697	·630	·7349	·830	·8832
·07	·1699	·435	·5741	·635	·7388	·835	·8867
·08	·1857	·440	·5785	·640	·7427	·840	·8903
·09	·2008	·445	·5829	·645	·7465	·845	·8938
·10	·2154	·450	·5872	·650	·7504	·850	·8973
·11	·2296	·455	·5916	·655	·7542	·855	·9008
·12	·2433	·460	·5959	·660	·7580	·860	·9043
·13	·2566	·465	·6002	·665	·7619	·865	·9078
·14	·2696	·470	·6045	·670	·7657	·870	·9113
·15	·2823	·475	·6088	·675	·7695	·875	·9148
·16	·2947	·480	·6130	·680	·7733	·880	·9183
·17	·3069	·485	·6173	·685	·7771	·885	·9218
·18	·3188	·490	·6215	·690	·7808	·890	·9253
·19	·3305	·495	·6258	·695	·7846	·895	·9287
·20	·3420	·500	·6300	·700	·7884	·900	·9322
·21	·3533	·505	·6342	·705	·7921	·905	·9356
·22	·3644	·510	·6383	·710	·7959	·910	·9391
·23	·3754	·515	·6425	·715	·7996	·915	·9425
·24	·3862	·520	·6466	·720	·8033	·920	·9459
·25	·3969	·525	·6508	·725	·8070	·925	·9494
·26	·4074	·530	·6549	·730	·8107	·930	·9528
·27	·4177	·535	·6590	·735	·8144	·935	·9562
·28	·4280	·540	·6631	·740	·8181	·940	·9596
·29	·4381	·545	·6672	·745	·8218	·945	·9630
·30	·4481	·550	·6713	·750	·8255	·950	·9664
·31	·4580	·555	·6754	·755	·8291	·955	·9698
·32	·4678	·560	·6794	·760	·8328	·960	·9732
·33	·4775	·565	·6834	·765	·8365	·965	·9766
·34	·4871	·570	·6875	·770	·8401	·970	·9799
·35	·4966	·575	·6915	·775	·8437	·975	·9833
·36	·5061	·580	·6955	·780	·8474	·980	·9866
·37	·5154	·585	·6995	·785	·8510	·985	·9900
·38	·5246	·590	·7035	·790	·8546	·990	·9933
·39	·5338	·595	·7074	·795	·8582	·995	·9967
·40	·5429	·600	·7114	·800	·8618	1·000	1·0000

TABLE XI.—Mean relative Dimensions of equally Discharging Trapezoidal Channels, with Side Slopes varying from 0 to 1, up to 2 to 1.—Half sum of the top and bottom is the mean width. The ratio of the slope, multiplied by the depth, subtracted from the mean width, will give the bottom; and if added, will give the top. TABLE XII. gives the discharge in cubic feet per minute from the primary channel, 70 wide, and the corresponding depths taken in feet. For lesser or greater channels and discharges, see Rules, pp. 243 to 251, and 267 to 271.

The mean widths are given in the top horizontal line, and the corresponding depths in the other horizontal lines. They may be taken in inches, feet, yards, fathoms, or any other measures, whatever.									
70	60	50	40	35	30	25	20	15	10
125	13	15	17	20	23	26	29	35	48
25	27	30	35	40	45	52	58	71	98
375	41	46	54	60	67	76	88	109	151
5	55	62	73	80	89	102	119	148	204*
625	68	78	91	100	112	129	150	188	262
75	82	94	110	120	135	156	182	228	322*
875	96	110	129	141	158	183	214	269	386
1	110	126	148	162	181	210	246	311	450
1125	124	142	167	183	204	237	279	354	519*
125	139	158	186	204	228	265	312	398	589
1375	153	174	205	225	251	292	346	443	660
15	167	190	224	246	275	320	380	488	731
1625	181	206	243	267	299	347	415	534	808
175	195	222	262	288	323	375	450	580	886
1875	209	238	281	309	347	403	486	629	968
2	223	254	300	331	372	432	522	678	1050
2125	237	270	319	352	396	461	558	729	1137
225	251	286	338	373	421	491	595	781*	1225
2375	265	302	357	394	445	520	631	832	1312
25	279	318	376	416	470	550	668	884	1400
2625	293	334	395	438	495	579	706	938	1492
275	307	351	415	460	521	609	745	993	1584
2875	321	367	434	482	546	639	783	1048	1676
3	335	384	454	504	572	669	822	1103	1768
3125	349	400	473	526	597	700	862	1160	1868
325	363	417	493	549	623	731	902	1217	1968
3375	377	433	513	572	649	762	942	1274	2068
35	391	450	533	595	675	793	982	1332	2168
3625	405	466	553	617	701	825	1023*	1392	2276
375	419	482	573	640	728	857	1065	1453	2384
3875	433	498	593	662	754	889	1106	1514	2492
4	448	514	613	685	781	921	1148	1575	2600
425	476	546	654	730	835	985	1233	1698	2818
45	505	579	695	775	890	1050	1319	1822	3036
475	533	612	735	820	945	1114	1407	1950	3268
5	562	645	775	866	1000	1179	1496	2080	3500
525	590	678	816	914	1055	1251*	1586	2213	3740
55	618	712	857	962	1110	1324	1677	2347	3981
575	646	746	898	1011	1166	1394	1771	2486	4233
6	675	780	940	1060	1222	1465	1865	2625	4486

For a similar Table, see p. 270.

TABLE XII.—Discharges from the Primary Channel in the first column of Table XI.

If the dimensions of the primary channel be in inches, divide the discharges in this table by 500; if in yards, multiply by 15·6; if in quarters, multiply by 32; and if in fathoms, by 88·2, &c.: see pp. 243 to 251. The final figures in the discharges may be rejected when they do not exceed one-half per cent., or 0·5 in 100. See pages 267 to 271.

Depths of a channel whose mean width is 70 :—in feet.	Falls, inclinations, and discharges in cubic feet per minute. Interpolate for intermediate falls; divide greater falls by 4, and double the corresponding discharges						
	1 inch per mile, 1 in 63360.	2 inches per mile, 1 in 31680.	3 inches per mile, 1 in 21120.	6 inches per mile, 1 in 10560.	9 inches per mile, 1 in 7040.	12 inches per mile, 1 in 5280.	15 inches per mile, 1 in 4224.
·125	47	72	93	139	175	205	233
·25	136	210	268	403	506	596	675
·375	249	389	498	746	940	1105	1252
·50	387	603	770	1155	1454	1709	1935
·625	541	849	1078	1617	2036	2395	2714
·75	714	1112	1420	2128	2681	3153	3573
·875	900	1401	1791	2685	3382	3978	4507
1·	1100	1714	2190	3283	4134	4862	5507
1·125	1310	2042	2614	3909	4927	5792	6577
1·25	1534	2384	3058	4581	5766	6780	7690
1·375	1767	2757	3521	5279	6661	7823	8863
1·50	2013	3142	4006	6016	7588	8915	10099
1·625	2268	3540	4525	6781	8541	10044	11381
1·75	2534	3950	5053	7570	9537	11210	12703
1·875	2812	4384	5599	8386	10570	12429	14083
2·	3090	4821	6161	9230	11628	13675	15513
2·125	3377	5273	6738	10092	12718	14956	16943
2·25	3674	5736	7331	10981	13833	16281	18435
2·375	3977	6210	7937	11889	14981	17645	19960
2·50	4293	6699	8563	12829	16161	19045	21534
2·625	4616	7203	9204	13800	17380	20434	23135
2·75	4947	7716	9865	14782	18624	21886	24800
2·875	5280	8233	10525	15773	19887	23360	26473
3·	5621	8762	11204	16788	21165	24833	28176
3·125	5972	9310	11900	17830	22454	26410	29925
3·25	6329	9862	12614	18897	23780	27994	31714
3·375	6689	10420	13320	19963	25145	29570	33507
3·50	7049	10995	14048	21052	26509	31262	35329
3·625	7418	11574	14785	22153	27906	32860	37186
3·75	7794	12163	15526	23284	29321	34479	39080
3·875	8178	12753	16283	24416	30756	36170	41013
4·	8566	13354	17070	25592	32225	37898	42954
4·25	9355	14582	18643	27936	35191	41368	46916
4·50	10173	15849	20267	30366	38254	44982	50973
4·75	11001	17140	21908	32818	41356	48630	55102
5·	11833	18454	23595	35355	44546	52378	59346
5·25	12696	19802	25362	37939	47795	56209	63688
5·50	13576	21172	27248	40564	51097	60079	68097
5·75	14478	22580	29160	43253	54478	64058	72591
6·	15393	23995	31122	45969	57897	68082	77154

For a similar Table, see p. 271.

TABLE XII.—Discharges from the Primary Channel in the first column of Table XI.

If the dimensions of the primary channel be in inches, divide the discharges in this table by 500; if in yards, multiply by 15.6, if in quarters, multiply by 32, and if in fathoms, by 88.2, etc.: see pp. 243 to 251. The final figures in the discharges may be rejected when they do not exceed one-half per cent., or 0.5 in 100. See pages 267 to 271.

Falls, inclinations, and discharges in cubic feet per minute. Interpolate for intermediate falls: divide greater falls by 4, and double the corresponding discharges.							Depths of a channel whose mean width is 70:—in feet.
18 inches per mile, 1 in 3520.	21 inches per mile, 1 in 3017.	24 inches per mile, 1 in 2640.	27 inches per mile, 1 in 2347.	30 inches per mile, 1 in 2112.	33 inches per mile, 1 in 1920.	36 inches per mile, 1 in 1760.	
258	281	303	323	343	362	380	1.25
748	815	877	936	993	1049	1100	.25
1387	1511	1627	1736	1843	1952	2037	.375
2145	2336	2515	2684	2852	3023	3155	.50
3004	3274	3527	3753	4021	4207	4414	.625
3957	4311	4645	4968	5287	5553	5817	.75
4991	5422	5859	6274	6650	6992	7342	.875
6097	6622	7159	7631	8107	8540	8974	1.
7266	7920	8531	9124	9660	10200	10693	1.125
8514	9284	9995	10658	11318	11923	12520	1.25
9816	10697	11539	12307	13045	13741	14479	1.375
11182	12185	13152	14007	14862	15666	16448	1.50
12601	13730	14821	15786	16750	17657	18552	1.625
14069	15331	16525	17616	18700	19698	20696	1.75
15593	16997	18306	19517	20728	21840	22944	1.875
17157	18697	20141	21469	22303	24017	25242	2.
18766	20446	22030	23480	24938	26269	27601	2.125
20410	22247	23965	25547	27129	28578	30027	2.25
22104	24087	25947	27662	29395	30934	32512	2.375
23848	25988	27992	29841	31701	33381	35096	2.50
25669	27953	30100	32069	34086	35910	37725	2.625
27479	29933	32247	34384	36512	38471	40415	2.75
29318	31947	34408	36697	38958	41055	43135	2.875
31206	34002	36624	39050	41464	43680	45896	3.
33141	36112	38897	41482	44048	46398	48747	3.125
35126	38266	41223	43954	46672	49174	51664	3.25
37109	40438	43556	46438	49330	51951	54586	3.375
39140	42631	45925	48963	51993	54775	57550	3.50
41184	44872	48343	51537	54728	57659	60580	3.625
43273	47158	50807	54162	57514	60585	63656	3.75
45407	49468	53300	56840	60341	63560	66784	3.875
47551	51818	55832	59414	63200	66576	69951	4.
51911	56586	60973	64974	69013	72694	76383	4.25
56448	61508	66176	70623	75017	79017	82994	4.50
61014	66500	71625	76408	81097	85426	89767	4.75
65713	71628	77140	82250	87351	92015	96653	5.
70509	76863	82779	88200	93731	98729	103745	5.25
75383	82159	88434	94344	100200	105550	110905	5.50
80379	87590	94348	100616	106823	112540	118254	5.75
85407	93093	100275	106911	113505	119616	125664	6.

For a similar Table, see p. 271.

TABLE XIII.—The Square Roots of the fifth powers of numbers for finding the Diameter of a Pipe, or dimensions of a Channel from the Discharge, or the Reverse; showing the relative Discharging Powers of pipes of different Diameters, and of any similar Channels whatever, closed or open. See pages 17, 18, 245, etc.—If d be the diameter of a pipe, in feet, and D the discharge in cubic feet per minute, then for long straight pipes we shall have for velocities of nearly 3 feet per

second, $D = 2400 \left(\frac{D^5}{d^5} \right)^{\frac{1}{2}}$, and $d = .044 \left(\frac{D^5}{d^5} \right)^{\frac{1}{2}}$; or if D be the discharge per

second, $D = 40 \left(\frac{D^5}{d^5} \right)^{\frac{1}{2}}$, and $d = .223 \left(\frac{D^5}{d^5} \right)^{\frac{1}{2}}$.

Relative dimensions or diameters of pipes.	Relative discharging powers.	Relative dimensions or diameters of pipes.	Relative discharging powers.	Relative dimensions or diameters of pipes.	Relative discharging powers.	Relative dimensions or diameters of pipes.	Relative discharging powers.
.25	.031	10.5	357.2	30.5	5138.	61.	29062.
.5	.177	11.	401.3	31.	5351.	62.	30268.
.75	.485	11.5	448.5	31.5	5569.	63.	31503.
1.	1.	12.	498.8	32.	5793.	64.	32768.
1.25	1.747	12.5	552.4	32.5	6022.	65.	34063.
1.5	2.756	13.	609.3	33.	6256.	66.	35388.
1.75	4.051	13.5	669.6	33.5	6496.	67.	36744.
2.	5.657	14.	733.4	34.	6741.	68.	38131.
2.25	7.594	14.5	800.6	34.5	6991.	69.	39548.
2.5	9.882	15.	871.4	35.	7247.	70.	40996.
2.75	12.541	15.5	945.9	35.5	7509.	71.	42476.
3.	15.588	16.	1024.	36.	7776.	72.	43988.
3.25	19.042	16.5	1105.9	36.5	8049.	73.	45531.
3.5	22.918	17.	1191.6	37.	8327.	74.	47106.
3.75	27.232	17.5	1281.1	37.5	8611.	75.	48714.
4.	32.	18.	1374.6	38.	8901.	76.	50354.
4.25	37.24	18.5	1472.1	38.5	9197.	77.	52027.
4.5	42.96	19.	1573.6	39.	9498.	78.	53732.
4.75	49.17	19.5	1679.1	39.5	9806.	79.	55471.
5.	55.90	20.	1788.9	40.	10119.	80.	57243.
5.25	63.15	20.5	1902.8	41.	10764.	81.	59049.
5.5	70.94	21.	2020.9	42.	11432.	82.	60888.
5.75	79.28	21.5	2143.4	43.	12125.	83.	62762.
6.	88.18	22.	2270.2	44.	12842.	84.	64669.
6.25	97.66	22.5	2401.4	45.	13584.	85.	66611.
6.5	107.72	23.	2537.	46.	14351.	86.	68588.
6.75	118.38	23.5	2677.1	47.	15144.	87.	70599.
7.	129.64	24.	2821.8	48.	15963.	88.	72645.
7.25	141.53	24.5	2971.1	49.	16807.	89.	74727.
7.5	154.05	25.	3125.	50.	17678.	90.	76843.
7.75	167.21	25.5	3283.6	51.	18575.	91.	78996.
8.	181.02	26.	3446.9	52.	19499.	92.	81184.
8.25	195.50	26.5	3615.1	53.	20450.	93.	83408.
8.5	210.64	27.	3788.	54.	21428.	94.	85668.
8.75	226.48	27.5	3965.8	55.	22434.	95.	87965.
9.	243.	28.	4148.5	56.	23468.	96.	90298.
9.25	260.23	28.5	4336.2	57.	24529.	97.	92668.
9.5	278.17	29.	4528.9	58.	25620.	98.	95075.
9.75	296.83	29.5	4726.7	59.	26738.	99.	97519.
10.	316.23	30.	4929.5	60.	27886.	100.	100000.

TABLE XIV.—Weights and Measures, English and French, with their relative values.

MEASURES OF LENGTH.

12 inches	1 foot.
7·92 inches	1 link.
3 feet	1 yard.
5½ yards = 16½ feet	1 pole or perch.
100 links = 22 yards.	1 chain = 4 perches.
40 perches = 220 yards	1 furlong.
8 furlongs = 1760 yards	1 mile.
6 feet	1 fathom.
120 fathoms	1 cable's length.
1 Nautical mile	6082·7 feet.
69·12 miles	1 Geographical deg.
3 miles	1 league.

The Irish perch is 21 feet, or seven yards. Three inches make a palm; 4 inches a hand; 5 feet a pace. In cloth measure 2½ inches = 1 nail; 4 nails = 1 quarter; 4 quarters = 1 yard. 11 Irish miles = 14 English.

MEASURES OF SURFACE.

144 square inches	1 square foot.
62·7264 „	1 square link.
9 square feet	1 square yard.
30½ square yards = 272½ square feet	1 square perch.
10,000 square links = 4,356 „	1 square chain.
10 square chains = 160 square perches	1 acre.
1 rood = 210 square yards	40 perches.
4 roods = 4,840 „	1 acre.
640 acres = 3,097,600 „	1 square mile.

The Irish perch is 49 square yards, or 441 square feet; 1 Irish acre = 1a. 2r. 19·17p. statute; and 1 statute acre = 0a. 2r. 18·77p. Irish. The Irish acre is to the English acre as 196 is to 121. 100 square feet is a square of roofing, slating, or flooring. The Cunningham acre is = 1a. 1r. 6·61p. English; and 1 English acre is = 0a. 3r. 3·904p. Cunningham measure.

TABLE XIV.—*Continued.*

CUBIC MEASURES, AND MEASURES OF CAPACITY AND WEIGHT.

1728 cubic inches	1 cubic foot.
27 cubic feet	1 cubic yard.
$16\frac{1}{2} \times 1\frac{1}{4} \times 1 = 24\cdot75$ cubic feet	1 perch of masonry.
$16\frac{1}{2} \times 16\frac{1}{2} \times 1\frac{1}{4} = 306$ cubic feet	1 rod of brickwork.
$21 \times 1\frac{1}{2} \times 1 = 30\frac{1}{2}$ cubic feet	1 Irish perch of masonry.

The standard gallon, imperial measure, contains 10 lbs. avoirdupois, of distilled water at 62° Fahrenheit, the barometer standing at 30 inches.

6·232 gallons	1 cubic foot.
8·665 cubic inches	1 gill.
4 gills 34·659 cubic inches	1 pint.
2 pints 69·318 cubic inches	1 quart.
2 quarts 138·637 cubic inches	1 pottle.
2 pottles 277·274 cubic inches	1 gallon.
2 gallons 554·548 cubic inches	1 peck.
4 pecks 2218·191 cubic inches	1 bushel.

The old Irish gallon contained 217·6 cubic inches, nearly, and 1 Irish gallon is therefore = ·7850 imperial gallon. The Irish barrel of lime still measures 40 Irish gallons, or 31·321 imperial gallons, or 4 bushels, very nearly. It is measured by a cylindrical measure 12 inches high, and about 21½ inches in diameter, containing half the Irish barrel. In the old English liquid measures for ale and beer, 36 gallons = 1 barrel = 36 gallons, 3½ quarts, imperial measure, nearly.

For old dry measures, 32 bushels = 1 chaldron = 31 bushels, 1 pint, imperial measure, nearly.

And 36 bushels of coal = 1 chaldron of coal = 34 bushels, 3 pecks, and 1 gallon, imperial measure. The Irish barrel of wheat is 20 stone; barley, 16 stone; oats, 14 stone.

TROY WEIGHT.

24 grains	1 pennyweight.
20 pennyweights	1 ounce.
12 ounces	1 pound.

One pound Troy = 22·816 cubic inches of distilled water, barometer 0 inches; thermometer 62°.

TABLE XIV.—*Continued.*

APOTHECARY'S WEIGHT.

20 Troy grains	1 scruple.
3 scruples	1 drachm.
8 drachms	1 ounce.
12 ounces	1 pound.

The ounce weighs 480 grains, and the pound 5760 grains, both in Troy and Apothecary's weight.

AVOIRDUPOIS OR COMMERCIAL WEIGHT.

One pound Avoirdupois = 27·7274 cubic inches, when the barometer stands at 30 inches, and Fahrenheit's thermometer at 62°.

16 drachms =	437·5 Troy grains	. 1 ounce.
16 ounces =	7,000 Troy grains	. 1 pound.
14 pounds =	98,000 Troy grains	. 1 stone.
8 stone =	112 pounds	. 1 cwt.
20 cwt. =	2,240 pounds	. 1 ton.

One pound Troy = ·82286 pounds Avoirdupois, and one pound Avoirdupois is equal to 1·2153 pounds Troy. One ton of water contains about 36 cubic feet, equal to 224 imperial gallons, nearly. Ten pounds of distilled water is equal to one gallon, the barometer and thermometer being as above stated.

FRENCH MEASURES AND WEIGHTS COMPARED WITH ENGLISH.

MEASURES OF LENGTH.

1 mètre	3·2808992 feet	1 foot English	·3047945 mètre
1 décimètre	·3280899 "	1 inch	·0253995 "
1 centimètre	·0328090 "	1 yard	·9143835 "
1 millimètre	·0032809 "	1 perch 5½ yds.	5·0291092 "
1 kilomètre (or {	·621383 mile	1 mile	1·60932 kilomètre
1000 mètres)			

1000 mètres = 100 décimètres = 10 hectomètres = 1 kilomètre = 3280·849 feet. The mètre is the 10,000,000th part of a quadrental arc of the meridian or 39·3708 inches English.

TABLE XIV.—Continued.

MEASURES OF SURFACE.

1 centiare (one square mètre)	} 10·7643 sq. ft.	119·6033 sq. yds	1 are
1 deciare . . . 107·6430 „		11·9603 „	1 deciare
1 are . . . 1076·430 „		1·1960 „	{ 1 centiare or sq. mètre.

100 ares = 10 deciares = 1 hectare = 2·471143 English acres, and 17 hectares are nearly equal to 42 English acres.

The old Paris foot is equal 1·06578 English feet; the French inch = 1·06578 English inches; the French line = 0·8882 of an English inch; the toise is equal to 6 French feet = 76·736 English inches = 6·39468 feet. The perch is 18 French feet; and the perch royal 22 French feet. The French square foot or inch = 1·13581 English square feet or inches, and the cubic foot or inch = 1·21061 English.

MEASURES OF SOLIDITY AND CAPACITY.

	Cubic feet.		Eng. cub. in.
1 millistere	·0353166	1 millilitre	·0610279
1 centistere	·353166	1 centilitre	·610279
1 decistere	3·53166	1 decilitre	6·10279
1 stere (one cubic mètre)	35·3166	1 litre	61·0279
1 decastere	353·166	1 decalitre	610·279
1 hectostere	3531·66	1 hectolitre	6102·79
1 kilostere	35316·6	1 kilolitre	61027·9

The stere and kilolitre are each a cubic mètre, and the litre is a cubic decimètre; 50 litres are nearly 11 English gallons, and 1 hectolitre 2·751207 English bushels.

MEASURES OF WEIGHT.

·0648 gramme = 1 grain, and 7000 grains = 1 lb. Avoirdupois.

1 milligramme . . .	·015432 grains	1 gramme . . .	15·432 grains
1 centigramme . . .	·15432 „	1 decagramme . .	·02205 lb. avoird.
1 decigramme . . .	1·5432 „	1 hectogramme . .	·2205 „
1 gramme . . .	15·432 „	1 kilogramme . .	2·2046 „

1·01605 tonnes = 1 ton: and 1 tonne = ·984206 ton.

A gramme is the weight of a cubic centimètre of water and its maximum density in vacuo: 1 kilogramme = 2·6795 lbs. Troy = 2·2046 lbs. Avoirdupois. 1 metrical quintal 220·46 lbs. Avoirdupois, and 10 quintals is equal to the weight of a cubic mètre of water.

TABLE XIV.—Continued.

CIRCULAR FRENCH AND BRITISH DIVISIONS.

French to British.	1° circular measure French	=	9 degree British.
	1 minute	= $\frac{9 \times 60}{100}$	= 54 British minutes.
	1 second	= $\frac{9 \times 60 \times 60}{100 \times 100}$	= 324 British seconds.
British to French.	1° circular	= $\frac{100}{90}$	= 1.1 = 1½ French degrees.
	1 minute	= $\frac{100}{9 \times 60}$	= 1.851 = 1¾ French minutes.
	1 second	= $\frac{100}{9 \times 60} \times \frac{100}{60} = \frac{100 \times 100}{9 \times 60 \times 60}$	= 3.08642 = 3¼ seconds.

TO REDUCE FRENCH TO BRITISH CIRCULAR MEASURES AND THE REVERSE.

Put n = number of British degrees, &c. and n_r = French, &c.

Then $n_r = n - \frac{n_r}{10}$ and $n_r = n + \frac{n_r}{9}$.

EXAMPLE 1. Given 309° 57' 90" French. Reduce to British

309° 57' 90"

deduct one-tenth 30° 95' 79"

$n_r = 278^\circ 62' 11''$ in decimal measures English
60

37° 2660 English minutes and decimals
60

15° 9600 English seconds and decimals.

Ans. 278° 37' 15" 96 according to the sexagesimal division.

EXAMPLE 2. Reduce 278° : 37' : 15" 96 British to French.

TABLE XIV.—*Continued.*

Make the seconds decimal parts of the minutes by dividing them by 6 and multiplying by 10. This then becomes $278^{\circ}37'266$. In degrees, minutes, and decimals of a minute. Make now the minutes into degrees and decimals of a degree by dividing *them* by 6 and multiplying by 10. The last figures then become

$278^{\circ}6211$ = English degrees and decimals

Add one-ninth $30\cdot9579$

$309\cdot5790$.

DECIMAL $309^{\circ}57'90''$ French measure.

And so on for others.

FRENCH MEASURES COMPARED WITH ENGLISH.

{ 1 MÈTRE = 3·281 feet = 39·371 inches = 1·0936 yds. = ·1988 perch.

{ 1 SQUARE MÈTRE = 10·764 sq. feet = 1·196 yds. = ·03954 sq. perch.

{ 1 FOOT = ·3048 mètre and 1 inch = ·0254 mètre.

{ 1 SQUARE FOOT = ·0929 sq. mètre.

{ 1 PERCH 16½ feet = 5·029 mètres.

{ 1 sq. PERCH 272½ ft. = 25·292 sq. mètres = 30½ sq. yds.

{ ARE = 100 sq. mètres = 3·954 sq. perches.

{ HECTARE—100 *Ares* = 395·4 perches = 2 1 35·4.

1 lb. avoirdupois = ·4536 kilogramme.

LITRE = cubic decimètre = 1·76 pint = ·22 gallon.

DECALITRE = 2·2 gallons = 1·1 peck

HECTOLITRE = 22 gallons = 11 pecks = 2·75 bushels.

KILOGRAMME = weight of one cubic decimètre of distilled water
= 2·2046 lbs. avoirdupois = 2·679 troy pounds = 15432·35 grains.

1000 KILOGRAMMES = 2204·6 lbs. = nearly 1 *ton British*, is called
a MILLIER or TONNE = 19·68 cwt.

KILOGRAMME = 1000 grammes = 10,000 decigrammes.


7000 grains = 1 lb. avoir. 437·5 grs. = 1 oz. avoir.

5760 grains = 1 lb. troy. 480 grs. = 1 oz. troy.

FORCE OF GRAVITY g = 9·809 mètres = 32·18 feet.

TABLE XIV.—Continued.

{ Length of a pendulum	} = 39·13 inches = ·994 mètre.
{ Vibrating seconds	
{ Latitude of Paris	
{ Mean barometer at 30 inches = 76·2 centimetres.	
{ 1 cubic foot of air weighs 536 grains or 1·23 oza. avoirdupois = 1·1 oz. troy.	
{ Average height of an atmosphere of equal density about 5 miles.	
{ Thermometers 9° Fahrenheit = 5° centigrade = 4° Réaumur.	
{ Freezing point 32° Fahrenheit = 0° centigrade = 0° Réaumur.	
{ Boiling point 212° ,, = 100° ,, = 80° ,,	



$\frac{1}{257}$ increase or decrease in volume of a gas for each degree centigrade.

$\frac{1}{256}$ increase or decrease in volume of a gas for each degree Fahrenheit.

{ 10 lbs. of distilled water = 1 gallon.	
{ 62·32 lbs. of distilled water = 1 cube foot.	
{ 1 cubic foot = 6·232 gallons.	

CIRCULAR.	{	100° French = 90° British. French division 1° = 100 minutes, 1 minute = 100 seconds.
		100 minutes French = 54 minutes British.
		100 seconds French = 32·4 seconds British. Or
		1° French = ·9° British.
		1' French = ·54 British.
		1" French = ·324 British.

TABLE IV. Showing the Weight, Specific Gravity, strength, and elasticity of various materials employed by the *Physicist and Engineer*. When used by the *Engineer* only about one-fourth of the ultimate strengths here given should be calculated from.

MATERIALS.	Moduli of Rupture.	Moduli of Elasticity.	Crushing forces per square inch, in lbs.	Tenacities per sq. in. in lbs.	Weights of a cubic foot in lbs.	Specific gravities.
Acacia, English Growth	11,200	1,150,000	..	16,000	44.3	.71
Ash	12,000	1,600,000	9,000	17,000	48.0	.77
Brass, Cast	8,900,000	10,300	18,000	525.0	8.40
Beech	9,300	1,350,000	8,500	16,000	43.0	.77
Brick, Red	800	230	135.5	2.20
Brickwork	112.5	1.80
Do. Pale Red	550	300	130.3	2.08
Cedar, American, Fresh	490,000	5,600	11,400	56.8	0.91
Do. do. Seasoned	4,900	..	47.0	0.75
Copper, Cast	19,000	538.0	8.61
Do. Sheet	30,000	549.0	8.80
Do. Wire-drawn	60,000	560.0	8.88
Deal, Christiana	9,900	1,670,000	..	12,400	43.6	0.70
Do. Memel	10,400	1,530,000	37.0	0.60
Do. Norway Spruce	17,600	21.2	0.34
Elm, Seasoned	6,100	700,000	10,300	13,500	36.8	0.59
Fir, New England	6,600	2,190,000	..	10,000	34.5	0.55
Do. Riga	7,600	1,100,000	6,100	12,000	47.0	0.75
Glass	8,000,000	33,000	2,400	153.3	2.45
Iron, Wrought, English	57,000	481.2	7.70
Do. in Bars	57,000	487.0	7.80
Do. rolled in Sheets and Rivetted	31,000	487	7.8
Cast Iron Cannon, cold blast	38,500	17,270,000	106,000	16,700	441	7.07
Do. Hot Blast	37,500	16,080,000	108,000	18,500	440.0	7.04
Do. Buffery	37,500	14,000,000	90,000	17,500	441.0	7.06
Larch, green	5,000	900,000	3,200	10,200	36.6	0.52
Do. dry	6,900	1,050,000	5,500	8,900	35.0	0.56
Lead, cast English	720,000	..	1,800	717.4	11.44
Do. milled sheet	3,800	712.9	11.40
Marble, white Italian	1,100	2,520,000	165.0	2.64
Do. black Galway	2,700	168.4	2.70
Mortar, old, good	250	80	107.1	1.75
Oak, English	10,000	1,450,000	6,600	17,300	58.3	0.98
Do. Canadian	10,500	2,150,000	6,500	10,200	54.5	0.87
Do. Dantzic	8,700	1,190,000	..	12,700	47.4	0.76
Do. African	13,600	2,280,000	60.7	0.97
Do. Adriatic	8,300	970,000	62.0	0.99
Pine, pitch	9,800	1,230,000	..	7,800	41.2	0.66
Do. red	8,900	1,840,000	5,800	..	41.2	0.66
Silver, Standard	40,900	644.5	10.31
Slate, Welsh	11,800	15,800,000	..	12,800	180.5	2.89
Do. Westmoreland	1,290,000	174.4	2.70
Do. Valentia	5,200	180.0	2.88
Steel, soft	120,000	486.2	7.80
Do. razor tempered	29,000,000	..	150,000	490.0	7.84
Stone, granite average	5,500	..	8,000	..	168.0	2.70
Do. Rochdale	2,400	161.0	2.58
Teak, dry	14,800	2,400,000	12,101	15,000	41.1	0.66
Tin, cast	4,600,000	..	5,300	455.7	7.30

CROSBY LOCKWOOD & SON'S

Catalogue of

Scientific, Technical and

Industrial Books.

	PAGE		PAGE
MECHANICAL ENGINEERING	1	DECORATIVE ARTS	80
CIVIL ENGINEERING	9	NATURAL SCIENCE	32
MARINE ENGINEERING, &c.	17	CHEMICAL MANUFACTURES	34
MINING & METALLURGY	19	INDUSTRIAL ARTS	36
ELECTRICITY	23	COMMERCE, TABLES, &c.	41
ARCHITECTURE & BUILDING	25	AGRICULTURE & GARDENING.	43
CARPENTRY & TIMBER	28	AUCTIONEERING, VALUING, &c.	46
LAW & MISCELLANEOUS	47		

MECHANICAL ENGINEERING, &c.

THE MECHANICAL ENGINEER'S POCKET-BOOK.

Comprising Tables, Formulæ, Rules, and Data: A Handy Book of Reference for Daily Use in Engineering Practice. By D. KINNEAR CLARK, M. Inst. C.E., Third Edition, Revised. Small 8vo, 700 pp., bound in flexible Leather Cover, rounded corners. **6/0**

SUMMARY OF CONTENTS:—MATHEMATICAL TABLES.—MEASUREMENT OF SURFACES AND SOLIDS.—ENGLISH AND FOREIGN WRIGHTS AND MEASURES.—MONEYS.—SPECIFIC GRAVITY, WEIGHT, AND VOLUME.—MANUFACTURED METALS.—STEEL PIPES.—BOLTS AND NUTS.—SUNDRY ARTICLES IN WROUGHT AND CAST IRON, COPPER, BRASS, LEAD, TIN, ZINC.—STRENGTH OF TIMBER.—STRENGTH OF CAST IRON.—STRENGTH OF WROUGHT IRON.—STRENGTH OF STEEL.—TENSILE STRENGTH OF COPPER, LEAD, &c.—RESISTANCE OF STONES AND OTHER BUILDING MATERIALS.—RIVETED JOINTS IN BOILER PLATES.—BOILER SHELLS.—WIRE ROPES AND HEMP ROPES.—CHAINS AND CHAIN CABLES.—FRAMING.—HARDNESS OF METALS, ALLOYS, AND STONES.—LABOUR OF ANIMALS.—MECHANICAL PRINCIPLES.—GRAVITY AND FALL OF BODIES.—ACCELERATING AND RETARDING FORCES.—MILL GEARING, SHAFTING, &c.—TRANSMISSION OF MOTIVE POWER.—HEAT.—COMBUSTION: FUELS.—WARMING, VENTILATION, COOKING STOVES.—STEAM.—STEAM ENGINES AND BOILERS.—RAILWAYS.—TRAMWAYS.—STEAM SHIPS.—PUMPING STEAM ENGINES AND PUMPS.—COAL GAS, GAS ENGINES, &c.—AIR IN MOTION.—COMPRESSED AIR.—HOT AIR ENGINES.—WATER POWER.—SPEED OF CUTTING TOOLS.—COLOURS.—ELECTRICAL ENGINEERING.


"Mr. Clark manifests what is an innate perception of what is likely to be useful in a pocket-book; and he is really unrivalled in the art of condensation. It is very difficult to hit upon any mechanical engineering subject concerning which this work supplies no information, and the excellent index at the end adds to its utility. In one word, it is an exceedingly handy and efficient tool, possessed of which the engineer will be saved many a wearisome calculation, or yet more wearisome hunt through various text-books and treatises, and, as such, we can heartily recommend it to our readers."—*The Engineer*.

"It would be found difficult to compress more matter within a similar compass, or produce a book of 650 pages which should be more compact or convenient for pocket reference. . . . Will be appreciated by mechanical engineers of all classes."—*Practical Engineer*.

MR. HUTTON'S PRACTICAL HANDBOOKS.

THE WORKS' MANAGER'S HANDBOOK.

Comprising Modern Rules, Tables, and Data. For Engineers, Millwrights, and Boiler Makers; Tool Makers, Machinists, and Metal Workers; Iron and Brass Founders, &c. By W. S. HUTTON, Civil and Mechanical Engineer, Author of "The Practical Engineer's Handbook." Fifth Edition, carefully Revised, with Additions. In One handsome Volume, medium 8vo, strongly bound 15/0

 The Author having compiled Rules and Data for his own use in a great variety of modern engineering work, and having found his notes extremely useful, decided to publish them—revised to date—believing that a practical work, suited to the DAILY REQUIREMENTS of MODERN ENGINEERS, would be favourably received.

"Of this edition we may repeat the appreciative remarks we made upon the first and third. Since the appearance of the latter very considerable modifications have been made, although the total number of pages remains almost the same. It is a very useful collection of rules, tables, and workshop and drawing office data."—*The Engineer*, May 10, 1895.

"The author treats every subject from the point of view of one who has collected workshop notes for application in workshop practice, rather than from the theoretical or literary aspect. The volume contains a great deal of that kind of information which is gained only by practical experience, and is seldom written in books."—*The Engineer*, June 5, 1895.

"The volume is an exceedingly useful one, brimful with engineer's notes, memoranda, and rules, and well worthy of being on every mechanical engineer's bookshelf."—*Mechanical World*.


"The information is precisely that likely to be required in practice. . . . The work forms a desirable addition to the library not only of the works' manager, but of any one connected with general engineering."—*Mining Journal*.

"Brimful of useful information, stated in a concise form, Mr. Hutton's books have met a pressing want among engineers. The book must prove extremely useful to every practical man possessing a copy."—*Practical Engineer*.

THE PRACTICAL ENGINEER'S HANDBOOK.

Comprising a Treatise on Modern Engines and Boilers, Marine, Locomotive, and Stationary. And containing a large collection of Rules and Practical Data relating to Recent Practice in Designing and Constructing all kinds of Engines, Boilers, and other Engineering work. The whole constituting a comprehensive Key to the Board of Trade and other Examinations for Certificates of Competency in Modern Mechanical Engineering. By WALTER S. HUTTON, Civil and Mechanical Engineer, Author of "The Works' Manager's Handbook for Engineers," &c. With upwards of 370 Illustrations. Fifth Edition, Revised with Additions. Medium 8vo, nearly 500 pp., strongly bound.

[Just Published. 18/0

 This Work is designed as a companion to the Author's "WORKS' MANAGER'S HANDBOOK." It possesses many new and original features, and contains, like its predecessor, a quantity of matter not originally intended for publication, but collected by the Author for his own use in the construction of a great variety of MODERN ENGINEERING WORK.

The information is given in a condensed and concise form, and is illustrated by upwards of 370 Woodcuts; and comprises a quantity of tabulated matter of great value to all engaged in designing, constructing, or estimating for ENGINES, BOILERS, and OTHER ENGINEERING WORK.

"We have kept it at hand for several weeks, referring to it as occasion arose, and we have not on a single occasion consulted its pages without finding the information of which we were in quest."—*Athenaeum*.

"A thoroughly good practical handbook, which no engineer can go through without learning something that will be of service to him."—*Marine Engineer*.

"An excellent book of reference for engineers, and a valuable text-book for students of engineering."—*Scotsman*.

"This valuable manual embodies the results and experience of the leading authorities on mechanical engineering."—*Building News*.

"The author has collected together a surprising quantity of rules and practical data, and has shown much judgment in the selections he has made. . . . There is no doubt that this book is one of the most useful of its kind published, and will be a very popular compendium."—*Engineer*.

"A mass of information set down in simple language, and in such a form that it can be easily referred to at any time. The matter is uniformly good and well chosen, and is greatly elucidated by the illustrations. The book will find its way on to most engineers' shelves, where it will rank as one of the most useful books of reference."—*Practical Engineer*.

"Full of useful information, and should be found on the office shelf of all practical engineers."—*English Mechanic*.

MR. HUTTON'S PRACTICAL HANDBOOKS—continued.

STEAM BOILER CONSTRUCTION.

A Practical Handbook for Engineers, Boiler-Makers, and Steam Users. Containing a large Collection of Rules and Data relating to Recent Practice in the Design, Construction, and Working of all Kinds of Stationary, Locomotive, and Marine Steam-Boilers. By WALTER S. HUTTON, Civil and Mechanical Engineer, Author of "The Works' Manager's Handbook," "The Practical Engineer's Handbook," &c. With upwards of 500 Illustrations. Third Edition, Revised and much Enlarged, medium 8vo, cloth . . . 18/0

THIS WORK is issued in continuation of the Series of Handbooks written by the Author, viz. :—"THE WORKS MANAGER'S HANDBOOK" and "THE PRACTICAL ENGINEER'S HANDBOOK," which are so highly appreciated by engineers for the practical nature of their information; and is consequently written in the same style as those works.

The Author believes that the concentration, in a convenient form for easy reference, of such a large amount of thoroughly practical information on Steam-Boilers, will be of considerable service to those for whom it is intended, and he trusts the book may be deemed worthy of as favourable a reception as has been accorded to its predecessors.

"Every detail, both in boiler design and management, is clearly laid before the reader. The volume shows that boiler construction has been reduced to the condition of one of the most exact sciences; and such a book is of the utmost value to the *fin de siècle* Engineer and Works Manager."—*Marine Engineer*.

"There has long been room for a modern handbook on steam boilers; there is not that room now, because Mr. Hutton has filled it. It is a thoroughly practical book for those who are occupied in the construction, design, selection, or use of boilers."—*Engineer*.

"The book is of so important and comprehensive a character that it must find its way into the libraries of every one interested in boiler using or boiler manufacture if they wish to be thoroughly informed. We strongly recommend the book for the intrinsic value of its contents."—*Machinery Market*.

"The value of this book can hardly be over-estimated. The author's rules, formulæ, &c., are all very fresh, and it is impossible to turn to the work and not find what you want. No practical engineer should be without it."—*Colliery Guardian*.

PRACTICAL MECHANICS' WORKSHOP COMPANION.

Comprising a great variety of the most useful Rules and Formulæ in Mechanical Science, with numerous Tables of Practical Data and Calculated Results for Facilitating Mechanical Operations. By WILLIAM TEMPLETON, Author of "The Engineer's Practical Assistant," &c., &c. Seventeenth Edition, Revised, Modernised, and considerably Enlarged by WALTER S. HUTTON, C.E., Author of "The Works' Manager's Handbook," "The Practical Engineer's Handbook," &c. Fcap. 8vo, nearly 500 pp., with 8 Plates and upwards of 250 Illustrative Diagrams, strongly bound for workshop or pocket wear and tear. 8/0

"In its modernised form Hutton's 'Templeton' should have a wide sale, for it contains much valuable information which the mechanic will often find of use, and not a few tables and notes which he might look for in vain in other works. This modernised edition will be appreciated by all who have learned to value the original editions of 'Templeton.'"—*English Mechanic*.

"It has met with great success in the engineering workshop, as we can testify; and there are a great many men who, in a great measure, owe their rise in life to this little book."—*Building News*.

"This familiar text-book—well known to all mechanics and engineers—is of essential service to the every-day requirements of engineers, millwrights, and the various trades connected with engineering and building. The new modernised edition is worth its weight in gold."—*Building News*. (Second Notice.)

"This well-known and largely-used book contains information, brought up to date, of the sort so useful to the foreman and draughtsman. So much fresh information has been introduced as to constitute it practically a new book. It will be largely used in the office and workshop."—*Mechanical World*.

"The publishers wisely entrusted the task of revision of this popular, valuable, and useful book to Mr. Hutton, than whom a more competent man they could not have found."—*Iron*.

ENGINEER'S AND MILLWRIGHT'S ASSISTANT.

A Collection of Useful Tables, Rules, and Data. By WILLIAM TEMPLETON. Seventh Edition, with Additions. 18mo, cloth . . . 2/6

"Occupies a foremost place among books of this kind. A more suitable present to an apprentice to any of the mechanical trades could not possibly be made."—*Building News*.

"A deservedly popular work. It should be in the 'drawer' of every mechanic."—*English Mechanic*.

THE MECHANICAL ENGINEER'S REFERENCE BOOK.

For Machine and Boiler Construction. In Two Parts. Part I. GENERAL ENGINEERING DATA. Part II. BOILER CONSTRUCTION. With 51 Plates and numerous Illustrations. By NELSON FOLEY, M.I.N.A. Second Edition, Revised throughout and much Enlarged. Folio, half-bound, net . **£3 3s.**

PART I.—MEASURES.—CIRCUMFERENCES AND AREAS, &c. SQUARES, CUBES, FOURTH POWERS.—SQUARE AND CUBE ROOTS.—SURFACE OF TUBES.—RECIPROCALLS.—LOGARITHMS.—MENSURATION.—SPECIFIC GRAVITIES AND WEIGHTS.—WORK AND POWER.—HEAT.—COMBUSTION.—EXPANSION AND CONTRACTION.—EXPANSION OF GASES.—STEAM.—STATIC FORCES.—GRAVITATION AND ATTRACTION.—MOTION AND COMPUTATION OF RESULTING FORCES.—ACCUMULATED WORK.—CENTRE AND RADIUS OF GYRATION.—MOMENT OF INERTIA.—CENTRE OF OSCILLATION.—ELECTRICITY.—STRENGTH OF MATERIALS.—ELASTICITY.—TEST SHEETS OF METALS.—FRICTION.—TRANSMISSION OF POWER.—FLOW OF LIQUIDS.—FLOW OF GASES.—AIR PUMPS, SURFACE CONDENSERS, &c.—SPEED OF STEAMSHIPS.—PROPELLERS.—CUTTING TOOLS.—FLANGES.—COPPER SHEETS AND TUBES.—SCREWS, NUTS, BOLT HEADS, &c.—VARIOUS RECIPES AND MISCELLANEOUS MATTER.—WITH DIAGRAMS FOR VALVE-GEAR, BELTING AND ROPES, DISCHARGE AND SUCTION PIPES, SCREW PROPELLERS, AND COPPER PIPES.

PART II.—TREATING OF POWER OF BOILERS.—USEFUL RATIOS.—NOTES ON CONSTRUCTION.—CYLINDRICAL BOILER SHELLS.—CIRCULAR FURNACES. FLAT PLATES.—STAYS.—GIRDERS.—SCREWS.—HYDRAULIC TESTS.—RIVETING.—BOILER SETTING, CHIMNEYS, AND MOUNTINGS.—FURLS, &c.—EXAMPLES OF BOILERS AND SPEEDS OF STEAMSHIPS.—NOMINAL AND NORMAL HORSE POWER.—WITH DIAGRAMS FOR ALL BOILER CALCULATIONS AND DRAWINGS OF MANY VARIETIES OF BOILERS.

"The book is one which every mechanical engineer may, with advantage to himself, add to his library."—*Industries*.

"Mr. Foley is well fitted to compile such a work. . . . The diagrams are a great feature of the work. . . . Regarding the whole work, it may be very fairly stated that Mr. Foley has produced a volume which will undoubtedly fulfil the desire of the author and become indispensable to all mechanical engineers."—*Marine Engineer*.

"We have carefully examined this work, and pronounce it a most excellent reference book for the use of marine engineers."—*Journal of American Society of Naval Engineers*.

COAL AND SPEED TABLES.

A Pocket Book for Engineers and Steam Users. By NELSON FOLEY, Author of "The Mechanical Engineer's Reference Book." Pocket-size, cloth . **3/6**

"These tables are designed to meet the requirements of every-day use; they are of sufficient scope for most practical purposes, and may be commended to engineers and users of steam."—*Iron*.

TEXT-BOOK ON THE STEAM ENGINE.

With a Supplement on GAS ENGINES, and PART II. on HEAT ENGINES. By T. M. GOODEVE, M.A., Barrister-at-Law, Professor of Mechanics at the Royal College of Science, London; Author of "The Principles of Mechanics," "The Elements of Mechanism," &c. Fourteenth Edition. Crown 8vo, cloth . **6/0**

"Professor Goodeve has given us a treatise on the steam engine which will bear comparison with anything written by Huxley or Maxwell, and we can award it no higher praise."—*Engineer*.

"Mr. Goodeve's text-book is a work of which every young engineer should possess himself."—*Mining Journal*.

ON GAS ENGINES.

With Appendix describing a Recent Engine with Tube Igniter. By T. M. GOODEVE, M.A. Crown 8vo, cloth . **2/6**

"Like all Mr. Goodeve's writings, the present is no exception in point of general excellence. It is a valuable little volume."—*Mechanical World*.

A TREATISE ON STEAM BOILERS.

Their Strength, Construction, and Economical Working. By R. WILSON, C.E. Fifth Edition. 12mo, cloth . **6/0**

"The best treatise that has ever been published on steam boilers."—*Engineer*.

"The author shows himself perfect master of his subject, and we heartily recommend all employing steam power to possess themselves of the work."—*Ryland's Iron Trade Circular*.

THE MECHANICAL ENGINEER'S COMPANION

of Areas, Circumferences, Decimal Equivalents, in inches and feet, millimetres, squares, cubes, roots, &c.; Weights, Measures, and other Data. Also Practical Rules for Modern Engine Proportions. By R. EDWARDS, M.Inst.C.E. Fcap. 8vo, cloth. [Just Published. **3/6**

A HANDBOOK ON THE STEAM ENGINE.

With especial Reference to Small and Medium-sized Engines. For the Use of Engine Makers, Mechanical Draughtsmen, Engineering Students, and users of Steam Power. By HERMAN HAEDER, C.E. Translated from the German with considerable additions and alterations, by H. H. P. POWLES, A.M.I.C.E., M.I.M.E. Second Edition, Revised. With nearly 1,100 Illustrations. Crown 8vo, cloth **9/0**

"A perfect encyclopedia of the steam engine and its details, and one which must take a permanent place in English drawing-offices and workshops."—*A Foreman Pattern-maker*.

"This is an excellent book, and should be in the hands of all who are interested in the construction and design of medium-sized stationary engines. . . . A careful study of its contents and the arrangement of the sections leads to the conclusion that there is probably no other book like it in this country. The volume aims at showing the results of practical experience, and it certainly may claim a complete achievement of this idea."—*Nature*.

"There can be no question as to its value. We cordially commend it to all concerned in the design and construction of the steam engine."—*Mechanical World*.

BOILER AND FACTORY CHIMNEYS.

Their Draught-Power and Stability. With a chapter on *Lightning Conductors*. By ROBERT WILSON, A.I.C.E., Author of "A Treatise on Steam Boilers," &c. Crown 8vo, cloth **3/6**

"A valuable contribution to the literature of scientific building."—*The Builder*.

BOILER MAKER'S READY RECKONER & ASSISTANT.

With Examples of Practical Geometry and Templating, for the Use of Platers, Smiths, and Riveters. By JOHN COURTNEY, Edited by D. K. CLARK, M.I.C.E. Third Edition, 480 pp., with 140 Illustrations. Fcap. 8vo . **7/0**

"No workman or apprentice should be without this book."—*Iron Trade Circular*.

REFRIGERATING & ICE-MAKING MACHINERY.

A Descriptive Treatise for the Use of Persons Employing Refrigerating and Ice-Making Installations, and others. By A. J. WALLIS-TAYLER, A.-M. Inst. C.E. Second Edition, Revised and Enlarged. With Illustrations. Crown 8vo, cloth. [Just Published. **7/6**

"Practical, explicit, and profusely illustrated."—*Glasgow Herald*.

"We recommend the book, which gives the cost of various systems and illustrations showing details of parts of machinery and general arrangements of complete installations."—*Builder*.

"May be recommended as a useful description of the machinery, the processes, and of the facts, figures, and tabulated physics of refrigerating. It is one of the best compilations on the subject."—*Engineer*.

HYDRAULIC MACHINERY.

A Practical Handbook on the Machinery Employed in the Concentration and Transmission of Power. By G. CROYDON MARKS, A.M.I.C.E., A.M.I.M.E. New Edition, Enlarged. Crown 8vo. [In the Press.

THE LOCOMOTIVE ENGINE AND ITS DEVELOPMENT.

A Popular Treatise on the Gradual Improvements made in Railway Engines between 1803 and 1896. By CLEMENT E. STRETTON, C.E. Fifth Edition, Enlarged. With 120 Illustrations. Crown 8vo, cloth. [Just Published. **3/6**

"Students of railway history and all who are interested in the evolution of the modern locomotive will find much to attract and entertain in this volume."—*The Times*.

"The author of this work is well known to the railway world, and no one, probably, has a better knowledge of the history and development of the locomotive. The volume before us should be of value to all connected with the railway system of this country."—*Nature*.

ENGINEERING ESTIMATES, COSTS, AND ACCOUNTS.

A Guide to Commercial Engineering. With numerous examples of Estimates and Costs of Millwright Work, Miscellaneous Productions, Steam Engines and Steam Boilers; and a Section on the Preparation of Costs Accounts. By A GENERAL MANAGER. Second Edition. 8vo, cloth. [Just Published. **12/0**

"This is an excellent and very useful book, covering subject-matter in constant requisition in every factory and workshop. . . . The book is invaluable, not only to the young engineer, but also to the estimate department of every works."—*Builder*.

"We accord the work unqualified praise. The information is given in a plain, straightforward manner, and bears throughout evidence of the intimate practical acquaintance of the author with every phase of commercial engineering."—*Mechanical World*.

PLATING AND BOILER MAKING.

A Practical Handbook for Workshop Operations. By JOSEPH G. HORNER, A.M.I.M.E. ("Foreman Pattern Maker"), Author of "Pattern Making," &c. 380 pp. with 338 Illustrations. Crown 8vo, cloth. [Just Published. 7/6

"The latest production from the pen of this writer is characterised by that evidence of close acquaintance with workshop methods which will render the book exceedingly acceptable to the practical hand. We have no hesitation in commending the work as a serviceable and practical handbook on a subject which has not hitherto received much attention from those qualified to deal with it in a satisfactory manner."—*Mechanical World*.

PATTERN MAKING.

A Practical Treatise, embracing the Main Types of Engineering Construction, and including Gearing, both Hand and Machine-made, Engine Work, Sheaves and Pulleys, Pipes and Columns, Screws, Machine Parts, Pumps and Cocks, the Moulding of Patterns in Loam and Greensand, &c., together with the methods of estimating the weight of Castings; to which is added an Appendix of Tables for Workshop Reference. By JOSEPH G. HORNER, A.M.I.M.E. ("Foreman Pattern Maker"). Second Edition, thoroughly Revised and much Enlarged. With 450 Illustrations. Crown 8vo, cloth. 7/6

"A well-written technical guide, evidently written by a man who understands and has practised what he has written about. . . . We cordially recommend it to engineering students, young journeymen, and others desirous of being initiated into the mysteries of pattern-making."—*Builder*.

"More than 400 illustrations help to explain the text, which is, however, always clear and explicit, thus rendering the work an excellent *trade mecum* for the apprentice who desires to become master of his trade."—*English Mechanic*.

MECHANICAL ENGINEERING TERMS

(Lockwood's Dictionary of). Embracing those current in the Drawing Office, Pattern Shop, Foundry, Fitting, Turning, Smiths', and Boiler Shops, &c., &c. Comprising upwards of 6,000 Definitions. Edited by JOSEPH G. HORNER, A.M.I.M.E. ("Foreman Pattern Maker"), Author of "Pattern Making," &c. Second Edition, Revised, with Additions. Crown 8vo, cloth. 7/6

"Just the sort of handy dictionary required by the various trades engaged in mechanical engineering. The practical engineering pupil will find the book of great value in his studies, and every foreman engineer and mechanic should have a copy."—*Building News*.

"Not merely a dictionary, but, to a certain extent, also a most valuable guide. It strikes us as a happy idea to combine with a definition of the phrase useful information on the subject of which it treats."—*Machinery Market*.

TOOTHED GEARING.

A Practical Handbook for Offices and Workshops. By JOSEPH HORNER, A.M.I.M.E. ("Foreman Pattern Maker"), Author of "Pattern Making," &c. With 184 Illustrations. Crown 8vo, cloth. 6/0

"We must give the book our unqualified praise for its thoroughness of treatment, and we can heartily recommend it to all interested as the most practical book on the subject yet written."—*Mechanical World*.

FIRE, FIRE-ENGINES, & FIRE BRIGADES.

With a History of Fire-Engines, their Construction, Use, and Management; Remarks on Fire-proof Buildings, and the Preservation of Life from Fire; Statistics of the Fire Appliances in English Towns; Foreign Fire Systems; Hints on Fire-Brigades, &c., &c. By CHARLES F. T. YOUNG, C.E. With Illustrations, 544 pp. Demy 8vo, cloth. £1 4s.

"To such of our readers as are interested in the subject of fires and fire apparatus, we can most heartily commend this book. It is really the only English work we now have upon the subject."—*Engineering*.

MOTOR CARS FOR COMMON ROADS.

By A. J. WALLIS-TAYLER, Assoc. Memb. Inst. C.E., Author of "Modern Cycles," &c. Including Early and Recent Examples of Steam Road Carriages, Internal Combustion or Explosive Engine Carriages, Electric Motor Carriages, Miscellaneous Motor Cars, Auto-Car Bill, Rules and Regulations, &c. With numerous Illustrations. Crown 8vo, cloth. [Just Published. 4/6

STONE-WORKING MACHINERY.

A Manual dealing with the Rapid and Economical Conversion of Stone. With Hints on the Arrangement and Management of Stone Works. By M. POWIS BALE, M.I.M.E. Second Edition, enlarged. With Illustrations. Crown 8vo, cloth. [Just Published. 9/0

"The book should be in the hands of every mason or student of stonework."—*Colliery Guardian*

"A capital handbook for all who manipulate stone for building or ornamental purposes."—*Machinery Market*.

PUMPS AND PUMPING.

A Handbook for Pump Users. Being Notes on Selection, Construction, and Management. By M. POWIS BALE, M.I.M.E. Third Edition, Revised. Crown 8vo, cloth. [Just Published. 2/6

"The matter is set forth as concisely as possible. In fact, condensation rather than diffuseness has been the author's aim throughout; yet he does not seem to have omitted anything likely to be of use."—*Journal of Gas Lighting*.

"Thoroughly practical and simply and clearly written."—*Glasgow Herald*

MILLING MACHINES AND PROCESSES.

A Practical Treatise on Shaping Metals by Rotary Cutters. Including Information on Making and Grinding the Cutters. By PAUL N. HASLUCK, Author of "Lathe-Work." 352 pp. With upwards of 300 Engravings. Large crown 8vo, cloth. 12/6

"A new departure in engineering literature. . . . We can recommend this work to all interested in milling machines; it is what it professes to be—a practical treatise."—*Engineer*.

"A capital and reliable book which will no doubt be of considerable service both to those who are already acquainted with the process as well as to those who contemplate its adoption."—*Industries*.

LATHE-WORK.

A Practical Treatise on the Tools, Appliances, and Processes employed in the Art of Turning. By PAUL N. HASLUCK. Fifth Edition. Crown 8vo, cloth. 5/0

"Written by a man who knows not only how work ought to be done, but who also knows how to do it, and how to convey his knowledge to others. To all turners this book would be valuable."—*Engineering*.

"We can safely recommend the work to young engineers. To the amateur it will simply be invaluable. To the student it will convey a great deal of useful information."—*Engineer*.

SCREW-THREADS,

And Methods of Producing Them. With numerous Tables and complete Directions for using Screw-Cutting Lathes. By PAUL N. HASLUCK, Author of "Lathe-Work," &c. With Seventy-four Illustrations. Fourth Edition, Re-written and Enlarged. Waistcoat-pocket size. 1/6

"Full of useful information, hints and practical criticism. Taps, dies, and screwing tools generally are illustrated and their actions described."—*Mechanical World*.

"It is a complete compendium of all the details of the screw-cutting lathe; in fact a *multum-in-parvo* on all the subjects it treats upon."—*Carpenter and Builder*.

TABLES AND MEMORANDA FOR ENGINEERS, MECHANICS, ARCHITECTS, BUILDERS, &c.

Selected and Arranged by FRANCIS SMITH. Sixth Edition, Revised, including ELECTRICAL TABLES, FORMULÆ, and MEMORANDA. Waistcoat-pocket size, limp leather. [Just Published. 1/6

"It would, perhaps, be as difficult to make a small pocket-book selection of notes and formulæ to suit ALL engineers as it would be to make a universal medicine; but Mr. Smith's waistcoat-pocket collection may be looked upon as a successful attempt."—*Engineer*.

"The best example we have ever seen of 270 pages of useful matter packed into the dimensions of a card-case."—*Building News*. "A veritable pocket treasury of knowledge."—*Iron*.

POCKET GLOSSARY OF TECHNICAL TERMS.

English-French, French-English; with Tables suitable for the Architectural, Engineering, Manufacturing, and Nautical Professions. By JOHN JAMES FLETCHER, Engineer and Surveyor. Second Edition, Revised and Enlarged, 200 pp. Waistcoat-pocket size, limp leather. 1/6

"It is a very great advantage for readers and correspondents in France and England to have so large a number of the words relating to engineering and manufacturers collected in a lilliputian volume. The little book will be useful both to students and travellers."—*Architect*.

"The glossary of terms is very complete, and many of the Tables are new and well arranged. We cordially commend the book."—*Mechanical World*.

THE ENGINEER'S YEAR BOOK FOR 1898.

Comprising Formulæ, Rules, Tables, Data and Memoranda in Civil, Mechanical, Electrical, Marine and Mine Engineering. By H. R. KEMPE, A.M. Inst. C.E., M.I.E.E., Technical Officer of the Engineer-in-Chief's Office, General Post Office, London, Author of "A Handbook of Electrical Testing." "The Electrical Engineer's Pocket-Book," &c. With about 850 Illustrations, specially Engraved for the work. Crown 8vo, 700 pp., leather. [Just Published. 8/0

"Represents an enormous quantity of work, and forms a desirable book of reference."—*The Engineer*.

"The volume is distinctly in advance of most similar publications in this country."—*Engineering*.

"This valuable and well-designed book of reference meets the demands of all descriptions of engineers."—*Saturday Review*.

"Teems with up-to-date information in every branch of engineering and construction."—*Building News*.

"The needs of the engineering profession could hardly be supplied in a more admirable, complete and convenient form. To say that it more than sustains all comparisons is praise of the highest sort, and that may justly be said of it."—*Mining Journal*.

"There is certainly room for the newcomer, which supplies explanations and directions, as well as formulæ and tables. It deserves to become one of the most successful of the technical annuals."—*Architect*.

"Brings together with great skill all the technical information which an engineer has to use day by day. It is in every way admirably equipped, and is sure to prove successful."—*Scotsman*.

"The up-to-dateness of Mr. Kempe's compilation is a quality that will not be lost on the busy people for whom the work is intended."—*Glasgow Herald*.

THE PORTABLE ENGINE.

A Practical Manual on its Construction and Management. For the use of Owners and Users of Steam Engines generally. By WILLIAM DYSON WANSBROUGH. Crown 8vo, cloth 3/6

"This is a work of value to those who use steam machinery. . . . Should be read by every one who has a steam engine, on a farm or elsewhere."—*Mark Lane Express*.

"We cordially commend this work to buyers and owners of steam engines, and to those who have to do with their construction or use."—*Timber Trades Journal*.

"Such a general knowledge of the steam-engine as Mr. Wansbrough furnishes to the reader should be acquired by all intelligent owners and others who use the steam engine."—*Building News*.

"An excellent text-book of this useful form of engine. The 'Hints to Purchasers' contain a good deal of common-sense and practical wisdom."—*English Mechanic*.

IRON AND STEEL.

A Work for the Forge, Foundry, Factory, and Office. Containing ready, useful, and trustworthy Information for Ironmasters and their Stock-takers; Managers of Bar, Rail, Plate, and Sheet Rolling Mills; Iron and Metal Founders; Iron Ship and Bridge Builders; Mechanical, Mining, and Consulting Engineers; Architects, Contractors, Builders, &c. By CHARLES HOARE, Author of "The Slide Rule," &c. Ninth Edition. 32mo, leather . . 6/0

"For comprehensiveness the book has not its equal."—*Iron*.

"One of the best of the pocket books."—*English Mechanic*.

CONDENSED MECHANICS.

A Selection of Formulæ, Rules, Tables, and Data for the Use of Engineering Students, Science Classes, &c. In accordance with the Requirements of the Science and Art Department. By W. G. CRAWFORD HUGHES, A.M.I.C.E. Crown 8vo, cloth 2/6

"The book is well fitted for those who are either confronted with practical problems in their work, or are preparing for examination and wish to refresh their knowledge by going through their formulæ again."—*Marine Engineer*.

"It is well arranged, and meets the wants of those for whom it is intended."—*Railway News*.

THE SAFE USE OF STEAM.

Containing Rules for Unprofessional Steam Users. By an ENGINEER. Seventh Edition. Sewed. 6d.

"If steam-users would but learn this little book by heart, boiler explosions would become sensations by their rarity."—*English Mechanic*.

HEATING BY HOT WATER.

With Information and Suggestions on the best Methods of Heating Public, Private and Horticultural Buildings. By WALTER JONES. Second Edition. With 66 Illustrations, crown 8vo, cloth Not 2/6

"We confidently recommend all interested in heating by hot water to secure a copy of this valuable little treatise."—*The Plumber and Decorator*.

CIVIL ENGINEERING, SURVEYING, &c.

LIGHT RAILWAYS FOR THE UNITED KINGDOM, INDIA, AND THE COLONIES.

A Practical Handbook setting forth the Principles on which Light Railways should be Constructed, Worked, and Financed; and detailing the Cost of Construction, Equipment, Revenue and Working Expenses of Local Railways already established in the above-mentioned countries, and in Belgium, France, Switzerland, &c. By J. C. MACKAY, F.G.S., A.M. Inst. C.E. Illustrated with Plates and Diagrams. Medium 8vo, cloth. [Just Published. 15/0

"Mr. Mackay's volume is clearly and concisely written, admirably arranged, and freely illustrated. The book is exactly what has been long wanted. We recommend it to all interested in the subject. It is sure to have a wide sale."—*Railway News*.

"Those who desire to have within reach general information concerning almost all the light railway systems in the world will do well to buy Mr. Mackay's book."—*Engineer*.

"This work appears very opportunely, when the extension of the system on a large scale to England is at last being mooted. In its pages we find all the information that the heart of man can desire on the subject. . . . every detail in its story, founded on the experience of other countries and applied to the possibilities of England, is put before us."—*Spectator*.

PRACTICAL TUNNELLING.

Explaining in detail Setting-out the Works, Shaft-sinking, and Heading-driving, Ranging the Lines and Levelling underground, Sub-Excavating, Timbering and the Construction of the Brickwork of Tunnels, with the amount of Labour required for, and the Cost of, the various portions of the work. By FREDERICK W. SIMMS, M. Inst. C.E. Fourth Edition, Revised and Further Extended, including the most recent (1895) Examples of Sub-aqueous and other Tunnels, by D. KINNEAR CLARK, M. Inst. C.E. Imperial 8vo, with 34 Folding Plates and other Illustrations. Cloth. [Just Published. 22 2s.

"The present (1896) edition has been brought right up to date, and is thus rendered a work to which civil engineers generally should have ready access, and to which engineers who have construction work can hardly afford to be without, but which to the younger members of the profession is invaluable, as from its pages they can learn the state to which the science of tunnelling has attained."—*Railway News*.

"The estimation in which Mr. Simms's book has been held for many years cannot be more truly expressed than in the words of the late Prof. Rankine: 'The best source of information on the subject of tunnels is Mr. F. W. Simms's work on Practical Tunnelling.'"—*Architect*.

THE WATER SUPPLY OF TOWNS AND THE CONSTRUCTION OF WATER-WORKS.

A Practical Treatise for the Use of Engineers and Students of Engineering. By W. K. BURTON, A.M. Inst. C.E., Professor of Sanitary Engineering in the Imperial University, Tokyo, Japan, and Consulting Engineer to the Tokyo Water-works. Second Edition, Revised and Extended. With numerous Plates and Illustrations. Super-royal 8vo, buckram. [Just Published. 25/0

I. INTRODUCTORY.—II. DIFFERENT QUALITIES OF WATER.—III. QUANTITY OF WATER TO BE PROVIDED.—IV. ON ASCERTAINING WHETHER A PROPOSED SOURCE OF SUPPLY IS SUFFICIENT.—V. ON ESTIMATING THE STORAGE CAPACITY REQUIRED TO BE PROVIDED.—VI. CLASSIFICATION OF WATER-WORKS.—VII. IMPOUNDING RESERVOIRS.—VIII. EARTHWORK DAMS.—IX. MASONRY DAMS.—X. THE PURIFICATION OF WATER.—XI. SETTTLING RESERVOIRS.—XII. SAND FILTRATION.—XIII. PURIFICATION OF WATER BY ACTION OF IRON, SOFTENING OF WATER BY ACTION OF LIME, NATURAL FILTRATION.—XIV. SERVICE OR CLEAN WATER RESERVOIRS—WATER TOWERS—STAND PIPES.—XV. THE CONNECTION OF SETTTLING RESERVOIRS, FILTER BEDS AND SERVICE RESERVOIRS.—XVI. PUMPING MACHINERY.—XVII. FLOW OF WATER IN CONDUITS—PIPES AND OPEN CHANNELS.—XVIII. DISTRIBUTION SYSTEMS.—XIX. SPECIAL PROVISIONS FOR THE EXTINCTION OF FIRE.—XX. PIPES FOR WATER-WORKS.—XXI. PREVENTION OF WASTE OF WATER.—XXII. VARIOUS APPLICATIONS USED IN CONNECTION WITH WATER-WORKS.

APPENDIX I. By PROF. JOHN MUIR, F.R.S.—CONSIDERATIONS CONCERNING THE PROBABLE EFFECTS OF EARTHQUAKES ON WATER-WORKS, AND THE SPECIAL PRECAUTIONS TO BE TAKEN IN EARTHQUAKE COUNTRIES.

APPENDIX II. By JOHN DE RIJKE, C.E.—ON SAND DUNES AND DUNE SAND AS A SOURCE OF WATER SUPPLY.

"The chapter upon filtration of water is very complete, and the details of construction well illustrated. . . . The work should be specially valuable to civil engineers engaged in work in Japan, but the interest is by no means confined to that locality."—*Engineer*.

"We congratulate the author upon the practical commonsense shown in the preparation of this work. . . . The plates and diagrams have evidently been prepared with great care, and cannot fail to be of great assistance to the student."—*Builder*.

"The whole art of water-works construction is dealt with in a clear and comprehensive fashion in this handsome volume. . . . Mr. Burton's practical treatise shows in all its sections the fruit of independent study and individual experience. It is largely based upon his own practice in the branch of engineering of which it treats."—*Saturday Review*.

THE WATER SUPPLY OF CITIES AND TOWNS.

By WILLIAM HUMBER, A. M. Inst. C.E., and M. Inst. M.E., Author of "Cast and Wrought Iron Bridge Construction," &c., &c. Illustrated with 50 Double Plates, 1 Single Plate, Coloured Frontispiece, and upwards of 250 Woodcuts, and containing 400 pp. of Text. Imp. 4to, elegantly and substantially half-bound in morocco **£8 6s.**

LIST OF CONTENTS.

I. HISTORICAL SKETCH OF SOME OF THE MEANS THAT HAVE BEEN ADOPTED FOR THE SUPPLY OF WATER TO CITIES AND TOWNS.—II. WATER AND THE FOREIGN MATTER USUALLY ASSOCIATED WITH IT.—III. RAINFALL AND EVAPORATION.—IV. SPRINGS AND THE WATER-BEARING FORMATIONS OF VARIOUS DISTRICTS.—V. MEASUREMENT AND ESTIMATION OF THE FLOW OF WATER.—VI. ON THE SELECTION OF THE SOURCE OF SUPPLY.—VII. WELLS.—VIII. RESERVOIRS.—IX. THE PURIFICATION OF WATER.—X. PUMPS.—XI. PUMPING MACHINERY.—XII. CONDUITS.—XIII. DISTRIBUTION OF WATER.—XIV. METERS, SERVICE PIPES, AND HOUSE FITTINGS.—XV. THE LAW OF ECONOMY OF WATER-WORKS.—XVI. CONSTANT AND INTERMITTENT SUPPLY.—XVII. DESCRIPTION OF PLATES.—APPENDICES, GIVING TABLES OF RATES OF SUPPLY, VELOCITIES, &c., &c., TOGETHER WITH SPECIFICATIONS OF SEVERAL WORKS ILLUSTRATED, AMONG WHICH WILL BE FOUND: ABERDEEN, BIDEFORD, CANTERBURY, DUNDEE, HALIFAX, LAMBETH, ROTHERHAM, DUBLIN, AND OTHERS.

"The most systematic and valuable work upon water supply hitherto produced in English, or in any other language. . . . Mr. Humber's work is characterised almost throughout by an exhaustiveness much more distinctive of French and German than of English technical treatises."—*Engineer*.

RURAL WATER SUPPLY.

A Practical Handbook on the Supply of Water and Construction of Water-works for small Country Districts. By ALLAN GREENWELL, A.M.I.C.E., and W. T. CURRY, A.M.I.C.E., F.G.S. With Illustrations. Crown 8vo, cloth. [Just Published. **5/0**

"We conscientiously recommend it as a very useful book for those concerned in obtaining water for small districts, giving a great deal of practical information in a small compass."—*Builder*.

"The volume contains valuable information upon all matters connected with water supply. . . . It is full of details on points which are continually before water-works engineers."—*Nature*.

HYDRAULIC TABLES, CO-EFFICIENTS, & FORMULÆ.

For Finding the Discharge of Water from Orifices, Notches, Weirs, Pipes, and Rivers. With New Formulæ, Tables, and General Information on Rain-fall, Catchment-Basins, Drainage, Sewerage, Water Supply for Towns and Mill Power. By JOHN NEVILLE, Civil Engineer, M.R.I.A. Third Edition, revised, with additions. Numerous Illustrations. Crown 8vo, cloth . **14/0**

"It is, of all English books on the subject, the one nearest to completeness. . . . From the good arrangement of the matter, the clear explanations and abundance of formulæ, the carefully calculated tables, and, above all, the thorough acquaintance with both theory and construction, which is displayed from first to last, the book will be found to be an acquisition."—*Architect*.

HYDRAULIC MANUAL.

Consisting of Working Tables and Explanatory Text. Intended as a Guide in Hydraulic Calculations and Field Operations. By LEWIS D'A. JACKSON, Author of "Aid to Survey Practice," "Modern Metrology," &c. Fourth Edition, Enlarged. Large crown 8vo, cloth **16/0**

"The author has had a wide experience in hydraulic engineering and has been a careful observer of the facts which have come under his notice, and from the great mass of material at his command he has constructed a manual which may be accepted as a trustworthy guide to this branch of the engineer's profession."—*Engineering*.

"The most useful feature of this work is its freedom from what is superannuated, and its thorough adoption of recent experiments; the text is in fact in great part a short account of the great modern experiments."—*Nature*.

WATER ENGINEERING.

A Practical Treatise on the Measurement, Storage, Conveyance, and Utilisation of Water for the Supply of Towns, for Mill Power, and for other Purposes. By C. SLAGO, A. M. Inst. C.E. Second Edition. Crown 8vo, cloth . **7/6**

As a small practical treatise on the water supply of towns, and on some applications of water-power, the work is in many respects excellent."—*Engineering*.

"The author has collated the results deduced from the experiments of the most eminent authorities, and has presented them in a compact and practical form, accompanied by very clear and detailed explanations. . . . The application of water as a motive power is treated very carefully and exhaustively."—*Builder*.

MASONRY DAMS FROM INCEPTION TO COMPLETION.

Including numerous Formulæ, Forms of Specification and Tender, Pocket Diagram of Forces, &c. For the use of Civil and Mining Engineers. By C. F. COURTNEY, M. Inst. C.E. 8vo, cloth. [Just Published. 9/6

RIVER BARS.

The Causes of their Formation, and their Treatment by "Induced Tidal Scour;" with a Description of the Successful Reduction by this Method of the Bar at Dublin. By I. J. MANN, Assist. Eng. to the Dublin Port and Docks Board. Royal 8vo, cloth. 7/6

"We recommend all interested in harbour works—and, indeed, those concerned in the improvements of rivers generally—to read Mr. Mann's interesting work on the treatment of river bars."—*Engineer*.

DRAINAGE OF LANDS, TOWNS AND BUILDINGS.

By G. D. DEMPSEY, C.E. Revised, with large Additions on RECENT PRACTICE IN DRAINAGE ENGINEERING, by D. KINNEAR CLARK, M. Inst. C.E., Author of "Tramways: their Construction and Working." Cr. 8vo, cloth. 4/6

"The new matter added to Mr. Dempsey's excellent work is characterised by the comprehensive grasp and accuracy of detail for which the name of Mr. D. K. Clark is a sufficient voucher."—*Athenæum*.

TRAMWAYS: THEIR CONSTRUCTION AND WORKING.

Embracing a Comprehensive History of the System; with an exhaustive Analysis of the Various Modes of Traction, including Horse Power, Steam, Cable Traction, Electric Traction, &c.; a Description of the Varieties of Rolling Stock; and ample Details of Cost and Working Expenses. New Edition, Thoroughly Revised, and Including the Progress recently made in Tramway Construction, &c., &c. By D. KINNEAR CLARK, M. Inst. C.E. With 400 Illustrations. 8vo, 780 pp., buckram. [Just Published. 28/0

"Although described as a new edition, this book is really a new one, a large part of it, which covers historical ground, having been re-written and amplified; while the parts which relate to all that has been done since 1882 appear in this edition only. It is sixteen years since the first edition appeared, and twelve years since the supplementary volume to the first book was published. After a lapse, then, of twelve years, it is obvious that the author has at his disposal a vast quantity of descriptive and statistical information, with which he may, and has, produced a volume of great value to all interested in tramway construction and working. The new volume is one which will rank, among tramway engineers and those interested in tramway working, with his world-famed book on railway machinery."—*The Engineer*, March 8, 1895.

PRACTICAL SURVEYING.

A Text-Book for Students preparing for Examinations or for Survey-work in the Colonies. By GEORGE W. USILL, A.M.I.C.E. With 4 Plates and upwards of 330 Illustrations. Fifth Edition, Revised and Enlarged. Including Tables of Natural Sines, Tangents, Secants, &c. Crown 8vo, cloth 7/6; or, on THIN PAPER, bound in limp leather, gilt edges, rounded corners, for pocket use. 12/6

"The best forms of instruments are described as to their construction, uses and modes of employment, and there are innumerable hints on work and equipment such as the author, in his experience as surveyor, draughtsman and teacher, has found necessary, and which the student in his inexperience will find most serviceable."—*Engineer*.

"The latest treatise in the English language on surveying, and we have no hesitation in saying that the student will find it a better guide than any of its predecessors. Deserves to be recognised as the first book which should be put in the hands of a pupil of Civil Engineering."—*Architect*.

AID TO SURVEY PRACTICE.

For Reference in Surveying, Levelling, and Setting-out; and in Route Surveys of Travellers by Land and Sea. With Tables, Illustrations, and Records. By LEWIS D'A. JACKSON, A.M.I.C.E. Second Edition, Enlarged. Large crown 8vo, cloth. 12/6

"Mr. Jackson has produced a valuable *trade-mecum* for the surveyor. We can recommend this book as containing an admirable supplement to the teaching of the accomplished surveyor."—*Athenæum*.

"As a text-book we should advise all surveyors to place it in their libraries, and study well the matured instructions afforded in its pages."—*Coltury Guardian*.

"The author brings to his work a fortunate union of theory and practical experience which, aided by a clear and lucid style of writing, renders the book a very useful one."—*Builder*.

ENGINEER'S & MINING SURVEYOR'S FIELD BOOK.

Consisting of a Series of Tables, with Rules, Explanations of Systems, and use of Theodolite for Traverse Surveying and plotting the work with minute accuracy by means of Straight Edge and Set Square only; Levelling with the Theodolite, Casting-out and Reducing Levels to Datum, and Plotting Sections in the ordinary manner; Setting-out Curves with the Theodolite by Tangential Angles and Multiples with Right and Left-hand Readings of the Instrument; Setting-out Curves without Theodolite on the System of Tangential Angles by Sets of Tangents and Offsets; and Earthwork Tables to 80 feet deep, calculated for every 6 inches in depth. By W. DAVIS HASKOLL, C.E. With numerous Woodcuts. Fourth Edition, Enlarged. Crown 8vo, cloth. **12/0**

"The book is very handy; the separate tables of sines and tangents to every minute will make it useful for many other purposes, the genuine traverse tables existing all the same."—*Athenaeum*.

"Every person engaged in engineering field operations will estimate the importance of such a work and the amount of valuable time which will be saved by reference to a set of reliable tables prepared with the accuracy and fulness of those given in this volume."—*Railway News*.

LAND AND MARINE SURVEYING.

In Reference to the Preparation of Plans for Roads and Railways; Canals, Rivers, Towns' Water Supplies; Docks and Harbours. With Description and Use of Surveying Instruments. By W. DAVIS HASKOLL, C.E. Second Edition, Revised, with Additions. Large crown 8vo, cloth. . . . **9/0**

"This book must prove of great value to the student. We have no hesitation in recommending it, feeling assured that it will more than repay a careful study."—*Mechanical World*.

"A most useful book for the student. We strongly recommend it as a carefully-written and valuable text-book. It enjoys a well-deserved repute among surveyors."—*Builder*.

"This volume cannot fail to prove of the utmost practical utility. It may be safely recommended to all students who aspire to become clean and expert surveyors."—*Mining Journal*.

PRINCIPLES AND PRACTICE OF LEVELLING.

Showing its Application to Purposes of Railway and Civil Engineering in the Construction of Roads; with Mr. TELFORD'S Rules for the same. By FREDERICK W. SIMMS, F.G.S., M. Inst. C.E. Eighth Edition, with the addition of LAW'S Practical Examples for Setting-out Railway Curves, and TRAUTWINE'S Field Practice of Laying-out Circular Curves. With 7 Plates and numerous Woodcuts, 8vo, cloth. . . . **8/6**

* * * TRAUTWINE ON CURVES may be had separate . . . **5/0**

"The text-book on levelling in most of our engineering schools and colleges."—*Engineer*.

"The publishers have rendered a substantial service to the profession, especially to the younger members, by bringing out the present edition of Mr. Simms' useful work."—*Engineering*.

AN OUTLINE OF THE METHOD OF CONDUCTING A TRIGONOMETRICAL SURVEY.

For the Formation of Geographical and Topographical Maps and Plans, Military Reconnaissance, LEVELLING, &c., with Useful Problems, Formulae, and Tables. By Lieut.-General FROME, R.E. Fourth Edition, Revised and partly Re-written by Major-General Sir CHARLES WARREN, G.C.M.G., R.E. With 19 Plates and 115 Woodcuts, royal 8vo, cloth. . . . **16/0**

"No words of praise from us can strengthen the position so well and so steadily maintained by this work. Sir Charles Warren has revised the entire work, and made such additions as were necessary to bring every portion of the contents up to the present date."—*Broad Arrow*.

TABLES OF TANGENTIAL ANGLES AND MULTIPLES FOR SETTING-OUT CURVES.

From 5 to 200 Radius. By A. BRAZELEV, M. Inst. C.E. 6th Edition, Revised. With an Appendix on the use of the Tables for Measuring up Curves. Printed on 50 Cards, and sold in a cloth box, waistcoat pocket size. [Just Published. **3/6**

"Each table is printed on a card, which, placed on the theodolite, leaves the hands free to manipulate the instrument—no small advantage as regards the rapidity of work."—*Engineer*.

"Very handy: a man may know that all his day's work must fall on two of these cards, which he puts into his own card-case, and leaves the rest behind."—*Athenaeum*.

HANDY GENERAL EARTH-WORK TABLES.

Giving the Contents in Cubic Yards of Centre and Slopes of Cuttings and Embankments from 3 inches to 80 feet in Depth or Height, for use with either 66 feet Chain or 100 feet Chain. By J. H. WATSON BUCK, M. Inst. C.E. On a Sheet mounted in cloth case. [Just Published. **3/6**

EARTHWORK TABLES.

Showing the Contents in Cubic Yards of Embankments, Cuttings, &c., of Heights or Depths up to an average of 80 feet. By JOSEPH BROADBENT, C.E., and FRANCIS CAMPIN, C.E. Crown 8vo, cloth 5/0

"The way in which accuracy is attained, by a simple division of each cross section into three elements, two in which are constant and one variable, is ingenious."—*Athenæum*

A MANUAL ON EARTHWORK.

By ALEX. J. S. GRAHAM, C.E. With numerous Diagrams. Second Edition. 18mo, cloth 2/6

THE CONSTRUCTION OF LARGE TUNNEL SHAFTS.

A Practical and Theoretical Essay. By J. H. WATSON BUCK, M. Inst. C.E., Resident Engineer, L. and N. W. R. With Folding Plates, 8vo, cloth 12/0

"Many of the methods given are of extreme practical value to the mason, and the observations on the form of arch, the rules for ordering the stone, and the construction of the templates, will be found of considerable use. We commend the book to the engineering profession."—*Building News*.

"Will be regarded by civil engineers as of the utmost value, and calculated to save much time and obviate many mistakes."—*Colliery Guardian*.

CAST & WROUGHT IRON BRIDGE CONSTRUCTION.

(A Complete and Practical Treatise on), including Iron Foundations. In Three Parts.—Theoretical, Practical, and Descriptive. By WILLIAM HUMBER, A. M. Inst. C.E., and M. Inst. M.E. Third Edition, revised and much improved, with 115 Double Plates (20 of which now first appear in this edition), and numerous Additions to the Text. In 2 vols., imp. 4to, half-bound in morocco £6 18s. 6s.

"A very valuable contribution to the standard literature of civil engineering. In addition to elevations, plans, and sections, large scale details are given, which very much enhance the instructive worth of those illustrations."—*Civil Engineer and Architect's Journal*.

"Mr. Humber's stately volumes, lately issued—in which the most important bridges erected during the last five years, under the direction of the late Mr. Brunel, Sir W. Cubitt, Mr. Hawkshaw, Mr. Page, Mr. Fowler, Mr. Hennans, and others among our most eminent engineers, are drawn and specified in great detail."—*Engineer*.

ESSAY ON OBLIQUE BRIDGES

(Practical and Theoretical). With 13 large Plates. By the late GEORGE WATSON BUCK, M.I.C.E. Fourth Edition, revised by his Son, J. H. WATSON BUCK, M.I.C.E.; and with the addition of Description to Diagrams for Facilitating the Construction of Oblique Bridges, by W. H. BARLOW, M.I.C.E. Royal 8vo, cloth 12/0

"The standard text-book for all engineers regarding skew arches is Mr. Buck's treatise, and it would be impossible to consult a better."—*Engineer*.

"Mr. Buck's treatise is recognised as a standard text-book, and his treatment has divested the subject of many of the intricacies supposed to belong to it. As a guide to the engineer and architect, on a confessedly difficult subject, Mr. Buck's work is unsurpassed."—*Building News*.

THE CONSTRUCTION OF OBLIQUE ARCHES

(A Practical Treatise on). By JOHN HART. Third Edition, with Plates. Imperial 8vo, cloth 8/0

GRAPHIC AND ANALYTIC STATICS.

In their Practical Application to the Treatment of Stresses in Roofs, Solid Girders, Lattice, Bowstring, and Suspension Bridges, Braced Iron Arches and Piers, and other Frameworks. By R. HUDSON GRAHAM, C.E. Containing Diagrams and Plates to Scale. With numerous Examples, many taken from existing Structures. Specially arranged for Class-work in Colleges and Universities. Second Edition, Revised and Enlarged. 8vo, cloth . . . 16/0

"Mr. Graham's book will find a place wherever graphic and analytic statics are used or studied."—*Engineer*.

"The work is excellent from a practical point of view, and has evidently been prepared with much care. The directions for working are simple, and are illustrated by an abundance of well-selected examples. It is an excellent text-book for the practical draughtsman."—*Athenæum*.

WEIGHTS OF WROUGHT IRON & STEEL GIRDERS.

A Graphic Table for Facilitating the Computation of the Weights of Wrought Iron and Steel Girders, &c., for Parliamentary and other Estimates. By J. H. WATSON BUCK, M. Inst. C.E. On a Sheet 2/6

HANDY BOOK FOR THE CALCULATION OF STRAINS

In Girders and Similar Structures and their Strength. Consisting of Formulæ and Corresponding Diagrams, with numerous details for Practical Application, &c. By WILLIAM HUMBER, A. M. Inst. C.E., &c. Fifth Edition. Crown 8vo, with nearly 100 Woodcuts and 3 Plates, cloth 7/6

"The formulæ are neatly expressed, and the diagrams good."—*Athenæum*.

"We heartily commend this really *handy* book to our engineer and architect readers."—*English Mechanic*.

TRUSSES OF WOOD AND IRON.

Practical Applications of Science in Determining the Stresses, Breaking Weights, Safe Loads, Scantlings, and Details of Construction. With Complete Working Drawings. By WILLIAM GRIFFITHS, Surveyor, Assistant Master, Tranmere School of Science and Art. Oblong 8vo, cloth 4/6

"This handy little book enters so minutely into every detail connected with the construction of roof trusses that no student need be ignorant of these matters."—*Practical Engineer*.

THE STRAINS ON STRUCTURES OF IRONWORK.

With Practical Remarks on Iron Construction. By F. W. SHEILDS, M.I.C.E. 8vo, cloth 5/0

A TREATISE ON THE STRENGTH OF MATERIALS.

With Rules for Application in Architecture, the Construction of Suspension Bridges, Railways, &c. By PETER BARLOW, F.R.S. A new Edition, revised by his Sons, P. W. BARLOW, F.R.S., and W. H. BARLOW, F.R.S.; to which are added, Experiments by HODGKINSON, FAIRBAIRN, and KIRKALDY; and Formulæ for calculating Girders, &c. Arranged and Edited by WM. HUMBER, A. M. Inst. C.E. Demy 8vo, 400 pp., with 19 large Plates and numerous Woodcuts, cloth 18/0

"Valuable alike to the student, tyro, and the experienced practitioner, it will always rank in future as it has hitherto done, as the standard treatise on that particular subject."—*Engineer*.

"As a scientific work of the first class, it deserves a foremost place on the bookshelves of every civil engineer and practical mechanic."—*English Mechanic*.

STRENGTH OF CAST IRON AND OTHER METALS.

By THOMAS TREDGOLD, C.E. Fifth Edition, including HODGKINSON'S Experimental Researches. 8vo, cloth 12/0

SAFE RAILWAY WORKING.

A Treatise on Railway Accidents, their Cause and Prevention; with a Description of Modern Appliances and Systems. By CLEMENT E. STRETTON, C.E., Vice-President and Consulting Engineer, Amalgamated Society of Railway Servants. With Illustrations and Coloured Plates. Third Edition, Enlarged. Crown 8vo, cloth 3/6

"A book for the engineer, the directors, the managers; and, in short, all who wish for information on railway matters will find a perfect encyclopædia in 'Safe Railway Working.'"—*Railway Review*.

"We commend the remarks on railway signalling to all railway managers, especially where a uniform code and practice is advocated."—*Herepath's Railway Journal*.

"The author may be congratulated on having collected, in a very convenient form, much valuable information on the principal questions affecting the safe working of railways."—*Railway Engineer*.

EXPANSION OF STRUCTURES BY HEAT.

By JOHN KEILY, C.E., late of the Indian Public Works Department. Crown 8vo, cloth 3/6

"The aim the author has set before him, viz., to show the effects of heat upon metallic and other structures, is a laudable one, for this is a branch of physics upon which the engineer or architect can find but little reliable and comprehensive data in books."—*Builder*.

A TREATISE ON FIELD FORTIFICATION.

The Attack of Fortresses, Military Mining, and Reconnoitring. By Professor Colonel I. S. MACAULAY. Sixth Edition, crown 8vo, with separate Atlas of 12 Plates, cloth 12/0

RECORD OF THE PROGRESS OF MODERN ENGINEERING.

Complete in Four Volumes, imperial 4to, half-morocco, price **£12 12s.**

Each volume sold separately, as follows:—

FIRST SERIES, Comprising Civil, Mechanical, Marine, Hydraulic, Railway, Bridge, and other Engineering Works, &c. By **WILLIAM HUMBER**, A. M. Inst. C.E., &c. Imp. 4to, with 36 Double Plates, drawn to a large scale, Photographic Portrait of John Hawkshaw, C.E., F.R.S., &c., and copious descriptive Letterpress, Specifications, &c. Half-morocco . . . **£3 3s.**

LIST OF THE PLATES AND DIAGRAMS.

VICTORIA STATION AND ROOF, L. B. & S. C. R. (8 PLATES); SOUTHPORT PIER (2 PLATES); VICTORIA STATION AND ROOF, L. C. & D. AND G. W. R. (6 PLATES); ROOF OF CREMORNE MUSIC HALL; BRIDGE OVER G. N. RAILWAY; ROOF OF STATION, DUTCH RHENISH RAIL. (2 PLATES); BRIDGE OVER THE THAMES, WEST LONDON EXTENSION RAILWAY (5 PLATES); ARMOUR PLATES: SUSPENSION BRIDGE, THAMES (4 PLATES); THE ALLEN ENGINE; SUSPENSION BRIDGE, AVON (3 PLATES); UNDERGROUND RAILWAY (3 PLATES).

HUMBER'S PROGRESS OF MODERN ENGINEERING.

SECOND SERIES. Imp. 4to, with 3 Double Plates, Photographic Portrait of Robert Stephenson, C.E., M.P., F.R.S., &c., and copious descriptive Letterpress, Specifications, &c. Half-morocco . . . **£3 3s.**

LIST OF THE PLATES AND DIAGRAMS.

BIRKENHEAD DOCKS, LOW WATER BASIN (15 PLATES); CHARING CROSS STATION ROOF, C. C. RAILWAY (3 PLATES); DIGSWELL VIADUCT, GREAT NORTHERN RAILWAY; ROBBERY WOOD VIADUCT, GREAT NORTHERN RAILWAY; IRON PERMANENT WAY; CLYDACH VIADUCT, MERTHYR, TREDEGAR, AND ABERGAVENNY RAILWAY; EBBW VIADUCT, MERTHYR, TREDEGAR, AND ABERGAVENNY RAILWAY; COLLEGE WOOD VIADUCT, CORNWALL RAILWAY; DUBLIN WINTER PALACE ROOF (3 PLATES); BRIDGE OVER THE THAMES, L. C. & D. RAILWAY (6 PLATES); ALBERT HARBOUR, GREENOCK (4 PLATES).

HUMBER'S PROGRESS OF MODERN ENGINEERING.

THIRD SERIES. Imp. 4to, with 40 Double Plates, Photographic Portrait of J. R. McClean, late Pres. Inst. C.E., and copious descriptive Letterpress, Specifications, &c. Half-morocco . . . **£3 3s.**

LIST OF THE PLATES AND DIAGRAMS.

MAIN DRAINAGE, METROPOLIS.—*North Side*.—MAP SHOWING INTERCEPTION OF SEWERS; MIDDLE LEVEL SEWER (2 PLATES); OUTFALL SEWER, BRIDGE OVER RIVER LEA (3 PLATES); OUTFALL SEWER, BRIDGE OVER MARSH LANE, NORTH WOOLWICH RAILWAY, AND BOW AND BARKING RAILWAY JUNCTION; OUTFALL SEWER, BRIDGE OVER BOW AND BARKING RAILWAY (3 PLATES); OUTFALL SEWER, BRIDGE OVER EAST LONDON WATER-WORKS' FREDER (2 PLATES); OUTFALL SEWER RESERVOIR (2 PLATES); OUTFALL SEWER, TUMBLING BAY AND OUTLET; OUTFALL SEWER, TENSTOCKS. *South Side*.—OUTFALL SEWER, BERMONDSEY BRANCH (2 PLATES); OUTFALL SEWER, RESERVOIR AND OUTLET (4 PLATES); OUTFALL SEWER, FILTH HOIST; SECTIONS OF SEWERS (NORTH AND SOUTH SIDES).

THAMES EMBANKMENT.—SECTION OF RIVER WALL; STEAMBOAT PIER, WESTMINSTER (2 PLATES); LANDING STAIRS BETWEEN CHARING CROSS AND WATERLOO BRIDGES; YORK GATE (2 PLATES); OVERFLOW AND OUTLET AT SAVOY STREET SEWER (3 PLATES); STEAMBOAT PIER, WATERLOO BRIDGE (3 PLATES); JUNCTION OF SEWERS, PLANS AND SECTIONS; GULLIES, PLANS AND SECTIONS; ROLLING STOCK; GRANITE AND IRON FORTS.

HUMBER'S PROGRESS OF MODERN ENGINEERING.

FOURTH SERIES. Imp. 4to, with 36 Double Plates, Photographic Portrait of John Fowler, late Pres. Inst. C.E., and copious descriptive Letterpress, Specifications, &c. Half-morocco . . . **£3 3s.**

LIST OF THE PLATES AND DIAGRAMS.

ABBEY MILLS PUMPING STATION, MAIN DRAINAGE, METROPOLIS (4 PLATES); BARROW DOCKS (5 PLATES); MANQUIS VIADUCT, SANTIAGO AND VALPARAISO RAILWAY, (2 PLATES); ADAM'S LOCOMOTIVE, ST. HELEN'S CANAL RAILWAY (2 PLATES); CANNON STREET STATION ROOF, CHARING CROSS RAILWAY (3 PLATES); ROAD BRIDGE OVER THE RIVER MOKA (2 PLATES); TELEGRAPHIC APPARATUS FOR MESOPOTAMIA; VIADUCT OVER THE RIVER WYE, MIDLAND RAILWAY (3 PLATES); ST. GERMAN'S VIADUCT, CORNWALL RAILWAY (2 PLATES); WROUGHT-IRON CYLINDER FOR DIVING BELL; MILLWALL DOCKS (6 PLATES); MILROY'S PATENT EXCAVATOR; METROPOLITAN DISTRICT RAILWAY (6 PLATES); HARBOURS, PORTS, AND BREAKWATERS (3 PLATES).

THE POPULAR WORKS OF MICHAEL REYNOLDS.

LOCOMOTIVE ENGINE DRIVING.

A Practical Manual for Engineers in Charge of Locomotive Engines. By MICHAEL REYNOLDS, Member of the Society of Engineers, formerly Locomotive Inspector, L. B. & S. C. R. Ninth Edition. Including a KEY TO THE LOCOMOTIVE ENGINE. With Illustrations and Portrait of Author. Crown 8vo, cloth 4/6

"Mr. Reynolds has supplied a want, and has supplied it well. We can confidently recommend the book not only to the practical driver, but to everyone who takes an interest in the performance of locomotive engines."—*The Engineer*.

"Mr. Reynolds has opened a new chapter in the literature of the day. This admirable practical treatise, of the practical utility of which we have to speak in terms of warm commendation."—*Athenaeum*.

"Evidently the work of one who knows his subject thoroughly."—*Railway Service Gazette*.

"Were the cautions and rules given in the book to become part of the every-day working of our engine-drivers, we might have fewer distressing accidents to deplore."—*Scotsman*.

STATIONARY ENGINE DRIVING.

A Practical Manual for Engineers in Charge of Stationary Engines. By MICHAEL REYNOLDS. Fifth Edition, Enlarged. With Plates and Woodcuts. Crown 8vo, cloth 4/6

"The author is thoroughly acquainted with his subjects, and his advice on the various points treated is clear and practical. . . . He has produced a manual which is an exceedingly useful one for the class for whom it is specially intended."—*Engineering*.

"Our author leaves no stone unturned. He is determined that his readers shall not only know something about the stationary engine, but all about it."—*Engineer*.

"An engineman who has mastered the contents of Mr. Reynolds's book will require but little actual experience with boilers and engines before he can be trusted to look after them."—*English Mechanic*.

THE MODEL LOCOMOTIVE ENGINEER,

Fireman, and Engine-Boy. Comprising a Historical Notice of the Pioneer Locomotive Engines and their Inventors. By MICHAEL REYNOLDS. Second Edition, with Revised Appendix. With numerous Illustrations, and Portrait of George Stephenson. Crown 8vo, cloth. [Just Published. 4/6

"From the technical knowledge of the author, it will appeal to the railway man of to-day more forcibly than anything written by Dr. Smiles. . . . The volume contains information of a technical kind, and facts that every driver should be familiar with."—*English Mechanic*.

"We should be glad to see this book in the possession of everyone in the kingdom who has ever laid, or is to lay, hands on a locomotive engine."—*Iron*.

CONTINUOUS RAILWAY BRAKES.

A Practical Treatise on the several Systems in Use in the United Kingdom: their Construction and Performance. With copious Illustrations and numerous Tables. By MICHAEL REYNOLDS. Large crown 8vo, cloth 9/0

"A popular explanation of the different brakes. It will be of great assistance in forming public opinion, and will be studied with benefit by those who take an interest in the brake."—*English Mechanic*.

"Written with sufficient technical detail to enable the principal and relative connection of the various parts of each particular brake to be readily grasped."—*Mechanical World*.

ENGINE-DRIVING LIFE.

Stirring Adventures and Incidents in the Lives of Locomotive Engine-Drivers. By MICHAEL REYNOLDS. Third Edition. Crown 8vo, cloth . . . 1/6

"From first to last perfectly fascinating. Wilkie Collins's most thrilling conceptions are thrown into the shade by true incidents, endless in their variety, related in every page."—*North British Mail*.

"Anyone who wishes to get a real insight into railway life cannot do better than read 'Engine-Driving Life' for himself, and if he once takes it up he will find that the author's enthusiasm and real love of the engine-driving profession will carry him on until he has read every page."—*Saturday Review*.

THE ENGINEMAN'S POCKET COMPANION,

And Practical Educator for Enginemen, Boiler Attendants, and Mechanics. By MICHAEL REYNOLDS. With 45 Illustrations and numerous Diagrams. Third Edition, Revised. Royal 18mo, strongly bound for pocket wear 3/6

"This admirable work is well suited to accomplish its object, being the honest workmanship of a competent engineer."—*Glasgow Herald*.

"A most meritorious work, giving in a succinct and practical form all the information an engine-minder desirous of mastering the scientific principles of his daily calling would require."—*The Miller*.

"A boon to those who are striving to become efficient mechanics."—*Daily Chronicle*.

MARINE ENGINEERING, SHIPBUILDING, NAVIGATION, &c.

THE NAVAL ARCHITECT'S AND SHIPBUILDER'S POCKET-BOOK of Formulae, Rules, and Tables, and Marine Engineer's and Surveyor's Handy Book of Reference. By CLEMENT MACKROW, M.I.N.A. Sixth Edition, Revised, 700 pp., with 300 Illustrations. Fcap., leather. **12/6**

SUMMARY OF CONTENTS:—SIGNS AND SYMBOLS, DECIMAL FRACTIONS.—TRIGONOMETRY.—PRACTICAL GEOMETRY.—MENSURATION.—CENTRES AND MOMENTS OF FIGURES.—MOMENTS OF INERTIA AND RADII OF GYRATION.—ALGEBRAICAL EXPRESSIONS FOR SIMPSON'S RULES.—MECHANICAL PRINCIPLES.—CENTRE OF GRAVITY.—LAWS OF MOTION.—DISPLACEMENT.—CENTRE OF BUOYANCY.—CENTRE OF GRAVITY OF SHIP'S HULL.—STABILITY CURVES AND METACENTRES.—SEA AND SHALLOW-WATER WAVES.—ROLLING OF SHIPS.—PROPULSION AND RESISTANCE OF VESSELS.—SPEED TRIALS.—SAILING, CENTRE OF EFFORT.—DISTANCES DOWN RIVERS, COAST LINES.—STEERING AND RUDDERS OF VESSELS.—LAUNCHING CALCULATIONS AND VELOCITIES.—WEIGHT OF MATERIAL AND GEAR.—GUN PARTICULARS AND WEIGHT.—STANDARD GAUGES.—RIVETED JOINTS AND RIVETING.—STRENGTH AND TESTS OF MATERIALS.—BINDING AND SHEARING STRESSES, &c.—STRENGTH OF SHAFTING, PILLARS, WHEELS, &c.—HYDRAULIC DATA, &c.—CONIC SECTIONS, CATENARIAN CURVES.—MECHANICAL POWERS, WORK.—BOARD OF TRADE REGULATIONS FOR BOILERS AND ENGINES.—BOARD OF TRADE REGULATIONS FOR SHIPS.—LLOYD'S RULES FOR BOILERS.—LLOYD'S WEIGHT OF CHAINS.—LLOYD'S SCANTLINGS FOR SHIPS.—DATA OF ENGINES AND VESSELS.—SHIPS' FITTINGS AND TESTS.—SEASONING PRESERVING TIMBER.—MEASUREMENT OF TIMBER.—ALLOYS, PAINTS, VARNISHES.—DATA FOR STOWAGE.—ADMIRALTY TRANSPORT REGULATIONS.—RULES FOR HORSE-POWER, SCREW PROPELLERS, &c.—PERCENTAGES FOR BUTT STRAPS, &c.—PARTICULARS OF YACHTS.—MASTING AND RIGGING VESSELS.—DISTANCES OF FOREIGN PORTS.—TONNAGE TABLES.—VOCABULARY OF FRENCH AND ENGLISH TERMS.—ENGLISH WEIGHTS AND MEASURES.—FOREIGN WEIGHTS AND MEASURES.—DECIMAL EQUIVALENTS.—FOREIGN MONEY.—DISCOUNT AND WAGES TABLES.—USEFUL NUMBERS AND READY RECKONERS.—TABLES OF CIRCULAR MEASURES.—TABLES OF AREAS OF AND CIRCUMFERENCES OF CIRCLES.—TABLES OF AREAS OF SEGMENTS OF CIRCLES.—TABLES OF SQUARES AND CUBES AND ROOTS OF NUMBERS.—TABLES OF LOGARITHMS OF NUMBERS.—TABLES OF HYPERBOLIC LOGARITHMS.—TABLES OF NATURAL SINES, TANGENTS, &c.—TABLES OF LOGARITHMIC SINES, TANGENTS, &c.

"In these days of advanced knowledge a work like this is of the greatest value. It contains a vast amount of information. We unhesitatingly say that it is the most valuable compilation for its specific purpose that has ever been printed. No naval architect, engineer, surveyor, or seaman, wood or iron shipbuilder can afford to be without this work."—*Nautical Magazine*.

"Should be used by all who are engaged in the construction or design of vessels. . . . Will be found to contain the most useful tables and formulae required by shipbuilders, carefully collected from the best authorities, and put together in a popular and simple form. The book is one of exceptional merit."—*Engineer*.

"The professional shipbuilder has now, in a convenient and accessible form, reliable data for solving many of the numerous problems that present themselves in the course of his work."—*Iron*.

"There is no doubt that a pocket-book of this description must be a necessity in the shipbuilding trade. . . . The volume contains a mass of useful information clearly expressed and presented in a handy form."—*Marine Engineer*.

MARINE ENGINES AND STEAM VESSELS.

A Treatise on. By ROBERT MURRAY, C.E. Eighth Edition, thoroughly Revised, with considerable Additions by the Author and by GEORGE CARLISLE, C.E., Senior Surveyor to the Board of Trade at Liverpool. 12mo, cloth. **4/6**

"Well adapted to give the young steamship engineer or marine engine and boiler maker a general introduction into his practical work."—*Mechanical World*.

"We feel sure that this thoroughly revised edition will continue to be as popular in the future as it has been in the past, as, for its size, it contains more useful information than any similar treatise."—*Industries*.

"The information given is both sound and sensible, and well qualified to direct young seagoing hands on the straight road to the extra chief's certificate. . . . Most useful to surveyors, inspectors, draughtsmen, and all young engineers who take an interest in their profession."—*Glasgow Herald*.

SEA TERMS, PHRASES, AND WORDS

(Technical Dictionary of) used in the English and French Languages (English-French, French-English). For the Use of Seamen, Engineers, Pilots, Shipbuilders, Shipowners, and Ship-brokers. Compiled by W. PIRRIE, late of the African Steamship Company. Fcap. 8vo, cloth limp. [Just Published. **5/0**

"This volume will be highly appreciated by seamen, engineers, pilots, shipbuilders and shipowners. It will be found wonderfully accurate and complete."—*Scotsman*.

"A very useful dictionary, which has long been wanted by French and English engineers, masters, officers and others."—*Shipping World*.

ELECTRIC SHIP LIGHTING.

A Handbook on the Practical Fitting and Running of Ships' Electrical Plant, for the Use of Shipowners and Builders, Marine Electricians and Sea-going Engineers in Charge. By J. W. URQUHART, Author of "Electric Light," "Dynamo Construction," &c. With numerous Illustrations. Crown 8vo, cloth **7/6**

MARINE ENGINEERS' POCKET-BOOK.

Consisting of useful Tables and Formulæ. By FRANK PROCTOR, A.I.N.A. Third Edition. Royal 32mo, leather, gilt edges, with strap **4/0**

"We recommend it to our readers as going far to supply a long-felt want."—*Naval Science*.
 "A most useful companion to all marine engineers."—*United Service Gazette*.

ELEMENTARY ENGINEERING.

A Manual for Young Marine Engineers and Apprentices. In the Form of Questions and Answers on Metals, Alloys, Strength of Materials, Construction and Management of Marine Engines and Boilers, Geometry, &c., &c. With an Appendix of Useful Tables. By JOHN SHERREN BREWER, Government Marine Surveyor, Hong Kong. Third Edition, small crown 8vo, cloth **1/6**

"Contains much valuable information for the class for whom it is intended, especially in the chapters on the management of boilers and engines."—*Nautical Magazine*.

"A useful introduction to the more elaborate text-books."—*Scotsman*.

"To a student who has the requisite desire and resolve to attain a thorough knowledge Mr. Brewer offers decidedly useful help."—*Athenæum*.

PRACTICAL NAVIGATION.

Consisting of THE SAILOR'S SEA-BOOK, by JAMES GREENWOOD and W. H. ROSSER; together with the requisite Mathematical and Nautical Tables for the Working of the Problems, by HENRY LAW, C.E., and Professor J. K. YOUNG. Illustrated. 12mo, strongly half-bound **7/0**

MARINE ENGINEER'S DRAWING-BOOK.

Adapted to the Requirements of the Board of Trade Examinations. By JOHN LOCKIE, C.E. With 22 Plates, Drawn to Scale. Royal 8vo, cloth . . . **3/6**

"The student who learns from these drawings will have nothing to unlearn."—*Engineer*.

"The examples chosen are essentially practical, and are such as should prove of service to engineers generally, while admirably fulfilling their specific purpose."—*Mechanical World*.

THE ART AND SCIENCE OF SAILMAKING.

By SAMUEL B. SADLER, Practical Sailmaker, late in the employment of Messrs. Ratsey and Lapthorne, of Cowes and Gosport. With Plates and other Illustrations. Small 4to, cloth **12/6**

"This extremely practical work gives a complete education in all the branches of the manufacture, cutting out, roping, seaming, and goring. It is copiously illustrated, and will form a first-rate text-book and guide."—*Portsmouth Times*.

"The author of this work has rendered a distinct service to all interested in the art of sailmaking. The subject of which he treats is a congenial one. Mr. Sadler is a practical sailmaker, and has devoted years of careful observation and study to the subject; and the results of the experience thus gained he has set forth in the volume before us."—*Steamship*.

CHAIN CABLES AND CHAINS.

Comprising Sizes and Curves of Links, Studs, &c., Iron for Cables and Chains, Chain Cable and Chain Making, Forming and Welding Links, Strength of Cables and Chains, Certificates for Cables, Marking Cables, Prices of Chain Cables and Chains, Historical Notes, Acts of Parliament, Statutory Tests, Charges for Testing, List of Manufacturers of Cables, &c., &c. By THOMAS W. TRAILL, F.E.R.N., M.Inst.C.E., Engineer-Surveyor-in-Chief, Board of Trade, Inspector of Chain Cable and Anchor Proving Establishments, and General Superintendent Lloyd's Committee on Proving Establishments. With numerous Tables, Illustrations, and Lithographic Drawings. Folio, cloth, bevelled boards **£2 2s.**

"It contains a vast amount of valuable information. Nothing seems to be wanting to make it a complete and standard work of reference on the subject."—*Nautical Magazine*.

MINING AND METALLURGY.

COLLIERY WORKING AND MANAGEMENT.

Comprising the Duties of a Colliery Manager, the Oversight and Arrangement of Labour and Wages, and the different Systems of Working Coal Seams. By H. F. BULMAN and R. A. S. REDMAYNE. 350 pp., with 28 Plates and other Illustrations, including Underground Photographs. Medium 8vo, cloth. [Just Published. 18/0

"This is, indeed, an admirable Handbook for Colliery Managers, in fact it is an indispensable adjunct to a Colliery Manager's education, as well as being a most useful and interesting work on the subject for all who in any way have to do with coal mining. The underground photographs are an attractive feature of the work, being very lifelike and necessarily true representations of the scenes they depict."—*Colliery Guardian*.

"Mr. Bulman and Mr. Redmayne, who are both experienced Colliery Managers of great literary ability, are to be congratulated on having supplied an authoritative work dealing with a side of the subject of coal mining which has hitherto received but scant treatment. The authors elucidate their text by 119 woodcuts and 28 plates, most of the latter being admirable reproductions of photographs taken underground with the aid of the magnesium flash-light. These illustrations are excellent."—*Nature*.

INFLAMMABLE GAS AND VAPOUR IN THE AIR

(The Detection and Measurement of). By FRANK CLOWES, D.Sc., Lond., F.I.C., Prof. of Chemistry in the University College, Nottingham. With a Chapter on THE DETECTION AND MEASUREMENT OF PETROLEUM VAPOUR by BOVERTON REDWOOD, F.R.S.E., Consulting Adviser to the Corporation of London under the Petroleum Acts. Crown 8vo, cloth.

[Just Published. Net. 5/0

"Professor Clowes has given us a volume on a subject of much industrial importance . . . Those interested in these matters may be recommended to study this book, which is easy of comprehension and contains many good things."—*The Engineer*.

"A convenient summary of the work on which Professor Clowes has been engaged for some considerable time. . . . It is hardly necessary to say that any work on these subjects with these names on the title-page must be a valuable one, and one that no mining engineer—certainly no coal miner—can afford to ignore or to leave unread."—*Mining Journal*.

MACHINERY FOR METALLIFEROUS MINES.

A Practical Treatise for Mining Engineers, Metallurgists, and Managers of Mines. By E. HENRY DAVIES, M.E., F.G.S. Crown 8vo, 580 pp., with upwards of 300 Illustrations, cloth. [Just Published. 12/6

"Mr. Davies, in this handsome volume, has done the advanced student and the manager of mines good service. Almost every kind of machinery in actual use is carefully described, and the woodcuts and plates are good."—*Athenaeum*.

"From cover to cover the work exhibits all the same characteristics which excite the confidence and attract the attention of the student as he peruses the first page. The work may safely be recommended. By its publication the literature connected with the industry will be enriched and the reputation of its author enhanced."—*Mining Journal*.

METALLIFEROUS MINERALS AND MINING.

By D. C. DAVIES, F.G.S., Mining Engineer, &c., Author of "A Treatise on Slate and Slate Quarrying." Fifth Edition, thoroughly Revised and much Enlarged by his Son, E. HENRY DAVIES, M.E., F.G.S. With about 150 Illustrations. Crown 8vo, cloth. . . . 12/6

"Neither the practical miner nor the general reader, interested in mines, can have a better book for his companion and his guide."—*Mining Journal*.

"We are doing our readers a service in calling their attention to this valuable work."—*Mining World*.

"As a history of the present state of mining throughout the world this book has a real value, and it supplies an actual want."—*Athenaeum*.

EARTHY AND OTHER MINERALS AND MINING.

By D. C. DAVIES, F.G.S., Author of "Metalliferous Minerals," &c. Third Edition, Revised and Enlarged by his Son, E. HENRY DAVIES, M.E., F.G.S. With about 100 Illustrations. Crown 8vo, cloth. . . . 12/6

"We do not remember to have met with any English work on mining matters that contains the same amount of information packed in equally convenient form."—*Academy*.

"We should be inclined to rank it as among the very best of the handy technical and trades manuals which have recently appeared."—*British Quarterly Review*.

BRITISH MINING.

A Treatise on the History, Discovery, Practical Development, and Future Prospects of Metalliferous Mines in the United Kingdom. By ROBERT HUNT, F.R.S., late Keeper of Mining Records. Upwards of 950 pp., with 230 Illustrations. Second Edition, Revised. Super-royal 8vo, cloth **£2 2s.**

"The book is a treasure-house of statistical information on mining subjects, and we know of no other work embodying so great a mass of matter of this kind. Were this the only merit of Mr. Hunt's volume it would be sufficient to render it indispensable in the library of every one interested in the development of the mining and metallurgical industries of this country."—*Athenæum*.

"A mass of information not elsewhere available, and of the greatest value to those who may be interested in our great mineral industries."—*Engineer*.

MINE DRAINAGE.

A Complete and Practical Treatise on Direct-Acting Underground Steam Pumping Machinery, with a Description of a large number of the best known Engines, their General Utility and the Special Sphere of their Action, the Mode of their Application, and their merits compared with other forms of Pumping Machinery. By STEPHEN MICHELL. 8vo, cloth **15/0**

"Will be highly esteemed by colliery owners and lessees, mining engineers, and students generally who require to be acquainted with the best means of securing the drainage of mines. It is a most valuable work, and stands almost alone in the literature of steam pumping machinery."—*Colliery Guardian*.

"Much valuable information is given, so that the book is thoroughly worthy of an extensive circulation amongst practical men and purchasers of machinery."—*Mining Journal*.

THE PROSPECTOR'S HANDBOOK.

A Guide for the Prospector and Traveller in search of Metal-Bearing or other Valuable Minerals. By J. W. ANDERSON, M.A. (Camb.), F.R.G.S., Author of "Fiji and New Caledonia." Seventh Edition, thoroughly Revised and much Enlarged. Small crown 8vo, cloth, **3/6**; or, leather, pocket-book form, with tuck. [Just Published. **4/6**.

"Will supply a much-felt want, especially among Colonists, in whose way are so often thrown many mineralogical specimens the value of which it is difficult to determine."—*Engineer*.

"How to find commercial minerals, and how to identify them when they are found, are the leading points to which attention is directed. The author has managed to pack as much practical detail into his pages as would supply material for a book three times its size."—*Mining Journal*.

NOTES AND FORMULÆ FOR MINING STUDENTS.

By JOHN HERMAN MERIVALE, M.A., Late Professor of Mining in the Durham College of Science, Newcastle-upon-Tyne. Fourth Edition, Revised and Enlarged. By H. F. BULMAN, A.M.Inst.C.E. Small crown 8vo, cloth.

[Just Published. **2/6**

"The author has done his work in a creditable manner, and has produced a book that will be of service to students and those who are practically engaged in mining operations."—*Engineer*

THE MINER'S HANDBOOK.

A Handy Book of Reference on the subjects of Mineral Deposits, Mining Operations, Ore Dressing, &c. For the Use of Students and others interested in Mining Matters. By JOHN MILNE, F.R.S., Professor of Mining in the Imperial University of Japan. Revised Edition. Fcap. 8vo, leather. **7/6**

"Professor Milne's handbook is sure to be received with favour by all connected with mining, and will be extremely popular among students."—*Athenæum*.

POCKET-BOOK for MINERS and METALLURGISTS.

Comprising Rules, Formulæ, Tables, and Notes for Use in Field and Office Work. By F. DANVERS POWER, F.G.S., M.E. Fcap. 8vo, leather. **9/0**

"This excellent book is an admirable example of its kind, and ought to find a large sale amongst English-speaking prospectors and mining engineers."—*Engineering*.

MINERAL SURVEYOR and VALUER'S GUIDE.

Comprising a Treatise on Improved Mining Surveying and the Valuation of Mining Properties, with New Traverse Tables. By WM. LINTERN. Fourth Edition, Enlarged. 12mo, cloth **3/6**

THE COLLIERY MANAGER'S HANDBOOK.

A Comprehensive Treatise on the Laying-out and Working of Collieries, Designed as a Book of Reference for Colliery Managers, and for the Use of Coal Mining Students preparing for First-class Certificates. By **CALEB PAMELY**, Mining Engineer and Surveyor; Member of the North of England Institute of Mining and Mechanical Engineers; and Member of the South Wales Institute of Mining Engineers. With 700 Plans, Diagrams, and other Illustrations. Fourth Edition, Revised and Enlarged, medium 8vo, over 900 pp. Strongly bound **£1 8s.**

SUMMARY OF CONTENTS:—GEOLOGY.—SEARCH FOR COAL.—MINERAL LEASES AND OTHER HOLDINGS.—SHAFT SINKING.—FITTING UP THE SHAFT AND SURFACE ARRANGEMENTS.—STEAM BOILERS AND THEIR FITTINGS.—TIMBERING AND WALLING.—NARROW WORK AND METHODS OF WORKING.—UNDERGROUND CONVEYANCE.—DRAINAGE.—THE GASES MET WITH IN MINES; VENTILATION.—ON THE FRICTION OF AIR IN MINES.—THE PRIESTMAN OIL ENGINE; PETROLEUM AND NATURAL GAS.—SURVEYING AND PLANNING.—SAFETY LAMPS AND FIREDAMP DETECTORS.—SUNDRY AND INCIDENTAL OPERATIONS AND APPLIANCES.—COLLIERY EXPLOSIONS.—MISCELLANEOUS QUESTIONS AND ANSWERS.—Appendix: SUMMARY OF REPORT OF H.M. COMMISSIONERS ON ACCIDENTS IN MINES.

"Mr. Pameley has not only given us a comprehensive reference book of a very high order, suitable to the requirements of mining engineers and colliery managers, but has also provided mining students with a class-book that is as interesting as it is instructive."—*Colliery Manager*.

"Mr. Pameley's work is eminently suited to the purpose for which it is intended, being clear, interesting, exhaustive, rich in detail, and up to date, giving descriptions of the latest machines in every department. A mining engineer could scarcely go wrong who followed this work."—*Colliery Guardian*.

"This is the most complete 'all-round' work on coal-mining published in the English language. . . . No library of coal-mining books is complete without it."—*Colliery Engineer* (Scranton, Pa., U.S.A.).

COAL & IRON INDUSTRIES of the UNITED KINGDOM.

Comprising a Description of the Coal Fields, and of the Principal Seams of Coal, with Returns of their Produce and its Distribution, and Analyses of Special Varieties. Also, an Account of the Occurrence of Iron: Ores in Veins or Seams; Analyses of each Variety; and a History of the Rise and Progress of Pig Iron Manufacture. By **RICHARD MEADE**. 8vo, cloth . . . **£1 8s.**

"Of this book we may unreservedly say that it is the best of its class which we have ever met. . . . A book of reference which no one engaged in the Iron or coal trades should omit from his library."—*Iron and Coal Trades Review*.

COAL AND COAL MINING.

By the late Sir **WARINGTON W. SMYTH, M.A., F.R.S., &c.**, Chief Inspector of the Mines of the Crown. Seventh Edition, Revised and Enlarged. With numerous Illustrations, 12mo, cloth . . . **3/6**

"As an outline is given of every known coal-field in this and other countries, as well as of the principal methods of working, the book will doubtless interest a very large number of readers."—*Mining Journal*.

ASBESTOS AND ASBESTIC.

Their Properties, Occurrence, and Use. By **ROBERT H. JONES, F.S.A.**, Mineralogist, Hon. Mem. Asbestos Club, Black Lake, Canada. With Ten Collotype Plates and other Illustrations. Demy 8vo, cloth. [Just Published. **16/0**

"An interesting and invaluable work."—*Colliery Guardian*

SUBTERRANEAN SURVEYING

(Elementary and Practical Treatise on), with and without the Magnetic Needle. By **THOMAS FENWICK**, Surveyor of Mines, and **THOMAS BAKER, C.E.** Illustrated. 12mo, cloth **2/6**

GRANITES AND OUR GRANITE INDUSTRIES.

By **GEORGE F. HARRIS, F.G.S.**, Membre de la Société Belge de Géologie, Lecturer on Economic Geology at the Birkbeck Institution, &c. With Illustrations. Crown 8vo, cloth **2/6**

"A clearly and well-written manual for persons engaged or interested in the granite industry."—*Scotsman*.

THE METALLURGY OF GOLD.

A Practical Treatise on the Metallurgical Treatment of Gold-bearing Ores. Including the Processes of Concentration, Chlorination, and Extraction by Cyanide, and the Assaying, Melting, and Refining of Gold. By M. EISSLER, Mining Engineer and Metallurgical Chemist, formerly Assistant Assayer of the U.S. Mint, San Francisco. Fourth Edition, Enlarged. With about 250 Illustrations and numerous Folding Plates and Working Drawings. Large crown 8vo, cloth.

[Just Published. 18/0

"This book thoroughly deserves its title of a 'Practical Treatise.' The whole process of gold milling, from the breaking of the quartz to the assay of the bullion, is described in clear and orderly narrative and with much, but not too much, fulness of detail."—*Saturday Review*.

"The work is a storehouse of information and valuable data, and we strongly recommend it to all professional men engaged in the gold-mining industry."—*Mining Journal*.

THE CYANIDE PROCESS OF GOLD EXTRACTION.

Including its Practical Application on the Witwatersrand Gold Fields in South Africa. By M. EISSLER, M.E., Author of "The Metallurgy of Gold," &c. With Diagrams and Working Drawings. Second Edition, Revised and Enlarged. 8vo, cloth.

[Just Published. 7/6

"This book is just what was needed to acquaint mining men with the actual working of a process which is not only the most popular, but is, as a general rule, the most successful for the extraction of gold from tailings."—*Mining Journal*.

"The work will prove invaluable to all interested in gold mining, whether metallurgists or as investors."—*Chemical News*.

THE METALLURGY OF SILVER.

A Practical Treatise on the Amalgamation, Roasting, and Lixiviation of Silver Ores. Including the Assaying, Melting, and Refining of Silver Bullion. By M. EISSLER, Author of "The Metallurgy of Gold," &c. Third Edition. Crown 8vo, cloth 10/6

"A practical treatise, and a technical work which we are convinced will supply a long-felt want amongst practical men, and at the same time be of value to students and others indirectly connected with the industries."—*Mining Journal*.

"From first to last the book is thoroughly sound and reliable."—*Colliery Guardian*.

"For chemists, practical miners, assayers, and investors alike we do not know of any work on the subject so handy and yet so comprehensive."—*Glasgow Herald*.

THE METALLURGY OF ARGENTIFEROUS LEAD.

A Practical Treatise on the Smelting of Silver-Lead Ores and the Refining of Lead Bullion. Including Reports on various Smelting Establishments and Descriptions of Modern Smelting Furnaces and Plants in Europe and America. By M. EISSLER, M.E., Author of "The Metallurgy of Gold," &c. Crown 8vo, 400 pp., with 183 Illustrations, cloth 12/6

"The numerous metallurgical processes, which are fully and extensively treated of, embrace all the stages experienced in the passage of the lead from the various natural states to its issue from the refinery as an article of commerce."—*Practical Engineer*.

"The present volume fully maintains the reputation of the author. Those who wish to obtain a thorough insight into the present state of this industry cannot do better than read this volume, and all mining engineers cannot fail to find many useful hints and suggestions in it."—*Industries*.

METALLURGY OF IRON.

By H. BAUERMAN, F.G.S., A.R.S.M. Sixth Edition, Revised and Enlarged. 12mo, cloth 5/0

THE IRON ORES of GREAT BRITAIN and IRELAND.

Their Mode of Occurrence, Age and Origin, and the Methods of Searching for and Working Them. With a Notice of some of the Iron Ores of Spain. By J. D. KENDALL, F.G.S., Mining Engineer. Crown 8vo, cloth 18/0

"The author has a thorough practical knowledge of his subject, and has supplemented a careful study of the available literature by unpublished information derived from his own observations. The result is a very useful volume, which cannot fail to be of value to all interested in the iron industry of the country."—*Industries*.

ELECTRICITY, ELECTRICAL ENGINEERING, &c.

SUBMARINE TELEGRAPHS.

Their History, Construction, and Working. Founded in part on WÜNSCHEN-DORFF'S "Traité de Télégraphie Sous-Marine," and Compiled from Authoritative and Exclusive Sources. By CHARLES BRIGHT, F.R.S.E. Super-royal 8vo, about 780 pp., fully Illustrated, [Just Published. Net, £3 3s.

THE ELECTRICAL ENGINEER'S POCKET-BOOK.

Consisting of Modern Rules, Formulæ, Tables, and Data. By H. R. KEMPE, M.Inst.E.E., A.M.Inst.C.E., Technical Officer Postal Telegraphs, Author of "A Handbook of Electrical Testing," "The Engineer's Year-Book," &c. Second Edition, thoroughly Revised, with Additions. With numerous Illustrations. Royal 32mo, oblong, leather 5/0

"There is very little in the shape of formulæ or data which the electrician is likely to want in a hurry which cannot be found in its pages."—*Practical Engineer*.

"A very useful book of reference for daily use in practical electrical engineering and its various applications to the industries of the present day."—*Iron*.

"It is the best book of its kind."—*Electrical Engineer*.

"The Electrical Engineer's Pocket-Book is a good one."—*Electrician*.

"Strongly recommended to those engaged in the electrical industries."—*Electrical Review*.

ELECTRIC LIGHT FITTING.

A Handbook for Working Electrical Engineers, embodying Practical Notes on Installation Management. By J. W. URQUHART, Electrician, Author of "Electric Light," &c. With numerous Illustrations. Third Edition, Revised, with Additions. Crown 8vo, cloth, [Just Published. 5/0

"This volume deals with what may be termed the mechanics of electric lighting, and is addressed to men who are already engaged in the work, or are training for it. The work traverses a great deal of ground, and may be read as a sequel to the same author's useful work on 'Electric Light.'"—*Electrician*.

"This is an attempt to state in the simplest language the precautions which should be adopted in installing the electric light, and to give information for the guidance of those who have to run the plant when installed. The book is well worth the perusal of the workman, for whom it is written."—*Electrical Review*.

"Eminently practical and useful. . . . Ought to be in the hands of every one in charge of an electric light plant."—*Electrical Engineer*.

ELECTRIC LIGHT.

Its Production and Use, Embodying Plain Directions for the Treatment of Dynamo-Electric Machines, Batteries, Accumulators, and Electric Lamps. By J. W. URQUHART, C.E., Author of "Electric Light Fitting," "Electroplating," &c. Sixth Edition, carefully Revised, with Additions and 145 Illustrations. Crown 8vo, cloth, [Just Published. 7/6

"The whole ground of electric lighting is more or less covered and explained in a very clear and concise manner."—*Electrical Review*.

"Contains a good deal of very interesting information, especially in the parts where the author gives dimensions and working costs."—*Electrical Engineer*.

"A *valde-mecum* of the salient facts connected with the science of electric lighting."—*Electrician*.

"You cannot for your purpose have a better book than 'Electric Light' by Urquhart."—*Engineer*.

DYNAMO CONSTRUCTION.

A Practical Handbook for the Use of Engineer-Constructors and Electricians-in-Charge. Embracing Framework Building, Field Magnet and Armature Winding and Grouping, Compounding, &c. With Examples of leading English, American, and Continental Dynamos and Motors. By J. W. URQUHART, Author of "Electric Light," &c. Second Edition, Enlarged. With 114 Illustrations. Crown 8vo, cloth 7/6

"Mr. Urquhart's book is the first one which deals with these matters in such a way that the engineering student can understand them. The book is very readable, and the author leads his readers up to difficult subjects by reasonably simple tests."—*Engineering Review*.

"'Dynamo Construction' more than sustains the high character of the author's previous publications. It is sure to be widely read by the large and rapidly-increasing number of practical electricians."—*Glasgow Herald*.

"A book for which a demand has long existed."—*Mechanical World*.

THE MANAGEMENT OF DYNAMOS.

A Handy Book of Theory and Practice for the Use of Mechanics, Engineers, Students, and others in Charge of Dynamos. By G. W. LUMMIS PATERSON. With numerous Illustrations. Crown 8vo, cloth 3/6

"An example which deserves to be taken as a model by other authors. The subject is treated in a manner which any intelligent man who is fit to be entrusted with charge of an engine should be able to understand. It is a useful book to all who make, tend, or employ electric machinery."—*Architect*.

THE STANDARD ELECTRICAL DICTIONARY.

A Popular Encyclopædia of Words and Terms Used in the Practice of Electrical Engineering. By T. O'CONOR SLOANE, A.M., Ph.D. Second Edition, with Appendix to date. Crown 8vo, 680 pp., 390 Illustrations, cloth. [Just Published. 7/6

"The work has many attractive features in it, and is, beyond doubt, a well put together and useful publication. The amount of ground covered may be gathered from the fact that in the index about 5,600 references will be found."—*Electrical Review*.

ELECTRIC SHIP-LIGHTING.

A Handbook on the Practical Fitting and Running of Ships' Electrical Plant. For the Use of Shipowners and Builders, Marine Electricians, and Seagoing Engineers-in-Charge. By J. W. URQUHART, C.E. With 88 Illustrations. Crown 8vo, cloth 7/6

"The subject of ship electric lighting is one of vast importance, and Mr. Urquhart is to be highly complimented for placing such a valuable work at the service of marine electricians."—*The Steamship*.

ELECTRIC LIGHT FOR COUNTRY HOUSES.

A Practical Handbook on the Erection and Running of Small Installations, with Particulars of the Cost of Plant and Working. By J. H. KNIGHT. Second Edition, Revised. Crown 8vo, wrapper. [Just Published. 1/0

"The book contains excellent advice and many practical hints for the help of those who wish to light their own houses."—*Building News*.

ELEMENTARY PRINCIPLES OF ELECTRIC LIGHTING.

By ALAN A. CAMPBELL SWINTON, Associate I.E.E. Third Edition, Enlarged and Revised. With 16 Illustrations. Crown 8vo, cloth 1/6

"Any one who desires a short and thoroughly clear exposition of the elementary principles of electric lighting cannot do better than read this little work."—*Bradford Observer*.

DYNAMIC ELECTRICITY AND MAGNETISM.

By PHILIP ATKINSON, A.M., Ph.D., Author of "Elements of Static Electricity," &c. Crown 8vo, 417 pp., with 120 Illustrations, cloth 10/6

THE ELECTRIC TRANSFORMATION OF POWER.

With its Application by the Electric Motor, including Electric Railway Construction. By P. ATKINSON, A.M., Ph.D. With 96 Illustrations. Crown 8vo, cloth 7/6

HOW TO MAKE A DYNAMO.

A Practical Treatise for Amateurs. Containing numerous Illustrations and Detailed Instructions for Constructing a Small Dynamo to Produce the Electric Light. By ALFRED CROFTS. Fifth Edition, Revised and Enlarged. Crown 8vo, cloth. [Just Published. 2/0

"The instructions given in this unpretentious little book are sufficiently clear and explicit to enable any amateur mechanic possessed of average skill and the usual tools to be found in an amateur's workshop to build a practical dynamo machine."—*Electrician*.

THE STUDENT'S TEXT-BOOK OF ELECTRICITY.

By H. M. NOAD, F.R.S. Cheaper Edition. 650 pp., with 470 Illustrations. Crown 8vo, cloth 9/0

ARCHITECTURE, BUILDING, &c.

PRACTICAL BUILDING CONSTRUCTION.

A Handbook for Students Preparing for Examinations, and a Book of Reference for Persons Engaged in Building. By JOHN PARNELL ALLEN, Surveyor, Lecturer on Building Construction at the Durham College of Science, Newcastle-on-Tyne. Second Edition, Revised and Enlarged. Medium 8vo, 450 pp., with 1,000 Illustrations, cloth. [Just Published. 7/6

"The most complete exposition of building construction we have seen. It contains all that is necessary to prepare students for the various examinations in building construction."—*Building News*.

"The author depends nearly as much on his diagrams as on his type. The pages suggest the hand of a man of experience in building operations—and the volume must be a blessing to many teachers as well as to students."—*The Architect*.

"The work is sure to prove a formidable rival to great and small competitors alike, and bids fair to take a permanent place as a favourite student's text-book. The large number of illustrations deserve particular mention for the great merit they possess for purposes of reference in exactly corresponding to convenient scales."—*Journal of the Royal Institute of British Architects*.

PRACTICAL MASONRY.

A Guide to the Art of Stone Cutting. Comprising the Construction, Setting Out, and Working of Stairs, Circular Work, Arches, Niches, Domes, Pendentives, Vaults, Tracery Windows, &c., &c. For the Use of Students, Masons, and other Workmen. By WILLIAM R. PURCHASE, Building Inspector to the Town of Hove. Royal 8vo, 134 pp., with 50 Lithographic Plates, comprising nearly 400 separate Diagrams, cloth. 7/6

"Mr. Purchase's 'Practical Masonry' will undoubtedly be found useful to all interested in this important subject, whether theoretically or practically. Most of the examples given are from actual work carried out, the diagrams being carefully drawn. The book is a practical treatise on the subject, the author himself having commenced as an operative mason, and afterwards acted as foreman mason on many large and important buildings prior to the attainment of his present position. It should be found of general utility to architectural students and others, as well as to those to whom it is specially addressed."—*Journal of the Royal Institute of British Architects*.

"The author has evidently devoted much time and conscientious labour in the production of his book, which will be found very serviceable to students, masons, and other workmen, while its value is much enhanced by the capital illustrations, consisting of fifty lithographic plates, comprising about 400 diagrams."—*Illustrated Carpenter and Builder*.

CONCRETE: ITS NATURE AND USES.

A Book for Architects, Builders, Contractors, and Clerks of Works. By GEORGE L. SUTCLIFFE, A.R.I.B.A. 350 pp., with numerous Illustrations. Crown 8vo, cloth. 7/6

"The author treats a difficult subject in a lucid manner. The manual fills a long-felt gap. It is careful and exhaustive; equally useful as a student's guide and an architect's book of reference."—*Journal of the Royal Institute of British Architects*.

"There is room for this new book, which will probably be for some time the standard work on the subject for a builder's purpose."—*Glasgow Herald*.

THE MECHANICS OF ARCHITECTURE.

A Treatise on Applied Mechanics, especially Adapted to the Use of Architects. By E. W. TARN, M.A., Author of "The Science of Building," &c. Second Edition, Enlarged. Illustrated with 125 Diagrams. Crown 8vo, cloth 7/6

"The book is a very useful and helpful manual of architectural mechanics, and really contains sufficient to enable a careful and painstaking student to grasp the principles bearing upon the majority of building problems. Mr. Tarn has added, by this volume, to the debt of gratitude which is owing to him by architectural students for the many valuable works which he has produced for their use."—*The Builder*.

"The mechanics in the volume are really mechanics, and are harmoniously wrought in with the distinctive professional matter proper to the subject. The diagrams and type are commendably clear."—*The Schoolmaster*.

LOCKWOOD'S BUILDER'S PRICE BOOK for 1898.

A Comprehensive Handbook of the Latest Prices and Data for Builders, Architects, Engineers, and Contractors. Re-constructed, Re-written, and Greatly Enlarged. By FRANCIS T. W. MILLER. 800 closely-printed pages, crown 8vo, cloth. 4/0

"This book is a very useful one, and should find a place in every English office connected with the building and engineering professions."—*Industries*.

"An excellent book of reference."—*Architect*.

"In its new and revised form this Price Book is what a work of this kind should be—comprehensive, reliable, well arranged, legible, and well bound."—*British Architect*.

THE LONDON BUILDING ACT, 1894.

With the By-Laws and Regulations of the London County Council, and Introduction, Notes, Cases, and Index. By ALEX. J. DAVID, B.A., LL.M., of the Inner Temple, Barrister-at-Law. Crown 8vo, cloth **3/6**

"To all architects and district surveyors and builders Mr. David's manual will be welcome."
—*Building News*.

"The volume will doubtless be eagerly consulted by the building fraternity."—*Illustrated Carpenter and Builder*.

THE DESIGN OF BUILDINGS.

Being Elementary Notes on the Planning, Sanitation, and Ornamentive Formation of Structures, based on Modern Practice. Illustrated with Nine Folding Plates. By W. WOODLEV. 8vo, cloth **6/0**

THE DECORATIVE PART OF CIVIL ARCHITECTURE.

By Sir WILLIAM CHAMBERS, F.R.S. With Portrait, Illustrations, Notes, and an EXAMINATION OF GRECIAN ARCHITECTURE, by JOSEPH GWILT, F.S.A. Revised and Edited by W. H. LEEDS. 66 Plates, 4to, cloth **21/0**

A HANDY BOOK OF VILLA ARCHITECTURE.

Being a Series of Designs for Villa Residences in various Styles. With Outline Specifications and Estimates. By C. WICKES, Architect, Author of "The Spires and Towers of England," &c. 61 Plates, 4to, half-morocco, gilt edges **£1 11s. 6s.**

"The whole of the designs bear evidence of their being the work of an artistic architect, and they will prove very valuable and suggestive."—*Building News*.

THE ARCHITECT'S GUIDE.

Being a Text-book of Useful Information for Architects, Engineers, Surveyors, Contractors, Clerks of Works, &c., &c. By FREDERICK ROGERS, Architect. Third Edition. Crown 8vo, cloth **3/6**

"As a text-book of useful information for architects, engineers, surveyors, &c., it would be hard to find a handier or more complete little volume."—*Standard*

ARCHITECTURAL PERSPECTIVE.

The whole Course and Operations of the Draughtsman in Drawing a Large House in Linear Perspective. Illustrated by 43 Folding Plates. By F. O. FERGUSON. Second Edition, Enlarged. 8vo, boards **3/6**

"It is the most intelligible of the treatises on this ill-treated subject that I have met with."—E. INGRESS BELL, ESQ., in the *R.I.B.A. Journal*.

PRACTICAL RULES ON DRAWING.

For the Operative Builder and Young Student in Architecture. By GEORGE PYNE. 14 Plates, 4to, boards **7/6**

MEASURING AND VALUING ARTIFICER'S WORK.

(The Student's Guide to the Practice of.) Containing Directions for taking Dimensions, Abstracting the same, and bringing the Quantities into Bill, with Tables of Constants for Valuation of Labour, and for the Calculation of Areas and Solidities. Originally edited by E. DOBSON, Architect. With Additions by E. W. TARN, M.A. Sixth Edition. With 8 Plates and 63 Woodcuts. Crown 8vo, cloth **7/6**

"This edition will be found the most complete treatise on the principles of measuring and valuing artificer's work that has yet been published."—*Building News*.

TECHNICAL GUIDE, MEASURER, and ESTIMATOR.

For Builders and Surveyors. Containing Technical Directions for Measuring Work in all the Building Trades, Complete Specifications for Houses, Roads, and Drains, and an Easy Method of Estimating the parts of a Building collectively. By A. C. BEATON. Eighth Edition. Waistcoat-pocket size, gilt edges **1/6**

"No builder, architect, surveyor, or valuer should be without his 'Beaton.'"—*Building News*

CONSTRUCTIONAL IRON AND STEEL WORK.

As Applied to Public, Private, and Domestic Buildings. A Practical Treatise for Architects, Students, and Builders. By F. CAMPIN. Crown 8vo, cloth.

[Just Published. 3/6

"Any one who wants a book on ironwork, as employed in buildings for stanchions, columns, and beams, will find the present volume to be suitable. The author has had long and varied experience in designing this class of work. The illustrations have the character of working drawings. This practical book may be counted a most valuable work."—*British Architect*.

SPECIFICATIONS for PRACTICAL ARCHITECTURE.

A Guide to the Architect, Engineer, Surveyor, and Builder. With an Essay on the Structure and Science of Modern Buildings. Upon the Basis of the Work by ALFRED BARTHOLOMEW, thoroughly Revised, Corrected, and greatly added to by FREDERICK ROGERS, Architect. Third Edition, Revised. 8vo, cloth 15/0

"The work is too well known to need any recommendation from us. It is one of the books with which every young architect must be equipped."—*Architect*.

THE SCIENCE OF BUILDING.

An Elementary Treatise on the Principles of Construction. By E. WYNDHAM TARN, M.A., Architect. Fourth Edition, with 59 Engravings. Fcap. 8vo, cloth 3/6

"A very valuable book, which we strongly recommend to all students."—*Builder*.

THE HOUSE-OWNER'S ESTIMATOR.

Or, What will it Cost to Build, Alter, or Repair? A Price Book for Un-professional People as well as the Architectural Surveyor and Builder. By J. D. SIMON. Edited by F. T. W. MILLER, A.R.I.B.A. Fourth Edition. Crown 8vo, cloth 3/6

"In two years it will repay its cost a hundred times over."—*Field*.

A BOOK ON BUILDING.

Civil and Ecclesiastical, including Church Restoration; with the Theory of Domes and the Great Pyramid, &c. By Sir EDMUND BECKETT, Bart., LL.D., F.R.A.S. Second Edit. Fcap. 8vo, cloth 4/6

"A book which is always amusing and nearly always instructive."—*The Times*.

SANITARY ARRANGEMENT OF DWELLING-HOUSES.

A Handbook for Householders and Owners of Houses. By A. J. WALLIS-TAYLER, A.M.Inst.C.E. With Illustrations. Crown 8vo, cloth 2/6

"This book will be largely read; it will be of considerable service to the public. It is well arranged, easily read, and for the most part devoid of technical terms."—*Lancet*.

VENTILATION.

A Text-book to the Practice of the Art of Ventilating Buildings. By W. P. BUCHAN, R.P. 12mo, cloth 3/6

"Contains a great amount of useful practical information as thoroughly interesting as it is technically reliable."—*British Architect*.

PLUMBING.

A Text-book to the Practice of the Art or Craft of the Plumber. By W. P. BUCHAN, R.P. Seventh Edition, Enlarged. Crown 8vo, cloth 3/6

"A text-book which may be safely put in the hands of every young plumber."—*Builder*.

PRACTICAL GEOMETRY.

For the Architect, Engineer, and Mechanic. Giving Rules for the Delineation and Application of various Geometrical Lines, Figures, and Curves. By E. W. TARN, M.A., Architect. 8vo, cloth 9/0

"No book with the same objects in view has ever been published in which the clearness of the rules laid down and the illustrative diagrams have been so satisfactory."—*Scotsman*.

THE GEOMETRY OF COMPASSES.

Or, Problems Resolved by the mere Description of Circles and the use of Coloured Diagrams and Symbols. By OLIVER BYRNE. Coloured Plates. Crown 8vo, cloth 3/6

CARPENTRY, TIMBER, &c.

THE ELEMENTARY PRINCIPLES OF CARPENTRY.

A Treatise on the Pressure and Equilibrium of Timber Framing, the Resistance of Timber, and the Construction of Floors, Arches, Bridges, Roofs, Uniting Iron and Stone with Timber, &c. To which is added an Essay on the Nature and Properties of Timber, &c., with Descriptions of the kinds of Wood used in Building; also numerous Tables of the Scantlings of Timber for different purposes, the Specific Gravities of Materials, &c. By THOMAS TREDGOLD, C.E. With an Appendix of Specimens of Various Roofs of Iron and Stone, Illustrated. Seventh Edition, thoroughly Revised and considerably Enlarged by E. WYNDHAM TARN, M.A., Author of "The Science of Building," &c. With 61 Plates, Portrait of the Author, and several Woodcuts. In One large Vol., 4to, cloth 25/0

"Ought to be in every architect's and every builder's library."—*Builder*.

"A work whose monumental excellence must commend it wherever skilful carpentry is concerned. The author's principles are rather confirmed than impaired by time. The additional plates are of great intrinsic value."—*Building News*.

WOODWORKING MACHINERY.

Its Rise, Progress, and Construction. With Hints on the Management of Saw Mills and the Economical Conversion of Timber. Illustrated with Examples of Recent Designs by leading English, French, and American Engineers. By M. POWIS BALE, A.M.Inst.C.E., M.I.M.E. Second Edition, Revised, with large Additions, large crown 8vo, 440 pp., cloth 9/0

"Mr. Bale is evidently an expert on the subject, and he has collected so much information that his book is all-sufficient for builders and others engaged in the conversion of timber."—*Architect*.

"The most comprehensive compendium of wood-working machinery we have seen. The author is a thorough master of his subject."—*Building News*.

SAW MILLS.

Their Arrangement and Management, and the Economical Conversion of Timber. By M. POWIS BALE, A.M.Inst.C.E. Second Edition, Revised. Crown 8vo, cloth. [Just Published, 10/6]

"The administration of a large sawing establishment is discussed, and the subject examined from a financial standpoint. Hence the size, shape, order, and disposition of saw mills and the like are gone into in detail, and the course of the timber is traced from its reception to its delivery in its converted state. We could not desire a more complete or practical treatise."—*Builder*.

THE CARPENTER'S NEW GUIDE.

Or, Book of Lines for Carpenters; comprising all the Elementary Principles essential for acquiring a knowledge of Carpentry. Founded on the late PETER NICHOLSON'S standard work. A New Edition, Revised by ARTHUR ASHPITEL, F.S.A. Together with Practical Rules on Drawing, by GEORGE PYNE. With 74 Plates, 4to, cloth £1 1s.

A PRACTICAL TREATISE ON HANDRAILING.

Showing New and Simple Methods for Finding the Pitch of the Plank, Drawing the Moulds, Beveling, Jointing-up, and Squaring the Wreath. By GEORGE COLLINGS. Second Edition, Revised and Enlarged, to which is added A TREATISE ON STAIR-BUILDING. With Plates and Diagrams 2/6

"Will be found of practical utility in the execution of this difficult branch of joinery."—*Builder*.

"Almost every difficult phase of this somewhat intricate branch of joinery is elucidated by the aid of plates and explanatory letterpress."—*Furniture Gazette*.

CIRCULAR WORK IN CARPENTRY AND JOINERY.

A Practical Treatise on Circular Work of Single and Double Curvature. By GEORGE COLLINGS. With Diagrams. Second Edition, 12mo, cloth 2/6

"An excellent example of what a book of this kind should be. Cheap in price, clear in definition, and practical in the examples selected."—*Builder*.

HANDRAILING COMPLETE IN EIGHT LESSONS.

On the Square-Cut System. By J. S. GOLDTHORP, Head of Building Department, Halifax Technical School. With Eight Plates and over 150 Practical Exercises. 4to, cloth 3/6

"Likely to be of considerable value to joiners and others who take a pride in good work. The arrangement of the book is excellent. We heartily commend it to teachers and students."—*Timber Trades Journal*.

TIMBER MERCHANT'S and BUILDER'S COMPANION.

Containing New and Copious Tables of the Reduced Weight and Measurement of Deals and Battens, of all sizes, from One to a Thousand Pieces, and the relative Price that each size bears per Lineal Foot to any given Price per Petersburg Standard Hundred; the Price per Cube Foot of Square Timber to any given Price per Load of 50 Feet, &c., &c. By WILLIAM DOWSING. Fourth Edition, Revised and Corrected. Crown 8vo, cloth 3/0

"We are glad to see a fourth edition of these admirable tables, which for correctness and simplicity of arrangement leave nothing to be desired."—*Timber Trades Journal*.

THE PRACTICAL TIMBER MERCHANT.

A Guide for the Use of Building Contractors, Surveyors, Builders, &c., comprising useful Tables for all purposes connected with the Timber Trade, Marks of Wood, Essay on the Strength of Timber, Remarks on the Growth of Timber, &c. By W. RICHARDSON. Second Edition. Fcap. 8vo, cloth . . . 3/6

"This handy manual contains much valuable information for the use of timber merchants, builders, foresters, and all others connected with the growth, sale, and manufacture of timber."—*Journal of Forestry*.

PACKING-CASE TABLES.

Showing the number of Superficial Feet in Boxes or Packing-Cases, from six inches square and upwards. By W. RICHARDSON, Timber Broker. Third Edition. Oblong 4to, cloth 3/6

"Invaluable labour-saving tables."—*Ironmonger*.

GUIDE TO SUPERFICIAL MEASUREMENT.

Tables calculated from 1 to 200 inches in length by 1 to 108 inches in breadth. For the use of Architects, Surveyors, Engineers, Timber Merchants, Builders, &c. By JAMES HAWKINGS. Fourth Edition. Fcap. cloth. 3/6

"A useful collection of tables to facilitate rapid calculation of surfaces. The exact area of any surface of which the limits have been ascertained can be instantly determined. The book will be found of the greatest utility to all engaged in building operations."—*Scottsman*.

PRACTICAL FORESTRY.

Its Bearing on the Improvement of Estates. By CHARLES E. CURTIS, F.S.I., F.S.S. Second Edition, Revised. Crown 8vo, cloth. [Just Published. 3/6

THE ELEMENTS OF FORESTRY.

Designed to afford Information concerning the Planting and Care of Forest Trees for Ornament or Profit, with suggestions upon the Creation and Care of Woodlands. By F. B. HOUGH. Large crown 8vo, cloth 10/0

THE TIMBER IMPORTER'S, TIMBER MERCHANT'S, AND BUILDER'S STANDARD GUIDE.

By RICHARD E. GRANDY. Comprising:—An Analysis of Deal Standards, Home and Foreign, with Comparative Values and Tabular Arrangements for fixing Net Landed Cost on Baltic and North American Deals, including all intermediate Expenses, Freight, Insurance, &c.; together with copious Information for the Retailer and Builder. Third Edition. 12mo, cloth 2/0

"Everything it pretends to be: built up gradually, it leads one from a forest to a treenail, and throws in as a makeweight a host of material concerning bricks, columns, cisterns, &c."—*English Mechanic*.

DECORATIVE ARTS, &c.

SCHOOL OF PAINTING FOR THE IMITATION OF WOODS AND MARBLES.

As Taught and Practised by A. R. VAN DER BURG and P. VAN DER BURG, Directors of the Rotterdam Painting Institution. Royal folio, 184 by 12½ in., Illustrated with 24 full-size Coloured Plates; also 12 plain Plates, comprising 154 Figures. Second and Cheaper Edition **£1 11s. 6s.**

LIST OF PLATES:—1. VARIOUS TOOLS REQUIRED FOR WOOD PAINTING.—2, 3. WALNUT; PRELIMINARY STAGES OF GRAINING AND FINISHED SPECIMEN.—4. TOOLS USED FOR MARBLE PAINTING AND METHOD OF MANIPULATION.—5, 6. ST. REMI MARBLE; EARLIER OPERATIONS AND FINISHED SPECIMEN.—7. METHODS OF SKETCHING DIFFERENT GRAINS, KNOTS, &c.—8, 9. ASH: PRELIMINARY STAGES AND FINISHED SPECIMEN.—10. METHODS OF SKETCHING MARBLE GRAINS.—11, 12. BRECHE MARBLE; PRELIMINARY STAGES OF WORKING AND FINISHED SPECIMEN.—13. MAPLE; METHODS OF PRODUCING THE DIFFERENT GRAINS.—14, 15. BIRD'S-EYE MAPLE; PRELIMINARY STAGES AND FINISHED SPECIMEN.—16. METHODS OF SKETCHING THE DIFFERENT SPECIES OF WHITE MARBLE.—17, 18. WHITE MARBLE; PRELIMINARY STAGES OF PROCESS AND FINISHED SPECIMEN.—19. MAHOGANY; SPECIMENS OF VARIOUS GRAINS AND METHODS OF MANIPULATION.—20, 21. MAHOGANY; EARLIER STAGES AND FINISHED SPECIMEN.—22, 23, 24. SIENNA MARBLE; VARIETIES OF GRAIN, PRELIMINARY STAGES AND FINISHED SPECIMEN.—25, 26, 27. JUNIPER WOOD; METHODS OF PRODUCING GRAIN, &c.; PRELIMINARY STAGES AND FINISHED SPECIMEN.—28, 29, 30. VERT DE MER MARBLE; VARIETIES OF GRAIN AND METHODS OF WORKING, UNFINISHED AND FINISHED SPECIMENS.—31, 32, 33. OAK; VARIETIES OF GRAIN, TOOLS EMPLOYED AND METHODS OF MANIPULATION, PRELIMINARY STAGES AND FINISHED SPECIMEN.—34, 35, 36. WAULSORT MARBLE; VARIETIES OF GRAIN, UNFINISHED AND FINISHED SPECIMENS.

"Those who desire to attain skill in the art of painting woods and marbles will find advantage in consulting this book. . . . Some of the Working Men's Clubs should give their young men the opportunity to study it."—*Builder*.

"A comprehensive guide to the art. The explanations of the processes, the manipulation and management of the colours, and the beautifully executed plates will not be the least valuable to the student who aims at making his work a faithful transcript of nature."—*Building News*.

"Students and novices are fortunate who are able to become the possessors of so noble a work."—*The Architect*.

ELEMENTARY DECORATION.

A Guide to the Simpler Forms of Everyday Art. Together with PRACTICAL HOUSE DECORATION. By JAMES W. FACEY. With numerous Illustrations. In One Vol., strongly half-bound **5/0**

HOUSE PAINTING, GRAINING, MARBLING, and SIGN WRITING.

A Practical Manual of. By ELLIS A. DAVIDSON. Seventh Edition. With Coloured Plates and Wood Engravings. 12mo, cloth boards **6/0**

"A mass of information of use to the amateur and of value to the practical man."—*English Mechanic*.

THE DECORATOR'S ASSISTANT.

A Modern Guide for Decorative Artists and Amateurs, Painters, Writers, Gilders, &c. Containing upwards of 600 Receipts, Rules, and Instructions; with a variety of Information for General Work connected with every Class of Interior and Exterior Decorations, &c. Sixth Edition. 152 pp., cr. 8vo . . . **1/0**

"Full of receipts of value to decorators, painters, gilders, &c. The book contains the gist of larger treatises on colour and technical processes. It would be difficult to meet with a work so full of varied information on the painter's art."—*Building News*.

MARBLE DECORATION

And the Terminology of British and Foreign Marbles. A Handbook for Students. By GEORGE H. BLAGROVE, Author of "Shoring and its Application," &c. With 28 Illustrations. Crown 8vo, cloth **3/6**

"This most useful and much wanted handbook should be in the hands of every architect and builder."—*Building World*.

"A carefully and usefully written treatise; the work is essentially practical."—*Scottsman*.

DELAMOTTE'S WORKS ON ALPHABETS AND ILLUMINATION.

ORNAMENTAL ALPHABETS, ANCIENT & MEDIÆVAL.

From the Eighth Century, with Numerals; including Gothic, Church-Text, large and small, German, Italian, Arabesque, Initials for Illumination, Monograms, Crosses, &c., &c., for the use of Architectural and Engineering Draughtsmen, Missal Painters, Masons, Decorative Painters, Lithographers, Engravers, Carvers, &c., &c. Collected and Engraved by F. DELAMOTTE, and printed in Colours. New and Cheaper Edition. Royal 8vo, oblong, ornamental boards 2/6

"For those who insert enamelled sentences round gilded chalices, who blazon shop legends over shop-doors, who letter church walls with jithy sentences from the Decalogue, this book will be useful."—*Athenæum*.

MODERN ALPHABETS, PLAIN AND ORNAMENTAL.

Including German, Old English, Saxon, Italic, Perspective, Greek, Hebrew, Court Hand, Engrossing, Tuscan, Riband, Gothic, Rustic, and Arabesque; with several Original Designs, and an Analysis of the Roman and Old English Alphabets, large and small, and Numerals, for the use of Draughtsmen, Surveyors, Masons, Decorative Painters, Lithographers, Engravers, Carvers, &c. Collected and Engraved by F. DELAMOTTE, and printed in Colours. New and Cheaper Edition. Royal 8vo, oblong, ornamental boards 2/6

"There is comprised in it every possible shape into which the letters of the alphabet and numerals can be formed, and the talent which has been expended in the conception of the various plain and ornamental letters is wonderful."—*Standard*.

MEDIÆVAL ALPHABETS AND INITIALS FOR ILLUMINATORS.

By F. G. DELAMOTTE. Containing 21 Plates and Illuminated Title, printed in Gold and Colours. With an Introduction by J. WILLIS BROOKS. Fourth and Cheaper Edition. Small 4to, ornamental boards 4/0

"A volume in which the letters of the alphabet come forth glorified in gilding and all the colours of the prism interwoven and intertwined and intermingled."—*Star*.

A PRIMER OF THE ART OF ILLUMINATION.

For the Use of Beginners; with a Rudimentary Treatise on the Art, Practical Directions for its Exercise, and Examples taken from Illuminated MSS., printed in Gold and Colours. By F. DELAMOTTE. New and Cheaper Edition. Small 4to, ornamental boards 6/0

"The examples of ancient MSS. recommended to the student, which, with much good sense, the author chooses from collections accessible to all, are selected with judgment and knowledge as well as taste."—*Athenæum*.

THE EMBROIDERER'S BOOK OF DESIGN.

Containing Initials, Emblems, Cyphers, Monograms, Ornamental Borders, Ecclesiastical Devices, Mediæval and Modern Alphabets, and National Emblems. Collected by F. DELAMOTTE, and printed in Colours. Oblong royal 8vo, ornamental wrapper 1/6

"The book will be of great assistance to ladies and young children who are endowed with the art of plying the needle in this most ornamental and useful pretty work."—*East Anglian Times*.

INSTRUCTIONS IN WOOD-CARVING FOR AMATEURS.

With Hints on Design. By A LADY. With 10 Plates. New and Cheaper Edition. Crown 8vo, in emblematic wrapper 2/0

"The handicraft of the wood-carver, so well as a book can impart it, may be learnt from 'A Lady's' publication."—*Athenæum*.

PAINTING POPULARLY EXPLAINED.

By THOMAS JOHN GULLICK, Painter, and JOHN TIMBS, F.S.A. Including Fresco, Oil, Mosaic, Water-Colour, Water-Glass, Tempera, Encaustic, Miniature, Painting on Ivory, Vellum, Pottery, Enamel, Glass, &c. Fifth Edition. Crown 8vo, cloth 5/0

. Adopted as a Prize Book at South Kensington.

"Much may be learned, even by those who fancy they do not require to be taught, from the careful perusal of this unpretending but comprehensive treatise."—*Art Journal*.

NATURAL SCIENCE, &c.

THE VISIBLE UNIVERSE.

Chapters on the Origin and Construction of the Heavens. By J. E. GORE, F.R.A.S., Author of "Star Groups," &c. Illustrated by 6 Stellar Photographs and 12 Plates. Demy 8vo, cloth 16/0

"A valuable and lucid summary of recent astronomical theory, rendered more valuable and attractive by a series of stellar photographs and other illustrations."—*The Times*.

"In presenting a clear and concise account of the present state of our knowledge Mr. Gore has made a valuable addition to the literature of the subject."—*Nature*.

"Mr. Gore's 'Visible Universe' is one of the finest works on astronomical science that have recently appeared in our language. In spirit and in method it is scientific from cover to cover, but the style is so clear and attractive that it will be as acceptable and as readable to those who make no scientific pretensions as to those who devote themselves specially to matters astronomical."—*Leeds Mercury*.

STAR GROUPS.

A Student's Guide to the Constellations. By J. ELLARD GORE, F.R.A.S., M.R.I.A., &c., Author of "The Visible Universe," "The Scenery of the Heavens," &c. With 30 Maps. Small 4to, cloth 5/0

"The volume contains thirty maps showing stars of the sixth magnitude—the usual naked-eye limit—and each is accompanied by a brief commentary adapted to facilitate recognition and bring to notice objects of special interest. For the purpose of a preliminary survey of the 'midnight pomp' of the heavens nothing could be better than a set of delineations averaging scarcely twenty square inches in area and including nothing that cannot at once be identified."—*Saturday Review*.

AN ASTRONOMICAL GLOSSARY.

Or, Dictionary of Terms used in Astronomy. With Tables of Data and Lists of Remarkable and Interesting Celestial Objects. By J. ELLARD GORE, F.R.A.S., Author of "The Visible Universe," &c. Small crown 8vo, cloth. 2/6

"A very useful little work for beginners in astronomy, and not to be despised by more advanced students."—*The Times*.

"A very handy book . . . the utility of which is much increased by its valuable tables of astronomical data."—*Athenæum*.

THE MICROSCOPE.

Its Construction and Management. Including Technique, Photo-micrography, and the Past and Future of the Microscope. By Dr. HENRI VAN HEURCK. Re-Edited and Augmented from the Fourth French Edition, and Translated by WYNNE E. BAXTER, F.G.S. 400 pp., with upwards of 250 Woodcuts, imp. 8vo, cloth 18/0

"A translation of a well-known work, at once popular and comprehensive."—*Times*.

"The translation is as felicitous as it is accurate."—*Nature*.

PHOTO-MICROGRAPHY.

By Dr. H. VAN HEURCK. Extracted from the above Work. Royal 8vo, with Illustrations, sewed 1/0

ASTRONOMY.

By the late Rev. ROBERT MAIN, M.A., F.R.S. Third Edition, Revised by WILLIAM THYNNE LYNN, B.A., F.R.A.S., formerly of the Royal Observatory, Greenwich. 12mo, cloth 2/0

"A sound and simple treatise, very carefully edited, and a capital book for beginners."—*Knowledge*.

"Accurately brought down to the requirements of the present time by Mr. Lynn."—*Educational Times*.

A MANUAL OF THE MOLLUSCA.

A Treatise on Recent and Fossil Shells. By S. P. WOODWARD, A.L.S., F.G.S. With an Appendix on RECENT AND FOSSIL CONCHOLOGICAL DISCOVERIES, by RALPH TATE, A.L.S., F.G.S. With 23 Plates and upwards of 300 Woodcuts. Reprint of Fourth Edition (1880). Crown 8vo, cloth 7/6

"A most valuable storehouse of conchological and geological information."—*Science Gossip*.

THE TWIN RECORDS OF CREATION.

Or, Geology and Genesis, their Perfect Harmony and Wonderful Concord. By G. W. V. LE VAUX. 8vo, cloth 5/0

"A valuable contribution to the evidences of Revelation, and disposes very conclusively of the arguments of those who would set God's Works against God's Word. No real difficulty is skirted, and no sophistry is left unexposed."—*The Rock*.

HANDBOOK OF MECHANICS.

By Dr. LARDNER. Enlarged and re-written by BENJAMIN LOEWY, F.R.A.S.
378 Illustrations. Post 8vo, cloth **6/0**

"The perspicuity of the original has been retained, and chapters which had become obsolete have been replaced by others of more modern character. The explanations throughout are studiously popular, and care has been taken to show the application of the various branches of physics to the industrial arts, and to the practical business of life."—*Mining Journal*.

HANDBOOK OF HYDROSTATICS AND PNEUMATICS.

By Dr. LARDNER. New Edition, Revised and Enlarged by BENJAMIN LOEWY, F.R.A.S. With 236 Illustrations. Post 8vo, cloth **5/0**

"For those 'who desire to attain an accurate knowledge of physical science without the profound methods of mathematical investigation,' this work is well adapted."—*Chemical News*.

HANDBOOK OF HEAT.

By Dr. LARDNER. Edited and re-written by BENJAMIN LOEWY, F.R.A.S., &c.
117 Illustrations. Post 8vo, cloth **6/0**

"The style is always clear and precise, and conveys instruction without leaving any cloudiness or lurking doubts behind."—*Engineering*.

HANDBOOK OF OPTICS.

By Dr. LARDNER. New Edition. Edited by T. OLVER HARDING, B.A. Lond.
With 298 Illustrations. Small 8vo, 448 pp., cloth **5/0**

"Written by one of the ablest English scientific writers, beautifully and elaborately illustrated."—*Mechanics Magazine*.

ELECTRICITY, MAGNETISM, AND ACOUSTICS.

By Dr. LARDNER. Edited by GEO. CAREY FOSTER, B.A., F.C.S. With
400 Illustrations. Small 8vo, cloth **5/0**

"The book could not have been entrusted to any one better calculated to preserve the terse and lucid style of Lardner, while correcting his errors and bringing up his work to the present state of scientific knowledge."—*Popular Science Review*.

HANDBOOK OF ASTRONOMY.

By Dr. LARDNER. Fourth Edition. Revised and Edited by EDWIN DUNKIN, F.R.A.S., Royal Observatory, Greenwich. With 38 Plates and upwards of
100 Woodcuts. 8vo, cloth **9/6**

"Probably no other book contains the same amount of information in so compendious and well arranged a form—certainly none at the price at which this is offered to the public."—*Athenaeum*.

"We can do no other than pronounce this work a most valuable manual of astronomy, and we strongly recommend it to all who wish to acquire a general—but at the same time correct—acquaintance with this sublime science."—*Quarterly Journal of Science*.

MUSEUM OF SCIENCE AND ART.

Edited by Dr. LARDNER. With upwards of 1,200 Engravings on Wood. In
Six Double Volumes, **£1 1s.** in a new and elegant cloth binding; or hand-
somely bound in half-morocco **£1 11s. 6s.**

"A cheap and interesting publication, alike informing and attractive. The papers combine subjects of importance and great scientific knowledge, considerable inductive powers, and a popular style of treatment."—*Spectator*.

Separate books formed from the above.

Common Things Explained. 5s.
The Microscope. 2s. cloth.
Popular Geology. 2s. 6d. cloth.
Popular Physics. 2s. 6d. cloth.

Steam and its Uses. 2s. cloth.
Popular Astronomy. 4s. 6d. cloth.
The Bee and White Ants. 2s. cloth.
The Electric Telegraph. 1s. 6d.

NATURAL PHILOSOPHY FOR SCHOOLS.

By Dr. LARDNER. Fcap. 8vo **3/6**

"A very convenient class book for junior students in private schools."—*British Quarterly Review*.

ANIMAL PHYSIOLOGY FOR SCHOOLS.

By Dr. LARDNER. Fcap. 8vo **3/6**

"Clearly written, well arranged, and excellently illustrated."—*Gardener's Chronicle*.

THE ELECTRIC TELEGRAPH.

By Dr. LARDNER. Revised by E. B. BRIGHT, F.R.A.S. Fcap. 8vo. **2/6**

"One of the most readable books extant on the Electric Telegraph."—*English Mechanic*.

CHEMICAL MANUFACTURES, CHEMISTRY, &c.

THE GAS ENGINEER'S POCKET BOOK.

Comprising Tables, Notes and Memoranda relating to the Manufacture, Distribution and Use of Coal Gas and the Construction of Gas Works. By H. O'CONNOR, A.M.Inst.C.E., 450 pp., crown 8vo, fully Illustrated, leather. [Just Published. 10/6

WATER AND ITS PURIFICATION.

A Handbook for the Use of Local Authorities, Sanitary Officers, and others interested in Water Supply. By S. RIDEAL, D.Sc. Lond., F.I.C. With numerous Illustrations and Tables. Crown 8vo, cloth. [Just Published. 7/6

"Dr. Rideal's book is both interesting and accurate, and contains a most useful résumé of the latest knowledge upon the subject of which it treats. It ought to be of great service to all who are connected with the supply of water for domestic or manufacturing purposes."—*The Engineer*.

"Dealing as clearly as it does with the various ramifications of such an important subject as water and its purification it may be warmly recommended. Local authorities and all engaged in sanitary affairs, and others interested in water supply, will read its pages with profit."—*Lancet*.

ENGINEERING CHEMISTRY.

A Practical Treatise for the Use of Analytical Chemists, Engineers, Iron Masters, Iron Founders, Students and others. Comprising Methods of Analysis and Valuation of the Principal Materials used in Engineering Work, with numerous Analyses, Examples and Suggestions. By H. J. PHILLIPS, F.I.C., F.C.S. Second Edition, Enlarged. Crown 8vo, 400 pp., with Illustrations, cloth. 10/6

"In this work the author has rendered no small service to a numerous body of practical men. . . . The analytical methods may be pronounced most satisfactory, being as accurate as the despatch required of engineering chemists permits."—*Chemical News*.

"The book is full of good things. As a handbook of technical analysis, it is very welcome."—*Builder*.

"The analytical methods given are, as a whole, such as are likely to give rapid and trustworthy results in experienced hands. . . . There is much excellent descriptive matter in the work, the chapter on 'Oils and Lubrication' being specially noticeable in this respect."—*Engineer*.

NITRO-EXPLOSIVES.

A Practical Treatise concerning the Properties, Manufacture, and Analysis of Nitrated Substances, including the Fulminates, Smokeless Powders, and Celluloid. By P. G. SANFORD, F.I.C., Consulting Chemist to the Cotton Powder Company, &c. With Illustrations. Crown 8vo, cloth. [Just Published. 9/0

"Any one having the requisite apparatus and materials could make nitro-glycerine or gun-cotton, to say nothing of other explosives, by the aid of the instructions contained in this volume. This is one of the very few text-books in which can be found just what is wanted. Mr. Sanford goes steadily through the whole list of explosives commonly used, he names any given explosive, and tells us of what it is composed and how it is manufactured. The book is excellent throughout."—*The Engineer*.

A HANDBOOK ON MODERN EXPLOSIVES.

A Practical Treatise on the Manufacture and Use of Dynamite, Gun-Cotton, Nitro-Glycerine and other Explosive Compounds, including Collodion-Cotton. With Chapters on Explosives in Practical Application. By M. EISSLER, Mining Engineer and Metallurgical Chemist. Second Edition, Enlarged. With 150 Illustrations. Crown 8vo, cloth. [Just Published. 12/6

"Useful not only to the miner, but also to officers of both services to whom blasting and the use of explosives generally may at any time become a necessary auxiliary."—*Nature*.

"A veritable mine of information on the subject of explosives employed for military, mining, and blasting purposes."—*Army and Navy Gazette*.

DANGEROUS GOODS.

Their Sources and Properties, Modes of Storage and Transport. With Notes and Comments on Accidents arising therefrom, together with the Government and Railway Classifications, Acts of Parliament, &c. A Guide for the Use of Government and Railway Officials, Steamship Owners, Insurance Companies and Manufacturers, and Users of Explosives and Dangerous Goods. By H. JOSHUA PHILLIPS, F.I.C., F.C.S. Crown 8vo, 374 pp., cloth. 9/0

"Merits a wide circulation, and an intelligent, appreciative study."—*Chemical News*.

A MANUAL OF THE ALKALI TRADE.

Including the Manufacture of Sulphuric Acid, Sulphate of Soda, and Bleaching Powder. By JOHN LOMAS, Alkali Manufacturer, Newcastle-upon-Tyne and London. 390 pp. of Text. With 232 Illustrations and Working Drawings. Second Edition, with Additions. Super-royal 8vo, cloth . . . £1 10s.

"This book is written by a manufacturer for manufacturers. The working details of the most approved forms of apparatus are given, and these are accompanied by no less than 232 wood engravings, all of which may be used for the purposes of construction. Every step in the manufacture is very fully described in this manual, and each improvement explained."—*Athenæum*.

"We find not merely a sound and luminous explanation of the chemical principles of the trade, but a notice of numerous matters which have a most important bearing on the successful conduct of alkali works, but which are generally overlooked by even experienced technological authors."—*Chemical Review*.

THE BLOWPIPE In CHEMISTRY, MINERALOGY, and GEOLOGY.

Containing all known Methods of Anhydrous Analysis, many Working Examples, and Instructions for Making Apparatus. By Lieut.-Colonel W. A. ROSS, R.A., F.G.S. With 120 Illustrations. Second Edition, Enlarged. Crown 8vo, cloth . . . 5/0

"The student who goes conscientiously through the course of experimentation here laid down will gain a better insight into inorganic chemistry and mineralogy than if he had 'got up' any of the best text-books of the day, and passed any number of examinations in their contents."—*Chemical News*.

COMMERCIAL HANDBOOK OF CHEMICAL ANALYSIS.

Or, Practical Instructions for the Determination of the Intrinsic or Commercial Value of Substances used in Manufactures, in Trades, and in the Arts. By A. NORMANDY. New Edition by H. M. NOAD, Ph.D., F.R.S. Crown 8vo, cloth . . . 12/6

"We strongly recommend this book to our readers as a guide, alike indispensable to the housewife as to the pharmaceutical practitioner."—*Medical Times*.

THE MANUAL OF COLOURS AND DYE-WARES.

Their Properties, Applications, Valuations, Impurities and Sophistications. For the Use of Dyers, Printers, Drysalts, Brokers, &c. By J. W. SLATER. Second Edition, Revised and greatly Enlarged. Crown 8vo, cloth . . . 7/6

"A complete encyclopædia of the *materia tinctoria*. The information given respecting each article is full and precise, and the methods of determining the value of articles such as these, so liable to sophistication, are given with clearness, and are practical as well as valuable."—*Chemist and Druggist*.

"There is no other work which covers precisely the same ground. To students preparing for examinations in dyeing and printing it will prove exceedingly useful."—*Chemical News*.

A HANDY BOOK FOR BREWERS.

Being a Practical Guide to the Art of Brewing and Malting. Embracing the Conclusions of Modern Research which bear upon the Practice of Brewing. By HERBERT EDWARDS WRIGHT, M.A. Second Edition, Enlarged. Crown 8vo, 530 pp., cloth. [Just Published. 12/6

"May be consulted with advantage by the student who is preparing himself for examinational tests, while the scientific brewer will find in it a *résumé* of all the most important discoveries of modern times. The work is written throughout in a clear and concise manner, and the author takes great care to discriminate between vague theories and well-established facts."—*Brewers' Journal*.

"We have great pleasure in recommending this handy book, and have no hesitation in saying that it is one of the best—if not the best—which has yet been written on the subject of beer-brewing in this country; it should have a place on the shelves of every brewer's library."—*Brewer's Guardian*.

"Although the requirements of the student are primarily considered, an acquaintance of half-an-hour's duration cannot fail to impress the practical brewer with the sense of having found a trustworthy guide and practical counsellor in brewery matters."—*Chemical Trade Journal*.

FUELS: SOLID, LIQUID, AND GASEOUS.

Their Analysis and Valuation. For the Use of Chemists and Engineers. By H. J. PHILLIPS, F.C.S., formerly Analytical and Consulting Chemist to the G.E. Ry. Third Edition, Revised and Enlarged. Crown 8vo, cloth 2/0

"Ought to have its place in the laboratory of every metallurgical establishment and wherever fuel is used on a large scale."—*Chemical News*.

THE ARTISTS' MANUAL OF PIGMENTS.

Showing their Composition, Conditions of Permanency, Non-Permanency, and Adulterations; Effects in Combination with Each Other and with Vehicles; and the most Reliable Tests of Purity. By H. C. STANDAGE. Third Edition, crown 8vo, cloth **2/6**

"This work is indeed *in unum-in-parto*, and we can, with good conscience, recommend it to all who come in contact with pigments, whether as makers, dealers, or users."—*Chemical Review*.

A POCKET-BOOK OF MENSURATION AND GAUGING.

Containing Tables, Rules, and Memoranda for Revenue Officers, Brewers, Spirit Merchants, &c. By J. B. MANT, Inland Revenue. Second Edition, Revised. 18mo, leather **4/0**

"This handy and useful book is adapted to the requirements of the Inland Revenue Department, and will be a favourite book of reference. The range of subjects is comprehensive, and the arrangement simple and clear."—*Civilian*.

"Should be in the hands of every practical brewer."—*Brewers' Journal*.

INDUSTRIAL ARTS, TRADES AND MANUFACTURES.**MODERN CYCLES.**

A Practical Handbook on their Construction and Repair. By A. J. WALLIS-TAYLER, A. M. Inst. C. E. Author of "Refrigerating Machinery," &c. With upwards of 300 Illustrations. Crown 8vo, cloth. [Just Published. **10/6**

"The large trade that is done in the component parts of bicycles has placed in the way of men mechanically inclined extraordinary facilities for building bicycles for their own use. . . . The book will prove a valuable guide for all those who aspire to the manufacture or repair of their own machines."—*The Field*.

"A most comprehensive and up-to-date treatise."—*The Cycle*.

"A very useful book, which is quite entitled to rank as a standard work for students of cycle construction."—*H. Keeling*.

TEA PLANTING AND MANUFACTURE.

(A Text Book of.) Comprising Chapters on the History and Development of the Industry, the Cultivation of the Plant, the Preparation of the Leaf for the Market, the Botany and Chemistry of Tea, &c. With some Account of the Laws affecting Labour in Tea Gardens in Assam and elsewhere. By DAVID CROLE, late of the Jokai Tea Company, &c. With Plates and other Illustrations. Medium 8vo, cloth. [Just Published. **18/0**

"The author writes as an expert, and gives the result of his personal experiences. The work can hardly fail to be of practical interest to tea growers and tea manufacturers."—*British Trade Journal*.

COTTON MANUFACTURE.

A Manual of Practical Instruction of the Processes of Opening, Carding, Combing, Drawing, Doubling and Spinning of Cotton, the Methods of Dyeing, &c. For the Use of Operatives, Overlookers, and Manufacturers. By JOHN LISTER, Technical Instructor, Pendleton. 8vo, cloth **7/6**

"This invaluable volume is a distinct advance in the literature of cotton manufacture."—*Machinery*.

"It is thoroughly reliable, fulfilling nearly all the requirements desired."—*Glasgow Herald*.

FLOUR MANUFACTURE.

A Treatise on Milling Science and Practice. By FRIEDRICH KICK, Imperial Regierungsrath, Professor of Mechanical Technology in the Imperial German Polytechnic Institute, Prague. Translated from the Second Enlarged and Revised Edition with Supplement. By H. H. P. POWLES, Assoc. Memb. Institution of Civil Engineers. Nearly 400 pp. Illustrated with 28 Folding Plates, and 167 Woodcuts. Royal 8vo, cloth **£1 6s.**

"This valuable work is, and will remain, the standard authority on the science of milling. . . . The miller who has read and digested this work will have laid the foundation, so to speak, of a successful career; he will have acquired a number of general principles which he can proceed to apply. In this handsome volume we at last have the accepted text-book of modern milling in good, sound English, which has little, if any, trace of the German idiom."—*The Miller*.

"The appearance of this celebrated work in English is very opportune, and British millers will, we are sure, not be slow in availing themselves of its pages."—*Millers' Gazette*.

CEMENTS, PASTES, GLUES AND GUMS.

A Practical Guide to the Manufacture and Application of the various Agglutinants required in the Building, Metal-Working, Wood-Working, and Leather-Working Trades, and for Workshop, Laboratory or Office Use. With upwards of 900 Recipes and Formulæ. By H. C. STANDAGE, Chemist. Third Edition. Crown 8vo, cloth. [Just Published. 2/0

"We have pleasure in speaking favourably of this volume. So far as we have had experience, which is not inconsiderable, this manual is trustworthy."—*Athenæum*.

"As a revelation of what are considered trade secrets, this book will arouse an amount of curiosity among the large number of industries it touches."—*Daily Chronicle*.

THE ART OF SOAP-MAKING.

A Practical Handbook of the Manufacture of Hard and Soft Soaps, Toilet Soaps, &c. Including many New Processes, and a Chapter on the Recovery of Glycerine from Waste Leys. By ALX. WATT. Fifth Edition, Revised, with an Appendix on Modern Candlemaking. Crown 8vo, cloth. . . . 7/6

"The work will prove very useful, not merely to the technological student, but to the practical soap boiler who wishes to understand the theory of his art."—*Chemical News*.

"A thoroughly practical treatise on an art which has almost no literature in our language. We congratulate the author on the success of his endeavour to fill a void in English technical literature."—*Nature*.

PRACTICAL PAPER-MAKING.

A Manual for Paper-Makers and Owners and Managers of Paper-Mills. With Tables, Calculations, &c. By G. CLAPPERTON, Paper-Maker. With Illustrations of Fibres from Micro-Photographs. Crown 8vo, cloth. . . . 5/0

"The author caters for the requirements of responsible mill hands, apprentices, &c., whilst his manual will be found of great service to students of technology, as well as to veteran paper-makers and mill owners. The illustrations form an excellent feature."—*The World's Paper Trade Review*.

"We recommend everybody interested in the trade to get a copy of this thoroughly practical book."—*Paper Making*.

THE ART OF PAPER-MAKING.

A Practical Handbook of the Manufacture of Paper from Rags, Esparto, Straw, and other Fibrous Materials. Including the Manufacture of Pulp from Wood Fibre, with a Description of the Machinery and Appliances used. To which are added Details of Processes for Recovering Soda from Waste Liquors. By ALEXANDER WATT, Author of "The Art of Soap-Making." With Illustrations. Crown 8vo, cloth. . . . 7/6

"It may be regarded as the standard work on the subject. The book is full of valuable information. The 'Art of Paper-Making' is in every respect a model of a text-book, either for a technical class, or for the private student."—*Paper and Printing Trades Journal*.

A TREATISE ON PAPER

For Printers and Stationers. With an Outline of Paper Manufacture; Complete Tables of Sizes, and Specimens of Different Kinds of Paper. By RICHARD PARKINSON, late of the Manchester Technical School. Demy 8vo, cloth. [Just Published. 3/6

THE ART OF LEATHER MANUFACTURE.

Being a Practical Handbook, in which the Operations of Tanning, Currying, and Leather Dressing are fully Described, and the Principles of Tanning Explained, and many Recent Processes Introduced; as also Methods for the Estimation of Tannin, and a Description of the Arts of Glue Boiling, Gut Dressing, &c. By ALEXANDER WATT, Author of "Soap-Making," &c. Fourth Edition. Crown 8vo, cloth. . . . 9/0

"A sound, comprehensive treatise on tanning and its accessories. The book is an eminently valuable production, which redounds to the credit of both author and publishers."—*Chemical Review*.

THE ART OF BOOT AND SHOE MAKING.

A Practical Handbook, including Measurement, Last-Fitting, Cutting-Out, Closing and Making, with a Description of the most approved Machinery Employed. By JOHN B. LENO, late Editor of *St. Crispin*, and *The Boot and Shoe-Maker*. 12mo, cloth. . . . 2/0

WOOD ENGRAVING.

A Practical and Easy Introduction to the Study of the Art. By W. N. BROWN. 12mo, cloth 1/6

"The book is clear and complete, and will be useful to any one wanting to understand the first elements of the beautiful art of wood engraving."—*Graphic*.

MODERN HOROLOGY, IN THEORY AND PRACTICE.

Translated from the French of CLAUDIUS SAUNIER, ex-Director of the School of Horology at Macon, by JULIEN TRIPPLIN, F.R.A.S., Besancon Watch Manufacturer, and EDWARD RIGG, M.A., Assayer in the Royal Mint. With Seventy-eight Woodcuts and Twenty-two Coloured Copper Plates. Second Edition. Super-royal 8vo, cloth, £2 2s. ; half-calf £2 10s.

"There is no horological work in the English language at all to be compared to this production of M. Saunier's for clearness and completeness. It is alike good as a guide for the student and as a reference for the experienced horologist and skilled workman."—*Horological Journal*.

"The latest, the most complete, and the most reliable of those literary productions to which continental watchmakers are indebted for the mechanical superiority over their English brethren—in fact, the Book of Books, is M. Saunier's 'Treatise.'"—*Watchmaker, Jeweller, and Silversmith*.

THE WATCH ADJUSTER'S MANUAL.

A Practical Guide for the Watch and Chronometer Adjuster in Making, Springing, Timing and Adjusting for Isochronism, Positions and Temperatures. By C. E. FRITTS. 370 pp., with Illustrations, 8vo, cloth 16/0

THE WATCHMAKER'S HANDBOOK.

Intended as a Workshop Companion for those engaged in Watchmaking and the Allied Mechanical Arts. Translated from the French of CLAUDIUS SAUNIER, and enlarged by JULIEN TRIPPLIN, F.R.A.S., and EDWARD RIGG, M.A., Assayer in the Royal Mint. Third Edition. 8vo, cloth. 9/0

"Each part is truly a treatise in itself. The arrangement is good and the language is clear and concise. It is an admirable guide for the young watchmaker."—*Engineering*.

"It is impossible to speak too highly of its excellence. It fulfils every requirement in a handbook intended for the use of a workman. Should be found in every workshop."—*Watch and Clockmaker*.

A HISTORY OF WATCHES & OTHER TIMEKEEPERS.

By JAMES F. KENDAL, M.B.H. Inst. Boards, 1/6; or cloth, gilt . . . 2/6

"The best which has yet appeared on this subject in the English language."—*Industries*.

"Open the book where you may, there is interesting matter in it concerning the ingenious devices of the ancient or modern horologist."—*Saturday Review*.

ELECTRO-DEPOSITION.

A Practical Treatise on the Electrolysis of Gold, Silver, Copper, Nickel, and other Metals and Alloys. With Descriptions of Voltaic Batteries, Magneto and Dynamo-Electric Machines, Thermopiles, and of the Materials and Processes used in every Department of the Art, and several Chapters on ELECTRO-METALLURGY. By ALEXANDER WATT, Author of "Electro-Metallurgy," &c. Third Edition, Revised. Crown 8vo, cloth . . . 9/0

"Eminently a book for the practical worker in electro-deposition. It contains practical descriptions of methods, processes and materials, as actually pursued and used in the workshop."—*Engineer*.

ELECTRO-METALLURGY.

Practically Treated. By ALEXANDER WATT. Tenth Edition, including the most recent Processes. 12mo, cloth 3/6

"From this book both amateur and artisan may learn everything necessary for the successful prosecution of electroplating."—*Iron*.

JEWELLER'S ASSISTANT IN WORKING IN GOLD.

A Practical Treatise for Masters and Workmen, Compiled from the Experience of Thirty Years' Workshop Practice. By GEORGE E. GEE, Author of "The Goldsmith's Handbook," &c. Crown 8vo, cloth 7/6

"This manual of technical education is apparently destined to be a valuable auxiliary to a handicraft which is certainly capable of great improvement."—*The Times*.

ELECTROPLATING.

A Practical Handbook on the Deposition of Copper, Silver, Nickel, Gold, Aluminium, Brass, Platinum, &c., &c. By J. W. URQUHART, C.E. Third Edition, Revised. Crown 8vo, cloth 5/0

"An excellent practical manual."—*Engineering*.

"An excellent work, giving the newest information."—*Horological Journal*.

ELECTROTYPING.

The Reproduction and Multiplication of Printing Surfaces and Works of Art by the Electro-Deposition of Metals. By J. W. URQUHART, C.E. Crown 8vo, cloth 5/0

"The book is thoroughly practical; the reader is, therefore, conducted through the leading laws of electricity, then through the metals used by electrotypers, the apparatus, and the depositing processes, up to the final preparation of the work."—*Art Journal*.

GOLDSMITH'S HANDBOOK.

By GEORGE E. GEE, Jeweller, &c. Fifth Edition. 12mo, cloth 3/0

"A good, sound educator, and will be generally accepted as an authority."—*Horological Journal*.

SILVERSMITH'S HANDBOOK.

By GEORGE E. GEE, Jeweller, &c. Third Edition, with numerous Illustrations. 12mo, cloth 3/0

"The chief merit of the work is its practical character. . . . The workers in the trade will speedily discover its merits when they sit down to study it."—*English Mechanic*.

* * * The above two works together, strongly half-bound, price 7s.

SHEET METAL WORKER'S INSTRUCTOR.

Comprising a Selection of Geometrical Problems and Practical Rules for Describing the Various Patterns Required by Zinc, Sheet-Iron, Copper, and Tin-Plate Workers. By REUBEN HENRY WARN. New Edition, Revised and greatly Enlarged by JOSEPH G. HORNER, A.M.I.M.E. Crown 8vo, 254 pp., with 430 Illustrations, cloth. [Just Published. 7/6

BREAD & BISCUIT BAKER'S & SUGAR-BOILER'S ASSISTANT.

Including a large variety of Modern Recipes. With Remarks on the Art of Bread-making. By ROBERT WELLS. Third Edition. Crown 8vo, cloth 2/0

"A large number of wrinkles for the ordinary cook, as well as the baker."—*Saturday Review*.

PASTRYCOOK & CONFECTIONER'S GUIDE.

For Hotels, Restaurants, and the Trade in general, adapted also for Family Use. By R. WELLS, Author of "The Bread and Biscuit Baker." Crown 8vo, cloth 2/0

"We cannot speak too highly of this really excellent work. In these days of keen competition our readers cannot do better than purchase this book."—*Baker's Times*.

ORNAMENTAL CONFECTIONERY.

A Guide for Bakers, Confectioners and Pastrycooks; including a variety of Modern Recipes, and Remarks on Decorative and Coloured Work. With 129 Original Designs. By ROBERT WELLS. Second Edition. Crown 8vo 5/0

"A valuable work, practical, and should be in the hands of every baker and confectioner. The illustrative designs are alone worth treble the amount charged for the whole work."—*Baker's Times*.

THE MODERN FLOUR CONFECTIONER, WHOLESALE & RETAIL.

Containing a large Collection of Recipes for Cheap Cakes, Biscuits, &c. With remarks on the Ingredients Used in their Manufacture. By ROBERT WELLS, Author of "The Bread and Biscuit Baker," &c. Crown 8vo, cloth 2/0

"The work is of a decidedly practical character, and in every recipe regard is had to economical working."—*North British Daily Mail*.

LAUNDRY MANAGEMENT.

A Handbook for Use in Private and Public Laundries. By the EDITOR of "The Laundry Journal." Third Edition. Crown 8vo, cloth. 2/0

"This book should certainly occupy an honoured place on the shelves of all housekeepers who wish to keep themselves au courant of the newest appliances and methods."—*The Queen*.

HANDYBOOKS FOR HANDICRAFTS.

BY PAUL N. HASLUCK.

Editor of "Work" (New Series), Author of "Lathe Work," "Milling Machines," &c. Crown 8vo, 144 pp., cloth, price 1s. each.

These HANDYBOOKS have been written to supply information for WORKMEN, STUDENTS, and AMATEURS in the several Handicrafts, on the actual PRACTICE of the WORKSHOP, and are intended to convey in plain language TECHNICAL KNOWLEDGE of the several CRAFTS. In describing the processes employed, and the manipulation of material, workshop terms are used; workshop practice is fully explained; and the text is freely illustrated with drawings of modern tools, appliances, and processes.

THE METAL TURNER'S HANDYBOOK.

A Practical Manual for Workers at the Foot-Lathe. With over 100 Illustrations. 1/0

"The book will be of service alike to the amateur and the artisan turner. It displays thorough knowledge of the subject."—*Scribner*.

THE WOOD TURNER'S HANDYBOOK.

A Practical Manual for Workers at the Lathe. With over 100 Illustrations 1/0

"We recommend the book to young turners and amateurs. A multitude of workmen have hitherto sought in vain for a manual of this special industry."—*Mechanical World*.

THE WATCH JOBBER'S HANDYBOOK.

A Practical Manual on Cleaning, Repairing, and Adjusting. With upwards of 100 Illustrations 1/0

"We strongly advise all young persons connected with the watch trade to acquire and study this inexpensive work."—*Clerkenwell Chronicle*.

THE PATTERN MAKER'S HANDYBOOK.

A Practical Manual on the Construction of Patterns for Founders. With upwards of 100 Illustrations 1/0

"A most valuable, if not indispensable manual for the pattern maker."—*Knowledge*.

THE MECHANIC'S WORKSHOP HANDYBOOK.

A Practical Manual on Mechanical Manipulation, embracing Information on various Handicraft Processes. With Useful Notes and Miscellaneous Memoranda. Comprising about 200 Subjects 1/0

"A very clever and useful book, which should be found in every workshop; and it should certainly find a place in all technical schools."—*Saturday Review*.

THE MODEL ENGINEER'S HANDYBOOK.

A Practical Manual on the Construction of Model Steam Engines. With upwards of 100 Illustrations. 1/0

"Mr. Hasluck has produced a very good little book."—*Builder*.

THE CLOCK JOBBER'S HANDYBOOK.

A Practical Manual on Cleaning, Repairing, and Adjusting. With upwards of 100 Illustrations 1/0

"It is of inestimable service to those commencing the trade."—*Coventry Standard*.

THE CABINET MAKER'S HANDYBOOK.

A Practical Manual on the Tools, Materials, Appliances, and Processes employed in Cabinet Work. With upwards of 100 Illustrations 1/0

"Mr. Hasluck's thorough-going little Handybook is amongst the most practical guides we have seen for beginners in cabinet-work."—*Saturday Review*.

THE WOODWORKER'S HANDYBOOK OF MANUAL INSTRUCTION.

Embracing Information on the Tools, Materials, Appliances and Processes Employed in Woodworking. With 104 Illustrations. 1/0

OPINIONS OF THE PRESS.

"Written by a man who knows, not only how work ought to be done, but how to do it, and how to convey his knowledge to others."—*Engineering*.

"Mr. Hasluck writes admirably, and gives complete instructions."—*Engineer*.

"Mr. Hasluck combines the experience of a practical teacher with the manipulative skill and scientific knowledge of processes of the trained mechanic, and the manuals are marvels of what can be produced at a popular price."—*Schoolmaster*.

"Helpful to workmen of all ages and degrees of experience."—*Daily Chronicle*.

"Practical, sensible, and remarkably cheap."—*Journal of Education*.

"Concise, clear and practical."—*Saturday Review*.

COMMERCE, COUNTING-HOUSE WORK, TABLES, &c.

LESSONS IN COMMERCE.

By Professor R. GAMBARO, of the Royal High Commercial School at Genoa. Edited and Revised by JAMES GAULT, Professor of Commerce and Commercial Law in King's College, London. Second Edition, Revised. Crown 8vo . 3/6

"The publishers of this work have rendered considerable service to the cause of commercial education by the opportune production of this volume. . . . The work is peculiarly acceptable to English readers and an admirable addition to existing class books. In a phrase, we think the work attains its object in furnishing a brief account of those laws and customs of British trade with which the commercial man interested therein should be familiar."—*Chamber of Commerce Journal*.

"An invaluable guide in the hands of those who are preparing for a commercial career, and, in fact, the information it contains on matters of business should be impressed on every one."—*Counting House*.

THE FOREIGN COMMERCIAL CORRESPONDENT.

Being Aids to Commercial Correspondence in Five Languages—English, French, German, Italian, and Spanish. By CONRAD E. BAKER. Second Edition. Crown 8vo, cloth . 3/6

"Whoever wishes to correspond in all the languages mentioned by Mr. Baker cannot do better than study this work, the materials of which are excellent and conveniently arranged. They consist not of entire specimen letters, but—what are far more useful—short passages, sentences, or phrases expressing the same general idea in various forms."—*Athenæum*.

"A careful examination has convinced us that it is unusually complete, well arranged and reliable. The book is a thoroughly good one."—*Schoolmaster*.

A NEW BOOK OF COMMERCIAL FRENCH.

Grammar—Vocabulary—Correspondence—Commercial Documents—Geography—Arithmetic—Lexicon. By P. CARROUÉ, Professor in the City High School J.—B. Say (Paris). Crown 8vo, cloth . 4/6

"M. Carroué's book is a *vade mecum* of commercial French, and would be distinctly in its place in every merchant's office. Nothing better could be desired."—*Educational Times*.

FACTORY ACCOUNTS: their PRINCIPLES & PRACTICE.

A Handbook for Accountants and Manufacturers, with Appendices on the Nomenclature of Machine Details; the Income Tax Acts; the Rating of Factories; Fire and Boiler Insurance; the Factory and Workshop Acts, &c., including also a Glossary of Terms and a large number of Specimen Rulings. By EMILE GARCKE and J. M. FELS. Fourth Edition, Revised and Enlarged. Demy 8vo, 250 pp., strongly bound . 6/0

"A very interesting description of the requirements of Factory Accounts. . . . The principle of assimilating the Factory Accounts to the general commercial books is one which we thoroughly agree with."—*Accountants' Journal*.

"Characterised by extreme thoroughness. There are few owners of factories who would not derive great benefit from the perusal of this most admirable work."—*Local Government Chronicle*

MODERN METROLOGY.

A Manual of the Metrical Units and Systems of the present Century. With an Appendix containing a proposed English System. By LOWIS D. A. JACKSON, A. M. Inst. C. E., Author of "Aid to Survey Practice," &c. Large crown 8vo, cloth . 12/6

"We recommend the work to all interested in the practical reform of our weights and measures."—*Nature*.

A SERIES OF METRIC TABLES.

In which the British Standard Measures and Weights are compared with those of the Metric System at present in Use on the Continent. By C. H. DOWLING, C. E. 8vo, strongly bound . 10/6

"Mr. Dowling's Tables are well put together as a ready reckoner for the conversion of one system into the other."—*Athenæum*.

THE IRON AND METAL TRADES' COMPANION.

For Expeditiously Ascertaining the Value of any Goods bought or sold by Weight, from 15. per cwt. to 1125. per cwt., and from one farthing per pound to one shilling per pound. By THOMAS DOWNIE. 396 pp., leather . 9/0

"A most useful set of tables, nothing like them before existed."—*Building News*.

"Although specially adapted to the iron and metal trades, the tables will be found useful in every other business in which merchandise is bought and sold by weight."—*Railway News*.

NUMBER, WEIGHT, AND FRACTIONAL CALCULATOR.

Containing upwards of 250,000 Separate Calculations, showing at a Glance the Value at 422 Different Rates, ranging from $\frac{1}{11}$ th of a Penny to 20s. each, or per cwt., and £20 per ton, of any number of articles consecutively, from 1 to 470. Any number of cwt.s., qrs., and lbs., from 1 cwt. to 470 cwt.s. Any number of tons, cwt.s., qrs., and lbs., from 1 to 1,000 tons. By WILLIAM CHADWICK, Public Accountant. Third Edition, Revised. 8vo, strongly bound . **18/0**

"It is as easy of reference for any answer or any number of answers as a dictionary. For making up accounts or estimates the book must prove invaluable to all who have any considerable quantity of calculations involving price and measure in any combination to do."—*Engineer*.
 "The most perfect work of the kind yet prepared."—*Glasgow Herald*.

THE WEIGHT CALCULATOR.

Being a Series of Tables upon a New and Comprehensive Plan, exhibiting at one Reference the exact Value of any Weight from 1 lb. to 15 tons, at 300 Progressive Rates, from 1d. to 168s. per cwt., and containing 186,000 Direct Answers, which, with their Combinations, consisting of a single addition (mostly to be performed at sight), will afford an aggregate of 10,266,000 Answers; the whole being calculated and designed to ensure correctness and promote despatch. By HENRY HARBEN, Accountant. Fifth Edition, carefully Corrected. Royal 8vo, strongly half-bound **£1 5s.**

"A practical and useful work of reference for men of business generally."—*Ironmonger*.

"Of priceless value to business men. It is a necessary book in all mercantile offices."—*Sheffield Independent*.

THE DISCOUNT GUIDE.

Comprising several Series of Tables for the Use of Merchants, Manufacturers, Ironmongers, and Others, by which may be ascertained the Exact Profit arising from any mode of using Discounts, either in the Purchase or Sale of Goods, and the method of either Altering a Rate of Discount, or Advancing a Price, so as to produce, by one operation, a sum that will realise any required Profit after allowing one or more Discounts; to which are added Tables of Profit or Advance from $\frac{1}{2}$ to 90 per cent., Tables of Discount from $\frac{1}{2}$ to 98 $\frac{1}{2}$ per cent., and Tables of Commission, &c., from $\frac{1}{4}$ to 10 per cent. By HENRY HARBEN, Accountant. New Edition, Corrected. Demy 8vo, half-bound **£1 5s.**

"A book such as this can only be appreciated by business men, to whom the saving of time means saving of money. The work must prove of great value to merchants, manufacturers, and general traders."—*British Trade Journal*.

TABLES OF WAGES.

At 54, 52, 50 and 48 Hours per Week. Showing the Amounts of Wages from One-quarter-of-an-hour to Sixty-four hours, in each case at Rates of Wages advancing by One Shilling from 4s. to 55s. per week. By THOS. GARBUTT, Accountant. Square crown 8vo, half-bound **6/0**

IRON-PLATE WEIGHT TABLES.

For Iron Shipbuilders, Engineers, and Iron Merchants. Containing the Calculated Weights of upwards of 150,000 different sizes of Iron Plates from 1 foot by 6 in. by $\frac{1}{4}$ in. to 10 feet by 5 feet by 1 in. Worked out on the Basis of 40 lbs. to the square foot of Iron of 1 inch in thickness. By H. BURLINSON and W. H. SIMPSON. 4to, half-bound **£1 5s.**

MATHEMATICAL TABLES (ACTUARIAL).

Comprising Commutation and Conversion Tables, Logarithms, Cologarithms, Antilogarithms and Reciprocals. By J. W. GORDON. Royal 8vo, mounted on canvas, in cloth case. [Just Published. **5/0**

AGRICULTURE, FARMING, GARDENING, &c.

THE COMPLETE GRAZIER AND FARMER'S AND CATTLE BREEDER'S ASSISTANT.

A Compendium of Husbandry. Originally Written by WILLIAM YOUATT, Thirteenth Edition, entirely Re-written, considerably Enlarged, and brought up to the Present Requirements of Agricultural Practice, by WILLIAM FREAM, LL.D., Steven Lecturer in the University of Edinburgh, Author of "The Elements of Agriculture," &c. Royal 8vo, 1,100 pp., with over 450 Illustrations, strongly and handsomely bound. . . . £1 11s. 6s.

SUMMARY OF CONTENTS.

BOOK I. ON THE VARIETIES, BREEDING, REARING, FATTENING AND MANAGEMENT OF CATTLE.
BOOK II. ON THE ECONOMY AND MANAGEMENT OF THE DAIRY.
BOOK III. ON THE BREEDING, REARING, AND MANAGEMENT OF HORSES.
BOOK IV. ON THE BREEDING, REARING, AND FATTENING OF SHEEP.
BOOK V. ON THE BREEDING, REARING, AND FATTENING OF SWINE.
BOOK VI. ON THE DISEASES OF LIVE STOCK.

BOOK VII. ON THE BREEDING, REARING, AND MANAGEMENT OF POULTRY.
BOOK VIII. ON FARM OFFICES AND IMPLEMENTS OF HUSBANDRY.
BOOK IX. ON THE CULTURE AND MANAGEMENT OF GRASS LANDS.
BOOK X. ON THE CULTIVATION AND APPLICATION OF GRASSES, PULSE AND ROOTS.
BOOK XI. ON MANURES AND THEIR APPLICATION TO GRASS LAND AND CROPS.
BOOK XII. MONTHLY CALENDARS OF FARMWORK.

*** OPINIONS OF THE PRESS ON THE NEW EDITION.

"Dr. Fream is to be congratulated on the successful attempt he has made to give us a work which will at once become the standard classic of the farm practice of the country. We believe that it will be found that it has no compeer among the many works at present in existence. The illustrations are admirable, while the frontispiece, which represents the well-known bull, New Year's Gift, bred by the Queen, is a work of art."—*The Times*

"The book must be recognised as occupying the proud position of the most exhaustive work of reference in the English language on the subject with which it deals."—*Athenaeum*.

"The most comprehensive guide to modern farm practice that exists in the English language to-day."—*The Times*. "The book is one that ought to be on every farm and in the library of every land owner."—*Mark Lane Express*.

"In point of exhaustiveness and accuracy the work will certainly hold a pre-eminent and unique position among books dealing with scientific agricultural practice. It is, in fact, an agricultural library of itself."—*North British Agriculturist*.

"A compendium of authoritative and well-ordered knowledge on every conceivable branch of the work of the live stock farmer; probably without an equal in this or any other country."—*Yorkshire Post*.

FARM LIVE STOCK OF GREAT BRITAIN.

By ROBERT WALLACE, F.L.S., F.R.S.E., &c., Professor of Agriculture and Rural Economy in the University of Edinburgh. Third Edition, thoroughly Revised and considerably Enlarged. With over 120 Phototypes of Prize Stock. Demy 8vo, 384 pp., with 79 Plates and Maps, cloth. . . . 12/6

"A really complete work on the history, breeds, and management of the farm stock of Great Britain, and one which is likely to find its way to the shelves of every country gentleman's library."—*The Times*.

"The latest edition of 'Farm Live Stock of Great Britain' is a production to be proud of, and its issue not the least of the services which its author has rendered to agricultural science."—*Scottish Farmer*.

"The book is very attractive, . . . and we can scarcely imagine the existence of a farmer who would not like to have a copy of this beautiful and useful work."—*Mark Lane Express*.

NOTE-BOOK OF AGRICULTURAL FACTS & FIGURES FOR FARMERS AND FARM STUDENTS.

By PRIMROSE MCCONNELL, B.Sc., Fellow of the Highland and Agricultural Society, Author of "Elements of Farming." Sixth Edition, Rewritten, Revised, and greatly Enlarged. Fcap. 8vo, 480 pp., leather. [Just Published. 6/0

SUMMARY OF CONTENTS: SURVEYING AND LEVELLING.—WEIGHTS AND MEASURES.—MACHINERY AND BUILDINGS.—LABOUR.—OPERATIONS.—DRAINING.—EMBANKING.—GEOLOGICAL MEMORANDA.—SOILS.—MANURES.—CROPPING.—CROPS.—ROTATIONS.—WEEDS.—FEEDING.—DAIRYING.—LIVE STOCK.—HORSES.—CATTLE.—SHEEP.—PIGS.—POULTRY.—FORESTRY.—HORTICULTURE.—MISCELLANEOUS.

"No farmer, and certainly no agricultural student, ought to be without this *multum in parvo* manual of all subjects connected with the farm."—*North British Agriculturist*.

"This little pocket-book contains a large amount of useful information upon all kinds of agricultural subjects. Something of the kind has long been wanted."—*Mark Lane Express*.

"The amount of information it contains is most surprising; the arrangement of the matter is so methodical—although so compressed—as to be intelligible to everyone who takes a glance through its pages. They teem with information."—*Farm and Home*.

BRITISH DAIRYING.

A Handy Volume on the Work of the Dairy-Farm. For the Use of Technical Instruction Classes, Students in Agricultural Colleges and the Working Dairy-Farmer. By Prof. J. P. SHELDON. With Illustrations. Second Edition, Revised. Crown 8vo, cloth. [Just Published. 2/6

"Confidently recommended as a useful text-book on dairy farming."—*Agricultural Gazette*.

"Probably the best half-crown manual on dairy work that has yet been produced."—*North British Agriculturist*.

"It is the soundest little work we have yet seen on the subject."—*The Times*.

MILK, CHEESE, AND BUTTER.

A Practical Handbook on their Properties and the Processes of their Production. Including a Chapter on Cream and the Methods of its Separation from Milk. By JOHN OLIVER, late Principal of the Western Dairy Institute, Berkeley. With Coloured Plates and 200 Illustrations. Crown 8vo, cloth.

7/6

"An exhaustive and masterly production. It may be cordially recommended to all students and practitioners of dairy science."—*North British Agriculturist*.

"We recommend this very comprehensive and carefully-written book to dairy-farmers and students of dairying. It is a distinct acquisition to the library of the agriculturist."—*Agricultural Gazette*.

SYSTEMATIC SMALL FARMING.

Or, The Lessons of My Farm. Being an Introduction to Modern Farm Practice for Small Farmers. By R. SCOTT BURN, Author of "Outlines of Modern Farming," &c. Crown 8vo, cloth. 6/0

"This is the completest book of its class we have seen, and one which every amateur farmer will read with pleasure, and accept as a guide."—*Fid.*

OUTLINES OF MODERN FARMING.

By R. SCOTT BURN. Soils, Manures, and Crops—Farming and Farming Economy—Cattle, Sheep, and Horses—Management of Dairy, Pigs, and Poultry—Utilisation of Town-Sewage, Irrigation, &c. Sixth Edition. In One Vol., 1,250 pp., half-bound, profusely Illustrated 12/0

FARM ENGINEERING, The COMPLETE TEXT-BOOK of.

Comprising Draining and Embanking; Irrigation and Water Supply; Farm Roads, Fences and Gates; Farm Buildings; Barn Implements and Machines; Field Implements and Machines; Agricultural Surveying, &c. By Professor JOHN SCOTT. In One Vol., 1,150 pp., half-bound, with over 600 Illustrations. 12/0

"Written with great care, as well as with knowledge and ability. The author has done his work well; we have found him a very trustworthy guide wherever we have tested his statements. The volume will be of great value to agricultural students."—*Mark Lane Express*.

THE FIELDS OF GREAT BRITAIN.

A Text-Book of Agriculture. Adapted to the Syllabus of the Science and Art Department. For Elementary and Advanced Students. By HUGH CLEMENTS (Board of Trade). Second Edition, Revised, with Additions. 18mo, cloth 2/6

"It is a long time since we have seen a book which has pleased us more, or which contains such a vast and useful fund of knowledge."—*Educational Times*.

TABLES and MEMORANDA for FARMERS, GRAZIERS, AGRICULTURAL STUDENTS, SURVEYORS, LAND AGENTS, AUCTIONEERS, &c.

With a New System of Farm Book-keeping. By SIDNEY FRANCIS. Third Edition, Revised. 272 pp., waistcoat-pocket size, limp leather 1/6

"Weighing less than 1 oz., and occupying no more space than a match-box, it contains a mass of facts and calculations which has never before, in such handy form, been obtainable. Every operation on the farm is dealt with. The work may be taken as thoroughly accurate, the whole of the tables having been revised by Dr. Fream. We cordially recommend it."—*Hell's Weekly Messenger*.

THE ROTHAMSTED EXPERIMENTS AND THEIR PRACTICAL LESSONS FOR FARMERS.

Part I. STOCK. Part II. CROPS. By C. J. R. TIPPER. Crown 8vo, cloth. [Just Published. 3/6

"We have no doubt that the book will be welcomed by a large class of farmers and others interested in agriculture."—*Standard*.

FERTILISERS AND FEEDING STUFFS.

A Handbook for the Practical Farmer. By BERNARD DYER, D.Sc. (Lond.). With the Text of the Fertilisers and Feeding Stuffs Act of 1893, &c. Third Edition, Revised. Crown 8vo, cloth. [Just Published. 1/0

"This little book is precisely what it professes to be—'A Handbook for the Practical Farmer.' Dr. Dyer has done farmers good service in placing at their disposal so much useful information in so intelligible a form."—*The Times*.

BEEES FOR PLEASURE AND PROFIT.

A Guide to the Manipulation of Bees, the Production of Honey, and the General Management of the Apiary. By G. GORDON SAMSON. With numerous Illustrations. Crown 8vo, cloth 1/0

BOOK-KEEPING for FARMERS and ESTATE OWNERS.

A Practical Treatise, presenting, in Three Plans, a System adapted for all Classes of Farms. By JOHNSON M. WOODMAN, Chartered Accountant. Second Edition, Revised. Crown 8vo, cloth boards, 3/6; or, cloth limp, 2/6

"The volume is a capital study of a most important subject."—*Agricultural Gazette*.

WOODMAN'S YEARLY FARM ACCOUNT BOOK.

Giving Weekly Labour Account and Diary, and showing the Income and Expenditure under each Department of Crops, Live Stock, Dairy, &c., &c. With Valuation, Profit and Loss Account, and Balance Sheet at the End of the Year. By JOHNSON M. WOODMAN, Chartered Accountant. Second Edition. Folio, half-bound 7/6 Net.

"Contains every requisite form for keeping farm accounts readily and accurately."—*Agriculture*.

THE FORCING GARDEN.

Or, How to Grow Early Fruits, Flowers and Vegetables. With Plans and Estimates for Building Glasshouses, Pits and Frames. With Illustrations. By SAMUEL WOOD. Crown 8vo, cloth 3/6

"A good book, containing a great deal of valuable teaching."—*Gardener's Magazine*.

A PLAIN GUIDE TO GOOD GARDENING.

Or, How to Grow Vegetables, Fruits, and Flowers. By S. WOOD. Fourth Edition, with considerable Additions, and numerous Illustrations. Crown 8vo, cloth 3/6

"A very good book, and one to be highly recommended as a practical guide. The practical directions are excellent."—*Athenæum*.

MULTUM-IN-PARVO GARDENING.

Or, How to Make One Acre of Land produce £620 a year, by the Cultivation of Fruits and Vegetables; also, How to Grow Flowers in Three Glass Houses, so as to realise £176 per annum clear Profit. By SAMUEL WOOD, Author of "Good Gardening," &c. Fifth and Cheaper Edition, Revised, with Additions. Crown 8vo, sewed 1/0

"We are bound to recommend it as not only suited to the case of the amateur and gentle man's gardener, but to the market grower."—*Gardeners' Magazine*.

THE LADIES' MULTUM-IN-PARVO FLOWER GARDEN.

And Amateur's Complete Guide. By S. WOOD. Crown 8vo, cloth . . . 3/6

"Full of shrewd hints and useful instructions, based on a lifetime of experience."—*Scotsman*.

POTATOES: HOW TO GROW AND SHOW THEM.

A Practical Guide to the Cultivation and General Treatment of the Potato. By J. PINK. Crown 8vo 2/0

MARKET AND KITCHEN GARDENING.

By C. W. SHAW, late Editor of "Gardening Illustrated." Cloth . . . 3/6

"The most valuable compendium of kitchen and market-garden work published."—*Farmer*.

AUCTIONEERING, VALUING, LAND SURVEYING, ESTATE AGENCY, &c.

THE APPRAISER, AUCTIONEER, BROKER, HOUSE AND ESTATE AGENT AND VALUER'S POCKET ASSISTANT.

For the Valuation for Purchase, Sale, or Renewal of Leases, Annuities, and Reversions, and of Property generally; with Prices for Inventories, &c. By JOHN WHEELER, Valuer, &c. Sixth Edition, Re-written and greatly Extended by C. NORRIS, Surveyor, Valuer, &c. Royal 32mo, cloth 5/0

"A neat and concise book of reference, containing an admirable and clearly-arranged list of prices for inventories, and a very practical guide to determine the value of furniture, &c."—*Standard*.
"Contains a large quantity of varied and useful information as to the valuation for purchase, sale, or renewal of leases, annuities and reversions, and of property generally, with prices for inventories, and a guide to determine the value of interior fittings and other effects."—*Builder*.

AUCTIONEERS: THEIR DUTIES AND LIABILITIES.

A Manual of Instruction and Counsel for the Young Auctioneer. By ROBERT SQUIBBS, Auctioneer. Second Edition, Revised and partly Re-written. Demy 8vo, cloth 12/6

"The standard text-book on the topics of which it treats."—*Athenaeum*.

"The work is one of general excellent character, and gives much information in a compendious and satisfactory form."—*Builder*.

"May be recommended as giving a great deal of information on the law relating to auctioneers, in a very readable form."—*Law Journal*.

"Auctioneers may be congratulated on having so pleasing a writer to minister to their special needs."—*Solicitors' Journal*.

TABLES FOR THE PURCHASING OF ESTATES: FREEHOLD, COPYHOLD, OR LEASEHOLD; ANNUITIES, ADVOWSONS, &c.

And for the Renewing of Leases held under Cathedral Churches, Colleges, or other Corporate bodies, for Terms of Years certain, and for Lives; also for Valuing Reversionary Estates, Deferred Annuities, Next Presentations, &c.; together with SMART'S Five Tables of Compound Interest, and an Extension of the same to Lower and Intermediate Rates. By W. INWOOD. 24th Edition, with considerable Additions, and new and valuable Tables of Logarithms for the more difficult Computations of the Interest of Money, Discount, Annuities, &c., by M. FÉDOR THOMAN. Crown 8vo, cloth 8/0

"Those interested in the purchase and sale of estates, and in the adjustment of compensation cases, as well as in transactions in annuities, life insurances, &c., will find the present edition of eminent service."—*Engineering*.

"Inwood's Tables' still maintain a most enviable reputation. The new issue has been enriched by large additional contributions by M. Fédor Thoman, whose carefully arranged Tables cannot fail to be of the utmost utility."—*Mining Journal*.

THE AGRICULTURAL VALUER'S ASSISTANT.

A Practical Handbook on the Valuation of Landed Estates; including Rules and Data for Measuring and Estimating the Contents, Weights and Values of Agricultural Produce and Timber, and the Values of Feeding Stuffs, Manures, and Labour; with Forms of Tenant-Right Valuations, Lists of Local Agricultural Customs, Scales of Compensation under the Agricultural Holdings Act, &c., &c. By TOM BRIGHT, Agricultural Surveyor. Second Edition, Enlarged. Crown 8vo, cloth 5/0

"Full of tables and examples in connection with the valuation of tenant-right, estates, labour, contents and weights of timber, and farm produce of all kinds."—*Agricultural Gazette*.

"An eminently practical handbook, full of practical tables and data of undoubted interest and value to surveyors and auctioneers in preparing valuations of all kinds."—*Farmer*.

POLE PLANTATIONS AND UNDERWOODS.

A Practical Handbook on Estimating the Cost of Forming, Renovating, Improving, and Grubbing Plantations and Underwoods, their Valuation for Purposes of Transfer, Rental, Sale or Assessment. By TOM BRIGHT. Crown 8vo, cloth 3/6

"To valuers, foresters and agents it will be a welcome aid."—*North British Agriculturist*.

"Well calculated to assist the valuer in the discharge of his duties, and of undoubted interest and use both to surveyors and auctioneers in preparing valuations of all kinds."—*Kent Herald*.

THE LAND VALUER'S BEST ASSISTANT.

Being Tables on a very much Improved Plan, for Calculating the Value of Estates. With Tables for reducing Scotch, Irish, and Provincial Customary Acres to Statute Measure, &c. By R. HUDSON, C.E. New Edition. Royal 32mo, leather, elastic band 4/0
 "Of incalculable value to the country gentleman and professional man."—*Farmers' Journal*.

THE LAND IMPROVER'S POCKET-BOOK.

Comprising Formulæ, Tables, and Memoranda required in any Computation relating to the Permanent Improvement of Landed Property. By JOHN EWART, Surveyor. Second Edition, Revised. Royal 32mo, oblong, leather . . . 4/0
 "A compendious and handy little volume."—*Spectator*.

THE LAND VALUER'S COMPLETE POCKET-BOOK.

Being the above Two Works bound together. Leather 7/6

HANDBOOK OF HOUSE PROPERTY.

A Popular and Practical Guide to the Purchase, Mortgage, Tenancy, and Compulsory Sale of Houses and Land, including the Law of Dilapidations and Fixtures: with Examples of all kinds of Valuations, Useful Information on Building and Suggestive Elucidations of Fine Art. By E. L. TARBUCK, Architect and Surveyor. Fifth Edition, Enlarged. 12mo, cloth . . . 5/0

LAW AND MISCELLANEOUS.

MODERN JOURNALISM.

A Handbook of Instruction and Counsel for the Young Journalist. By JOHN B. MACKIE, Fellow of the Institute of Journalists. Crown 8vo, cloth . . . 2/0
 "This invaluable guide to Journalism is a work which all aspirants to a journalistic career will read with advantage."—*Journalist*.

HANDBOOK FOR SOLICITORS AND ENGINEERS

Engaged in Promoting Private Acts of Parliament and Provisional Orders for the Authorisation of Railways, Tramways, Gas and Water Works, &c. By L. LIVINGSTONE MACASSEY, of the Middle Temple, Barrister-at-Law, M. Inst. C. E. 8vo, cloth £1 5s.

PATENTS for INVENTIONS, HOW to PROCURE THEM.

Compiled for the Use of Inventors, Patentees and others. By G. G. M. HARDINGHAM, Assoc. Mem. Inst. C. E., &c. Demy 8vo, cloth . . . 1/6

CONCILIATION & ARBITRATION in LABOUR DISPUTES.

A Historical Sketch and Brief Statement of the Present Position of the Question at Home and Abroad. By J. S. JEANS, Author of "England's Supremacy," &c. Crown 8vo, 200 pp., cloth 2/6

THE HEALTH OFFICER'S POCKET-BOOK.

A Guide to Sanitary Practice and Law. For Medical Officers of Health, Sanitary Inspectors, Members of Sanitary Authorities, &c. By EDWARD F. WILLOUGHBY, M.D. (Lond.), &c. Fcap. 8vo, cloth 7/6
 "A mine of condensed information of a pertinent and useful kind on the various subjects of which it treats. The matter seems to have been carefully compiled and arranged for facility of reference, and it is well illustrated by diagrams and woodcuts. The different subjects are succinctly but fully and scientifically dealt with."—*The Lancet*.
 "Ought to be welcome to those for whose use it is designed, since it practically boils down a reference library into a pocket volume. . . . It combines, with an uncommon degree of efficiency, the qualities of accuracy, conciseness and comprehensiveness."—*Scotsman*.

EVERY MAN'S OWN LAWYER.

A Handy-Book of the Principles of Law and Equity. With a Concise Dictionary of Legal Terms. By A BARRISTER. Thirty-fifth Edition, carefully Revised, and including New Acts of Parliament of 1897. Comprising the *Workmen's Compensation Act, 1897; Voluntary Schools Acts, 1897; Preferential Payments in Bankruptcy Amendment Act, 1897; Wrights and Measures (Metric System) Act, 1897; Infant Life Protection Act, 1897; Dangerous Performances (of Children) Act, 1897; Land Transfer Act, 1897, &c., &c.* Judicial Decisions during the year have also been duly noted. Crown 8vo, 750 pp. Price 6/8 (saved at every consultation!), strongly bound in cloth. [Just Published.]

The Book will be found to comprise (amongst other matter)—

THE RIGHTS AND WRONGS OF INDIVIDUALS—LANDLORD AND TENANT—VENDORS AND PURCHASERS—LEASES AND MORTGAGES—PRINCIPAL AND AGENT—PARTNERSHIP AND COMPANIES—MASTERS, SERVANTS AND WORKMEN—CONTRACTS AND AGREEMENTS—BORROWERS, LENDERS AND SURETIES—SALE AND PURCHASE OF GOODS—CHEQUES, BILLS AND NOTES—BILLS OF SALE—BANKRUPTCY—RAILWAY AND SHIPPING LAW—LIFE, FIRE, AND MARINE INSURANCE—ACCIDENT AND FIDELITY INSURANCE—CRIMINAL LAW—PARLIAMENTARY ELECTIONS—COUNTY COUNCILS—DISTRICT COUNCILS—PARISH COUNCILS—MUNICIPAL CORPORATIONS—LIBEL AND SLANDER—PUBLIC HEALTH AND NUISANCES—COPYRIGHT, PATENTS, TRADE MARKS—HUSBAND AND WIFE—DIVORCE—INFANCY—CUSTODY OF CHILDREN—TRUSTEES AND EXECUTORS—CLERGY, CHURCH-WARDENS, &c.—GAME LAWS AND SPORTING—INNKEEPERS—HORSES AND DOGS—TAXES AND DEATH DUTIES—FORMS OF AGREEMENTS, WILLS, CODICILS, NOTICES, &c.

The object of this work is to enable those who consult it to help themselves to the law; and thereby to dispense, as far as possible, with professional assistance and advice. There are many wrongs and grievances which persons submit to from time to time through not knowing how or where to apply for redress; and many persons have as great a dread of a lawyer's office as of a lion's den. With this book at hand it is believed that many a SIX-AND-EIGHTPENCE may be saved; many a wrong redressed; many a right reclaimed; many a law suit avoided; and many an evil abated. The work has established itself as the standard legal adviser of all classes, and has also made a reputation for itself as a useful book of reference for lawyers residing at a distance from law libraries, who are glad to have at hand a work embodying recent decisions and enactments.

OPINIONS OF THE PRESS.

"It is a complete code of English Law written in plain language, which all can understand

. Should be in the hands of every business man, and all who wish to abolish lawyers' bills."—*Weekly Times.*

"A useful and concise epitome of the law, compiled with considerable care."—*Law Magazine.*

"A complete digest of the most useful facts which constitute English law."—*Globe.*

"This excellent handbook. . . . Admirably done, admirably arranged, and admirably cheap."—*Leeds Mercury.*

"A concise, cheap, and complete epitome of the English law. So plainly written that he who runs may read, and he who reads may understand."—*Figure.*

"A dictionary of legal facts well put together. The book is a very useful one."—*Spectator.*

THE PAWNBROKERS', FACTORS', AND MERCHANTS' GUIDE TO THE LAW OF LOANS AND PLEDGES.

With the Statutes and a Digest of Cases. By H. C. FOLKARD, Barrister-at-Law. Cloth 3/6

LABOUR CONTRACTS.

A Popular Handbook on the Law of Contracts for Works and Services. By DAVID GIBBONS. Fourth Edition, with Appendix of Statutes by T. F. UTTLEY, Solicitor. Fcap. 8vo, cloth 3/6

SUMMARY OF THE FACTORY AND WORKSHOP ACTS

(1878-1891). For the Use of Manufacturers and Managers. By EMILE GARCKE and J. M. FELS. (Reprinted from "FACTORY ACCOUNTS.") Crown 8vo, sewed 6s.

WEALE'S SERIES OF SCIENTIFIC AND TECHNICAL WORKS.

"It is not too much to say that no books have ever proved more popular with or more useful to young engineers and others than the excellent treatises comprised in WEALE'S SERIES."—*Engineer.*

A New Classified List.

	PAGE		PAGE
CIVIL ENGINEERING AND SURVEYING	2	ARCHITECTURE AND BUILDING	6
MINING AND METALLURGY	8	INDUSTRIAL AND USEFUL ARTS . .	9
MECHANICAL ENGINEERING	4	AGRICULTURE, GARDENING, ETC. .	10
NAVIGATION, SHIPBUILDING, ETC. .	5	MATHEMATICS, ARITHMETIC, ETC. .	12
BOOKS OF REFERENCE AND MISCELLANEOUS VOLUMES . .		14	



CROSBY LOCKWOOD AND SON,
7, STATIONERS' HALL COURT, LONDON, E.C.

1898.

CIVIL ENGINEERING & SURVEYING.

Civil Engineering.

By HENRY LAW, M. Inst. C.E. Including a Treatise on HYDRAULIC ENGINEERING by G. R. BURNELL, M.I.C.E. Seventh Edition, revised, with LARGE ADDITIONS by D. K. CLARK, M.I.C.E. . . . 6/6

Pioneer Engineering:

A Treatise on the Engineering Operations connected with the Settlement of Waste Lands in New Countries. By EDWARD DOBSON, A.I.C.E. With numerous Plates. Second Edition 4/6

Iron Bridges of Moderate Span:

Their Construction and Erection. By HAMILTON W. PENDRED. With 40 Illustrations 2/0

Iron (Application of) to the Construction of Bridges, Roofs, and other Works.

By FRANCIS CAMPIN, C.E. Fourth Edition 2/6

Constructional Iron and Steel Work,

as applied to Public, Private, and Domestic Buildings. By FRANCIS CAMPIN, C.E. 3/6

Tubular and other Iron Girder Bridges.

Describing the Britannia and Conway Tubular Bridges. By G. DRYSDALE DEMPSEY, C.E. Fourth Edition 2/0

Materials and Construction:

A Theoretical and Practical Treatise on the Strains, Designing, and Erection of Works of Construction. By FRANCIS CAMPIN, C.E. . . 3/0

Sanitary Work in the Smaller Towns and in Villages.

By CHARLES SLAGG, Assoc. M. Inst. C.E. Second Edition . . 3/0

Roads and Streets (The Construction of).

In Two Parts: I. THE ART OF CONSTRUCTING COMMON ROADS, by H. LAW, C.E., Revised by D. K. CLARK, C.E.; II. RECENT PRACTICE: Including Pavements of Wood, Asphalte, etc. By D. K. CLARK, C.E. 4/6

Gas Works (The Construction of),

And the Manufacture and Distribution of Coal Gas. By S. HUGHES, C.E. Re-written by WILLIAM RICHARDS, C.E. Eighth Edition . . 5/6

Water Works

For the Supply of Cities and Towns. With a Description of the Principal Geological Formations of England as influencing Supplies of Water. By SAMUEL HUGHES, F.G.S., C.E. Enlarged Edition 4/0

The Power of Water,

As applied to drive Flour Mills, and to give motion to Turbines and other Hydrostatic Engines. By JOSEPH GLYNN, F.R.S. New Edition . 2/0

Wells and Well-Sinking.

By JOHN GEO. SWINDELL, A.R.I.B.A., and G. R. BURNELL, C.E. Revised Edition. With a New Appendix on the Qualities of Water. Illustrated 2/0

The Drainage of Lands, Towns, and Buildings.

By G. D. DEMPSEY, C.E. Revised, with large Additions on Recent Practice, by D. K. CLARK, M.I.C.E. Second Edition, corrected . 4/6

Embanking Lands from the Sea.

With Particulars of actual Embankments, &c. By JOHN WIGGINS. 2/0

The Blasting and Quarrying of Stone,

For Building and other Purposes. With Remarks on the Blowing up of Bridges. By Gen. Sir J. BURGVOYE, K.C.B. 1/6

Foundations and Concrete Works.

With Practical Remarks on Footings, Planking, Sand, Concrete, Béton, Pile-driving, Caissons, and Cofferdams. By E. DOBSON, M.R.I.B.A. Seventh Edition 1/6

Pneumatics,

Including Acoustics and the Phenomena of Wind Currents, for the Use of Beginners. By CHARLES TOMLINSON, F.R.S. Fourth Edition . . . 1/6

Land and Engineering Surveying.

For Students and Practical Use. By T. BAKER, C.E. Fifteenth Edition, revised and corrected by J. R. YOUNG, formerly Professor of Mathematics, Belfast College. Illustrated with Plates and Diagrams . . . 2/0

Mensuration and Measuring.

For Students and Practical Use. With the Mensuration and Levelling of Land for the purposes of Modern Engineering. By T. BAKER, C.E. New Edition by E. NUGENT, C.E. . . . 1/6

MINING AND METALLURGY**Mineralogy,**

Rudiments of. By A. RAMSAY, F.G.S. Third Edition, revised and enlarged. Woodcuts and Plates . . . 3/6

Coal and Coal Mining,

A Rudimentary Treatise on. By the late Sir WARINGTON W. SMYTH, F.R.S. Seventh Edition, revised and enlarged . . . 3/6

Metallurgy of Iron.

Containing Methods of Assay, Analyses of Iron Ores, Processes of Manufacture of Iron and Steel, &c. By H. BAUERMAN, F.G.S. With numerous Illustrations. Sixth Edition, revised and enlarged . . . 5/0

The Mineral Surveyor and Valuer's Complete Guide.

By W. LINTERN. Third Edition, with an Appendix on Magnetic and Angular Surveying . . . 3/6

Slate and Slate Quarrying:

Scientific, Practical, and Commercial. By D. C. DAVIES, F.G.S. With numerous Illustrations and Folding Plates. Third Edition . . . 3/0

A First Book of Mining and Quarrying,

with the Sciences connected therewith, for Primary Schools and Self Instruction. By J. H. COLLINS, F.G.S. Second Edition . . . 1/6

Subterraneous Surveying,

with and without the Magnetic Needle. By T. FENWICK and T. BAKER, C.E. Illustrated . . . 2/6

Mining Tools.

Manual of. By WILLIAM MORGANS, Lecturer on Practical Mining at the Bristol School of Mines . . . 2/6

Mining Tools, Atlas

of Engravings to Illustrate the above, containing 235 Illustrations of Mining Tools, drawn to Scale. 4to. . . . 4/6

Physical Geology,

Partly based on Major-General PORTLOCK's "Rudiments of Geology." By RALPH TATE, A.L.S., &c. Woodcuts . . . 2/0

Historical Geology,

Partly based on Major-General PORTLOCK's "Rudiments." By RALPH TATE, A.L.S., &c. Woodcuts . . . 2/6

Geology, Physical and Historical.

Consisting of "Physical Geology," which sets forth the Leading Principles of the Science; and "Historical Geology," which treats of the Mineral and Organic Conditions of the Earth at each successive epoch. By RALPH TATE, F.G.S. . . . 4/6

Electro-Metallurgy,

Practically Treated. By ALEXANDER WATT. Ninth Edition, enlarged and revised, including the most Recent Processes . . . 3/6

MECHANICAL ENGINEERING

- The Workman's Manual of Engineering Drawing.**
By JOHN MAXTON, Instructor in Engineering Drawing, Royal Naval College, Greenwich. Seventh Edition. 300 Plates and Diagrams . . . **3/6**
- Fuels: Solid, Liquid, and Gaseous.**
Their Analysis and Valuation. For the Use of Chemists and Engineers. By H. J. PHILLIPS, F.C.S., formerly Analytical and Consulting Chemist to the Great Eastern Railway. Second Edition, Revised. . . . **2/0**
- Fuel, Its Combustion and Economy.**
Consisting of an Abridgment of "A Treatise on the Combustion of Coal and the Prevention of Smoke." By C. W. WILLIAMS, A.I.C.E. With Extensive Additions by D. K. CLARK, M. Inst. C.E. Third Edition . . . **3/6**
- The Boilermaker's Assistant**
in Drawing, Templating, and Calculating Boiler Work, &c. By J. COURTNEY, Practical Boilermaker. Edited by D. K. CLARK, C.E. . . . **2/0**
- The Boiler-Maker's Ready Reckoner,**
with Examples of Practical Geometry and Templating for the Use of Platers, Smiths, and Riveters. By JOHN COURTNEY. Edited by D. K. CLARK, M.I.C.E. Second Edition, revised, with Additions . . . **4/0**
- *.* *The last two Works in One Volume, half-bound, entitled "THE BOILER-MAKER'S READY-RECKONER AND ASSISTANT."* By J. COURTNEY and D. K. CLARK. *Price 7s.*
- Steam Boilers:**
Their Construction and Management. By R. ARMSTRONG, C.E. Illustrated . . . **1/6**
- Steam and Machinery Management.**
A Guide to the Arrangement and Economical Management of Machinery. By M. POWIS BALE, M. Inst. M.E. **2/6**
- Steam and the Steam Engine,**
Stationary and Portable. Being an Extension of the Treatise on the Steam Engine of Mr. J. SEWELL. By D. K. CLARK, C.E. Third Edition **3/6**
- The Steam Engine,**
A Treatise on the Mathematical Theory of, with Rules and Examples for Practical Men. By T. BAKER, C.E. **1/6**
- The Steam Engine.**
By Dr. LARDNER. Illustrated **1/6**
- Locomotive Engines,**
By G. D. DEMPSEY, C.E. With large Additions treating of the Modern Locomotive, by D. K. CLARK, M. Inst. C.E. **3/0**
- Locomotive Engine-Driving.**
A Practical Manual for Engineers in charge of Locomotive Engines. By MICHAEL REYNOLDS. Eighth Edition. 3s. 6d. limp; cloth boards **4/6**
- Stationary Engine-Driving.**
A Practical Manual for Engineers in charge of Stationary Engines. By MICHAEL REYNOLDS. Fourth Edition. 3s. 6d. limp; cloth boards. **4/6**
- The Smithy and Forge.**
Including the Farrier's Art and Coach Smithing. By W. J. E. CRANK. Second Edition, revised **2/6**
- Modern Workshop Practice,**
As applied to Marine, Land, and Locomotive Engines, Floating Docks, Dredging Machines, Bridges, Ship-building, &c. By J. G. WINTON. Fourth Edition, Illustrated **3/6**
- Mechanical Engineering.**
Comprising Metallurgy, Moulding, Casting, Forging, Tools, Workshop Machinery, Mechanical Manipulation, Manufacture of the Steam Engine, &c. By FRANCIS CAMPIN, C.E. Third Edition **2/6**
- Details of Machinery.**
Comprising Instructions for the Execution of various Works in Iron in the Fitting-Shop, Foundry, and Boiler-Yard. By FRANCIS CAMPIN, C.E. **3/0**

Elementary Engineering:

A Manual for Young Marine Engineers and Apprentices. In the Form of Questions and Answers on Metals, Alloys, Strength of Materials, &c. By J. S. BREWER. Second Edition 2/0

Power in Motion:

Horse-power Motion, Toothed-Wheel Gearing, Long and Short Driving Bands, Angular Forces, &c. By JAMES ARMOUR, C.E. Third Edition 2/0

Iron and Heat,

Exhibiting the Principles concerned in the Construction of Iron Beams, Pillars, and Girders. By J. ARMOUR, C.E. 2/6

Practical Mechanism,

And Machine Tools. By T. BAKER, C.E. With Remarks on Tools and Machinery, by J. NASMYTH, C.E. 2/6

Mechanics:

Being a concise Exposition of the General Principles of Mechanical Science, and their Applications. By CHARLES TOMLINSON, F.R.S. . . . 1/6

Cranes (The Construction of),

And other Machinery for Raising Heavy Bodies for the Erection of Buildings, &c. By JOSEPH GLYNN, F.R.S. 1/6

NAVIGATION, SHIPBUILDING, ETC.**The Sailor's Sea Book:**

A Rudimentary Treatise on Navigation. By JAMES GREENWOOD, B.A. With numerous Woodcuts and Coloured Plates. New and enlarged Edition. By W. H. ROSSER 2/6

Practical Navigation.

Consisting of THE SAILOR'S SEA-BOOK, by JAMES GREENWOOD and W. H. ROSSER; together with Mathematical and Nautical Tables for the Working of the Problems, by HENRY LAW, C.E., and Prof. J. R. YOUNG. 7/0

Navigation and Nautical Astronomy,

In Theory and Practice. By Prof. J. R. YOUNG. New Edition. 2/6

Mathematical Tables,

For Trigonometrical, Astronomical, and Nautical Calculations; to which is prefixed a Treatise on Logarithms. By H. LAW, C.E. Together with a Series of Tables for Navigation and Nautical Astronomy. By Professor J. R. YOUNG. New Edition 4/0

Masting, Mast-Making, and Rigging of Ships.

Also Tables of Spars, Rigging, Blocks; Chain, Wire, and Hemp Ropes, &c., relative to every class of vessels. By ROBERT KIPPING, N.A. . . 2/0

Sails and Sail-Making.

With Draughting, and the Centre of Effort of the Sails. By ROBERT KIPPING, N.A. 2/6

Marine Engines and Steam Vessels.

By R. MURRAY, C.E. Eighth Edition, thoroughly Revised, with Additions by the Author and by GEORGE CARLISLE, C.E. 4/6

Iron Ship-Building.

With Practical Examples. By JOHN GRANTHAM. Fifth Edition . . 4/0

Naval Architecture:

An Exposition of Elementary Principles. By JAMES PEAKE . . . 3/6

Ships for Ocean and River Service,

Principles of the Construction of. By HAKON A. SOMMERFELDT . 1/6

Atlas of Engravings

To illustrate the above. Twelve large folding Plates. Royal 4to, cloth 7/6

The Forms of Ships and Boats.

By W. BLAND. Seventh Edition, revised, with numerous Illustrations and Models 1/6

ARCHITECTURE AND THE BUILDING ARTS.

- Constructional Iron and Steel Work,**
as applied to Public, Private, and Domestic Buildings. By FRANCIS
CAMPIN, C.E. **3/6**
- Building Estates:**
A Treatise on the Development, Sale, Purchase, and Management of Build-
ing Land. By F. MAITLAND. Second Edition, revised . . . **2/0**
- The Science of Building:**
An Elementary Treatise on the Principles of Construction. By E. WYND-
HAM TARN, M.A. Lond. Third Edition, revised and enlarged . . **3/6**
- The Art of Building:**
General Principles of Construction, Strength, and Use of Materials, Working
Drawings, Specifications, &c. By EDWARD DOBSON, M.R.I.B.A. . **2/0**
- A Book on Building,**
Civil and Ecclesiastical. By Sir EDMUND BECKETT, Q.C. (Lord GRIM-
THORPE). Second Edition **4/6**
- Dwelling-Houses (The Erection of),**
Illustrated by a Perspective View, Plans, and Sections of a Pair of Villas, with
Specification, Quantities, and Estimates. By S. H. BROOKS, Architect **2/6**
- Cottage Building.**
By C. BRUCE ALLEN. Eleventh Edition, with Chapter on Economic Cot-
tages for Allotments, by E. E. ALLEN, C.E. **2/0**
- Acoustics in Relation to Architecture and Building:**
The Laws of Sound as applied to the Arrangement of Buildings. By Pro-
fessor T. ROGER SMITH, F.R.I.B.A. New Edition, Revised . . **1/6**
- The Rudiments of Practical Bricklaying.**
General Principles of Bricklaying; Arch Drawing, Cutting, and Setting;
Pointing; Paving, Tiling, &c. By ADAM HAMMOND. With 68 Woodcuts
1/6
- The Art of Practical Brick Cutting and Setting.**
By ADAM HAMMOND. With 90 Engravings **1/6**
- Brickwork:**
A Practical Treatise, embodying the General and Higher Principles of
Bricklaying, Cutting and Setting; with the Application of Geometry to Roof
Tiling, &c. By F. WALKER **1/6**
- Bricks and Tiles,**
Rudimentary Treatise on the Manufacture of; containing an Outline of the
Principles of Brickmaking. By E. DOBSON, M.R.I.B.A. Additions by
C. TOMLINSON, F.R.S. Illustrated **3/0**
- The Practical Brick and Tile Book.**
Comprising: BRICK AND TILE MAKING, by E. DOBSON, A.I.C.E.; Prac-
tical BRICKLAYING, by A. HAMMOND; BRICKWORK, by F. WALKER.
550 pp. with 270 Illustrations, strongly half-bound **6/0**
- Carpentry and Joinery—**
THE ELEMENTARY PRINCIPLES OF CARPENTRY. Chiefly composed from the
Standard Work of THOMAS TREDGOLD, C.E. With Additions, and TREATISE
ON JOINERY, by E. W. TARN, M.A. Fifth Edition, Revised . . **3/6**
- Carpentry and Joinery—Atlas**
Of 35 Plates to accompany and illustrate the foregoing book. With
Descriptive Letterpress. 4to. **6/0**

- A Practical Treatise on Handrailing;**
Showing New and Simple Methods. By GEO. COLLINGS. Second Edition.
Revised, including a TREATISE ON STAIRBUILDING. With Plates . 2/6
- Circular Work in Carpentry and Joinery.**
A Practical Treatise on Circular Work of Single and Double Curvature.
By GEORGE COLLINGS. Second Edition 2/6
- Roof Carpentry:**
Practical Lessons in the Framing of Wood Roofs. For the Use of Working
Carpenters. By GEO. COLLINGS 2/0
- The Construction of Roofs of Wood and Iron;**
Deduced chiefly from the Works of Robison, Tredgold, and Humber. By
E. WYNDHAM TARN, M.A., Architect. Second Edition, revised . 1/6
- The Joints Made and Used by Builders.**
By WYVILL J. CHRISTY, Architect. With 160 Woodcuts . . . 3/0
- Shoring**
And Its Application: A Handbook for the Use of Students. By GEORGE
H. BLAGROVE. With 31 Illustrations 1/6
- The Timber Importer's, Timber Merchant's, and
Builder's Standard Guide.**
By R. E. GRANDY 2/0
- Plumbing:**
A Text-Book to the Practice of the Art or Craft of the Plumber. With
Chapters upon House Drainage and Ventilation. By WM. PATON BUCHAN.
Sixth Edition, revised and enlarged, with 380 Illustrations . . . 3/6
- Ventilation:**
A Text Book to the Practice of the Art of Ventilating Buildings. By W. P.
BUCHAN, R.P., Author of "Plumbing," &c. With 170 Illustrations 3/6
- The Practical Plasterer:**
A Compendium of Plain and Ornamental Plaster Work. By W. KEMP 2/0
- House Painting, Graining, Marbling, & Sign Writing.**
With a Course of Elementary Drawing, and a Collection of Useful Receipts.
By ELLIS A. DAVIDSON. Sixth Edition. Coloured Plates . . . 5/0
. *The above, in cloth boards, strongly bound, 6s.*
- A. Grammar of Colouring,**
Applied to Decorative Painting and the Arts. By GEORGE FIELD. New
Edition, enlarged, by ELLIS A. DAVIDSON. With Coloured Plates . 3/0
- Elementary Decoration**
As applied to Dwelling Houses, &c. By JAMES W. FACEY. Illustrated 2/0
- Practical House Decoration.**
A Guide to the Art of Ornamental Painting, the Arrangement of Colours in
Apartments, and the Principles of Decorative Design. By JAMES W. FACEY.
2/6
. *The last two Works in One handsome Vol., half-bound, entitled "HOUSE
DECORATION, ELEMENTARY AND PRACTICAL," price 5s.*
- Warming and Ventilation**
Of Domestic and Public Buildings, Mines, Lighthouses, Ships, &c. By
CHARLES TOMLINSON, F.R.S. 3/0
- Portland Cement for Users.**
By HENRY FAIJA, A.M. Inst. C.E. Third Edition, Corrected . 2/0
- Limes, Cements, Mortars, Concretes, Mastics, Plas-
tering, &c.**
By G. R. BURNELL, C.E. Thirteenth Edition 1/6

Masonry and Stone-Cutting.

The Principles of Masonic Protection and their application to Construction.
By EDWARD DOBSON, M.R.I.B.A. 2/6

Arches, Piers, Buttresses, &c.:

Experimental Essays on the Principles of Construction. By W. BLAND.
1/6

Quantities and Measurements,

In Bricklayers', Masons', Plasterers', Plumbers', Painters', Paperhangers',
Gilders', Smiths', Carpenters' and Joiners' Work. By A. C. BEATON 1/6

The Complete Measurer:

Setting forth the Measurement of Boards, Glass, Timber and Stone. By R.
HORTON. Fifth Edition 4/0

. *The above, strongly bound in leather, price 5s.*

Light:

An Introduction to the Science of Optics. Designed for the Use of Students
of Architecture, Engineering, and other Applied Sciences. By E. WYND-
HAM TARN, M.A., Author of "The Science of Building," &c. . . . 1/6

Hints to Young Architects.

By GEORGE WIGHTWICK, Architect. Fifth Edition, revised and enlarged
by G. HUSKISSON GUILLAUME, Architect 3/6

Architecture—Orders:

The Orders and their Æsthetic Principles. By W. H. LEEDS. Illustrated.
1/6

Architecture—Styles:

The History and Description of the Styles of Architecture of Various
Countries, from the Earliest to the Present Period. By T. TALBOT BURY,
F.R.I.B.A. Illustrated 2/0

. ORDERS AND STYLES OF ARCHITECTURE, in One Vol., 3s. 6d.

Architecture—Design:

The Principles of Design in Architecture, as deducible from Nature and
exemplified in the Works of the Greek and Gothic Architects. By EDW.
LACY GARBETT, Architect. Illustrated 2/6

. *The three preceding Works in One handsome Vol., half bound, entitled
"MODERN ARCHITECTURE," price 6s.*

Perspective for Beginners.

Adapted to Young Students and Amateurs in Architecture, Painting, &c.
By GEORGE PYNE 2/0

Architectural Modelling in Paper.

By T. A. RICHARDSON. With Illustrations, engraved by O. JEWITT 1/6

Glass Staining, and the Art of Painting on Glass.

From the German of DR. GESSERT and EMANUEL OTTO FROMBERG. With
an Appendix on THE ART OF ENAMELLING 2/6

Vitruvius—The Architecture of.

In Ten Books. Translated from the Latin by JOSEPH GWILT, F.S.A.,
F.R.A.S. With 23 Plates 5/0

N.B.—This is the only Edition of VITRUVIUS procurable at a moderate price.

Grecian Architecture,

An Inquiry into the Principles of Beauty in. With an Historical View of the
Rise and Progress of the Art in Greece. By the EARL OF ABERDEEN 1/0

. *The two preceding Works in One handsome Vol., half bound, entitled
"ANCIENT ARCHITECTURE," price 6s.*

INDUSTRIAL AND USEFUL ARTS.

Cements, Pastes, Glues, and Gums.

A Practical Guide to the Manufacture and Application of the various Agglutinants required for Workshop, Laboratory, or Office Use. With upwards of 900 Recipes and Formulæ. By H. C. STANDAGE . . . 2/0

Clocks and Watches, and Bells.

A Rudimentary Treatise on. By Sir EDMUND BECKETT, Q.C. (Lord GRIMTHORPE). Seventh Edition. 4/6

The Goldsmith's Handbook.

Containing full Instructions in the Art of Alloying, Melting, Reducing, Colouring, Collecting and Refining, Recovery of Waste, Solders, Enamels, &c., &c. By GEORGE E. GEE. Third Edition, enlarged. 3/0

The Silversmith's Handbook,

On the same plan as the GOLDSMITH'S HANDBOOK. By GEORGE E. GEE. Second Edition, Revised 3/0

*** *The last two Works, in One handsome Vol., half-bound, 7s.*

The Hall-Marking of Jewellery.

Comprising an account of all the different Assay Towns of the United Kingdom; with the Stamps and Laws relating to the Standards and Hall-Marks at the various Assay Offices. By GEORGE E. GEE 3/0

Practical Organ Building.

By W. E. DICKSON, M.A. Second Edition, Revised, with Additions 2/6

Coach-Building:

A Practical Treatise. By JAMES W. BURGESS. With 57 Illustrations 2/6

The Brass Founder's Manual:

Instructions for Modelling, Pattern Making, Moulding, Turning, &c. By W. GRAHAM 2/0

The Sheet-Metal Worker's Guide.

A Practical Handbook for Tinsmiths, Coppersmiths, Zincworkers, &c., with 46 Diagrams. By W. J. E. CRANE. Second Edition, revised 1/6

Sewing Machinery:

Its Construction, History, &c. With full Technical Directions for Adjusting, &c. By J. W. URQUHART, C.E. 2/0

Gas Fitting:

A Practical Handbook. By JOHN BLACK. Second Edition, Enlarged. With 130 Illustrations 2/6

Construction of Door Locks.

From the Papers of A. C. HOBBS. Edited by CHARLES TOMLINSON, F.R.S. With a Note upon IRON SAFES by ROBERT MALLET. Illustrated 2/6

The Model Locomotive Engineer, Fireman, and Engine-Boy.

Comprising an Historical Notice of the Pioneer Locomotive Engines and their Inventors. By MICHAEL REYNOLDS. Second Edition. With numerous Illustrations, and Portrait of George Stephenson 3/6

The Art of Letter Painting made Easy.

By J. G. BADENOCH. With 12 full-page Engravings of Examples 1/6

The Art of Boot and Shoemaking.

Including Measurement, Last-fitting, Cutting-out, Closing and Making. By JOHN BEDFORD LENO. With numerous Illustrations. Third Edition 2/0

Mechanical Dentistry:

A Practical Treatise on the Construction of the Various Kinds of Artificial Dentures. By CHARLES HUNTER. Third Edition, revised 3/0

Wood Engraving:

A Practical and Easy Introduction to the Art. By W. N. BROWN 1/6

Laundry Management.

A Handbook for Use in Private and Public Laundries. Including Accounts of Modern Machinery and Appliances. By the EDITOR of "The Laundry Journal." With numerous Illustrations. Second Edition 2/0

AGRICULTURE, GARDENING, ETC.

Draining and Embanking:

A Practical Treatise. By Prof. JOHN SCOTT. With 68 Illustrations 1/6

Irrigation and Water Supply:

A Practical Treatise on Water Meadows, Sewage Irrigation, Warping, &c.; on the Construction of Wells, Ponds, Reservoirs, &c. By Prof. JOHN SCOTT. With 34 Illustrations 1/6

Farm Roads, Fences, and Gates:

A Practical Treatise on the Roads, Tramways, and Waterways of the Farm; the Principles of Enclosures; and the different kinds of Fences, Gates, and Stiles. By Prof. JOHN SCOTT. With 75 Illustrations . 1/6

Farm Buildings:

A Practical Treatise on the Buildings necessary for various kinds of Farms, their Arrangement and Construction, with Plans and Estimates. By Prof. JOHN SCOTT. With 105 Illustrations 2/0

Barn Implements and Machines:

Treating of the Application of Power and Machines used in the Threshing-barn, Stockyard, Dairy, &c. By Prof. J. SCOTT. With 123 Illustrations. 2/0

Field Implements and Machines:

With Principles and Details of Construction and Points of Excellence, their Management, &c. By Prof. JOHN SCOTT. With 138 Illustrations 2/0

Agricultural Surveying:

A Treatise on Land Surveying, Levelling, and Setting-out; with Directions for Valuing Estates. By Prof. J. SCOTT. With 62 Illustrations . 1/6

Farm Engineering.

By Professor JOHN SCOTT. Comprising the above Seven Volumes in One, 1,150 pages, and over 600 Illustrations. Half-bound 12/0

Outlines of Farm Management.

Treating of the General Work of the Farm; Stock; Contract Work; Labour, &c. By R. SCOTT BURN 2/6

Outlines of Landed Estates Management.

Treating of the Varieties of Lands, Methods of Farming, Setting-out of Farms, Roads, Fences, Gates, Drainage, &c. By R. SCOTT BURN . 2/6
. The above Two Vols. in One, handsomely half-bound, price 6s.

Soils, Manures, and Crops.

(Vol. I. OUTLINES OF MODERN FARMING.) By R. SCOTT BURN . 2/0

Farming and Farming Economy.

(Vol. II. OUTLINES OF MODERN FARMING.) By R. SCOTT BURN 3/0

Stock: Cattle, Sheep, and Horses.

(Vol. III. OUTLINES OF MODERN FARMING.) By R. SCOTT BURN 2/6

Dairy, Pigs, and Poultry.

(Vol. IV. OUTLINES OF MODERN FARMING.) By R. SCOTT BURN 2/0

Utilization of Sewage, Irrigation, and Reclamation of Waste Land.

(Vol. V. OUTLINES OF MODERN FARMING.) By R. SCOTT BURN . 2/6

Outlines of Modern Farming.

By R. SCOTT BURN. Consisting of the above Five Volumes in One, 1,250 pp., profusely illustrated, half-bound 12/0

Book-keeping for Farmers and Estate Owners.

A Practical Treatise, presenting, in Three Plans, a System adapted for all classes of Farms. By J. M. WOODMAN. Third Edition, revised . 2/6

Ready Reckoner for the Admeasurement of Land.

By A. ARMAN. Third Edition, revised and extended by C. NORRIS 2/0

Miller's, Corn Merchant's, and Farmer's Ready Reckoner.

Second Edition, revised, with a Price List of Modern Flour Mill Machinery by W. S. HUTTON, C.E. 2/0

The Hay and Straw Measurer.

New Tables for the Use of Auctioneers, Valuers, Farmers, Hay and Straw Dealers, &c. By JOHN STEELE 2/0

Meat Production.

A Manual for Producers, Distributors, and Consumers of Butchers' Meat. By JOHN EWART 2/6

Sheep:

The History, Structure, Economy, and Diseases of. By W. C. SPOONER, M.R.V.S. Fifth Edition, with fine Engravings. 3/6

Market and Kitchen Gardening.

By C. W. SHAW, late Editor of "Gardening Illustrated" 3/0

Kitchen Gardening Made Easy.

Showing the best means of Cultivating every known Vegetable and Herb, &c., with directions for management all the year round. By GEORGE M. F. GLENNY. Illustrated 1/6

Cottage Gardening:

Or Flowers, Fruits, and Vegetables for Small Gardens. By E. HOBDAV. 1/6

Garden Receipts.

Edited by CHARLES W. QUIN 1/6

Fruit Trees,

The Scientific and Profitable Culture of. From the French of M. DU BREUIL. Fourth Edition, carefully Revised by GEORGE GLENNY. With 187 Woodcuts 3/6

The Tree Planter and Plant Propagator:

With numerous Illustrations of Grafting, Layering, Budding, Implements, Houses, Pits, &c. By SAMUEL WOOD 2/0

The Tree Pruner:

A Practical Manual on the Pruning of Fruit Trees, Shrubs, Climbers, and Flowering Plants. With numerous Illustrations. By SAMUEL WOOD 1/6

. The above Two Vols. in One, handsomely half-bound, price 3s. 6d.

The Art of Grafting and Budding.

By CHARLES BALTET. With Illustrations 2/6

MATHEMATICS, ARITHMETIC, ETC.

Descriptive Geometry,

An Elementary Treatise on ; with a Theory of Shadows and of Perspective, extracted from the French of G. MONGE. To which is added a Description of the Principles and Practice of Isometrical Projection. By J. F. HEATHER, M.A. With 14 Plates 2/0

Practical Plane Geometry:

Giving the Simplest Modes of Constructing Figures contained in one Plane and Geometrical Construction of the Ground. By J. F. HEATHER, M.A. With 215 Woodcuts 2/0

Analytical Geometry and Conic Sections,

A Rudimentary Treatise on. By JAMES HANN. A New Edition, rewritten and enlarged by Professor J. R. YOUNG 2/0

Euclid (The Elements of).

With many Additional Propositions and Explanatory Notes ; to which is prefixed an Introductory Essay on Logic. By HENRY LAW, C.E. 2/6

. Sold also separately, viz:—

Euclid. The First Three Books. By HENRY LAW, C.E. 1/6

Euclid. Books 4, 5, 6, 11, 12. By HENRY LAW, C.E. 1/6

Plane Trigonometry,

The Elements of. By JAMES HANN 1/6

Spherical Trigonometry,

The Elements of. By JAMES HANN. Revised by CHARLES H. DOWLING, C.E. 1/0

. Or with "The Elements of Plane Trigonometry," in One Volume, 2s. 6d.

Differential Calculus,

Elements of the. By W. S. B. WOOLHOUSE, F.R.A.S., &c. 1/6

Integral Calculus.

By HOMERSHAM COX, B.A. 1/0

Algebra,

The Elements of. By JAMES HADDON, M.A. With Appendix, containing Miscellaneous Investigations, and a collection of Problems 2/0

A Key and Companion to the Above.

An extensive repository of Solved Examples and Problems in Algebra. By J. R. YOUNG. 1/6

Commercial Book-keeping.

With Commercial Phrases and Forms in English, French, Italian, and German. By JAMES HADDON, M.A. 1/6

Arithmetic,

A Rudimentary Treatise on. With full Explanations of its Theoretical Principles, and numerous Examples for Practice. For the Use of Schools and for Self-Instruction. By J. R. YOUNG, late Professor of Mathematics in Belfast College. Eleventh Edition 1/6

A Key to the Above.

By J. R. YOUNG 1/6

Equational Arithmetic,

Applied to Questions of Interest, Annuities, Life Assurance, and General Commerce ; with various Tables by which all Calculations may be greatly facilitated. By W. HIPSLEY 2/0

Arithmetic,

Rudimentary, for the Use of Schools and Self-Instruction. By JAMES HADDON, M.A. Revised by ABRAHAM ARMAN 1/6

A Key to the Above.

By A. ARMAN 1/6

Mathematical Instruments:

Their Construction, Adjustment, Testing, and Use concisely explained. By J. F. HEATHER, M.A., of the Royal Military Academy, Woolwich. Fourteenth Edition, Revised, with Additions, by A. T. WALMSLEY, M.I.C.E. Original Edition, in 1 vol., Illustrated 2/0

. *In ordering the above, be careful to say "Original Edition," or give the number in the Series (32), to distinguish it from the Enlarged Edition in 3 vols. (Nos. 168-9-70).*

Drawing and Measuring Instruments.

Including—I. Instruments employed in Geometrical and Mechanical Drawing, and in the Construction, Copying, and Measurement of Maps and Plans. II. Instruments used for the purposes of Accurate Measurement, and for Arithmetical Computations. By J. F. HEATHER, M.A. . . 1/6

Optical Instruments.

Including (more especially) Telescopes, Microscopes, and Apparatus for producing copies of Maps and Plans by Photography. By J. F. HEATHER, M.A. Illustrated 1/6

Surveying and Astronomical Instruments.

Including—I. Instruments used for Determining the Geometrical Features of a portion of Ground. II. Instruments employed in Astronomical Observations. By J. F. HEATHER, M.A. Illustrated 1/6

. *The above three volumes form an enlargement of the Author's original work, "Mathematical Instruments;" price 2s. (See No. 32 in the Series.)*

Mathematical Instruments:

Their Construction, Adjustment, Testing and Use. Comprising Drawing, Measuring, Optical, Surveying, and Astronomical Instruments. By J. F. HEATHER, M.A. Enlarged Edition, for the most part entirely re-written. The Three Parts as above, in One thick Volume 4/6

The Slide Rule, and How to Use It.

Containing full, easy, and simple Instructions to perform all Business Calculations with unexampled rapidity and accuracy. By CHARLES HOARE, C.E. With a Slide Rule, in tuck of cover. Fifth Edition . . . 2/6

Logarithms.

With Mathematical Tables for Trigonometrical, Astronomical, and Nautical Calculations. By HENRY LAW, C.E. Revised Edition 3/0

Compound Interest and Annuities (Theory of).

With Tables of Logarithms for the more Difficult Computations of Interest, Discount, Annuities, &c., in all their Applications and Uses for Mercantile and State Purposes. By FEDOR THOMAN, Paris. Fourth Edition . . 4/0

Mathematical Tables,

For Trigonometrical, Astronomical, and Nautical Calculations; to which is prefixed a Treatise on Logarithms. By H. LAW, C.E. Together with a Series of Tables for Navigation and Nautical Astronomy. By Professor J. R. YOUNG. New Edition 4/0

Mathematics,

As applied to the Constructive Arts. By FRANCIS CAMPIN, C.E., &c. Second Edition 3/0

Astronomy.

By the late Rev. ROBERT MAIN, F.R.S. Third Edition, revised and corrected to the Present Time. By W. T. LYNN, F.R.A.S. 2/0

Statics and Dynamics,

The Principles and Practice of. Embracing also a clear development of Hydrostatics, Hydrodynamics, and Central Forces. By T. BAKER, C.E. Fourth Edition 1/6

BOOKS OF REFERENCE AND MISCELLANEOUS VOLUMES.

A Dictionary of Painters, and Handbook for Picture Amateurs.

Being a Guide for Visitors to Public and Private Picture Galleries, and for Art-Students, including Glossary of Terms, Sketch of Principal Schools of Painting, &c. By PHILIPPE DARVYL, B.A. 2/6

Painting Popularly Explained.

By T. J. GULLICK, Painter, and JOHN TIMBS, F.S.A. Including Fresco, Oil, Mosaic, Water Colour, Water-Glass, Tempera, Encaustic, Miniature, Painting on Ivory, Vellum, Pottery, Enamel, Glass, &c. Fifth Edition 5/0

A Dictionary of Terms used in Architecture, Building, Engineering, Mining, Metallurgy, Archaeology, the Fine Arts, &c.

By JOHN WEALE. Sixth Edition. Edited by ROBT. HUNT, F.R.S. Numerous Illustrations 5/0

Music:

A Rudimentary and Practical Treatise. With numerous Examples. By CHARLES CHILD SPENCER 2/6

Pianoforte,

The Art of Playing the. With numerous Exercises and Lessons. By CHARLES CHILD SPENCER 1/6

The House Manager.

Being a Guide to Housekeeping, Practical Cookery, Pickling and Preserving, Household Work, Dairy Management, Cellarage of Wines, Home-brewing and Wine-making, Stable Economy, Gardening Operations, &c. By AN OLD HOUSEKEEPER 3/6

Manual of Domestic Medicine.

By R. GOODING M.D. Intended as a Family Guide in all cases of Accident and Emergency Third Edition, carefully revised . . . 2/0

Management of Health.

A Manual of Home and Personal Hygiene. By Rev. JAMES BAIRD 1/0

Natural Philosophy,

For the Use of Beginners. By CHARLES TOMLINSON, F.R.S. . . . 1/6

The Electric Telegraph,

Its History and Progress. With Descriptions of some of the Apparatus. By R. SABINE, C.E., F.S.A., &c. 3/0

Handbook of Field Fortification.

By Major W. W. KNOLLYS, F.R.G.S. With 163 Woodcuts . . . 3/0

Logic,

Pure and Applied. By S. H. EMMENS. Third Edition 1/6

Locke on the Human Understanding,

Selections from. With Notes by S. H. EMMENS 1/6

The Compendious Calculator

(*Intuitive Calculations*). Or Easy and Concise Methods of Performing the various Arithmetical Operations required in Commercial and Business Transactions; together with Useful Tables, &c. By DANIEL O'GORMAN. Twenty-seventh Edition, carefully revised by C. NORRIS 2/6

Measures, Weights, and Moneys of all Nations.

With an Analysis of the Christian, Hebrew, and Mahometan Calendars.
By W. S. B. WOOLHOUSE, F.R.A.S., F.S.S. Seventh Edition . . . 2/6

Grammar of the English Tongue,

Spoken and Written. With an Introduction to the Study of Comparative Philology. By HYDE CLARKE, D.C.L. Fifth Edition. 1/6

Dictionary of the English Language,

As Spoken and Written. Containing above 100,000 Words. By HYDE CLARKE, D.C.L. 3/6
Complete with the GRAMMAR 5/6

Composition and Punctuation,

Familiarly Explained for those who have neglected the Study of Grammar. By JUSTIN BRENNAN. 18th Edition 1/6

French Grammar.

With Complete and Concise Rules on the Genders of French Nouns. By G. L. STRAUSS, Ph.D. 1/6

French-English Dictionary.

Comprising a large number of New Terms used in Engineering, Mining, &c. By ALFRED ELWES 1/6

English-French Dictionary.

By ALFRED ELWES 2/0

French Dictionary.

The two Parts, as above, complete in One Vol. 3/0
Or with the GRAMMAR, 4/6.

French and English Phrase Book.

Containing Introductory Lessons, with Translations, Vocabularies of Words, Collection of Phrases, and Easy Familiar Dialogues 1/6

German Grammar.

Adapted for English Students, from Heyse's Theoretical and Practical Grammar, by Dr. G. L. STRAUSS 1/6

German Triglot Dictionary.

By N. E. S. A. HAMILTON. Part I. German-French-English. Part II. English-German-French. Part III. French-German-English . . . 3/0

German Triglot Dictionary

(As above). Together with German Grammar in One Volume . . . 5/0

Italian Grammar

Arranged in Twenty Lessons, with Exercises. By ALFRED ELWES. 1/6

Italian Triglot Dictionary,

Wherein the Genders of all the Italian and French Nouns are carefully noted down. By ALFRED ELWES. Vol. 1. Italian-English-French. 2/6

Italian Triglot Dictionary.

By ALFRED ELWES. Vol. 2. English-French-Italian . . . 2/6

Italian Triglot Dictionary.

By ALFRED ELWES. Vol. 3. French-Italian-English . . . 2/6

Italian Triglot Dictionary

(As above). In One Vol. 7/6

Spanish Grammar.

In a Simple and Practical Form. With Exercises. By ALFRED ELWES 1/6

Spanish-English and English-Spanish Dictionary.

Including a large number of Technical Terms used in Mining, Engineering, &c., with the proper Accents and the Gender of every Noun. By ALFRED ELWES 4/0
Or with the GRAMMAR, 6/0.

16 WEALE'S SCIENTIFIC AND TECHNICAL SERIES.

Portuguese Grammar.

In a Simple and Practical Form. With Exercises. By ALFRED ELWES 1/6

Portuguese-English and English-Portuguese Dictionary.

Including a large number of Technical Terms used in Mining, Engineering, &c., with the proper Accents and the Gender of every Noun. By ALFRED ELWES. Third Edition, revised 5/0

. Or with the GRAMMAR, 7/0.

Animal Physics,

Handbook of. By DIONYSIUS LARDNER, D.C.L. With 520 Illustrations. In One Vol. (732 pages), cloth boards 7/6

. Sold also in Two Parts, as follows:—

ANIMAL PHYSICS. By Dr. LARDNER. Part I., Chapters I.—VII. 4/0

ANIMAL PHYSICS. By Dr. LARDNER. Part II., Chapters VIII.—XVIII. 3/0

WEALE'S SCIENTIFIC & TECHNICAL SERIES.

MATHEMATICS, ARITHMETIC, &c.

Geometry, Descriptive. J. F. HEATHER	2/-
Practical Plane Geometry. J. F. HEATHER.	2/-
Analytical Geometry. J. HANN & J. R. YOUNG.	2/-
Geometry. Part I. (Euclid, Bks. I.—III.) H. LAW	1/6
Part II. (Euclid, Books IV., V., VI., XI., XII.). H. LAW	1/6
Geometry, in 1 vol. (Euclid's Elements)	2/6
Plane Trigonometry. J. HANN	1/6
Spherical Trigonometry. J. HANN	1/-
The above 2 vols., bound together	2/6
Differential Calculus. W. S. B. WOOLHOUSE	1/6
Integral Calculus. H. COX	1/-
Integral Calculus. J. HANN	1/-
Algebra. J. HADDON	2/-
Key to ditto	1/6
Book-keeping. J. HADDON	1/6
Arithmetic. J. R. YOUNG	1/6
Key to ditto	1/6
Equational Arithmetic. W. HIPSLEY	2/-
Arithmetic. J. HADDON	1/6
Key to ditto	1/6
Mathematical Instruments. HEATHER & WALMSLEY	2/-
Drawing & Measuring Instruments. J. F. HEATHER	1/6
Optical Instruments. J. F. HEATHER	1/6
Surveying & Astronomical Instruments. J. F. HEATHER	1/6
The above 3 vols., bound together	4/6
Mensuration and Measuring. T. BAKER	1/6
Slide Rule, & How to Use it. C. HOARE	2/6
Measures, Weights, & Moneys. W. S. B. WOOLHOUSE	2/6
Logarithms, Treatise on, with Tables. H. LAW	3/-
Compound Interest and Annuities. F. THOMAN	4/-
Compendious Calculator. D. O'GORMAN	2/6
Mathematics. F. CAMPIN	3/-
Astronomy. R. MAIN & W. T. LYNN	2/-
Statics and Dynamics. T. BAKER	1/6

CROSBY LOCKWOOD & SON, 7, Stationers' Hall Court, E.C.

WEALE'S SCIENTIFIC & TECHNICAL SERIES.

BUILDING & ARCHITECTURE.

Building Estates. F. MAITLAND	2/-
Science of Building. E. W. TARN	3/6
Building, Art of. E. DOBSON	2/-
Book on Building. Sir E. BECKETT	4/6
Dwelling Houses, Erection of. S. H. BROOKS	2/6
Cottage Building. C. B. ALLEN	2/-
Acoustics of Public Buildings. Prof. T. R. SMITH	1/6
Practical Bricklaying. A. HAMMOND	1/6
Practical Brick Cutting & Setting. A. HAMMOND	1/6
Brickwork. F. WALKER	1/6
Brick and Tile Making. E. DOBSON	3/-
Practical Brick & Tile Book. DOBSON & HAMMOND	6/-
Carpentry and Joinery. T. TREDGOLD & E. W. TARN	3/6
Atlas of 35 plates to the above	6/-
Handrailing, and Staircasing. G. COLLINGS	2/6
Circular Work in Carpentry. G. COLLINGS	2/6
Roof Carpentry. G. COLLINGS	2/-
Construction of Roofs. E. W. TARN	1/6
Joints used by Builders. J. W. CHRISTY	3/-
Shoring. G. H. BLAGROVE	1/6
Timber Importer's & Builder's Guide. R. E. GRANDY	2/-
Plumbing. W. P. BUCHAN	3/6
Ventilation of Buildings. W. P. BUCHAN	3/6
Practical Plasterer. W. KEMP	2/-
House-Painting. E. A. DAVIDSON	5/-
Elementary Decoration. J. W. FACEY	2/-
Practical House Decoration. J. W. FACEY	2/6
Gas-Fitting. J. BLACK	2/6
Warming and Ventilation. C. TOMLINSON	3/-
Portland Cement for Users. H. FAIJA	2/-
Limes, Cements, & Mortars. G. R. BURNELL	1/6
Masonry and Stone Cutting. E. DOBSON	2/6
Arches, Piers, and Buttresses. W. BLAND	1/6
Quantities and Measurements. A. C. BEATON	1/6
Complete Measurer. R. HORTON	4/-
Light, for use of Architects. E. W. TARN	1/6
Hints to Young Architects. WIGHTWICK & GUILLAUME	3/6

CROSBY LOCKWOOD & SON, 7, Stationers' Hall Court, E.C.

WEALE'S SCIENTIFIC & TECHNICAL SERIES.

BUILDING & ARCHITECTURE—*contd.*

Dictionary of Architectural Terms. J. WEALE	5/-
Architecture, Orders. W. H. LEEDS	1/6
Architecture, Styles. T. T. BURY	2/-
The above 2 vols., bound together	3/6
Architecture, Design. E. L. GARBETT	2/6
The above 3 vols., bound together	6/-
Architectural Modelling. T. A. RICHARDSON	1/6
Vitruvius' Architecture. J. GWILT	5/-
Grecian Architecture. Lord ABERDEEN	1/-
The above 2 vols., bound together	6/-

FINE ARTS.

Dictionary of Painters. P. DARYL	2/6
Painting, Fine Art. T. J. GULLICK & J. TIMES	5/-
Grammar of Colouring. G. FIELD & E. A. DAVIDSON	3/-
Perspective. G. PYNE	2/-
Glass Staining & Painting on Glass	2/6
Music. C. C. SPENCER	2/6
Pianoforte Instruction. C. C. SPENCER	1/6

INDUSTRIAL & USEFUL ARTS.

Cements, Pastes, Glues, & Gums. H. C. STANDAGE	2/-
Clocks and Watches, and Bells. Sir E. BECKETT	4/6
Goldsmith's Handbook. G. E. GEE	3/-
Silversmith's Handbook. G. E. GEE	3/-
Goldsmith's & Silversmith's Handbook. G. E. GEE	7/-
Hall-Marking of Jewellery. G. E. GEE	3/-
Practical Organ Building. W. E. DICKSON	2/6
Coach Building. J. W. BURGESS	2/6
Brass Founder's Manual. W. GRAHAM	2/-
House Decoration. J. W. FACEY	5/-
Letter-Painting Made Easy. J. G. BADENOCH	1/6
Boot and Shoemaking. J. B. LENO	2/-
Mechanical Dentistry. C. HUNTER	3/-
Wood Engraving. W. N. BROWN	1/6
Laundry Management	2/-

CROSBY LOCKWOOD & SON, 7,

